

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504415

Luminaire Tested: PRLX-UHBS2-1218-MV-L8C5-U-A-06-BLAK-PS (4000K_L16_Narrow_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504415
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-40)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-1218-MV-L8C5-U-A-06-BLAK-PS (4000K_L16_Narrow_120V)
Description: PrentaLux UHBS2 6-INCH SELECTABLE HIGH BAY 1218 LIGHT ENGINE, DOMIC BLACK SHADE, NARROW DISTRIBUTION
LIGHT LEVEL 2 - 16,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 11085.1 lumens
Efficiency: N/A
Efficacy: 111.4 lumens/watt
Spacing Criteria (0/90/45): 0.97 / 0.97 / 0.97
Luminous Opening: Circular (Dia: 1.29' x H: 0')
CIE Type: Direct

Input Watts (W): 99.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504415

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-06-BLAK-PS (4000K_L16_Narrow_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1504415

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-06-BLAK-PS (4000K_L16_Narrow_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20				
RC	80					70					50					30					10				
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10		
RCR																									
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100							
1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	96	94	93							
2	107	102	97	94	105	100	96	93	97	93	91	94	91	89	91	89	87	85							
3	101	94	89	84	99	93	88	84	90	86	82	87	84	81	85	82	80	78							
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72							
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66							
6	85	75	69	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61							
7	80	70	64	59	79	69	63	59	68	62	58	67	62	58	66	61	58	56							
8	76	65	59	55	74	65	59	54	64	58	54	63	58	54	62	57	54	52							
9	72	61	55	51	71	61	55	51	60	54	50	59	54	50	58	53	50	49							
10	68	58	51	47	67	57	51	47	56	51	47	56	50	47	55	50	47	45							

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	82705
5°	82140
10°	79815
15°	76402
20°	71236
25°	64577
30°	55415
35°	42776
40°	31618
45°	18255
50°	10437
55°	5025
60°	1086
65°	395
70°	440
75°	486
80°	483
85°	481

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 18255 cd/sqm

TEST NUMBER: P1504415

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-06-BLAK-PS (4000K_L16_Narrow_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	938.4	8.5
10°-20°	2512.8	22.7
20°-30°	3245.0	29.3
30°-40°	2678.2	24.2
40°-50°	1320.8	11.9
50°-60°	339.9	3.1
60°-70°	28.4	0.3
70°-80°	15.9	0.1
80°-90°	5.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6696.1	60.4
0°-40°	9374.3	84.6
0°-60°	11035.0	99.5
0°-90°	11085.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	11085.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10068	
5°	9961	938
15°	8984	2513
25°	7125	3245
35°	4266	2678
45°	1571	1321
55°	351	340
65°	20	28
75°	15	16
85°	5	6
90°	0	

TEST NUMBER: P1504415

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-06-BLAK-PS (4000K_L16_Narrow_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	10068.2
2.5°	10021.4
5°	9961.4
7.5°	9811.9
10°	9568.8
12.5°	9303.4
15°	8984.0
17.5°	8599.5
20°	8149.0
22.5°	7663.8
25°	7124.8
27.5°	6526.7
30°	5842.2
32.5°	5026.5
35°	4265.7
37.5°	3590.3
40°	2948.6
42.5°	2286.4
45°	1571.4
47.5°	1199.2
50°	816.7
52.5°	595.0
55°	350.9
57.5°	158.7
60°	66.1
62.5°	33.6
65°	20.3
67.5°	19.3
70°	18.3
72.5°	17.3
75°	15.3
77.5°	13.2
80°	10.2
82.5°	8.1
85°	5.1
87.5°	3.1
90°	0.0

(END OF REPORT)