

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504243

Luminaire Tested: PRLX-UHBS2-1218-MV-L8C5-U-A-04-BLAK-PS (5000K_L16_Medium_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504243
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-17)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-1218-MV-L8C5-U-A-04-BLAK-PS (5000K_L16_Medium_120V)
Description: PrentaLux UHBS2 4-INCH SELECTABLE HIGH BAY 1218 LIGHT ENGINE, DOMIC BLACK SHADE, MEDIUM DISTRIBUTION
LIGHT LEVEL 2 - 16,000 LUMENS
Light Source: 5000K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 13523.8 lumens
Efficiency: N/A
Efficacy: 135.1 lumens/watt
Spacing Criteria (0/90/45): 1.11 / 1.11 / 1.11
Luminous Opening: Circular (Dia: 1.23' x H: 0')
CIE Type: Direct

Input Watts (W): 100.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504243

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-04-BLAK-PS (5000K_L16_Medium_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1504243

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-04-BLAK-PS (5000K_L16_Medium_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100								
1	113	109	106	104	110	107	105	102	103	101	99	99	98	96	96	95	93	91								
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83								
3	99	91	86	81	97	90	85	80	87	83	79	85	81	78	82	79	76	75								
4	93	84	77	72	91	83	76	72	80	75	71	78	74	70	76	72	69	67								
5	87	77	70	65	85	76	69	65	74	68	64	72	67	63	71	66	63	61								
6	81	71	64	59	80	70	63	58	68	62	58	67	62	58	65	61	57	56								
7	76	65	58	53	75	65	58	53	63	57	53	62	57	53	61	56	52	51								
8	72	61	54	49	70	60	53	49	59	53	49	58	52	48	57	52	48	46								
9	68	56	50	45	66	56	49	45	55	49	45	54	48	44	53	48	44	43								
10	64	53	46	41	63	52	46	41	51	45	41	50	45	41	50	45	41	39								

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	83043
5°	83088
10°	82670
15°	81777
20°	78950
25°	75456
30°	70201
35°	61731
40°	49725
45°	38410
50°	30373
55°	14816
60°	5410
65°	2282
70°	657
75°	325
80°	379
85°	430

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 38410 cd/sqm

TEST NUMBER: P1504243

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-04-BLAK-PS (5000K_L16_Medium_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	860.4	6.4
10°-20°	2425.6	17.9
20°-30°	3429.0	25.4
30°-40°	3415.3	25.3
40°-50°	2340.3	17.3
50°-60°	914.0	6.8
60°-70°	123.3	0.9
70°-80°	11.7	0.1
80°-90°	4.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6714.9	49.7
0°-40°	10130.2	74.9
0°-60°	13384.5	99.0
0°-90°	13523.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	13523.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9093	
5°	9063	860
15°	8649	2426
25°	7488	3429
35°	5537	3415
45°	2974	2340
55°	930	914
65°	106	123
75°	9	12
85°	4	4
90°	0	

TEST NUMBER: P1504243

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-04-BLAK-PS (5000K_L16_Medium_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	9092.7
2.5°	9066.1
5°	9063.0
7.5°	9014.8
10°	8914.4
12.5°	8803.7
15°	8649.0
17.5°	8415.3
20°	8123.3
22.5°	7814.8
25°	7487.9
27.5°	7108.8
30°	6656.8
32.5°	6126.0
35°	5536.8
37.5°	4864.5
40°	4170.8
42.5°	3531.3
45°	2973.9
47.5°	2538.3
50°	2137.7
52.5°	1561.7
55°	930.5
57.5°	442.7
60°	296.2
62.5°	186.5
65°	105.6
67.5°	51.2
70°	24.6
72.5°	11.3
75°	9.2
77.5°	8.2
80°	7.2
82.5°	6.1
85°	4.1
87.5°	2.0
90°	0.0

(END OF REPORT)