

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504379

Luminaire Tested: PRLX-UHBS2-1218-MV-L8C5-U-A-04-WHGL-PS (5000K_L16_Narrow_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504379
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-22)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-1218-MV-L8C5-U-A-04-WHGL-PS (5000K_L16_Narrow_120V)
Description: PrentaLux UHBS2 4-INCH SELECTABLE HIGH BAY 1218 LIGHT ENGINE, DOMIC WHITE
SHADE, NARROW DISTRIBUTION
LIGHT LEVEL 2 - 16,000 LUMENS
Light Source: 5000K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 14566.8 lumens
Efficiency: N/A
Efficacy: 145.5 lumens/watt
Spacing Criteria (0/90/45): 0.97 / 0.97 / 1
Luminous Opening: Circular (Dia: 1.23' x H: 0')
CIE Type: Direct

Input Watts (W): 100.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504379

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-04-WHGL-PS (5000K_L16_Narrow_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1504379

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-04-WHGL-PS (5000K_L16_Narrow_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	95	93	92	90		
2	104	98	93	89	102	96	92	88	93	89	86	90	87	84	87	84	82	80		
3	97	89	83	78	95	88	82	77	85	80	76	82	78	75	80	76	73	72		
4	91	81	74	69	89	80	74	69	78	72	68	76	71	67	74	70	66	64		
5	85	75	67	62	83	74	67	62	72	66	61	70	65	61	68	64	60	58		
6	80	69	61	56	78	68	61	56	66	60	55	65	59	55	63	58	55	53		
7	75	63	56	51	73	63	56	51	61	55	51	60	54	50	59	54	50	48		
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44		
9	66	55	48	43	65	54	47	43	53	47	43	52	47	43	51	46	42	41		
10	63	51	44	40	61	51	44	40	50	44	40	49	43	39	48	43	39	38		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	95771
5°	95085
10°	92326
15°	88424
20°	82705
25°	75064
30°	65058
35°	54533
40°	45730
45°	39349
50°	35890
55°	21457
60°	12278
65°	8903
70°	7771
75°	8786
80°	10293
85°	11275

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 47.5°

Luminance: 39897 cd/sqm

TEST NUMBER: P1504379

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-04-WHGL-PS (5000K_L16_Narrow_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	976.8	6.7
10°-20°	2616.7	18.0
20°-30°	3395.6	23.3
30°-40°	3071.6	21.1
40°-50°	2422.5	16.6
50°-60°	1276.6	8.8
60°-70°	433.7	3.0
70°-80°	260.2	1.8
80°-90°	113.1	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6989.1	48.0
0°-40°	10060.7	69.1
0°-60°	13759.8	94.5
0°-90°	14566.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	14566.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10486	
5°	10372	977
15°	9352	2617
25°	7449	3396
35°	4891	3072
45°	3047	2423
55°	1348	1277
65°	412	434
75°	249	260
85°	108	113
90°	0	

TEST NUMBER: P1504379

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-04-WHGL-PS (5000K_L16_Narrow_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	10486.4
2.5°	10436.2
5°	10371.6
7.5°	10213.8
10°	9955.6
12.5°	9674.8
15°	9352.0
17.5°	8958.5
20°	8509.6
22.5°	8006.5
25°	7449.0
27.5°	6823.9
30°	6169.1
32.5°	5519.4
35°	4891.2
37.5°	4328.6
40°	3835.7
42.5°	3396.1
45°	3046.6
47.5°	2951.3
50°	2526.0
52.5°	1976.8
55°	1347.6
57.5°	845.4
60°	672.2
62.5°	527.8
65°	412.0
67.5°	336.1
70°	291.0
72.5°	265.4
75°	249.0
77.5°	227.5
80°	195.7
82.5°	155.8
85°	107.6
87.5°	54.3
90°	0.0

(END OF REPORT)