

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504750

Luminaire Tested: PRLX-UHBS2-1218-MV-L8C5-U-B-04-WHGL-PS (6500K_L18_Medium_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504750
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-35)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-1218-MV-L8C5-U-B-04-WHGL-PS (6500K_L18_Medium_120V)
Description: PrentaLux UHBS2 4-INCH SELECTABLE HIGH BAY 1218 LIGHT ENGINE, CONIC WHITE SHADE, MEDIUM DISTRIBUTION
LIGHT LEVEL 1 - 18,000 LUMENS
Light Source: 6500K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 17390.7 lumens
Efficiency: N/A
Efficacy: 141.0 lumens/watt
Spacing Criteria (0/90/45): 1.13 / 1.13 / 1.13
Luminous Opening: Circular (Dia: 1.26' x H: 0')
CIE Type: Direct

Input Watts (W): 123.3
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504750

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-B-04-WHGL-PS (6500K_L18_Medium_120V)

Luminous Intensity Polar Plot



TEST NUMBER: P1504750

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-B-04-WHGL-PS (6500K_L18_Medium_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90		
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80		
3	97	89	83	78	95	88	82	77	85	80	76	82	78	74	80	76	73	71		
4	91	81	74	69	89	80	73	68	78	72	68	75	71	67	73	69	66	64		
5	85	74	67	62	83	73	66	61	71	65	61	69	64	60	68	63	59	58		
6	79	68	61	55	78	67	60	55	66	59	55	64	59	54	63	58	54	52		
7	74	63	55	50	73	62	55	50	61	54	50	59	54	49	58	53	49	47		
8	70	58	51	46	68	57	51	46	56	50	45	55	49	45	54	49	45	43		
9	66	54	47	42	64	53	47	42	52	46	42	51	46	42	50	45	41	40		
10	62	50	43	39	61	50	43	39	49	43	38	48	42	38	47	42	38	37		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	92359
5°	92416
10°	91917
15°	90929
20°	88248
25°	84878
30°	79903
35°	71584
40°	58692
45°	46596
50°	38086
55°	22076
60°	11962
65°	9323
70°	8579
75°	9692
80°	10991
85°	11887

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 46596 cd/sqm

TEST NUMBER: P1504750

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-B-04-WHGL-PS (6500K_L18_Medium_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1009.6	5.8
10°-20°	2849.4	16.4
20°-30°	4075.4	23.4
30°-40°	4177.5	24.0
40°-50°	2991.7	17.2
50°-60°	1388.3	8.0
60°-70°	471.1	2.7
70°-80°	301.3	1.7
80°-90°	126.4	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	7934.4	45.6
0°-40°	12112.0	69.6
0°-60°	16491.9	94.8
0°-90°	17390.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	17390.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10671	
5°	10637	###
15°	10147	2849
25°	8888	4075
35°	6775	4178
45°	3807	2992
55°	1463	1388
65°	455	471
75°	290	301
85°	120	126
90°	0	

TEST NUMBER: P1504750

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-B-04-WHGL-PS (6500K_L18_Medium_120V)

CANDELA DISTRIBUTION (FULL):

0°	
0°	10670.6
2.5°	10642.4
5°	10636.6
7.5°	10576.7
10°	10458.2
12.5°	10322.2
15°	10147.4
17.5°	9895.2
20°	9580.8
22.5°	9246.4
25°	8887.5
27.5°	8480.4
30°	7994.7
32.5°	7431.6
35°	6774.7
37.5°	6018.0
40°	5194.5
42.5°	4450.8
45°	3806.7
47.5°	3310.5
50°	2828.4
52.5°	2174.9
55°	1462.9
57.5°	881.0
60°	691.0
62.5°	558.4
65°	455.2
67.5°	378.9
70°	339.0
72.5°	310.9
75°	289.8
77.5°	260.4
80°	220.5
82.5°	172.4
85°	119.7
87.5°	62.2
90°	0.0

(END OF REPORT)