

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1505608

Luminaire Tested: PRLX-UHBS2-2436-MV-L8C5-U-B-06-WHGL-PS (3000K_L24_Medium_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1505608
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-122)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-2436-MV-L8C5-U-B-06-WHGL-PS (3000K_L24_Medium_120V)
Description: PrentaLux UHBS2 6-INCH SELECTABLE HIGH BAY 2436 LIGHT ENGINE, CONIC WHITE SHADE, MEDIUM DISTRIBUTION
LIGHT LEVEL 1 - 24,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 23603.4 lumens
Efficiency: N/A
Efficacy: 148.1 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 1.47' x H: 0')
CIE Type: Direct

Input Watts (W): 159.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1505608

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-B-06-WHGL-PS (3000K_L24_Medium_120V)

Luminous Intensity Polar Plot



TEST NUMBER: P1505608

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-B-06-WHGL-PS (3000K_L24_Medium_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	108	105	102	109	106	103	100	101	99	97	98	96	94	94	93	91	89		
2	104	98	92	88	102	96	91	87	92	88	85	89	86	83	86	84	81	79		
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	80	76	73	71		
4	91	81	74	69	89	80	73	68	77	72	67	75	70	67	73	69	66	64		
5	85	74	67	62	83	73	66	61	71	65	61	69	64	60	68	63	59	58		
6	79	68	61	56	78	67	60	55	66	60	55	64	59	54	63	58	54	52		
7	74	63	56	50	73	62	55	50	61	55	50	60	54	50	58	53	49	48		
8	70	58	51	46	68	58	51	46	57	50	46	55	50	46	54	49	45	44		
9	66	54	47	42	65	54	47	42	53	46	42	52	46	42	51	46	42	40		
10	62	51	44	39	61	50	43	39	49	43	39	48	43	39	47	42	39	37		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	91700
5°	91771
10°	91428
15°	91142
20°	90353
25°	88815
30°	84770
35°	72726
40°	56648
45°	42452
50°	28465
55°	16092
60°	13351
65°	12238
70°	13433
75°	14521
80°	15226
85°	15322

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 42452 cd/sqm

TEST NUMBER: P1505608

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-B-06-WHGL-PS (3000K_L24_Medium_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1362.7	5.8
10°-20°	3895.3	16.5
20°-30°	5786.2	24.5
30°-40°	5773.5	24.5
40°-50°	3642.6	15.4
50°-60°	1470.4	6.2
60°-70°	830.9	3.5
70°-80°	614.5	2.6
80°-90°	227.3	1.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	11044.2	46.8
0°-40°	16817.7	71.3
0°-60°	21930.6	92.9
0°-90°	23603.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	23603.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	14393	
5°	14349	###
15°	13818	3895
25°	12634	5786
35°	9351	5774
45°	4712	3643
55°	1449	1470
65°	812	831
75°	590	614
85°	210	227
90°	0	

TEST NUMBER: P1505608

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-B-06-WHGL-PS (3000K_L24_Medium_120V)

CANDELA DISTRIBUTION (FULL):

0°	
0°	14393.0
2.5°	14365.0
5°	14349.3
7.5°	14270.1
10°	14132.3
12.5°	13991.2
15°	13818.0
17.5°	13591.1
20°	13326.3
22.5°	13012.0
25°	12634.1
27.5°	12140.8
30°	11522.8
32.5°	10548.5
35°	9350.6
37.5°	8071.0
40°	6811.2
42.5°	5694.2
45°	4711.6
47.5°	3779.3
50°	2871.8
52.5°	1984.1
55°	1448.7
57.5°	1228.4
60°	1047.8
62.5°	896.0
65°	811.8
67.5°	764.0
70°	721.1
72.5°	663.3
75°	589.9
77.5°	506.6
80°	415.0
82.5°	315.2
85°	209.6
87.5°	103.1
90°	0.0

(END OF REPORT)