

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1505128

Luminaire Tested: PRLX-UHBS2-2436-MV-L8C5-U-A-06-BLAK-PS (3500K_L36_Medium_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1505128
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-104)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-2436-MV-L8C5-U-A-06-BLAK-PS (3500K_L36_Medium_120V)
Description: PrentaLux UHBS2 6-INCH SELECTABLE HIGH BAY 2436 LIGHT ENGINE, DOMIC BLACK SHADE, MEDIUM DISTRIBUTION
LIGHT LEVEL 1 - 36,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 27015.8 lumens
Efficiency: N/A
Efficacy: 114.8 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.21 / 1.14
Luminous Opening: Circular (Dia: 1.43' x H: 0')
CIE Type: Direct

Input Watts (W): 235.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1505128

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-BLAK-PS (3500K_L36_Medium_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1505128

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-BLAK-PS (3500K_L36_Medium_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20				
RC	80					70					50					30					10				
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10		
RCR																									
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100							
1	113	110	107	104	110	107	105	103	103	101	100	100	98	97	96	95	94	92							
2	106	101	96	92	104	99	95	91	96	92	89	93	90	87	90	88	85	84							
3	100	92	87	82	98	91	86	82	88	84	80	86	82	79	84	80	78	76							
4	94	85	79	74	92	84	78	73	82	77	73	80	75	72	78	74	71	69							
5	88	78	72	67	86	77	71	66	76	70	66	74	69	65	72	68	65	63							
6	83	72	66	61	81	72	65	60	70	64	60	69	63	60	67	63	59	58							
7	78	67	60	55	76	66	60	55	65	59	55	64	58	55	63	58	54	53							
8	73	62	55	51	72	62	55	51	60	55	50	59	54	50	58	54	50	48							
9	69	58	51	47	68	57	51	47	56	51	46	55	50	46	55	50	46	45							
10	65	54	48	43	64	54	47	43	53	47	43	52	47	43	51	46	43	41							

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	122011
5°	121838
10°	121302
15°	121000
20°	120293
25°	119753
30°	117175
35°	100933
40°	76833
45°	51105
50°	27349
55°	7788
60°	3474
65°	1083
70°	815
75°	900
80°	983
85°	1064

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 51105 cd/sqm

TEST NUMBER: P1505128

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-BLAK-PS (3500K_L36_Medium_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1727.7	6.4
10°-20°	4940.6	18.3
20°-30°	7473.1	27.7
30°-40°	7625.4	28.2
40°-50°	4227.2	15.6
50°-60°	873.9	3.2
60°-70°	96.8	0.4
70°-80°	36.5	0.1
80°-90°	14.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	14141.4	52.3
0°-40°	21766.9	80.6
0°-60°	26867.9	99.5
0°-90°	27015.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	27015.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	18290	
5°	18195	###
15°	17520	4941
25°	16270	7473
35°	12394	7625
45°	5417	4227
55°	670	874
65°	69	97
75°	35	37
85°	14	15
90°	0	

TEST NUMBER: P1505128

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-BLAK-PS (3500K_L36_Medium_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	18289.9
2.5°	18230.6
5°	18194.6
7.5°	18088.8
10°	17907.5
12.5°	17722.6
15°	17520.4
17.5°	17243.7
20°	16945.0
22.5°	16624.1
25°	16269.6
27.5°	15806.9
30°	15211.7
32.5°	13956.3
35°	12394.0
37.5°	10688.7
40°	8823.0
42.5°	7037.4
45°	5417.0
47.5°	3986.0
50°	2635.3
52.5°	1433.3
55°	669.6
57.5°	431.3
60°	260.4
62.5°	129.0
65°	68.6
67.5°	46.5
70°	41.8
72.5°	38.4
75°	34.9
77.5°	31.4
80°	25.6
82.5°	19.8
85°	13.9
87.5°	7.0
90°	0.0

(END OF REPORT)