

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1505087

Luminaire Tested: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L24_Narrow_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1505087
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-85)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L24_Narrow_120V)
Description: PrentaLux UHBS2 4-INCH SELECTABLE HIGH BAY 2436 LIGHT ENGINE, DOMIC WHITE SHADE, NARROW DISTRIBUTION
LIGHT LEVEL 1 - 24,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 24297.4 lumens
Efficiency: N/A
Efficacy: 156.1 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 1.02
Luminous Opening: Circular (Dia: 1.37' x H: 0')
CIE Type: Direct

Input Watts (W): 155.7
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1505087

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L24_Narrow_120V)

Luminous Intensity Polar Plot



TEST NUMBER: P1505087

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L24_Narrow_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90		
2	104	98	93	88	102	96	91	87	93	89	85	90	86	83	87	84	82	80		
3	97	89	83	78	95	87	82	77	85	80	76	82	78	74	80	76	73	71		
4	91	81	74	69	89	80	73	68	78	72	67	75	71	67	73	69	66	64		
5	85	74	67	62	83	73	66	61	71	65	61	69	64	60	68	63	60	58		
6	79	68	61	56	78	67	60	55	66	60	55	64	59	55	63	58	54	52		
7	74	63	56	51	73	62	55	50	61	55	50	60	54	50	58	53	49	48		
8	70	58	51	46	69	58	51	46	57	50	46	55	50	46	54	49	45	44		
9	66	54	47	43	65	54	47	42	53	47	42	52	46	42	51	46	42	40		
10	62	51	44	39	61	50	44	39	49	43	39	49	43	39	48	43	39	37		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	120723
5°	120626
10°	119638
15°	117274
20°	110813
25°	101320
30°	87194
35°	72536
40°	60196
45°	51330
50°	47633
55°	33626
60°	17728
65°	13181
70°	10366
75°	11334
80°	13370
85°	14767

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 51330 cd/sqm

TEST NUMBER: P1505087

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L24_Narrow_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1552.8	6.4
10°-20°	4313.5	17.8
20°-30°	5691.3	23.4
30°-40°	5081.5	20.9
40°-50°	3936.6	16.2
50°-60°	2336.6	9.6
60°-70°	778.9	3.2
70°-80°	422.4	1.7
80°-90°	183.9	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	11557.6	47.6
0°-40°	16639.0	68.5
0°-60°	22912.2	94.3
0°-90°	24297.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	24297.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	16453	
5°	16377	###
15°	15438	4313
25°	12515	5691
35°	8098	5081
45°	4946	3937
55°	2628	2337
65°	759	779
75°	400	422
85°	175	184
90°	0	

TEST NUMBER: P1505087

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L24_Narrow_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	16452.6
2.5°	16417.3
5°	16376.9
7.5°	16250.5
10°	16057.1
12.5°	15802.5
15°	15438.0
17.5°	14880.8
20°	14191.3
22.5°	13433.8
25°	12514.6
27.5°	11452.7
30°	10291.1
32.5°	9169.1
35°	8097.7
37.5°	7116.7
40°	6284.4
42.5°	5584.5
45°	4946.5
47.5°	4681.7
50°	4172.7
52.5°	3420.3
55°	2628.5
57.5°	1796.2
60°	1208.0
62.5°	963.0
65°	759.2
67.5°	589.8
70°	483.2
72.5°	433.3
75°	399.8
77.5°	366.3
80°	316.4
82.5°	251.9
85°	175.4
87.5°	90.3
90°	0.0

(END OF REPORT)