

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1505093

Luminaire Tested: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L36_Narrow_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1505093
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-85)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L36_Narrow_120V)
Description: PrentaLux UHBS2 4-INCH SELECTABLE HIGH BAY 2436 LIGHT ENGINE, DOMIC WHITE SHADE, NARROW DISTRIBUTION
LIGHT LEVEL 1 - 36,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 34217.8 lumens
Efficiency: N/A
Efficacy: 147.6 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 1.02
Luminous Opening: Circular (Dia: 1.37' x H: 0')
CIE Type: Direct

Input Watts (W): 231.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1505093

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L36_Narrow_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1505093

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L36_Narrow_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90		
2	104	98	93	88	102	96	91	87	93	89	85	90	86	83	87	84	82	80		
3	97	89	83	78	95	87	82	77	85	80	76	82	78	74	80	76	73	71		
4	91	81	74	69	89	80	73	68	78	72	67	75	71	67	73	69	66	64		
5	85	74	67	62	83	73	66	61	71	65	61	69	64	60	68	63	60	58		
6	79	68	61	56	78	67	60	55	66	60	55	64	59	55	63	58	54	52		
7	74	63	56	51	73	62	55	50	61	55	50	60	54	50	58	53	49	48		
8	70	58	51	46	69	58	51	46	57	50	46	55	50	46	54	49	45	44		
9	66	54	47	43	65	54	47	42	53	47	42	52	46	42	51	46	42	40		
10	62	51	44	39	61	50	44	39	49	43	39	49	43	39	48	43	39	37		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	170013
5°	169877
10°	168485
15°	165155
20°	156057
25°	142688
30°	122795
35°	102152
40°	84772
45°	72287
50°	67080
55°	47354
60°	24967
65°	18564
70°	14599
75°	15964
80°	18829
85°	20795

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 72287 cd/sqm

TEST NUMBER: P1505093

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L36_Narrow_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2186.8	6.4
10°-20°	6074.6	17.8
20°-30°	8015.0	23.4
30°-40°	7156.2	20.9
40°-50°	5543.8	16.2
50°-60°	3290.6	9.6
60°-70°	1097.0	3.2
70°-80°	594.8	1.7
80°-90°	259.0	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	16276.4	47.6
0°-40°	23432.6	68.5
0°-60°	32267.0	94.3
0°-90°	34217.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	34217.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	23170	
5°	23063	###
15°	21741	6075
25°	17624	8015
35°	11404	7156
45°	6966	5544
55°	3702	3291
65°	1069	1097
75°	563	595
85°	247	259
90°	0	

TEST NUMBER: P1505093

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-04-WHGL-PS (4000K_L36_Narrow_120V)

CANDELA DISTRIBUTION (FULL):

0°	
0°	23170.0
2.5°	23120.3
5°	23063.4
7.5°	22885.4
10°	22613.0
12.5°	22254.6
15°	21741.1
17.5°	20956.5
20°	19985.4
22.5°	18918.6
25°	17624.2
27.5°	16128.8
30°	14492.9
32.5°	12912.7
35°	11404.0
37.5°	10022.4
40°	8850.2
42.5°	7864.6
45°	6966.1
47.5°	6593.2
50°	5876.3
52.5°	4816.8
55°	3701.6
57.5°	2529.5
60°	1701.3
62.5°	1356.2
65°	1069.2
67.5°	830.7
70°	680.5
72.5°	610.3
75°	563.1
77.5°	515.8
80°	445.6
82.5°	354.8
85°	247.0
87.5°	127.1
90°	0.0

(END OF REPORT)