

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1505280

Luminaire Tested: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (5000K_L32_Wide_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1505280
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-111)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (5000K_L32_Wide_120V)
Description: PrentaLux UHBS2 6-INCH SELECTABLE HIGH BAY 2436 LIGHT ENGINE, DOMIC WHITE SHADE, WIDE DISTRIBUTION
LIGHT LEVEL 2 - 32,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 30780.7 lumens
Efficiency: N/A
Efficacy: 157.4 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.24
Luminous Opening: Circular (Dia: 1.43' x H: 0')
CIE Type: Direct

Input Watts (W): 195.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1505280

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (5000K_L32_Wide_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1505280

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (5000K_L32_Wide_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88		
2	103	96	91	86	101	95	90	85	91	87	83	88	85	82	85	82	80	78		
3	96	87	81	75	94	86	80	75	83	78	73	80	76	72	78	74	71	69		
4	89	79	72	66	87	78	71	66	76	70	65	73	68	64	71	67	63	62		
5	83	72	65	59	81	71	64	59	69	63	58	67	62	58	66	61	57	55		
6	78	66	58	53	76	65	58	53	64	57	52	62	56	52	61	55	51	50		
7	73	61	53	48	71	60	53	48	59	52	47	57	51	47	56	51	47	45		
8	68	56	49	43	67	55	48	43	54	48	43	53	47	43	52	47	43	41		
9	64	52	45	40	63	51	44	40	50	44	39	49	43	39	48	43	39	37		
10	60	48	41	36	59	48	41	36	47	41	36	46	40	36	45	40	36	34		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	106407
5°	106594
10°	106920
15°	108093
20°	108904
25°	110084
30°	110927
35°	102135
40°	87457
45°	66621
50°	44404
55°	22944
60°	18840
65°	19796
70°	22446
75°	25316
80°	27571
85°	27585

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 66621 cd/sqm

TEST NUMBER: P1505280

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (5000K_L32_Wide_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1515.0	4.9
10°-20°	4420.4	14.4
20°-30°	6895.0	22.4
30°-40°	7749.9	25.2
40°-50°	5453.6	17.7
50°-60°	2083.6	6.8
60°-70°	1252.1	4.1
70°-80°	1019.2	3.3
80°-90°	391.9	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	12830.4	41.7
0°-40°	20580.3	66.9
0°-60°	28117.5	91.3
0°-90°	30780.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	30780.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	15951	
5°	15918	###
15°	15652	4420
25°	14956	6895
35°	12542	7750
45°	7062	5454
55°	1973	2084
65°	1254	1252
75°	982	1019
85°	360	392
90°	0	

TEST NUMBER: P1505280

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (5000K_L32_Wide_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	15950.8
2.5°	15926.5
5°	15918.1
7.5°	15865.4
10°	15784.3
12.5°	15727.4
15°	15651.5
17.5°	15522.9
20°	15340.6
22.5°	15157.2
25°	14956.0
27.5°	14709.4
30°	14400.6
32.5°	13563.9
35°	12541.6
37.5°	11360.3
40°	10043.0
42.5°	8591.9
45°	7061.7
47.5°	5669.6
50°	4278.6
52.5°	3023.4
55°	1972.8
57.5°	1559.7
60°	1412.1
62.5°	1312.0
65°	1254.1
67.5°	1204.5
70°	1150.8
72.5°	1078.1
75°	982.2
77.5°	865.2
80°	717.7
82.5°	544.8
85°	360.4
87.5°	176.0
90°	0.0

(END OF REPORT)