

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1505290

Luminaire Tested: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Medium_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1505290
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-110)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Medium_120V)
Description: PrentaLux UHBS2 6-INCH SELECTABLE HIGH BAY 2436 LIGHT ENGINE, DOMIC WHITE
SHADE, MEDIUM DISTRIBUTION
LIGHT LEVEL 1 - 36,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 33385.1 lumens
Efficiency: N/A
Efficacy: 139.3 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.13
Luminous Opening: Circular (Dia: 1.43' x H: 0')
CIE Type: Direct

Input Watts (W): 239.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1505290

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Medium_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1505290

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Medium_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	108	104	101	109	105	102	100	101	99	97	97	95	94	94	92	91	89		
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79		
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71		
4	90	81	74	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63		
5	84	74	67	61	83	73	66	61	71	65	60	69	64	60	67	63	59	57		
6	79	68	61	55	77	67	60	55	65	59	55	64	58	54	62	58	54	52		
7	74	63	55	50	73	62	55	50	61	54	50	59	54	49	58	53	49	47		
8	70	58	51	46	68	57	51	46	56	50	45	55	49	45	54	49	45	43		
9	66	54	47	42	64	53	47	42	52	46	42	51	46	42	50	45	41	40		
10	62	50	43	39	61	50	43	39	49	43	39	48	42	38	47	42	38	37		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	133803
5°	133749
10°	133248
15°	133223
20°	132650
25°	131543
30°	126578
35°	108183
40°	83625
45°	61204
50°	40006
55°	23711
60°	20118
65°	19253
70°	21527
75°	23947
80°	26284
85°	28067

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 61204 cd/sqm

TEST NUMBER: P1505290

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Medium_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1896.7	5.7
10°-20°	5442.1	16.3
20°-30°	8187.2	24.5
30°-40°	8197.9	24.6
40°-50°	5036.8	15.1
50°-60°	2029.3	6.1
60°-70°	1238.1	3.7
70°-80°	968.0	2.9
80°-90°	389.0	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	15526.0	46.5
0°-40°	23723.9	71.1
0°-60°	30790.0	92.2
0°-90°	33385.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	33385.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	20058	
5°	19973	###
15°	19290	5442
25°	17871	8187
35°	13284	8198
45°	6488	5037
55°	2039	2029
65°	1220	1238
75°	929	968
85°	367	389
90°	0	

TEST NUMBER: P1505290

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Medium_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	20057.6
2.5°	20007.2
5°	19973.3
7.5°	19854.9
10°	19671.0
12.5°	19496.4
15°	19290.2
17.5°	19025.4
20°	18685.6
22.5°	18322.4
25°	17871.3
27.5°	17257.4
30°	16432.5
32.5°	14997.2
35°	13284.3
37.5°	11441.2
40°	9602.9
42.5°	7945.0
45°	6487.5
47.5°	5163.5
50°	3854.8
52.5°	2665.5
55°	2038.7
57.5°	1744.6
60°	1507.9
62.5°	1315.8
65°	1219.7
67.5°	1157.6
70°	1103.7
72.5°	1027.5
75°	929.1
77.5°	815.5
80°	684.2
82.5°	535.4
85°	366.7
87.5°	185.1
90°	0.0

(END OF REPORT)