

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1505292

Luminaire Tested: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Wide_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1505292
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-111)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Wide_120V)
Description: PrentaLux UHBS2 6-INCH SELECTABLE HIGH BAY 2436 LIGHT ENGINE, DOMIC WHITE SHADE, WIDE DISTRIBUTION
LIGHT LEVEL 1 - 36,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 34222.2 lumens
Efficiency: N/A
Efficacy: 142.8 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.24
Luminous Opening: Circular (Dia: 1.43' x H: 0')
CIE Type: Direct

Input Watts (W): 239.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1505292

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Wide_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1505292

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Wide_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88		
2	103	96	91	86	101	95	90	85	91	87	83	88	85	82	85	82	80	78		
3	96	87	81	75	94	86	80	75	83	78	73	80	76	72	78	74	71	69		
4	89	79	72	66	87	78	71	66	76	70	65	73	68	64	71	67	63	62		
5	83	72	65	59	81	71	64	59	69	63	58	67	62	58	66	61	57	55		
6	78	66	58	53	76	65	58	53	64	57	52	62	56	52	61	55	51	50		
7	73	61	53	48	71	60	53	48	59	52	47	57	51	47	56	51	47	45		
8	68	56	49	43	67	55	48	43	54	48	43	53	47	43	52	47	43	41		
9	64	52	45	40	63	51	44	40	50	44	39	49	43	39	48	43	39	37		
10	60	48	41	36	59	48	41	36	47	41	36	46	40	36	45	40	36	34		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	118304
5°	118512
10°	118875
15°	120179
20°	121080
25°	122393
30°	123329
35°	113555
40°	97236
45°	74070
50°	49368
55°	25509
60°	20947
65°	22009
70°	24956
75°	28146
80°	30652
85°	30670

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 74070 cd/sqm

TEST NUMBER: P1505292

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Wide_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1684.4	4.9
10°-20°	4914.7	14.4
20°-30°	7665.9	22.4
30°-40°	8616.4	25.2
40°-50°	6063.3	17.7
50°-60°	2316.6	6.8
60°-70°	1392.2	4.1
70°-80°	1133.1	3.3
80°-90°	435.7	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	14265.0	41.7
0°-40°	22881.4	66.9
0°-60°	31261.3	91.3
0°-90°	34222.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	34222.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	17734	
5°	17698	###
15°	17402	4915
25°	16628	7666
35°	13944	8616
45°	7851	6063
55°	2193	2317
65°	1394	1392
75°	1092	1133
85°	401	436
90°	0	

TEST NUMBER: P1505292

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-A-06-WHGL-PS (6500K_L36_Wide_120V)

CANDELA DISTRIBUTION (FULL):

0°	
0°	17734.2
2.5°	17707.3
5°	17697.9
7.5°	17639.3
10°	17549.1
12.5°	17485.8
15°	17401.5
17.5°	17258.5
20°	17055.8
22.5°	16852.0
25°	16628.2
27.5°	16354.0
30°	16010.7
32.5°	15080.4
35°	13943.9
37.5°	12630.5
40°	11165.9
42.5°	9552.5
45°	7851.3
47.5°	6303.5
50°	4756.9
52.5°	3361.5
55°	2193.3
57.5°	1734.1
60°	1570.0
62.5°	1458.7
65°	1394.3
67.5°	1339.2
70°	1279.5
72.5°	1198.6
75°	1092.0
77.5°	961.9
80°	797.9
82.5°	605.7
85°	400.7
87.5°	195.7
90°	0.0

(END OF REPORT)