

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1505471

Luminaire Tested: PRLX-UHBS2-2436-MV-L8C5-U-B-04-WHGL-PS (6500K_L36_Narrow_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1505471
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-97)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-2436-MV-L8C5-U-B-04-WHGL-PS (6500K_L36_Narrow_120V)
Description: PrentaLux UHBS2 4-INCH SELECTABLE HIGH BAY 2436 LIGHT ENGINE, CONIC WHITE SHADE, NARROW DISTRIBUTION
LIGHT LEVEL 1 - 36,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 33249.7 lumens
Efficiency: N/A
Efficacy: 138.8 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 1.01
Luminous Opening: Circular (Dia: 1.38' x H: 0')
CIE Type: Direct

Input Watts (W): 239.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1505471

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-B-04-WHGL-PS (6500K_L36_Narrow_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1505471

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-B-04-WHGL-PS (6500K_L36_Narrow_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90		
2	104	98	93	88	102	96	91	87	93	89	85	90	86	83	87	84	82	80		
3	97	89	83	77	95	87	82	77	85	80	76	82	78	74	80	76	73	71		
4	91	81	74	69	89	80	73	68	78	72	67	75	71	67	73	69	66	64		
5	85	74	67	62	83	73	66	61	71	65	61	69	64	60	68	63	59	58		
6	79	68	61	56	78	67	60	55	66	60	55	64	59	54	63	58	54	52		
7	74	63	56	50	73	62	55	50	61	55	50	60	54	50	58	53	49	48		
8	70	58	51	46	69	58	51	46	57	50	46	55	50	46	54	49	45	44		
9	66	54	47	42	65	54	47	42	53	47	42	52	46	42	51	46	42	40		
10	62	51	44	39	61	50	44	39	49	43	39	48	43	39	48	43	39	37		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	163647
5°	163513
10°	161885
15°	157631
20°	148145
25°	134076
30°	114451
35°	94930
40°	79746
45°	68295
50°	64555
55°	46508
60°	24267
65°	18187
70°	14034
75°	15075
80°	17058
85°	17815

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 47.5°

Luminance: 69717 cd/sqm

TEST NUMBER: P1505471

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-B-04-WHGL-PS (6500K_L36_Narrow_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2155.7	6.5
10°-20°	5940.2	17.9
20°-30°	7715.2	23.2
30°-40°	6834.9	20.6
40°-50°	5411.1	16.3
50°-60°	3290.1	9.9
60°-70°	1096.5	3.3
70°-80°	574.1	1.7
80°-90°	232.0	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	15811.1	47.6
0°-40°	22646.0	68.1
0°-60°	31347.2	94.3
0°-90°	33249.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	33249.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	22850	
5°	22744	###
15°	21260	5940
25°	16967	7715
35°	10858	6835
45°	6743	5411
55°	3725	3290
65°	1073	1096
75°	545	574
85°	217	232
90°	0	

TEST NUMBER: P1505471

CATALOG NUMBER: PRLX-UHBS2-2436-MV-L8C5-U-B-04-WHGL-PS (6500K_L36_Narrow_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	22849.7
2.5°	22800.5
5°	22744.2
7.5°	22568.5
10°	22260.3
12.5°	21863.2
15°	21259.7
17.5°	20429.0
20°	19437.8
22.5°	18301.3
25°	16966.8
27.5°	15428.4
30°	13839.6
32.5°	12304.8
35°	10857.8
37.5°	9591.2
40°	8529.7
42.5°	7601.7
45°	6742.9
47.5°	6576.5
50°	5793.9
52.5°	4780.4
55°	3724.7
57.5°	2581.2
60°	1694.2
62.5°	1362.6
65°	1073.2
67.5°	827.2
70°	670.2
72.5°	596.4
75°	544.8
77.5°	490.9
80°	413.6
82.5°	321.0
85°	216.8
87.5°	107.8
90°	0.0

(END OF REPORT)