

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P691010

Luminaire Tested: **CRTK2-C01-D-U-T5R-8027-U0**

Issue Date: 6/13/2023

Test Information

Test Method: LM-79-08
Report Number: P691010
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2301-903-19)
Test Lab: INNOVATION CENTER
Issue Date: 6/13/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: CRTK2-C01-D-U-T5R-8027-U0
Description: CARETAKER AREA AND ROADWAY LUMINAIRE
(1) 80 CRI, 2700K LED WITH TYPE V ROUND OPTIC AND U0 SHIELD
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8018 lumens
Efficiency: N/A
Efficacy: 131.4 lumens/watt
Luminous Opening: Circular (Dia: 0.33' x H: 0')
IES Classification: Type V - Short
BUG Rating: B3 - U0 - G2

Input Watts (W): 61
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




REPORT NUMBER: P691010
 CATALOG NUMBER: CRTK2-C01-D-U-T5R-8027-U0

Iso-Footcandle Lines of Horizontal Illumination

✕ Max cd


--- 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 1.2 fc
 Type V - Short - N/A

REPORT NUMBER: P691010
CATALOG NUMBER: CRTK2-C01-D-U-T5R-8027-U0

Luminous Intensity Polar Plot



REPORT NUMBER: P691010

CATALOG NUMBER: CRTK2-C01-D-U-T5R-8027-U0


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	4009.0	0.0	4009.0
	% Fixture	50.0	0.0	50.0
Street Side	Lumens	4009.0	0.0	4009.0
	% Fixture	50.0	0.0	50.0
Total	Lumens	8018.0	0.0	8018.0
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	69.8	0.9
10°-20°	189.2	2.4
20°-30°	326.0	4.1
30°-40°	553.7	6.9
40°-50°	976.9	12.2
50°-60°	1664.8	20.8
60°-70°	2394.6	29.9
70°-80°	1741.3	21.7
80°-90°	101.6	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	8018.0	100.0
0°-180°	8018.0	100.0

Coefficient of Utilization



REPORT NUMBER: P691010


CATALOG NUMBER: CRTK2-C01-D-U-T5R-8027-U0

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	292.6	3.6			
FM	(30°-60°)	1597.7	19.9			
FH	(60°-80°)	2068.0	25.8			G2/5000
FVH	(80°-90°)	50.8	0.6			G1/100
BL	(0°-30°)	292.6	3.6	B1/500		
BM	(30°-60°)	1597.7	19.9	B2/2500		
BH	(60°-80°)	2068.0	25.8	B3/2500		G2/5000
BVH	(80°-90°)	50.8	0.6			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B3-U0-G2

Type V Short



REPORT NUMBER: P691010
CATALOG NUMBER: CRTK2-C01-D-U-T5R-8027-U0

CANDELA DISTRIBUTION (FULL):

	0°
0°	779.8
2.5°	767.1
5°	752.0
7.5°	724.1
10°	693.7
12.5°	673.5
15°	663.3
17.5°	660.8
20°	663.3
22.5°	676.0
25°	696.3
27.5°	724.1
30°	757.0
32.5°	802.6
35°	865.9
37.5°	944.4
40°	1025.4
42.5°	1124.1
45°	1240.6
47.5°	1377.3
50°	1526.7
52.5°	1686.2
55°	1853.3
57.5°	2010.3
60°	2169.8
62.5°	2316.6
65°	2488.8
67.5°	2559.7
70°	2382.5
72.5°	2109.0
75°	1757.1
77.5°	1268.5
80°	567.1
82.5°	73.4
85°	15.2
87.5°	2.5
90°	0.0

(END OF REPORT)