

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: STREETWORKS

Report Number: P1462438

Luminaire Tested: PRV-P-50-750-U-T2R

Issue Date: 06/10/2026

Test Information

Test Method: LM-79-2024
Report Number: P1462438
Test Lab: INNOVATION CENTER(G3)
Issue Date: 6/11/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: STREETWORKS
Catalog Number: PRV-P-50-750-U-T2R
Description: PREVAIL PETITE DISCRETE LED 1 SQUARE 50W 70CRI 5000K FIXTURE w/ TYPE II
ROADWAY DISTRIBUTION OPTIC
Light Source: (10) 5000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6504.3 lumens
Efficiency: N/A
Efficacy: 123.9 lumens/watt
Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
IES Classification: Type II - Medium
BUG Rating: B2 - U0 - G2

Input Watts (W): 52.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): 6.0%
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT


REPORT NUMBER: P1462438

CATALOG NUMBER: PRV-P-50-750-U-T2R

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 10 foot mounting height. Maximum calculated value = 17.7 fc
 Type II - Medium - N/A

REPORT NUMBER: P1462438

CATALOG NUMBER: PRV-P-50-750-U-T2R

Luminous Intensity Polar Plot



REPORT NUMBER: P1462438

CATALOG NUMBER: PRV-P-50-750-U-T2R


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	2020.0	0.0	2020.0
	% Fixture	31.1	0.0	31.1
Street Side	Lumens	4484.2	0.0	4484.2
	% Fixture	68.9	0.0	68.9
Total	Lumens	6504.3	0.0	6504.3
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	93.8	1.4
10°-20°	342.0	5.3
20°-30°	693.0	10.7
30°-40°	1084.9	16.7
40°-50°	1310.6	20.1
50°-60°	1234.6	19.0
60°-70°	1035.6	15.9
70°-80°	622.9	9.6
80°-90°	86.8	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	6504.3	100.0
0°-180°	6504.3	100.0

Coefficient of Utilization



REPORT NUMBER: P1462438


CATALOG NUMBER: PRV-P-50-750-U-T2R

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	694.2	10.7			
FM	(30°-60°)	2611.0	40.1			
FH	(60°-80°)	1122.1	17.3			G1/1800
FVH	(80°-90°)	57.0	0.9			G1/100
BL	(0°-30°)	434.7	6.7	B1/500		
BM	(30°-60°)	1019.1	15.7	B2/2500		
BH	(60°-80°)	536.5	8.2	B2/1000		G2/1000
BVH	(80°-90°)	29.8	0.5			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B2-U0-G2

Type II Medium



REPORT NUMBER: P1462438

CATALOG NUMBER: PRV-P-50-750-U-T2R

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	82°	85°
0°	901	901	901	901	901	901	901	901	901	901	901
2.5°	960	959	960	965	955	950	940	927	917	910	908
5°	1056	1062	1059	1052	1036	1015	989	960	944	932	927
7.5°	1187	1178	1184	1163	1135	1099	1049	1014	977	957	951
10°	1329	1328	1316	1294	1252	1197	1136	1075	1026	992	979
12.5°	1482	1481	1475	1434	1381	1302	1229	1150	1073	1037	1022
15°	1633	1641	1630	1582	1514	1416	1324	1228	1141	1089	1070
17.5°	1795	1794	1773	1725	1647	1546	1432	1305	1204	1147	1123
20°	1944	1961	1935	1885	1788	1678	1545	1399	1277	1208	1182
22.5°	2138	2136	2112	2036	1934	1802	1656	1500	1359	1275	1243
25°	2341	2346	2313	2221	2080	1938	1770	1610	1454	1349	1315
27.5°	2556	2560	2518	2407	2260	2077	1902	1717	1539	1431	1381
30°	2737	2740	2699	2586	2417	2225	2013	1825	1626	1511	1459
32.5°	2889	2881	2837	2733	2575	2369	2142	1928	1729	1596	1538
35°	2963	2972	2940	2845	2699	2504	2282	2050	1824	1680	1622
37.5°	2962	2971	2960	2898	2777	2610	2400	2177	1943	1777	1706
40°	2892	2904	2910	2878	2798	2679	2495	2290	2051	1873	1797
42.5°	2760	2769	2788	2772	2759	2691	2569	2401	2161	1970	1883
45°	2587	2593	2612	2629	2652	2645	2601	2500	2287	2070	1969
47.5°	2344	2365	2411	2470	2511	2559	2590	2565	2404	2180	2068
50°	2050	2048	2132	2229	2351	2423	2523	2609	2536	2311	2186
52.5°	1619	1643	1749	1940	2142	2275	2418	2608	2661	2458	2322
55°	1199	1254	1386	1579	1863	2108	2288	2556	2776	2620	2473
57.5°	872	872	1013	1197	1542	1898	2166	2467	2862	2802	2651
60°	635	631	733	891	1167	1569	2044	2386	2936	2991	2844
62.5°	467	464	518	650	865	1223	1840	2348	2974	3166	3044
65°	365	368	399	480	650	881	1554	2347	2979	3326	3211
67.5°	296	300	318	373	496	637	1190	2278	2967	3368	3289
70°	250	251	268	307	376	479	837	2074	2904	3230	3171
72.5°	207	210	228	253	303	369	562	1699	2690	2841	2796
75°	170	168	182	213	246	288	396	1205	2284	2254	2200
77.5°	135	134	147	176	196	226	285	764	1679	1651	1608
80°	97	92	100	127	148	168	197	408	986	958	972
82.5°	56	56	59	80	95	109	126	217	472	487	470
85°	13	14	16	20	28	40	46	70	118	127	126
87.5°	1	1	1	2	2	2	2	3	4	4	4
90°	0	0	0	0	0	0	0	0	0	0	0

REPORT NUMBER: P1462438

CATALOG NUMBER: PRV-P-50-750-U-T2R

CANDELA DISTRIBUTION (continued):

	90°	95°	105°	115°	125°	135°	145°	155°	165°	175°	180°
0°	901	901	901	901	901	901	901	901	901	901	901
2.5°	904	903	894	889	890	886	881	881	878	875	874
5°	918	912	902	893	893	889	887	882	881	878	879
7.5°	937	928	914	905	905	902	902	898	897	893	891
10°	967	954	938	928	927	926	925	924	919	915	913
12.5°	1003	987	968	961	959	957	955	949	945	940	937
15°	1045	1029	1008	999	995	991	981	975	968	960	958
17.5°	1094	1071	1046	1036	1028	1019	1010	996	985	976	974
20°	1147	1119	1090	1075	1064	1048	1030	1012	999	988	986
22.5°	1199	1172	1137	1116	1094	1069	1041	1017	1001	990	988
25°	1260	1226	1182	1149	1117	1082	1044	1013	992	981	977
27.5°	1325	1282	1223	1181	1134	1081	1030	995	969	954	952
30°	1388	1338	1265	1199	1138	1069	1005	959	928	908	906
32.5°	1462	1397	1298	1216	1134	1049	969	913	877	857	857
35°	1534	1459	1334	1229	1123	1017	925	860	818	795	793
37.5°	1608	1517	1361	1230	1103	974	873	803	758	731	726
40°	1685	1577	1381	1221	1071	925	817	740	679	644	636
42.5°	1753	1629	1392	1209	1032	869	750	657	592	560	554
45°	1811	1655	1385	1185	982	806	664	568	513	481	474
47.5°	1882	1697	1380	1158	923	726	572	482	434	410	408
50°	1964	1739	1377	1123	852	632	481	402	364	345	343
52.5°	2050	1784	1379	1080	765	527	400	340	308	298	296
55°	2169	1845	1387	1024	666	435	337	292	274	269	269
57.5°	2296	1915	1402	957	564	354	288	266	263	264	265
60°	2454	2012	1424	885	463	296	260	255	258	267	269
62.5°	2606	2110	1462	802	372	255	245	246	250	262	263
65°	2747	2203	1485	704	306	232	234	234	244	261	262
67.5°	2808	2281	1454	588	251	214	218	222	231	244	246
70°	2749	2258	1295	449	209	196	199	203	214	227	233
72.5°	2466	2033	995	322	179	175	178	185	193	208	217
75°	2025	1652	700	219	154	152	160	165	161	164	169
77.5°	1475	1168	427	163	128	131	135	129	111	96	101
80°	920	687	247	121	99	97	95	86	63	43	19
82.5°	473	359	155	85	62	59	59	46	32	13	0
85°	113	102	61	35	23	22	15	6	2	0	0
87.5°	4	4	3	2	2	1	1	1	1	0	0
90°	0	0	0	0	0	0	0	0	0	0	0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP2-2501-321-5

Test Date: 04/10/2025

Luminaire Tested: GKO-PB1E-750-U-T4W

Data in this report applies to families of products including GKO-PB1E-750-U-T4W

Test Information

Test Method: LM-79-2019
 Report Number: SP2-2501-321-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP2 - 165CM SPHERE
 Measurement Geometry: 4π
 Issue Date: 04/10/2025
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GKO-PB1E-750-U-T4W**
 Description: Gekko Wedge Wall Pack Fixture 1 SQ w/ T4W distribution

Spectral Parameters

CCT (K):	5105	CRI (Ra):	72.2		
CIE u':	0.2079	R1:	68.8	R9:	-38.2
CIE v':	0.4868	R2:	78.3	R10:	48.2
Duv:	0.0035	R3:	84.9	R11:	68.1
CIE x:	0.3428	R4:	71.7	R12:	42.9
CIE y:	0.3567	R5:	69.8	R13:	70.6
CIE z:	0.3005	R6:	69.8	R14:	91.6
Peak Wavelength (nm):	451	R7:	81.2	R15:	61.7
Dominant Wavelength (nm):	567	R8:	53.5		
Purity:	9.884628				
Rf:	74.2				
Rg:	92.7				



Test Conditions

Stabilization Time: 30M
 Operation Time: 1H 30M
 Sphere Temperature (°C): 25.0

REPORT NUMBER: SP2-2501-321-5


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN2187	1/6/2025	7/6/2025
Power Meter	INXT2011002	1/21/2025	1/21/2026
AC Power Source	IN0458	10/22/2024	10/22/2025
DC Power Source	IN0212	10/22/2024	10/22/2025
Sphere Thermometer	IN4036B	10/22/2024	10/22/2025
Room Thermometer	IN0046	10/22/2024	10/22/2025

REPORT NUMBER: SP2-2501-321-5

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 5000K 4-step quadrangle

REPORT NUMBER: SP2-2501-321-5

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	134	NR	620	390	NR	750	10	NR	880	0	NR
365	0	NR	495	165	NR	625	354	NR	755	9	NR	885	0	NR
370	0	NR	500	218	NR	630	319	NR	760	8	NR	890	0	NR
375	0	NR	505	281	NR	635	285	NR	765	7	NR	895	0	NR
380	0	NR	510	343	NR	640	254	NR	770	6	NR	900	0	NR
385	1	NR	515	400	NR	645	224	NR	775	5	NR	905	0	NR
390	2	NR	520	444	NR	650	197	NR	780	4	NR	910	0	NR
395	4	NR	525	477	NR	655	173	NR	785	4	NR	915	0	NR
400	6	NR	530	501	NR	660	150	NR	790	3	NR	920	0	NR
405	9	NR	535	520	NR	665	131	NR	795	3	NR	925	0	NR
410	14	NR	540	534	NR	670	113	NR	800	2	NR	930	0	NR
415	26	NR	545	547	NR	675	98	NR	805	2	NR	935	0	NR
420	50	NR	550	561	NR	680	85	NR	810	2	NR	940	0	NR
425	95	NR	555	574	NR	685	73	NR	815	2	NR	945	0	NR
430	168	NR	560	586	NR	690	63	NR	820	1	NR	950	0	NR
435	284	NR	565	596	NR	695	54	NR	825	1	NR	955	0	NR
440	452	NR	570	604	NR	700	46	NR	830	1	NR	960	0	NR
445	705	NR	575	606	NR	705	40	NR	835	1	NR	965	0	NR
450	980	NR	580	603	NR	710	34	NR	840	1	NR	970	0	NR
455	869	NR	585	592	NR	715	29	NR	845	1	NR	975	0	NR
460	531	NR	590	577	NR	720	25	NR	850	1	NR	980	0	NR
465	372	NR	595	554	NR	725	22	NR	855	1	NR	985	0	NR
470	268	NR	600	527	NR	730	19	NR	860	1	NR	990	0	NR
475	174	NR	605	497	NR	735	16	NR	865	0	NR	995	0	NR
480	135	NR	610	462	NR	740	14	NR	870	0	NR	1000	0	NR
485	126	NR	615	428	NR	745	12	NR	875	0	NR			

REPORT NUMBER: SP2-2501-321-5

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.82

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	134	NR	620	390	NR	750	10	NR	880	0	NR
365	0	NR	495	165	NR	625	354	NR	755	9	NR	885	0	NR
370	0	NR	500	218	NR	630	319	NR	760	8	NR	890	0	NR
375	0	NR	505	281	NR	635	285	NR	765	7	NR	895	0	NR
380	0	NR	510	343	NR	640	254	NR	770	6	NR	900	0	NR
385	1	NR	515	400	NR	645	224	NR	775	5	NR	905	0	NR
390	2	NR	520	444	NR	650	197	NR	780	4	NR	910	0	NR
395	4	NR	525	477	NR	655	173	NR	785	4	NR	915	0	NR
400	6	NR	530	501	NR	660	150	NR	790	3	NR	920	0	NR
405	9	NR	535	520	NR	665	131	NR	795	3	NR	925	0	NR
410	14	NR	540	534	NR	670	113	NR	800	2	NR	930	0	NR
415	26	NR	545	547	NR	675	98	NR	805	2	NR	935	0	NR
420	50	NR	550	561	NR	680	85	NR	810	2	NR	940	0	NR
425	95	NR	555	574	NR	685	73	NR	815	2	NR	945	0	NR
430	168	NR	560	586	NR	690	63	NR	820	1	NR	950	0	NR
435	284	NR	565	596	NR	695	54	NR	825	1	NR	955	0	NR
440	452	NR	570	604	NR	700	46	NR	830	1	NR	960	0	NR
445	705	NR	575	606	NR	705	40	NR	835	1	NR	965	0	NR
450	980	NR	580	603	NR	710	34	NR	840	1	NR	970	0	NR
455	869	NR	585	592	NR	715	29	NR	845	1	NR	975	0	NR
460	531	NR	590	577	NR	720	25	NR	850	1	NR	980	0	NR
465	372	NR	595	554	NR	725	22	NR	855	1	NR	985	0	NR
470	268	NR	600	527	NR	730	19	NR	860	1	NR	990	0	NR
475	174	NR	605	497	NR	735	16	NR	865	0	NR	995	0	NR
480	135	NR	610	462	NR	740	14	NR	870	0	NR	1000	0	NR
485	126	NR	615	428	NR	745	12	NR	875	0	NR			

REPORT NUMBER: SP2-2501-321-5

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 3.75

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	134	NR	620	390	NR	750	10	NR	880	0	NR
365	0	NR	495	165	NR	625	354	NR	755	9	NR	885	0	NR
370	0	NR	500	218	NR	630	319	NR	760	8	NR	890	0	NR
375	0	NR	505	281	NR	635	285	NR	765	7	NR	895	0	NR
380	0	NR	510	343	NR	640	254	NR	770	6	NR	900	0	NR
385	1	NR	515	400	NR	645	224	NR	775	5	NR	905	0	NR
390	2	NR	520	444	NR	650	197	NR	780	4	NR	910	0	NR
395	4	NR	525	477	NR	655	173	NR	785	4	NR	915	0	NR
400	6	NR	530	501	NR	660	150	NR	790	3	NR	920	0	NR
405	9	NR	535	520	NR	665	131	NR	795	3	NR	925	0	NR
410	14	NR	540	534	NR	670	113	NR	800	2	NR	930	0	NR
415	26	NR	545	547	NR	675	98	NR	805	2	NR	935	0	NR
420	50	NR	550	561	NR	680	85	NR	810	2	NR	940	0	NR
425	95	NR	555	574	NR	685	73	NR	815	2	NR	945	0	NR
430	168	NR	560	586	NR	690	63	NR	820	1	NR	950	0	NR
435	284	NR	565	596	NR	695	54	NR	825	1	NR	955	0	NR
440	452	NR	570	604	NR	700	46	NR	830	1	NR	960	0	NR
445	705	NR	575	606	NR	705	40	NR	835	1	NR	965	0	NR
450	980	NR	580	603	NR	710	34	NR	840	1	NR	970	0	NR
455	869	NR	585	592	NR	715	29	NR	845	1	NR	975	0	NR
460	531	NR	590	577	NR	720	25	NR	850	1	NR	980	0	NR
465	372	NR	595	554	NR	725	22	NR	855	1	NR	985	0	NR
470	268	NR	600	527	NR	730	19	NR	860	1	NR	990	0	NR
475	174	NR	605	497	NR	735	16	NR	865	0	NR	995	0	NR
480	135	NR	610	462	NR	740	14	NR	870	0	NR	1000	0	NR
485	126	NR	615	428	NR	745	12	NR	875	0	NR			

REPORT NUMBER: SP2-2501-321-5

TM-30-18

Summary

$R_f = 74.2$
 $R_g = 92.7$
 $\text{CIE } R_a = 72.2$
 $R_g = -38.2$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 85	CES26 = 63	CES51 = 89	CES76 = 51
CES02 = 59	CES27 = 89	CES52 = 89	CES77 = 68
CES03 = 30	CES28 = 81	CES53 = 79	CES78 = 54
CES04 = 69	CES29 = 69	CES54 = 84	CES79 = 80
CES05 = 46	CES30 = 88	CES55 = 83	CES80 = 77
CES06 = 50	CES31 = 72	CES56 = 74	CES81 = 79
CES07 = 38	CES32 = 63	CES57 = 73	CES82 = 91
CES08 = 38	CES33 = 82	CES58 = 74	CES83 = 90
CES09 = 29	CES34 = 70	CES59 = 86	CES84 = 85
CES10 = 72	CES35 = 83	CES60 = 88	CES85 = 78
CES11 = 56	CES36 = 88	CES61 = 82	CES86 = 75
CES12 = 61	CES37 = 78	CES62 = 81	CES87 = 77
CES13 = 41	CES38 = 98	CES63 = 73	CES88 = 81
CES14 = 74	CES39 = 97	CES64 = 64	CES89 = 73
CES15 = 70	CES40 = 91	CES65 = 61	CES90 = 80
CES16 = 46	CES41 = 96	CES66 = 56	CES91 = 72
CES17 = 49	CES42 = 80	CES67 = 54	CES92 = 58
CES18 = 55	CES43 = 79	CES68 = 64	CES93 = 75
CES19 = 71	CES44 = 99	CES69 = 73	CES94 = 53
CES20 = 63	CES45 = 87	CES70 = 56	CES95 = 64
CES21 = 85	CES46 = 85	CES71 = 47	CES96 = 76
CES22 = 77	CES47 = 90	CES72 = 82	CES97 = 86
CES23 = 91	CES48 = 80	CES73 = 47	CES98 = 76
CES24 = 90	CES49 = 83	CES74 = 90	CES99 = 62
CES25 = 71	CES50 = 89	CES75 = 50	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)