Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: STREETWORKS

Report Number: P981381

Luminaire Tested: **FFX-CLB-80-730-U-PG-T5**

Issue Date: 04/15/2025

Report Generated By 670245763

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

**Test Information**

| | |
|---|---|
| Test Method: | LM-79-08 |
| Report Number: | P981381 |
| Test Lab: | INNOVATION CENTER(G3) |
| Issue Date: | 04/15/2025 |
| Manufacturer: | COOPER LIGHTING SOLUTIONS (FORMERLY EATON) |
| Product Line: | STREETWORKS |
| Catalog Number: | FFX-CLB-80-730-U-PG-T5 |
| Description: | FAIRFAX POST TOP FIXTURE w/ PRISMATIC GLOBE |
| Light Source: | (4) 3000K CCT, 70 CRI LEDS |
| Ballast/Driver: | ELECTRONIC DRIVER |

**Summary**

| | |
|---|---|
| Lumens per Lamp: | N/A |
| Luminaire Lumens: | 13056.2 lumens |
| Efficiency: | N/A |
| Efficacy: | 159.6 lumens/watt |
| Luminous Opening: | Vertical Cylinder (Dia: 1.58' x H: 1.5') |
| IES Classification: | Type V - Short |
| BUG Rating: | B3 - U5 - G5 |

| | |
|---|---|
| Input Watts (W): | 81.8 |
| Input Voltage (V): | 120 |
| Input Current (Ain): | NR |
| Voltage Rise (V): | NR |
| Power Factor: | 0.99 |
| Total Harmonic Distortion (THDi): | 6.01% |
| Frequency (hertz): | 60 |
| Stabilization Time: | NR |
| Operation Time: | NR |
| Ambient Temperature (°C): | NR |
| Test Distance: | 28.75 FT |




Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P981381
CATALOG NUMBER: FFX-CLB-80-730-U-PG-T5

## Iso-Footcandle Lines of Horizontal Illumination





Based on 15 foot mounting height. Maximum calculated value = 1.8 fc
Type V - Short - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P981381
CATALOG NUMBER: FFX-CLB-80-730-U-PG-T5

## Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report


REPORT NUMBER: P981381
CATALOG NUMBER: FFX-CLB-80-730-U-PG-T5

**FLUX DISTRIBUTION:**

| | | Downward | Upward | Total |
|---|---|---|---|---|
| **House Side** | Lumens | 3833.3 | 2694.8 | 6528.1 |
| | % Fixture | 29.4 | 20.6 | 50.0 |
| **Street Side** | Lumens | 3833.3 | 2694.8 | 6528.1 |
| | % Fixture | 29.4 | 20.6 | 50.0 |
| **Total** | Lumens | 7666.7 | 5389.5 | 13056.2 |
| | % Fixture | 58.7 | 41.3 | 100.0 |

**ZONAL LUMENS:**

| Zone | Lumens | % Fixture |
|---|---|---|
| 0°-10° | 8.2 | 0.1 |
| 10°-20° | 24.5 | 0.2 |
| 20°-30° | 115.7 | 0.9 |
| 30°-40° | 410.0 | 3.1 |
| 40°-50° | 842.4 | 6.5 |
| 50°-60° | 1281.8 | 9.8 |
| 60°-70° | 1585.9 | 12.1 |
| 70°-80° | 1692.8 | 13.0 |
| 80°-90° | 1705.4 | 13.1 |
| 90°-100° | 1588.0 | 12.2 |
| 100°-110° | 1427.7 | 10.9 |
| 110°-120° | 984.1 | 7.5 |
| 120°-130° | 679.2 | 5.2 |
| 130°-140° | 393.5 | 3.0 |
| 140°-150° | 187.2 | 1.4 |
| 150°-160° | 81.8 | 0.6 |
| 160°-170° | 36.6 | 0.3 |
| 170°-180° | 11.4 | 0.1 |
| 0°-90° | 7666.7 | 58.7 |
| 0°-180° | 13056.2 | 100.0 |



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269


Scaled Data Report

REPORT NUMBER: P981381
CATALOG NUMBER: FFX-CLB-80-730-U-PG-T5

## LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

| Zone | | Lumens | % Fixture | Zone Rating/Lumen Limit B | U | G |
|---|---|---|---|---|---|---|
| FL | (0°-30°) | 74.2 | 0.6 | | | |
| FM | (30°-60°) | 1267.1 | 9.7 | | | |
| FH | (60°-80°) | 1639.3 | 12.6 | | | G1/1800 |
| FVH | (80°-90°) | 852.7 | 6.5 | | | G5 |
| BL | (0°-30°) | 74.2 | 0.6 | B0/110 | | |
| BM | (30°-60°) | 1267.1 | 9.7 | B2/2500 | | |
| BH | (60°-80°) | 1639.3 | 12.6 | B3/2500 | | G1/1800 |
| BVH | (80°-90°) | 852.7 | 6.5 | | | G5 |
| UL | (90°-100°) | 1588.0 | 12.2 | | U5 | |
| UH | (100°-180°) | 3801.5 | 29.1 | | U5 | |

**BUG Rating: B3-U5-G5**
Type V Short



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P981381
CATALOG NUMBER: FFX-CLB-80-730-U-PG-T5

**CANDELA DISTRIBUTION (FULL):**

| | 0° |
|---|---|
| 0° | 99.4 |
| 2.5° | 97.8 |
| 5° | 90.4 |
| 7.5° | 80.6 |
| 10° | 79.8 |
| 12.5° | 77.4 |
| 15° | 78.2 |
| 17.5° | 88.0 |
| 20° | 114.0 |
| 22.5° | 162.1 |
| 25° | 228.1 |
| 27.5° | 311.2 |
| 30° | 413.0 |
| 32.5° | 523.8 |
| 35° | 642.7 |
| 37.5° | 761.6 |
| 40° | 878.9 |
| 42.5° | 988.1 |
| 45° | 1086.7 |
| 47.5° | 1178.7 |
| 50° | 1273.2 |
| 52.5° | 1358.7 |
| 55° | 1434.5 |
| 57.5° | 1499.7 |
| 60° | 1549.4 |
| 62.5° | 1581.1 |
| 65° | 1603.1 |
| 67.5° | 1619.4 |
| 70° | 1621.0 |
| 72.5° | 1612.1 |
| 75° | 1600.7 |
| 77.5° | 1589.3 |
| 80° | 1577.1 |
| 82.5° | 1563.2 |
| 85° | 1551.0 |
| 87.5° | 1568.9 |
| 90° | 1561.6 |
| 92.5° | 1550.2 |
| 95° | 1490.7 |
| 97.5° | 1343.3 |
| 100° | 1310.7 |
| 102.5° | 1442.6 |
| 105° | 1442.6 |
| 107.5° | 1274.8 |
| 110° | 1158.4 |

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P981381
CATALOG NUMBER: FFX-CLB-80-730-U-PG-T5

**CANDELA DISTRIBUTION (continued):**

| | 0° |
|---|---|
| 112.5° | *1050.8* |
| 115° | *975.1* |
| 117.5° | *919.7* |
| 120° | *867.5* |
| 122.5° | *814.6* |
| 125° | *756.8* |
| 127.5° | *697.3* |
| 130° | *633.8* |
| 132.5° | *565.3* |
| 135° | *501.0* |
| 137.5° | *442.3* |
| 140° | *386.9* |
| 142.5° | *335.6* |
| 145° | *290.0* |
| 147.5° | *250.9* |
| 150° | *218.3* |
| 152.5° | *192.2* |
| 155° | *171.1* |
| 157.5° | *154.8* |
| 160° | *141.7* |
| 162.5° | *132.0* |
| 165° | *126.3* |
| 167.5° | *122.2* |
| 170° | *120.6* |
| 172.5° | *119.7* |
| 175° | *118.9* |
| 177.5° | *118.9* |
| 180° | *118.9* |

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

# LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Streetworks

Report Number: SP1-2501-332-4

Test Date: 03/21/2025

Luminaire Tested: FFX-CLB-100-730-U-FR-T5

Data in this report applies to families of products including FFX-CLB-100-730-U-FR-T5

Report Generated By FNC07603 / LDUCLS01DT446
Version: v7.04


## Test Information

| | |
|---|---|
| Test Method: | LM-79-2019 |
| Report Number: | SP1-2501-332-4 |
| Test Lab: | COOPER LIGHTING SOLUTIONS |
| Photometer: | SP1 - 76IN SPHERE |
| Measurement Geometry: | 4π |
| Issue Date: | 03/31/2025 |
| Manufacturer: | COOPER LIGHTING SOLUTIONS |
| Product Line: | Streetworks |
| Catalog Number: | **FFX-CLB-100-730-U-FR-T5** |
| Description: | FAIRFAX ACORN W/ FAIRFAX REFRACTOR 100W T5 |

## Spectral Parameters

| | | | | | |
|---|---|---|---|---|---|
| CCT (K): | 3061 | CRI (Ra): | 71.7 | | |
| CIE u': | 0.2489 | R1: | 67.8 | R9: | -40.3 |
| CIE v': | 0.5187 | R2: | 85.0 | R10: | 67.2 |
| Duv: | -0.0011 | R3: | 92.9 | R11: | 61.6 |
| CIE x: | 0.4312 | R4: | 66.0 | R12: | 59.9 |
| CIE y: | 0.3995 | R5: | 68.5 | R13: | 71.4 |
| CIE z: | 0.1693 | R6: | 80.2 | R14: | 96.3 |
| Peak Wavelength (nm): | 592 | R7: | 74.5 | R15: | 58.8 |
| Dominant Wavelength (nm): | 582 | R8: | 39.0 | | |
| Purity: | 49.32381 | | | | |

| | |
|---|---|
| Rf: | 76.8 |
| Rg: | 92.2 |




## Test Conditions


| | |
|---|---|
| Stabilization Time: | 56M |
| Operation Time: | 1H 56M |
| Sphere Temperature (°C): | 24.8 |

REPORT NUMBER: SP1-2501-332-4


| Measurement and Test Equipment | | | |
|---|---|---|---|
| Instrument | Identification Number | Calibration Date | Calibration Due Date |
| Photometer | IN0058 | 12/16/2024 | 6/16/2025 |
| Power Meter | INXT2011004 | 1/21/2025 | 1/21/2026 |
| AC Power Source | IN0063 | 10/22/2024 | 10/22/2025 |
| DC Power Source | IN0208 | 10/22/2024 | 10/22/2025 |
| Sphere Thermometer | IN0085 | 10/22/2024 | 10/22/2025 |
| Room Thermometer | IN0046 | 10/22/2024 | 10/22/2025 |

REPORT NUMBER: SP1-2501-332-4

## CIE 1931 Chromaticity Diagram




## CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles





CCT = 3061K
CIE x = 0.4312
CIE y = 0.3995
Duv = -0.0011

Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2501-332-4

## Photopic Flux vs. Wavelength





## Photopic Lumens: NR

| λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 360 | 0 | NR | 490 | 207 | NR | 620 | 786 | NR | 750 | 18 | NR | 880 | 0 | NR |
| 365 | 0 | NR | 495 | 241 | NR | 625 | 718 | NR | 755 | 15 | NR | 885 | 0 | NR |
| 370 | 0 | NR | 500 | 277 | NR | 630 | 654 | NR | 760 | 13 | NR | 890 | 0 | NR |
| 375 | 0 | NR | 505 | 309 | NR | 635 | 588 | NR | 765 | 11 | NR | 895 | 0 | NR |
| 380 | 0 | NR | 510 | 333 | NR | 640 | 523 | NR | 770 | 10 | NR | 900 | 0 | NR |
| 385 | 0 | NR | 515 | 356 | NR | 645 | 465 | NR | 775 | 8 | NR | 905 | 0 | NR |
| 390 | 0 | NR | 520 | 376 | NR | 650 | 407 | NR | 780 | 7 | NR | 910 | 0 | NR |
| 395 | 2 | NR | 525 | 398 | NR | 655 | 356 | NR | 785 | 6 | NR | 915 | 0 | NR |
| 400 | 4 | NR | 530 | 422 | NR | 660 | 308 | NR | 790 | 5 | NR | 920 | 0 | NR |
| 405 | 6 | NR | 535 | 450 | NR | 665 | 267 | NR | 795 | 5 | NR | 925 | 0 | NR |
| 410 | 12 | NR | 540 | 486 | NR | 670 | 229 | NR | 800 | 4 | NR | 930 | 0 | NR |
| 415 | 22 | NR | 545 | 530 | NR | 675 | 197 | NR | 805 | 3 | NR | 935 | 0 | NR |
| 420 | 39 | NR | 550 | 577 | NR | 680 | 169 | NR | 810 | 3 | NR | 940 | 0 | NR |
| 425 | 68 | NR | 555 | 633 | NR | 685 | 145 | NR | 815 | 3 | NR | 945 | 0 | NR |
| 430 | 111 | NR | 560 | 700 | NR | 690 | 123 | NR | 820 | 2 | NR | 950 | 0 | NR |
| 435 | 175 | NR | 565 | 766 | NR | 695 | 105 | NR | 825 | 2 | NR | 955 | 0 | NR |
| 440 | 269 | NR | 570 | 832 | NR | 700 | 89 | NR | 830 | 2 | NR | 960 | 0 | NR |
| 445 | 434 | NR | 575 | 893 | NR | 705 | 76 | NR | 835 | 2 | NR | 965 | 0 | NR |
| 450 | 579 | NR | 580 | 945 | NR | 710 | 64 | NR | 840 | 1 | NR | 970 | 0 | NR |
| 455 | 468 | NR | 585 | 979 | NR | 715 | 55 | NR | 845 | 1 | NR | 975 | 0 | NR |
| 460 | 320 | NR | 590 | 996 | NR | 720 | 47 | NR | 850 | 1 | NR | 980 | 0 | NR |
| 465 | 264 | NR | 595 | 998 | NR | 725 | 40 | NR | 855 | 1 | NR | 985 | 0 | NR |
| 470 | 204 | NR | 600 | 981 | NR | 730 | 33 | NR | 860 | 1 | NR | 990 | 0 | NR |
| 475 | 164 | NR | 605 | 949 | NR | 735 | 28 | NR | 865 | 1 | NR | 995 | 0 | NR |
| 480 | 166 | NR | 610 | 903 | NR | 740 | 24 | NR | 870 | 1 | NR | 1000 | 0 | NR |
| 485 | 183 | NR | 615 | 847 | NR | 745 | 21 | NR | 875 | 1 | NR | | | |

REPORT NUMBER: SP1-2501-332-4

## Scotopic Flux vs. Wavelength





**Scotopic Lumens: NR** **S/P: 1.29**

| λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 360 | 0 | NR | 490 | 207 | NR | 620 | 786 | NR | 750 | 18 | NR | 880 | 0 | NR |
| 365 | 0 | NR | 495 | 241 | NR | 625 | 718 | NR | 755 | 15 | NR | 885 | 0 | NR |
| 370 | 0 | NR | 500 | 277 | NR | 630 | 654 | NR | 760 | 13 | NR | 890 | 0 | NR |
| 375 | 0 | NR | 505 | 309 | NR | 635 | 588 | NR | 765 | 11 | NR | 895 | 0 | NR |
| 380 | 0 | NR | 510 | 333 | NR | 640 | 523 | NR | 770 | 10 | NR | 900 | 0 | NR |
| 385 | 0 | NR | 515 | 356 | NR | 645 | 465 | NR | 775 | 8 | NR | 905 | 0 | NR |
| 390 | 0 | NR | 520 | 376 | NR | 650 | 407 | NR | 780 | 7 | NR | 910 | 0 | NR |
| 395 | 2 | NR | 525 | 398 | NR | 655 | 356 | NR | 785 | 6 | NR | 915 | 0 | NR |
| 400 | 4 | NR | 530 | 422 | NR | 660 | 308 | NR | 790 | 5 | NR | 920 | 0 | NR |
| 405 | 6 | NR | 535 | 450 | NR | 665 | 267 | NR | 795 | 5 | NR | 925 | 0 | NR |
| 410 | 12 | NR | 540 | 486 | NR | 670 | 229 | NR | 800 | 4 | NR | 930 | 0 | NR |
| 415 | 22 | NR | 545 | 530 | NR | 675 | 197 | NR | 805 | 3 | NR | 935 | 0 | NR |
| 420 | 39 | NR | 550 | 577 | NR | 680 | 169 | NR | 810 | 3 | NR | 940 | 0 | NR |
| 425 | 68 | NR | 555 | 633 | NR | 685 | 145 | NR | 815 | 3 | NR | 945 | 0 | NR |
| 430 | 111 | NR | 560 | 700 | NR | 690 | 123 | NR | 820 | 2 | NR | 950 | 0 | NR |
| 435 | 175 | NR | 565 | 766 | NR | 695 | 105 | NR | 825 | 2 | NR | 955 | 0 | NR |
| 440 | 269 | NR | 570 | 832 | NR | 700 | 89 | NR | 830 | 2 | NR | 960 | 0 | NR |
| 445 | 434 | NR | 575 | 893 | NR | 705 | 76 | NR | 835 | 2 | NR | 965 | 0 | NR |
| 450 | 579 | NR | 580 | 945 | NR | 710 | 64 | NR | 840 | 1 | NR | 970 | 0 | NR |
| 455 | 468 | NR | 585 | 979 | NR | 715 | 55 | NR | 845 | 1 | NR | 975 | 0 | NR |
| 460 | 320 | NR | 590 | 996 | NR | 720 | 47 | NR | 850 | 1 | NR | 980 | 0 | NR |
| 465 | 264 | NR | 595 | 998 | NR | 725 | 40 | NR | 855 | 1 | NR | 985 | 0 | NR |
| 470 | 204 | NR | 600 | 981 | NR | 730 | 33 | NR | 860 | 1 | NR | 990 | 0 | NR |
| 475 | 164 | NR | 605 | 949 | NR | 735 | 28 | NR | 865 | 1 | NR | 995 | 0 | NR |
| 480 | 166 | NR | 610 | 903 | NR | 740 | 24 | NR | 870 | 1 | NR | 1000 | 0 | NR |
| 485 | 183 | NR | 615 | 847 | NR | 745 | 21 | NR | 875 | 1 | NR | | | |

REPORT NUMBER: SP1-2501-332-4

## Melanopic Flux vs. Wavelength




**Melanopic Lumens: NR** **M/P: 2.47**

| λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) | λ (nm) | Power W^/nm | Lumens (ϕ/nm) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 360 | 0 | NR | 490 | 207 | NR | 620 | 786 | NR | 750 | 18 | NR | 880 | 0 | NR |
| 365 | 0 | NR | 495 | 241 | NR | 625 | 718 | NR | 755 | 15 | NR | 885 | 0 | NR |
| 370 | 0 | NR | 500 | 277 | NR | 630 | 654 | NR | 760 | 13 | NR | 890 | 0 | NR |
| 375 | 0 | NR | 505 | 309 | NR | 635 | 588 | NR | 765 | 11 | NR | 895 | 0 | NR |
| 380 | 0 | NR | 510 | 333 | NR | 640 | 523 | NR | 770 | 10 | NR | 900 | 0 | NR |
| 385 | 0 | NR | 515 | 356 | NR | 645 | 465 | NR | 775 | 8 | NR | 905 | 0 | NR |
| 390 | 0 | NR | 520 | 376 | NR | 650 | 407 | NR | 780 | 7 | NR | 910 | 0 | NR |
| 395 | 2 | NR | 525 | 398 | NR | 655 | 356 | NR | 785 | 6 | NR | 915 | 0 | NR |
| 400 | 4 | NR | 530 | 422 | NR | 660 | 308 | NR | 790 | 5 | NR | 920 | 0 | NR |
| 405 | 6 | NR | 535 | 450 | NR | 665 | 267 | NR | 795 | 5 | NR | 925 | 0 | NR |
| 410 | 12 | NR | 540 | 486 | NR | 670 | 229 | NR | 800 | 4 | NR | 930 | 0 | NR |
| 415 | 22 | NR | 545 | 530 | NR | 675 | 197 | NR | 805 | 3 | NR | 935 | 0 | NR |
| 420 | 39 | NR | 550 | 577 | NR | 680 | 169 | NR | 810 | 3 | NR | 940 | 0 | NR |
| 425 | 68 | NR | 555 | 633 | NR | 685 | 145 | NR | 815 | 3 | NR | 945 | 0 | NR |
| 430 | 111 | NR | 560 | 700 | NR | 690 | 123 | NR | 820 | 2 | NR | 950 | 0 | NR |
| 435 | 175 | NR | 565 | 766 | NR | 695 | 105 | NR | 825 | 2 | NR | 955 | 0 | NR |
| 440 | 269 | NR | 570 | 832 | NR | 700 | 89 | NR | 830 | 2 | NR | 960 | 0 | NR |
| 445 | 434 | NR | 575 | 893 | NR | 705 | 76 | NR | 835 | 2 | NR | 965 | 0 | NR |
| 450 | 579 | NR | 580 | 945 | NR | 710 | 64 | NR | 840 | 1 | NR | 970 | 0 | NR |
| 455 | 468 | NR | 585 | 979 | NR | 715 | 55 | NR | 845 | 1 | NR | 975 | 0 | NR |
| 460 | 320 | NR | 590 | 996 | NR | 720 | 47 | NR | 850 | 1 | NR | 980 | 0 | NR |
| 465 | 264 | NR | 595 | 998 | NR | 725 | 40 | NR | 855 | 1 | NR | 985 | 0 | NR |
| 470 | 204 | NR | 600 | 981 | NR | 730 | 33 | NR | 860 | 1 | NR | 990 | 0 | NR |
| 475 | 164 | NR | 605 | 949 | NR | 735 | 28 | NR | 865 | 1 | NR | 995 | 0 | NR |
| 480 | 166 | NR | 610 | 903 | NR | 740 | 24 | NR | 870 | 1 | NR | 1000 | 0 | NR |
| 485 | 183 | NR | 615 | 847 | NR | 745 | 21 | NR | 875 | 1 | NR | | | |


REPORT NUMBER: SP1-2501-332-4

# TM-30-18


## Summary


$R_f$ = 76.8
$R_g$ = 92.2
CIE $R_a$ = 71.7
$R_9$ = -40.3


## Spectral Power Distribution Comparison





## Color Vector Graphics







REPORT NUMBER: SP1-2501-332-4

## TM-30-18

**Individual Sample Fidelity Index ($R_{f,i}$)**


| | | | |
|---|---|---|---|
| CES01 = 86 | CES26 = 71 | CES51 = 88 | CES76 = 68 |
| CES02 = 62 | CES27 = 92 | CES52 = 85 | CES77 = 80 |
| CES03 = 31 | CES28 = 90 | CES53 = 79 | CES78 = 70 |
| CES04 = 71 | CES29 = 75 | CES54 = 86 | CES79 = 88 |
| CES05 = 49 | CES30 = 87 | CES55 = 84 | CES80 = 87 |
| CES06 = 51 | CES31 = 79 | CES56 = 76 | CES81 = 69 |
| CES07 = 41 | CES32 = 72 | CES57 = 76 | CES82 = 94 |
| CES08 = 40 | CES33 = 84 | CES58 = 77 | CES83 = 92 |
| CES09 = 29 | CES34 = 83 | CES59 = 84 | CES84 = 88 |
| CES10 = 76 | CES35 = 91 | CES60 = 90 | CES85 = 73 |
| CES11 = 59 | CES36 = 92 | CES61 = 81 | CES86 = 60 |
| CES12 = 65 | CES37 = 91 | CES62 = 91 | CES87 = 77 |
| CES13 = 43 | CES38 = 97 | CES63 = 81 | CES88 = 79 |
| CES14 = 74 | CES39 = 98 | CES64 = 69 | CES89 = 66 |
| CES15 = 71 | CES40 = 94 | CES65 = 69 | CES90 = 80 |
| CES16 = 47 | CES41 = 95 | CES66 = 67 | CES91 = 79 |
| CES17 = 50 | CES42 = 92 | CES67 = 65 | CES92 = 53 |
| CES18 = 56 | CES43 = 83 | CES68 = 70 | CES93 = 71 |
| CES19 = 73 | CES44 = 99 | CES69 = 78 | CES94 = 47 |
| CES20 = 66 | CES45 = 87 | CES70 = 66 | CES95 = 65 |
| CES21 = 87 | CES46 = 83 | CES71 = 66 | CES96 = 76 |
| CES22 = 79 | CES47 = 91 | CES72 = 87 | CES97 = 81 |
| CES23 = 92 | CES48 = 75 | CES73 = 60 | CES98 = 76 |
| CES24 = 91 | CES49 = 83 | CES74 = 94 | CES99 = 63 |
| CES25 = 73 | CES50 = 87 | CES75 = 70 | |





REPORT NUMBER: SP1-2501-332-4

# TM-30-18

## Color Rendition by Hue-Angle Bin











REPORT NUMBER: SP1-2501-332-4

# TM-30-18

## Measure Comparisons




(END OF REPORT)