Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: STREETWORKS

Report Number: P981258

Luminaire Tested: **FFX-CLB-50-740-U-VM8-T5**

Issue Date: 04/15/2025

Report Generated By 670245763

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

Test Information

Test Method:	LM-79-08
Report Number:	P981258
Test Lab:	INNOVATION CENTER(G3)
Issue Date:	04/15/2025
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	STREETWORKS
Catalog Number:	FFX-CLB-50-740-U-VM8-T5
Description:	FAIRFAX POST TOP FIXTURE w/ ULA ACORN 8 INCH NECK
Light Source:	(6) 4000K CCT, 70 CRI LEDS
Ballast/Driver:	ELECTRONIC DRIVER

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	8677.9 lumens
Efficiency:	N/A
Efficacy:	171.5 lumens/watt
Luminous Opening:	Vertical Cylinder (Dia: 1.33' x H: 2.08')
IES Classification:	Type V - Short
BUG Rating:	B2 - U5 - G4

Input Watts (W):	50.6
Input Voltage (V):	120
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	0.99
Total Harmonic Distortion (THDi):	6.12%
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	28.75 FT




Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P981258
CATALOG NUMBER: FFX-CLB-50-740-U-VM8-T5

Iso-Footcandle Lines of Horizontal Illumination




Based on 15 foot mounting height. Maximum calculated value = 1.5 fc
Type V - Short - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P981258
CATALOG NUMBER: FFX-CLB-50-740-U-VM8-T5

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report


REPORT NUMBER: P981258
CATALOG NUMBER: FFX-CLB-50-740-U-VM8-T5

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	2482.4	1856.5	4338.9
	% Fixture	28.6	21.4	50.0
Street Side	Lumens	2482.4	1856.5	4338.9
	% Fixture	28.6	21.4	50.0
Total	Lumens	4964.8	3713.0	8677.9
	% Fixture	57.2	42.8	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	11.6	0.1
10°-20°	70.6	0.8
20°-30°	191.1	2.2
30°-40°	377.2	4.3
40°-50°	594.3	6.8
50°-60°	787.5	9.1
60°-70°	925.9	10.7
70°-80°	1000.3	11.5
80°-90°	1006.5	11.6
90°-100°	947.7	10.9
100°-110°	837.6	9.7
110°-120°	690.5	8.0
120°-130°	516.2	5.9
130°-140°	344.6	4.0
140°-150°	204.7	2.4
150°-160°	107.8	1.2
160°-170°	49.7	0.6
170°-180°	14.2	0.2
0°-90°	4964.8	57.2
0°-180°	8677.9	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269


Scaled Data Report

REPORT NUMBER: P981258
CATALOG NUMBER: FFX-CLB-50-740-U-VM8-T5

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	136.6	1.6			
FM	(30°-60°)	879.5	10.1			
FH	(60°-80°)	963.1	11.1			G1/1800
FVH	(80°-90°)	503.2	5.8			G4/750
BL	(0°-30°)	136.6	1.6	B1/500		
BM	(30°-60°)	879.5	10.1	B1/1000		
BH	(60°-80°)	963.1	11.1	B2/1000		G1/1800
BVH	(80°-90°)	503.2	5.8			G4/750
UL	(90°-100°)	947.7	10.9		U4/1000	
UH	(100°-180°)	2765.4	31.9		U5	

BUG Rating: B2-U5-G4
Type V Short



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P981258
CATALOG NUMBER: FFX-CLB-50-740-U-VM8-T5

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	90.2	90.2	90.2	*90.2*	90.2	90.2	90.2	90.2	90.2	90.2	90.2
2.5°	84.7	84.7	85.3	*85.8*	86.4	86.9	87.4	88.0	88.5	88.0	88.0
5°	97.8	98.8	98.8	*98.8*	98.3	98.8	99.9	99.9	101.0	100.5	99.9
7.5°	125.5	128.2	128.2	*127.6*	127.1	127.6	127.1	127.1	127.1	126.5	127.6
10°	163.5	162.4	162.9	*162.4*	161.3	161.8	162.4	161.3	161.3	161.3	161.3
12.5°	200.4	199.9	201.5	*200.9*	201.5	199.9	200.9	199.9	199.9	198.2	198.8
15°	243.8	243.8	243.3	*241.7*	242.2	240.0	241.1	240.6	239.0	239.0	238.4
17.5°	284.0	283.5	284.0	*281.9*	281.9	281.3	280.2	279.7	279.7	278.1	277.5
20°	324.2	323.1	322.6	*322.6*	321.0	321.0	319.9	317.7	316.6	317.2	316.1
22.5°	367.7	365.5	365.5	*365.5*	362.2	361.2	360.6	358.4	358.4	356.8	356.8
25°	411.1	411.7	411.7	*409.5*	407.9	405.7	404.6	403.0	401.3	400.8	401.3
27.5°	458.9	460.0	458.4	*454.6*	454.0	451.8	449.1	447.0	447.5	444.8	447.0
30°	511.0	508.9	505.6	*504.5*	502.4	500.2	498.0	493.7	494.2	493.1	493.7
32.5°	558.8	558.8	557.7	*554.5*	552.9	548.0	545.8	540.4	540.9	540.4	538.2
35°	611.0	609.3	607.2	*606.6*	601.2	597.9	594.1	588.2	589.2	588.7	589.2
37.5°	655.0	655.5	656.6	*653.9*	649.0	644.6	640.3	636.0	634.9	635.4	634.3
40°	702.8	702.2	701.1	*697.9*	694.1	689.2	683.7	681.0	677.8	679.9	679.4
42.5°	741.9	743.5	742.9	*739.7*	734.8	729.9	725.6	721.2	719.6	719.0	719.0
45°	779.9	780.4	778.8	*778.2*	771.7	767.4	761.9	758.1	757.1	757.1	758.7
47.5°	815.2	814.6	813.5	*812.5*	807.6	801.0	794.5	791.8	791.3	792.4	792.9
50°	843.4	844.5	844.0	*842.3*	837.4	831.5	824.4	821.7	822.2	823.3	823.9
52.5°	868.9	868.9	869.5	*867.3*	863.0	856.4	849.9	847.8	847.8	849.4	848.3
55°	888.5	889.6	890.1	*888.5*	885.8	878.2	871.7	867.8	869.5	871.1	871.7
57.5°	907.0	908.0	908.0	*908.0*	903.7	896.6	890.1	886.9	889.0	891.7	892.3
60°	921.6	922.2	923.8	*923.8*	920.0	911.8	904.8	902.1	904.8	908.6	908.0
62.5°	932.5	932.5	934.6	*935.2*	931.4	923.2	916.2	914.0	917.3	921.6	923.2
65°	941.7	942.3	943.9	*944.4*	941.2	931.9	924.3	923.8	928.1	932.5	933.0
67.5°	946.6	947.1	949.9	*950.9*	947.1	937.9	930.8	929.2	935.2	940.6	941.2
70°	949.9	950.9	954.2	*955.3*	951.5	941.7	934.1	933.6	940.1	946.1	946.6
72.5°	*952.0*	*952.6*	*955.8*	*956.9*	*953.1*	*943.9*	*936.3*	*936.3*	*942.3*	*949.3*	*950.4*
75°	952.0	952.6	955.3	*956.9*	953.1	943.3	935.2	935.2	943.3	950.4	952.0
77.5°	947.7	949.3	952.6	*954.2*	950.4	940.6	933.0	933.0	941.2	948.8	950.4
80°	943.3	943.9	947.7	*949.9*	945.5	936.3	928.1	928.1	936.8	945.0	946.1
82.5°	936.3	936.8	940.6	*942.8*	939.0	929.2	921.1	921.6	929.8	937.9	939.0
85°	926.5	927.6	931.4	*933.0*	929.8	919.4	911.8	912.4	921.1	928.7	929.8
87.5°	916.2	916.2	920.5	*922.2*	918.9	908.6	901.0	901.0	909.7	917.8	918.4
90°	902.1	903.1	907.0	*909.7*	905.3	896.6	888.5	888.5	896.6	904.2	906.4
92.5°	889.0	889.6	893.4	*895.0*	891.2	882.0	874.9	874.9	883.1	890.7	891.7
95°	873.3	873.3	876.0	*878.2*	873.8	866.2	859.7	859.7	866.2	872.7	873.8
97.5°	856.4	856.4	859.7	*859.2*	855.9	847.8	842.3	841.8	848.3	853.7	855.4
100°	837.4	838.5	840.7	*840.2*	837.4	829.3	824.4	824.4	829.3	834.2	835.3
102.5°	819.0	819.0	820.1	*819.5*	815.7	808.7	805.9	805.4	809.7	813.0	813.5
105°	800.0	800.0	798.9	*798.9*	794.0	788.6	785.3	785.3	789.1	791.3	791.3
107.5°	778.2	777.2	778.2	*776.6*	771.7	766.3	764.7	764.1	765.7	767.9	766.8
110°	756.0	755.4	754.9	*751.6*	747.8	744.6	741.9	741.9	743.5	744.0	744.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P981258
CATALOG NUMBER: FFX-CLB-50-740-U-VM8-T5

CANDELA DISTRIBUTION (continued):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
112.5°	732.6	732.1	730.4	*727.7*	723.4	720.1	718.0	718.0	718.5	718.0	716.9
115°	707.1	706.0	704.4	*699.5*	695.1	693.0	691.9	693.0	692.4	690.8	690.8
117.5°	679.4	678.3	675.6	*670.2*	666.4	664.7	665.3	664.7	663.6	662.0	662.6
120°	648.4	648.4	644.1	*639.8*	636.5	636.5	636.0	636.0	634.3	632.2	631.1
122.5°	616.4	616.4	612.6	*608.8*	605.0	605.0	605.5	605.0	603.9	601.7	600.7
125°	585.4	582.7	579.5	*575.1*	572.4	571.9	573.5	574.0	571.9	569.2	569.7
127.5°	551.2	549.6	546.3	*541.5*	539.3	538.7	540.4	541.5	538.7	537.1	536.6
130°	515.4	514.3	511.6	*507.8*	505.6	506.2	507.8	509.4	506.7	505.1	504.0
132.5°	480.1	480.1	478.5	*474.7*	471.9	474.1	475.2	476.3	473.6	473.0	472.5
135°	448.0	447.5	444.2	*442.1*	439.9	440.4	442.6	442.1	441.5	440.4	439.4
137.5°	414.9	414.9	413.3	*409.5*	409.5	410.0	411.1	411.1	411.7	409.5	410.0
140°	384.0	383.4	382.3	*379.6*	378.0	379.1	380.2	380.7	380.7	378.5	379.1
142.5°	354.6	354.1	350.8	*349.2*	349.2	349.7	350.3	350.8	350.8	349.7	350.3
145°	323.1	324.2	322.6	*321.0*	321.0	321.0	322.6	323.1	323.7	322.6	322.6
147.5°	297.1	298.2	296.5	*295.4*	295.4	295.4	296.5	297.1	296.0	296.5	296.5
150°	272.6	272.6	271.5	*271.0*	270.5	271.0	272.1	272.6	272.6	271.5	271.5
152.5°	249.3	248.7	248.2	*248.2*	248.2	248.2	249.3	249.3	249.8	249.8	248.7
155°	229.2	228.6	228.6	*228.1*	228.6	228.6	228.6	229.2	229.2	229.7	230.3
157.5°	210.7	210.2	210.7	*210.7*	210.7	211.3	211.3	211.8	210.7	211.3	211.8
160°	195.5	196.1	195.5	*195.0*	195.0	195.5	195.5	196.1	196.1	195.5	196.1
162.5°	182.5	182.5	181.9	*182.5*	183.0	182.5	182.5	183.0	183.0	183.0	183.0
165°	172.2	171.6	171.6	*171.6*	171.6	171.6	172.2	172.2	172.2	172.2	172.7
167.5°	162.9	162.4	162.4	*162.4*	162.9	162.9	162.9	163.5	163.5	163.5	162.9
170°	155.9	155.3	155.3	*155.3*	155.9	155.9	155.9	155.9	155.9	155.9	155.9
172.5°	149.9	149.9	149.9	*149.9*	149.9	149.9	149.9	149.9	149.9	150.4	149.9
175°	146.1	146.1	146.1	*146.1*	145.5	145.5	146.1	146.1	146.1	146.1	146.1
177.5°	142.8	142.8	143.4	*142.8*	142.8	142.8	143.4	143.4	143.4	142.8	142.8
180°	141.7	141.7	141.7	*141.7*	141.7	141.7	141.7	141.7	141.7	141.7	141.7

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Streetworks

Report Number: SP1-2501-332-1

Test Date: 03/20/2025

Luminaire Tested: FFX-CLB-100-740-U-FR-T5

Data in this report applies to families of products including FFX-CLB-100-740-U-FR-T5

Report Generated By FNC07603 / LDUCLS01DT446
Version: v7.04


Test Information

Test Method:	LM-79-2019
Report Number:	SP1-2501-332-1
Test Lab:	COOPER LIGHTING SOLUTIONS
Photometer:	SP1 - 76IN SPHERE
Measurement Geometry:	4π
Issue Date:	03/31/2025
Manufacturer:	COOPER LIGHTING SOLUTIONS
Product Line:	Streetworks
Catalog Number:	**FFX-CLB-100-740-U-FR-T5**
Description:	FAIRFAX ACORN W/ FAIRFAX REFRACTOR 100W T5

Spectral Parameters

CCT (K):	3990	CRI (Ra):	73.9		
CIE u':	0.2247	R1:	69.6	R9:	-36.4
CIE v':	0.5031	R2:	83.0	R10:	60.9
Duv:	0.0011	R3:	93.1	R11:	66.8
CIE x:	0.3816	R4:	70.6	R12:	52.5
CIE y:	0.3798	R5:	70.6	R13:	72.5
CIE z:	0.2386	R6:	76.4	R14:	96.4
Peak Wavelength (nm):	450	R7:	79.8	R15:	61.3
Dominant Wavelength (nm):	578	R8:	48.1		
Purity:	28.50862				

Rf:	77.5
Rg:	91.9




Test Conditions

Stabilization Time:	70M
Operation Time:	2H 10M
Sphere Temperature (°C):	25.0


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	12/16/2024	6/16/2025
Power Meter	INXT2011004	1/21/2025	1/21/2026
AC Power Source	IN0063	10/22/2024	10/22/2025
DC Power Source	IN0208	10/22/2024	10/22/2025
Sphere Thermometer	IN0085	10/22/2024	10/22/2025
Room Thermometer	IN0046	10/22/2024	10/22/2025

REPORT NUMBER: SP1-2501-332-1

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles




CCT = 3990K
CIE x = 0.3816
CIE y = 0.3798
Duv = 0.0011

Point lies inside the ANSI 4000K 4-step quadrangle

REPORT NUMBER: SP1-2501-332-1

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	275	NR	620	703	NR	750	16	NR	880	1	NR
365	0	NR	495	324	NR	625	637	NR	755	14	NR	885	0	NR
370	0	NR	500	380	NR	630	576	NR	760	12	NR	890	0	NR
375	0	NR	505	431	NR	635	514	NR	765	10	NR	895	0	NR
380	0	NR	510	472	NR	640	456	NR	770	9	NR	900	0	NR
385	1	NR	515	508	NR	645	403	NR	775	8	NR	905	0	NR
390	2	NR	520	538	NR	650	353	NR	780	7	NR	910	0	NR
395	4	NR	525	567	NR	655	307	NR	785	6	NR	915	0	NR
400	7	NR	530	595	NR	660	266	NR	790	5	NR	920	0	NR
405	12	NR	535	624	NR	665	230	NR	795	4	NR	925	0	NR
410	21	NR	540	660	NR	670	198	NR	800	4	NR	930	0	NR
415	39	NR	545	700	NR	675	170	NR	805	3	NR	935	0	NR
420	69	NR	550	739	NR	680	146	NR	810	3	NR	940	0	NR
425	121	NR	555	784	NR	685	125	NR	815	3	NR	945	0	NR
430	202	NR	560	836	NR	690	107	NR	820	2	NR	950	0	NR
435	319	NR	565	881	NR	695	91	NR	825	2	NR	955	0	NR
440	492	NR	570	923	NR	700	77	NR	830	2	NR	960	0	NR
445	777	NR	575	955	NR	705	66	NR	835	1	NR	965	0	NR
450	1000	NR	580	978	NR	710	56	NR	840	1	NR	970	0	NR
455	797	NR	585	982	NR	715	48	NR	845	1	NR	975	0	NR
460	530	NR	590	976	NR	720	41	NR	850	1	NR	980	0	NR
465	418	NR	595	955	NR	725	35	NR	855	1	NR	985	0	NR
470	311	NR	600	922	NR	730	30	NR	860	1	NR	990	0	NR
475	239	NR	605	877	NR	735	25	NR	865	1	NR	995	0	NR
480	229	NR	610	823	NR	740	22	NR	870	1	NR	1000	0	NR
485	245	NR	615	764	NR	745	19	NR	875	1	NR			

REPORT NUMBER: SP1-2501-332-1

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR **S/P: 1.59**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	275	NR	620	703	NR	750	16	NR	880	1	NR
365	0	NR	495	324	NR	625	637	NR	755	14	NR	885	0	NR
370	0	NR	500	380	NR	630	576	NR	760	12	NR	890	0	NR
375	0	NR	505	431	NR	635	514	NR	765	10	NR	895	0	NR
380	0	NR	510	472	NR	640	456	NR	770	9	NR	900	0	NR
385	1	NR	515	508	NR	645	403	NR	775	8	NR	905	0	NR
390	2	NR	520	538	NR	650	353	NR	780	7	NR	910	0	NR
395	4	NR	525	567	NR	655	307	NR	785	6	NR	915	0	NR
400	7	NR	530	595	NR	660	266	NR	790	5	NR	920	0	NR
405	12	NR	535	624	NR	665	230	NR	795	4	NR	925	0	NR
410	21	NR	540	660	NR	670	198	NR	800	4	NR	930	0	NR
415	39	NR	545	700	NR	675	170	NR	805	3	NR	935	0	NR
420	69	NR	550	739	NR	680	146	NR	810	3	NR	940	0	NR
425	121	NR	555	784	NR	685	125	NR	815	3	NR	945	0	NR
430	202	NR	560	836	NR	690	107	NR	820	2	NR	950	0	NR
435	319	NR	565	881	NR	695	91	NR	825	2	NR	955	0	NR
440	492	NR	570	923	NR	700	77	NR	830	2	NR	960	0	NR
445	777	NR	575	955	NR	705	66	NR	835	1	NR	965	0	NR
450	1000	NR	580	978	NR	710	56	NR	840	1	NR	970	0	NR
455	797	NR	585	982	NR	715	48	NR	845	1	NR	975	0	NR
460	530	NR	590	976	NR	720	41	NR	850	1	NR	980	0	NR
465	418	NR	595	955	NR	725	35	NR	855	1	NR	985	0	NR
470	311	NR	600	922	NR	730	30	NR	860	1	NR	990	0	NR
475	239	NR	605	877	NR	735	25	NR	865	1	NR	995	0	NR
480	229	NR	610	823	NR	740	22	NR	870	1	NR	1000	0	NR
485	245	NR	615	764	NR	745	19	NR	875	1	NR			

REPORT NUMBER: SP1-2501-332-1

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR **M/P: 3.21**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	275	NR	620	703	NR	750	16	NR	880	1	NR
365	0	NR	495	324	NR	625	637	NR	755	14	NR	885	0	NR
370	0	NR	500	380	NR	630	576	NR	760	12	NR	890	0	NR
375	0	NR	505	431	NR	635	514	NR	765	10	NR	895	0	NR
380	0	NR	510	472	NR	640	456	NR	770	9	NR	900	0	NR
385	1	NR	515	508	NR	645	403	NR	775	8	NR	905	0	NR
390	2	NR	520	538	NR	650	353	NR	780	7	NR	910	0	NR
395	4	NR	525	567	NR	655	307	NR	785	6	NR	915	0	NR
400	7	NR	530	595	NR	660	266	NR	790	5	NR	920	0	NR
405	12	NR	535	624	NR	665	230	NR	795	4	NR	925	0	NR
410	21	NR	540	660	NR	670	198	NR	800	4	NR	930	0	NR
415	39	NR	545	700	NR	675	170	NR	805	3	NR	935	0	NR
420	69	NR	550	739	NR	680	146	NR	810	3	NR	940	0	NR
425	121	NR	555	784	NR	685	125	NR	815	3	NR	945	0	NR
430	202	NR	560	836	NR	690	107	NR	820	2	NR	950	0	NR
435	319	NR	565	881	NR	695	91	NR	825	2	NR	955	0	NR
440	492	NR	570	923	NR	700	77	NR	830	2	NR	960	0	NR
445	777	NR	575	955	NR	705	66	NR	835	1	NR	965	0	NR
450	1000	NR	580	978	NR	710	56	NR	840	1	NR	970	0	NR
455	797	NR	585	982	NR	715	48	NR	845	1	NR	975	0	NR
460	530	NR	590	976	NR	720	41	NR	850	1	NR	980	0	NR
465	418	NR	595	955	NR	725	35	NR	855	1	NR	985	0	NR
470	311	NR	600	922	NR	730	30	NR	860	1	NR	990	0	NR
475	239	NR	605	877	NR	735	25	NR	865	1	NR	995	0	NR
480	229	NR	610	823	NR	740	22	NR	870	1	NR	1000	0	NR
485	245	NR	615	764	NR	745	19	NR	875	1	NR			


REPORT NUMBER: SP1-2501-332-1

TM-30-18


Summary


R_f = 77.5
R_g = 91.9
CIE R_a = 73.9
R_9 = -36.4


Spectral Power Distribution Comparison




Color Vector Graphics










REPORT NUMBER: SP1-2501-332-1

TM-30-18

Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 85	CES26 = 72	CES51 = 89	CES76 = 64
CES02 = 61	CES27 = 92	CES52 = 88	CES77 = 77
CES03 = 30	CES28 = 88	CES53 = 81	CES78 = 65
CES04 = 70	CES29 = 78	CES54 = 85	CES79 = 88
CES05 = 47	CES30 = 92	CES55 = 84	CES80 = 86
CES06 = 50	CES31 = 81	CES56 = 77	CES81 = 77
CES07 = 40	CES32 = 72	CES57 = 76	CES82 = 94
CES08 = 39	CES33 = 87	CES58 = 77	CES83 = 94
CES09 = 29	CES34 = 80	CES59 = 86	CES84 = 87
CES10 = 74	CES35 = 89	CES60 = 89	CES85 = 76
CES11 = 57	CES36 = 87	CES61 = 82	CES86 = 68
CES12 = 63	CES37 = 87	CES62 = 85	CES87 = 78
CES13 = 42	CES38 = 98	CES63 = 79	CES88 = 81
CES14 = 74	CES39 = 98	CES64 = 68	CES89 = 71
CES15 = 71	CES40 = 94	CES65 = 67	CES90 = 81
CES16 = 46	CES41 = 98	CES66 = 65	CES91 = 73
CES17 = 49	CES42 = 91	CES67 = 62	CES92 = 55
CES18 = 56	CES43 = 86	CES68 = 69	CES93 = 73
CES19 = 72	CES44 = 99	CES69 = 76	CES94 = 51
CES20 = 65	CES45 = 89	CES70 = 64	CES95 = 65
CES21 = 86	CES46 = 86	CES71 = 59	CES96 = 77
CES22 = 78	CES47 = 93	CES72 = 86	CES97 = 85
CES23 = 92	CES48 = 79	CES73 = 56	CES98 = 77
CES24 = 91	CES49 = 85	CES74 = 93	CES99 = 63
CES25 = 72	CES50 = 89	CES75 = 63	





REPORT NUMBER: SP1-2501-332-1

TM-30-18

Color Rendition by Hue-Angle Bin









REPORT NUMBER: SP1-2501-332-1

TM-30-18

Measure Comparisons





(END OF REPORT)