

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066470

Luminaire Tested: **NVN-SA5B-722-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066470
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5B-722-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 5xLight Square PACKAGE
70CRI 2200K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 2200K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 14093.1 lumens
Efficiency: N/A
Efficacy: 78.8 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 178.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	83.8	0.0	83.8
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	14009.3	0.0	14009.3
	% Fixture	99.4	0.0	99.4
Total	Lumens	14093.1	0.0	14093.1
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.2	0.0
10°-20°	20.7	0.1
20°-30°	263.0	1.9
30°-40°	886.5	6.3
40°-50°	2677.3	19.0
50°-60°	4723.5	33.5
60°-70°	4161.4	29.5
70°-80°	1324.7	9.4
80°-90°	31.9	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	14093.1	100.0
0°-180°	14093.1	100.0



REPORT NUMBER: P1066470


CATALOG NUMBER: NVN-SA5B-722-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	275.3	2.0			
FM	(30°-60°)	8254.8	58.6			
FH	(60°-80°)	5453.3	38.7			G3/7500
FVH	(80°-90°)	25.9	0.2			G1/100
BL	(0°-30°)	12.6	0.1	B0/110		
BM	(30°-60°)	32.5	0.2	B0/220		
BH	(60°-80°)	32.8	0.2	B0/110		G0/110
BVH	(80°-90°)	5.9	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	30.9
5°	44.2	44.2	44.2	39.8	39.8	39.8	35.4	35.4	35.4	35.4	35.4
7.5°	53.0	48.6	48.6	44.2	44.2	44.2	39.8	39.8	39.8	39.8	35.4
10°	61.9	57.5	57.5	53.0	53.0	48.6	48.6	44.2	44.2	39.8	39.8
12.5°	70.7	66.3	61.9	57.5	57.5	53.0	53.0	48.6	48.6	44.2	44.2
15°	79.6	75.1	70.7	66.3	61.9	61.9	57.5	53.0	48.6	48.6	44.2
17.5°	92.8	84.0	79.6	70.7	66.3	61.9	57.5	53.0	53.0	48.6	48.6
20°	97.2	88.4	84.0	75.1	70.7	66.3	61.9	57.5	53.0	53.0	48.6
22.5°	114.9	97.2	92.8	84.0	79.6	75.1	66.3	61.9	57.5	53.0	48.6
25°	141.4	114.9	101.7	88.4	84.0	75.1	70.7	61.9	57.5	53.0	48.6
27.5°	172.4	128.2	114.9	97.2	88.4	79.6	70.7	61.9	57.5	53.0	48.6
30°	212.1	150.3	128.2	106.1	97.2	88.4	75.1	66.3	61.9	57.5	48.6
32.5°	296.1	185.6	150.3	114.9	101.7	92.8	79.6	66.3	61.9	57.5	48.6
35°	358.0	225.4	181.2	132.6	114.9	101.7	84.0	66.3	61.9	57.5	48.6
37.5°	415.4	229.8	185.6	141.4	123.7	106.1	84.0	66.3	61.9	57.5	48.6
40°	508.3	238.7	185.6	132.6	119.3	101.7	88.4	70.7	66.3	57.5	53.0
42.5°	685.0	274.0	198.9	123.7	110.5	101.7	88.4	75.1	66.3	61.9	53.0
45°	1140.3	406.6	269.6	128.2	114.9	101.7	88.4	75.1	70.7	61.9	57.5
47.5°	1940.2	707.1	419.9	132.6	119.3	101.7	88.4	70.7	66.3	61.9	53.0
50°	2483.8	906.0	530.4	154.7	132.6	114.9	92.8	70.7	66.3	61.9	57.5
52.5°	2638.5	963.5	574.5	181.2	154.7	128.2	97.2	70.7	66.3	66.3	61.9
55°	2417.5	937.0	574.5	212.1	176.8	145.8	110.5	75.1	70.7	70.7	66.3
57.5°	2055.1	866.2	548.0	229.8	194.5	154.7	119.3	79.6	75.1	75.1	70.7
60°	1692.7	729.2	495.0	256.3	216.6	176.8	137.0	97.2	92.8	88.4	79.6
62.5°	1343.6	587.8	433.1	274.0	234.2	190.0	150.3	106.1	101.7	97.2	92.8
65°	1012.1	512.7	402.2	287.3	243.1	198.9	154.7	110.5	106.1	106.1	101.7
67.5°	777.8	468.5	384.5	296.1	251.9	207.7	163.5	119.3	114.9	110.5	106.1
70°	614.3	433.1	362.4	291.7	251.9	212.1	167.9	128.2	119.3	114.9	106.1
72.5°	512.7	393.3	335.9	278.4	247.5	216.6	185.6	154.7	137.0	123.7	106.1
75°	428.7	353.6	305.0	251.9	229.8	212.1	190.0	167.9	145.8	123.7	101.7
77.5°	282.9	256.3	234.2	212.1	198.9	185.6	167.9	154.7	132.6	114.9	92.8
80°	119.3	110.5	114.9	114.9	114.9	114.9	110.5	110.5	97.2	84.0	66.3
82.5°	26.5	22.1	26.5	26.5	26.5	26.5	22.1	22.1	22.1	17.7	17.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9
5°	35.4	35.4	35.4	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9
7.5°	35.4	35.4	35.4	30.9	30.9	30.9	30.9	26.5	26.5	26.5	26.5
10°	35.4	35.4	35.4	30.9	30.9	30.9	30.9	26.5	26.5	26.5	26.5
12.5°	39.8	39.8	35.4	35.4	30.9	30.9	30.9	26.5	26.5	26.5	26.5
15°	39.8	39.8	35.4	35.4	30.9	30.9	30.9	26.5	26.5	26.5	26.5
17.5°	44.2	39.8	39.8	35.4	30.9	30.9	30.9	26.5	26.5	26.5	26.5
20°	44.2	39.8	39.8	35.4	30.9	30.9	30.9	26.5	26.5	26.5	26.5
22.5°	44.2	39.8	39.8	35.4	30.9	30.9	26.5	26.5	22.1	22.1	17.7
25°	44.2	39.8	39.8	35.4	30.9	30.9	26.5	26.5	22.1	17.7	17.7
27.5°	44.2	39.8	39.8	35.4	30.9	26.5	26.5	22.1	17.7	13.3	13.3
30°	44.2	39.8	39.8	35.4	30.9	26.5	22.1	17.7	13.3	13.3	8.8
32.5°	44.2	39.8	35.4	30.9	26.5	22.1	22.1	17.7	13.3	8.8	8.8
35°	44.2	39.8	35.4	30.9	26.5	22.1	22.1	17.7	13.3	8.8	8.8
37.5°	44.2	39.8	35.4	30.9	26.5	22.1	17.7	13.3	8.8	8.8	4.4
40°	44.2	39.8	35.4	30.9	26.5	22.1	17.7	13.3	8.8	8.8	4.4
42.5°	44.2	39.8	35.4	30.9	26.5	22.1	17.7	13.3	8.8	8.8	4.4
45°	48.6	44.2	39.8	30.9	26.5	22.1	22.1	17.7	13.3	8.8	8.8
47.5°	48.6	44.2	39.8	30.9	26.5	22.1	22.1	17.7	13.3	8.8	8.8
50°	53.0	48.6	44.2	35.4	30.9	26.5	22.1	13.3	8.8	8.8	4.4
52.5°	57.5	53.0	48.6	44.2	39.8	30.9	22.1	13.3	4.4	4.4	4.4
55°	61.9	57.5	57.5	53.0	48.6	35.4	26.5	13.3	0.0	0.0	0.0
57.5°	66.3	61.9	61.9	57.5	53.0	39.8	26.5	13.3	0.0	0.0	0.0
60°	75.1	70.7	66.3	57.5	53.0	39.8	26.5	13.3	0.0	0.0	0.0
62.5°	88.4	79.6	66.3	57.5	44.2	35.4	22.1	13.3	0.0	0.0	0.0
65°	97.2	84.0	70.7	53.0	39.8	30.9	22.1	8.8	0.0	0.0	0.0
67.5°	101.7	84.0	70.7	53.0	35.4	26.5	17.7	8.8	0.0	0.0	0.0
70°	97.2	79.6	66.3	48.6	30.9	22.1	17.7	8.8	0.0	0.0	0.0
72.5°	88.4	75.1	57.5	44.2	26.5	22.1	13.3	8.8	0.0	0.0	0.0
75°	79.6	66.3	48.6	35.4	17.7	13.3	8.8	4.4	0.0	0.0	0.0
77.5°	70.7	57.5	39.8	26.5	8.8	8.8	4.4	4.4	0.0	0.0	0.0
80°	53.0	39.8	26.5	13.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	13.3	8.8	8.8	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	26.5	26.5	26.5	26.5	26.5	26.5	26.5	26.5	26.5	26.5	26.5
5°	26.5	26.5	26.5	26.5	22.1	22.1	22.1	22.1	22.1	22.1	22.1
7.5°	26.5	26.5	26.5	26.5	22.1	22.1	22.1	22.1	17.7	17.7	17.7
10°	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	17.7	17.7	17.7
12.5°	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	17.7	17.7	17.7
15°	22.1	22.1	22.1	22.1	22.1	22.1	22.1	17.7	17.7	13.3	13.3
17.5°	22.1	22.1	22.1	22.1	17.7	17.7	17.7	13.3	13.3	8.8	8.8
20°	22.1	22.1	22.1	17.7	17.7	13.3	13.3	8.8	8.8	4.4	4.4
22.5°	17.7	13.3	13.3	8.8	8.8	4.4	4.4	4.4	0.0	0.0	0.0
25°	13.3	8.8	8.8	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.8	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.8	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	26.5	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1
5°	22.1	22.1	22.1	22.1	17.7	17.7	17.7	17.7	17.7	17.7	17.7
7.5°	17.7	17.7	17.7	17.7	17.7	17.7	13.3	13.3	13.3	13.3	13.3
10°	17.7	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	8.8	8.8
12.5°	17.7	13.3	13.3	13.3	8.8	8.8	8.8	8.8	8.8	4.4	4.4
15°	13.3	8.8	8.8	8.8	4.4	4.4	4.4	4.4	4.4	0.0	0.0
17.5°	8.8	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	26.5	26.5
5°	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7
7.5°	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3
10°	8.8	8.8	8.8	8.8	8.8	8.8	4.4	4.4	4.4	4.4	4.4
12.5°	4.4	4.4	4.4	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	26.5	26.5	26.5	26.5	26.5	30.9	30.9	35.4	35.4	39.8	39.8
5°	17.7	17.7	22.1	22.1	22.1	22.1	26.5	26.5	26.5	30.9	30.9
7.5°	13.3	13.3	13.3	13.3	13.3	17.7	17.7	22.1	22.1	26.5	26.5
10°	4.4	4.4	8.8	8.8	8.8	8.8	13.3	13.3	13.3	17.7	22.1
12.5°	0.0	0.0	4.4	4.4	4.4	4.4	8.8	8.8	8.8	13.3	17.7
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	8.8	13.3
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	8.8
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	44.2	44.2	48.6	48.6	53.0	53.0	57.5	57.5	57.5	57.5	57.5
5°	35.4	35.4	39.8	44.2	44.2	48.6	53.0	53.0	53.0	53.0	53.0
7.5°	30.9	30.9	35.4	39.8	39.8	44.2	48.6	48.6	53.0	53.0	53.0
10°	22.1	26.5	30.9	35.4	35.4	39.8	44.2	44.2	48.6	48.6	48.6
12.5°	17.7	22.1	26.5	30.9	30.9	35.4	39.8	39.8	44.2	44.2	48.6
15°	13.3	17.7	22.1	26.5	26.5	30.9	35.4	35.4	39.8	44.2	48.6
17.5°	8.8	13.3	17.7	22.1	22.1	26.5	30.9	35.4	39.8	39.8	44.2
20°	8.8	8.8	13.3	17.7	17.7	22.1	26.5	30.9	35.4	35.4	39.8
22.5°	4.4	4.4	8.8	13.3	13.3	17.7	22.1	26.5	30.9	30.9	35.4
25°	0.0	0.0	4.4	8.8	8.8	13.3	17.7	17.7	22.1	22.1	26.5
27.5°	0.0	0.0	4.4	4.4	8.8	8.8	13.3	13.3	17.7	17.7	22.1
30°	0.0	0.0	4.4	4.4	8.8	8.8	13.3	13.3	17.7	17.7	17.7
32.5°	0.0	0.0	0.0	4.4	4.4	4.4	8.8	8.8	13.3	13.3	17.7
35°	0.0	0.0	0.0	4.4	4.4	4.4	8.8	8.8	13.3	13.3	13.3
37.5°	0.0	0.0	0.0	4.4	4.4	4.4	8.8	8.8	8.8	8.8	13.3
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.8	8.8	8.8
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.8	8.8	8.8
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.8	8.8	8.8
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.8	8.8	8.8
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.8	8.8	8.8
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.8	8.8	8.8
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.8	8.8	8.8
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	8.8
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	57.5	57.5
5°	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	53.0	53.0
7.5°	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	53.0	53.0
10°	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0
12.5°	48.6	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0
15°	48.6	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0
17.5°	44.2	48.6	48.6	48.6	53.0	53.0	53.0	53.0	53.0	53.0	53.0
20°	39.8	44.2	44.2	44.2	48.6	48.6	48.6	48.6	53.0	53.0	53.0
22.5°	35.4	39.8	39.8	39.8	44.2	44.2	44.2	44.2	48.6	48.6	48.6
25°	30.9	30.9	35.4	35.4	39.8	39.8	39.8	39.8	39.8	39.8	39.8
27.5°	22.1	26.5	26.5	26.5	30.9	30.9	30.9	30.9	35.4	35.4	35.4
30°	22.1	22.1	22.1	22.1	26.5	26.5	26.5	26.5	30.9	30.9	30.9
32.5°	17.7	22.1	22.1	22.1	26.5	26.5	26.5	26.5	30.9	30.9	30.9
35°	17.7	17.7	17.7	17.7	22.1	22.1	22.1	22.1	26.5	26.5	26.5
37.5°	13.3	17.7	17.7	17.7	22.1	22.1	22.1	22.1	26.5	26.5	26.5
40°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.1	22.1	22.1
42.5°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.1	22.1	22.1
45°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.1	22.1	22.1
47.5°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.1	22.1	22.1
50°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.1	22.1	22.1
52.5°	8.8	8.8	8.8	8.8	13.3	13.3	13.3	13.3	17.7	17.7	17.7
55°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	13.3	13.3	13.3
57.5°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	13.3	13.3	13.3
60°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
62.5°	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
65°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	4.4	4.4
67.5°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
70°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
72.5°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
75°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
77.5°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
80°	13.3	13.3	13.3	13.3	13.3	8.8	8.8	8.8	8.8	8.8	8.8
82.5°	8.8	13.3	13.3	13.3	13.3	8.8	8.8	8.8	8.8	8.8	8.8
85°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
87.5°	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	57.5	57.5	53.0	53.0	53.0	53.0	53.0	53.0	53.0	57.5	57.5
5°	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	57.5	57.5
7.5°	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	57.5	57.5
10°	53.0	53.0	53.0	53.0	48.6	48.6	53.0	53.0	53.0	57.5	57.5
12.5°	53.0	53.0	53.0	53.0	48.6	48.6	53.0	53.0	57.5	57.5	61.9
15°	53.0	53.0	48.6	48.6	48.6	48.6	53.0	53.0	57.5	57.5	61.9
17.5°	53.0	53.0	48.6	48.6	48.6	48.6	53.0	53.0	57.5	57.5	61.9
20°	53.0	53.0	48.6	48.6	48.6	48.6	48.6	48.6	53.0	57.5	57.5
22.5°	48.6	48.6	48.6	48.6	44.2	44.2	48.6	48.6	53.0	57.5	57.5
25°	39.8	44.2	44.2	44.2	44.2	44.2	48.6	48.6	53.0	57.5	57.5
27.5°	35.4	39.8	39.8	39.8	39.8	44.2	44.2	48.6	53.0	57.5	57.5
30°	30.9	35.4	35.4	35.4	39.8	44.2	44.2	48.6	53.0	57.5	57.5
32.5°	30.9	35.4	35.4	35.4	39.8	39.8	44.2	44.2	48.6	53.0	57.5
35°	30.9	30.9	35.4	35.4	35.4	39.8	39.8	44.2	48.6	53.0	57.5
37.5°	30.9	30.9	35.4	35.4	35.4	39.8	39.8	44.2	48.6	53.0	57.5
40°	26.5	30.9	30.9	35.4	35.4	39.8	39.8	44.2	48.6	57.5	61.9
42.5°	26.5	26.5	30.9	30.9	35.4	39.8	39.8	44.2	48.6	57.5	61.9
45°	26.5	30.9	30.9	35.4	39.8	44.2	44.2	48.6	53.0	57.5	61.9
47.5°	26.5	30.9	30.9	35.4	44.2	44.2	48.6	48.6	53.0	57.5	61.9
50°	26.5	30.9	30.9	35.4	48.6	48.6	48.6	48.6	53.0	57.5	61.9
52.5°	22.1	26.5	26.5	30.9	39.8	44.2	48.6	53.0	57.5	61.9	66.3
55°	17.7	22.1	22.1	26.5	35.4	39.8	48.6	57.5	61.9	66.3	70.7
57.5°	17.7	17.7	22.1	22.1	30.9	39.8	53.0	61.9	66.3	70.7	75.1
60°	13.3	13.3	17.7	17.7	26.5	35.4	48.6	61.9	66.3	75.1	79.6
62.5°	8.8	13.3	13.3	17.7	22.1	35.4	48.6	61.9	70.7	79.6	84.0
65°	8.8	8.8	13.3	13.3	22.1	30.9	44.2	53.0	66.3	79.6	92.8
67.5°	13.3	13.3	17.7	17.7	22.1	30.9	44.2	53.0	66.3	84.0	97.2
70°	13.3	13.3	17.7	17.7	26.5	35.4	44.2	53.0	66.3	84.0	97.2
72.5°	13.3	13.3	17.7	17.7	26.5	30.9	39.8	48.6	61.9	75.1	88.4
75°	8.8	13.3	13.3	13.3	22.1	26.5	35.4	44.2	57.5	70.7	84.0
77.5°	8.8	8.8	8.8	8.8	17.7	22.1	30.9	35.4	48.6	61.9	75.1
80°	8.8	8.8	8.8	8.8	13.3	17.7	26.5	30.9	44.2	57.5	70.7
82.5°	8.8	8.8	4.4	4.4	8.8	13.3	17.7	22.1	35.4	44.2	57.5
85°	8.8	8.8	4.4	4.4	4.4	8.8	8.8	13.3	17.7	22.1	26.5
87.5°	8.8	8.8	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	57.5	57.5	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9
5°	57.5	61.9	61.9	66.3	66.3	66.3	70.7	70.7	70.7	70.7	70.7
7.5°	57.5	61.9	61.9	66.3	66.3	66.3	70.7	70.7	70.7	75.1	75.1
10°	57.5	61.9	61.9	66.3	66.3	70.7	75.1	75.1	79.6	79.6	79.6
12.5°	61.9	66.3	66.3	70.7	70.7	75.1	79.6	79.6	84.0	88.4	88.4
15°	61.9	66.3	70.7	70.7	75.1	79.6	84.0	84.0	88.4	92.8	97.2
17.5°	61.9	66.3	70.7	70.7	75.1	79.6	88.4	92.8	97.2	106.1	110.5
20°	61.9	66.3	70.7	70.7	75.1	84.0	88.4	97.2	101.7	110.5	119.3
22.5°	61.9	66.3	70.7	75.1	79.6	88.4	97.2	101.7	110.5	123.7	132.6
25°	61.9	66.3	70.7	75.1	79.6	88.4	97.2	106.1	114.9	132.6	150.3
27.5°	61.9	66.3	75.1	79.6	84.0	92.8	106.1	114.9	123.7	154.7	185.6
30°	61.9	66.3	75.1	79.6	84.0	97.2	110.5	119.3	132.6	185.6	234.2
32.5°	61.9	70.7	75.1	84.0	88.4	101.7	119.3	132.6	145.8	221.0	291.7
35°	61.9	70.7	75.1	84.0	88.4	106.1	123.7	141.4	159.1	269.6	380.1
37.5°	61.9	70.7	75.1	84.0	88.4	114.9	141.4	167.9	194.5	309.4	424.3
40°	66.3	75.1	79.6	88.4	92.8	119.3	145.8	172.4	198.9	313.8	428.7
42.5°	66.3	75.1	79.6	88.4	92.8	114.9	141.4	163.5	185.6	313.8	442.0
45°	66.3	75.1	84.0	88.4	97.2	119.3	141.4	159.1	181.2	344.7	503.8
47.5°	66.3	75.1	84.0	88.4	97.2	119.3	141.4	163.5	185.6	455.2	720.4
50°	66.3	75.1	84.0	88.4	97.2	123.7	150.3	176.8	203.3	680.6	1157.9
52.5°	70.7	75.1	84.0	88.4	92.8	123.7	154.7	185.6	216.6	883.9	1546.9
55°	75.1	79.6	84.0	88.4	92.8	132.6	172.4	212.1	251.9	950.2	1644.1
57.5°	79.6	84.0	88.4	88.4	92.8	141.4	194.5	243.1	291.7	945.8	1595.5
60°	84.0	88.4	92.8	97.2	101.7	150.3	203.3	251.9	300.5	857.4	1414.3
62.5°	92.8	101.7	110.5	114.9	123.7	172.4	216.6	265.2	309.4	702.7	1091.6
65°	106.1	114.9	119.3	128.2	132.6	176.8	225.4	269.6	313.8	583.4	848.6
67.5°	110.5	119.3	123.7	132.6	137.0	181.2	225.4	269.6	313.8	495.0	671.8
70°	110.5	119.3	128.2	132.6	141.4	185.6	225.4	269.6	309.4	428.7	548.0
72.5°	101.7	114.9	123.7	137.0	145.8	185.6	221.0	260.8	296.1	380.1	464.1
75°	97.2	114.9	128.2	145.8	159.1	185.6	216.6	243.1	269.6	331.5	393.3
77.5°	88.4	110.5	132.6	154.7	176.8	194.5	207.7	225.4	238.7	278.4	318.2
80°	84.0	106.1	128.2	150.3	172.4	181.2	185.6	194.5	198.9	203.3	207.7
82.5°	66.3	84.0	101.7	114.9	132.6	123.7	119.3	110.5	101.7	97.2	92.8
85°	30.9	35.4	35.4	39.8	39.8	39.8	35.4	35.4	30.9	26.5	22.1
87.5°	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	61.9	61.9	61.9	61.9	57.5	57.5	57.5	57.5	53.0	53.0	53.0
5°	70.7	70.7	70.7	70.7	66.3	66.3	66.3	66.3	61.9	61.9	61.9
7.5°	75.1	75.1	75.1	75.1	75.1	75.1	75.1	75.1	75.1	75.1	75.1
10°	84.0	84.0	84.0	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4
12.5°	92.8	92.8	97.2	97.2	101.7	101.7	106.1	106.1	110.5	110.5	110.5
15°	101.7	106.1	110.5	114.9	114.9	119.3	123.7	128.2	132.6	137.0	141.4
17.5°	119.3	123.7	132.6	141.4	150.3	159.1	172.4	190.0	203.3	216.6	234.2
20°	132.6	145.8	172.4	203.3	229.8	256.3	322.6	388.9	455.2	521.5	587.8
22.5°	159.1	185.6	274.0	366.8	455.2	543.6	751.3	959.1	1162.4	1370.1	1555.7
25°	212.1	269.6	472.9	676.2	875.1	1078.4	1449.6	1825.3	2196.5	2567.8	2912.5
27.5°	291.7	397.8	729.2	1065.1	1396.6	1728.1	2267.3	2810.9	3350.1	3893.7	4375.4
30°	406.6	579.0	1074.0	1573.4	2068.4	2563.4	3244.0	3929.0	4609.6	5290.3	5732.2
32.5°	552.4	808.8	1436.4	2064.0	2691.5	3319.1	4070.5	4821.8	5568.7	6320.0	6788.5
35°	707.1	1034.2	1789.9	2550.1	3305.9	4066.0	4857.1	5648.2	6439.4	7230.5	7805.0
37.5°	795.5	1166.8	2064.0	2961.1	3853.9	4751.1	5617.3	6488.0	7354.2	8220.5	8918.8
40°	879.5	1325.9	2360.1	3394.3	4428.4	5462.6	6474.7	7486.8	8498.9	9511.0	10408.2
42.5°	1003.2	1564.5	2771.1	3977.6	5179.8	6386.3	7716.6	9051.3	10381.6	11711.9	13090.9
45°	1259.6	2015.3	3579.9	5144.4	6704.5	8269.1	10156.2	12047.8	13935.0	15826.6	17594.4
47.5°	1878.3	3031.8	5166.5	7301.2	9435.8	11570.5	13745.0	15919.4	18093.8	20268.3	22372.0
50°	2908.1	4653.8	7323.3	9992.7	12657.7	15327.2	17497.2	19667.2	21832.8	24002.8	26093.3
52.5°	3876.0	6205.1	9073.4	11946.2	14814.5	17687.2	19609.8	21532.3	23454.8	25377.3	27401.5
55°	4207.5	6766.4	9670.1	12578.2	15481.9	18390.0	20241.8	22098.0	23949.8	25801.6	27900.9
57.5°	3915.8	6236.1	9161.8	12087.6	15009.0	17934.7	20003.1	22075.9	24144.3	26217.1	28466.6
60°	3279.3	5140.0	8211.6	11287.7	14359.3	17430.9	19764.4	22098.0	24431.5	26765.1	29010.2
62.5°	2598.7	4101.4	7354.2	10607.0	13859.9	17112.7	19486.0	21863.8	24237.1	26610.4	28334.1
65°	1993.2	3137.9	6337.7	9541.9	12741.7	15945.9	17890.5	19839.6	21784.2	23733.2	24926.5
67.5°	1480.6	2289.4	5087.0	7889.0	10686.6	13484.2	14916.1	16352.5	17784.5	19220.8	20149.0
70°	1091.6	1630.8	3535.7	5440.5	7341.0	9245.8	10558.4	11871.0	13179.2	14491.9	15455.3
72.5°	755.8	1043.0	2183.3	3328.0	4468.2	5608.5	6938.8	8269.1	9594.9	10925.2	12021.3
75°	517.1	640.8	1175.6	1710.4	2245.2	2779.9	3787.6	4795.3	5802.9	6810.6	7389.6
77.5°	384.5	450.8	609.9	773.4	932.5	1091.6	1286.1	1480.6	1675.0	1869.5	2121.4
80°	212.1	212.1	234.2	251.9	274.0	291.7	344.7	402.2	455.2	512.7	583.4
82.5°	97.2	101.7	110.5	119.3	123.7	132.6	141.4	150.3	159.1	167.9	167.9
85°	26.5	30.9	30.9	26.5	26.5	22.1	22.1	26.5	26.5	26.5	26.5
87.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	53.0	48.6	48.6	48.6	44.2	44.2	44.2	44.2	44.2	44.2	44.2
5°	61.9	61.9	61.9	61.9	57.5	57.5	57.5	57.5	57.5	53.0	53.0
7.5°	75.1	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	66.3	66.3
10°	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	84.0	84.0
12.5°	110.5	110.5	110.5	110.5	114.9	114.9	110.5	110.5	110.5	106.1	106.1
15°	145.8	150.3	154.7	154.7	159.1	159.1	159.1	154.7	154.7	150.3	145.8
17.5°	247.5	260.8	278.4	296.1	313.8	327.1	327.1	318.2	309.4	300.5	291.7
20°	658.5	724.8	795.5	866.2	941.4	994.4	959.1	932.5	906.0	875.1	848.6
22.5°	1745.7	1931.4	2121.4	2254.0	2386.6	2479.4	2404.3	2258.4	2112.6	1971.1	1825.3
25°	3257.2	3597.6	3942.3	4083.7	4229.6	4335.6	4287.0	4066.0	3845.1	3628.5	3407.5
27.5°	4857.1	5334.5	5816.2	5939.9	6063.7	6156.5	6138.8	5851.5	5564.3	5277.0	4989.7
30°	6174.2	6616.1	7058.1	7181.8	7305.6	7389.6	7296.8	7009.5	6722.2	6434.9	6147.7
32.5°	7261.4	7729.9	8202.8	8366.3	8529.8	8640.3	8529.8	8185.1	7840.4	7500.1	7155.3
35°	8379.6	8949.7	9524.2	9732.0	9939.7	10072.3	9886.6	9462.4	9038.1	8618.2	8193.9
37.5°	9617.0	10310.9	11009.2	11292.1	11579.4	11778.2	11636.8	11106.5	10571.7	10041.3	9506.6
40°	11309.8	12206.9	13108.5	13616.8	14120.6	14478.6	14226.7	13612.4	12993.6	12379.3	11760.6
42.5°	14474.2	15853.1	17232.0	17961.3	18686.1	19212.0	18929.1	18173.4	17417.6	16661.9	15906.1
45°	19362.3	21125.7	22893.5	23958.6	25028.2	25814.9	25487.8	24537.6	23583.0	22632.8	21682.6
47.5°	24475.7	26579.5	28683.2	29531.8	30384.7	31047.7	30968.1	29783.7	28599.2	27419.2	26234.7
50°	28188.2	30278.7	32369.1	33098.4	33832.0	34375.6	34172.3	32665.3	31153.8	29646.7	28135.2
52.5°	29425.7	31445.4	33469.6	34340.3	35210.9	35860.6	35613.1	33916.0	32218.9	30526.2	28829.0
55°	30000.2	32099.5	34198.9	35259.6	36324.7	37102.5	36744.5	34883.9	33018.8	31158.2	29293.1
57.5°	30716.2	32965.8	35215.4	36377.7	37540.1	38379.8	37902.5	35975.5	34048.6	32126.1	30199.1
60°	31255.4	33496.1	35741.3	36673.8	37610.8	38264.9	37805.3	35931.3	34053.0	32179.1	30305.2
62.5°	30062.1	31785.8	33509.4	34203.3	34897.2	35401.0	35140.2	33363.6	31586.9	29810.2	28033.5
65°	26124.3	27317.5	28515.3	28983.7	29447.8	29805.8	29726.2	28228.0	26729.7	25235.9	23737.7
67.5°	21081.5	22009.6	22942.1	23605.1	24272.4	24789.5	24732.1	23366.4	22000.8	20635.1	19269.5
70°	16423.2	17386.7	18350.2	19185.5	20025.2	20674.9	20590.9	19322.5	18049.6	16781.2	15508.4
72.5°	13121.8	14217.9	15313.9	15791.2	16268.5	16604.4	16356.9	15397.9	14434.4	13475.4	12511.9
75°	7968.5	8543.1	9122.1	9117.6	9117.6	9064.6	8817.1	8269.1	7721.0	7173.0	6625.0
77.5°	2373.3	2625.2	2877.2	3120.2	3367.7	3553.4	3504.7	3217.5	2925.8	2638.5	2346.8
80°	654.1	720.4	791.1	822.0	853.0	892.8	994.4	923.7	853.0	786.7	716.0
82.5°	167.9	167.9	167.9	163.5	159.1	150.3	137.0	128.2	119.3	110.5	101.7
85°	26.5	22.1	22.1	22.1	17.7	17.7	17.7	17.7	13.3	13.3	8.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
2.5°	44.2	44.2	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	35.4
5°	53.0	53.0	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	44.2
7.5°	66.3	66.3	61.9	61.9	61.9	61.9	57.5	57.5	57.5	57.5	53.0
10°	84.0	79.6	79.6	75.1	75.1	75.1	70.7	70.7	70.7	66.3	66.3
12.5°	106.1	101.7	101.7	97.2	92.8	92.8	88.4	84.0	79.6	79.6	75.1
15°	141.4	137.0	132.6	128.2	123.7	114.9	110.5	101.7	97.2	92.8	88.4
17.5°	269.6	247.5	225.4	203.3	185.6	167.9	150.3	132.6	123.7	114.9	106.1
20°	751.3	649.7	552.4	455.2	393.3	331.5	269.6	207.7	181.2	159.1	132.6
22.5°	1626.4	1423.1	1224.2	1020.9	857.4	698.3	534.8	371.2	309.4	251.9	190.0
25°	3023.0	2634.1	2249.6	1860.7	1551.3	1241.9	932.5	623.2	508.3	393.3	278.4
27.5°	4485.9	3982.1	3478.2	2974.4	2483.8	1988.8	1493.8	1003.2	804.4	609.9	411.0
30°	5612.9	5078.1	4547.8	4013.0	3394.3	2775.5	2152.3	1533.6	1219.8	906.0	587.8
32.5°	6580.8	6001.8	5427.3	4848.3	4132.3	3416.4	2700.4	1984.4	1591.1	1197.7	799.9
35°	7539.8	6881.3	6227.2	5568.7	4799.7	4030.7	3261.7	2492.7	1993.2	1493.8	990.0
37.5°	8706.6	7902.2	7102.3	6302.3	5511.2	4724.6	3933.4	3142.3	2505.9	1873.9	1237.5
40°	10739.6	9714.3	8693.4	7668.0	6744.3	5825.0	4901.3	3977.6	3177.7	2377.7	1573.4
42.5°	14620.0	13333.9	12052.2	10766.1	9488.9	8211.6	6929.9	5652.7	4512.4	3376.6	2236.3
45°	20034.0	18385.5	16741.4	15092.9	13519.6	11950.6	10377.2	8803.8	7071.4	5338.9	3602.0
47.5°	24431.5	22623.9	20820.7	19013.1	17267.4	15526.1	13780.3	12034.6	9815.9	7601.7	5383.1
50°	26415.9	24692.3	22973.1	21249.4	19499.3	17744.7	15990.1	14239.9	11694.3	9153.0	6607.3
52.5°	27083.3	25333.1	23587.4	21837.2	20100.3	18363.4	16626.5	14889.6	12242.3	9599.4	6952.0
55°	27450.1	25602.7	23759.8	21912.4	20042.9	18169.0	16295.1	14425.6	11791.5	9161.8	6527.7
57.5°	28192.6	26181.7	24175.2	22164.3	20034.0	17903.8	15769.1	13638.9	11040.2	8441.4	5842.7
60°	28329.6	26349.7	24374.1	22398.5	20042.9	17687.2	15327.2	12971.5	10390.5	7813.9	5232.8
62.5°	26380.6	24727.7	23079.1	21426.2	19066.2	16706.1	14341.6	11981.5	9511.0	7040.4	4565.4
65°	22310.1	20882.6	19459.5	18032.0	16105.0	14182.5	12255.5	10328.6	8123.2	5922.3	3716.9
67.5°	17872.9	16476.3	15084.1	13687.5	12237.9	10792.7	9343.0	7893.4	6191.9	4490.3	2788.8
70°	14169.2	12825.7	11486.5	10143.0	8861.3	7575.2	6289.1	5007.4	3951.1	2899.3	1843.0
72.5°	11230.2	9944.1	8662.4	7376.3	6214.0	5051.6	3889.2	2726.9	2201.0	1679.4	1153.5
75°	5957.6	5290.3	4627.3	3960.0	3305.9	2647.3	1988.8	1334.7	1127.0	919.3	707.1
77.5°	2055.1	1763.4	1476.1	1184.5	985.6	786.7	587.8	388.9	366.8	349.1	327.1
80°	623.2	530.4	437.5	344.7	305.0	265.2	225.4	185.6	172.4	159.1	141.4
82.5°	97.2	88.4	84.0	75.1	70.7	70.7	66.3	61.9	53.0	48.6	39.8
85°	8.8	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	39.8	39.8
2.5°	35.4	35.4
5°	44.2	44.2
7.5°	53.0	53.0
10°	61.9	61.9
12.5°	70.7	70.7
15°	84.0	79.6
17.5°	97.2	92.8
20°	106.1	97.2
22.5°	128.2	110.5
25°	163.5	137.0
27.5°	212.1	167.9
30°	274.0	212.1
32.5°	406.6	296.1
35°	490.6	358.0
37.5°	601.1	415.4
40°	773.4	503.8
42.5°	1096.1	685.0
45°	1869.5	1135.8
47.5°	3168.9	1935.8
50°	4061.6	2483.8
52.5°	4309.1	2634.1
55°	3898.1	2417.5
57.5°	3244.0	2055.1
60°	2656.2	1692.7
62.5°	2094.9	1339.1
65°	1511.5	1012.1
67.5°	1087.2	777.8
70°	791.1	609.9
72.5°	627.6	508.3
75°	499.4	424.3
77.5°	309.4	282.9
80°	128.2	119.3
82.5°	30.9	26.5
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066470

CATALOG NUMBER: NVN-SA5B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-2

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-722-U-5WQ


Data in this report applies to families of products including GSS-SB1A-722-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-2
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-722-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2200K CCT 26 LEDS

Spectral Parameters

CCT (K):	2160	CRI (Ra):	71.9		
CIE u':	0.2927	R1:	68.7	R9:	-17.8
CIE v':	0.5388	R2:	82.6	R10:	60.5
Duv:	0.0015	R3:	95.5	R11:	60.2
CIE x:	0.5130	R4:	66.4	R12:	48.2
CIE y:	0.4197	R5:	65.4	R13:	70.7
CIE z:	0.0674	R6:	75.9	R14:	96.8
Peak Wavelength (nm):	609	R7:	77.2	R15:	61.8
Dominant Wavelength (nm):	587	R8:	43.5		
Purity:	79.96089				
Rf:	70.6				
Rg:	97.6				



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-2


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-2

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2200K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-2

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 0.8

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.21


λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2





TM-30-18

Summary

$R_f = 70.6$
 $R_g = 97.6$
 $CIE\ R_a = 71.9$
 $R_g = -17.8$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 87	CES26 = 60	CES51 = 74	CES76 = 58
CES02 = 65	CES27 = 77	CES52 = 77	CES77 = 82
CES03 = 32	CES28 = 85	CES53 = 65	CES78 = 65
CES04 = 72	CES29 = 50	CES54 = 77	CES79 = 86
CES05 = 52	CES30 = 49	CES55 = 74	CES80 = 85
CES06 = 53	CES31 = 55	CES56 = 64	CES81 = 61
CES07 = 44	CES32 = 55	CES57 = 60	CES82 = 93
CES08 = 43	CES33 = 55	CES58 = 64	CES83 = 83
CES09 = 29	CES34 = 75	CES59 = 84	CES84 = 93
CES10 = 79	CES35 = 88	CES60 = 89	CES85 = 81
CES11 = 62	CES36 = 78	CES61 = 84	CES86 = 55
CES12 = 68	CES37 = 82	CES62 = 68	CES87 = 79
CES13 = 45	CES38 = 54	CES63 = 68	CES88 = 72
CES14 = 75	CES39 = 90	CES64 = 69	CES89 = 62
CES15 = 72	CES40 = 86	CES65 = 66	CES90 = 67
CES16 = 49	CES41 = 75	CES66 = 64	CES91 = 89
CES17 = 51	CES42 = 83	CES67 = 63	CES92 = 67
CES18 = 57	CES43 = 68	CES68 = 71	CES93 = 78
CES19 = 74	CES44 = 98	CES69 = 81	CES94 = 52
CES20 = 68	CES45 = 76	CES70 = 65	CES95 = 76
CES21 = 89	CES46 = 68	CES71 = 64	CES96 = 78
CES22 = 81	CES47 = 60	CES72 = 88	CES97 = 76
CES23 = 92	CES48 = 47	CES73 = 59	CES98 = 71
CES24 = 92	CES49 = 65	CES74 = 85	CES99 = 65
CES25 = 74	CES50 = 74	CES75 = 66	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)