

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066474

Luminaire Tested: **NVN-SA6B-722-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066474
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA6B-722-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 6xLight Square PACKAGE
70CRI 2200K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (84) 2200K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 16953.5 lumens
Efficiency: N/A
Efficacy: 80.3 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 211
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3.3 fc
 Type III - Short - N/A

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	100.8	0.0	100.8
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	16852.6	0.0	16852.6
	% Fixture	99.4	0.0	99.4
Total	Lumens	16953.4	0.0	16953.4
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	5.0	0.0
10°-20°	24.9	0.1
20°-30°	316.4	1.9
30°-40°	1066.4	6.3
40°-50°	3220.6	19.0
50°-60°	5682.2	33.5
60°-70°	5006.0	29.5
70°-80°	1593.5	9.4
80°-90°	38.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	16953.4	100.0
0°-180°	16953.5	100.0



REPORT NUMBER: P1066474


CATALOG NUMBER: NVN-SA6B-722-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	331.2	2.0			
FM	(30°-60°)	9930.2	58.6			
FH	(60°-80°)	6560.0	38.7			G3/7500
FVH	(80°-90°)	31.2	0.2			G1/100
BL	(0°-30°)	15.1	0.1	B0/110		
BM	(30°-60°)	39.1	0.2	B0/220		
BH	(60°-80°)	39.5	0.2	B0/110		G0/110
BVH	(80°-90°)	7.1	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	37.2
5°	53.2	53.2	53.2	47.8	47.8	47.8	42.5	42.5	42.5	42.5	42.5
7.5°	63.8	58.5	58.5	53.2	53.2	53.2	47.8	47.8	47.8	47.8	42.5
10°	74.4	69.1	69.1	63.8	63.8	58.5	58.5	53.2	53.2	47.8	47.8
12.5°	85.1	79.7	74.4	69.1	69.1	63.8	63.8	58.5	58.5	53.2	53.2
15°	95.7	90.4	85.1	79.7	74.4	74.4	69.1	63.8	58.5	58.5	53.2
17.5°	111.6	101.0	95.7	85.1	79.7	74.4	69.1	63.8	63.8	58.5	58.5
20°	117.0	106.3	101.0	90.4	85.1	79.7	74.4	69.1	63.8	63.8	58.5
22.5°	138.2	117.0	111.6	101.0	95.7	90.4	79.7	74.4	69.1	63.8	58.5
25°	170.1	138.2	122.3	106.3	101.0	90.4	85.1	74.4	69.1	63.8	58.5
27.5°	207.3	154.2	138.2	117.0	106.3	95.7	85.1	74.4	69.1	63.8	58.5
30°	255.2	180.8	154.2	127.6	117.0	106.3	90.4	79.7	74.4	69.1	58.5
32.5°	356.2	223.3	180.8	138.2	122.3	111.6	95.7	79.7	74.4	69.1	58.5
35°	430.6	271.1	218.0	159.5	138.2	122.3	101.0	79.7	74.4	69.1	58.5
37.5°	499.8	276.5	223.3	170.1	148.9	127.6	101.0	79.7	74.4	69.1	58.5
40°	611.4	287.1	223.3	159.5	143.5	122.3	106.3	85.1	79.7	69.1	63.8
42.5°	824.1	329.6	239.2	148.9	132.9	122.3	106.3	90.4	79.7	74.4	63.8
45°	1371.7	489.1	324.3	154.2	138.2	122.3	106.3	90.4	85.1	74.4	69.1
47.5°	2334.0	850.7	505.1	159.5	143.5	122.3	106.3	85.1	79.7	74.4	63.8
50°	2987.9	1089.9	638.0	186.1	159.5	138.2	111.6	85.1	79.7	74.4	69.1
52.5°	3174.0	1159.0	691.2	218.0	186.1	154.2	117.0	85.1	79.7	79.7	74.4
55°	2908.2	1127.1	691.2	255.2	212.7	175.4	132.9	90.4	85.1	85.1	79.7
57.5°	2472.2	1042.1	659.3	276.5	233.9	186.1	143.5	95.7	90.4	90.4	85.1
60°	2036.3	877.2	595.5	308.4	260.5	212.7	164.8	117.0	111.6	106.3	95.7
62.5°	1616.2	707.1	521.0	329.6	281.8	228.6	180.8	127.6	122.3	117.0	111.6
65°	1217.5	616.7	483.8	345.6	292.4	239.2	186.1	132.9	127.6	127.6	122.3
67.5°	935.7	563.6	462.5	356.2	303.0	249.9	196.7	143.5	138.2	132.9	127.6
70°	739.0	521.0	436.0	350.9	303.0	255.2	202.0	154.2	143.5	138.2	127.6
72.5°	616.7	473.2	404.1	334.9	297.7	260.5	223.3	186.1	164.8	148.9	127.6
75°	515.7	425.3	366.8	303.0	276.5	255.2	228.6	202.0	175.4	148.9	122.3
77.5°	340.3	308.4	281.8	255.2	239.2	223.3	202.0	186.1	159.5	138.2	111.6
80°	143.5	132.9	138.2	138.2	138.2	138.2	132.9	132.9	117.0	101.0	79.7
82.5°	31.9	26.6	31.9	31.9	31.9	31.9	26.6	26.6	26.6	21.3	21.3
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
5°	42.5	42.5	42.5	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
7.5°	42.5	42.5	42.5	37.2	37.2	37.2	37.2	31.9	31.9	31.9	31.9
10°	42.5	42.5	42.5	37.2	37.2	37.2	37.2	31.9	31.9	31.9	31.9
12.5°	47.8	47.8	42.5	42.5	37.2	37.2	37.2	31.9	31.9	31.9	31.9
15°	47.8	47.8	42.5	42.5	37.2	37.2	37.2	31.9	31.9	31.9	31.9
17.5°	53.2	47.8	47.8	42.5	37.2	37.2	37.2	31.9	31.9	31.9	31.9
20°	53.2	47.8	47.8	42.5	37.2	37.2	37.2	31.9	31.9	31.9	31.9
22.5°	53.2	47.8	47.8	42.5	37.2	37.2	31.9	31.9	26.6	26.6	21.3
25°	53.2	47.8	47.8	42.5	37.2	37.2	31.9	31.9	26.6	21.3	21.3
27.5°	53.2	47.8	47.8	42.5	37.2	31.9	31.9	26.6	21.3	15.9	15.9
30°	53.2	47.8	47.8	42.5	37.2	31.9	26.6	21.3	15.9	15.9	10.6
32.5°	53.2	47.8	42.5	37.2	31.9	26.6	26.6	21.3	15.9	10.6	10.6
35°	53.2	47.8	42.5	37.2	31.9	26.6	26.6	21.3	15.9	10.6	10.6
37.5°	53.2	47.8	42.5	37.2	31.9	26.6	21.3	15.9	10.6	10.6	5.3
40°	53.2	47.8	42.5	37.2	31.9	26.6	21.3	15.9	10.6	10.6	5.3
42.5°	53.2	47.8	42.5	37.2	31.9	26.6	21.3	15.9	10.6	10.6	5.3
45°	58.5	53.2	47.8	37.2	31.9	26.6	26.6	21.3	15.9	10.6	10.6
47.5°	58.5	53.2	47.8	37.2	31.9	26.6	26.6	21.3	15.9	10.6	10.6
50°	63.8	58.5	53.2	42.5	37.2	31.9	26.6	15.9	10.6	10.6	5.3
52.5°	69.1	63.8	58.5	53.2	47.8	37.2	26.6	15.9	5.3	5.3	5.3
55°	74.4	69.1	69.1	63.8	58.5	42.5	31.9	15.9	0.0	0.0	0.0
57.5°	79.7	74.4	74.4	69.1	63.8	47.8	31.9	15.9	0.0	0.0	0.0
60°	90.4	85.1	79.7	69.1	63.8	47.8	31.9	15.9	0.0	0.0	0.0
62.5°	106.3	95.7	79.7	69.1	53.2	42.5	26.6	15.9	0.0	0.0	0.0
65°	117.0	101.0	85.1	63.8	47.8	37.2	26.6	10.6	0.0	0.0	0.0
67.5°	122.3	101.0	85.1	63.8	42.5	31.9	21.3	10.6	0.0	0.0	0.0
70°	117.0	95.7	79.7	58.5	37.2	26.6	21.3	10.6	0.0	0.0	0.0
72.5°	106.3	90.4	69.1	53.2	31.9	26.6	15.9	10.6	0.0	0.0	0.0
75°	95.7	79.7	58.5	42.5	21.3	15.9	10.6	5.3	0.0	0.0	0.0
77.5°	85.1	69.1	47.8	31.9	10.6	10.6	5.3	5.3	0.0	0.0	0.0
80°	63.8	47.8	31.9	15.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	15.9	10.6	10.6	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9
5°	31.9	31.9	31.9	31.9	26.6	26.6	26.6	26.6	26.6	26.6	26.6
7.5°	31.9	31.9	31.9	31.9	26.6	26.6	26.6	26.6	21.3	21.3	21.3
10°	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	21.3	21.3	21.3
12.5°	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	21.3	21.3	21.3
15°	26.6	26.6	26.6	26.6	26.6	26.6	26.6	21.3	21.3	15.9	15.9
17.5°	26.6	26.6	26.6	26.6	21.3	21.3	21.3	15.9	15.9	10.6	10.6
20°	26.6	26.6	26.6	21.3	21.3	15.9	15.9	10.6	10.6	5.3	5.3
22.5°	21.3	15.9	15.9	10.6	10.6	5.3	5.3	5.3	0.0	0.0	0.0
25°	15.9	10.6	10.6	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	10.6	5.3	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	10.6	5.3	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	31.9	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6
5°	26.6	26.6	26.6	26.6	21.3	21.3	21.3	21.3	21.3	21.3	21.3
7.5°	21.3	21.3	21.3	21.3	21.3	21.3	15.9	15.9	15.9	15.9	15.9
10°	21.3	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	10.6	10.6
12.5°	21.3	15.9	15.9	15.9	10.6	10.6	10.6	10.6	10.6	5.3	5.3
15°	15.9	10.6	10.6	10.6	5.3	5.3	5.3	5.3	5.3	0.0	0.0
17.5°	10.6	5.3	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	31.9	31.9
5°	21.3	21.3	21.3	21.3	21.3	21.3	21.3	21.3	21.3	21.3	21.3
7.5°	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9
10°	10.6	10.6	10.6	10.6	10.6	10.6	5.3	5.3	5.3	5.3	5.3
12.5°	5.3	5.3	5.3	5.3	5.3	5.3	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	31.9	31.9	31.9	31.9	31.9	37.2	37.2	42.5	42.5	47.8	47.8
5°	21.3	21.3	26.6	26.6	26.6	26.6	31.9	31.9	31.9	37.2	37.2
7.5°	15.9	15.9	15.9	15.9	15.9	21.3	21.3	26.6	26.6	31.9	31.9
10°	5.3	5.3	10.6	10.6	10.6	10.6	15.9	15.9	15.9	21.3	26.6
12.5°	0.0	0.0	5.3	5.3	5.3	5.3	10.6	10.6	10.6	15.9	21.3
15°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	10.6	15.9
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	10.6
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	53.2	53.2	58.5	58.5	63.8	63.8	69.1	69.1	69.1	69.1	69.1
5°	42.5	42.5	47.8	53.2	53.2	58.5	63.8	63.8	63.8	63.8	63.8
7.5°	37.2	37.2	42.5	47.8	47.8	53.2	58.5	58.5	63.8	63.8	63.8
10°	26.6	31.9	37.2	42.5	42.5	47.8	53.2	53.2	58.5	58.5	58.5
12.5°	21.3	26.6	31.9	37.2	37.2	42.5	47.8	47.8	53.2	53.2	58.5
15°	15.9	21.3	26.6	31.9	31.9	37.2	42.5	42.5	47.8	53.2	58.5
17.5°	10.6	15.9	21.3	26.6	26.6	31.9	37.2	42.5	47.8	47.8	53.2
20°	10.6	10.6	15.9	21.3	21.3	26.6	31.9	37.2	42.5	42.5	47.8
22.5°	5.3	5.3	10.6	15.9	15.9	21.3	26.6	31.9	37.2	37.2	42.5
25°	0.0	0.0	5.3	10.6	10.6	15.9	21.3	21.3	26.6	26.6	31.9
27.5°	0.0	0.0	5.3	5.3	10.6	10.6	15.9	15.9	21.3	21.3	26.6
30°	0.0	0.0	5.3	5.3	10.6	10.6	15.9	15.9	21.3	21.3	21.3
32.5°	0.0	0.0	0.0	5.3	5.3	5.3	10.6	10.6	15.9	15.9	21.3
35°	0.0	0.0	0.0	5.3	5.3	5.3	10.6	10.6	15.9	15.9	15.9
37.5°	0.0	0.0	0.0	5.3	5.3	5.3	10.6	10.6	10.6	10.6	15.9
40°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.6	10.6	10.6
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.6	10.6	10.6
45°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.6	10.6	10.6
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.6	10.6	10.6
50°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.6	10.6	10.6
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
55°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
75°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.6	10.6	10.6
80°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.6	10.6	10.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	10.6
85°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	69.1	69.1
5°	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	63.8	63.8
7.5°	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	63.8	63.8
10°	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8
12.5°	58.5	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8
15°	58.5	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8
17.5°	53.2	58.5	58.5	58.5	63.8	63.8	63.8	63.8	63.8	63.8	63.8
20°	47.8	53.2	53.2	53.2	58.5	58.5	58.5	58.5	63.8	63.8	63.8
22.5°	42.5	47.8	47.8	47.8	53.2	53.2	53.2	53.2	58.5	58.5	58.5
25°	37.2	37.2	42.5	42.5	47.8	47.8	47.8	47.8	47.8	47.8	47.8
27.5°	26.6	31.9	31.9	31.9	37.2	37.2	37.2	37.2	42.5	42.5	42.5
30°	26.6	26.6	26.6	26.6	31.9	31.9	31.9	31.9	37.2	37.2	37.2
32.5°	21.3	26.6	26.6	26.6	31.9	31.9	31.9	31.9	37.2	37.2	37.2
35°	21.3	21.3	21.3	21.3	26.6	26.6	26.6	26.6	31.9	31.9	31.9
37.5°	15.9	21.3	21.3	21.3	26.6	26.6	26.6	26.6	31.9	31.9	31.9
40°	15.9	15.9	15.9	15.9	21.3	21.3	21.3	21.3	26.6	26.6	26.6
42.5°	15.9	15.9	15.9	15.9	21.3	21.3	21.3	21.3	26.6	26.6	26.6
45°	15.9	15.9	15.9	15.9	21.3	21.3	21.3	21.3	26.6	26.6	26.6
47.5°	15.9	15.9	15.9	15.9	21.3	21.3	21.3	21.3	26.6	26.6	26.6
50°	15.9	15.9	15.9	15.9	21.3	21.3	21.3	21.3	26.6	26.6	26.6
52.5°	10.6	10.6	10.6	10.6	15.9	15.9	15.9	15.9	21.3	21.3	21.3
55°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	15.9	15.9	15.9
57.5°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	15.9	15.9	15.9
60°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
62.5°	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
65°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	5.3	5.3
67.5°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
70°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
72.5°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
75°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
77.5°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
80°	15.9	15.9	15.9	15.9	15.9	10.6	10.6	10.6	10.6	10.6	10.6
82.5°	10.6	15.9	15.9	15.9	15.9	10.6	10.6	10.6	10.6	10.6	10.6
85°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
87.5°	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	69.1	69.1	63.8	63.8	63.8	63.8	63.8	63.8	63.8	69.1	69.1
5°	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	69.1	69.1
7.5°	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	69.1	69.1
10°	63.8	63.8	63.8	63.8	58.5	58.5	63.8	63.8	63.8	69.1	69.1
12.5°	63.8	63.8	63.8	63.8	58.5	58.5	63.8	63.8	69.1	69.1	74.4
15°	63.8	63.8	58.5	58.5	58.5	58.5	63.8	63.8	69.1	69.1	74.4
17.5°	63.8	63.8	58.5	58.5	58.5	58.5	63.8	63.8	69.1	69.1	74.4
20°	63.8	63.8	58.5	58.5	58.5	58.5	58.5	58.5	63.8	69.1	69.1
22.5°	58.5	58.5	58.5	58.5	53.2	53.2	58.5	58.5	63.8	69.1	69.1
25°	47.8	53.2	53.2	53.2	53.2	53.2	58.5	58.5	63.8	69.1	69.1
27.5°	42.5	47.8	47.8	47.8	47.8	53.2	53.2	58.5	63.8	69.1	69.1
30°	37.2	42.5	42.5	42.5	47.8	53.2	53.2	58.5	63.8	69.1	69.1
32.5°	37.2	42.5	42.5	42.5	47.8	47.8	53.2	53.2	58.5	63.8	69.1
35°	37.2	37.2	42.5	42.5	42.5	47.8	47.8	53.2	58.5	63.8	69.1
37.5°	37.2	37.2	42.5	42.5	42.5	47.8	47.8	53.2	58.5	63.8	69.1
40°	31.9	37.2	37.2	42.5	42.5	47.8	47.8	53.2	58.5	69.1	74.4
42.5°	31.9	31.9	37.2	37.2	42.5	47.8	47.8	53.2	58.5	69.1	74.4
45°	31.9	37.2	37.2	42.5	47.8	53.2	53.2	58.5	63.8	69.1	74.4
47.5°	31.9	37.2	37.2	42.5	53.2	53.2	58.5	58.5	63.8	69.1	74.4
50°	31.9	37.2	37.2	42.5	58.5	58.5	58.5	58.5	63.8	69.1	74.4
52.5°	26.6	31.9	31.9	37.2	47.8	53.2	58.5	63.8	69.1	74.4	79.7
55°	21.3	26.6	26.6	31.9	42.5	47.8	58.5	69.1	74.4	79.7	85.1
57.5°	21.3	21.3	26.6	26.6	37.2	47.8	63.8	74.4	79.7	85.1	90.4
60°	15.9	15.9	21.3	21.3	31.9	42.5	58.5	74.4	79.7	90.4	95.7
62.5°	10.6	15.9	15.9	21.3	26.6	42.5	58.5	74.4	85.1	95.7	101.0
65°	10.6	10.6	15.9	15.9	26.6	37.2	53.2	63.8	79.7	95.7	111.6
67.5°	15.9	15.9	21.3	21.3	26.6	37.2	53.2	63.8	79.7	101.0	117.0
70°	15.9	15.9	21.3	21.3	31.9	42.5	53.2	63.8	79.7	101.0	117.0
72.5°	15.9	15.9	21.3	21.3	31.9	37.2	47.8	58.5	74.4	90.4	106.3
75°	10.6	15.9	15.9	15.9	26.6	31.9	42.5	53.2	69.1	85.1	101.0
77.5°	10.6	10.6	10.6	10.6	21.3	26.6	37.2	42.5	58.5	74.4	90.4
80°	10.6	10.6	10.6	10.6	15.9	21.3	31.9	37.2	53.2	69.1	85.1
82.5°	10.6	10.6	5.3	5.3	10.6	15.9	21.3	26.6	42.5	53.2	69.1
85°	10.6	10.6	5.3	5.3	5.3	10.6	10.6	15.9	21.3	26.6	31.9
87.5°	10.6	10.6	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	69.1	69.1	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4
5°	69.1	74.4	74.4	79.7	79.7	79.7	85.1	85.1	85.1	85.1	85.1
7.5°	69.1	74.4	74.4	79.7	79.7	79.7	85.1	85.1	85.1	90.4	90.4
10°	69.1	74.4	74.4	79.7	79.7	85.1	90.4	90.4	95.7	95.7	95.7
12.5°	74.4	79.7	79.7	85.1	85.1	90.4	95.7	95.7	101.0	106.3	106.3
15°	74.4	79.7	85.1	85.1	90.4	95.7	101.0	101.0	106.3	111.6	117.0
17.5°	74.4	79.7	85.1	85.1	90.4	95.7	106.3	111.6	117.0	127.6	132.9
20°	74.4	79.7	85.1	85.1	90.4	101.0	106.3	117.0	122.3	132.9	143.5
22.5°	74.4	79.7	85.1	90.4	95.7	106.3	117.0	122.3	132.9	148.9	159.5
25°	74.4	79.7	85.1	90.4	95.7	106.3	117.0	127.6	138.2	159.5	180.8
27.5°	74.4	79.7	90.4	95.7	101.0	111.6	127.6	138.2	148.9	186.1	223.3
30°	74.4	79.7	90.4	95.7	101.0	117.0	132.9	143.5	159.5	223.3	281.8
32.5°	74.4	85.1	90.4	101.0	106.3	122.3	143.5	159.5	175.4	265.8	350.9
35°	74.4	85.1	90.4	101.0	106.3	127.6	148.9	170.1	191.4	324.3	457.2
37.5°	74.4	85.1	90.4	101.0	106.3	138.2	170.1	202.0	233.9	372.2	510.4
40°	79.7	90.4	95.7	106.3	111.6	143.5	175.4	207.3	239.2	377.5	515.7
42.5°	79.7	90.4	95.7	106.3	111.6	138.2	170.1	196.7	223.3	377.5	531.7
45°	79.7	90.4	101.0	106.3	117.0	143.5	170.1	191.4	218.0	414.7	606.1
47.5°	79.7	90.4	101.0	106.3	117.0	143.5	170.1	196.7	223.3	547.6	866.6
50°	79.7	90.4	101.0	106.3	117.0	148.9	180.8	212.7	244.6	818.8	1392.9
52.5°	85.1	90.4	101.0	106.3	111.6	148.9	186.1	223.3	260.5	1063.3	1860.8
55°	90.4	95.7	101.0	106.3	111.6	159.5	207.3	255.2	303.0	1143.1	1977.8
57.5°	95.7	101.0	106.3	106.3	111.6	170.1	233.9	292.4	350.9	1137.8	1919.3
60°	101.0	106.3	111.6	117.0	122.3	180.8	244.6	303.0	361.5	1031.4	1701.3
62.5°	111.6	122.3	132.9	138.2	148.9	207.3	260.5	319.0	372.2	845.3	1313.2
65°	127.6	138.2	143.5	154.2	159.5	212.7	271.1	324.3	377.5	701.8	1020.8
67.5°	132.9	143.5	148.9	159.5	164.8	218.0	271.1	324.3	377.5	595.5	808.1
70°	132.9	143.5	154.2	159.5	170.1	223.3	271.1	324.3	372.2	515.7	659.3
72.5°	122.3	138.2	148.9	164.8	175.4	223.3	265.8	313.7	356.2	457.2	558.2
75°	117.0	138.2	154.2	175.4	191.4	223.3	260.5	292.4	324.3	398.7	473.2
77.5°	106.3	132.9	159.5	186.1	212.7	233.9	249.9	271.1	287.1	334.9	382.8
80°	101.0	127.6	154.2	180.8	207.3	218.0	223.3	233.9	239.2	244.6	249.9
82.5°	79.7	101.0	122.3	138.2	159.5	148.9	143.5	132.9	122.3	117.0	111.6
85°	37.2	42.5	42.5	47.8	47.8	47.8	42.5	42.5	37.2	31.9	26.6
87.5°	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	74.4	74.4	74.4	74.4	69.1	69.1	69.1	69.1	63.8	63.8	63.8
5°	85.1	85.1	85.1	85.1	79.7	79.7	79.7	79.7	74.4	74.4	74.4
7.5°	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4
10°	101.0	101.0	101.0	106.3	106.3	106.3	106.3	106.3	106.3	106.3	106.3
12.5°	111.6	111.6	117.0	117.0	122.3	122.3	127.6	127.6	132.9	132.9	132.9
15°	122.3	127.6	132.9	138.2	138.2	143.5	148.9	154.2	159.5	164.8	170.1
17.5°	143.5	148.9	159.5	170.1	180.8	191.4	207.3	228.6	244.6	260.5	281.8
20°	159.5	175.4	207.3	244.6	276.5	308.4	388.1	467.9	547.6	627.4	707.1
22.5°	191.4	223.3	329.6	441.3	547.6	653.9	903.8	1153.7	1398.3	1648.1	1871.4
25°	255.2	324.3	568.9	813.4	1052.7	1297.2	1743.8	2195.8	2642.3	3088.9	3503.6
27.5°	350.9	478.5	877.2	1281.3	1680.0	2078.8	2727.4	3381.4	4030.0	4683.9	5263.4
30°	489.1	696.5	1291.9	1892.7	2488.2	3083.6	3902.4	4726.5	5545.2	6364.0	6895.6
32.5°	664.6	972.9	1727.9	2482.8	3237.8	3992.8	4896.6	5800.4	6698.9	7602.7	8166.3
35°	850.7	1244.1	2153.2	3067.7	3976.8	4891.3	5842.9	6794.6	7746.3	8697.9	9389.1
37.5°	957.0	1403.6	2482.8	3562.1	4636.1	5715.3	6757.4	7804.8	8846.8	9888.9	10728.9
40°	1058.0	1595.0	2839.1	4083.1	5327.2	6571.3	7788.8	9006.3	10223.8	11441.3	12520.6
42.5°	1206.9	1882.1	3333.5	4784.9	6231.0	7682.5	9282.8	10888.4	12488.7	14089.0	15747.8
45°	1515.2	2424.4	4306.4	6188.5	8065.3	9947.3	12217.5	14493.0	16763.2	19038.7	21165.4
47.5°	2259.6	3647.2	6215.1	8783.0	11350.9	13918.8	16534.6	19150.4	21766.1	24381.9	26912.6
50°	3498.3	5598.4	8809.6	12020.8	15226.7	18438.0	21048.4	23658.8	26264.0	28874.4	31389.2
52.5°	4662.7	7464.5	10915.0	14370.8	17821.2	21277.0	23589.7	25902.4	28215.2	30527.9	32962.9
55°	5061.4	8139.7	11632.7	15131.0	18624.0	22122.4	24350.0	26583.0	28810.6	31038.3	33563.7
57.5°	4710.5	7501.7	11021.3	14540.9	18055.2	21574.7	24062.9	26556.4	29044.6	31538.0	34244.2
60°	3944.9	6183.2	9878.2	13578.6	17273.6	20968.6	23775.8	26583.0	29390.1	32197.3	34898.1
62.5°	3126.2	4933.8	8846.8	12759.8	16672.8	20585.9	23440.9	26301.2	29156.2	32011.2	34084.7
65°	2397.8	3774.8	7624.0	11478.5	15327.7	19182.3	21521.6	23866.2	26205.5	28550.1	29985.6
67.5°	1781.1	2754.0	6119.4	9490.1	12855.5	16220.9	17943.5	19671.4	21394.0	23121.9	24238.4
70°	1313.2	1961.8	4253.3	6544.7	8830.9	11122.3	12701.3	14280.4	15854.1	17433.1	18592.1
72.5°	909.1	1254.7	2626.4	4003.4	5375.1	6746.8	8347.1	9947.3	11542.3	13142.6	14461.1
75°	622.0	770.9	1414.2	2057.5	2700.8	3344.1	4556.3	5768.5	6980.7	8192.9	8889.3
77.5°	462.5	542.3	733.7	930.4	1121.8	1313.2	1547.1	1781.1	2015.0	2248.9	2552.0
80°	255.2	255.2	281.8	303.0	329.6	350.9	414.7	483.8	547.6	616.7	701.8
82.5°	117.0	122.3	132.9	143.5	148.9	159.5	170.1	180.8	191.4	202.0	202.0
85°	31.9	37.2	37.2	31.9	31.9	26.6	26.6	31.9	31.9	31.9	31.9
87.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	63.8	58.5	58.5	58.5	53.2	53.2	53.2	53.2	53.2	53.2	53.2
5°	74.4	74.4	74.4	74.4	69.1	69.1	69.1	69.1	69.1	63.8	63.8
7.5°	90.4	85.1	85.1	85.1	85.1	85.1	85.1	85.1	85.1	79.7	79.7
10°	106.3	106.3	106.3	106.3	106.3	106.3	106.3	106.3	106.3	101.0	101.0
12.5°	132.9	132.9	132.9	132.9	138.2	138.2	132.9	132.9	132.9	127.6	127.6
15°	175.4	180.8	186.1	186.1	191.4	191.4	191.4	186.1	186.1	180.8	175.4
17.5°	297.7	313.7	334.9	356.2	377.5	393.4	393.4	382.8	372.2	361.5	350.9
20°	792.2	871.9	957.0	1042.1	1132.4	1196.2	1153.7	1121.8	1089.9	1052.7	1020.8
22.5°	2100.1	2323.4	2552.0	2711.5	2871.0	2982.6	2892.2	2716.8	2541.3	2371.2	2195.8
25°	3918.3	4327.7	4742.4	4912.5	5088.0	5215.6	5157.1	4891.3	4625.4	4364.9	4099.1
27.5°	5842.9	6417.1	6996.6	7145.5	7294.4	7406.0	7384.8	7039.2	6693.6	6348.0	6002.4
30°	7427.3	7958.9	8490.6	8639.5	8788.3	8889.3	8777.7	8432.1	8086.5	7741.0	7395.4
32.5°	8735.2	9298.7	9867.6	10064.3	10261.0	10393.9	10261.0	9846.3	9431.6	9022.3	8607.6
35°	10080.3	10766.1	11457.3	11707.1	11957.0	12116.5	11893.2	11382.8	10872.4	10367.4	9857.0
37.5°	11568.9	12403.6	13243.6	13583.9	13929.5	14168.7	13998.6	13360.6	12717.3	12079.3	11436.0
40°	13605.2	14684.4	15769.0	16380.4	16986.5	17417.2	17114.1	16375.1	15630.8	14891.8	14147.5
42.5°	17411.8	19070.6	20729.4	21606.6	22478.6	23111.2	22771.0	21861.8	20952.7	20043.6	19134.4
45°	23292.0	25413.3	27540.0	28821.3	30107.9	31054.2	30660.8	29517.7	28369.3	27226.3	26083.2
47.5°	29443.3	31974.0	34504.7	35525.5	36551.6	37349.1	37253.4	35828.5	34403.7	32984.2	31559.3
50°	33909.2	36424.0	38938.7	39816.0	40698.5	41352.5	41107.9	39295.0	37476.7	35663.7	33845.4
52.5°	35397.9	37827.6	40262.6	41309.9	42357.3	43138.8	42841.1	40799.5	38758.0	36721.7	34680.1
55°	36089.0	38614.4	41139.8	42415.8	43697.1	44632.8	44202.2	41963.9	39720.3	37482.0	35238.4
57.5°	36950.3	39656.5	42362.6	43760.9	45159.2	46169.3	45595.1	43277.1	40959.0	38646.3	36328.3
60°	37599.0	40294.5	42995.3	44117.1	45244.2	46031.1	45478.2	43223.9	40964.4	38710.1	36455.9
62.5°	36163.5	38236.9	40310.4	41145.1	41979.8	42585.9	42272.2	40135.0	37997.7	35860.4	33723.2
65°	31426.4	32861.9	34302.7	34866.2	35424.5	35855.1	35759.4	33957.1	32154.8	30357.8	28555.4
67.5°	25360.2	26476.6	27598.4	28395.9	29198.7	29820.8	29751.7	28108.8	26466.0	24823.2	23180.4
70°	19756.5	20915.5	22074.5	23079.3	24089.5	24871.0	24770.0	23244.2	21713.0	20187.1	18655.9
72.5°	15785.0	17103.5	18422.0	18996.2	19570.4	19974.4	19676.7	18523.0	17364.0	16210.3	15051.3
75°	9585.8	10277.0	10973.5	10968.1	10968.1	10904.3	10606.6	9947.3	9288.1	8628.8	7969.6
77.5°	2855.0	3158.1	3461.1	3753.5	4051.2	4274.5	4216.1	3870.5	3519.6	3174.0	2823.1
80°	786.9	866.6	951.7	988.9	1026.1	1074.0	1196.2	1111.2	1026.1	946.4	861.3
82.5°	202.0	202.0	202.0	196.7	191.4	180.8	164.8	154.2	143.5	132.9	122.3
85°	31.9	26.6	26.6	26.6	21.3	21.3	21.3	21.3	15.9	15.9	10.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
2.5°	53.2	53.2	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	42.5
5°	63.8	63.8	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	53.2
7.5°	79.7	79.7	74.4	74.4	74.4	74.4	69.1	69.1	69.1	69.1	63.8
10°	101.0	95.7	95.7	90.4	90.4	90.4	85.1	85.1	85.1	79.7	79.7
12.5°	127.6	122.3	122.3	117.0	111.6	111.6	106.3	101.0	95.7	95.7	90.4
15°	170.1	164.8	159.5	154.2	148.9	138.2	132.9	122.3	117.0	111.6	106.3
17.5°	324.3	297.7	271.1	244.6	223.3	202.0	180.8	159.5	148.9	138.2	127.6
20°	903.8	781.5	664.6	547.6	473.2	398.7	324.3	249.9	218.0	191.4	159.5
22.5°	1956.5	1711.9	1472.7	1228.1	1031.4	840.0	643.3	446.6	372.2	303.0	228.6
25°	3636.6	3168.7	2706.1	2238.3	1866.1	1494.0	1121.8	749.6	611.4	473.2	334.9
27.5°	5396.3	4790.3	4184.2	3578.1	2987.9	2392.5	1797.0	1206.9	967.6	733.7	494.4
30°	6752.1	6108.8	5470.8	4827.5	4083.1	3338.8	2589.2	1844.9	1467.4	1089.9	707.1
32.5°	7916.4	7219.9	6528.8	5832.3	4971.0	4109.7	3248.4	2387.2	1914.0	1440.8	962.3
35°	9070.1	8277.9	7491.1	6698.9	5773.8	4848.7	3923.6	2998.6	2397.8	1797.0	1190.9
37.5°	10473.7	9506.1	8543.8	7581.5	6629.8	5683.4	4731.8	3780.1	3014.5	2254.2	1488.6
40°	12919.3	11685.9	10457.7	9224.3	8113.1	7007.3	5896.1	4784.9	3822.6	2860.3	1892.7
42.5°	17587.3	16040.2	14498.4	12951.2	11414.7	9878.2	8336.4	6799.9	5428.2	4061.9	2690.2
45°	24100.1	22117.0	20139.3	18156.2	16263.5	14376.1	12483.4	10590.7	8506.6	6422.4	4333.0
47.5°	29390.1	27215.6	25046.5	22872.0	20771.9	18677.2	16577.1	14477.1	11808.2	9144.5	6475.6
50°	31777.3	29703.8	27635.7	25562.2	23456.8	21346.1	19235.4	17130.1	14067.7	11010.7	7948.3
52.5°	32580.1	30474.7	28374.7	26269.3	24179.9	22090.5	20001.0	17911.6	14727.0	11547.6	8363.0
55°	33021.4	30799.0	28582.0	26359.7	24110.8	21856.5	19602.3	17353.4	14184.7	11021.3	7852.6
57.5°	33914.6	31495.5	29081.8	26662.7	24100.1	21537.5	18969.6	16407.0	13280.9	10154.7	7028.5
60°	34079.4	31697.5	29321.0	26944.5	24110.8	21277.0	18438.0	15604.2	12499.3	9399.7	6294.8
62.5°	31734.8	29746.3	27763.3	25774.9	22935.8	20096.7	17252.3	14413.3	11441.3	8469.3	5492.0
65°	26838.2	25120.9	23409.0	21691.7	19373.7	17061.0	14742.9	12424.9	9771.9	7124.2	4471.3
67.5°	21500.3	19820.3	18145.5	16465.5	14721.7	12983.1	11239.3	9495.4	7448.5	5401.7	3354.8
70°	17045.0	15428.8	13817.8	12201.6	10659.8	9112.6	7565.5	6023.7	4753.0	3487.7	2217.0
72.5°	13509.5	11962.3	10420.5	8873.4	7475.1	6076.9	4678.6	3280.3	2647.7	2020.3	1387.6
75°	7166.8	6364.0	5566.5	4763.7	3976.8	3184.6	2392.5	1605.6	1355.7	1105.9	850.7
77.5°	2472.2	2121.3	1775.7	1424.8	1185.6	946.4	707.1	467.9	441.3	420.0	393.4
80°	749.6	638.0	526.3	414.7	366.8	319.0	271.1	223.3	207.3	191.4	170.1
82.5°	117.0	106.3	101.0	90.4	85.1	85.1	79.7	74.4	63.8	58.5	47.8
85°	10.6	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	47.8	47.8
2.5°	42.5	42.5
5°	53.2	53.2
7.5°	63.8	63.8
10°	74.4	74.4
12.5°	85.1	85.1
15°	101.0	95.7
17.5°	117.0	111.6
20°	127.6	117.0
22.5°	154.2	132.9
25°	196.7	164.8
27.5°	255.2	202.0
30°	329.6	255.2
32.5°	489.1	356.2
35°	590.1	430.6
37.5°	723.1	499.8
40°	930.4	606.1
42.5°	1318.5	824.1
45°	2248.9	1366.4
47.5°	3812.0	2328.7
50°	4886.0	2987.9
52.5°	5183.7	3168.7
55°	4689.2	2908.2
57.5°	3902.4	2472.2
60°	3195.3	2036.3
62.5°	2520.1	1610.9
65°	1818.3	1217.5
67.5°	1307.9	935.7
70°	951.7	733.7
72.5°	755.0	611.4
75°	600.8	510.4
77.5°	372.2	340.3
80°	154.2	143.5
82.5°	37.2	31.9
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066474

CATALOG NUMBER: NVN-SA6B-722-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-2

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-722-U-5WQ

Data in this report applies to families of products including GSS-SB1A-722-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-2
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-722-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2200K CCT 26 LEDS

Spectral Parameters

CCT (K):	2160	CRI (Ra):	71.9		
CIE u':	0.2927	R1:	68.7	R9:	-17.8
CIE v':	0.5388	R2:	82.6	R10:	60.5
Duv:	0.0015	R3:	95.5	R11:	60.2
CIE x:	0.5130	R4:	66.4	R12:	48.2
CIE y:	0.4197	R5:	65.4	R13:	70.7
CIE z:	0.0674	R6:	75.9	R14:	96.8
Peak Wavelength (nm):	609	R7:	77.2	R15:	61.8
Dominant Wavelength (nm):	587	R8:	43.5		
Purity:	79.96089				
Rf:	70.6				
Rg:	97.6				



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-2

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-2

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2200K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-2

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 0.8

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.21

λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	27	NR	620	966	NR	750	46	NR	880	1	NR
365	0	NR	495	42	NR	625	930	NR	755	39	NR	885	1	NR
370	0	NR	500	67	NR	630	888	NR	760	34	NR	890	1	NR
375	0	NR	505	101	NR	635	835	NR	765	30	NR	895	1	NR
380	0	NR	510	139	NR	640	778	NR	770	26	NR	900	1	NR
385	0	NR	515	183	NR	645	717	NR	775	22	NR	905	1	NR
390	0	NR	520	224	NR	650	656	NR	780	19	NR	910	1	NR
395	0	NR	525	262	NR	655	595	NR	785	17	NR	915	1	NR
400	1	NR	530	299	NR	660	536	NR	790	15	NR	920	1	NR
405	3	NR	535	332	NR	665	480	NR	795	13	NR	925	1	NR
410	7	NR	540	365	NR	670	425	NR	800	11	NR	930	1	NR
415	17	NR	545	400	NR	675	376	NR	805	10	NR	935	0	NR
420	36	NR	550	437	NR	680	332	NR	810	8	NR	940	0	NR
425	67	NR	555	479	NR	685	291	NR	815	8	NR	945	0	NR
430	105	NR	560	525	NR	690	255	NR	820	7	NR	950	0	NR
435	141	NR	565	579	NR	695	221	NR	825	6	NR	955	0	NR
440	169	NR	570	639	NR	700	192	NR	830	5	NR	960	0	NR
445	173	NR	575	703	NR	705	167	NR	835	4	NR	965	0	NR
450	136	NR	580	769	NR	710	144	NR	840	4	NR	970	0	NR
455	80	NR	585	832	NR	715	125	NR	845	3	NR	975	0	NR
460	45	NR	590	890	NR	720	109	NR	850	3	NR	980	0	NR
465	32	NR	595	937	NR	725	94	NR	855	3	NR	985	0	NR
470	23	NR	600	972	NR	730	81	NR	860	2	NR	990	0	NR
475	18	NR	605	992	NR	735	70	NR	865	2	NR	995	0	NR
480	18	NR	610	998	NR	740	61	NR	870	2	NR	1000	0	NR
485	20	NR	615	990	NR	745	53	NR	875	2	NR			

REPORT NUMBER: SP1-2407-184-2

TM-30-18

Summary

$R_f = 70.6$
 $R_g = 97.6$
 $CIE R_a = 71.9$
 $R_g = -17.8$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 87	CES26 = 60	CES51 = 74	CES76 = 58
CES02 = 65	CES27 = 77	CES52 = 77	CES77 = 82
CES03 = 32	CES28 = 85	CES53 = 65	CES78 = 65
CES04 = 72	CES29 = 50	CES54 = 77	CES79 = 86
CES05 = 52	CES30 = 49	CES55 = 74	CES80 = 85
CES06 = 53	CES31 = 55	CES56 = 64	CES81 = 61
CES07 = 44	CES32 = 55	CES57 = 60	CES82 = 93
CES08 = 43	CES33 = 55	CES58 = 64	CES83 = 83
CES09 = 29	CES34 = 75	CES59 = 84	CES84 = 93
CES10 = 79	CES35 = 88	CES60 = 89	CES85 = 81
CES11 = 62	CES36 = 78	CES61 = 84	CES86 = 55
CES12 = 68	CES37 = 82	CES62 = 68	CES87 = 79
CES13 = 45	CES38 = 54	CES63 = 68	CES88 = 72
CES14 = 75	CES39 = 90	CES64 = 69	CES89 = 62
CES15 = 72	CES40 = 86	CES65 = 66	CES90 = 67
CES16 = 49	CES41 = 75	CES66 = 64	CES91 = 89
CES17 = 51	CES42 = 83	CES67 = 63	CES92 = 67
CES18 = 57	CES43 = 68	CES68 = 71	CES93 = 78
CES19 = 74	CES44 = 98	CES69 = 81	CES94 = 52
CES20 = 68	CES45 = 76	CES70 = 65	CES95 = 76
CES21 = 89	CES46 = 68	CES71 = 64	CES96 = 78
CES22 = 81	CES47 = 60	CES72 = 88	CES97 = 76
CES23 = 92	CES48 = 47	CES73 = 59	CES98 = 71
CES24 = 92	CES49 = 65	CES74 = 85	CES99 = 65
CES25 = 74	CES50 = 74	CES75 = 66	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)