

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066483

Luminaire Tested: **NVN-SA2C-727-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066483
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA2C-727-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1050mA 2xLight Square PACKAGE
70CRI 2700K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (28) 2700K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8069.2 lumens
Efficiency: N/A
Efficacy: 83.9 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 96.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 1.6 fc
 Type III - Short - N/A

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	48.0	0.0	48.0
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	8021.1	0.0	8021.1
	% Fixture	99.4	0.0	99.4
Total	Lumens	8069.1	0.0	8069.1
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2.4	0.0
10°-20°	11.8	0.1
20°-30°	150.6	1.9
30°-40°	507.6	6.3
40°-50°	1532.9	19.0
50°-60°	2704.5	33.5
60°-70°	2382.7	29.5
70°-80°	758.5	9.4
80°-90°	18.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	8069.1	100.0
0°-180°	8069.2	100.0



REPORT NUMBER: P1066483


CATALOG NUMBER: NVN-SA2C-727-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	157.6	2.0			
FM	(30°-60°)	4726.4	58.6			
FH	(60°-80°)	3122.3	38.7			G2/5000
FVH	(80°-90°)	14.9	0.2			G1/100
BL	(0°-30°)	7.2	0.1	B0/110		
BM	(30°-60°)	18.6	0.2	B0/220		
BH	(60°-80°)	18.8	0.2	B0/110		G0/110
BVH	(80°-90°)	3.4	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2	17.7
5°	25.3	25.3	25.3	22.8	22.8	22.8	20.2	20.2	20.2	20.2	20.2
7.5°	30.4	27.8	27.8	25.3	25.3	25.3	22.8	22.8	22.8	22.8	20.2
10°	35.4	32.9	32.9	30.4	30.4	27.8	27.8	25.3	25.3	22.8	22.8
12.5°	40.5	38.0	35.4	32.9	32.9	30.4	30.4	27.8	27.8	25.3	25.3
15°	45.5	43.0	40.5	38.0	35.4	35.4	32.9	30.4	27.8	27.8	25.3
17.5°	53.1	48.1	45.5	40.5	38.0	35.4	32.9	30.4	30.4	27.8	27.8
20°	55.7	50.6	48.1	43.0	40.5	38.0	35.4	32.9	30.4	30.4	27.8
22.5°	65.8	55.7	53.1	48.1	45.5	43.0	38.0	35.4	32.9	30.4	27.8
25°	81.0	65.8	58.2	50.6	48.1	43.0	40.5	35.4	32.9	30.4	27.8
27.5°	98.7	73.4	65.8	55.7	50.6	45.5	40.5	35.4	32.9	30.4	27.8
30°	121.5	86.0	73.4	60.7	55.7	50.6	43.0	38.0	35.4	32.9	27.8
32.5°	169.5	106.3	86.0	65.8	58.2	53.1	45.5	38.0	35.4	32.9	27.8
35°	205.0	129.1	103.7	75.9	65.8	58.2	48.1	38.0	35.4	32.9	27.8
37.5°	237.9	131.6	106.3	81.0	70.9	60.7	48.1	38.0	35.4	32.9	27.8
40°	291.0	136.6	106.3	75.9	68.3	58.2	50.6	40.5	38.0	32.9	30.4
42.5°	392.2	156.9	113.9	70.9	63.3	58.2	50.6	43.0	38.0	35.4	30.4
45°	652.9	232.8	154.4	73.4	65.8	58.2	50.6	43.0	40.5	35.4	32.9
47.5°	1110.9	404.9	240.4	75.9	68.3	58.2	50.6	40.5	38.0	35.4	30.4
50°	1422.1	518.7	303.7	88.6	75.9	65.8	53.1	40.5	38.0	35.4	32.9
52.5°	1510.7	551.6	329.0	103.7	88.6	73.4	55.7	40.5	38.0	38.0	35.4
55°	1384.2	536.5	329.0	121.5	101.2	83.5	63.3	43.0	40.5	40.5	38.0
57.5°	1176.7	496.0	313.8	131.6	111.3	88.6	68.3	45.5	43.0	43.0	40.5
60°	969.2	417.5	283.4	146.8	124.0	101.2	78.4	55.7	53.1	50.6	45.5
62.5°	769.3	336.6	248.0	156.9	134.1	108.8	86.0	60.7	58.2	55.7	53.1
65°	579.5	293.5	230.3	164.5	139.2	113.9	88.6	63.3	60.7	60.7	58.2
67.5°	445.4	268.2	220.2	169.5	144.2	118.9	93.6	68.3	65.8	63.3	60.7
70°	351.7	248.0	207.5	167.0	144.2	121.5	96.2	73.4	68.3	65.8	60.7
72.5°	293.5	225.2	192.3	159.4	141.7	124.0	106.3	88.6	78.4	70.9	60.7
75°	245.5	202.4	174.6	144.2	131.6	121.5	108.8	96.2	83.5	70.9	58.2
77.5°	162.0	146.8	134.1	121.5	113.9	106.3	96.2	88.6	75.9	65.8	53.1
80°	68.3	63.3	65.8	65.8	65.8	65.8	63.3	63.3	55.7	48.1	38.0
82.5°	15.2	12.7	15.2	15.2	15.2	15.2	12.7	12.7	12.7	10.1	10.1
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7
5°	20.2	20.2	20.2	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7
7.5°	20.2	20.2	20.2	17.7	17.7	17.7	17.7	15.2	15.2	15.2	15.2
10°	20.2	20.2	20.2	17.7	17.7	17.7	17.7	15.2	15.2	15.2	15.2
12.5°	22.8	22.8	20.2	20.2	17.7	17.7	17.7	15.2	15.2	15.2	15.2
15°	22.8	22.8	20.2	20.2	17.7	17.7	17.7	15.2	15.2	15.2	15.2
17.5°	25.3	22.8	22.8	20.2	17.7	17.7	17.7	15.2	15.2	15.2	15.2
20°	25.3	22.8	22.8	20.2	17.7	17.7	17.7	15.2	15.2	15.2	15.2
22.5°	25.3	22.8	22.8	20.2	17.7	17.7	15.2	15.2	12.7	12.7	10.1
25°	25.3	22.8	22.8	20.2	17.7	17.7	15.2	15.2	12.7	10.1	10.1
27.5°	25.3	22.8	22.8	20.2	17.7	15.2	15.2	12.7	10.1	7.6	7.6
30°	25.3	22.8	22.8	20.2	17.7	15.2	12.7	10.1	7.6	7.6	5.1
32.5°	25.3	22.8	20.2	17.7	15.2	12.7	12.7	10.1	7.6	5.1	5.1
35°	25.3	22.8	20.2	17.7	15.2	12.7	12.7	10.1	7.6	5.1	5.1
37.5°	25.3	22.8	20.2	17.7	15.2	12.7	10.1	7.6	5.1	5.1	2.5
40°	25.3	22.8	20.2	17.7	15.2	12.7	10.1	7.6	5.1	5.1	2.5
42.5°	25.3	22.8	20.2	17.7	15.2	12.7	10.1	7.6	5.1	5.1	2.5
45°	27.8	25.3	22.8	17.7	15.2	12.7	12.7	10.1	7.6	5.1	5.1
47.5°	27.8	25.3	22.8	17.7	15.2	12.7	12.7	10.1	7.6	5.1	5.1
50°	30.4	27.8	25.3	20.2	17.7	15.2	12.7	7.6	5.1	5.1	2.5
52.5°	32.9	30.4	27.8	25.3	22.8	17.7	12.7	7.6	2.5	2.5	2.5
55°	35.4	32.9	32.9	30.4	27.8	20.2	15.2	7.6	0.0	0.0	0.0
57.5°	38.0	35.4	35.4	32.9	30.4	22.8	15.2	7.6	0.0	0.0	0.0
60°	43.0	40.5	38.0	32.9	30.4	22.8	15.2	7.6	0.0	0.0	0.0
62.5°	50.6	45.5	38.0	32.9	25.3	20.2	12.7	7.6	0.0	0.0	0.0
65°	55.7	48.1	40.5	30.4	22.8	17.7	12.7	5.1	0.0	0.0	0.0
67.5°	58.2	48.1	40.5	30.4	20.2	15.2	10.1	5.1	0.0	0.0	0.0
70°	55.7	45.5	38.0	27.8	17.7	12.7	10.1	5.1	0.0	0.0	0.0
72.5°	50.6	43.0	32.9	25.3	15.2	12.7	7.6	5.1	0.0	0.0	0.0
75°	45.5	38.0	27.8	20.2	10.1	7.6	5.1	2.5	0.0	0.0	0.0
77.5°	40.5	32.9	22.8	15.2	5.1	5.1	2.5	2.5	0.0	0.0	0.0
80°	30.4	22.8	15.2	7.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	7.6	5.1	5.1	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	15.2	15.2	15.2	15.2	15.2	15.2	15.2	15.2	15.2	15.2	15.2
5°	15.2	15.2	15.2	15.2	12.7	12.7	12.7	12.7	12.7	12.7	12.7
7.5°	15.2	15.2	15.2	15.2	12.7	12.7	12.7	12.7	10.1	10.1	10.1
10°	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	10.1	10.1	10.1
12.5°	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	10.1	10.1	10.1
15°	12.7	12.7	12.7	12.7	12.7	12.7	12.7	10.1	10.1	7.6	7.6
17.5°	12.7	12.7	12.7	12.7	10.1	10.1	10.1	7.6	7.6	5.1	5.1
20°	12.7	12.7	12.7	10.1	10.1	7.6	7.6	5.1	5.1	2.5	2.5
22.5°	10.1	7.6	7.6	5.1	5.1	2.5	2.5	2.5	0.0	0.0	0.0
25°	7.6	5.1	5.1	2.5	2.5	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	5.1	2.5	2.5	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	5.1	2.5	2.5	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	15.2	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7
5°	12.7	12.7	12.7	12.7	10.1	10.1	10.1	10.1	10.1	10.1	10.1
7.5°	10.1	10.1	10.1	10.1	10.1	10.1	7.6	7.6	7.6	7.6	7.6
10°	10.1	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	5.1	5.1
12.5°	10.1	7.6	7.6	7.6	5.1	5.1	5.1	5.1	5.1	2.5	2.5
15°	7.6	5.1	5.1	5.1	2.5	2.5	2.5	2.5	2.5	0.0	0.0
17.5°	5.1	2.5	2.5	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	15.2	15.2
5°	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1
7.5°	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6
10°	5.1	5.1	5.1	5.1	5.1	5.1	2.5	2.5	2.5	2.5	2.5
12.5°	2.5	2.5	2.5	2.5	2.5	2.5	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	15.2	15.2	15.2	15.2	15.2	17.7	17.7	20.2	20.2	22.8	22.8
5°	10.1	10.1	12.7	12.7	12.7	12.7	15.2	15.2	15.2	17.7	17.7
7.5°	7.6	7.6	7.6	7.6	7.6	10.1	10.1	12.7	12.7	15.2	15.2
10°	2.5	2.5	5.1	5.1	5.1	5.1	7.6	7.6	7.6	10.1	12.7
12.5°	0.0	0.0	2.5	2.5	2.5	2.5	5.1	5.1	5.1	7.6	10.1
15°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5	5.1	7.6
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	5.1
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	25.3	25.3	27.8	27.8	30.4	30.4	32.9	32.9	32.9	32.9	32.9
5°	20.2	20.2	22.8	25.3	25.3	27.8	30.4	30.4	30.4	30.4	30.4
7.5°	17.7	17.7	20.2	22.8	22.8	25.3	27.8	27.8	30.4	30.4	30.4
10°	12.7	15.2	17.7	20.2	20.2	22.8	25.3	25.3	27.8	27.8	27.8
12.5°	10.1	12.7	15.2	17.7	17.7	20.2	22.8	22.8	25.3	25.3	27.8
15°	7.6	10.1	12.7	15.2	15.2	17.7	20.2	20.2	22.8	25.3	27.8
17.5°	5.1	7.6	10.1	12.7	12.7	15.2	17.7	20.2	22.8	22.8	25.3
20°	5.1	5.1	7.6	10.1	10.1	12.7	15.2	17.7	20.2	20.2	22.8
22.5°	2.5	2.5	5.1	7.6	7.6	10.1	12.7	15.2	17.7	17.7	20.2
25°	0.0	0.0	2.5	5.1	5.1	7.6	10.1	10.1	12.7	12.7	15.2
27.5°	0.0	0.0	2.5	2.5	5.1	5.1	7.6	7.6	10.1	10.1	12.7
30°	0.0	0.0	2.5	2.5	5.1	5.1	7.6	7.6	10.1	10.1	10.1
32.5°	0.0	0.0	0.0	2.5	2.5	2.5	5.1	5.1	7.6	7.6	10.1
35°	0.0	0.0	0.0	2.5	2.5	2.5	5.1	5.1	7.6	7.6	7.6
37.5°	0.0	0.0	0.0	2.5	2.5	2.5	5.1	5.1	5.1	5.1	7.6
40°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	5.1	5.1	5.1
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	5.1	5.1	5.1
45°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	5.1	5.1	5.1
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	5.1	5.1	5.1
50°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	5.1	5.1	5.1
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5	2.5	2.5
55°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5	2.5	2.5
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5
75°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5	2.5	2.5
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	5.1	5.1	5.1
80°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	5.1	5.1	5.1
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5	2.5	5.1
85°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5	2.5	2.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.5	2.5	2.5	2.5	2.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	32.9	32.9
5°	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	30.4	30.4
7.5°	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	30.4	30.4
10°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
12.5°	27.8	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
15°	27.8	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
17.5°	25.3	27.8	27.8	27.8	30.4	30.4	30.4	30.4	30.4	30.4	30.4
20°	22.8	25.3	25.3	25.3	27.8	27.8	27.8	27.8	30.4	30.4	30.4
22.5°	20.2	22.8	22.8	22.8	25.3	25.3	25.3	25.3	27.8	27.8	27.8
25°	17.7	17.7	20.2	20.2	22.8	22.8	22.8	22.8	22.8	22.8	22.8
27.5°	12.7	15.2	15.2	15.2	17.7	17.7	17.7	17.7	20.2	20.2	20.2
30°	12.7	12.7	12.7	12.7	15.2	15.2	15.2	15.2	17.7	17.7	17.7
32.5°	10.1	12.7	12.7	12.7	15.2	15.2	15.2	15.2	17.7	17.7	17.7
35°	10.1	10.1	10.1	10.1	12.7	12.7	12.7	12.7	15.2	15.2	15.2
37.5°	7.6	10.1	10.1	10.1	12.7	12.7	12.7	12.7	15.2	15.2	15.2
40°	7.6	7.6	7.6	7.6	10.1	10.1	10.1	10.1	12.7	12.7	12.7
42.5°	7.6	7.6	7.6	7.6	10.1	10.1	10.1	10.1	12.7	12.7	12.7
45°	7.6	7.6	7.6	7.6	10.1	10.1	10.1	10.1	12.7	12.7	12.7
47.5°	7.6	7.6	7.6	7.6	10.1	10.1	10.1	10.1	12.7	12.7	12.7
50°	7.6	7.6	7.6	7.6	10.1	10.1	10.1	10.1	12.7	12.7	12.7
52.5°	5.1	5.1	5.1	5.1	7.6	7.6	7.6	7.6	10.1	10.1	10.1
55°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	7.6	7.6	7.6
57.5°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	7.6	7.6	7.6
60°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
62.5°	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
65°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	2.5	2.5
67.5°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
70°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
72.5°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
75°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
77.5°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
80°	7.6	7.6	7.6	7.6	7.6	5.1	5.1	5.1	5.1	5.1	5.1
82.5°	5.1	7.6	7.6	7.6	7.6	5.1	5.1	5.1	5.1	5.1	5.1
85°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
87.5°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	32.9	32.9	30.4	30.4	30.4	30.4	30.4	30.4	30.4	32.9	32.9
5°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	32.9	32.9
7.5°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	32.9	32.9
10°	30.4	30.4	30.4	30.4	27.8	27.8	30.4	30.4	30.4	32.9	32.9
12.5°	30.4	30.4	30.4	30.4	27.8	27.8	30.4	30.4	32.9	32.9	35.4
15°	30.4	30.4	27.8	27.8	27.8	27.8	30.4	30.4	32.9	32.9	35.4
17.5°	30.4	30.4	27.8	27.8	27.8	27.8	30.4	30.4	32.9	32.9	35.4
20°	30.4	30.4	27.8	27.8	27.8	27.8	27.8	27.8	30.4	32.9	32.9
22.5°	27.8	27.8	27.8	27.8	25.3	25.3	27.8	27.8	30.4	32.9	32.9
25°	22.8	25.3	25.3	25.3	25.3	25.3	27.8	27.8	30.4	32.9	32.9
27.5°	20.2	22.8	22.8	22.8	22.8	25.3	25.3	27.8	30.4	32.9	32.9
30°	17.7	20.2	20.2	20.2	22.8	25.3	25.3	27.8	30.4	32.9	32.9
32.5°	17.7	20.2	20.2	20.2	22.8	22.8	25.3	25.3	27.8	30.4	32.9
35°	17.7	17.7	20.2	20.2	20.2	22.8	22.8	25.3	27.8	30.4	32.9
37.5°	17.7	17.7	20.2	20.2	20.2	22.8	22.8	25.3	27.8	30.4	32.9
40°	15.2	17.7	17.7	20.2	20.2	22.8	22.8	25.3	27.8	32.9	35.4
42.5°	15.2	15.2	17.7	17.7	20.2	22.8	22.8	25.3	27.8	32.9	35.4
45°	15.2	17.7	17.7	20.2	22.8	25.3	25.3	27.8	30.4	32.9	35.4
47.5°	15.2	17.7	17.7	20.2	25.3	25.3	27.8	27.8	30.4	32.9	35.4
50°	15.2	17.7	17.7	20.2	27.8	27.8	27.8	27.8	30.4	32.9	35.4
52.5°	12.7	15.2	15.2	17.7	22.8	25.3	27.8	30.4	32.9	35.4	38.0
55°	10.1	12.7	12.7	15.2	20.2	22.8	27.8	32.9	35.4	38.0	40.5
57.5°	10.1	10.1	12.7	12.7	17.7	22.8	30.4	35.4	38.0	40.5	43.0
60°	7.6	7.6	10.1	10.1	15.2	20.2	27.8	35.4	38.0	43.0	45.5
62.5°	5.1	7.6	7.6	10.1	12.7	20.2	27.8	35.4	40.5	45.5	48.1
65°	5.1	5.1	7.6	7.6	12.7	17.7	25.3	30.4	38.0	45.5	53.1
67.5°	7.6	7.6	10.1	10.1	12.7	17.7	25.3	30.4	38.0	48.1	55.7
70°	7.6	7.6	10.1	10.1	15.2	20.2	25.3	30.4	38.0	48.1	55.7
72.5°	7.6	7.6	10.1	10.1	15.2	17.7	22.8	27.8	35.4	43.0	50.6
75°	5.1	7.6	7.6	7.6	12.7	15.2	20.2	25.3	32.9	40.5	48.1
77.5°	5.1	5.1	5.1	5.1	10.1	12.7	17.7	20.2	27.8	35.4	43.0
80°	5.1	5.1	5.1	5.1	7.6	10.1	15.2	17.7	25.3	32.9	40.5
82.5°	5.1	5.1	2.5	2.5	5.1	7.6	10.1	12.7	20.2	25.3	32.9
85°	5.1	5.1	2.5	2.5	2.5	5.1	5.1	7.6	10.1	12.7	15.2
87.5°	5.1	5.1	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	32.9	32.9	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
5°	32.9	35.4	35.4	38.0	38.0	38.0	40.5	40.5	40.5	40.5	40.5
7.5°	32.9	35.4	35.4	38.0	38.0	38.0	40.5	40.5	40.5	43.0	43.0
10°	32.9	35.4	35.4	38.0	38.0	40.5	43.0	43.0	45.5	45.5	45.5
12.5°	35.4	38.0	38.0	40.5	40.5	43.0	45.5	45.5	48.1	50.6	50.6
15°	35.4	38.0	40.5	40.5	43.0	45.5	48.1	48.1	50.6	53.1	55.7
17.5°	35.4	38.0	40.5	40.5	43.0	45.5	50.6	53.1	55.7	60.7	63.3
20°	35.4	38.0	40.5	40.5	43.0	48.1	50.6	55.7	58.2	63.3	68.3
22.5°	35.4	38.0	40.5	43.0	45.5	50.6	55.7	58.2	63.3	70.9	75.9
25°	35.4	38.0	40.5	43.0	45.5	50.6	55.7	60.7	65.8	75.9	86.0
27.5°	35.4	38.0	43.0	45.5	48.1	53.1	60.7	65.8	70.9	88.6	106.3
30°	35.4	38.0	43.0	45.5	48.1	55.7	63.3	68.3	75.9	106.3	134.1
32.5°	35.4	40.5	43.0	48.1	50.6	58.2	68.3	75.9	83.5	126.5	167.0
35°	35.4	40.5	43.0	48.1	50.6	60.7	70.9	81.0	91.1	154.4	217.6
37.5°	35.4	40.5	43.0	48.1	50.6	65.8	81.0	96.2	111.3	177.1	242.9
40°	38.0	43.0	45.5	50.6	53.1	68.3	83.5	98.7	113.9	179.7	245.5
42.5°	38.0	43.0	45.5	50.6	53.1	65.8	81.0	93.6	106.3	179.7	253.0
45°	38.0	43.0	48.1	50.6	55.7	68.3	81.0	91.1	103.7	197.4	288.5
47.5°	38.0	43.0	48.1	50.6	55.7	68.3	81.0	93.6	106.3	260.6	412.5
50°	38.0	43.0	48.1	50.6	55.7	70.9	86.0	101.2	116.4	389.7	663.0
52.5°	40.5	43.0	48.1	50.6	53.1	70.9	88.6	106.3	124.0	506.1	885.7
55°	43.0	45.5	48.1	50.6	53.1	75.9	98.7	121.5	144.2	544.1	941.3
57.5°	45.5	48.1	50.6	50.6	53.1	81.0	111.3	139.2	167.0	541.5	913.5
60°	48.1	50.6	53.1	55.7	58.2	86.0	116.4	144.2	172.1	490.9	809.8
62.5°	53.1	58.2	63.3	65.8	70.9	98.7	124.0	151.8	177.1	402.3	625.0
65°	60.7	65.8	68.3	73.4	75.9	101.2	129.1	154.4	179.7	334.0	485.9
67.5°	63.3	68.3	70.9	75.9	78.4	103.7	129.1	154.4	179.7	283.4	384.6
70°	63.3	68.3	73.4	75.9	81.0	106.3	129.1	154.4	177.1	245.5	313.8
72.5°	58.2	65.8	70.9	78.4	83.5	106.3	126.5	149.3	169.5	217.6	265.7
75°	55.7	65.8	73.4	83.5	91.1	106.3	124.0	139.2	154.4	189.8	225.2
77.5°	50.6	63.3	75.9	88.6	101.2	111.3	118.9	129.1	136.6	159.4	182.2
80°	48.1	60.7	73.4	86.0	98.7	103.7	106.3	111.3	113.9	116.4	118.9
82.5°	38.0	48.1	58.2	65.8	75.9	70.9	68.3	63.3	58.2	55.7	53.1
85°	17.7	20.2	20.2	22.8	22.8	22.8	20.2	20.2	17.7	15.2	12.7
87.5°	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	35.4	35.4	35.4	35.4	32.9	32.9	32.9	32.9	30.4	30.4	30.4
5°	40.5	40.5	40.5	40.5	38.0	38.0	38.0	38.0	35.4	35.4	35.4
7.5°	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0
10°	48.1	48.1	48.1	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6
12.5°	53.1	53.1	55.7	55.7	58.2	58.2	60.7	60.7	63.3	63.3	63.3
15°	58.2	60.7	63.3	65.8	65.8	68.3	70.9	73.4	75.9	78.4	81.0
17.5°	68.3	70.9	75.9	81.0	86.0	91.1	98.7	108.8	116.4	124.0	134.1
20°	75.9	83.5	98.7	116.4	131.6	146.8	184.7	222.7	260.6	298.6	336.6
22.5°	91.1	106.3	156.9	210.0	260.6	311.2	430.2	549.1	665.5	784.4	890.7
25°	121.5	154.4	270.8	387.2	501.0	617.4	830.0	1045.1	1257.6	1470.2	1667.6
27.5°	167.0	227.7	417.5	609.8	799.6	989.4	1298.1	1609.4	1918.1	2229.4	2505.2
30°	232.8	331.5	614.9	900.9	1184.3	1467.7	1857.4	2249.6	2639.3	3029.0	3282.0
32.5°	316.3	463.1	822.4	1181.7	1541.1	1900.4	2330.6	2760.8	3188.4	3618.6	3886.8
35°	404.9	592.1	1024.8	1460.1	1892.8	2328.0	2781.0	3234.0	3686.9	4139.9	4468.8
37.5°	455.5	668.0	1181.7	1695.4	2206.6	2720.3	3216.2	3714.7	4210.7	4706.7	5106.5
40°	503.6	759.1	1351.3	1943.4	2535.5	3127.7	3707.2	4286.6	4866.1	5445.6	5959.3
42.5°	574.4	895.8	1586.6	2277.4	2965.7	3656.5	4418.2	5182.4	5944.1	6705.8	7495.3
45°	721.2	1153.9	2049.7	2945.5	3838.7	4734.5	5815.0	6898.1	7978.6	9061.6	10073.8
47.5°	1075.5	1735.9	2958.1	4180.3	5402.6	6624.8	7869.8	9114.8	10359.8	11604.8	12809.3
50°	1665.1	2664.6	4193.0	5721.4	7247.3	8775.7	10018.2	11260.6	12500.6	13743.0	14939.9
52.5°	2219.2	3552.8	5195.1	6839.9	8482.2	10127.0	11227.7	12328.5	13429.2	14530.0	15689.0
55°	2409.0	3874.2	5536.7	7201.7	8864.3	10529.3	11589.6	12652.4	13712.7	14772.9	15974.9
57.5°	2242.0	3570.5	5245.7	6920.9	8593.5	10268.7	11452.9	12639.7	13824.0	15010.8	16298.8
60°	1877.6	2942.9	4701.6	6462.8	8221.5	9980.2	11316.3	12652.4	13988.5	15324.6	16610.1
62.5°	1487.9	2348.3	4210.7	6073.1	7935.6	9798.0	11156.9	12518.3	13877.1	15236.0	16222.9
65°	1141.2	1796.6	3628.7	5463.3	7295.4	9130.0	10243.4	11359.3	12472.7	13588.7	14271.9
67.5°	847.7	1310.8	2912.6	4516.9	6118.7	7720.5	8540.4	9362.8	10182.6	11005.0	11536.4
70°	625.0	933.7	2024.4	3115.0	4203.1	5293.8	6045.3	6796.9	7545.9	8297.4	8849.1
72.5°	432.7	597.2	1250.1	1905.4	2558.3	3211.2	3972.9	4734.5	5493.7	6255.3	6882.9
75°	296.1	366.9	673.1	979.3	1285.5	1591.7	2168.6	2745.6	3322.5	3899.5	4231.0
77.5°	220.2	258.1	349.2	442.8	533.9	625.0	736.4	847.7	959.1	1070.4	1214.6
80°	121.5	121.5	134.1	144.2	156.9	167.0	197.4	230.3	260.6	293.5	334.0
82.5°	55.7	58.2	63.3	68.3	70.9	75.9	81.0	86.0	91.1	96.2	96.2
85°	15.2	17.7	17.7	15.2	15.2	12.7	12.7	15.2	15.2	15.2	15.2
87.5°	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	30.4	27.8	27.8	27.8	25.3	25.3	25.3	25.3	25.3	25.3	25.3
5°	35.4	35.4	35.4	35.4	32.9	32.9	32.9	32.9	32.9	30.4	30.4
7.5°	43.0	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	38.0	38.0
10°	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6	48.1	48.1
12.5°	63.3	63.3	63.3	63.3	65.8	65.8	63.3	63.3	63.3	60.7	60.7
15°	83.5	86.0	88.6	88.6	91.1	91.1	91.1	88.6	88.6	86.0	83.5
17.5°	141.7	149.3	159.4	169.5	179.7	187.3	187.3	182.2	177.1	172.1	167.0
20°	377.0	415.0	455.5	496.0	539.0	569.4	549.1	533.9	518.7	501.0	485.9
22.5°	999.5	1105.8	1214.6	1290.5	1366.5	1419.6	1376.6	1293.1	1209.6	1128.6	1045.1
25°	1865.0	2059.8	2257.2	2338.2	2421.7	2482.4	2454.6	2328.0	2201.5	2077.5	1951.0
27.5°	2781.0	3054.3	3330.1	3401.0	3471.8	3525.0	3514.8	3350.4	3185.9	3021.4	2856.9
30°	3535.1	3788.1	4041.2	4112.0	4182.9	4231.0	4177.8	4013.3	3848.9	3684.4	3519.9
32.5°	4157.6	4425.8	4696.6	4790.2	4883.8	4947.1	4883.8	4686.4	4489.1	4294.2	4096.8
35°	4797.8	5124.2	5453.2	5572.1	5691.0	5767.0	5660.7	5417.8	5174.8	4934.4	4691.5
37.5°	5506.3	5903.6	6303.4	6465.4	6629.9	6743.7	6662.7	6359.1	6052.9	5749.2	5443.1
40°	6475.5	6989.2	7505.4	7796.4	8084.9	8289.8	8145.6	7793.9	7439.6	7087.9	6733.6
42.5°	8287.3	9076.8	9866.3	10283.9	10698.9	11000.0	10838.0	10405.3	9972.6	9539.9	9107.2
45°	11086.0	12095.7	13107.9	13717.7	14330.1	14780.5	14593.3	14049.2	13502.6	12958.6	12414.5
47.5°	14013.8	15218.3	16422.8	16908.7	17397.0	17776.6	17731.1	17052.9	16374.7	15699.1	15020.9
50°	16139.4	17336.3	18533.2	18950.7	19370.8	19682.1	19565.7	18702.8	17837.3	16974.4	16109.0
52.5°	16847.9	18004.4	19163.3	19661.8	20160.3	20532.3	20390.6	19418.9	18447.2	17478.0	16506.3
55°	17176.9	18378.9	19580.8	20188.2	20798.0	21243.4	21038.4	19973.1	18905.2	17839.9	16772.0
57.5°	17586.8	18874.8	20162.8	20828.4	21493.9	21974.7	21701.4	20598.1	19494.8	18394.0	17290.8
60°	17895.5	19178.5	20464.0	20997.9	21534.4	21908.9	21645.7	20572.8	19497.3	18424.4	17351.5
62.5°	17212.3	18199.2	19186.1	19583.4	19980.7	20269.1	20119.8	19102.6	18085.3	17068.1	16050.8
65°	14957.7	15640.9	16326.6	16594.9	16860.6	17065.5	17020.0	16162.2	15304.3	14449.0	13591.2
67.5°	12070.4	12601.8	13135.7	13515.3	13897.4	14193.5	14160.6	13378.6	12596.7	11814.8	11032.9
70°	9403.3	9954.9	10506.5	10984.8	11465.6	11837.6	11789.5	11063.2	10334.5	9608.2	8879.4
72.5°	7513.0	8140.5	8768.1	9041.4	9314.7	9507.0	9365.3	8816.2	8264.5	7715.4	7163.8
75°	4562.5	4891.4	5222.9	5220.4	5220.4	5190.0	5048.3	4734.5	4420.7	4107.0	3793.2
77.5°	1358.9	1503.1	1647.3	1786.5	1928.2	2034.5	2006.7	1842.2	1675.2	1510.7	1343.7
80°	374.5	412.5	453.0	470.7	488.4	511.2	569.4	528.9	488.4	450.4	409.9
82.5°	96.2	96.2	96.2	93.6	91.1	86.0	78.4	73.4	68.3	63.3	58.2
85°	15.2	12.7	12.7	12.7	10.1	10.1	10.1	10.1	7.6	7.6	5.1
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8
2.5°	25.3	25.3	22.8	22.8	22.8	22.8	22.8	22.8	22.8	22.8	20.2
5°	30.4	30.4	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	25.3
7.5°	38.0	38.0	35.4	35.4	35.4	35.4	32.9	32.9	32.9	32.9	30.4
10°	48.1	45.5	45.5	43.0	43.0	43.0	40.5	40.5	40.5	38.0	38.0
12.5°	60.7	58.2	58.2	55.7	53.1	53.1	50.6	48.1	45.5	45.5	43.0
15°	81.0	78.4	75.9	73.4	70.9	65.8	63.3	58.2	55.7	53.1	50.6
17.5°	154.4	141.7	129.1	116.4	106.3	96.2	86.0	75.9	70.9	65.8	60.7
20°	430.2	372.0	316.3	260.6	225.2	189.8	154.4	118.9	103.7	91.1	75.9
22.5°	931.2	814.8	700.9	584.5	490.9	399.8	306.2	212.6	177.1	144.2	108.8
25°	1730.8	1508.2	1288.0	1065.3	888.2	711.1	533.9	356.8	291.0	225.2	159.4
27.5°	2568.4	2280.0	1991.5	1703.0	1422.1	1138.7	855.3	574.4	460.5	349.2	235.3
30°	3213.7	2907.5	2603.9	2297.7	1943.4	1589.1	1232.3	878.1	698.4	518.7	336.6
32.5°	3767.9	3436.4	3107.4	2775.9	2366.0	1956.1	1546.1	1136.2	911.0	685.8	458.0
35°	4317.0	3940.0	3565.4	3188.4	2748.1	2307.8	1867.5	1427.2	1141.2	855.3	566.8
37.5°	4985.0	4524.5	4066.5	3608.5	3155.5	2705.1	2252.1	1799.2	1434.8	1072.9	708.5
40°	6149.1	5562.0	4977.5	4390.4	3861.5	3335.2	2806.3	2277.4	1819.4	1361.4	900.9
42.5°	8370.8	7634.5	6900.6	6164.2	5432.9	4701.6	3967.8	3236.5	2583.6	1933.3	1280.4
45°	11470.7	10526.8	9585.5	8641.6	7740.7	6842.4	5941.6	5040.7	4048.8	3056.8	2062.3
47.5°	13988.5	12953.5	11921.1	10886.1	9886.6	8889.6	7890.0	6890.5	5620.2	4352.4	3082.1
50°	15124.7	14137.8	13153.4	12166.5	11164.5	10159.9	9155.3	8153.2	6695.6	5240.6	3783.1
52.5°	15506.8	14504.7	13505.2	12503.1	11508.6	10514.1	9519.7	8525.2	7009.4	5496.2	3980.4
55°	15716.8	14659.1	13603.8	12546.1	11475.7	10402.8	9329.9	8259.5	6751.3	5245.7	3737.5
57.5°	16141.9	14990.6	13841.7	12690.3	11470.7	10251.0	9028.7	7809.1	6321.1	4833.2	3345.3
60°	16220.4	15086.7	13955.6	12824.5	11475.7	10127.0	8775.7	7427.0	5949.2	4473.9	2996.1
62.5°	15104.4	14158.0	13214.2	12267.8	10916.5	9565.2	8211.4	6860.1	5445.6	4031.1	2614.0
65°	12773.9	11956.5	11141.7	10324.3	9221.1	8120.3	7017.0	5913.7	4651.0	3390.8	2128.1
67.5°	10233.3	9433.6	8636.5	7836.9	7006.9	6179.4	5349.4	4519.4	3545.2	2571.0	1596.7
70°	8112.7	7343.4	6576.7	5807.4	5073.6	4337.2	3600.9	2867.0	2262.2	1660.0	1055.2
72.5°	6429.9	5693.6	4959.7	4223.4	3557.9	2892.3	2226.8	1561.3	1260.2	961.6	660.5
75°	3411.1	3029.0	2649.4	2267.3	1892.8	1515.8	1138.7	764.2	645.3	526.3	404.9
77.5°	1176.7	1009.7	845.2	678.2	564.3	450.4	336.6	222.7	210.0	199.9	187.3
80°	356.8	303.7	250.5	197.4	174.6	151.8	129.1	106.3	98.7	91.1	81.0
82.5°	55.7	50.6	48.1	43.0	40.5	40.5	38.0	35.4	30.4	27.8	22.8
85°	5.1	2.5	2.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	22.8	22.8
2.5°	20.2	20.2
5°	25.3	25.3
7.5°	30.4	30.4
10°	35.4	35.4
12.5°	40.5	40.5
15°	48.1	45.5
17.5°	55.7	53.1
20°	60.7	55.7
22.5°	73.4	63.3
25°	93.6	78.4
27.5°	121.5	96.2
30°	156.9	121.5
32.5°	232.8	169.5
35°	280.9	205.0
37.5°	344.1	237.9
40°	442.8	288.5
42.5°	627.6	392.2
45°	1070.4	650.3
47.5°	1814.4	1108.3
50°	2325.5	1422.1
52.5°	2467.2	1508.2
55°	2231.9	1384.2
57.5°	1857.4	1176.7
60°	1520.8	969.2
62.5°	1199.4	766.7
65°	865.4	579.5
67.5°	622.5	445.4
70°	453.0	349.2
72.5°	359.3	291.0
75°	285.9	242.9
77.5°	177.1	162.0
80°	73.4	68.3
82.5°	17.7	15.2
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066483

CATALOG NUMBER: NVN-SA2C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-3

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-727-U-5WQ

Data in this report applies to families of products including GSS-SB1A-727-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-3
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-727-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2700K CCT 26 LEDS

Spectral Parameters

CCT (K):	2672	CRI (Ra):	71.1		
CIE u':	0.2638	R1:	68.3	R9:	-27.8
CIE v':	0.5276	R2:	79.8	R10:	54.4
Duv:	-0.0002	R3:	91.2	R11:	65.8
CIE x:	0.4619	R4:	69.4	R12:	45.6
CIE y:	0.4106	R5:	66.5	R13:	69.8
CIE z:	0.1275	R6:	72.6	R14:	94.5
Peak Wavelength (nm):	601	R7:	77.0	R15:	60.1
Dominant Wavelength (nm):	584	R8:	44.1		
Purity:	61.88407				
Rf:	67.9				
Rg:	98.6				



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-3

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-3

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2700K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-3

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.02

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.71

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			


REPORT NUMBER: SP1-2407-184-3

TM-30-18


Summary

$R_f = 67.9$
 $R_g = 98.6$
 $CIE\ R_a = 71.1$
 $R_g = -27.8$

Spectral Power Distribution Comparison



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 53	CES51 = 75	CES76 = 51
CES02 = 63	CES27 = 70	CES52 = 80	CES77 = 79
CES03 = 31	CES28 = 81	CES53 = 64	CES78 = 58
CES04 = 71	CES29 = 37	CES54 = 73	CES79 = 82
CES05 = 50	CES30 = 33	CES55 = 69	CES80 = 82
CES06 = 52	CES31 = 44	CES56 = 60	CES81 = 69
CES07 = 42	CES32 = 47	CES57 = 54	CES82 = 92
CES08 = 41	CES33 = 45	CES58 = 59	CES83 = 82
CES09 = 29	CES34 = 67	CES59 = 85	CES84 = 92
CES10 = 77	CES35 = 84	CES60 = 86	CES85 = 87
CES11 = 60	CES36 = 68	CES61 = 86	CES86 = 60
CES12 = 66	CES37 = 77	CES62 = 59	CES87 = 79
CES13 = 44	CES38 = 40	CES63 = 66	CES88 = 70
CES14 = 74	CES39 = 88	CES64 = 69	CES89 = 66
CES15 = 72	CES40 = 82	CES65 = 64	CES90 = 64
CES16 = 48	CES41 = 70	CES66 = 65	CES91 = 81
CES17 = 51	CES42 = 76	CES67 = 64	CES92 = 69
CES18 = 57	CES43 = 63	CES68 = 73	CES93 = 81
CES19 = 73	CES44 = 97	CES69 = 83	CES94 = 53
CES20 = 67	CES45 = 74	CES70 = 64	CES95 = 77
CES21 = 88	CES46 = 67	CES71 = 60	CES96 = 79
CES22 = 80	CES47 = 55	CES72 = 87	CES97 = 78
CES23 = 92	CES48 = 42	CES73 = 57	CES98 = 69
CES24 = 92	CES49 = 65	CES74 = 84	CES99 = 60
CES25 = 73	CES50 = 74	CES75 = 60	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)