

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066484

Luminaire Tested: **NVN-SA2D-727-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066484
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA2D-727-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1200mA 2xLight Square PACKAGE
70CRI 2700K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (28) 2700K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8860 lumens
Efficiency: N/A
Efficacy: 82.8 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 107
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 1.7 fc
 Type III - Short - N/A

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	52.7	0.0	52.7
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	8807.3	0.0	8807.3
	% Fixture	99.4	0.0	99.4
Total	Lumens	8860.0	0.0	8860.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2.6	0.0
10°-20°	13.0	0.1
20°-30°	165.4	1.9
30°-40°	557.3	6.3
40°-50°	1683.1	19.0
50°-60°	2969.6	33.5
60°-70°	2616.2	29.5
70°-80°	832.8	9.4
80°-90°	20.1	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	8860.0	100.0
0°-180°	8860.0	100.0



REPORT NUMBER: P1066484


CATALOG NUMBER: NVN-SA2D-727-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	173.1	2.0			
FM	(30°-60°)	5189.6	58.6			
FH	(60°-80°)	3428.3	38.7			G2/5000
FVH	(80°-90°)	16.3	0.2			G1/100
BL	(0°-30°)	7.9	0.1	B0/110		
BM	(30°-60°)	20.4	0.2	B0/220		
BH	(60°-80°)	20.7	0.2	B0/110		G0/110
BVH	(80°-90°)	3.7	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short





REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	19.4
5°	27.8	27.8	27.8	25.0	25.0	25.0	22.2	22.2	22.2	22.2	22.2
7.5°	33.3	30.6	30.6	27.8	27.8	27.8	25.0	25.0	25.0	25.0	22.2
10°	38.9	36.1	36.1	33.3	33.3	30.6	30.6	27.8	27.8	25.0	25.0
12.5°	44.5	41.7	38.9	36.1	36.1	33.3	33.3	30.6	30.6	27.8	27.8
15°	50.0	47.2	44.5	41.7	38.9	38.9	36.1	33.3	30.6	30.6	27.8
17.5°	58.3	52.8	50.0	44.5	41.7	38.9	36.1	33.3	33.3	30.6	30.6
20°	61.1	55.6	52.8	47.2	44.5	41.7	38.9	36.1	33.3	33.3	30.6
22.5°	72.2	61.1	58.3	52.8	50.0	47.2	41.7	38.9	36.1	33.3	30.6
25°	88.9	72.2	63.9	55.6	52.8	47.2	44.5	38.9	36.1	33.3	30.6
27.5°	108.4	80.6	72.2	61.1	55.6	50.0	44.5	38.9	36.1	33.3	30.6
30°	133.4	94.5	80.6	66.7	61.1	55.6	47.2	41.7	38.9	36.1	30.6
32.5°	186.2	116.7	94.5	72.2	63.9	58.3	50.0	41.7	38.9	36.1	30.6
35°	225.1	141.7	113.9	83.4	72.2	63.9	52.8	41.7	38.9	36.1	30.6
37.5°	261.2	144.5	116.7	88.9	77.8	66.7	52.8	41.7	38.9	36.1	30.6
40°	319.5	150.0	116.7	83.4	75.0	63.9	55.6	44.5	41.7	36.1	33.3
42.5°	430.7	172.3	125.0	77.8	69.5	63.9	55.6	47.2	41.7	38.9	33.3
45°	716.9	255.6	169.5	80.6	72.2	63.9	55.6	47.2	44.5	38.9	36.1
47.5°	1219.8	444.6	264.0	83.4	75.0	63.9	55.6	44.5	41.7	38.9	33.3
50°	1561.5	569.6	333.4	97.2	83.4	72.2	58.3	44.5	41.7	38.9	36.1
52.5°	1658.8	605.7	361.2	113.9	97.2	80.6	61.1	44.5	41.7	41.7	38.9
55°	1519.8	589.0	361.2	133.4	111.1	91.7	69.5	47.2	44.5	44.5	41.7
57.5°	1292.0	544.6	344.5	144.5	122.3	97.2	75.0	50.0	47.2	47.2	44.5
60°	1064.2	458.5	311.2	161.2	136.1	111.1	86.1	61.1	58.3	55.6	50.0
62.5°	844.7	369.5	272.3	172.3	147.3	119.5	94.5	66.7	63.9	61.1	58.3
65°	636.3	322.3	252.8	180.6	152.8	125.0	97.2	69.5	66.7	66.7	63.9
67.5°	489.0	294.5	241.7	186.2	158.4	130.6	102.8	75.0	72.2	69.5	66.7
70°	386.2	272.3	227.8	183.4	158.4	133.4	105.6	80.6	75.0	72.2	66.7
72.5°	322.3	247.3	211.2	175.0	155.6	136.1	116.7	97.2	86.1	77.8	66.7
75°	269.5	222.3	191.7	158.4	144.5	133.4	119.5	105.6	91.7	77.8	63.9
77.5°	177.8	161.2	147.3	133.4	125.0	116.7	105.6	97.2	83.4	72.2	58.3
80°	75.0	69.5	72.2	72.2	72.2	72.2	69.5	69.5	61.1	52.8	41.7
82.5°	16.7	13.9	16.7	16.7	16.7	16.7	13.9	13.9	13.9	11.1	11.1
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4
5°	22.2	22.2	22.2	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4
7.5°	22.2	22.2	22.2	19.4	19.4	19.4	19.4	16.7	16.7	16.7	16.7
10°	22.2	22.2	22.2	19.4	19.4	19.4	19.4	16.7	16.7	16.7	16.7
12.5°	25.0	25.0	22.2	22.2	19.4	19.4	19.4	16.7	16.7	16.7	16.7
15°	25.0	25.0	22.2	22.2	19.4	19.4	19.4	16.7	16.7	16.7	16.7
17.5°	27.8	25.0	25.0	22.2	19.4	19.4	19.4	16.7	16.7	16.7	16.7
20°	27.8	25.0	25.0	22.2	19.4	19.4	19.4	16.7	16.7	16.7	16.7
22.5°	27.8	25.0	25.0	22.2	19.4	19.4	16.7	16.7	13.9	13.9	11.1
25°	27.8	25.0	25.0	22.2	19.4	19.4	16.7	16.7	13.9	11.1	11.1
27.5°	27.8	25.0	25.0	22.2	19.4	16.7	16.7	13.9	11.1	8.3	8.3
30°	27.8	25.0	25.0	22.2	19.4	16.7	13.9	11.1	8.3	8.3	5.6
32.5°	27.8	25.0	22.2	19.4	16.7	13.9	13.9	11.1	8.3	5.6	5.6
35°	27.8	25.0	22.2	19.4	16.7	13.9	13.9	11.1	8.3	5.6	5.6
37.5°	27.8	25.0	22.2	19.4	16.7	13.9	11.1	8.3	5.6	5.6	2.8
40°	27.8	25.0	22.2	19.4	16.7	13.9	11.1	8.3	5.6	5.6	2.8
42.5°	27.8	25.0	22.2	19.4	16.7	13.9	11.1	8.3	5.6	5.6	2.8
45°	30.6	27.8	25.0	19.4	16.7	13.9	13.9	11.1	8.3	5.6	5.6
47.5°	30.6	27.8	25.0	19.4	16.7	13.9	13.9	11.1	8.3	5.6	5.6
50°	33.3	30.6	27.8	22.2	19.4	16.7	13.9	8.3	5.6	5.6	2.8
52.5°	36.1	33.3	30.6	27.8	25.0	19.4	13.9	8.3	2.8	2.8	2.8
55°	38.9	36.1	36.1	33.3	30.6	22.2	16.7	8.3	0.0	0.0	0.0
57.5°	41.7	38.9	38.9	36.1	33.3	25.0	16.7	8.3	0.0	0.0	0.0
60°	47.2	44.5	41.7	36.1	33.3	25.0	16.7	8.3	0.0	0.0	0.0
62.5°	55.6	50.0	41.7	36.1	27.8	22.2	13.9	8.3	0.0	0.0	0.0
65°	61.1	52.8	44.5	33.3	25.0	19.4	13.9	5.6	0.0	0.0	0.0
67.5°	63.9	52.8	44.5	33.3	22.2	16.7	11.1	5.6	0.0	0.0	0.0
70°	61.1	50.0	41.7	30.6	19.4	13.9	11.1	5.6	0.0	0.0	0.0
72.5°	55.6	47.2	36.1	27.8	16.7	13.9	8.3	5.6	0.0	0.0	0.0
75°	50.0	41.7	30.6	22.2	11.1	8.3	5.6	2.8	0.0	0.0	0.0
77.5°	44.5	36.1	25.0	16.7	5.6	5.6	2.8	2.8	0.0	0.0	0.0
80°	33.3	25.0	16.7	8.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	8.3	5.6	5.6	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	16.7	16.7	16.7	16.7	16.7	16.7	16.7	16.7	16.7	16.7	16.7
5°	16.7	16.7	16.7	16.7	13.9	13.9	13.9	13.9	13.9	13.9	13.9
7.5°	16.7	16.7	16.7	16.7	13.9	13.9	13.9	13.9	11.1	11.1	11.1
10°	13.9	13.9	13.9	13.9	13.9	13.9	13.9	13.9	11.1	11.1	11.1
12.5°	13.9	13.9	13.9	13.9	13.9	13.9	13.9	13.9	11.1	11.1	11.1
15°	13.9	13.9	13.9	13.9	13.9	13.9	13.9	11.1	11.1	8.3	8.3
17.5°	13.9	13.9	13.9	13.9	11.1	11.1	11.1	8.3	8.3	5.6	5.6
20°	13.9	13.9	13.9	11.1	11.1	8.3	8.3	5.6	5.6	2.8	2.8
22.5°	11.1	8.3	8.3	5.6	5.6	2.8	2.8	2.8	0.0	0.0	0.0
25°	8.3	5.6	5.6	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	16.7	13.9	13.9	13.9	13.9	13.9	13.9	13.9	13.9	13.9	13.9
5°	13.9	13.9	13.9	13.9	11.1	11.1	11.1	11.1	11.1	11.1	11.1
7.5°	11.1	11.1	11.1	11.1	11.1	11.1	8.3	8.3	8.3	8.3	8.3
10°	11.1	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	5.6	5.6
12.5°	11.1	8.3	8.3	8.3	5.6	5.6	5.6	5.6	5.6	2.8	2.8
15°	8.3	5.6	5.6	5.6	2.8	2.8	2.8	2.8	2.8	0.0	0.0
17.5°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	13.9	13.9	13.9	13.9	13.9	13.9	13.9	13.9	13.9	16.7	16.7
5°	11.1	11.1	11.1	11.1	11.1	11.1	11.1	11.1	11.1	11.1	11.1
7.5°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
10°	5.6	5.6	5.6	5.6	5.6	5.6	2.8	2.8	2.8	2.8	2.8
12.5°	2.8	2.8	2.8	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	16.7	16.7	16.7	16.7	16.7	19.4	19.4	22.2	22.2	25.0	25.0
5°	11.1	11.1	13.9	13.9	13.9	13.9	16.7	16.7	16.7	19.4	19.4
7.5°	8.3	8.3	8.3	8.3	8.3	11.1	11.1	13.9	13.9	16.7	16.7
10°	2.8	2.8	5.6	5.6	5.6	5.6	8.3	8.3	8.3	11.1	13.9
12.5°	0.0	0.0	2.8	2.8	2.8	2.8	5.6	5.6	5.6	8.3	11.1
15°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	5.6	8.3
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	5.6
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	27.8	27.8	30.6	30.6	33.3	33.3	36.1	36.1	36.1	36.1	36.1
5°	22.2	22.2	25.0	27.8	27.8	30.6	33.3	33.3	33.3	33.3	33.3
7.5°	19.4	19.4	22.2	25.0	25.0	27.8	30.6	30.6	33.3	33.3	33.3
10°	13.9	16.7	19.4	22.2	22.2	25.0	27.8	27.8	30.6	30.6	30.6
12.5°	11.1	13.9	16.7	19.4	19.4	22.2	25.0	25.0	27.8	27.8	30.6
15°	8.3	11.1	13.9	16.7	16.7	19.4	22.2	22.2	25.0	27.8	30.6
17.5°	5.6	8.3	11.1	13.9	13.9	16.7	19.4	22.2	25.0	25.0	27.8
20°	5.6	5.6	8.3	11.1	11.1	13.9	16.7	19.4	22.2	22.2	25.0
22.5°	2.8	2.8	5.6	8.3	8.3	11.1	13.9	16.7	19.4	19.4	22.2
25°	0.0	0.0	2.8	5.6	5.6	8.3	11.1	11.1	13.9	13.9	16.7
27.5°	0.0	0.0	2.8	2.8	5.6	5.6	8.3	8.3	11.1	11.1	13.9
30°	0.0	0.0	2.8	2.8	5.6	5.6	8.3	8.3	11.1	11.1	11.1
32.5°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	8.3	8.3	11.1
35°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	8.3	8.3	8.3
37.5°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	5.6	5.6	8.3
40°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
45°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
50°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
55°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
75°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
80°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	5.6
85°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	36.1	36.1
5°	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	33.3	33.3
7.5°	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	33.3	33.3
10°	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
12.5°	30.6	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
15°	30.6	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
17.5°	27.8	30.6	30.6	30.6	33.3	33.3	33.3	33.3	33.3	33.3	33.3
20°	25.0	27.8	27.8	27.8	30.6	30.6	30.6	30.6	33.3	33.3	33.3
22.5°	22.2	25.0	25.0	25.0	27.8	27.8	27.8	27.8	30.6	30.6	30.6
25°	19.4	19.4	22.2	22.2	25.0	25.0	25.0	25.0	25.0	25.0	25.0
27.5°	13.9	16.7	16.7	16.7	19.4	19.4	19.4	19.4	22.2	22.2	22.2
30°	13.9	13.9	13.9	13.9	16.7	16.7	16.7	16.7	19.4	19.4	19.4
32.5°	11.1	13.9	13.9	13.9	16.7	16.7	16.7	16.7	19.4	19.4	19.4
35°	11.1	11.1	11.1	11.1	13.9	13.9	13.9	13.9	16.7	16.7	16.7
37.5°	8.3	11.1	11.1	11.1	13.9	13.9	13.9	13.9	16.7	16.7	16.7
40°	8.3	8.3	8.3	8.3	11.1	11.1	11.1	11.1	13.9	13.9	13.9
42.5°	8.3	8.3	8.3	8.3	11.1	11.1	11.1	11.1	13.9	13.9	13.9
45°	8.3	8.3	8.3	8.3	11.1	11.1	11.1	11.1	13.9	13.9	13.9
47.5°	8.3	8.3	8.3	8.3	11.1	11.1	11.1	11.1	13.9	13.9	13.9
50°	8.3	8.3	8.3	8.3	11.1	11.1	11.1	11.1	13.9	13.9	13.9
52.5°	5.6	5.6	5.6	5.6	8.3	8.3	8.3	8.3	11.1	11.1	11.1
55°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	8.3	8.3	8.3
57.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	8.3	8.3	8.3
60°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
62.5°	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
65°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	2.8	2.8
67.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
70°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
72.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
75°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
77.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
80°	8.3	8.3	8.3	8.3	8.3	5.6	5.6	5.6	5.6	5.6	5.6
82.5°	5.6	8.3	8.3	8.3	8.3	5.6	5.6	5.6	5.6	5.6	5.6
85°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
87.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	36.1	36.1	33.3	33.3	33.3	33.3	33.3	33.3	33.3	36.1	36.1
5°	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	36.1	36.1
7.5°	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	36.1	36.1
10°	33.3	33.3	33.3	33.3	30.6	30.6	33.3	33.3	33.3	36.1	36.1
12.5°	33.3	33.3	33.3	33.3	30.6	30.6	33.3	33.3	36.1	36.1	38.9
15°	33.3	33.3	30.6	30.6	30.6	30.6	33.3	33.3	36.1	36.1	38.9
17.5°	33.3	33.3	30.6	30.6	30.6	30.6	33.3	33.3	36.1	36.1	38.9
20°	33.3	33.3	30.6	30.6	30.6	30.6	30.6	30.6	33.3	36.1	36.1
22.5°	30.6	30.6	30.6	30.6	27.8	27.8	30.6	30.6	33.3	36.1	36.1
25°	25.0	27.8	27.8	27.8	27.8	27.8	30.6	30.6	33.3	36.1	36.1
27.5°	22.2	25.0	25.0	25.0	25.0	27.8	27.8	30.6	33.3	36.1	36.1
30°	19.4	22.2	22.2	22.2	25.0	27.8	27.8	30.6	33.3	36.1	36.1
32.5°	19.4	22.2	22.2	22.2	25.0	25.0	27.8	27.8	30.6	33.3	36.1
35°	19.4	19.4	22.2	22.2	22.2	25.0	25.0	27.8	30.6	33.3	36.1
37.5°	19.4	19.4	22.2	22.2	22.2	25.0	25.0	27.8	30.6	33.3	36.1
40°	16.7	19.4	19.4	22.2	22.2	25.0	25.0	27.8	30.6	36.1	38.9
42.5°	16.7	16.7	19.4	19.4	22.2	25.0	25.0	27.8	30.6	36.1	38.9
45°	16.7	19.4	19.4	22.2	25.0	27.8	27.8	30.6	33.3	36.1	38.9
47.5°	16.7	19.4	19.4	22.2	27.8	27.8	30.6	30.6	33.3	36.1	38.9
50°	16.7	19.4	19.4	22.2	30.6	30.6	30.6	30.6	33.3	36.1	38.9
52.5°	13.9	16.7	16.7	19.4	25.0	27.8	30.6	33.3	36.1	38.9	41.7
55°	11.1	13.9	13.9	16.7	22.2	25.0	30.6	36.1	38.9	41.7	44.5
57.5°	11.1	11.1	13.9	13.9	19.4	25.0	33.3	38.9	41.7	44.5	47.2
60°	8.3	8.3	11.1	11.1	16.7	22.2	30.6	38.9	41.7	47.2	50.0
62.5°	5.6	8.3	8.3	11.1	13.9	22.2	30.6	38.9	44.5	50.0	52.8
65°	5.6	5.6	8.3	8.3	13.9	19.4	27.8	33.3	41.7	50.0	58.3
67.5°	8.3	8.3	11.1	11.1	13.9	19.4	27.8	33.3	41.7	52.8	61.1
70°	8.3	8.3	11.1	11.1	16.7	22.2	27.8	33.3	41.7	52.8	61.1
72.5°	8.3	8.3	11.1	11.1	16.7	19.4	25.0	30.6	38.9	47.2	55.6
75°	5.6	8.3	8.3	8.3	13.9	16.7	22.2	27.8	36.1	44.5	52.8
77.5°	5.6	5.6	5.6	5.6	11.1	13.9	19.4	22.2	30.6	38.9	47.2
80°	5.6	5.6	5.6	5.6	8.3	11.1	16.7	19.4	27.8	36.1	44.5
82.5°	5.6	5.6	2.8	2.8	5.6	8.3	11.1	13.9	22.2	27.8	36.1
85°	5.6	5.6	2.8	2.8	2.8	5.6	5.6	8.3	11.1	13.9	16.7
87.5°	5.6	5.6	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	36.1	36.1	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9
5°	36.1	38.9	38.9	41.7	41.7	41.7	44.5	44.5	44.5	44.5	44.5
7.5°	36.1	38.9	38.9	41.7	41.7	41.7	44.5	44.5	44.5	47.2	47.2
10°	36.1	38.9	38.9	41.7	41.7	44.5	47.2	47.2	50.0	50.0	50.0
12.5°	38.9	41.7	41.7	44.5	44.5	47.2	50.0	50.0	52.8	55.6	55.6
15°	38.9	41.7	44.5	44.5	47.2	50.0	52.8	52.8	55.6	58.3	61.1
17.5°	38.9	41.7	44.5	44.5	47.2	50.0	55.6	58.3	61.1	66.7	69.5
20°	38.9	41.7	44.5	44.5	47.2	52.8	55.6	61.1	63.9	69.5	75.0
22.5°	38.9	41.7	44.5	47.2	50.0	55.6	61.1	63.9	69.5	77.8	83.4
25°	38.9	41.7	44.5	47.2	50.0	55.6	61.1	66.7	72.2	83.4	94.5
27.5°	38.9	41.7	47.2	50.0	52.8	58.3	66.7	72.2	77.8	97.2	116.7
30°	38.9	41.7	47.2	50.0	52.8	61.1	69.5	75.0	83.4	116.7	147.3
32.5°	38.9	44.5	47.2	52.8	55.6	63.9	75.0	83.4	91.7	138.9	183.4
35°	38.9	44.5	47.2	52.8	55.6	66.7	77.8	88.9	100.0	169.5	239.0
37.5°	38.9	44.5	47.2	52.8	55.6	72.2	88.9	105.6	122.3	194.5	266.7
40°	41.7	47.2	50.0	55.6	58.3	75.0	91.7	108.4	125.0	197.3	269.5
42.5°	41.7	47.2	50.0	55.6	58.3	72.2	88.9	102.8	116.7	197.3	277.8
45°	41.7	47.2	52.8	55.6	61.1	75.0	88.9	100.0	113.9	216.7	316.7
47.5°	41.7	47.2	52.8	55.6	61.1	75.0	88.9	102.8	116.7	286.2	452.9
50°	41.7	47.2	52.8	55.6	61.1	77.8	94.5	111.1	127.8	427.9	728.0
52.5°	44.5	47.2	52.8	55.6	58.3	77.8	97.2	116.7	136.1	555.7	972.5
55°	47.2	50.0	52.8	55.6	58.3	83.4	108.4	133.4	158.4	597.4	1033.6
57.5°	50.0	52.8	55.6	55.6	58.3	88.9	122.3	152.8	183.4	594.6	1003.0
60°	52.8	55.6	58.3	61.1	63.9	94.5	127.8	158.4	188.9	539.0	889.1
62.5°	58.3	63.9	69.5	72.2	77.8	108.4	136.1	166.7	194.5	441.8	686.3
65°	66.7	72.2	75.0	80.6	83.4	111.1	141.7	169.5	197.3	366.8	533.5
67.5°	69.5	75.0	77.8	83.4	86.1	113.9	141.7	169.5	197.3	311.2	422.3
70°	69.5	75.0	80.6	83.4	88.9	116.7	141.7	169.5	194.5	269.5	344.5
72.5°	63.9	72.2	77.8	86.1	91.7	116.7	138.9	163.9	186.2	239.0	291.7
75°	61.1	72.2	80.6	91.7	100.0	116.7	136.1	152.8	169.5	208.4	247.3
77.5°	55.6	69.5	83.4	97.2	111.1	122.3	130.6	141.7	150.0	175.0	200.1
80°	52.8	66.7	80.6	94.5	108.4	113.9	116.7	122.3	125.0	127.8	130.6
82.5°	41.7	52.8	63.9	72.2	83.4	77.8	75.0	69.5	63.9	61.1	58.3
85°	19.4	22.2	22.2	25.0	25.0	25.0	22.2	22.2	19.4	16.7	13.9
87.5°	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	38.9	38.9	38.9	38.9	36.1	36.1	36.1	36.1	33.3	33.3	33.3
5°	44.5	44.5	44.5	44.5	41.7	41.7	41.7	41.7	38.9	38.9	38.9
7.5°	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2
10°	52.8	52.8	52.8	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6
12.5°	58.3	58.3	61.1	61.1	63.9	63.9	66.7	66.7	69.5	69.5	69.5
15°	63.9	66.7	69.5	72.2	72.2	75.0	77.8	80.6	83.4	86.1	88.9
17.5°	75.0	77.8	83.4	88.9	94.5	100.0	108.4	119.5	127.8	136.1	147.3
20°	83.4	91.7	108.4	127.8	144.5	161.2	202.8	244.5	286.2	327.9	369.5
22.5°	100.0	116.7	172.3	230.6	286.2	341.8	472.3	602.9	730.7	861.3	978.0
25°	133.4	169.5	297.3	425.1	550.1	678.0	911.3	1147.5	1380.9	1614.3	1831.0
27.5°	183.4	250.1	458.5	669.6	878.0	1086.4	1425.4	1767.1	2106.1	2447.9	2750.7
30°	255.6	364.0	675.2	989.1	1300.3	1611.5	2039.4	2470.1	2898.0	3325.9	3603.7
32.5°	347.3	508.5	903.0	1297.6	1692.1	2086.7	2559.0	3031.3	3500.9	3973.2	4267.8
35°	444.6	650.2	1125.3	1603.2	2078.3	2556.2	3053.6	3550.9	4048.3	4545.6	4906.8
37.5°	500.1	733.5	1297.6	1861.6	2422.8	2986.9	3531.5	4078.8	4623.4	5168.0	5607.0
40°	552.9	833.5	1483.7	2133.9	2784.1	3434.2	4070.5	4706.8	5343.0	5979.3	6543.4
42.5°	630.7	983.6	1742.1	2500.6	3256.4	4014.9	4851.3	5690.4	6526.7	7363.0	8229.9
45°	791.9	1267.0	2250.6	3234.2	4215.0	5198.6	6385.0	7574.2	8760.6	9949.8	11061.2
47.5°	1180.9	1906.0	3248.1	4590.1	5932.1	7274.1	8641.1	10008.1	11375.2	12742.2	14064.7
50°	1828.3	2925.8	4604.0	6282.2	7957.6	9635.8	11000.1	12364.3	13725.8	15090.0	16404.2
52.5°	2436.7	3901.0	5704.3	7510.3	9313.5	11119.5	12328.2	13536.8	14745.5	15954.1	17226.7
55°	2645.1	4253.9	6079.3	7907.6	9733.1	11561.3	12725.5	13892.5	15056.7	16220.9	17540.6
57.5°	2461.7	3920.5	5759.8	7599.2	9435.8	11275.1	12575.5	13878.6	15178.9	16482.0	17896.3
60°	2061.6	3231.4	5162.4	7096.3	9027.3	10958.4	12425.4	13892.5	15359.5	16826.6	18238.0
62.5°	1633.8	2578.4	4623.4	6668.4	8713.4	10758.3	12250.4	13745.2	15237.3	16729.3	17812.9
65°	1253.1	1972.7	3984.4	5998.8	8010.4	10024.8	11247.4	12472.7	13695.2	14920.5	15670.7
67.5°	930.8	1439.3	3198.0	4959.6	6718.4	8477.2	9377.4	10280.4	11180.7	12083.7	12667.2
70°	686.3	1025.3	2222.8	3420.3	4615.1	5812.6	6637.8	7463.0	8285.5	9110.7	9716.4
72.5°	475.1	655.7	1372.6	2092.2	2809.1	3525.9	4362.2	5198.6	6032.1	6868.4	7557.5
75°	325.1	402.9	739.1	1075.3	1411.5	1747.7	2381.2	3014.7	3648.2	4281.7	4645.6
77.5°	241.7	283.4	383.4	486.2	586.3	686.3	808.5	930.8	1053.0	1175.3	1333.7
80°	133.4	133.4	147.3	158.4	172.3	183.4	216.7	252.8	286.2	322.3	366.8
82.5°	61.1	63.9	69.5	75.0	77.8	83.4	88.9	94.5	100.0	105.6	105.6
85°	16.7	19.4	19.4	16.7	16.7	13.9	13.9	16.7	16.7	16.7	16.7
87.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	33.3	30.6	30.6	30.6	27.8	27.8	27.8	27.8	27.8	27.8	27.8
5°	38.9	38.9	38.9	38.9	36.1	36.1	36.1	36.1	36.1	33.3	33.3
7.5°	47.2	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	41.7	41.7
10°	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6	52.8	52.8
12.5°	69.5	69.5	69.5	69.5	72.2	72.2	69.5	69.5	69.5	66.7	66.7
15°	91.7	94.5	97.2	97.2	100.0	100.0	100.0	97.2	97.2	94.5	91.7
17.5°	155.6	163.9	175.0	186.2	197.3	205.6	205.6	200.1	194.5	188.9	183.4
20°	414.0	455.7	500.1	544.6	591.8	625.2	602.9	586.3	569.6	550.1	533.5
22.5°	1097.5	1214.2	1333.7	1417.0	1500.4	1558.7	1511.5	1419.8	1328.1	1239.2	1147.5
25°	2047.8	2261.7	2478.4	2567.3	2659.0	2725.7	2695.1	2556.2	2417.3	2281.1	2142.2
27.5°	3053.6	3353.6	3656.5	3734.3	3812.1	3870.4	3859.3	3678.7	3498.1	3317.5	3136.9
30°	3881.6	4159.4	4437.3	4515.1	4592.9	4645.6	4587.3	4406.7	4226.1	4045.5	3864.9
32.5°	4565.1	4859.6	5156.9	5259.7	5362.5	5432.0	5362.5	5145.8	4929.1	4715.1	4498.4
35°	5268.0	5626.5	5987.7	6118.2	6248.8	6332.2	6215.5	5948.8	5682.0	5418.1	5151.3
37.5°	6046.0	6482.2	6921.2	7099.1	7279.7	7404.7	7315.8	6982.4	6646.2	6312.7	5976.5
40°	7110.2	7674.2	8241.0	8560.5	8877.3	9102.4	8944.0	8557.8	8168.8	7782.6	7393.6
42.5°	9099.6	9966.5	10833.4	11291.8	11747.5	12078.1	11900.3	11425.2	10950.1	10474.9	9999.8
45°	12172.6	13281.2	14392.6	15062.2	15734.6	16229.2	16023.6	15426.2	14826.1	14228.7	13631.3
47.5°	15387.3	16709.9	18032.4	18565.9	19102.2	19518.9	19468.9	18724.3	17979.6	17237.8	16493.2
50°	17721.2	19035.5	20349.7	20808.2	21269.4	21611.1	21483.3	20535.9	19585.6	18638.2	17687.9
52.5°	18499.2	19769.0	21041.5	21588.9	22136.3	22544.7	22389.1	21322.2	20255.2	19191.1	18124.1
55°	18860.4	20180.2	21500.0	22166.8	22836.5	23325.5	23100.4	21930.7	20758.1	19588.4	18415.9
57.5°	19310.5	20724.8	22139.1	22869.8	23600.5	24128.5	23828.4	22617.0	21405.5	20196.9	18985.5
60°	19649.5	21058.2	22469.7	23056.0	23645.0	24056.2	23767.3	22589.2	21408.3	20230.2	19052.1
62.5°	18899.3	19982.9	21066.6	21502.8	21939.0	22255.8	22091.8	20974.9	19857.9	18741.0	17624.0
65°	16423.7	17173.9	17926.9	18221.4	18513.1	18738.2	18688.2	17746.3	16804.3	15865.2	14923.3
67.5°	13253.4	13836.9	14423.2	14839.9	15259.5	15584.6	15548.5	14689.9	13831.4	12972.8	12114.2
70°	10324.9	10930.6	11536.3	12061.5	12589.4	12997.8	12945.0	12147.6	11347.4	10549.9	9749.7
72.5°	8249.4	8938.4	9627.5	9927.6	10227.6	10438.8	10283.2	9680.3	9074.6	8471.6	7865.9
75°	5009.6	5370.8	5734.8	5732.0	5732.0	5698.7	5543.1	5198.6	4854.0	4509.5	4165.0
77.5°	1492.1	1650.4	1808.8	1961.6	2117.2	2233.9	2203.3	2022.7	1839.4	1658.8	1475.4
80°	411.2	452.9	497.4	516.8	536.2	561.3	625.2	580.7	536.2	494.6	450.1
82.5°	105.6	105.6	105.6	102.8	100.0	94.5	86.1	80.6	75.0	69.5	63.9
85°	16.7	13.9	13.9	13.9	11.1	11.1	11.1	11.1	8.3	8.3	5.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0
2.5°	27.8	27.8	25.0	25.0	25.0	25.0	25.0	25.0	25.0	25.0	22.2
5°	33.3	33.3	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	27.8
7.5°	41.7	41.7	38.9	38.9	38.9	38.9	36.1	36.1	36.1	36.1	33.3
10°	52.8	50.0	50.0	47.2	47.2	47.2	44.5	44.5	44.5	41.7	41.7
12.5°	66.7	63.9	63.9	61.1	58.3	58.3	55.6	52.8	50.0	50.0	47.2
15°	88.9	86.1	83.4	80.6	77.8	72.2	69.5	63.9	61.1	58.3	55.6
17.5°	169.5	155.6	141.7	127.8	116.7	105.6	94.5	83.4	77.8	72.2	66.7
20°	472.3	408.4	347.3	286.2	247.3	208.4	169.5	130.6	113.9	100.0	83.4
22.5°	1022.5	894.7	769.6	641.8	539.0	439.0	336.2	233.4	194.5	158.4	119.5
25°	1900.5	1656.0	1414.3	1169.7	975.3	780.8	586.3	391.8	319.5	247.3	175.0
27.5°	2820.2	2503.4	2186.7	1869.9	1561.5	1250.3	939.1	630.7	505.7	383.4	258.4
30°	3528.7	3192.5	2859.1	2522.9	2133.9	1744.9	1353.1	964.1	766.9	569.6	369.5
32.5°	4137.2	3773.2	3412.0	3048.0	2597.9	2147.8	1697.7	1247.5	1000.3	753.0	502.9
35°	4740.1	4326.1	3914.9	3500.9	3017.4	2534.0	2050.5	1567.1	1253.1	939.1	622.4
37.5°	5473.6	4968.0	4465.0	3962.1	3464.8	2970.2	2472.9	1975.5	1575.4	1178.1	778.0
40°	6751.7	6107.1	5465.3	4820.7	4240.0	3662.1	3081.4	2500.6	1997.7	1494.8	989.1
42.5°	9191.3	8382.7	7577.0	6768.4	5965.4	5162.4	4356.7	3553.7	2836.8	2122.8	1405.9
45°	12594.9	11558.5	10524.9	9488.6	8499.4	7513.1	6523.9	5534.8	4445.6	3356.4	2264.5
47.5°	15359.5	14223.1	13089.5	11953.1	10855.6	9760.9	8663.4	7565.8	6171.0	4779.0	3384.2
50°	16607.1	15523.5	14442.6	13359.0	12258.7	11155.7	10052.6	8952.3	7351.9	5754.3	4153.9
52.5°	17026.6	15926.3	14828.8	13728.5	12636.6	11544.7	10452.7	9360.8	7696.4	6034.9	4370.6
55°	17257.2	16095.8	14937.2	13775.8	12600.5	11422.4	10244.3	9069.0	7413.0	5759.8	4103.8
57.5°	17724.0	16459.8	15198.4	13934.2	12594.9	11255.7	9913.7	8574.4	6940.7	5306.9	3673.2
60°	17810.2	16565.4	15323.4	14081.4	12600.5	11119.5	9635.8	8154.9	6532.2	4912.4	3289.7
62.5°	16584.8	15545.7	14509.3	13470.1	11986.4	10502.7	9016.2	7532.5	5979.3	4426.1	2870.2
65°	14025.8	13128.4	12233.7	11336.3	10124.8	8916.2	7704.8	6493.3	5106.9	3723.2	2336.7
67.5°	11236.2	10358.2	9483.0	8605.0	7693.7	6785.1	5873.7	4962.4	3892.7	2823.0	1753.2
70°	8907.9	8063.2	7221.3	6376.6	5570.9	4762.3	3953.8	3148.0	2484.0	1822.7	1158.6
72.5°	7060.2	6251.6	5445.9	4637.3	3906.6	3175.8	2445.1	1714.3	1383.7	1055.8	725.2
75°	3745.4	3325.9	2909.1	2489.5	2078.3	1664.3	1250.3	839.1	708.5	577.9	444.6
77.5°	1292.0	1108.6	928.0	744.6	619.6	494.6	369.5	244.5	230.6	219.5	205.6
80°	391.8	333.4	275.1	216.7	191.7	166.7	141.7	116.7	108.4	100.0	88.9
82.5°	61.1	55.6	52.8	47.2	44.5	44.5	41.7	38.9	33.3	30.6	25.0
85°	5.6	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	25.0	25.0
2.5°	22.2	22.2
5°	27.8	27.8
7.5°	33.3	33.3
10°	38.9	38.9
12.5°	44.5	44.5
15°	52.8	50.0
17.5°	61.1	58.3
20°	66.7	61.1
22.5°	80.6	69.5
25°	102.8	86.1
27.5°	133.4	105.6
30°	172.3	133.4
32.5°	255.6	186.2
35°	308.4	225.1
37.5°	377.9	261.2
40°	486.2	316.7
42.5°	689.1	430.7
45°	1175.3	714.1
47.5°	1992.2	1217.0
50°	2553.4	1561.5
52.5°	2709.0	1656.0
55°	2450.6	1519.8
57.5°	2039.4	1292.0
60°	1669.9	1064.2
62.5°	1317.0	841.9
65°	950.2	636.3
67.5°	683.5	489.0
70°	497.4	383.4
72.5°	394.5	319.5
75°	314.0	266.7
77.5°	194.5	177.8
80°	80.6	75.0
82.5°	19.4	16.7
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066484

CATALOG NUMBER: NVN-SA2D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-3

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-727-U-5WQ

Data in this report applies to families of products including GSS-SB1A-727-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-3
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-727-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2700K CCT 26 LEDS

Spectral Parameters

CCT (K):	2672	CRI (Ra):	71.1		
CIE u':	0.2638	R1:	68.3	R9:	-27.8
CIE v':	0.5276	R2:	79.8	R10:	54.4
Duv:	-0.0002	R3:	91.2	R11:	65.8
CIE x:	0.4619	R4:	69.4	R12:	45.6
CIE y:	0.4106	R5:	66.5	R13:	69.8
CIE z:	0.1275	R6:	72.6	R14:	94.5
Peak Wavelength (nm):	601	R7:	77.0	R15:	60.1
Dominant Wavelength (nm):	584	R8:	44.1		
Purity:	61.88407				
Rf:	67.9				
Rg:	98.6				



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-3

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-3

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.02

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 1.71

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			


REPORT NUMBER: SP1-2407-184-3

TM-30-18



Summary

$R_f = 67.9$
 $R_g = 98.6$
 $CIE R_a = 71.1$
 $R_g = -27.8$

Spectral Power Distribution Comparison




Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 53	CES51 = 75	CES76 = 51
CES02 = 63	CES27 = 70	CES52 = 80	CES77 = 79
CES03 = 31	CES28 = 81	CES53 = 64	CES78 = 58
CES04 = 71	CES29 = 37	CES54 = 73	CES79 = 82
CES05 = 50	CES30 = 33	CES55 = 69	CES80 = 82
CES06 = 52	CES31 = 44	CES56 = 60	CES81 = 69
CES07 = 42	CES32 = 47	CES57 = 54	CES82 = 92
CES08 = 41	CES33 = 45	CES58 = 59	CES83 = 82
CES09 = 29	CES34 = 67	CES59 = 85	CES84 = 92
CES10 = 77	CES35 = 84	CES60 = 86	CES85 = 87
CES11 = 60	CES36 = 68	CES61 = 86	CES86 = 60
CES12 = 66	CES37 = 77	CES62 = 59	CES87 = 79
CES13 = 44	CES38 = 40	CES63 = 66	CES88 = 70
CES14 = 74	CES39 = 88	CES64 = 69	CES89 = 66
CES15 = 72	CES40 = 82	CES65 = 64	CES90 = 64
CES16 = 48	CES41 = 70	CES66 = 65	CES91 = 81
CES17 = 51	CES42 = 76	CES67 = 64	CES92 = 69
CES18 = 57	CES43 = 63	CES68 = 73	CES93 = 81
CES19 = 73	CES44 = 97	CES69 = 83	CES94 = 53
CES20 = 67	CES45 = 74	CES70 = 64	CES95 = 77
CES21 = 88	CES46 = 67	CES71 = 60	CES96 = 79
CES22 = 80	CES47 = 55	CES72 = 87	CES97 = 78
CES23 = 92	CES48 = 42	CES73 = 57	CES98 = 69
CES24 = 92	CES49 = 65	CES74 = 84	CES99 = 60
CES25 = 73	CES50 = 74	CES75 = 60	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)