

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066488

Luminaire Tested: **NVN-SA3D-727-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066488
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA3D-727-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1200mA 3xLight Square PACKAGE
70CRI 2700K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 2700K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 13187 lumens
Efficiency: N/A
Efficacy: 82.0 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 160.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.6 fc
 Type III - Short - N/A

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	78.4	0.0	78.4
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	13108.6	0.0	13108.6
	% Fixture	99.4	0.0	99.4
Total	Lumens	13187.0	0.0	13187.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.9	0.0
10°-20°	19.3	0.1
20°-30°	246.1	1.9
30°-40°	829.5	6.3
40°-50°	2505.1	19.0
50°-60°	4419.8	33.5
60°-70°	3893.9	29.5
70°-80°	1239.5	9.4
80°-90°	29.8	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	13187.0	100.0
0°-180°	13187.0	100.0



REPORT NUMBER: P1066488


CATALOG NUMBER: NVN-SA3D-727-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	257.6	2.0			
FM	(30°-60°)	7724.1	58.6			
FH	(60°-80°)	5102.6	38.7			G3/7500
FVH	(80°-90°)	24.3	0.2			G1/100
BL	(0°-30°)	11.8	0.1	B0/110		
BM	(30°-60°)	30.4	0.2	B0/220		
BH	(60°-80°)	30.7	0.2	B0/110		G0/110
BVH	(80°-90°)	5.6	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	28.9
5°	41.4	41.4	41.4	37.2	37.2	37.2	33.1	33.1	33.1	33.1	33.1
7.5°	49.6	45.5	45.5	41.4	41.4	41.4	37.2	37.2	37.2	37.2	33.1
10°	57.9	53.8	53.8	49.6	49.6	45.5	45.5	41.4	41.4	37.2	37.2
12.5°	66.2	62.0	57.9	53.8	53.8	49.6	49.6	45.5	45.5	41.4	41.4
15°	74.4	70.3	66.2	62.0	57.9	57.9	53.8	49.6	45.5	45.5	41.4
17.5°	86.8	78.6	74.4	66.2	62.0	57.9	53.8	49.6	49.6	45.5	45.5
20°	91.0	82.7	78.6	70.3	66.2	62.0	57.9	53.8	49.6	49.6	45.5
22.5°	107.5	91.0	86.8	78.6	74.4	70.3	62.0	57.9	53.8	49.6	45.5
25°	132.3	107.5	95.1	82.7	78.6	70.3	66.2	57.9	53.8	49.6	45.5
27.5°	161.3	119.9	107.5	91.0	82.7	74.4	66.2	57.9	53.8	49.6	45.5
30°	198.5	140.6	119.9	99.3	91.0	82.7	70.3	62.0	57.9	53.8	45.5
32.5°	277.1	173.7	140.6	107.5	95.1	86.8	74.4	62.0	57.9	53.8	45.5
35°	335.0	210.9	169.6	124.1	107.5	95.1	78.6	62.0	57.9	53.8	45.5
37.5°	388.7	215.0	173.7	132.3	115.8	99.3	78.6	62.0	57.9	53.8	45.5
40°	475.6	223.3	173.7	124.1	111.7	95.1	82.7	66.2	62.0	53.8	49.6
42.5°	641.0	256.4	186.1	115.8	103.4	95.1	82.7	70.3	62.0	57.9	49.6
45°	1066.9	380.5	252.3	119.9	107.5	95.1	82.7	70.3	66.2	57.9	53.8
47.5°	1815.5	661.7	392.9	124.1	111.7	95.1	82.7	66.2	62.0	57.9	49.6
50°	2324.1	847.8	496.3	144.7	124.1	107.5	86.8	66.2	62.0	57.9	53.8
52.5°	2468.9	901.5	537.6	169.6	144.7	119.9	91.0	66.2	62.0	62.0	57.9
55°	2262.1	876.7	537.6	198.5	165.4	136.5	103.4	70.3	66.2	66.2	62.0
57.5°	1923.0	810.5	512.8	215.0	182.0	144.7	111.7	74.4	70.3	70.3	66.2
60°	1583.9	682.3	463.2	239.9	202.6	165.4	128.2	91.0	86.8	82.7	74.4
62.5°	1257.2	550.0	405.3	256.4	219.2	177.8	140.6	99.3	95.1	91.0	86.8
65°	947.0	479.7	376.3	268.8	227.4	186.1	144.7	103.4	99.3	99.3	95.1
67.5°	727.8	438.4	359.8	277.1	235.7	194.4	153.0	111.7	107.5	103.4	99.3
70°	574.8	405.3	339.1	272.9	235.7	198.5	157.1	119.9	111.7	107.5	99.3
72.5°	479.7	368.1	314.3	260.5	231.6	202.6	173.7	144.7	128.2	115.8	99.3
75°	401.1	330.8	285.3	235.7	215.0	198.5	177.8	157.1	136.5	115.8	95.1
77.5°	264.7	239.9	219.2	198.5	186.1	173.7	157.1	144.7	124.1	107.5	86.8
80°	111.7	103.4	107.5	107.5	107.5	107.5	103.4	103.4	91.0	78.6	62.0
82.5°	24.8	20.7	24.8	24.8	24.8	24.8	20.7	20.7	20.7	16.5	16.5
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	28.9	28.9	28.9	28.9	28.9	28.9	28.9	28.9	28.9	28.9	28.9
5°	33.1	33.1	33.1	28.9	28.9	28.9	28.9	28.9	28.9	28.9	28.9
7.5°	33.1	33.1	33.1	28.9	28.9	28.9	28.9	24.8	24.8	24.8	24.8
10°	33.1	33.1	33.1	28.9	28.9	28.9	28.9	24.8	24.8	24.8	24.8
12.5°	37.2	37.2	33.1	33.1	28.9	28.9	28.9	24.8	24.8	24.8	24.8
15°	37.2	37.2	33.1	33.1	28.9	28.9	28.9	24.8	24.8	24.8	24.8
17.5°	41.4	37.2	37.2	33.1	28.9	28.9	28.9	24.8	24.8	24.8	24.8
20°	41.4	37.2	37.2	33.1	28.9	28.9	28.9	24.8	24.8	24.8	24.8
22.5°	41.4	37.2	37.2	33.1	28.9	28.9	24.8	24.8	20.7	20.7	16.5
25°	41.4	37.2	37.2	33.1	28.9	28.9	24.8	24.8	20.7	16.5	16.5
27.5°	41.4	37.2	37.2	33.1	28.9	24.8	24.8	20.7	16.5	12.4	12.4
30°	41.4	37.2	37.2	33.1	28.9	24.8	20.7	16.5	12.4	12.4	8.3
32.5°	41.4	37.2	33.1	28.9	24.8	20.7	20.7	16.5	12.4	8.3	8.3
35°	41.4	37.2	33.1	28.9	24.8	20.7	20.7	16.5	12.4	8.3	8.3
37.5°	41.4	37.2	33.1	28.9	24.8	20.7	16.5	12.4	8.3	8.3	4.1
40°	41.4	37.2	33.1	28.9	24.8	20.7	16.5	12.4	8.3	8.3	4.1
42.5°	41.4	37.2	33.1	28.9	24.8	20.7	16.5	12.4	8.3	8.3	4.1
45°	45.5	41.4	37.2	28.9	24.8	20.7	20.7	16.5	12.4	8.3	8.3
47.5°	45.5	41.4	37.2	28.9	24.8	20.7	20.7	16.5	12.4	8.3	8.3
50°	49.6	45.5	41.4	33.1	28.9	24.8	20.7	12.4	8.3	8.3	4.1
52.5°	53.8	49.6	45.5	41.4	37.2	28.9	20.7	12.4	4.1	4.1	4.1
55°	57.9	53.8	53.8	49.6	45.5	33.1	24.8	12.4	0.0	0.0	0.0
57.5°	62.0	57.9	57.9	53.8	49.6	37.2	24.8	12.4	0.0	0.0	0.0
60°	70.3	66.2	62.0	53.8	49.6	37.2	24.8	12.4	0.0	0.0	0.0
62.5°	82.7	74.4	62.0	53.8	41.4	33.1	20.7	12.4	0.0	0.0	0.0
65°	91.0	78.6	66.2	49.6	37.2	28.9	20.7	8.3	0.0	0.0	0.0
67.5°	95.1	78.6	66.2	49.6	33.1	24.8	16.5	8.3	0.0	0.0	0.0
70°	91.0	74.4	62.0	45.5	28.9	20.7	16.5	8.3	0.0	0.0	0.0
72.5°	82.7	70.3	53.8	41.4	24.8	20.7	12.4	8.3	0.0	0.0	0.0
75°	74.4	62.0	45.5	33.1	16.5	12.4	8.3	4.1	0.0	0.0	0.0
77.5°	66.2	53.8	37.2	24.8	8.3	8.3	4.1	4.1	0.0	0.0	0.0
80°	49.6	37.2	24.8	12.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	12.4	8.3	8.3	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	24.8	24.8	24.8	24.8	24.8	24.8	24.8	24.8	24.8	24.8	24.8
5°	24.8	24.8	24.8	24.8	20.7	20.7	20.7	20.7	20.7	20.7	20.7
7.5°	24.8	24.8	24.8	24.8	20.7	20.7	20.7	20.7	16.5	16.5	16.5
10°	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	16.5	16.5	16.5
12.5°	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	16.5	16.5	16.5
15°	20.7	20.7	20.7	20.7	20.7	20.7	20.7	16.5	16.5	12.4	12.4
17.5°	20.7	20.7	20.7	20.7	16.5	16.5	16.5	12.4	12.4	8.3	8.3
20°	20.7	20.7	20.7	16.5	16.5	12.4	12.4	8.3	8.3	4.1	4.1
22.5°	16.5	12.4	12.4	8.3	8.3	4.1	4.1	4.1	0.0	0.0	0.0
25°	12.4	8.3	8.3	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.3	4.1	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.3	4.1	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	24.8	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7
5°	20.7	20.7	20.7	20.7	16.5	16.5	16.5	16.5	16.5	16.5	16.5
7.5°	16.5	16.5	16.5	16.5	16.5	16.5	12.4	12.4	12.4	12.4	12.4
10°	16.5	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	8.3	8.3
12.5°	16.5	12.4	12.4	12.4	8.3	8.3	8.3	8.3	8.3	4.1	4.1
15°	12.4	8.3	8.3	8.3	4.1	4.1	4.1	4.1	4.1	0.0	0.0
17.5°	8.3	4.1	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	24.8	24.8
5°	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5
7.5°	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4
10°	8.3	8.3	8.3	8.3	8.3	8.3	4.1	4.1	4.1	4.1	4.1
12.5°	4.1	4.1	4.1	4.1	4.1	4.1	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	24.8	24.8	24.8	24.8	24.8	28.9	28.9	33.1	33.1	37.2	37.2
5°	16.5	16.5	20.7	20.7	20.7	20.7	24.8	24.8	24.8	28.9	28.9
7.5°	12.4	12.4	12.4	12.4	12.4	16.5	16.5	20.7	20.7	24.8	24.8
10°	4.1	4.1	8.3	8.3	8.3	8.3	12.4	12.4	12.4	16.5	20.7
12.5°	0.0	0.0	4.1	4.1	4.1	4.1	8.3	8.3	8.3	12.4	16.5
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	8.3	12.4
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	8.3
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	41.4	41.4	45.5	45.5	49.6	49.6	53.8	53.8	53.8	53.8	53.8
5°	33.1	33.1	37.2	41.4	41.4	45.5	49.6	49.6	49.6	49.6	49.6
7.5°	28.9	28.9	33.1	37.2	37.2	41.4	45.5	45.5	49.6	49.6	49.6
10°	20.7	24.8	28.9	33.1	33.1	37.2	41.4	41.4	45.5	45.5	45.5
12.5°	16.5	20.7	24.8	28.9	28.9	33.1	37.2	37.2	41.4	41.4	45.5
15°	12.4	16.5	20.7	24.8	24.8	28.9	33.1	33.1	37.2	41.4	45.5
17.5°	8.3	12.4	16.5	20.7	20.7	24.8	28.9	33.1	37.2	37.2	41.4
20°	8.3	8.3	12.4	16.5	16.5	20.7	24.8	28.9	33.1	33.1	37.2
22.5°	4.1	4.1	8.3	12.4	12.4	16.5	20.7	24.8	28.9	28.9	33.1
25°	0.0	0.0	4.1	8.3	8.3	12.4	16.5	16.5	20.7	20.7	24.8
27.5°	0.0	0.0	4.1	4.1	8.3	8.3	12.4	12.4	16.5	16.5	20.7
30°	0.0	0.0	4.1	4.1	8.3	8.3	12.4	12.4	16.5	16.5	16.5
32.5°	0.0	0.0	0.0	4.1	4.1	4.1	8.3	8.3	12.4	12.4	16.5
35°	0.0	0.0	0.0	4.1	4.1	4.1	8.3	8.3	12.4	12.4	12.4
37.5°	0.0	0.0	0.0	4.1	4.1	4.1	8.3	8.3	8.3	8.3	12.4
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.3	8.3	8.3
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.3	8.3	8.3
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.3	8.3	8.3
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.3	8.3	8.3
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.3	8.3	8.3
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.3	8.3	8.3
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.3	8.3	8.3
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	8.3
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	53.8	53.8
5°	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	49.6	49.6
7.5°	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	49.6	49.6
10°	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
12.5°	45.5	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
15°	45.5	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
17.5°	41.4	45.5	45.5	45.5	49.6	49.6	49.6	49.6	49.6	49.6	49.6
20°	37.2	41.4	41.4	41.4	45.5	45.5	45.5	45.5	49.6	49.6	49.6
22.5°	33.1	37.2	37.2	37.2	41.4	41.4	41.4	41.4	45.5	45.5	45.5
25°	28.9	28.9	33.1	33.1	37.2	37.2	37.2	37.2	37.2	37.2	37.2
27.5°	20.7	24.8	24.8	24.8	28.9	28.9	28.9	28.9	33.1	33.1	33.1
30°	20.7	20.7	20.7	20.7	24.8	24.8	24.8	24.8	28.9	28.9	28.9
32.5°	16.5	20.7	20.7	20.7	24.8	24.8	24.8	24.8	28.9	28.9	28.9
35°	16.5	16.5	16.5	16.5	20.7	20.7	20.7	20.7	24.8	24.8	24.8
37.5°	12.4	16.5	16.5	16.5	20.7	20.7	20.7	20.7	24.8	24.8	24.8
40°	12.4	12.4	12.4	12.4	16.5	16.5	16.5	16.5	20.7	20.7	20.7
42.5°	12.4	12.4	12.4	12.4	16.5	16.5	16.5	16.5	20.7	20.7	20.7
45°	12.4	12.4	12.4	12.4	16.5	16.5	16.5	16.5	20.7	20.7	20.7
47.5°	12.4	12.4	12.4	12.4	16.5	16.5	16.5	16.5	20.7	20.7	20.7
50°	12.4	12.4	12.4	12.4	16.5	16.5	16.5	16.5	20.7	20.7	20.7
52.5°	8.3	8.3	8.3	8.3	12.4	12.4	12.4	12.4	16.5	16.5	16.5
55°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	12.4	12.4	12.4
57.5°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	12.4	12.4	12.4
60°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
62.5°	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1
65°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	4.1	4.1
67.5°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
70°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
72.5°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
75°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
77.5°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
80°	12.4	12.4	12.4	12.4	12.4	8.3	8.3	8.3	8.3	8.3	8.3
82.5°	8.3	12.4	12.4	12.4	12.4	8.3	8.3	8.3	8.3	8.3	8.3
85°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
87.5°	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	53.8	53.8	49.6	49.6	49.6	49.6	49.6	49.6	49.6	53.8	53.8
5°	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	53.8	53.8
7.5°	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	53.8	53.8
10°	49.6	49.6	49.6	49.6	45.5	45.5	49.6	49.6	49.6	53.8	53.8
12.5°	49.6	49.6	49.6	49.6	45.5	45.5	49.6	49.6	53.8	53.8	57.9
15°	49.6	49.6	45.5	45.5	45.5	45.5	49.6	49.6	53.8	53.8	57.9
17.5°	49.6	49.6	45.5	45.5	45.5	45.5	49.6	49.6	53.8	53.8	57.9
20°	49.6	49.6	45.5	45.5	45.5	45.5	45.5	45.5	49.6	53.8	53.8
22.5°	45.5	45.5	45.5	45.5	41.4	41.4	45.5	45.5	49.6	53.8	53.8
25°	37.2	41.4	41.4	41.4	41.4	41.4	45.5	45.5	49.6	53.8	53.8
27.5°	33.1	37.2	37.2	37.2	37.2	41.4	41.4	45.5	49.6	53.8	53.8
30°	28.9	33.1	33.1	33.1	37.2	41.4	41.4	45.5	49.6	53.8	53.8
32.5°	28.9	33.1	33.1	33.1	37.2	37.2	41.4	41.4	45.5	49.6	53.8
35°	28.9	28.9	33.1	33.1	33.1	37.2	37.2	41.4	45.5	49.6	53.8
37.5°	28.9	28.9	33.1	33.1	33.1	37.2	37.2	41.4	45.5	49.6	53.8
40°	24.8	28.9	28.9	33.1	33.1	37.2	37.2	41.4	45.5	53.8	57.9
42.5°	24.8	24.8	28.9	28.9	33.1	37.2	37.2	41.4	45.5	53.8	57.9
45°	24.8	28.9	28.9	33.1	37.2	41.4	41.4	45.5	49.6	53.8	57.9
47.5°	24.8	28.9	28.9	33.1	41.4	41.4	45.5	45.5	49.6	53.8	57.9
50°	24.8	28.9	28.9	33.1	45.5	45.5	45.5	45.5	49.6	53.8	57.9
52.5°	20.7	24.8	24.8	28.9	37.2	41.4	45.5	49.6	53.8	57.9	62.0
55°	16.5	20.7	20.7	24.8	33.1	37.2	45.5	53.8	57.9	62.0	66.2
57.5°	16.5	16.5	20.7	20.7	28.9	37.2	49.6	57.9	62.0	66.2	70.3
60°	12.4	12.4	16.5	16.5	24.8	33.1	45.5	57.9	62.0	70.3	74.4
62.5°	8.3	12.4	12.4	16.5	20.7	33.1	45.5	57.9	66.2	74.4	78.6
65°	8.3	8.3	12.4	12.4	20.7	28.9	41.4	49.6	62.0	74.4	86.8
67.5°	12.4	12.4	16.5	16.5	20.7	28.9	41.4	49.6	62.0	78.6	91.0
70°	12.4	12.4	16.5	16.5	24.8	33.1	41.4	49.6	62.0	78.6	91.0
72.5°	12.4	12.4	16.5	16.5	24.8	28.9	37.2	45.5	57.9	70.3	82.7
75°	8.3	12.4	12.4	12.4	20.7	24.8	33.1	41.4	53.8	66.2	78.6
77.5°	8.3	8.3	8.3	8.3	16.5	20.7	28.9	33.1	45.5	57.9	70.3
80°	8.3	8.3	8.3	8.3	12.4	16.5	24.8	28.9	41.4	53.8	66.2
82.5°	8.3	8.3	4.1	4.1	8.3	12.4	16.5	20.7	33.1	41.4	53.8
85°	8.3	8.3	4.1	4.1	4.1	8.3	8.3	12.4	16.5	20.7	24.8
87.5°	8.3	8.3	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	53.8	53.8	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9
5°	53.8	57.9	57.9	62.0	62.0	62.0	66.2	66.2	66.2	66.2	66.2
7.5°	53.8	57.9	57.9	62.0	62.0	62.0	66.2	66.2	66.2	70.3	70.3
10°	53.8	57.9	57.9	62.0	62.0	66.2	70.3	70.3	74.4	74.4	74.4
12.5°	57.9	62.0	62.0	66.2	66.2	70.3	74.4	74.4	78.6	82.7	82.7
15°	57.9	62.0	66.2	66.2	70.3	74.4	78.6	78.6	82.7	86.8	91.0
17.5°	57.9	62.0	66.2	66.2	70.3	74.4	82.7	86.8	91.0	99.3	103.4
20°	57.9	62.0	66.2	66.2	70.3	78.6	82.7	91.0	95.1	103.4	111.7
22.5°	57.9	62.0	66.2	70.3	74.4	82.7	91.0	95.1	103.4	115.8	124.1
25°	57.9	62.0	66.2	70.3	74.4	82.7	91.0	99.3	107.5	124.1	140.6
27.5°	57.9	62.0	70.3	74.4	78.6	86.8	99.3	107.5	115.8	144.7	173.7
30°	57.9	62.0	70.3	74.4	78.6	91.0	103.4	111.7	124.1	173.7	219.2
32.5°	57.9	66.2	70.3	78.6	82.7	95.1	111.7	124.1	136.5	206.8	272.9
35°	57.9	66.2	70.3	78.6	82.7	99.3	115.8	132.3	148.9	252.3	355.6
37.5°	57.9	66.2	70.3	78.6	82.7	107.5	132.3	157.1	182.0	289.5	397.0
40°	62.0	70.3	74.4	82.7	86.8	111.7	136.5	161.3	186.1	293.6	401.1
42.5°	62.0	70.3	74.4	82.7	86.8	107.5	132.3	153.0	173.7	293.6	413.5
45°	62.0	70.3	78.6	82.7	91.0	111.7	132.3	148.9	169.6	322.6	471.4
47.5°	62.0	70.3	78.6	82.7	91.0	111.7	132.3	153.0	173.7	426.0	674.1
50°	62.0	70.3	78.6	82.7	91.0	115.8	140.6	165.4	190.2	636.9	1083.5
52.5°	66.2	70.3	78.6	82.7	86.8	115.8	144.7	173.7	202.6	827.1	1447.4
55°	70.3	74.4	78.6	82.7	86.8	124.1	161.3	198.5	235.7	889.1	1538.4
57.5°	74.4	78.6	82.7	82.7	86.8	132.3	182.0	227.4	272.9	885.0	1492.9
60°	78.6	82.7	86.8	91.0	95.1	140.6	190.2	235.7	281.2	802.3	1323.3
62.5°	86.8	95.1	103.4	107.5	115.8	161.3	202.6	248.1	289.5	657.5	1021.5
65°	99.3	107.5	111.7	119.9	124.1	165.4	210.9	252.3	293.6	545.9	794.0
67.5°	103.4	111.7	115.8	124.1	128.2	169.6	210.9	252.3	293.6	463.2	628.6
70°	103.4	111.7	119.9	124.1	132.3	173.7	210.9	252.3	289.5	401.1	512.8
72.5°	95.1	107.5	115.8	128.2	136.5	173.7	206.8	244.0	277.1	355.6	434.2
75°	91.0	107.5	119.9	136.5	148.9	173.7	202.6	227.4	252.3	310.2	368.1
77.5°	82.7	103.4	124.1	144.7	165.4	182.0	194.4	210.9	223.3	260.5	297.8
80°	78.6	99.3	119.9	140.6	161.3	169.6	173.7	182.0	186.1	190.2	194.4
82.5°	62.0	78.6	95.1	107.5	124.1	115.8	111.7	103.4	95.1	91.0	86.8
85°	28.9	33.1	33.1	37.2	37.2	37.2	33.1	33.1	28.9	24.8	20.7
87.5°	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	57.9	57.9	57.9	57.9	53.8	53.8	53.8	53.8	49.6	49.6	49.6
5°	66.2	66.2	66.2	66.2	62.0	62.0	62.0	62.0	57.9	57.9	57.9
7.5°	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3
10°	78.6	78.6	78.6	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7
12.5°	86.8	86.8	91.0	91.0	95.1	95.1	99.3	99.3	103.4	103.4	103.4
15°	95.1	99.3	103.4	107.5	107.5	111.7	115.8	119.9	124.1	128.2	132.3
17.5°	111.7	115.8	124.1	132.3	140.6	148.9	161.3	177.8	190.2	202.6	219.2
20°	124.1	136.5	161.3	190.2	215.0	239.9	301.9	363.9	426.0	488.0	550.0
22.5°	148.9	173.7	256.4	343.2	426.0	508.7	703.0	897.4	1087.6	1282.0	1455.7
25°	198.5	252.3	442.5	632.7	818.8	1009.0	1356.4	1707.9	2055.3	2402.7	2725.3
27.5°	272.9	372.2	682.3	996.6	1306.8	1617.0	2121.5	2630.1	3134.7	3643.3	4094.1
30°	380.5	541.7	1004.9	1472.2	1935.4	2398.6	3035.4	3676.4	4313.3	4950.1	5363.7
32.5°	516.9	756.8	1344.0	1931.3	2518.5	3105.7	3808.7	4511.8	5210.7	5913.7	6352.0
35°	661.7	967.7	1674.9	2386.1	3093.3	3804.6	4544.8	5285.1	6025.3	6765.6	7303.2
37.5°	744.4	1091.8	1931.3	2770.7	3606.1	4445.6	5256.1	6070.8	6881.4	7691.9	8345.3
40°	823.0	1240.6	2208.3	3176.0	4143.7	5111.4	6058.4	7005.4	7952.5	8899.5	9739.0
42.5°	938.7	1463.9	2592.9	3721.9	4846.7	5975.7	7220.5	8469.4	9714.2	10958.9	12249.2
45°	1178.6	1885.8	3349.7	4813.7	6273.5	7737.4	9503.2	11273.2	13039.0	14809.0	16463.2
47.5°	1757.6	2836.9	4834.3	6831.7	8829.2	10826.6	12861.2	14895.9	16930.5	18965.1	20933.6
50°	2721.1	4354.6	6852.4	9350.2	11843.9	14341.7	16372.2	18402.7	20429.1	22459.6	24415.6
52.5°	3626.8	5806.2	8490.1	11178.1	13862.0	16550.0	18349.0	20147.9	21946.8	23745.7	25639.7
55°	3936.9	6331.4	9048.3	11769.5	14486.4	17207.6	18940.3	20677.2	22410.0	24142.7	26107.0
57.5°	3664.0	5835.1	8572.8	11310.4	14044.0	16781.6	18717.0	20656.5	22591.9	24531.4	26636.4
60°	3068.5	4809.5	7683.6	10561.9	13436.0	16310.2	18493.7	20677.2	22860.7	25044.2	27145.0
62.5°	2431.6	3837.7	6881.4	9925.1	12968.7	16012.4	18233.2	20458.0	22678.8	24899.5	26512.3
65°	1865.1	2936.2	5930.2	8928.4	11922.5	14920.7	16740.3	18564.0	20383.6	22207.3	23323.9
67.5°	1385.4	2142.2	4759.9	7381.8	9999.5	12617.2	13957.1	15301.1	16641.0	17985.0	18853.5
70°	1021.5	1526.0	3308.4	5090.7	6869.0	8651.3	9879.6	11107.8	12331.9	13560.1	14461.6
72.5°	707.2	976.0	2042.9	3114.0	4180.9	5247.9	6492.6	7737.4	8978.0	10222.8	11248.4
75°	483.8	599.6	1100.0	1600.4	2100.8	2601.2	3544.1	4487.0	5429.8	6372.7	6914.5
77.5°	359.8	421.8	570.7	723.7	872.6	1021.5	1203.4	1385.4	1567.3	1749.3	1985.0
80°	198.5	198.5	219.2	235.7	256.4	272.9	322.6	376.3	426.0	479.7	545.9
82.5°	91.0	95.1	103.4	111.7	115.8	124.1	132.3	140.6	148.9	157.1	157.1
85°	24.8	28.9	28.9	24.8	24.8	20.7	20.7	24.8	24.8	24.8	24.8
87.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	49.6	45.5	45.5	45.5	41.4	41.4	41.4	41.4	41.4	41.4	41.4
5°	57.9	57.9	57.9	57.9	53.8	53.8	53.8	53.8	53.8	49.6	49.6
7.5°	70.3	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	62.0	62.0
10°	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7	82.7	78.6	78.6
12.5°	103.4	103.4	103.4	103.4	107.5	107.5	103.4	103.4	103.4	99.3	99.3
15°	136.5	140.6	144.7	144.7	148.9	148.9	148.9	144.7	144.7	140.6	136.5
17.5°	231.6	244.0	260.5	277.1	293.6	306.0	306.0	297.8	289.5	281.2	272.9
20°	616.2	678.2	744.4	810.5	880.8	930.5	897.4	872.6	847.8	818.8	794.0
22.5°	1633.5	1807.2	1985.0	2109.1	2233.1	2320.0	2249.7	2113.2	1976.7	1844.4	1707.9
25°	3047.8	3366.2	3688.8	3821.1	3957.6	4056.9	4011.4	3804.6	3597.8	3395.2	3188.4
27.5°	4544.8	4991.5	5442.2	5558.0	5673.8	5760.7	5744.1	5475.3	5206.5	4937.7	4668.9
30°	5777.2	6190.8	6604.3	6720.1	6835.9	6914.5	6827.6	6558.8	6290.0	6021.2	5752.4
32.5°	6794.5	7232.9	7675.4	7828.4	7981.4	8084.8	7981.4	7658.8	7336.3	7017.8	6695.3
35°	7840.8	8374.3	8911.9	9106.2	9300.6	9424.7	9251.0	8854.0	8457.0	8064.1	7667.1
37.5°	8998.7	9648.0	10301.4	10566.1	10834.9	11020.9	10888.6	10392.4	9892.0	9395.7	8895.3
40°	10582.6	11422.1	12265.7	12741.3	13212.7	13547.7	13312.0	12737.2	12158.2	11583.4	11004.4
42.5°	13543.6	14833.8	16124.1	16806.4	17484.6	17976.8	17712.1	17004.9	16297.8	15590.6	14883.5
45°	18117.4	19767.4	21421.6	22418.2	23419.0	24155.1	23849.1	22960.0	22066.7	21177.6	20288.5
47.5°	22902.1	24870.5	26839.0	27633.0	28431.2	29051.5	28977.0	27868.7	26760.4	25656.3	24548.0
50°	26375.8	28331.9	30288.0	30970.3	31656.8	32165.5	31975.2	30565.0	29150.7	27740.5	26326.2
52.5°	27533.8	29423.7	31317.7	32132.4	32947.1	33555.0	33323.4	31735.4	30147.4	28563.5	26975.5
55°	28071.4	30035.7	32000.0	32992.5	33989.2	34717.0	34382.1	32641.0	30895.9	29154.9	27409.7
57.5°	28741.3	30846.3	32951.2	34038.8	35126.4	35912.2	35465.5	33662.5	31859.4	30060.5	28257.5
60°	29245.8	31342.5	33443.3	34315.9	35192.6	35804.6	35374.6	33621.1	31863.6	30110.1	28356.7
62.5°	28129.3	29742.1	31354.9	32004.2	32653.4	33124.9	32880.9	31218.4	29556.0	27893.5	26231.1
65°	24444.6	25561.2	26681.9	27120.2	27554.4	27889.4	27815.0	26413.1	25011.1	23613.4	22211.5
67.5°	19726.1	20594.5	21467.1	22087.4	22711.8	23195.7	23141.9	21864.1	20586.2	19308.4	18030.5
70°	15367.3	16268.8	17170.4	17951.9	18737.7	19345.6	19267.0	18080.1	16889.1	15702.3	14511.3
72.5°	12278.1	13303.7	14329.3	14775.9	15222.6	15536.9	15305.3	14407.9	13506.3	12609.0	11707.4
75°	7456.2	7993.8	8535.5	8531.4	8531.4	8481.8	8250.2	7737.4	7224.6	6711.8	6199.0
77.5°	2220.7	2456.5	2692.2	2919.6	3151.2	3324.9	3279.4	3010.6	2737.7	2468.9	2195.9
80°	612.0	674.1	740.2	769.2	798.1	835.4	930.5	864.3	798.1	736.1	669.9
82.5°	157.1	157.1	157.1	153.0	148.9	140.6	128.2	119.9	111.7	103.4	95.1
85°	24.8	20.7	20.7	20.7	16.5	16.5	16.5	16.5	12.4	12.4	8.3
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2
2.5°	41.4	41.4	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	33.1
5°	49.6	49.6	45.5	45.5	45.5	45.5	45.5	45.5	45.5	45.5	41.4
7.5°	62.0	62.0	57.9	57.9	57.9	57.9	53.8	53.8	53.8	53.8	49.6
10°	78.6	74.4	74.4	70.3	70.3	70.3	66.2	66.2	66.2	62.0	62.0
12.5°	99.3	95.1	95.1	91.0	86.8	86.8	82.7	78.6	74.4	74.4	70.3
15°	132.3	128.2	124.1	119.9	115.8	107.5	103.4	95.1	91.0	86.8	82.7
17.5°	252.3	231.6	210.9	190.2	173.7	157.1	140.6	124.1	115.8	107.5	99.3
20°	703.0	607.9	516.9	426.0	368.1	310.2	252.3	194.4	169.6	148.9	124.1
22.5°	1521.8	1331.6	1145.5	955.3	802.3	653.4	500.4	347.4	289.5	235.7	177.8
25°	2828.6	2464.7	2104.9	1741.0	1451.5	1162.1	872.6	583.1	475.6	368.1	260.5
27.5°	4197.5	3726.0	3254.6	2783.2	2324.1	1860.9	1397.8	938.7	752.7	570.7	384.6
30°	5252.0	4751.6	4255.4	3755.0	3176.0	2597.1	2014.0	1435.0	1141.4	847.8	550.0
32.5°	6157.7	5615.9	5078.3	4536.6	3866.6	3196.7	2526.8	1856.8	1488.8	1120.7	748.5
35°	7055.1	6438.9	5826.8	5210.7	4491.1	3771.5	3052.0	2332.4	1865.1	1397.8	926.3
37.5°	8146.8	7394.2	6645.7	5897.1	5156.9	4420.8	3680.5	2940.3	2344.8	1753.4	1157.9
40°	10049.1	9089.7	8134.4	7175.0	6310.7	5450.5	4586.2	3721.9	2973.4	2224.9	1472.2
42.5°	13680.0	12476.6	11277.3	10073.9	8878.8	7683.6	6484.4	5289.2	4222.3	3159.5	2092.5
45°	18746.0	17203.4	15665.0	14122.5	12650.3	11182.2	9710.0	8237.8	6616.7	4995.6	3370.4
47.5°	22860.7	21169.3	19482.1	17790.7	16157.2	14527.8	12894.3	11260.8	9184.8	7113.0	5037.0
50°	24717.5	23104.7	21496.0	19883.2	18245.6	16603.8	14962.0	13324.4	10942.4	8564.5	6182.5
52.5°	25342.0	23704.3	22070.8	20433.2	18808.0	17182.8	15557.5	13932.3	11455.2	8982.2	6505.0
55°	25685.2	23956.6	22232.1	20503.5	18754.2	17000.8	15247.4	13498.1	11033.4	8572.8	6108.0
57.5°	26380.0	24498.4	22620.9	20739.2	18746.0	16752.7	14755.3	12762.0	10330.3	7898.7	5467.1
60°	26508.2	24655.5	22807.0	20958.4	18754.2	16550.0	14341.7	12137.5	9722.4	7311.5	4896.4
62.5°	24684.4	23137.8	21595.3	20048.6	17840.3	15632.0	13419.5	11211.2	8899.5	6587.8	4271.9
65°	20875.7	19540.0	18208.3	16872.6	15069.5	13270.6	11467.6	9664.5	7600.9	5541.5	3477.9
67.5°	16723.7	15416.9	14114.3	12807.5	11451.0	10098.7	8742.3	7385.9	5793.8	4201.6	2609.5
70°	13258.2	12001.0	10748.0	9490.8	8291.6	7088.1	5884.7	4685.5	3697.1	2712.8	1724.5
72.5°	10508.2	9304.7	8105.5	6902.1	5814.4	4726.8	3639.2	2551.6	2059.4	1571.5	1079.4
75°	5574.6	4950.1	4329.8	3705.4	3093.3	2477.1	1860.9	1248.9	1054.5	860.2	661.7
77.5°	1923.0	1650.0	1381.2	1108.3	922.2	736.1	550.0	363.9	343.2	326.7	306.0
80°	583.1	496.3	409.4	322.6	285.3	248.1	210.9	173.7	161.3	148.9	132.3
82.5°	91.0	82.7	78.6	70.3	66.2	66.2	62.0	57.9	49.6	45.5	37.2
85°	8.3	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066488
 CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	37.2	37.2
2.5°	33.1	33.1
5°	41.4	41.4
7.5°	49.6	49.6
10°	57.9	57.9
12.5°	66.2	66.2
15°	78.6	74.4
17.5°	91.0	86.8
20°	99.3	91.0
22.5°	119.9	103.4
25°	153.0	128.2
27.5°	198.5	157.1
30°	256.4	198.5
32.5°	380.5	277.1
35°	459.0	335.0
37.5°	562.4	388.7
40°	723.7	471.4
42.5°	1025.6	641.0
45°	1749.3	1062.8
47.5°	2965.1	1811.3
50°	3800.5	2324.1
52.5°	4032.1	2464.7
55°	3647.5	2262.1
57.5°	3035.4	1923.0
60°	2485.4	1583.9
62.5°	1960.2	1253.0
65°	1414.3	947.0
67.5°	1017.3	727.8
70°	740.2	570.7
72.5°	587.2	475.6
75°	467.3	397.0
77.5°	289.5	264.7
80°	119.9	111.7
82.5°	28.9	24.8
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066488

CATALOG NUMBER: NVN-SA3D-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-3

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-727-U-5WQ


Data in this report applies to families of products including GSS-SB1A-727-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-3
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-727-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2700K CCT 26 LEDS

Spectral Parameters

CCT (K):	2672	CRI (Ra):	71.1		
CIE u':	0.2638	R1:	68.3	R9:	-27.8
CIE v':	0.5276	R2:	79.8	R10:	54.4
Duv:	-0.0002	R3:	91.2	R11:	65.8
CIE x:	0.4619	R4:	69.4	R12:	45.6
CIE y:	0.4106	R5:	66.5	R13:	69.8
CIE z:	0.1275	R6:	72.6	R14:	94.5
Peak Wavelength (nm):	601	R7:	77.0	R15:	60.1
Dominant Wavelength (nm):	584	R8:	44.1		
Purity:	61.88407				
Rf:	67.9				
Rg:	98.6				



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-3


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-3

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



REPORT NUMBER: SP1-2407-184-3

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.02

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 1.71

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			


REPORT NUMBER: SP1-2407-184-3

TM-30-18





Summary

$R_f = 67.9$
 $R_g = 98.6$
 $CIE R_a = 71.1$
 $R_g = -27.8$

Spectral Power Distribution Comparison




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 53	CES51 = 75	CES76 = 51
CES02 = 63	CES27 = 70	CES52 = 80	CES77 = 79
CES03 = 31	CES28 = 81	CES53 = 64	CES78 = 58
CES04 = 71	CES29 = 37	CES54 = 73	CES79 = 82
CES05 = 50	CES30 = 33	CES55 = 69	CES80 = 82
CES06 = 52	CES31 = 44	CES56 = 60	CES81 = 69
CES07 = 42	CES32 = 47	CES57 = 54	CES82 = 92
CES08 = 41	CES33 = 45	CES58 = 59	CES83 = 82
CES09 = 29	CES34 = 67	CES59 = 85	CES84 = 92
CES10 = 77	CES35 = 84	CES60 = 86	CES85 = 87
CES11 = 60	CES36 = 68	CES61 = 86	CES86 = 60
CES12 = 66	CES37 = 77	CES62 = 59	CES87 = 79
CES13 = 44	CES38 = 40	CES63 = 66	CES88 = 70
CES14 = 74	CES39 = 88	CES64 = 69	CES89 = 66
CES15 = 72	CES40 = 82	CES65 = 64	CES90 = 64
CES16 = 48	CES41 = 70	CES66 = 65	CES91 = 81
CES17 = 51	CES42 = 76	CES67 = 64	CES92 = 69
CES18 = 57	CES43 = 63	CES68 = 73	CES93 = 81
CES19 = 73	CES44 = 97	CES69 = 83	CES94 = 53
CES20 = 67	CES45 = 74	CES70 = 64	CES95 = 77
CES21 = 88	CES46 = 67	CES71 = 60	CES96 = 79
CES22 = 80	CES47 = 55	CES72 = 87	CES97 = 78
CES23 = 92	CES48 = 42	CES73 = 57	CES98 = 69
CES24 = 92	CES49 = 65	CES74 = 84	CES99 = 60
CES25 = 73	CES50 = 74	CES75 = 60	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)