

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066490

Luminaire Tested: **NVN-SA4B-727-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066490
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA4B-727-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 4xLight Square PACKAGE
70CRI 2700K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 2700K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 12713.5 lumens
Efficiency: N/A
Efficacy: 88.2 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 144.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.5 fc
 Type III - Short - N/A

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	75.6	0.0	75.6
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	12637.8	0.0	12637.8
	% Fixture	99.4	0.0	99.4
Total	Lumens	12713.5	0.0	12713.5
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.8	0.0
10°-20°	18.7	0.1
20°-30°	237.3	1.9
30°-40°	799.7	6.3
40°-50°	2415.2	19.0
50°-60°	4261.1	33.5
60°-70°	3754.0	29.5
70°-80°	1195.0	9.4
80°-90°	28.8	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	12713.5	100.0
0°-180°	12713.5	100.0



REPORT NUMBER: P1066490


CATALOG NUMBER: NVN-SA4B-727-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	248.4	2.0			
FM	(30°-60°)	7446.7	58.6			
FH	(60°-80°)	4919.4	38.7			G2/5000
FVH	(80°-90°)	23.4	0.2			G1/100
BL	(0°-30°)	11.3	0.1	B0/110		
BM	(30°-60°)	29.3	0.2	B0/220		
BH	(60°-80°)	29.6	0.2	B0/110		G0/110
BVH	(80°-90°)	5.4	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	27.9
5°	39.9	39.9	39.9	35.9	35.9	35.9	31.9	31.9	31.9	31.9	31.9
7.5°	47.8	43.9	43.9	39.9	39.9	39.9	35.9	35.9	35.9	35.9	31.9
10°	55.8	51.8	51.8	47.8	47.8	43.9	43.9	39.9	39.9	35.9	35.9
12.5°	63.8	59.8	55.8	51.8	51.8	47.8	47.8	43.9	43.9	39.9	39.9
15°	71.8	67.8	63.8	59.8	55.8	55.8	51.8	47.8	43.9	43.9	39.9
17.5°	83.7	75.8	71.8	63.8	59.8	55.8	51.8	47.8	47.8	43.9	43.9
20°	87.7	79.7	75.8	67.8	63.8	59.8	55.8	51.8	47.8	47.8	43.9
22.5°	103.7	87.7	83.7	75.8	71.8	67.8	59.8	55.8	51.8	47.8	43.9
25°	127.6	103.7	91.7	79.7	75.8	67.8	63.8	55.8	51.8	47.8	43.9
27.5°	155.5	115.6	103.7	87.7	79.7	71.8	63.8	55.8	51.8	47.8	43.9
30°	191.4	135.6	115.6	95.7	87.7	79.7	67.8	59.8	55.8	51.8	43.9
32.5°	267.1	167.5	135.6	103.7	91.7	83.7	71.8	59.8	55.8	51.8	43.9
35°	322.9	203.3	163.5	119.6	103.7	91.7	75.8	59.8	55.8	51.8	43.9
37.5°	374.8	207.3	167.5	127.6	111.6	95.7	75.8	59.8	55.8	51.8	43.9
40°	458.5	215.3	167.5	119.6	107.6	91.7	79.7	63.8	59.8	51.8	47.8
42.5°	618.0	247.2	179.4	111.6	99.7	91.7	79.7	67.8	59.8	55.8	47.8
45°	1028.6	366.8	243.2	115.6	103.7	91.7	79.7	67.8	63.8	55.8	51.8
47.5°	1750.3	637.9	378.8	119.6	107.6	91.7	79.7	63.8	59.8	55.8	47.8
50°	2240.7	817.3	478.4	139.5	119.6	103.7	83.7	63.8	59.8	55.8	51.8
52.5°	2380.2	869.2	518.3	163.5	139.5	115.6	87.7	63.8	59.8	59.8	55.8
55°	2180.9	845.2	518.3	191.4	159.5	131.6	99.7	67.8	63.8	63.8	59.8
57.5°	1853.9	781.4	494.4	207.3	175.4	139.5	107.6	71.8	67.8	67.8	63.8
60°	1527.0	657.8	446.5	231.2	195.4	159.5	123.6	87.7	83.7	79.7	71.8
62.5°	1212.0	530.3	390.7	247.2	211.3	171.4	135.6	95.7	91.7	87.7	83.7
65°	913.0	462.5	362.8	259.2	219.3	179.4	139.5	99.7	95.7	95.7	91.7
67.5°	701.7	422.6	346.9	267.1	227.3	187.4	147.5	107.6	103.7	99.7	95.7
70°	554.2	390.7	326.9	263.1	227.3	191.4	151.5	115.6	107.6	103.7	95.7
72.5°	462.5	354.8	303.0	251.2	223.3	195.4	167.5	139.5	123.6	111.6	95.7
75°	386.7	319.0	275.1	227.3	207.3	191.4	171.4	151.5	131.6	111.6	91.7
77.5°	255.2	231.2	211.3	191.4	179.4	167.5	151.5	139.5	119.6	103.7	83.7
80°	107.6	99.7	103.7	103.7	103.7	103.7	99.7	99.7	87.7	75.8	59.8
82.5°	23.9	19.9	23.9	23.9	23.9	23.9	19.9	19.9	19.9	15.9	15.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	27.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9
5°	31.9	31.9	31.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9
7.5°	31.9	31.9	31.9	27.9	27.9	27.9	27.9	23.9	23.9	23.9	23.9
10°	31.9	31.9	31.9	27.9	27.9	27.9	27.9	23.9	23.9	23.9	23.9
12.5°	35.9	35.9	31.9	31.9	27.9	27.9	27.9	23.9	23.9	23.9	23.9
15°	35.9	35.9	31.9	31.9	27.9	27.9	27.9	23.9	23.9	23.9	23.9
17.5°	39.9	35.9	35.9	31.9	27.9	27.9	27.9	23.9	23.9	23.9	23.9
20°	39.9	35.9	35.9	31.9	27.9	27.9	27.9	23.9	23.9	23.9	23.9
22.5°	39.9	35.9	35.9	31.9	27.9	27.9	23.9	23.9	19.9	19.9	15.9
25°	39.9	35.9	35.9	31.9	27.9	27.9	23.9	23.9	19.9	15.9	15.9
27.5°	39.9	35.9	35.9	31.9	27.9	23.9	23.9	19.9	15.9	12.0	12.0
30°	39.9	35.9	35.9	31.9	27.9	23.9	19.9	15.9	12.0	12.0	8.0
32.5°	39.9	35.9	31.9	27.9	23.9	19.9	19.9	15.9	12.0	8.0	8.0
35°	39.9	35.9	31.9	27.9	23.9	19.9	19.9	15.9	12.0	8.0	8.0
37.5°	39.9	35.9	31.9	27.9	23.9	19.9	15.9	12.0	8.0	8.0	4.0
40°	39.9	35.9	31.9	27.9	23.9	19.9	15.9	12.0	8.0	8.0	4.0
42.5°	39.9	35.9	31.9	27.9	23.9	19.9	15.9	12.0	8.0	8.0	4.0
45°	43.9	39.9	35.9	27.9	23.9	19.9	19.9	15.9	12.0	8.0	8.0
47.5°	43.9	39.9	35.9	27.9	23.9	19.9	19.9	15.9	12.0	8.0	8.0
50°	47.8	43.9	39.9	31.9	27.9	23.9	19.9	12.0	8.0	8.0	4.0
52.5°	51.8	47.8	43.9	39.9	35.9	27.9	19.9	12.0	4.0	4.0	4.0
55°	55.8	51.8	51.8	47.8	43.9	31.9	23.9	12.0	0.0	0.0	0.0
57.5°	59.8	55.8	55.8	51.8	47.8	35.9	23.9	12.0	0.0	0.0	0.0
60°	67.8	63.8	59.8	51.8	47.8	35.9	23.9	12.0	0.0	0.0	0.0
62.5°	79.7	71.8	59.8	51.8	39.9	31.9	19.9	12.0	0.0	0.0	0.0
65°	87.7	75.8	63.8	47.8	35.9	27.9	19.9	8.0	0.0	0.0	0.0
67.5°	91.7	75.8	63.8	47.8	31.9	23.9	15.9	8.0	0.0	0.0	0.0
70°	87.7	71.8	59.8	43.9	27.9	19.9	15.9	8.0	0.0	0.0	0.0
72.5°	79.7	67.8	51.8	39.9	23.9	19.9	12.0	8.0	0.0	0.0	0.0
75°	71.8	59.8	43.9	31.9	15.9	12.0	8.0	4.0	0.0	0.0	0.0
77.5°	63.8	51.8	35.9	23.9	8.0	8.0	4.0	4.0	0.0	0.0	0.0
80°	47.8	35.9	23.9	12.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	12.0	8.0	8.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	23.9	23.9	23.9	23.9	23.9	23.9	23.9	23.9	23.9	23.9	23.9
5°	23.9	23.9	23.9	23.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9
7.5°	23.9	23.9	23.9	23.9	19.9	19.9	19.9	19.9	15.9	15.9	15.9
10°	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	15.9	15.9	15.9
12.5°	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	15.9	15.9	15.9
15°	19.9	19.9	19.9	19.9	19.9	19.9	19.9	15.9	15.9	12.0	12.0
17.5°	19.9	19.9	19.9	19.9	15.9	15.9	15.9	12.0	12.0	8.0	8.0
20°	19.9	19.9	19.9	15.9	15.9	12.0	12.0	8.0	8.0	4.0	4.0
22.5°	15.9	12.0	12.0	8.0	8.0	4.0	4.0	4.0	0.0	0.0	0.0
25°	12.0	8.0	8.0	4.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.0	4.0	4.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.0	4.0	4.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	23.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9
5°	19.9	19.9	19.9	19.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9
7.5°	15.9	15.9	15.9	15.9	15.9	15.9	12.0	12.0	12.0	12.0	12.0
10°	15.9	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	8.0	8.0
12.5°	15.9	12.0	12.0	12.0	8.0	8.0	8.0	8.0	8.0	4.0	4.0
15°	12.0	8.0	8.0	8.0	4.0	4.0	4.0	4.0	4.0	0.0	0.0
17.5°	8.0	4.0	4.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	23.9	23.9
5°	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9
7.5°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
10°	8.0	8.0	8.0	8.0	8.0	8.0	4.0	4.0	4.0	4.0	4.0
12.5°	4.0	4.0	4.0	4.0	4.0	4.0	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	23.9	23.9	23.9	23.9	23.9	27.9	27.9	31.9	31.9	35.9	35.9
5°	15.9	15.9	19.9	19.9	19.9	19.9	23.9	23.9	23.9	27.9	27.9
7.5°	12.0	12.0	12.0	12.0	12.0	15.9	15.9	19.9	19.9	23.9	23.9
10°	4.0	4.0	8.0	8.0	8.0	8.0	12.0	12.0	12.0	15.9	19.9
12.5°	0.0	0.0	4.0	4.0	4.0	4.0	8.0	8.0	8.0	12.0	15.9
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0	8.0	12.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	8.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	39.9	39.9	43.9	43.9	47.8	47.8	51.8	51.8	51.8	51.8	51.8
5°	31.9	31.9	35.9	39.9	39.9	43.9	47.8	47.8	47.8	47.8	47.8
7.5°	27.9	27.9	31.9	35.9	35.9	39.9	43.9	43.9	47.8	47.8	47.8
10°	19.9	23.9	27.9	31.9	31.9	35.9	39.9	39.9	43.9	43.9	43.9
12.5°	15.9	19.9	23.9	27.9	27.9	31.9	35.9	35.9	39.9	39.9	43.9
15°	12.0	15.9	19.9	23.9	23.9	27.9	31.9	31.9	35.9	39.9	43.9
17.5°	8.0	12.0	15.9	19.9	19.9	23.9	27.9	31.9	35.9	35.9	39.9
20°	8.0	8.0	12.0	15.9	15.9	19.9	23.9	27.9	31.9	31.9	35.9
22.5°	4.0	4.0	8.0	12.0	12.0	15.9	19.9	23.9	27.9	27.9	31.9
25°	0.0	0.0	4.0	8.0	8.0	12.0	15.9	15.9	19.9	19.9	23.9
27.5°	0.0	0.0	4.0	4.0	8.0	8.0	12.0	12.0	15.9	15.9	19.9
30°	0.0	0.0	4.0	4.0	8.0	8.0	12.0	12.0	15.9	15.9	15.9
32.5°	0.0	0.0	0.0	4.0	4.0	4.0	8.0	8.0	12.0	12.0	15.9
35°	0.0	0.0	0.0	4.0	4.0	4.0	8.0	8.0	12.0	12.0	12.0
37.5°	0.0	0.0	0.0	4.0	4.0	4.0	8.0	8.0	8.0	8.0	12.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	8.0	8.0	8.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	8.0	8.0	8.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	8.0	8.0	8.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	8.0	8.0	8.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	8.0	8.0	8.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0	4.0	4.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0	4.0	4.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0	4.0	4.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0	4.0	4.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	8.0	8.0	8.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	8.0	8.0	8.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0	4.0	8.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0	4.0	4.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.0	4.0	4.0	4.0	4.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	51.8	51.8
5°	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	47.8	47.8
7.5°	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	47.8	47.8
10°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
12.5°	43.9	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
15°	43.9	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
17.5°	39.9	43.9	43.9	43.9	47.8	47.8	47.8	47.8	47.8	47.8	47.8
20°	35.9	39.9	39.9	39.9	43.9	43.9	43.9	43.9	47.8	47.8	47.8
22.5°	31.9	35.9	35.9	35.9	39.9	39.9	39.9	39.9	43.9	43.9	43.9
25°	27.9	27.9	31.9	31.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
27.5°	19.9	23.9	23.9	23.9	27.9	27.9	27.9	27.9	31.9	31.9	31.9
30°	19.9	19.9	19.9	19.9	23.9	23.9	23.9	23.9	27.9	27.9	27.9
32.5°	15.9	19.9	19.9	19.9	23.9	23.9	23.9	23.9	27.9	27.9	27.9
35°	15.9	15.9	15.9	15.9	19.9	19.9	19.9	19.9	23.9	23.9	23.9
37.5°	12.0	15.9	15.9	15.9	19.9	19.9	19.9	19.9	23.9	23.9	23.9
40°	12.0	12.0	12.0	12.0	15.9	15.9	15.9	15.9	19.9	19.9	19.9
42.5°	12.0	12.0	12.0	12.0	15.9	15.9	15.9	15.9	19.9	19.9	19.9
45°	12.0	12.0	12.0	12.0	15.9	15.9	15.9	15.9	19.9	19.9	19.9
47.5°	12.0	12.0	12.0	12.0	15.9	15.9	15.9	15.9	19.9	19.9	19.9
50°	12.0	12.0	12.0	12.0	15.9	15.9	15.9	15.9	19.9	19.9	19.9
52.5°	8.0	8.0	8.0	8.0	12.0	12.0	12.0	12.0	15.9	15.9	15.9
55°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	12.0	12.0	12.0
57.5°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	12.0	12.0	12.0
60°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
62.5°	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
65°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	4.0	4.0
67.5°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
70°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
72.5°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
75°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
77.5°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
80°	12.0	12.0	12.0	12.0	12.0	8.0	8.0	8.0	8.0	8.0	8.0
82.5°	8.0	12.0	12.0	12.0	12.0	8.0	8.0	8.0	8.0	8.0	8.0
85°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
87.5°	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	51.8	51.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	51.8	51.8
5°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	51.8	51.8
7.5°	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	51.8	51.8
10°	47.8	47.8	47.8	47.8	43.9	43.9	47.8	47.8	47.8	51.8	51.8
12.5°	47.8	47.8	47.8	47.8	43.9	43.9	47.8	47.8	51.8	51.8	55.8
15°	47.8	47.8	43.9	43.9	43.9	43.9	47.8	47.8	51.8	51.8	55.8
17.5°	47.8	47.8	43.9	43.9	43.9	43.9	47.8	47.8	51.8	51.8	55.8
20°	47.8	47.8	43.9	43.9	43.9	43.9	43.9	43.9	47.8	51.8	51.8
22.5°	43.9	43.9	43.9	43.9	39.9	39.9	43.9	43.9	47.8	51.8	51.8
25°	35.9	39.9	39.9	39.9	39.9	39.9	43.9	43.9	47.8	51.8	51.8
27.5°	31.9	35.9	35.9	35.9	35.9	39.9	39.9	43.9	47.8	51.8	51.8
30°	27.9	31.9	31.9	31.9	35.9	39.9	39.9	43.9	47.8	51.8	51.8
32.5°	27.9	31.9	31.9	31.9	35.9	35.9	39.9	39.9	43.9	47.8	51.8
35°	27.9	27.9	31.9	31.9	31.9	35.9	35.9	39.9	43.9	47.8	51.8
37.5°	27.9	27.9	31.9	31.9	31.9	35.9	35.9	39.9	43.9	47.8	51.8
40°	23.9	27.9	27.9	31.9	31.9	35.9	35.9	39.9	43.9	51.8	55.8
42.5°	23.9	23.9	27.9	27.9	31.9	35.9	35.9	39.9	43.9	51.8	55.8
45°	23.9	27.9	27.9	31.9	35.9	39.9	39.9	43.9	47.8	51.8	55.8
47.5°	23.9	27.9	27.9	31.9	39.9	39.9	43.9	43.9	47.8	51.8	55.8
50°	23.9	27.9	27.9	31.9	43.9	43.9	43.9	43.9	47.8	51.8	55.8
52.5°	19.9	23.9	23.9	27.9	35.9	39.9	43.9	47.8	51.8	55.8	59.8
55°	15.9	19.9	19.9	23.9	31.9	35.9	43.9	51.8	55.8	59.8	63.8
57.5°	15.9	15.9	19.9	19.9	27.9	35.9	47.8	55.8	59.8	63.8	67.8
60°	12.0	12.0	15.9	15.9	23.9	31.9	43.9	55.8	59.8	67.8	71.8
62.5°	8.0	12.0	12.0	15.9	19.9	31.9	43.9	55.8	63.8	71.8	75.8
65°	8.0	8.0	12.0	12.0	19.9	27.9	39.9	47.8	59.8	71.8	83.7
67.5°	12.0	12.0	15.9	15.9	19.9	27.9	39.9	47.8	59.8	75.8	87.7
70°	12.0	12.0	15.9	15.9	23.9	31.9	39.9	47.8	59.8	75.8	87.7
72.5°	12.0	12.0	15.9	15.9	23.9	27.9	35.9	43.9	55.8	67.8	79.7
75°	8.0	12.0	12.0	12.0	19.9	23.9	31.9	39.9	51.8	63.8	75.8
77.5°	8.0	8.0	8.0	8.0	15.9	19.9	27.9	31.9	43.9	55.8	67.8
80°	8.0	8.0	8.0	8.0	12.0	15.9	23.9	27.9	39.9	51.8	63.8
82.5°	8.0	8.0	4.0	4.0	8.0	12.0	15.9	19.9	31.9	39.9	51.8
85°	8.0	8.0	4.0	4.0	4.0	8.0	8.0	12.0	15.9	19.9	23.9
87.5°	8.0	8.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	51.8	51.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8
5°	51.8	55.8	55.8	59.8	59.8	59.8	63.8	63.8	63.8	63.8	63.8
7.5°	51.8	55.8	55.8	59.8	59.8	59.8	63.8	63.8	63.8	67.8	67.8
10°	51.8	55.8	55.8	59.8	59.8	63.8	67.8	67.8	71.8	71.8	71.8
12.5°	55.8	59.8	59.8	63.8	63.8	67.8	71.8	71.8	75.8	79.7	79.7
15°	55.8	59.8	63.8	63.8	67.8	71.8	75.8	75.8	79.7	83.7	87.7
17.5°	55.8	59.8	63.8	63.8	67.8	71.8	79.7	83.7	87.7	95.7	99.7
20°	55.8	59.8	63.8	63.8	67.8	75.8	79.7	87.7	91.7	99.7	107.6
22.5°	55.8	59.8	63.8	67.8	71.8	79.7	87.7	91.7	99.7	111.6	119.6
25°	55.8	59.8	63.8	67.8	71.8	79.7	87.7	95.7	103.7	119.6	135.6
27.5°	55.8	59.8	67.8	71.8	75.8	83.7	95.7	103.7	111.6	139.5	167.5
30°	55.8	59.8	67.8	71.8	75.8	87.7	99.7	107.6	119.6	167.5	211.3
32.5°	55.8	63.8	67.8	75.8	79.7	91.7	107.6	119.6	131.6	199.3	263.1
35°	55.8	63.8	67.8	75.8	79.7	95.7	111.6	127.6	143.5	243.2	342.9
37.5°	55.8	63.8	67.8	75.8	79.7	103.7	127.6	151.5	175.4	279.1	382.7
40°	59.8	67.8	71.8	79.7	83.7	107.6	131.6	155.5	179.4	283.1	386.7
42.5°	59.8	67.8	71.8	79.7	83.7	103.7	127.6	147.5	167.5	283.1	398.7
45°	59.8	67.8	75.8	79.7	87.7	107.6	127.6	143.5	163.5	311.0	454.5
47.5°	59.8	67.8	75.8	79.7	87.7	107.6	127.6	147.5	167.5	410.7	649.9
50°	59.8	67.8	75.8	79.7	87.7	111.6	135.6	159.5	183.4	614.0	1044.6
52.5°	63.8	67.8	75.8	79.7	83.7	111.6	139.5	167.5	195.4	797.4	1395.4
55°	67.8	71.8	75.8	79.7	83.7	119.6	155.5	191.4	227.3	857.2	1483.1
57.5°	71.8	75.8	79.7	79.7	83.7	127.6	175.4	219.3	263.1	853.2	1439.3
60°	75.8	79.7	83.7	87.7	91.7	135.6	183.4	227.3	271.1	773.5	1275.8
62.5°	83.7	91.7	99.7	103.7	111.6	155.5	195.4	239.2	279.1	633.9	984.8
65°	95.7	103.7	107.6	115.6	119.6	159.5	203.3	243.2	283.1	526.3	765.5
67.5°	99.7	107.6	111.6	119.6	123.6	163.5	203.3	243.2	283.1	446.5	606.0
70°	99.7	107.6	115.6	119.6	127.6	167.5	203.3	243.2	279.1	386.7	494.4
72.5°	91.7	103.7	111.6	123.6	131.6	167.5	199.3	235.2	267.1	342.9	418.6
75°	87.7	103.7	115.6	131.6	143.5	167.5	195.4	219.3	243.2	299.0	354.8
77.5°	79.7	99.7	119.6	139.5	159.5	175.4	187.4	203.3	215.3	251.2	287.1
80°	75.8	95.7	115.6	135.6	155.5	163.5	167.5	175.4	179.4	183.4	187.4
82.5°	59.8	75.8	91.7	103.7	119.6	111.6	107.6	99.7	91.7	87.7	83.7
85°	27.9	31.9	31.9	35.9	35.9	35.9	31.9	31.9	27.9	23.9	19.9
87.5°	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	55.8	55.8	55.8	55.8	51.8	51.8	51.8	51.8	47.8	47.8	47.8
5°	63.8	63.8	63.8	63.8	59.8	59.8	59.8	59.8	55.8	55.8	55.8
7.5°	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8
10°	75.8	75.8	75.8	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7
12.5°	83.7	83.7	87.7	87.7	91.7	91.7	95.7	95.7	99.7	99.7	99.7
15°	91.7	95.7	99.7	103.7	103.7	107.6	111.6	115.6	119.6	123.6	127.6
17.5°	107.6	111.6	119.6	127.6	135.6	143.5	155.5	171.4	183.4	195.4	211.3
20°	119.6	131.6	155.5	183.4	207.3	231.2	291.0	350.9	410.7	470.5	530.3
22.5°	143.5	167.5	247.2	330.9	410.7	490.4	677.8	865.2	1048.6	1235.9	1403.4
25°	191.4	243.2	426.6	610.0	789.4	972.8	1307.7	1646.6	1981.5	2316.4	2627.4
27.5°	263.1	358.8	657.8	960.9	1259.9	1558.9	2045.3	2535.7	3022.1	3512.5	3947.1
30°	366.8	522.3	968.8	1419.3	1865.9	2312.4	2926.4	3544.4	4158.4	4772.4	5171.1
32.5°	498.4	729.6	1295.8	1861.9	2428.0	2994.2	3672.0	4349.7	5023.5	5701.3	6123.9
35°	637.9	932.9	1614.7	2300.5	2982.2	3668.0	4381.6	5095.3	5809.0	6522.6	7040.9
37.5°	717.6	1052.6	1861.9	2671.2	3476.6	4286.0	5067.4	5852.8	6634.3	7415.7	8045.6
40°	793.4	1196.1	2129.0	3062.0	3994.9	4927.8	5840.9	6753.9	7666.9	8579.9	9389.2
42.5°	905.0	1411.4	2499.8	3588.2	4672.7	5761.1	6961.2	8165.2	9365.3	10565.4	11809.3
45°	1136.3	1818.0	3229.4	4640.8	6048.2	7459.6	9162.0	10868.4	12570.8	14277.2	15872.0
47.5°	1694.4	2735.0	4660.7	6586.4	8512.1	10437.8	12399.4	14360.9	16322.5	18284.1	20181.9
50°	2623.4	4198.2	6606.3	9014.5	11418.6	13826.7	15784.3	17741.9	19695.5	21653.0	23538.9
52.5°	3496.5	5597.7	8185.2	10776.7	13364.2	15955.7	17690.0	19424.3	21158.7	22893.0	24719.0
55°	3795.6	6104.0	8723.4	11346.8	13966.2	16589.6	18260.2	19934.7	21605.2	23275.7	25169.5
57.5°	3532.4	5625.6	8264.9	10904.3	13539.6	16179.0	18044.9	19914.7	21780.6	23650.5	25679.8
60°	2958.3	4636.8	7407.7	10182.6	12953.5	15724.5	17829.6	19934.7	22039.8	24144.9	26170.2
62.5°	2344.3	3699.9	6634.3	9568.6	12503.0	15437.4	17578.4	19723.4	21864.3	24005.3	25560.2
65°	1798.1	2830.7	5717.3	8607.8	11494.3	14384.9	16139.1	17897.3	19651.6	21409.8	22486.3
67.5°	1335.6	2065.2	4589.0	7116.7	9640.4	12164.1	13455.9	14751.7	16043.4	17339.2	18176.4
70°	984.8	1471.2	3189.5	4907.9	6622.3	8340.7	9524.8	10708.9	11889.0	13073.2	13942.3
72.5°	681.8	940.9	1969.5	3002.2	4030.8	5059.4	6259.5	7459.6	8655.6	9855.7	10844.5
75°	466.5	578.1	1060.5	1542.9	2025.4	2507.8	3416.8	4325.8	5234.8	6143.9	6666.2
77.5°	346.9	406.7	550.2	697.7	841.2	984.8	1160.2	1335.6	1511.0	1686.5	1913.7
80°	191.4	191.4	211.3	227.3	247.2	263.1	311.0	362.8	410.7	462.5	526.3
82.5°	87.7	91.7	99.7	107.6	111.6	119.6	127.6	135.6	143.5	151.5	151.5
85°	23.9	27.9	27.9	23.9	23.9	19.9	19.9	23.9	23.9	23.9	23.9
87.5°	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	47.8	43.9	43.9	43.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
5°	55.8	55.8	55.8	55.8	51.8	51.8	51.8	51.8	51.8	47.8	47.8
7.5°	67.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	63.8	59.8	59.8
10°	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7	79.7	75.8	75.8
12.5°	99.7	99.7	99.7	99.7	103.7	103.7	99.7	99.7	99.7	95.7	95.7
15°	131.6	135.6	139.5	139.5	143.5	143.5	143.5	139.5	139.5	135.6	131.6
17.5°	223.3	235.2	251.2	267.1	283.1	295.0	295.0	287.1	279.1	271.1	263.1
20°	594.1	653.9	717.6	781.4	849.2	897.1	865.2	841.2	817.3	789.4	765.5
22.5°	1574.8	1742.3	1913.7	2033.3	2152.9	2236.7	2168.9	2037.3	1905.8	1778.2	1646.6
25°	2938.4	3245.4	3556.3	3683.9	3815.5	3911.2	3867.3	3668.0	3468.6	3273.3	3073.9
27.5°	4381.6	4812.2	5246.8	5358.4	5470.1	5553.8	5537.9	5278.7	5019.5	4760.4	4501.2
30°	5569.7	5968.4	6367.1	6478.8	6590.4	6666.2	6582.4	6323.3	6064.1	5805.0	5545.8
32.5°	6550.5	6973.1	7399.7	7547.3	7694.8	7794.5	7694.8	7383.8	7072.8	6765.8	6454.8
35°	7559.2	8073.5	8591.8	8779.2	8966.6	9086.2	8918.8	8536.0	8153.3	7774.5	7391.8
37.5°	8675.6	9301.5	9931.5	10186.6	10445.8	10625.2	10497.6	10019.2	9536.7	9058.3	8575.9
40°	10202.6	11011.9	11825.2	12283.7	12738.3	13061.2	12833.9	12279.8	11721.6	11167.4	10609.2
42.5°	13057.2	14301.1	15545.1	16202.9	16856.8	17331.2	17076.0	16394.3	15712.5	15030.7	14349.0
45°	17466.8	19057.5	20652.3	21613.2	22578.0	23287.7	22992.6	22135.5	21274.3	20417.1	19559.9
47.5°	22079.6	23977.4	25875.2	26640.7	27410.2	28008.2	27936.4	26867.9	25799.4	24734.9	23666.4
50°	25428.7	27314.5	29200.3	29858.1	30520.0	31010.4	30827.0	29467.4	28103.9	26744.4	25380.8
52.5°	26545.0	28367.0	30193.0	30978.5	31763.9	32350.0	32126.7	30595.7	29064.7	27537.8	26006.8
55°	27063.3	28957.1	30850.9	31807.8	32768.6	33470.3	33147.4	31468.9	29786.4	28107.9	26425.4
57.5°	27709.2	29738.5	31767.9	32816.5	33865.0	34622.5	34191.9	32453.6	30715.3	28981.0	27242.7
60°	28195.6	30217.0	32242.3	33083.6	33928.8	34518.9	34104.2	32413.8	30719.3	29028.9	27338.4
62.5°	27119.1	28674.0	30228.9	30854.9	31480.8	31935.3	31700.1	30097.4	28494.6	26891.9	25289.1
65°	23566.8	24643.2	25723.7	26146.3	26564.9	26887.9	26816.1	25464.5	24113.0	22765.4	21413.8
67.5°	19017.7	19854.9	20696.2	21294.2	21896.2	22362.7	22310.9	21078.9	19847.0	18615.0	17383.0
70°	14815.4	15684.6	16553.7	17307.3	18064.8	18650.9	18575.1	17430.9	16282.6	15138.4	13990.1
72.5°	11837.2	12826.0	13814.7	14245.3	14675.9	14978.9	14755.6	13890.5	13021.3	12156.2	11287.0
75°	7188.4	7706.7	8229.0	8225.0	8225.0	8177.2	7953.9	7459.6	6965.2	6470.8	5976.4
77.5°	2141.0	2368.2	2595.5	2814.8	3038.0	3205.5	3161.6	2902.5	2639.4	2380.2	2117.1
80°	590.1	649.9	713.7	741.6	769.5	805.4	897.1	833.3	769.5	709.7	645.9
82.5°	151.5	151.5	151.5	147.5	143.5	135.6	123.6	115.6	107.6	99.7	91.7
85°	23.9	19.9	19.9	19.9	15.9	15.9	15.9	15.9	12.0	12.0	8.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
2.5°	39.9	39.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	31.9
5°	47.8	47.8	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	39.9
7.5°	59.8	59.8	55.8	55.8	55.8	55.8	51.8	51.8	51.8	51.8	47.8
10°	75.8	71.8	71.8	67.8	67.8	67.8	63.8	63.8	63.8	59.8	59.8
12.5°	95.7	91.7	91.7	87.7	83.7	83.7	79.7	75.8	71.8	71.8	67.8
15°	127.6	123.6	119.6	115.6	111.6	103.7	99.7	91.7	87.7	83.7	79.7
17.5°	243.2	223.3	203.3	183.4	167.5	151.5	135.6	119.6	111.6	103.7	95.7
20°	677.8	586.1	498.4	410.7	354.8	299.0	243.2	187.4	163.5	143.5	119.6
22.5°	1467.2	1283.8	1104.4	921.0	773.5	629.9	482.4	334.9	279.1	227.3	171.4
25°	2727.1	2376.2	2029.3	1678.5	1399.4	1120.3	841.2	562.2	458.5	354.8	251.2
27.5°	4046.7	3592.2	3137.7	2683.2	2240.7	1794.1	1347.6	905.0	725.6	550.2	370.8
30°	5063.4	4581.0	4102.6	3620.1	3062.0	2503.8	1941.6	1383.5	1100.4	817.3	530.3
32.5°	5936.5	5414.3	4896.0	4373.7	3727.8	3081.9	2436.0	1790.1	1435.3	1080.5	721.6
35°	6801.7	6207.7	5617.6	5023.5	4329.8	3636.1	2942.4	2248.6	1798.1	1347.6	893.1
37.5°	7854.3	7128.6	6407.0	5685.4	4971.7	4262.0	3548.4	2834.7	2260.6	1690.5	1116.3
40°	9688.2	8763.3	7842.3	6917.3	6084.1	5254.8	4421.5	3588.2	2866.6	2145.0	1419.3
42.5°	13188.8	12028.6	10872.4	9712.2	8559.9	7407.7	6251.5	5099.3	4070.7	3046.0	2017.4
45°	18072.8	16585.6	15102.5	13615.4	12196.0	10780.7	9361.3	7942.0	6379.1	4816.2	3249.4
47.5°	22039.8	20409.1	18782.4	17151.8	15576.9	14006.1	12431.3	10856.4	8855.0	6857.5	4856.1
50°	23829.9	22275.0	20724.1	19169.2	17590.4	16007.5	14424.7	12845.9	10549.4	8256.9	5960.5
52.5°	24431.9	22853.1	21278.3	19699.4	18132.6	16565.7	14998.8	13432.0	11043.8	8659.6	6271.4
55°	24762.8	23096.3	21433.8	19767.2	18080.7	16390.3	14699.8	13013.4	10637.1	8264.9	5888.7
57.5°	25432.6	23618.6	21808.5	19994.5	18072.8	16151.1	14225.4	12303.7	9959.4	7615.0	5270.7
60°	25556.2	23770.1	21987.9	20205.8	18080.7	15955.7	13826.7	11701.6	9373.3	7048.9	4720.5
62.5°	23798.0	22306.9	20819.8	19328.7	17199.6	15070.6	12937.6	10808.6	8579.9	6351.2	4118.5
65°	20126.0	18838.3	17554.5	16266.7	14528.4	12794.1	11055.8	9317.5	7328.0	5342.5	3353.0
67.5°	16123.2	14863.3	13607.4	12347.5	11039.8	9736.1	8428.4	7120.7	5585.7	4050.7	2515.8
70°	12782.1	11570.1	10362.0	9150.0	7993.8	6833.6	5673.4	4517.2	3564.3	2615.4	1662.6
72.5°	10130.8	8970.6	7814.4	6654.2	5605.6	4557.1	3508.5	2459.9	1985.5	1515.0	1040.6
75°	5374.4	4772.4	4174.3	3572.3	2982.2	2388.2	1794.1	1204.1	1016.7	829.3	637.9
77.5°	1853.9	1590.8	1331.6	1068.5	889.1	709.7	530.3	350.9	330.9	315.0	295.0
80°	562.2	478.4	394.7	311.0	275.1	239.2	203.3	167.5	155.5	143.5	127.6
82.5°	87.7	79.7	75.8	67.8	63.8	63.8	59.8	55.8	47.8	43.9	35.9
85°	8.0	4.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	35.9	35.9
2.5°	31.9	31.9
5°	39.9	39.9
7.5°	47.8	47.8
10°	55.8	55.8
12.5°	63.8	63.8
15°	75.8	71.8
17.5°	87.7	83.7
20°	95.7	87.7
22.5°	115.6	99.7
25°	147.5	123.6
27.5°	191.4	151.5
30°	247.2	191.4
32.5°	366.8	267.1
35°	442.5	322.9
37.5°	542.2	374.8
40°	697.7	454.5
42.5°	988.8	618.0
45°	1686.5	1024.6
47.5°	2858.6	1746.3
50°	3664.0	2240.7
52.5°	3887.3	2376.2
55°	3516.5	2180.9
57.5°	2926.4	1853.9
60°	2396.1	1527.0
62.5°	1889.8	1208.0
65°	1363.5	913.0
67.5°	980.8	701.7
70°	713.7	550.2
72.5°	566.1	458.5
75°	450.5	382.7
77.5°	279.1	255.2
80°	115.6	107.6
82.5°	27.9	23.9
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066490

CATALOG NUMBER: NVN-SA4B-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-3

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-727-U-5WQ

Data in this report applies to families of products including GSS-SB1A-727-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-3
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-727-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2700K CCT 26 LEDS

Spectral Parameters

CCT (K):	2672	CRI (Ra):	71.1		
CIE u':	0.2638	R1:	68.3	R9:	-27.8
CIE v':	0.5276	R2:	79.8	R10:	54.4
Duv:	-0.0002	R3:	91.2	R11:	65.8
CIE x:	0.4619	R4:	69.4	R12:	45.6
CIE y:	0.4106	R5:	66.5	R13:	69.8
CIE z:	0.1275	R6:	72.6	R14:	94.5
Peak Wavelength (nm):	601	R7:	77.0	R15:	60.1
Dominant Wavelength (nm):	584	R8:	44.1		
Purity:	61.88407				
Rf:	67.9				
Rg:	98.6				



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-3

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-3

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2700K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-3

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.02

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.71

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

TM-30-18


Summary

$R_f = 67.9$
 $R_g = 98.6$
 $CIE R_a = 71.1$
 $R_g = -27.8$

Spectral Power Distribution Comparison



Color Vector Graphics




Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 53	CES51 = 75	CES76 = 51
CES02 = 63	CES27 = 70	CES52 = 80	CES77 = 79
CES03 = 31	CES28 = 81	CES53 = 64	CES78 = 58
CES04 = 71	CES29 = 37	CES54 = 73	CES79 = 82
CES05 = 50	CES30 = 33	CES55 = 69	CES80 = 82
CES06 = 52	CES31 = 44	CES56 = 60	CES81 = 69
CES07 = 42	CES32 = 47	CES57 = 54	CES82 = 92
CES08 = 41	CES33 = 45	CES58 = 59	CES83 = 82
CES09 = 29	CES34 = 67	CES59 = 85	CES84 = 92
CES10 = 77	CES35 = 84	CES60 = 86	CES85 = 87
CES11 = 60	CES36 = 68	CES61 = 86	CES86 = 60
CES12 = 66	CES37 = 77	CES62 = 59	CES87 = 79
CES13 = 44	CES38 = 40	CES63 = 66	CES88 = 70
CES14 = 74	CES39 = 88	CES64 = 69	CES89 = 66
CES15 = 72	CES40 = 82	CES65 = 64	CES90 = 64
CES16 = 48	CES41 = 70	CES66 = 65	CES91 = 81
CES17 = 51	CES42 = 76	CES67 = 64	CES92 = 69
CES18 = 57	CES43 = 63	CES68 = 73	CES93 = 81
CES19 = 73	CES44 = 97	CES69 = 83	CES94 = 53
CES20 = 67	CES45 = 74	CES70 = 64	CES95 = 77
CES21 = 88	CES46 = 67	CES71 = 60	CES96 = 79
CES22 = 80	CES47 = 55	CES72 = 87	CES97 = 78
CES23 = 92	CES48 = 42	CES73 = 57	CES98 = 69
CES24 = 92	CES49 = 65	CES74 = 84	CES99 = 60
CES25 = 73	CES50 = 74	CES75 = 60	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)