

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066491

Luminaire Tested: **NVN-SA4C-727-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066491
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA4C-727-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1050mA 4xLight Square PACKAGE
70CRI 2700K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 2700K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 15862.4 lumens
Efficiency: N/A
Efficacy: 83.3 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 190.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3.1 fc
 Type III - Short - N/A

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	94.3	0.0	94.3
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	15768.1	0.0	15768.1
	% Fixture	99.4	0.0	99.4
Total	Lumens	15862.4	0.0	15862.4
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.7	0.0
10°-20°	23.3	0.1
20°-30°	296.1	1.9
30°-40°	997.8	6.3
40°-50°	3013.4	19.0
50°-60°	5316.5	33.5
60°-70°	4683.9	29.5
70°-80°	1491.0	9.4
80°-90°	35.9	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	15862.4	100.0
0°-180°	15862.4	100.0



REPORT NUMBER: P1066491


CATALOG NUMBER: NVN-SA4C-727-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	309.9	2.0			
FM	(30°-60°)	9291.2	58.6			
FH	(60°-80°)	6137.9	38.7			G3/7500
FVH	(80°-90°)	29.2	0.2			G1/100
BL	(0°-30°)	14.1	0.1	B0/110		
BM	(30°-60°)	36.6	0.2	B0/220		
BH	(60°-80°)	37.0	0.2	B0/110		G0/110
BVH	(80°-90°)	6.7	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	34.8
5°	49.7	49.7	49.7	44.8	44.8	44.8	39.8	39.8	39.8	39.8	39.8
7.5°	59.7	54.7	54.7	49.7	49.7	49.7	44.8	44.8	44.8	44.8	39.8
10°	69.6	64.7	64.7	59.7	59.7	54.7	54.7	49.7	49.7	44.8	44.8
12.5°	79.6	74.6	69.6	64.7	64.7	59.7	59.7	54.7	54.7	49.7	49.7
15°	89.5	84.6	79.6	74.6	69.6	69.6	64.7	59.7	54.7	54.7	49.7
17.5°	104.5	94.5	89.5	79.6	74.6	69.6	64.7	59.7	59.7	54.7	54.7
20°	109.4	99.5	94.5	84.6	79.6	74.6	69.6	64.7	59.7	59.7	54.7
22.5°	129.3	109.4	104.5	94.5	89.5	84.6	74.6	69.6	64.7	59.7	54.7
25°	159.2	129.3	114.4	99.5	94.5	84.6	79.6	69.6	64.7	59.7	54.7
27.5°	194.0	144.3	129.3	109.4	99.5	89.5	79.6	69.6	64.7	59.7	54.7
30°	238.8	169.1	144.3	119.4	109.4	99.5	84.6	74.6	69.6	64.7	54.7
32.5°	333.3	208.9	169.1	129.3	114.4	104.5	89.5	74.6	69.6	64.7	54.7
35°	402.9	253.7	204.0	149.2	129.3	114.4	94.5	74.6	69.6	64.7	54.7
37.5°	467.6	258.7	208.9	159.2	139.3	119.4	94.5	74.6	69.6	64.7	54.7
40°	572.1	268.6	208.9	149.2	134.3	114.4	99.5	79.6	74.6	64.7	59.7
42.5°	771.0	308.4	223.9	139.3	124.4	114.4	99.5	84.6	74.6	69.6	59.7
45°	1283.4	457.6	303.4	144.3	129.3	114.4	99.5	84.6	79.6	69.6	64.7
47.5°	2183.8	795.9	472.6	149.2	134.3	114.4	99.5	79.6	74.6	69.6	59.7
50°	2795.6	1019.8	596.9	174.1	149.2	129.3	104.5	79.6	74.6	69.6	64.7
52.5°	2969.7	1084.4	646.7	204.0	174.1	144.3	109.4	79.6	74.6	74.6	69.6
55°	2721.0	1054.6	646.7	238.8	199.0	164.2	124.4	84.6	79.6	79.6	74.6
57.5°	2313.1	975.0	616.8	258.7	218.9	174.1	134.3	89.5	84.6	84.6	79.6
60°	1905.2	820.8	557.1	288.5	243.7	199.0	154.2	109.4	104.5	99.5	89.5
62.5°	1512.2	661.6	487.5	308.4	263.6	213.9	169.1	119.4	114.4	109.4	104.5
65°	1139.1	577.0	452.7	323.3	273.6	223.9	174.1	124.4	119.4	119.4	114.4
67.5°	875.5	527.3	432.8	333.3	283.5	233.8	184.1	134.3	129.3	124.4	119.4
70°	691.4	487.5	407.9	328.3	283.5	238.8	189.0	144.3	134.3	129.3	119.4
72.5°	577.0	442.7	378.1	313.4	278.6	243.7	208.9	174.1	154.2	139.3	119.4
75°	482.5	398.0	343.2	283.5	258.7	238.8	213.9	189.0	164.2	139.3	114.4
77.5°	318.4	288.5	263.6	238.8	223.9	208.9	189.0	174.1	149.2	129.3	104.5
80°	134.3	124.4	129.3	129.3	129.3	129.3	124.4	124.4	109.4	94.5	74.6
82.5°	29.8	24.9	29.8	29.8	29.8	29.8	24.9	24.9	24.9	19.9	19.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8
5°	39.8	39.8	39.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8
7.5°	39.8	39.8	39.8	34.8	34.8	34.8	34.8	29.8	29.8	29.8	29.8
10°	39.8	39.8	39.8	34.8	34.8	34.8	34.8	29.8	29.8	29.8	29.8
12.5°	44.8	44.8	39.8	39.8	34.8	34.8	34.8	29.8	29.8	29.8	29.8
15°	44.8	44.8	39.8	39.8	34.8	34.8	34.8	29.8	29.8	29.8	29.8
17.5°	49.7	44.8	44.8	39.8	34.8	34.8	34.8	29.8	29.8	29.8	29.8
20°	49.7	44.8	44.8	39.8	34.8	34.8	34.8	29.8	29.8	29.8	29.8
22.5°	49.7	44.8	44.8	39.8	34.8	34.8	29.8	29.8	24.9	24.9	19.9
25°	49.7	44.8	44.8	39.8	34.8	34.8	29.8	29.8	24.9	19.9	19.9
27.5°	49.7	44.8	44.8	39.8	34.8	29.8	29.8	24.9	19.9	14.9	14.9
30°	49.7	44.8	44.8	39.8	34.8	29.8	24.9	19.9	14.9	14.9	9.9
32.5°	49.7	44.8	39.8	34.8	29.8	24.9	24.9	19.9	14.9	9.9	9.9
35°	49.7	44.8	39.8	34.8	29.8	24.9	24.9	19.9	14.9	9.9	9.9
37.5°	49.7	44.8	39.8	34.8	29.8	24.9	19.9	14.9	9.9	9.9	5.0
40°	49.7	44.8	39.8	34.8	29.8	24.9	19.9	14.9	9.9	9.9	5.0
42.5°	49.7	44.8	39.8	34.8	29.8	24.9	19.9	14.9	9.9	9.9	5.0
45°	54.7	49.7	44.8	34.8	29.8	24.9	24.9	19.9	14.9	9.9	9.9
47.5°	54.7	49.7	44.8	34.8	29.8	24.9	24.9	19.9	14.9	9.9	9.9
50°	59.7	54.7	49.7	39.8	34.8	29.8	24.9	14.9	9.9	9.9	5.0
52.5°	64.7	59.7	54.7	49.7	44.8	34.8	24.9	14.9	5.0	5.0	5.0
55°	69.6	64.7	64.7	59.7	54.7	39.8	29.8	14.9	0.0	0.0	0.0
57.5°	74.6	69.6	69.6	64.7	59.7	44.8	29.8	14.9	0.0	0.0	0.0
60°	84.6	79.6	74.6	64.7	59.7	44.8	29.8	14.9	0.0	0.0	0.0
62.5°	99.5	89.5	74.6	64.7	49.7	39.8	24.9	14.9	0.0	0.0	0.0
65°	109.4	94.5	79.6	59.7	44.8	34.8	24.9	9.9	0.0	0.0	0.0
67.5°	114.4	94.5	79.6	59.7	39.8	29.8	19.9	9.9	0.0	0.0	0.0
70°	109.4	89.5	74.6	54.7	34.8	24.9	19.9	9.9	0.0	0.0	0.0
72.5°	99.5	84.6	64.7	49.7	29.8	24.9	14.9	9.9	0.0	0.0	0.0
75°	89.5	74.6	54.7	39.8	19.9	14.9	9.9	5.0	0.0	0.0	0.0
77.5°	79.6	64.7	44.8	29.8	9.9	9.9	5.0	5.0	0.0	0.0	0.0
80°	59.7	44.8	29.8	14.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	14.9	9.9	9.9	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8	29.8
5°	29.8	29.8	29.8	29.8	24.9	24.9	24.9	24.9	24.9	24.9	24.9
7.5°	29.8	29.8	29.8	29.8	24.9	24.9	24.9	24.9	19.9	19.9	19.9
10°	24.9	24.9	24.9	24.9	24.9	24.9	24.9	24.9	19.9	19.9	19.9
12.5°	24.9	24.9	24.9	24.9	24.9	24.9	24.9	24.9	19.9	19.9	19.9
15°	24.9	24.9	24.9	24.9	24.9	24.9	24.9	19.9	19.9	14.9	14.9
17.5°	24.9	24.9	24.9	24.9	19.9	19.9	19.9	14.9	14.9	9.9	9.9
20°	24.9	24.9	24.9	19.9	19.9	14.9	14.9	9.9	9.9	5.0	5.0
22.5°	19.9	14.9	14.9	9.9	9.9	5.0	5.0	5.0	0.0	0.0	0.0
25°	14.9	9.9	9.9	5.0	5.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	9.9	5.0	5.0	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	9.9	5.0	5.0	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	29.8	24.9	24.9	24.9	24.9	24.9	24.9	24.9	24.9	24.9	24.9
5°	24.9	24.9	24.9	24.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9
7.5°	19.9	19.9	19.9	19.9	19.9	19.9	14.9	14.9	14.9	14.9	14.9
10°	19.9	14.9	14.9	14.9	14.9	14.9	14.9	14.9	14.9	9.9	9.9
12.5°	19.9	14.9	14.9	14.9	9.9	9.9	9.9	9.9	9.9	5.0	5.0
15°	14.9	9.9	9.9	9.9	5.0	5.0	5.0	5.0	5.0	0.0	0.0
17.5°	9.9	5.0	5.0	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	24.9	24.9	24.9	24.9	24.9	24.9	24.9	24.9	24.9	29.8	29.8
5°	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9	19.9
7.5°	14.9	14.9	14.9	14.9	14.9	14.9	14.9	14.9	14.9	14.9	14.9
10°	9.9	9.9	9.9	9.9	9.9	9.9	5.0	5.0	5.0	5.0	5.0
12.5°	5.0	5.0	5.0	5.0	5.0	5.0	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	29.8	29.8	29.8	29.8	29.8	34.8	34.8	39.8	39.8	44.8	44.8
5°	19.9	19.9	24.9	24.9	24.9	24.9	29.8	29.8	29.8	34.8	34.8
7.5°	14.9	14.9	14.9	14.9	14.9	19.9	19.9	24.9	24.9	29.8	29.8
10°	5.0	5.0	9.9	9.9	9.9	9.9	14.9	14.9	14.9	19.9	24.9
12.5°	0.0	0.0	5.0	5.0	5.0	5.0	9.9	9.9	9.9	14.9	19.9
15°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0	9.9	14.9
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0	9.9
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	49.7	49.7	54.7	54.7	59.7	59.7	64.7	64.7	64.7	64.7	64.7
5°	39.8	39.8	44.8	49.7	49.7	54.7	59.7	59.7	59.7	59.7	59.7
7.5°	34.8	34.8	39.8	44.8	44.8	49.7	54.7	54.7	59.7	59.7	59.7
10°	24.9	29.8	34.8	39.8	39.8	44.8	49.7	49.7	54.7	54.7	54.7
12.5°	19.9	24.9	29.8	34.8	34.8	39.8	44.8	44.8	49.7	49.7	54.7
15°	14.9	19.9	24.9	29.8	29.8	34.8	39.8	39.8	44.8	49.7	54.7
17.5°	9.9	14.9	19.9	24.9	24.9	29.8	34.8	39.8	44.8	44.8	49.7
20°	9.9	9.9	14.9	19.9	19.9	24.9	29.8	34.8	39.8	39.8	44.8
22.5°	5.0	5.0	9.9	14.9	14.9	19.9	24.9	29.8	34.8	34.8	39.8
25°	0.0	0.0	5.0	9.9	9.9	14.9	19.9	19.9	24.9	24.9	29.8
27.5°	0.0	0.0	5.0	5.0	9.9	9.9	14.9	14.9	19.9	19.9	24.9
30°	0.0	0.0	5.0	5.0	9.9	9.9	14.9	14.9	19.9	19.9	19.9
32.5°	0.0	0.0	0.0	5.0	5.0	5.0	9.9	9.9	14.9	14.9	19.9
35°	0.0	0.0	0.0	5.0	5.0	5.0	9.9	9.9	14.9	14.9	14.9
37.5°	0.0	0.0	0.0	5.0	5.0	5.0	9.9	9.9	9.9	9.9	14.9
40°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	9.9	9.9	9.9
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	9.9	9.9	9.9
45°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	9.9	9.9	9.9
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	9.9	9.9	9.9
50°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	9.9	9.9	9.9
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0	5.0	5.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0	5.0	5.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0	5.0	5.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0	5.0	5.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	9.9	9.9	9.9
80°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	9.9	9.9	9.9
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0	5.0	9.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0	5.0	5.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.0	5.0	5.0	5.0	5.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	64.7	64.7
5°	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	59.7	59.7
7.5°	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	59.7	59.7
10°	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7
12.5°	54.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7
15°	54.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7
17.5°	49.7	54.7	54.7	54.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7
20°	44.8	49.7	49.7	49.7	54.7	54.7	54.7	54.7	59.7	59.7	59.7
22.5°	39.8	44.8	44.8	44.8	49.7	49.7	49.7	49.7	54.7	54.7	54.7
25°	34.8	34.8	39.8	39.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
27.5°	24.9	29.8	29.8	29.8	34.8	34.8	34.8	34.8	39.8	39.8	39.8
30°	24.9	24.9	24.9	24.9	29.8	29.8	29.8	29.8	34.8	34.8	34.8
32.5°	19.9	24.9	24.9	24.9	29.8	29.8	29.8	29.8	34.8	34.8	34.8
35°	19.9	19.9	19.9	19.9	24.9	24.9	24.9	24.9	29.8	29.8	29.8
37.5°	14.9	19.9	19.9	19.9	24.9	24.9	24.9	24.9	29.8	29.8	29.8
40°	14.9	14.9	14.9	14.9	19.9	19.9	19.9	19.9	24.9	24.9	24.9
42.5°	14.9	14.9	14.9	14.9	19.9	19.9	19.9	19.9	24.9	24.9	24.9
45°	14.9	14.9	14.9	14.9	19.9	19.9	19.9	19.9	24.9	24.9	24.9
47.5°	14.9	14.9	14.9	14.9	19.9	19.9	19.9	19.9	24.9	24.9	24.9
50°	14.9	14.9	14.9	14.9	19.9	19.9	19.9	19.9	24.9	24.9	24.9
52.5°	9.9	9.9	9.9	9.9	14.9	14.9	14.9	14.9	19.9	19.9	19.9
55°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	14.9	14.9	14.9
57.5°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	14.9	14.9	14.9
60°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
62.5°	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
65°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	5.0	5.0
67.5°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
70°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
72.5°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
75°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
77.5°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
80°	14.9	14.9	14.9	14.9	14.9	9.9	9.9	9.9	9.9	9.9	9.9
82.5°	9.9	14.9	14.9	14.9	14.9	9.9	9.9	9.9	9.9	9.9	9.9
85°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
87.5°	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	64.7	64.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	64.7	64.7
5°	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	64.7	64.7
7.5°	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	64.7	64.7
10°	59.7	59.7	59.7	59.7	54.7	54.7	59.7	59.7	59.7	64.7	64.7
12.5°	59.7	59.7	59.7	59.7	54.7	54.7	59.7	59.7	64.7	64.7	69.6
15°	59.7	59.7	54.7	54.7	54.7	54.7	59.7	59.7	64.7	64.7	69.6
17.5°	59.7	59.7	54.7	54.7	54.7	54.7	59.7	59.7	64.7	64.7	69.6
20°	59.7	59.7	54.7	54.7	54.7	54.7	54.7	54.7	59.7	64.7	64.7
22.5°	54.7	54.7	54.7	54.7	49.7	49.7	54.7	54.7	59.7	64.7	64.7
25°	44.8	49.7	49.7	49.7	49.7	49.7	54.7	54.7	59.7	64.7	64.7
27.5°	39.8	44.8	44.8	44.8	44.8	49.7	49.7	54.7	59.7	64.7	64.7
30°	34.8	39.8	39.8	39.8	44.8	49.7	49.7	54.7	59.7	64.7	64.7
32.5°	34.8	39.8	39.8	39.8	44.8	44.8	49.7	49.7	54.7	59.7	64.7
35°	34.8	34.8	39.8	39.8	39.8	44.8	44.8	49.7	54.7	59.7	64.7
37.5°	34.8	34.8	39.8	39.8	39.8	44.8	44.8	49.7	54.7	59.7	64.7
40°	29.8	34.8	34.8	39.8	39.8	44.8	44.8	49.7	54.7	64.7	69.6
42.5°	29.8	29.8	34.8	34.8	39.8	44.8	44.8	49.7	54.7	64.7	69.6
45°	29.8	34.8	34.8	39.8	44.8	49.7	49.7	54.7	59.7	64.7	69.6
47.5°	29.8	34.8	34.8	39.8	49.7	49.7	54.7	54.7	59.7	64.7	69.6
50°	29.8	34.8	34.8	39.8	54.7	54.7	54.7	54.7	59.7	64.7	69.6
52.5°	24.9	29.8	29.8	34.8	44.8	49.7	54.7	59.7	64.7	69.6	74.6
55°	19.9	24.9	24.9	29.8	39.8	44.8	54.7	64.7	69.6	74.6	79.6
57.5°	19.9	19.9	24.9	24.9	34.8	44.8	59.7	69.6	74.6	79.6	84.6
60°	14.9	14.9	19.9	19.9	29.8	39.8	54.7	69.6	74.6	84.6	89.5
62.5°	9.9	14.9	14.9	19.9	24.9	39.8	54.7	69.6	79.6	89.5	94.5
65°	9.9	9.9	14.9	14.9	24.9	34.8	49.7	59.7	74.6	89.5	104.5
67.5°	14.9	14.9	19.9	19.9	24.9	34.8	49.7	59.7	74.6	94.5	109.4
70°	14.9	14.9	19.9	19.9	29.8	39.8	49.7	59.7	74.6	94.5	109.4
72.5°	14.9	14.9	19.9	19.9	29.8	34.8	44.8	54.7	69.6	84.6	99.5
75°	9.9	14.9	14.9	14.9	24.9	29.8	39.8	49.7	64.7	79.6	94.5
77.5°	9.9	9.9	9.9	9.9	19.9	24.9	34.8	39.8	54.7	69.6	84.6
80°	9.9	9.9	9.9	9.9	14.9	19.9	29.8	34.8	49.7	64.7	79.6
82.5°	9.9	9.9	5.0	5.0	9.9	14.9	19.9	24.9	39.8	49.7	64.7
85°	9.9	9.9	5.0	5.0	5.0	9.9	9.9	14.9	19.9	24.9	29.8
87.5°	9.9	9.9	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	64.7	64.7	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6
5°	64.7	69.6	69.6	74.6	74.6	74.6	79.6	79.6	79.6	79.6	79.6
7.5°	64.7	69.6	69.6	74.6	74.6	74.6	79.6	79.6	79.6	84.6	84.6
10°	64.7	69.6	69.6	74.6	74.6	79.6	84.6	84.6	89.5	89.5	89.5
12.5°	69.6	74.6	74.6	79.6	79.6	84.6	89.5	89.5	94.5	99.5	99.5
15°	69.6	74.6	79.6	79.6	84.6	89.5	94.5	94.5	99.5	104.5	109.4
17.5°	69.6	74.6	79.6	79.6	84.6	89.5	99.5	104.5	109.4	119.4	124.4
20°	69.6	74.6	79.6	79.6	84.6	94.5	99.5	109.4	114.4	124.4	134.3
22.5°	69.6	74.6	79.6	84.6	89.5	99.5	109.4	114.4	124.4	139.3	149.2
25°	69.6	74.6	79.6	84.6	89.5	99.5	109.4	119.4	129.3	149.2	169.1
27.5°	69.6	74.6	84.6	89.5	94.5	104.5	119.4	129.3	139.3	174.1	208.9
30°	69.6	74.6	84.6	89.5	94.5	109.4	124.4	134.3	149.2	208.9	263.6
32.5°	69.6	79.6	84.6	94.5	99.5	114.4	134.3	149.2	164.2	248.7	328.3
35°	69.6	79.6	84.6	94.5	99.5	119.4	139.3	159.2	179.1	303.4	427.8
37.5°	69.6	79.6	84.6	94.5	99.5	129.3	159.2	189.0	218.9	348.2	477.5
40°	74.6	84.6	89.5	99.5	104.5	134.3	164.2	194.0	223.9	353.2	482.5
42.5°	74.6	84.6	89.5	99.5	104.5	129.3	159.2	184.1	208.9	353.2	497.4
45°	74.6	84.6	94.5	99.5	109.4	134.3	159.2	179.1	204.0	388.0	567.1
47.5°	74.6	84.6	94.5	99.5	109.4	134.3	159.2	184.1	208.9	512.4	810.8
50°	74.6	84.6	94.5	99.5	109.4	139.3	169.1	199.0	228.8	766.1	1303.3
52.5°	79.6	84.6	94.5	99.5	104.5	139.3	174.1	208.9	243.7	994.9	1741.1
55°	84.6	89.5	94.5	99.5	104.5	149.2	194.0	238.8	283.5	1069.5	1850.5
57.5°	89.5	94.5	99.5	99.5	104.5	159.2	218.9	273.6	328.3	1064.5	1795.8
60°	94.5	99.5	104.5	109.4	114.4	169.1	228.8	283.5	338.3	965.0	1591.8
62.5°	104.5	114.4	124.4	129.3	139.3	194.0	243.7	298.5	348.2	790.9	1228.7
65°	119.4	129.3	134.3	144.3	149.2	199.0	253.7	303.4	353.2	656.6	955.1
67.5°	124.4	134.3	139.3	149.2	154.2	204.0	253.7	303.4	353.2	557.1	756.1
70°	124.4	134.3	144.3	149.2	159.2	208.9	253.7	303.4	348.2	482.5	616.8
72.5°	114.4	129.3	139.3	154.2	164.2	208.9	248.7	293.5	333.3	427.8	522.3
75°	109.4	129.3	144.3	164.2	179.1	208.9	243.7	273.6	303.4	373.1	442.7
77.5°	99.5	124.4	149.2	174.1	199.0	218.9	233.8	253.7	268.6	313.4	358.2
80°	94.5	119.4	144.3	169.1	194.0	204.0	208.9	218.9	223.9	228.8	233.8
82.5°	74.6	94.5	114.4	129.3	149.2	139.3	134.3	124.4	114.4	109.4	104.5
85°	34.8	39.8	39.8	44.8	44.8	44.8	39.8	39.8	34.8	29.8	24.9
87.5°	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	69.6	69.6	69.6	69.6	64.7	64.7	64.7	64.7	59.7	59.7	59.7
5°	79.6	79.6	79.6	79.6	74.6	74.6	74.6	74.6	69.6	69.6	69.6
7.5°	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6
10°	94.5	94.5	94.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
12.5°	104.5	104.5	109.4	109.4	114.4	114.4	119.4	119.4	124.4	124.4	124.4
15°	114.4	119.4	124.4	129.3	129.3	134.3	139.3	144.3	149.2	154.2	159.2
17.5°	134.3	139.3	149.2	159.2	169.1	179.1	194.0	213.9	228.8	243.7	263.6
20°	149.2	164.2	194.0	228.8	258.7	288.5	363.1	437.8	512.4	587.0	661.6
22.5°	179.1	208.9	308.4	412.9	512.4	611.9	845.7	1079.5	1308.3	1542.1	1751.0
25°	238.8	303.4	532.3	761.1	984.9	1213.8	1631.6	2054.4	2472.3	2890.2	3278.2
27.5°	328.3	447.7	820.8	1198.8	1571.9	1945.0	2551.9	3163.8	3770.6	4382.5	4924.7
30°	457.6	651.7	1208.8	1770.9	2328.0	2885.2	3651.2	4422.3	5188.4	5954.4	6451.9
32.5°	621.8	910.3	1616.7	2323.1	3029.4	3735.8	4581.5	5427.1	6267.8	7113.5	7640.8
35°	795.9	1164.0	2014.7	2870.3	3720.9	4576.5	5466.9	6357.4	7247.8	8138.2	8784.9
37.5°	895.4	1313.3	2323.1	3332.9	4337.7	5347.5	6322.5	7302.5	8277.5	9252.5	10038.4
40°	989.9	1492.3	2656.4	3820.4	4984.4	6148.4	7287.6	8426.7	9565.9	10705.0	11714.8
42.5°	1129.2	1761.0	3119.0	4477.0	5830.1	7188.1	8685.4	10187.7	11685.0	13182.3	14734.3
45°	1417.7	2268.4	4029.3	5790.3	7546.2	9307.2	11431.3	13560.4	15684.5	17813.5	19803.3
47.5°	2114.1	3412.5	5815.1	8217.8	10620.5	13023.1	15470.5	17918.0	20365.4	22812.8	25180.7
50°	3273.2	5238.1	8242.7	11247.2	14246.8	17251.4	19693.9	22136.3	24573.8	27016.3	29369.2
52.5°	4362.6	6984.1	10212.6	13445.9	16674.4	19907.8	22071.6	24235.5	26399.4	28563.3	30841.6
55°	4735.7	7615.9	10884.1	14157.3	17425.5	20698.7	22783.0	24872.3	26956.6	29040.9	31403.7
57.5°	4407.4	7019.0	10312.0	13605.1	16893.2	20186.3	22514.4	24847.4	27175.4	29508.5	32040.5
60°	3691.0	5785.3	9242.5	12704.8	16162.0	19619.2	22245.8	24872.3	27498.8	30125.3	32652.3
62.5°	2925.0	4616.3	8277.5	11938.7	15599.9	19261.1	21932.4	24608.6	27279.9	29951.2	31891.2
65°	2243.5	3531.9	7133.4	10739.8	14341.3	17947.8	20136.6	22330.3	24519.1	26712.8	28055.9
67.5°	1666.4	2576.8	5725.6	8879.4	12028.2	15177.1	16788.8	18405.5	20017.2	21633.9	22678.5
70°	1228.7	1835.6	3979.6	6123.6	8262.6	10406.6	11884.0	13361.4	14833.8	16311.2	17395.7
72.5°	850.6	1174.0	2457.4	3745.8	5029.2	6312.6	7809.9	9307.2	10799.5	12296.8	13530.5
75°	582.0	721.3	1323.2	1925.1	2527.0	3128.9	4263.1	5397.3	6531.5	7665.6	8317.3
77.5°	432.8	507.4	686.5	870.5	1049.6	1228.7	1447.6	1666.4	1885.3	2104.2	2387.7
80°	238.8	238.8	263.6	283.5	308.4	328.3	388.0	452.7	512.4	577.0	656.6
82.5°	109.4	114.4	124.4	134.3	139.3	149.2	159.2	169.1	179.1	189.0	189.0
85°	29.8	34.8	34.8	29.8	29.8	24.9	24.9	29.8	29.8	29.8	29.8
87.5°	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	59.7	54.7	54.7	54.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7
5°	69.6	69.6	69.6	69.6	64.7	64.7	64.7	64.7	64.7	59.7	59.7
7.5°	84.6	79.6	79.6	79.6	79.6	79.6	79.6	79.6	79.6	74.6	74.6
10°	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	94.5	94.5
12.5°	124.4	124.4	124.4	124.4	129.3	129.3	124.4	124.4	124.4	119.4	119.4
15°	164.2	169.1	174.1	174.1	179.1	179.1	179.1	174.1	174.1	169.1	164.2
17.5°	278.6	293.5	313.4	333.3	353.2	368.1	368.1	358.2	348.2	338.3	328.3
20°	741.2	815.8	895.4	975.0	1059.6	1119.3	1079.5	1049.6	1019.8	984.9	955.1
22.5°	1964.9	2173.8	2387.7	2537.0	2686.2	2790.7	2706.1	2541.9	2377.8	2218.6	2054.4
25°	3666.2	4049.2	4437.2	4596.4	4760.6	4879.9	4825.2	4576.5	4327.8	4084.0	3835.3
27.5°	5466.9	6004.2	6546.4	6685.7	6824.9	6929.4	6909.5	6586.2	6262.8	5939.5	5616.2
30°	6949.3	7446.8	7944.2	8083.5	8222.8	8317.3	8212.8	7889.5	7566.1	7242.8	6919.5
32.5°	8173.0	8700.3	9232.6	9416.6	9600.7	9725.1	9600.7	9212.7	8824.7	8441.6	8053.6
35°	9431.6	10073.3	10719.9	10953.7	11187.5	11336.8	11127.9	10650.3	10172.8	9700.2	9222.6
37.5°	10824.4	11605.4	12391.4	12709.7	13033.1	13256.9	13097.7	12500.8	11898.9	11302.0	10700.0
40°	12729.6	13739.4	14754.2	15326.3	15893.4	16296.3	16012.8	15321.3	14624.9	13933.4	13237.0
42.5°	16291.3	17843.4	19395.4	20216.2	21032.0	21623.9	21305.6	20455.0	19604.3	18753.7	17903.1
45°	21793.1	23777.9	25767.7	26966.5	28170.3	29055.8	28687.7	27618.2	26543.7	25474.2	24404.7
47.5°	27548.5	29916.4	32284.2	33239.3	34199.4	34945.5	34856.0	33522.8	32189.7	30861.5	29528.4
50°	31727.1	34080.0	36432.9	37253.7	38079.4	38691.3	38462.5	36766.2	35064.9	33368.6	31667.4
52.5°	33119.9	35393.2	37671.5	38651.5	39631.5	40362.7	40084.1	38174.0	36263.8	34358.5	32448.4
55°	33766.6	36129.5	38492.3	39686.2	40885.0	41760.5	41357.6	39263.4	37164.1	35069.9	32970.7
57.5°	34572.4	37104.4	39636.4	40944.7	42253.0	43198.1	42660.9	40492.0	38323.2	36159.3	33990.4
60°	35179.3	37701.4	40228.4	41278.0	42332.6	43068.8	42551.5	40442.3	38328.2	36219.0	34109.8
62.5°	33836.2	35776.3	37716.3	38497.3	39278.3	39845.4	39551.9	37552.1	35552.4	33552.7	31553.0
65°	29404.0	30747.1	32095.2	32622.5	33144.8	33547.7	33458.2	31771.8	30085.5	28404.1	26717.8
67.5°	23728.1	24772.8	25822.4	26568.6	27319.7	27901.7	27837.0	26299.9	24762.8	23225.7	21688.6
70°	18485.1	19569.5	20653.9	21594.1	22539.2	23270.5	23176.0	21748.3	20315.7	18888.0	17455.4
72.5°	14769.2	16002.8	17236.5	17773.7	18311.0	18689.0	18410.5	17331.0	16246.6	15167.1	14082.7
75°	8968.9	9615.6	10267.3	10262.3	10262.3	10202.6	9924.0	9307.2	8690.4	8073.5	7456.7
77.5°	2671.3	2954.8	3238.4	3512.0	3790.5	3999.5	3944.7	3621.4	3293.1	2969.7	2641.4
80°	736.2	810.8	890.4	925.2	960.1	1004.8	1119.3	1039.7	960.1	885.5	805.9
82.5°	189.0	189.0	189.0	184.1	179.1	169.1	154.2	144.3	134.3	124.4	114.4
85°	29.8	24.9	24.9	24.9	19.9	19.9	19.9	19.9	14.9	14.9	9.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
2.5°	49.7	49.7	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	39.8
5°	59.7	59.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	49.7
7.5°	74.6	74.6	69.6	69.6	69.6	69.6	64.7	64.7	64.7	64.7	59.7
10°	94.5	89.5	89.5	84.6	84.6	84.6	79.6	79.6	79.6	74.6	74.6
12.5°	119.4	114.4	114.4	109.4	104.5	104.5	99.5	94.5	89.5	89.5	84.6
15°	159.2	154.2	149.2	144.3	139.3	129.3	124.4	114.4	109.4	104.5	99.5
17.5°	303.4	278.6	253.7	228.8	208.9	189.0	169.1	149.2	139.3	129.3	119.4
20°	845.7	731.2	621.8	512.4	442.7	373.1	303.4	233.8	204.0	179.1	149.2
22.5°	1830.6	1601.8	1377.9	1149.1	965.0	786.0	601.9	417.9	348.2	283.5	213.9
25°	3402.5	2964.8	2532.0	2094.2	1746.0	1397.8	1049.6	701.4	572.1	442.7	313.4
27.5°	5049.1	4482.0	3914.9	3347.8	2795.6	2238.5	1681.4	1129.2	905.4	686.5	462.6
30°	6317.6	5715.6	5118.7	4516.8	3820.4	3124.0	2422.6	1726.1	1372.9	1019.8	661.6
32.5°	7407.0	6755.3	6108.6	5457.0	4651.1	3845.3	3039.4	2233.5	1790.8	1348.1	900.4
35°	8486.4	7745.2	7009.0	6267.8	5402.3	4536.7	3671.1	2805.6	2243.5	1681.4	1114.3
37.5°	9799.7	8894.3	7993.9	7093.6	6203.1	5317.7	4427.3	3536.8	2820.5	2109.2	1392.8
40°	12087.9	10933.8	9784.7	8630.7	7591.0	6556.3	5516.7	4477.0	3576.6	2676.3	1770.9
42.5°	16455.5	15007.9	13565.3	12117.8	10680.2	9242.5	7799.9	6362.3	5078.9	3800.5	2517.1
45°	22549.2	20693.7	18843.2	16987.8	15216.9	13450.9	11680.0	9909.1	7959.1	6009.1	4054.2
47.5°	27498.8	25464.2	23434.6	21400.1	19435.2	17475.3	15510.3	13545.4	11048.3	8556.1	6058.9
50°	29732.3	27792.3	25857.2	23917.2	21947.3	19972.4	17997.6	16027.7	13162.4	10302.1	7436.8
52.5°	30483.4	28513.6	26548.7	24578.8	22623.8	20668.9	18713.9	16758.9	13779.2	10804.5	7824.8
55°	30896.3	28817.0	26742.7	24663.3	22559.1	20450.0	18340.8	16236.6	13271.8	10312.0	7347.3
57.5°	31732.0	29468.7	27210.3	24946.9	22549.2	20151.5	17748.8	15351.2	12426.2	9501.2	6576.2
60°	31886.2	29657.7	27434.1	25210.5	22559.1	19907.8	17251.4	14600.0	11694.9	8794.8	5889.8
62.5°	29692.5	27832.1	25976.6	24116.1	21459.8	18803.4	16142.1	13485.7	10705.0	7924.3	5138.6
65°	25111.0	23504.3	21902.5	20295.8	18126.9	15963.0	13794.2	11625.3	9143.0	6665.8	4183.5
67.5°	20116.7	18544.8	16977.8	15405.9	13774.3	12147.6	10516.0	8884.4	6969.2	5054.0	3138.9
70°	15948.1	14435.9	12928.6	11416.4	9973.8	8526.2	7078.6	5636.1	4447.2	3263.2	2074.3
72.5°	12640.1	11192.5	9749.9	8302.4	6994.1	5685.8	4377.5	3069.2	2477.3	1890.3	1298.3
75°	6705.6	5954.4	5208.3	4457.1	3720.9	2979.7	2238.5	1502.3	1268.5	1034.7	795.9
77.5°	2313.1	1984.8	1661.5	1333.2	1109.3	885.5	661.6	437.8	412.9	393.0	368.1
80°	701.4	596.9	492.5	388.0	343.2	298.5	253.7	208.9	194.0	179.1	159.2
82.5°	109.4	99.5	94.5	84.6	79.6	79.6	74.6	69.6	59.7	54.7	44.8
85°	9.9	5.0	5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	44.8	44.8
2.5°	39.8	39.8
5°	49.7	49.7
7.5°	59.7	59.7
10°	69.6	69.6
12.5°	79.6	79.6
15°	94.5	89.5
17.5°	109.4	104.5
20°	119.4	109.4
22.5°	144.3	124.4
25°	184.1	154.2
27.5°	238.8	189.0
30°	308.4	238.8
32.5°	457.6	333.3
35°	552.2	402.9
37.5°	676.5	467.6
40°	870.5	567.1
42.5°	1233.7	771.0
45°	2104.2	1278.4
47.5°	3566.7	2178.8
50°	4571.5	2795.6
52.5°	4850.1	2964.8
55°	4387.5	2721.0
57.5°	3651.2	2313.1
60°	2989.6	1905.2
62.5°	2357.9	1507.3
65°	1701.3	1139.1
67.5°	1223.7	875.5
70°	890.4	686.5
72.5°	706.4	572.1
75°	562.1	477.5
77.5°	348.2	318.4
80°	144.3	134.3
82.5°	34.8	29.8
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066491

CATALOG NUMBER: NVN-SA4C-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-3

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-727-U-5WQ

Data in this report applies to families of products including GSS-SB1A-727-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-3
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-727-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2700K CCT 26 LEDS

Spectral Parameters

CCT (K):	2672	CRI (Ra):	71.1		
CIE u':	0.2638	R1:	68.3	R9:	-27.8
CIE v':	0.5276	R2:	79.8	R10:	54.4
Duv:	-0.0002	R3:	91.2	R11:	65.8
CIE x:	0.4619	R4:	69.4	R12:	45.6
CIE y:	0.4106	R5:	66.5	R13:	69.8
CIE z:	0.1275	R6:	72.6	R14:	94.5
Peak Wavelength (nm):	601	R7:	77.0	R15:	60.1
Dominant Wavelength (nm):	584	R8:	44.1		
Purity:	61.88407				
Rf:	67.9				
Rg:	98.6				



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-3

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-3

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2700K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-3

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.02

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.71

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

TM-30-18

Summary

$R_f = 67.9$
 $R_g = 98.6$
 $CIE\ R_a = 71.1$
 $R_g = -27.8$

Spectral Power Distribution Comparison



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 86	CES26 = 53	CES51 = 75	CES76 = 51
CES02 = 63	CES27 = 70	CES52 = 80	CES77 = 79
CES03 = 31	CES28 = 81	CES53 = 64	CES78 = 58
CES04 = 71	CES29 = 37	CES54 = 73	CES79 = 82
CES05 = 50	CES30 = 33	CES55 = 69	CES80 = 82
CES06 = 52	CES31 = 44	CES56 = 60	CES81 = 69
CES07 = 42	CES32 = 47	CES57 = 54	CES82 = 92
CES08 = 41	CES33 = 45	CES58 = 59	CES83 = 82
CES09 = 29	CES34 = 67	CES59 = 85	CES84 = 92
CES10 = 77	CES35 = 84	CES60 = 86	CES85 = 87
CES11 = 60	CES36 = 68	CES61 = 86	CES86 = 60
CES12 = 66	CES37 = 77	CES62 = 59	CES87 = 79
CES13 = 44	CES38 = 40	CES63 = 66	CES88 = 70
CES14 = 74	CES39 = 88	CES64 = 69	CES89 = 66
CES15 = 72	CES40 = 82	CES65 = 64	CES90 = 64
CES16 = 48	CES41 = 70	CES66 = 65	CES91 = 81
CES17 = 51	CES42 = 76	CES67 = 64	CES92 = 69
CES18 = 57	CES43 = 63	CES68 = 73	CES93 = 81
CES19 = 73	CES44 = 97	CES69 = 83	CES94 = 53
CES20 = 67	CES45 = 74	CES70 = 64	CES95 = 77
CES21 = 88	CES46 = 67	CES71 = 60	CES96 = 79
CES22 = 80	CES47 = 55	CES72 = 87	CES97 = 78
CES23 = 92	CES48 = 42	CES73 = 57	CES98 = 69
CES24 = 92	CES49 = 65	CES74 = 84	CES99 = 60
CES25 = 73	CES50 = 74	CES75 = 60	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)