

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066497

Luminaire Tested: **NVN-SA6A-727-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066497
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA6A-727-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 615mA 6xLight Square PACKAGE
70CRI 2700K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (84) 2700K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 15427.6 lumens
Efficiency: N/A
Efficacy: 95.5 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 161.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3 fc
 Type III - Short - N/A

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	91.8	0.0	91.8
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	15335.8	0.0	15335.8
	% Fixture	99.4	0.0	99.4
Total	Lumens	15427.6	0.0	15427.6
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.6	0.0
10°-20°	22.6	0.1
20°-30°	287.9	1.9
30°-40°	970.4	6.3
40°-50°	2930.8	19.0
50°-60°	5170.8	33.5
60°-70°	4555.5	29.5
70°-80°	1450.1	9.4
80°-90°	34.9	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	15427.6	100.0
0°-180°	15427.6	100.0



REPORT NUMBER: P1066497


CATALOG NUMBER: NVN-SA6A-727-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	301.4	2.0			
FM	(30°-60°)	9036.5	58.6			
FH	(60°-80°)	5969.6	38.7			G3/7500
FVH	(80°-90°)	28.4	0.2			G1/100
BL	(0°-30°)	13.8	0.1	B0/110		
BM	(30°-60°)	35.6	0.2	B0/220		
BH	(60°-80°)	35.9	0.2	B0/110		G0/110
BVH	(80°-90°)	6.5	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7	33.9
5°	48.4	48.4	48.4	43.5	43.5	43.5	38.7	38.7	38.7	38.7	38.7
7.5°	58.1	53.2	53.2	48.4	48.4	48.4	43.5	43.5	43.5	43.5	38.7
10°	67.7	62.9	62.9	58.1	58.1	53.2	53.2	48.4	48.4	43.5	43.5
12.5°	77.4	72.6	67.7	62.9	62.9	58.1	58.1	53.2	53.2	48.4	48.4
15°	87.1	82.2	77.4	72.6	67.7	67.7	62.9	58.1	53.2	53.2	48.4
17.5°	101.6	91.9	87.1	77.4	72.6	67.7	62.9	58.1	58.1	53.2	53.2
20°	106.4	96.8	91.9	82.2	77.4	72.6	67.7	62.9	58.1	58.1	53.2
22.5°	125.8	106.4	101.6	91.9	87.1	82.2	72.6	67.7	62.9	58.1	53.2
25°	154.8	125.8	111.3	96.8	91.9	82.2	77.4	67.7	62.9	58.1	53.2
27.5°	188.7	140.3	125.8	106.4	96.8	87.1	77.4	67.7	62.9	58.1	53.2
30°	232.2	164.5	140.3	116.1	106.4	96.8	82.2	72.6	67.7	62.9	53.2
32.5°	324.2	203.2	164.5	125.8	111.3	101.6	87.1	72.6	67.7	62.9	53.2
35°	391.9	246.7	198.4	145.1	125.8	111.3	91.9	72.6	67.7	62.9	53.2
37.5°	454.8	251.6	203.2	154.8	135.5	116.1	91.9	72.6	67.7	62.9	53.2
40°	556.4	261.3	203.2	145.1	130.6	111.3	96.8	77.4	72.6	62.9	58.1
42.5°	749.9	300.0	217.7	135.5	121.0	111.3	96.8	82.2	72.6	67.7	58.1
45°	1248.2	445.1	295.1	140.3	125.8	111.3	96.8	82.2	77.4	67.7	62.9
47.5°	2123.9	774.1	459.6	145.1	130.6	111.3	96.8	77.4	72.6	67.7	58.1
50°	2719.0	991.8	580.6	169.3	145.1	125.8	101.6	77.4	72.6	67.7	62.9
52.5°	2888.3	1054.7	629.0	198.4	169.3	140.3	106.4	77.4	72.6	72.6	67.7
55°	2646.4	1025.7	629.0	232.2	193.5	159.7	121.0	82.2	77.4	77.4	72.6
57.5°	2249.7	948.3	599.9	251.6	212.9	169.3	130.6	87.1	82.2	82.2	77.4
60°	1853.0	798.3	541.9	280.6	237.1	193.5	150.0	106.4	101.6	96.8	87.1
62.5°	1470.8	643.5	474.1	300.0	256.4	208.0	164.5	116.1	111.3	106.4	101.6
65°	1107.9	561.2	440.3	314.5	266.1	217.7	169.3	121.0	116.1	116.1	111.3
67.5°	851.5	512.8	420.9	324.2	275.8	227.4	179.0	130.6	125.8	121.0	116.1
70°	672.5	474.1	396.7	319.3	275.8	232.2	183.8	140.3	130.6	125.8	116.1
72.5°	561.2	430.6	367.7	304.8	270.9	237.1	203.2	169.3	150.0	135.5	116.1
75°	469.3	387.0	333.8	275.8	251.6	232.2	208.0	183.8	159.7	135.5	111.3
77.5°	309.6	280.6	256.4	232.2	217.7	203.2	183.8	169.3	145.1	125.8	101.6
80°	130.6	121.0	125.8	125.8	125.8	125.8	121.0	121.0	106.4	91.9	72.6
82.5°	29.0	24.2	29.0	29.0	29.0	29.0	24.2	24.2	24.2	19.4	19.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	33.9	33.9	33.9	33.9	33.9	33.9	33.9	33.9	33.9	33.9	33.9
5°	38.7	38.7	38.7	33.9	33.9	33.9	33.9	33.9	33.9	33.9	33.9
7.5°	38.7	38.7	38.7	33.9	33.9	33.9	33.9	29.0	29.0	29.0	29.0
10°	38.7	38.7	38.7	33.9	33.9	33.9	33.9	29.0	29.0	29.0	29.0
12.5°	43.5	43.5	38.7	38.7	33.9	33.9	33.9	29.0	29.0	29.0	29.0
15°	43.5	43.5	38.7	38.7	33.9	33.9	33.9	29.0	29.0	29.0	29.0
17.5°	48.4	43.5	43.5	38.7	33.9	33.9	33.9	29.0	29.0	29.0	29.0
20°	48.4	43.5	43.5	38.7	33.9	33.9	33.9	29.0	29.0	29.0	29.0
22.5°	48.4	43.5	43.5	38.7	33.9	33.9	29.0	29.0	24.2	24.2	19.4
25°	48.4	43.5	43.5	38.7	33.9	33.9	29.0	29.0	24.2	19.4	19.4
27.5°	48.4	43.5	43.5	38.7	33.9	29.0	29.0	24.2	19.4	14.5	14.5
30°	48.4	43.5	43.5	38.7	33.9	29.0	24.2	19.4	14.5	14.5	9.7
32.5°	48.4	43.5	38.7	33.9	29.0	24.2	24.2	19.4	14.5	9.7	9.7
35°	48.4	43.5	38.7	33.9	29.0	24.2	24.2	19.4	14.5	9.7	9.7
37.5°	48.4	43.5	38.7	33.9	29.0	24.2	19.4	14.5	9.7	9.7	4.8
40°	48.4	43.5	38.7	33.9	29.0	24.2	19.4	14.5	9.7	9.7	4.8
42.5°	48.4	43.5	38.7	33.9	29.0	24.2	19.4	14.5	9.7	9.7	4.8
45°	53.2	48.4	43.5	33.9	29.0	24.2	24.2	19.4	14.5	9.7	9.7
47.5°	53.2	48.4	43.5	33.9	29.0	24.2	24.2	19.4	14.5	9.7	9.7
50°	58.1	53.2	48.4	38.7	33.9	29.0	24.2	14.5	9.7	9.7	4.8
52.5°	62.9	58.1	53.2	48.4	43.5	33.9	24.2	14.5	4.8	4.8	4.8
55°	67.7	62.9	62.9	58.1	53.2	38.7	29.0	14.5	0.0	0.0	0.0
57.5°	72.6	67.7	67.7	62.9	58.1	43.5	29.0	14.5	0.0	0.0	0.0
60°	82.2	77.4	72.6	62.9	58.1	43.5	29.0	14.5	0.0	0.0	0.0
62.5°	96.8	87.1	72.6	62.9	48.4	38.7	24.2	14.5	0.0	0.0	0.0
65°	106.4	91.9	77.4	58.1	43.5	33.9	24.2	9.7	0.0	0.0	0.0
67.5°	111.3	91.9	77.4	58.1	38.7	29.0	19.4	9.7	0.0	0.0	0.0
70°	106.4	87.1	72.6	53.2	33.9	24.2	19.4	9.7	0.0	0.0	0.0
72.5°	96.8	82.2	62.9	48.4	29.0	24.2	14.5	9.7	0.0	0.0	0.0
75°	87.1	72.6	53.2	38.7	19.4	14.5	9.7	4.8	0.0	0.0	0.0
77.5°	77.4	62.9	43.5	29.0	9.7	9.7	4.8	4.8	0.0	0.0	0.0
80°	58.1	43.5	29.0	14.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	14.5	9.7	9.7	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0
5°	29.0	29.0	29.0	29.0	24.2	24.2	24.2	24.2	24.2	24.2	24.2
7.5°	29.0	29.0	29.0	29.0	24.2	24.2	24.2	24.2	19.4	19.4	19.4
10°	24.2	24.2	24.2	24.2	24.2	24.2	24.2	24.2	19.4	19.4	19.4
12.5°	24.2	24.2	24.2	24.2	24.2	24.2	24.2	24.2	19.4	19.4	19.4
15°	24.2	24.2	24.2	24.2	24.2	24.2	24.2	19.4	19.4	14.5	14.5
17.5°	24.2	24.2	24.2	24.2	19.4	19.4	19.4	14.5	14.5	9.7	9.7
20°	24.2	24.2	24.2	19.4	19.4	14.5	14.5	9.7	9.7	4.8	4.8
22.5°	19.4	14.5	14.5	9.7	9.7	4.8	4.8	4.8	0.0	0.0	0.0
25°	14.5	9.7	9.7	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	9.7	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	9.7	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	29.0	24.2	24.2	24.2	24.2	24.2	24.2	24.2	24.2	24.2	24.2
5°	24.2	24.2	24.2	24.2	19.4	19.4	19.4	19.4	19.4	19.4	19.4
7.5°	19.4	19.4	19.4	19.4	19.4	19.4	14.5	14.5	14.5	14.5	14.5
10°	19.4	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	9.7	9.7
12.5°	19.4	14.5	14.5	14.5	9.7	9.7	9.7	9.7	9.7	4.8	4.8
15°	14.5	9.7	9.7	9.7	4.8	4.8	4.8	4.8	4.8	0.0	0.0
17.5°	9.7	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	24.2	24.2	24.2	24.2	24.2	24.2	24.2	24.2	24.2	29.0	29.0
5°	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4
7.5°	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5
10°	9.7	9.7	9.7	9.7	9.7	9.7	4.8	4.8	4.8	4.8	4.8
12.5°	4.8	4.8	4.8	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	29.0	29.0	29.0	29.0	29.0	33.9	33.9	38.7	38.7	43.5	43.5
5°	19.4	19.4	24.2	24.2	24.2	24.2	29.0	29.0	29.0	33.9	33.9
7.5°	14.5	14.5	14.5	14.5	14.5	19.4	19.4	24.2	24.2	29.0	29.0
10°	4.8	4.8	9.7	9.7	9.7	9.7	14.5	14.5	14.5	19.4	24.2
12.5°	0.0	0.0	4.8	4.8	4.8	4.8	9.7	9.7	9.7	14.5	19.4
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	9.7	14.5
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	9.7
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	48.4	48.4	53.2	53.2	58.1	58.1	62.9	62.9	62.9	62.9	62.9
5°	38.7	38.7	43.5	48.4	48.4	53.2	58.1	58.1	58.1	58.1	58.1
7.5°	33.9	33.9	38.7	43.5	43.5	48.4	53.2	53.2	58.1	58.1	58.1
10°	24.2	29.0	33.9	38.7	38.7	43.5	48.4	48.4	53.2	53.2	53.2
12.5°	19.4	24.2	29.0	33.9	33.9	38.7	43.5	43.5	48.4	48.4	53.2
15°	14.5	19.4	24.2	29.0	29.0	33.9	38.7	38.7	43.5	48.4	53.2
17.5°	9.7	14.5	19.4	24.2	24.2	29.0	33.9	38.7	43.5	43.5	48.4
20°	9.7	9.7	14.5	19.4	19.4	24.2	29.0	33.9	38.7	38.7	43.5
22.5°	4.8	4.8	9.7	14.5	14.5	19.4	24.2	29.0	33.9	33.9	38.7
25°	0.0	0.0	4.8	9.7	9.7	14.5	19.4	19.4	24.2	24.2	29.0
27.5°	0.0	0.0	4.8	4.8	9.7	9.7	14.5	14.5	19.4	19.4	24.2
30°	0.0	0.0	4.8	4.8	9.7	9.7	14.5	14.5	19.4	19.4	19.4
32.5°	0.0	0.0	0.0	4.8	4.8	4.8	9.7	9.7	14.5	14.5	19.4
35°	0.0	0.0	0.0	4.8	4.8	4.8	9.7	9.7	14.5	14.5	14.5
37.5°	0.0	0.0	0.0	4.8	4.8	4.8	9.7	9.7	9.7	9.7	14.5
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.7	9.7	9.7
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.7	9.7	9.7
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.7	9.7	9.7
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.7	9.7	9.7
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.7	9.7	9.7
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.7	9.7	9.7
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.7	9.7	9.7
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	9.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	62.9	62.9
5°	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	58.1	58.1
7.5°	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	58.1	58.1
10°	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1
12.5°	53.2	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1
15°	53.2	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1
17.5°	48.4	53.2	53.2	53.2	58.1	58.1	58.1	58.1	58.1	58.1	58.1
20°	43.5	48.4	48.4	48.4	53.2	53.2	53.2	53.2	58.1	58.1	58.1
22.5°	38.7	43.5	43.5	43.5	48.4	48.4	48.4	48.4	53.2	53.2	53.2
25°	33.9	33.9	38.7	38.7	43.5	43.5	43.5	43.5	43.5	43.5	43.5
27.5°	24.2	29.0	29.0	29.0	33.9	33.9	33.9	33.9	38.7	38.7	38.7
30°	24.2	24.2	24.2	24.2	29.0	29.0	29.0	29.0	33.9	33.9	33.9
32.5°	19.4	24.2	24.2	24.2	29.0	29.0	29.0	29.0	33.9	33.9	33.9
35°	19.4	19.4	19.4	19.4	24.2	24.2	24.2	24.2	29.0	29.0	29.0
37.5°	14.5	19.4	19.4	19.4	24.2	24.2	24.2	24.2	29.0	29.0	29.0
40°	14.5	14.5	14.5	14.5	19.4	19.4	19.4	19.4	24.2	24.2	24.2
42.5°	14.5	14.5	14.5	14.5	19.4	19.4	19.4	19.4	24.2	24.2	24.2
45°	14.5	14.5	14.5	14.5	19.4	19.4	19.4	19.4	24.2	24.2	24.2
47.5°	14.5	14.5	14.5	14.5	19.4	19.4	19.4	19.4	24.2	24.2	24.2
50°	14.5	14.5	14.5	14.5	19.4	19.4	19.4	19.4	24.2	24.2	24.2
52.5°	9.7	9.7	9.7	9.7	14.5	14.5	14.5	14.5	19.4	19.4	19.4
55°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	14.5	14.5	14.5
57.5°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	14.5	14.5	14.5
60°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7
62.5°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
65°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	4.8	4.8
67.5°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7
70°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7
72.5°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7
75°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7
77.5°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7
80°	14.5	14.5	14.5	14.5	14.5	9.7	9.7	9.7	9.7	9.7	9.7
82.5°	9.7	14.5	14.5	14.5	14.5	9.7	9.7	9.7	9.7	9.7	9.7
85°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7
87.5°	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	62.9	62.9	58.1	58.1	58.1	58.1	58.1	58.1	58.1	62.9	62.9
5°	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	62.9	62.9
7.5°	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	62.9	62.9
10°	58.1	58.1	58.1	58.1	53.2	53.2	58.1	58.1	58.1	62.9	62.9
12.5°	58.1	58.1	58.1	58.1	53.2	53.2	58.1	58.1	62.9	62.9	67.7
15°	58.1	58.1	53.2	53.2	53.2	53.2	58.1	58.1	62.9	62.9	67.7
17.5°	58.1	58.1	53.2	53.2	53.2	53.2	58.1	58.1	62.9	62.9	67.7
20°	58.1	58.1	53.2	53.2	53.2	53.2	53.2	53.2	58.1	62.9	62.9
22.5°	53.2	53.2	53.2	53.2	48.4	48.4	53.2	53.2	58.1	62.9	62.9
25°	43.5	48.4	48.4	48.4	48.4	48.4	53.2	53.2	58.1	62.9	62.9
27.5°	38.7	43.5	43.5	43.5	43.5	48.4	48.4	53.2	58.1	62.9	62.9
30°	33.9	38.7	38.7	38.7	43.5	48.4	48.4	53.2	58.1	62.9	62.9
32.5°	33.9	38.7	38.7	38.7	43.5	43.5	48.4	48.4	53.2	58.1	62.9
35°	33.9	33.9	38.7	38.7	38.7	43.5	43.5	48.4	53.2	58.1	62.9
37.5°	33.9	33.9	38.7	38.7	38.7	43.5	43.5	48.4	53.2	58.1	62.9
40°	29.0	33.9	33.9	38.7	38.7	43.5	43.5	48.4	53.2	62.9	67.7
42.5°	29.0	29.0	33.9	33.9	38.7	43.5	43.5	48.4	53.2	62.9	67.7
45°	29.0	33.9	33.9	38.7	43.5	48.4	48.4	53.2	58.1	62.9	67.7
47.5°	29.0	33.9	33.9	38.7	48.4	48.4	53.2	53.2	58.1	62.9	67.7
50°	29.0	33.9	33.9	38.7	53.2	53.2	53.2	53.2	58.1	62.9	67.7
52.5°	24.2	29.0	29.0	33.9	43.5	48.4	53.2	58.1	62.9	67.7	72.6
55°	19.4	24.2	24.2	29.0	38.7	43.5	53.2	62.9	67.7	72.6	77.4
57.5°	19.4	19.4	24.2	24.2	33.9	43.5	58.1	67.7	72.6	77.4	82.2
60°	14.5	14.5	19.4	19.4	29.0	38.7	53.2	67.7	72.6	82.2	87.1
62.5°	9.7	14.5	14.5	19.4	24.2	38.7	53.2	67.7	77.4	87.1	91.9
65°	9.7	9.7	14.5	14.5	24.2	33.9	48.4	58.1	72.6	87.1	101.6
67.5°	14.5	14.5	19.4	19.4	24.2	33.9	48.4	58.1	72.6	91.9	106.4
70°	14.5	14.5	19.4	19.4	29.0	38.7	48.4	58.1	72.6	91.9	106.4
72.5°	14.5	14.5	19.4	19.4	29.0	33.9	43.5	53.2	67.7	82.2	96.8
75°	9.7	14.5	14.5	14.5	24.2	29.0	38.7	48.4	62.9	77.4	91.9
77.5°	9.7	9.7	9.7	9.7	19.4	24.2	33.9	38.7	53.2	67.7	82.2
80°	9.7	9.7	9.7	9.7	14.5	19.4	29.0	33.9	48.4	62.9	77.4
82.5°	9.7	9.7	4.8	4.8	9.7	14.5	19.4	24.2	38.7	48.4	62.9
85°	9.7	9.7	4.8	4.8	4.8	9.7	9.7	14.5	19.4	24.2	29.0
87.5°	9.7	9.7	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	62.9	62.9	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7	67.7
5°	62.9	67.7	67.7	72.6	72.6	72.6	77.4	77.4	77.4	77.4	77.4
7.5°	62.9	67.7	67.7	72.6	72.6	72.6	77.4	77.4	77.4	82.2	82.2
10°	62.9	67.7	67.7	72.6	72.6	77.4	82.2	82.2	87.1	87.1	87.1
12.5°	67.7	72.6	72.6	77.4	77.4	82.2	87.1	87.1	91.9	96.8	96.8
15°	67.7	72.6	77.4	77.4	82.2	87.1	91.9	91.9	96.8	101.6	106.4
17.5°	67.7	72.6	77.4	77.4	82.2	87.1	96.8	101.6	106.4	116.1	121.0
20°	67.7	72.6	77.4	77.4	82.2	91.9	96.8	106.4	111.3	121.0	130.6
22.5°	67.7	72.6	77.4	82.2	87.1	96.8	106.4	111.3	121.0	135.5	145.1
25°	67.7	72.6	77.4	82.2	87.1	96.8	106.4	116.1	125.8	145.1	164.5
27.5°	67.7	72.6	82.2	87.1	91.9	101.6	116.1	125.8	135.5	169.3	203.2
30°	67.7	72.6	82.2	87.1	91.9	106.4	121.0	130.6	145.1	203.2	256.4
32.5°	67.7	77.4	82.2	91.9	96.8	111.3	130.6	145.1	159.7	241.9	319.3
35°	67.7	77.4	82.2	91.9	96.8	116.1	135.5	154.8	174.2	295.1	416.1
37.5°	67.7	77.4	82.2	91.9	96.8	125.8	154.8	183.8	212.9	338.7	464.5
40°	72.6	82.2	87.1	96.8	101.6	130.6	159.7	188.7	217.7	343.5	469.3
42.5°	72.6	82.2	87.1	96.8	101.6	125.8	154.8	179.0	203.2	343.5	483.8
45°	72.6	82.2	91.9	96.8	106.4	130.6	154.8	174.2	198.4	377.4	551.5
47.5°	72.6	82.2	91.9	96.8	106.4	130.6	154.8	179.0	203.2	498.3	788.6
50°	72.6	82.2	91.9	96.8	106.4	135.5	164.5	193.5	222.6	745.1	1267.6
52.5°	77.4	82.2	91.9	96.8	101.6	135.5	169.3	203.2	237.1	967.6	1693.3
55°	82.2	87.1	91.9	96.8	101.6	145.1	188.7	232.2	275.8	1040.2	1799.8
57.5°	87.1	91.9	96.8	96.8	101.6	154.8	212.9	266.1	319.3	1035.4	1746.5
60°	91.9	96.8	101.6	106.4	111.3	164.5	222.6	275.8	329.0	938.6	1548.2
62.5°	101.6	111.3	121.0	125.8	135.5	188.7	237.1	290.3	338.7	769.3	1195.0
65°	116.1	125.8	130.6	140.3	145.1	193.5	246.7	295.1	343.5	638.6	928.9
67.5°	121.0	130.6	135.5	145.1	150.0	198.4	246.7	295.1	343.5	541.9	735.4
70°	121.0	130.6	140.3	145.1	154.8	203.2	246.7	295.1	338.7	469.3	599.9
72.5°	111.3	125.8	135.5	150.0	159.7	203.2	241.9	285.4	324.2	416.1	508.0
75°	106.4	125.8	140.3	159.7	174.2	203.2	237.1	266.1	295.1	362.9	430.6
77.5°	96.8	121.0	145.1	169.3	193.5	212.9	227.4	246.7	261.3	304.8	348.3
80°	91.9	116.1	140.3	164.5	188.7	198.4	203.2	212.9	217.7	222.6	227.4
82.5°	72.6	91.9	111.3	125.8	145.1	135.5	130.6	121.0	111.3	106.4	101.6
85°	33.9	38.7	38.7	43.5	43.5	43.5	38.7	38.7	33.9	29.0	24.2
87.5°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	67.7	67.7	67.7	67.7	62.9	62.9	62.9	62.9	58.1	58.1	58.1
5°	77.4	77.4	77.4	77.4	72.6	72.6	72.6	72.6	67.7	67.7	67.7
7.5°	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2
10°	91.9	91.9	91.9	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
12.5°	101.6	101.6	106.4	106.4	111.3	111.3	116.1	116.1	121.0	121.0	121.0
15°	111.3	116.1	121.0	125.8	125.8	130.6	135.5	140.3	145.1	150.0	154.8
17.5°	130.6	135.5	145.1	154.8	164.5	174.2	188.7	208.0	222.6	237.1	256.4
20°	145.1	159.7	188.7	222.6	251.6	280.6	353.2	425.8	498.3	570.9	643.5
22.5°	174.2	203.2	300.0	401.6	498.3	595.1	822.5	1049.9	1272.4	1499.8	1703.0
25°	232.2	295.1	517.7	740.2	957.9	1180.5	1586.9	1998.1	2404.5	2810.9	3188.3
27.5°	319.3	435.4	798.3	1166.0	1528.8	1891.7	2481.9	3077.0	3667.3	4262.4	4789.7
30°	445.1	633.8	1175.7	1722.4	2264.2	2806.1	3551.2	4301.1	5046.1	5791.2	6275.0
32.5°	604.8	885.4	1572.4	2259.4	2946.4	3633.4	4455.9	5278.4	6096.0	6918.5	7431.3
35°	774.1	1132.1	1959.4	2791.6	3618.9	4451.0	5317.1	6183.1	7049.1	7915.1	8544.1
37.5°	870.9	1277.3	2259.4	3241.5	4218.8	5200.9	6149.2	7102.3	8050.6	8998.8	9763.3
40°	962.8	1451.4	2583.5	3715.7	4847.8	5979.9	7087.8	8195.7	9303.6	10411.6	11393.7
42.5°	1098.2	1712.7	3033.5	4354.3	5670.2	6991.0	8447.3	9908.4	11364.7	12820.9	14330.4
45°	1378.9	2206.2	3918.8	5631.5	7339.4	9052.1	11117.9	13188.6	15254.5	17325.2	19260.4
47.5°	2056.2	3318.9	5655.7	7992.5	10329.3	12666.1	15046.4	17426.8	19807.1	22187.5	24490.4
50°	3183.5	5094.5	8016.7	10938.9	13856.3	16778.5	19154.0	21529.5	23900.1	26275.6	28564.1
52.5°	4243.0	6792.7	9932.6	13077.3	16217.3	19362.0	21466.6	23571.2	25675.7	27780.3	29996.1
55°	4605.9	7407.1	10585.7	13769.2	16947.8	20131.3	22158.4	24190.4	26217.6	28244.7	30542.8
57.5°	4286.5	6826.5	10029.4	13232.2	16430.1	19633.0	21897.2	24166.2	26430.5	28699.5	31162.1
60°	3589.9	5626.7	8989.2	12356.5	15718.9	19081.4	21635.9	24190.4	26744.9	29299.5	31757.2
62.5°	2844.8	4489.7	8050.6	11611.4	15172.2	18733.1	21331.1	23934.0	26532.1	29130.1	31017.0
65°	2182.0	3435.0	6937.8	10445.4	13948.2	17455.8	19584.6	21718.2	23846.9	25980.5	27286.8
67.5°	1620.8	2506.1	5568.6	8636.0	11698.5	14761.0	16328.5	17900.9	19468.5	21040.8	22056.8
70°	1195.0	1785.3	3870.5	5955.7	8036.1	10121.3	11558.2	12995.1	14427.2	15864.1	16918.8
72.5°	827.3	1141.8	2390.0	3643.1	4891.3	6139.5	7595.8	9052.1	10503.5	11959.7	13159.6
75°	566.1	701.5	1286.9	1872.3	2457.7	3043.2	4146.2	5249.3	6352.4	7455.5	8089.3
77.5°	420.9	493.5	667.7	846.7	1020.8	1195.0	1407.9	1620.8	1833.6	2046.5	2322.3
80°	232.2	232.2	256.4	275.8	300.0	319.3	377.4	440.3	498.3	561.2	638.6
82.5°	106.4	111.3	121.0	130.6	135.5	145.1	154.8	164.5	174.2	183.8	183.8
85°	29.0	33.9	33.9	29.0	29.0	24.2	24.2	29.0	29.0	29.0	29.0
87.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	58.1	53.2	53.2	53.2	48.4	48.4	48.4	48.4	48.4	48.4	48.4
5°	67.7	67.7	67.7	67.7	62.9	62.9	62.9	62.9	62.9	58.1	58.1
7.5°	82.2	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	72.6	72.6
10°	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	91.9	91.9
12.5°	121.0	121.0	121.0	121.0	125.8	125.8	121.0	121.0	121.0	116.1	116.1
15°	159.7	164.5	169.3	169.3	174.2	174.2	174.2	169.3	169.3	164.5	159.7
17.5°	270.9	285.4	304.8	324.2	343.5	358.0	358.0	348.3	338.7	329.0	319.3
20°	720.9	793.4	870.9	948.3	1030.5	1088.6	1049.9	1020.8	991.8	957.9	928.9
22.5°	1911.0	2114.2	2322.3	2467.4	2612.6	2714.2	2631.9	2472.3	2312.6	2157.8	1998.1
25°	3565.7	3938.2	4315.6	4470.4	4630.0	4746.2	4692.9	4451.0	4209.1	3972.1	3730.2
27.5°	5317.1	5839.6	6366.9	6502.4	6637.9	6739.5	6720.1	6405.6	6091.2	5776.7	5462.2
30°	6758.8	7242.6	7726.4	7861.9	7997.4	8089.3	7987.7	7673.2	7358.7	7044.3	6729.8
32.5°	7949.0	8461.8	8979.5	9158.5	9337.5	9458.5	9337.5	8960.1	8582.8	8210.2	7832.9
35°	9173.0	9797.1	10426.1	10653.5	10880.9	11026.0	10822.8	10358.3	9893.9	9434.3	8969.8
37.5°	10527.7	11287.3	12051.7	12361.3	12675.8	12893.5	12738.7	12158.1	11572.7	10992.1	10406.7
40°	12380.7	13362.8	14349.8	14906.1	15457.7	15849.6	15573.8	14901.3	14224.0	13551.5	12874.1
42.5°	15844.7	17354.2	18863.7	19662.0	20455.4	21031.2	20721.5	19894.2	19066.9	18239.6	17412.3
45°	21195.7	23126.1	25061.3	26227.3	27398.1	28259.3	27901.2	26861.1	25816.0	24775.8	23735.7
47.5°	26793.3	29096.3	31399.2	32328.1	33261.8	33987.6	33900.5	32603.9	31307.3	30015.5	28718.9
50°	30857.3	33145.7	35434.1	36232.4	37035.6	37630.6	37408.1	35758.3	34103.7	32453.9	30799.3
52.5°	32212.0	34423.0	36638.8	37591.9	38545.0	39256.2	38985.3	37127.5	35269.6	33416.7	31558.8
55°	32840.9	35139.0	37437.1	38598.3	39764.2	40615.7	40223.9	38187.0	36145.3	34108.5	32066.8
57.5°	33624.7	36087.3	38549.9	39822.3	41094.7	42013.9	41491.4	39382.0	37272.6	35168.1	33058.6
60°	34214.9	36667.9	39125.6	40146.4	41172.1	41888.2	41385.0	39333.6	37277.5	35226.1	33174.8
62.5°	32908.7	34795.5	36682.4	37442.0	38201.5	38753.1	38467.6	36522.7	34577.8	32632.9	30688.0
65°	28597.9	29904.2	31215.3	31728.2	32236.2	32628.1	32541.0	30900.9	29260.7	27625.5	25985.4
67.5°	23077.7	24093.7	25114.5	25840.2	26570.8	27136.8	27073.9	25579.0	24084.0	22589.0	21094.1
70°	17978.3	19033.0	20087.7	21002.1	21921.4	22632.6	22540.6	21152.1	19758.7	18370.2	16976.8
72.5°	14364.3	15564.1	16764.0	17286.5	17809.0	18176.7	17905.8	16855.9	15801.2	14751.3	13696.6
75°	8723.1	9352.0	9985.8	9981.0	9981.0	9922.9	9652.0	9052.1	8452.1	7852.2	7252.3
77.5°	2598.1	2873.8	3149.6	3415.7	3686.6	3889.8	3836.6	3522.1	3202.8	2888.3	2569.0
80°	716.0	788.6	866.0	899.9	933.8	977.3	1088.6	1011.2	933.8	861.2	783.8
82.5°	183.8	183.8	183.8	179.0	174.2	164.5	150.0	140.3	130.6	121.0	111.3
85°	29.0	24.2	24.2	24.2	19.4	19.4	19.4	19.4	14.5	14.5	9.7
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
2.5°	48.4	48.4	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	38.7
5°	58.1	58.1	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	48.4
7.5°	72.6	72.6	67.7	67.7	67.7	67.7	62.9	62.9	62.9	62.9	58.1
10°	91.9	87.1	87.1	82.2	82.2	82.2	77.4	77.4	77.4	72.6	72.6
12.5°	116.1	111.3	111.3	106.4	101.6	101.6	96.8	91.9	87.1	87.1	82.2
15°	154.8	150.0	145.1	140.3	135.5	125.8	121.0	111.3	106.4	101.6	96.8
17.5°	295.1	270.9	246.7	222.6	203.2	183.8	164.5	145.1	135.5	125.8	116.1
20°	822.5	711.2	604.8	498.3	430.6	362.9	295.1	227.4	198.4	174.2	145.1
22.5°	1780.4	1557.9	1340.1	1117.6	938.6	764.4	585.4	406.4	338.7	275.8	208.0
25°	3309.3	2883.5	2462.6	2036.8	1698.2	1359.5	1020.8	682.2	556.4	430.6	304.8
27.5°	4910.7	4359.1	3807.6	3256.0	2719.0	2177.1	1635.3	1098.2	880.5	667.7	449.9
30°	6144.4	5559.0	4978.4	4393.0	3715.7	3038.3	2356.1	1678.8	1335.3	991.8	643.5
32.5°	7203.9	6570.1	5941.2	5307.4	4523.6	3739.8	2956.1	2172.3	1741.7	1311.1	875.7
35°	8253.8	7532.9	6816.9	6096.0	5254.2	4412.3	3570.5	2728.7	2182.0	1635.3	1083.7
37.5°	9531.0	8650.5	7774.8	6899.1	6033.1	5171.9	4305.9	3439.9	2743.2	2051.3	1354.7
40°	11756.5	10634.1	9516.5	8394.1	7382.9	6376.6	5365.4	4354.3	3478.6	2602.9	1722.4
42.5°	16004.4	14596.5	13193.5	11785.6	10387.4	8989.2	7586.1	6187.9	4939.7	3696.3	2448.1
45°	21931.0	20126.4	18326.7	16522.1	14799.7	13082.2	11359.8	9637.5	7740.9	5844.4	3943.0
47.5°	26744.9	24766.2	22792.2	20813.4	18902.4	16996.2	15085.2	13174.1	10745.4	8321.5	5892.8
50°	28917.2	27030.4	25148.4	23261.5	21345.6	19424.9	17504.2	15588.3	12801.6	10019.7	7232.9
52.5°	29647.8	27731.9	25820.9	23905.0	22003.6	20102.2	18200.9	16299.5	13401.5	10508.3	7610.3
55°	30049.4	28027.0	26009.6	23987.2	21940.7	19889.4	17838.0	15791.5	12908.0	10029.4	7145.9
57.5°	30862.2	28660.8	26464.3	24263.0	21931.0	19599.1	17262.3	14930.3	12085.5	9240.7	6396.0
60°	31012.1	28844.7	26682.0	24519.4	21940.7	19362.0	16778.5	14199.8	11374.3	8553.7	5728.3
62.5°	28878.5	27069.1	25264.5	23455.0	20871.5	18288.0	15699.6	13116.1	10411.6	7707.1	4997.7
65°	24422.7	22860.0	21302.1	19739.4	17630.0	15525.4	13416.0	11306.6	8892.4	6483.0	4068.8
67.5°	19565.2	18036.4	16512.4	14983.6	13396.7	11814.6	10227.7	8640.8	6778.2	4915.5	3052.8
70°	15510.9	14040.1	12574.2	11103.4	9700.4	8292.5	6884.6	5481.6	4325.2	3173.8	2017.5
72.5°	12293.6	10885.7	9482.6	8074.8	6802.3	5529.9	4257.5	2985.1	2409.4	1838.5	1262.7
75°	6521.7	5791.2	5065.5	4334.9	3618.9	2898.0	2177.1	1461.1	1233.7	1006.3	774.1
77.5°	2249.7	1930.4	1615.9	1296.6	1078.9	861.2	643.5	425.8	401.6	382.2	358.0
80°	682.2	580.6	479.0	377.4	333.8	290.3	246.7	203.2	188.7	174.2	154.8
82.5°	106.4	96.8	91.9	82.2	77.4	77.4	72.6	67.7	58.1	53.2	43.5
85°	9.7	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066497
 CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	43.5	43.5
2.5°	38.7	38.7
5°	48.4	48.4
7.5°	58.1	58.1
10°	67.7	67.7
12.5°	77.4	77.4
15°	91.9	87.1
17.5°	106.4	101.6
20°	116.1	106.4
22.5°	140.3	121.0
25°	179.0	150.0
27.5°	232.2	183.8
30°	300.0	232.2
32.5°	445.1	324.2
35°	537.0	391.9
37.5°	658.0	454.8
40°	846.7	551.5
42.5°	1199.8	749.9
45°	2046.5	1243.4
47.5°	3468.9	2119.1
50°	4446.2	2719.0
52.5°	4717.1	2883.5
55°	4267.2	2646.4
57.5°	3551.2	2249.7
60°	2907.7	1853.0
62.5°	2293.3	1465.9
65°	1654.6	1107.9
67.5°	1190.2	851.5
70°	866.0	667.7
72.5°	687.0	556.4
75°	546.7	464.5
77.5°	338.7	309.6
80°	140.3	130.6
82.5°	33.9	29.0
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066497

CATALOG NUMBER: NVN-SA6A-727-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-3

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-727-U-5WQ

Data in this report applies to families of products including GSS-SB1A-727-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-3
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-727-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 2700K CCT 26 LEDS

Spectral Parameters

CCT (K):	2672	CRI (Ra):	71.1		
CIE u':	0.2638	R1:	68.3	R9:	-27.8
CIE v':	0.5276	R2:	79.8	R10:	54.4
Duv:	-0.0002	R3:	91.2	R11:	65.8
CIE x:	0.4619	R4:	69.4	R12:	45.6
CIE y:	0.4106	R5:	66.5	R13:	69.8
CIE z:	0.1275	R6:	72.6	R14:	94.5
Peak Wavelength (nm):	601	R7:	77.0	R15:	60.1
Dominant Wavelength (nm):	584	R8:	44.1		
Purity:	61.88407				
Rf:	67.9				
Rg:	98.6				



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-3

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-3

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2700K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-3

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.02

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.71

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	52	NR	620	888	NR	750	27	NR	880	1	NR
365	0	NR	495	87	NR	625	834	NR	755	23	NR	885	1	NR
370	0	NR	500	135	NR	630	776	NR	760	20	NR	890	1	NR
375	0	NR	505	196	NR	635	712	NR	765	17	NR	895	0	NR
380	0	NR	510	258	NR	640	648	NR	770	15	NR	900	0	NR
385	1	NR	515	317	NR	645	583	NR	775	12	NR	905	0	NR
390	2	NR	520	368	NR	650	523	NR	780	11	NR	910	0	NR
395	4	NR	525	408	NR	655	465	NR	785	9	NR	915	0	NR
400	6	NR	530	443	NR	660	410	NR	790	8	NR	920	0	NR
405	11	NR	535	473	NR	665	360	NR	795	7	NR	925	0	NR
410	23	NR	540	498	NR	670	313	NR	800	6	NR	930	0	NR
415	51	NR	545	530	NR	675	272	NR	805	5	NR	935	0	NR
420	111	NR	550	563	NR	680	236	NR	810	4	NR	940	0	NR
425	214	NR	555	605	NR	685	203	NR	815	4	NR	945	0	NR
430	339	NR	560	651	NR	690	175	NR	820	3	NR	950	0	NR
435	467	NR	565	705	NR	695	150	NR	825	3	NR	955	0	NR
440	535	NR	570	765	NR	700	128	NR	830	3	NR	960	0	NR
445	372	NR	575	824	NR	705	110	NR	835	2	NR	965	0	NR
450	160	NR	580	882	NR	710	94	NR	840	2	NR	970	0	NR
455	89	NR	585	930	NR	715	80	NR	845	2	NR	975	0	NR
460	53	NR	590	968	NR	720	69	NR	850	1	NR	980	0	NR
465	31	NR	595	991	NR	725	59	NR	855	1	NR	985	0	NR
470	23	NR	600	999	NR	730	50	NR	860	1	NR	990	0	NR
475	21	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	23	NR	610	969	NR	740	36	NR	870	1	NR	1000	0	NR
485	32	NR	615	935	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-3

TM-30-18

Summary

$R_f = 67.9$
 $R_g = 98.6$
 $CIE\ R_a = 71.1$
 $R_g = -27.8$

Spectral Power Distribution Comparison




Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 53	CES51 = 75	CES76 = 51
CES02 = 63	CES27 = 70	CES52 = 80	CES77 = 79
CES03 = 31	CES28 = 81	CES53 = 64	CES78 = 58
CES04 = 71	CES29 = 37	CES54 = 73	CES79 = 82
CES05 = 50	CES30 = 33	CES55 = 69	CES80 = 82
CES06 = 52	CES31 = 44	CES56 = 60	CES81 = 69
CES07 = 42	CES32 = 47	CES57 = 54	CES82 = 92
CES08 = 41	CES33 = 45	CES58 = 59	CES83 = 82
CES09 = 29	CES34 = 67	CES59 = 85	CES84 = 92
CES10 = 77	CES35 = 84	CES60 = 86	CES85 = 87
CES11 = 60	CES36 = 68	CES61 = 86	CES86 = 60
CES12 = 66	CES37 = 77	CES62 = 59	CES87 = 79
CES13 = 44	CES38 = 40	CES63 = 66	CES88 = 70
CES14 = 74	CES39 = 88	CES64 = 69	CES89 = 66
CES15 = 72	CES40 = 82	CES65 = 64	CES90 = 64
CES16 = 48	CES41 = 70	CES66 = 65	CES91 = 81
CES17 = 51	CES42 = 76	CES67 = 64	CES92 = 69
CES18 = 57	CES43 = 63	CES68 = 73	CES93 = 81
CES19 = 73	CES44 = 97	CES69 = 83	CES94 = 53
CES20 = 67	CES45 = 74	CES70 = 64	CES95 = 77
CES21 = 88	CES46 = 67	CES71 = 60	CES96 = 79
CES22 = 80	CES47 = 55	CES72 = 87	CES97 = 78
CES23 = 92	CES48 = 42	CES73 = 57	CES98 = 69
CES24 = 92	CES49 = 65	CES74 = 84	CES99 = 60
CES25 = 73	CES50 = 74	CES75 = 60	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)