

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066511

Luminaire Tested: **NVN-SA3C-730-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066511
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA3C-730-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1050mA 3xLight Square PACKAGE
70CRI 3000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 3000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 13041.9 lumens
Efficiency: N/A
Efficacy: 92.9 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3


Input Watts (W): 140.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	77.6	0.0	77.6
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	12964.3	0.0	12964.3
	% Fixture	99.4	0.0	99.4
Total	Lumens	13041.9	0.0	13041.9
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.9	0.0
10°-20°	19.1	0.1
20°-30°	243.4	1.9
30°-40°	820.4	6.3
40°-50°	2477.6	19.0
50°-60°	4371.2	33.5
60°-70°	3851.0	29.5
70°-80°	1225.9	9.4
80°-90°	29.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	13041.9	100.0
0°-180°	13041.9	100.0



REPORT NUMBER: P1066511


CATALOG NUMBER: NVN-SA3C-730-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	254.8	2.0			
FM	(30°-60°)	7639.1	58.6			
FH	(60°-80°)	5046.5	38.7			G3/7500
FVH	(80°-90°)	24.0	0.2			G1/100
BL	(0°-30°)	11.6	0.1	B0/110		
BM	(30°-60°)	30.1	0.2	B0/220		
BH	(60°-80°)	30.4	0.2	B0/110		G0/110
BVH	(80°-90°)	5.5	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	32.7	28.6
5°	40.9	40.9	40.9	36.8	36.8	36.8	32.7	32.7	32.7	32.7	32.7
7.5°	49.1	45.0	45.0	40.9	40.9	40.9	36.8	36.8	36.8	36.8	32.7
10°	57.3	53.2	53.2	49.1	49.1	45.0	45.0	40.9	40.9	36.8	36.8
12.5°	65.4	61.3	57.3	53.2	53.2	49.1	49.1	45.0	45.0	40.9	40.9
15°	73.6	69.5	65.4	61.3	57.3	57.3	53.2	49.1	45.0	45.0	40.9
17.5°	85.9	77.7	73.6	65.4	61.3	57.3	53.2	49.1	49.1	45.0	45.0
20°	90.0	81.8	77.7	69.5	65.4	61.3	57.3	53.2	49.1	49.1	45.0
22.5°	106.3	90.0	85.9	77.7	73.6	69.5	61.3	57.3	53.2	49.1	45.0
25°	130.9	106.3	94.1	81.8	77.7	69.5	65.4	57.3	53.2	49.1	45.0
27.5°	159.5	118.6	106.3	90.0	81.8	73.6	65.4	57.3	53.2	49.1	45.0
30°	196.3	139.1	118.6	98.2	90.0	81.8	69.5	61.3	57.3	53.2	45.0
32.5°	274.0	171.8	139.1	106.3	94.1	85.9	73.6	61.3	57.3	53.2	45.0
35°	331.3	208.6	167.7	122.7	106.3	94.1	77.7	61.3	57.3	53.2	45.0
37.5°	384.5	212.7	171.8	130.9	114.5	98.2	77.7	61.3	57.3	53.2	45.0
40°	470.3	220.9	171.8	122.7	110.4	94.1	81.8	65.4	61.3	53.2	49.1
42.5°	633.9	253.6	184.0	114.5	102.2	94.1	81.8	69.5	61.3	57.3	49.1
45°	1055.2	376.3	249.5	118.6	106.3	94.1	81.8	69.5	65.4	57.3	53.2
47.5°	1795.5	654.4	388.5	122.7	110.4	94.1	81.8	65.4	61.3	57.3	49.1
50°	2298.5	838.4	490.8	143.1	122.7	106.3	85.9	65.4	61.3	57.3	53.2
52.5°	2441.7	891.6	531.7	167.7	143.1	118.6	90.0	65.4	61.3	61.3	57.3
55°	2237.2	867.1	531.7	196.3	163.6	135.0	102.2	69.5	65.4	65.4	61.3
57.5°	1901.8	801.6	507.2	212.7	180.0	143.1	110.4	73.6	69.5	69.5	65.4
60°	1566.4	674.8	458.1	237.2	200.4	163.6	126.8	90.0	85.9	81.8	73.6
62.5°	1243.3	544.0	400.8	253.6	216.8	175.9	139.1	98.2	94.1	90.0	85.9
65°	936.6	474.4	372.2	265.8	224.9	184.0	143.1	102.2	98.2	98.2	94.1
67.5°	719.8	433.5	355.8	274.0	233.1	192.2	151.3	110.4	106.3	102.2	98.2
70°	568.5	400.8	335.4	269.9	233.1	196.3	155.4	118.6	110.4	106.3	98.2
72.5°	474.4	364.0	310.8	257.7	229.0	200.4	171.8	143.1	126.8	114.5	98.2
75°	396.7	327.2	282.2	233.1	212.7	196.3	175.9	155.4	135.0	114.5	94.1
77.5°	261.8	237.2	216.8	196.3	184.0	171.8	155.4	143.1	122.7	106.3	85.9
80°	110.4	102.2	106.3	106.3	106.3	106.3	102.2	102.2	90.0	77.7	61.3
82.5°	24.5	20.4	24.5	24.5	24.5	24.5	20.4	20.4	20.4	16.4	16.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6
5°	32.7	32.7	32.7	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6
7.5°	32.7	32.7	32.7	28.6	28.6	28.6	28.6	24.5	24.5	24.5	24.5
10°	32.7	32.7	32.7	28.6	28.6	28.6	28.6	24.5	24.5	24.5	24.5
12.5°	36.8	36.8	32.7	32.7	28.6	28.6	28.6	24.5	24.5	24.5	24.5
15°	36.8	36.8	32.7	32.7	28.6	28.6	28.6	24.5	24.5	24.5	24.5
17.5°	40.9	36.8	36.8	32.7	28.6	28.6	28.6	24.5	24.5	24.5	24.5
20°	40.9	36.8	36.8	32.7	28.6	28.6	28.6	24.5	24.5	24.5	24.5
22.5°	40.9	36.8	36.8	32.7	28.6	28.6	24.5	24.5	20.4	20.4	16.4
25°	40.9	36.8	36.8	32.7	28.6	28.6	24.5	24.5	20.4	16.4	16.4
27.5°	40.9	36.8	36.8	32.7	28.6	24.5	24.5	20.4	16.4	12.3	12.3
30°	40.9	36.8	36.8	32.7	28.6	24.5	20.4	16.4	12.3	12.3	8.2
32.5°	40.9	36.8	32.7	28.6	24.5	20.4	20.4	16.4	12.3	8.2	8.2
35°	40.9	36.8	32.7	28.6	24.5	20.4	20.4	16.4	12.3	8.2	8.2
37.5°	40.9	36.8	32.7	28.6	24.5	20.4	16.4	12.3	8.2	8.2	4.1
40°	40.9	36.8	32.7	28.6	24.5	20.4	16.4	12.3	8.2	8.2	4.1
42.5°	40.9	36.8	32.7	28.6	24.5	20.4	16.4	12.3	8.2	8.2	4.1
45°	45.0	40.9	36.8	28.6	24.5	20.4	20.4	16.4	12.3	8.2	8.2
47.5°	45.0	40.9	36.8	28.6	24.5	20.4	20.4	16.4	12.3	8.2	8.2
50°	49.1	45.0	40.9	32.7	28.6	24.5	20.4	12.3	8.2	8.2	4.1
52.5°	53.2	49.1	45.0	40.9	36.8	28.6	20.4	12.3	4.1	4.1	4.1
55°	57.3	53.2	53.2	49.1	45.0	32.7	24.5	12.3	0.0	0.0	0.0
57.5°	61.3	57.3	57.3	53.2	49.1	36.8	24.5	12.3	0.0	0.0	0.0
60°	69.5	65.4	61.3	53.2	49.1	36.8	24.5	12.3	0.0	0.0	0.0
62.5°	81.8	73.6	61.3	53.2	40.9	32.7	20.4	12.3	0.0	0.0	0.0
65°	90.0	77.7	65.4	49.1	36.8	28.6	20.4	8.2	0.0	0.0	0.0
67.5°	94.1	77.7	65.4	49.1	32.7	24.5	16.4	8.2	0.0	0.0	0.0
70°	90.0	73.6	61.3	45.0	28.6	20.4	16.4	8.2	0.0	0.0	0.0
72.5°	81.8	69.5	53.2	40.9	24.5	20.4	12.3	8.2	0.0	0.0	0.0
75°	73.6	61.3	45.0	32.7	16.4	12.3	8.2	4.1	0.0	0.0	0.0
77.5°	65.4	53.2	36.8	24.5	8.2	8.2	4.1	4.1	0.0	0.0	0.0
80°	49.1	36.8	24.5	12.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	12.3	8.2	8.2	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5
5°	24.5	24.5	24.5	24.5	20.4	20.4	20.4	20.4	20.4	20.4	20.4
7.5°	24.5	24.5	24.5	24.5	20.4	20.4	20.4	20.4	16.4	16.4	16.4
10°	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	16.4	16.4	16.4
12.5°	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	16.4	16.4	16.4
15°	20.4	20.4	20.4	20.4	20.4	20.4	20.4	16.4	16.4	12.3	12.3
17.5°	20.4	20.4	20.4	20.4	16.4	16.4	16.4	12.3	12.3	8.2	8.2
20°	20.4	20.4	20.4	16.4	16.4	12.3	12.3	8.2	8.2	4.1	4.1
22.5°	16.4	12.3	12.3	8.2	8.2	4.1	4.1	4.1	0.0	0.0	0.0
25°	12.3	8.2	8.2	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.2	4.1	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.2	4.1	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	24.5	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4
5°	20.4	20.4	20.4	20.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4
7.5°	16.4	16.4	16.4	16.4	16.4	16.4	12.3	12.3	12.3	12.3	12.3
10°	16.4	12.3	12.3	12.3	12.3	12.3	12.3	12.3	12.3	8.2	8.2
12.5°	16.4	12.3	12.3	12.3	8.2	8.2	8.2	8.2	8.2	4.1	4.1
15°	12.3	8.2	8.2	8.2	4.1	4.1	4.1	4.1	4.1	0.0	0.0
17.5°	8.2	4.1	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	24.5	24.5
5°	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4
7.5°	12.3	12.3	12.3	12.3	12.3	12.3	12.3	12.3	12.3	12.3	12.3
10°	8.2	8.2	8.2	8.2	8.2	8.2	4.1	4.1	4.1	4.1	4.1
12.5°	4.1	4.1	4.1	4.1	4.1	4.1	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	24.5	24.5	24.5	24.5	24.5	28.6	28.6	32.7	32.7	36.8	36.8
5°	16.4	16.4	20.4	20.4	20.4	20.4	24.5	24.5	24.5	28.6	28.6
7.5°	12.3	12.3	12.3	12.3	12.3	16.4	16.4	20.4	20.4	24.5	24.5
10°	4.1	4.1	8.2	8.2	8.2	8.2	12.3	12.3	12.3	16.4	20.4
12.5°	0.0	0.0	4.1	4.1	4.1	4.1	8.2	8.2	8.2	12.3	16.4
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	8.2	12.3
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	8.2
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	40.9	40.9	45.0	45.0	49.1	49.1	53.2	53.2	53.2	53.2	53.2
5°	32.7	32.7	36.8	40.9	40.9	45.0	49.1	49.1	49.1	49.1	49.1
7.5°	28.6	28.6	32.7	36.8	36.8	40.9	45.0	45.0	49.1	49.1	49.1
10°	20.4	24.5	28.6	32.7	32.7	36.8	40.9	40.9	45.0	45.0	45.0
12.5°	16.4	20.4	24.5	28.6	28.6	32.7	36.8	36.8	40.9	40.9	45.0
15°	12.3	16.4	20.4	24.5	24.5	28.6	32.7	32.7	36.8	40.9	45.0
17.5°	8.2	12.3	16.4	20.4	20.4	24.5	28.6	32.7	36.8	36.8	40.9
20°	8.2	8.2	12.3	16.4	16.4	20.4	24.5	28.6	32.7	32.7	36.8
22.5°	4.1	4.1	8.2	12.3	12.3	16.4	20.4	24.5	28.6	28.6	32.7
25°	0.0	0.0	4.1	8.2	8.2	12.3	16.4	16.4	20.4	20.4	24.5
27.5°	0.0	0.0	4.1	4.1	8.2	8.2	12.3	12.3	16.4	16.4	20.4
30°	0.0	0.0	4.1	4.1	8.2	8.2	12.3	12.3	16.4	16.4	16.4
32.5°	0.0	0.0	0.0	4.1	4.1	4.1	8.2	8.2	12.3	12.3	16.4
35°	0.0	0.0	0.0	4.1	4.1	4.1	8.2	8.2	12.3	12.3	12.3
37.5°	0.0	0.0	0.0	4.1	4.1	4.1	8.2	8.2	8.2	8.2	12.3
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.2	8.2	8.2
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.2	8.2	8.2
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.2	8.2	8.2
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.2	8.2	8.2
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.2	8.2	8.2
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.2	8.2	8.2
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	8.2	8.2	8.2
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	8.2
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.1	4.1	4.1	4.1	4.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	53.2	53.2
5°	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	49.1	49.1
7.5°	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	49.1	49.1
10°	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1
12.5°	45.0	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1
15°	45.0	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1
17.5°	40.9	45.0	45.0	45.0	49.1	49.1	49.1	49.1	49.1	49.1	49.1
20°	36.8	40.9	40.9	40.9	45.0	45.0	45.0	45.0	49.1	49.1	49.1
22.5°	32.7	36.8	36.8	36.8	40.9	40.9	40.9	40.9	45.0	45.0	45.0
25°	28.6	28.6	32.7	32.7	36.8	36.8	36.8	36.8	36.8	36.8	36.8
27.5°	20.4	24.5	24.5	24.5	28.6	28.6	28.6	28.6	32.7	32.7	32.7
30°	20.4	20.4	20.4	20.4	24.5	24.5	24.5	24.5	28.6	28.6	28.6
32.5°	16.4	20.4	20.4	20.4	24.5	24.5	24.5	24.5	28.6	28.6	28.6
35°	16.4	16.4	16.4	16.4	20.4	20.4	20.4	20.4	24.5	24.5	24.5
37.5°	12.3	16.4	16.4	16.4	20.4	20.4	20.4	20.4	24.5	24.5	24.5
40°	12.3	12.3	12.3	12.3	16.4	16.4	16.4	16.4	20.4	20.4	20.4
42.5°	12.3	12.3	12.3	12.3	16.4	16.4	16.4	16.4	20.4	20.4	20.4
45°	12.3	12.3	12.3	12.3	16.4	16.4	16.4	16.4	20.4	20.4	20.4
47.5°	12.3	12.3	12.3	12.3	16.4	16.4	16.4	16.4	20.4	20.4	20.4
50°	12.3	12.3	12.3	12.3	16.4	16.4	16.4	16.4	20.4	20.4	20.4
52.5°	8.2	8.2	8.2	8.2	12.3	12.3	12.3	12.3	16.4	16.4	16.4
55°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	12.3	12.3	12.3
57.5°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	12.3	12.3	12.3
60°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
62.5°	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1
65°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	4.1	4.1
67.5°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
70°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
72.5°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
75°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
77.5°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
80°	12.3	12.3	12.3	12.3	12.3	8.2	8.2	8.2	8.2	8.2	8.2
82.5°	8.2	12.3	12.3	12.3	12.3	8.2	8.2	8.2	8.2	8.2	8.2
85°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
87.5°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	53.2	53.2	49.1	49.1	49.1	49.1	49.1	49.1	49.1	53.2	53.2
5°	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	53.2	53.2
7.5°	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	53.2	53.2
10°	49.1	49.1	49.1	49.1	45.0	45.0	49.1	49.1	49.1	53.2	53.2
12.5°	49.1	49.1	49.1	49.1	45.0	45.0	49.1	49.1	53.2	53.2	57.3
15°	49.1	49.1	45.0	45.0	45.0	45.0	49.1	49.1	53.2	53.2	57.3
17.5°	49.1	49.1	45.0	45.0	45.0	45.0	49.1	49.1	53.2	53.2	57.3
20°	49.1	49.1	45.0	45.0	45.0	45.0	45.0	45.0	49.1	53.2	53.2
22.5°	45.0	45.0	45.0	45.0	40.9	40.9	45.0	45.0	49.1	53.2	53.2
25°	36.8	40.9	40.9	40.9	40.9	40.9	45.0	45.0	49.1	53.2	53.2
27.5°	32.7	36.8	36.8	36.8	36.8	40.9	40.9	45.0	49.1	53.2	53.2
30°	28.6	32.7	32.7	32.7	36.8	40.9	40.9	45.0	49.1	53.2	53.2
32.5°	28.6	32.7	32.7	32.7	36.8	36.8	40.9	40.9	45.0	49.1	53.2
35°	28.6	28.6	32.7	32.7	32.7	36.8	36.8	40.9	45.0	49.1	53.2
37.5°	28.6	28.6	32.7	32.7	32.7	36.8	36.8	40.9	45.0	49.1	53.2
40°	24.5	28.6	28.6	32.7	32.7	36.8	36.8	40.9	45.0	53.2	57.3
42.5°	24.5	24.5	28.6	28.6	32.7	36.8	36.8	40.9	45.0	53.2	57.3
45°	24.5	28.6	28.6	32.7	36.8	40.9	40.9	45.0	49.1	53.2	57.3
47.5°	24.5	28.6	28.6	32.7	40.9	40.9	45.0	45.0	49.1	53.2	57.3
50°	24.5	28.6	28.6	32.7	45.0	45.0	45.0	45.0	49.1	53.2	57.3
52.5°	20.4	24.5	24.5	28.6	36.8	40.9	45.0	49.1	53.2	57.3	61.3
55°	16.4	20.4	20.4	24.5	32.7	36.8	45.0	53.2	57.3	61.3	65.4
57.5°	16.4	16.4	20.4	20.4	28.6	36.8	49.1	57.3	61.3	65.4	69.5
60°	12.3	12.3	16.4	16.4	24.5	32.7	45.0	57.3	61.3	69.5	73.6
62.5°	8.2	12.3	12.3	16.4	20.4	32.7	45.0	57.3	65.4	73.6	77.7
65°	8.2	8.2	12.3	12.3	20.4	28.6	40.9	49.1	61.3	73.6	85.9
67.5°	12.3	12.3	16.4	16.4	20.4	28.6	40.9	49.1	61.3	77.7	90.0
70°	12.3	12.3	16.4	16.4	24.5	32.7	40.9	49.1	61.3	77.7	90.0
72.5°	12.3	12.3	16.4	16.4	24.5	28.6	36.8	45.0	57.3	69.5	81.8
75°	8.2	12.3	12.3	12.3	20.4	24.5	32.7	40.9	53.2	65.4	77.7
77.5°	8.2	8.2	8.2	8.2	16.4	20.4	28.6	32.7	45.0	57.3	69.5
80°	8.2	8.2	8.2	8.2	12.3	16.4	24.5	28.6	40.9	53.2	65.4
82.5°	8.2	8.2	4.1	4.1	8.2	12.3	16.4	20.4	32.7	40.9	53.2
85°	8.2	8.2	4.1	4.1	4.1	8.2	8.2	12.3	16.4	20.4	24.5
87.5°	8.2	8.2	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	53.2	53.2	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3	57.3
5°	53.2	57.3	57.3	61.3	61.3	61.3	65.4	65.4	65.4	65.4	65.4
7.5°	53.2	57.3	57.3	61.3	61.3	61.3	65.4	65.4	65.4	69.5	69.5
10°	53.2	57.3	57.3	61.3	61.3	65.4	69.5	69.5	73.6	73.6	73.6
12.5°	57.3	61.3	61.3	65.4	65.4	69.5	73.6	73.6	77.7	81.8	81.8
15°	57.3	61.3	65.4	65.4	69.5	73.6	77.7	77.7	81.8	85.9	90.0
17.5°	57.3	61.3	65.4	65.4	69.5	73.6	81.8	85.9	90.0	98.2	102.2
20°	57.3	61.3	65.4	65.4	69.5	77.7	81.8	90.0	94.1	102.2	110.4
22.5°	57.3	61.3	65.4	69.5	73.6	81.8	90.0	94.1	102.2	114.5	122.7
25°	57.3	61.3	65.4	69.5	73.6	81.8	90.0	98.2	106.3	122.7	139.1
27.5°	57.3	61.3	69.5	73.6	77.7	85.9	98.2	106.3	114.5	143.1	171.8
30°	57.3	61.3	69.5	73.6	77.7	90.0	102.2	110.4	122.7	171.8	216.8
32.5°	57.3	65.4	69.5	77.7	81.8	94.1	110.4	122.7	135.0	204.5	269.9
35°	57.3	65.4	69.5	77.7	81.8	98.2	114.5	130.9	147.2	249.5	351.7
37.5°	57.3	65.4	69.5	77.7	81.8	106.3	130.9	155.4	180.0	286.3	392.6
40°	61.3	69.5	73.6	81.8	85.9	110.4	135.0	159.5	184.0	290.4	396.7
42.5°	61.3	69.5	73.6	81.8	85.9	106.3	130.9	151.3	171.8	290.4	409.0
45°	61.3	69.5	77.7	81.8	90.0	110.4	130.9	147.2	167.7	319.0	466.3
47.5°	61.3	69.5	77.7	81.8	90.0	110.4	130.9	151.3	171.8	421.3	666.7
50°	61.3	69.5	77.7	81.8	90.0	114.5	139.1	163.6	188.1	629.9	1071.6
52.5°	65.4	69.5	77.7	81.8	85.9	114.5	143.1	171.8	200.4	818.0	1431.5
55°	69.5	73.6	77.7	81.8	85.9	122.7	159.5	196.3	233.1	879.3	1521.5
57.5°	73.6	77.7	81.8	81.8	85.9	130.9	180.0	224.9	269.9	875.2	1476.5
60°	77.7	81.8	85.9	90.0	94.1	139.1	188.1	233.1	278.1	793.4	1308.8
62.5°	85.9	94.1	102.2	106.3	114.5	159.5	200.4	245.4	286.3	650.3	1010.2
65°	98.2	106.3	110.4	118.6	122.7	163.6	208.6	249.5	290.4	539.9	785.3
67.5°	102.2	110.4	114.5	122.7	126.8	167.7	208.6	249.5	290.4	458.1	621.7
70°	102.2	110.4	118.6	122.7	130.9	171.8	208.6	249.5	286.3	396.7	507.2
72.5°	94.1	106.3	114.5	126.8	135.0	171.8	204.5	241.3	274.0	351.7	429.4
75°	90.0	106.3	118.6	135.0	147.2	171.8	200.4	224.9	249.5	306.7	364.0
77.5°	81.8	102.2	122.7	143.1	163.6	180.0	192.2	208.6	220.9	257.7	294.5
80°	77.7	98.2	118.6	139.1	159.5	167.7	171.8	180.0	184.0	188.1	192.2
82.5°	61.3	77.7	94.1	106.3	122.7	114.5	110.4	102.2	94.1	90.0	85.9
85°	28.6	32.7	32.7	36.8	36.8	36.8	32.7	32.7	28.6	24.5	20.4
87.5°	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	57.3	57.3	57.3	57.3	53.2	53.2	53.2	53.2	49.1	49.1	49.1
5°	65.4	65.4	65.4	65.4	61.3	61.3	61.3	61.3	57.3	57.3	57.3
7.5°	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5
10°	77.7	77.7	77.7	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8
12.5°	85.9	85.9	90.0	90.0	94.1	94.1	98.2	98.2	102.2	102.2	102.2
15°	94.1	98.2	102.2	106.3	106.3	110.4	114.5	118.6	122.7	126.8	130.9
17.5°	110.4	114.5	122.7	130.9	139.1	147.2	159.5	175.9	188.1	200.4	216.8
20°	122.7	135.0	159.5	188.1	212.7	237.2	298.6	359.9	421.3	482.6	544.0
22.5°	147.2	171.8	253.6	339.5	421.3	503.1	695.3	887.5	1075.7	1267.9	1439.7
25°	196.3	249.5	437.6	625.8	809.8	997.9	1341.5	1689.1	2032.7	2376.3	2695.3
27.5°	269.9	368.1	674.8	985.7	1292.4	1599.2	2098.1	2601.2	3100.2	3603.2	4049.0
30°	376.3	535.8	993.9	1456.0	1914.1	2372.2	3002.0	3636.0	4265.8	4895.7	5304.6
32.5°	511.2	748.5	1329.2	1910.0	2490.8	3071.5	3766.8	4462.1	5153.3	5848.6	6282.1
35°	654.4	957.0	1656.4	2359.9	3059.3	3762.7	4494.8	5226.9	5959.0	6691.1	7222.8
37.5°	736.2	1079.7	1910.0	2740.3	3566.4	4396.7	5198.3	6004.0	6805.7	7607.3	8253.5
40°	813.9	1227.0	2184.0	3141.1	4098.1	5055.2	5991.8	6928.4	7864.9	8801.5	9631.8
42.5°	928.4	1447.8	2564.4	3680.9	4793.4	5910.0	7141.0	8376.2	9607.3	10838.3	12114.4
45°	1165.6	1865.0	3312.8	4760.7	6204.4	7652.3	9398.7	11149.2	12895.6	14646.1	16282.0
47.5°	1738.2	2805.7	4781.1	6756.6	8732.0	10707.5	12719.7	14732.0	16744.2	18756.5	20703.3
50°	2691.2	4306.7	6777.0	9247.3	11713.6	14183.9	16192.1	18200.2	20204.3	22212.4	24147.0
52.5°	3586.9	5742.3	8396.6	11055.1	13709.5	16367.9	18147.1	19926.2	21705.3	23484.4	25357.6
55°	3893.6	6261.7	8948.8	11640.0	14327.0	17018.2	18731.9	20449.7	22163.4	23877.1	25819.8
57.5°	3623.7	5770.9	8478.4	11186.0	13889.4	16597.0	18511.1	20429.2	22343.3	24261.5	26343.3
60°	3034.7	4756.6	7599.1	10445.7	13288.2	16130.7	18290.2	20449.7	22609.2	24768.7	26846.3
62.5°	2404.9	3795.5	6805.7	9815.8	12826.0	15836.2	18032.5	20232.9	22429.2	24625.5	26220.6
65°	1844.6	2903.9	5865.0	8830.2	11791.3	14756.5	16556.1	18359.7	20159.3	21963.0	23067.2
67.5°	1370.1	2118.6	4707.5	7300.5	9889.5	12478.4	13803.5	15132.8	16457.9	17787.1	18646.0
70°	1010.2	1509.2	3271.9	5034.7	6793.4	8556.1	9770.9	10985.6	12196.2	13410.9	14302.5
72.5°	699.4	965.2	2020.4	3079.7	4134.9	5190.1	6421.2	7652.3	8879.3	10110.3	11124.6
75°	478.5	593.0	1087.9	1582.8	2077.7	2572.6	3505.1	4437.6	5370.1	6302.6	6838.4
77.5°	355.8	417.2	564.4	715.7	863.0	1010.2	1190.2	1370.1	1550.1	1730.0	1963.2
80°	196.3	196.3	216.8	233.1	253.6	269.9	319.0	372.2	421.3	474.4	539.9
82.5°	90.0	94.1	102.2	110.4	114.5	122.7	130.9	139.1	147.2	155.4	155.4
85°	24.5	28.6	28.6	24.5	24.5	20.4	20.4	24.5	24.5	24.5	24.5
87.5°	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	49.1	45.0	45.0	45.0	40.9	40.9	40.9	40.9	40.9	40.9	40.9
5°	57.3	57.3	57.3	57.3	53.2	53.2	53.2	53.2	53.2	49.1	49.1
7.5°	69.5	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	61.3	61.3
10°	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	77.7	77.7
12.5°	102.2	102.2	102.2	102.2	106.3	106.3	102.2	102.2	102.2	98.2	98.2
15°	135.0	139.1	143.1	143.1	147.2	147.2	147.2	143.1	143.1	139.1	135.0
17.5°	229.0	241.3	257.7	274.0	290.4	302.7	302.7	294.5	286.3	278.1	269.9
20°	609.4	670.7	736.2	801.6	871.2	920.2	887.5	863.0	838.4	809.8	785.3
22.5°	1615.5	1787.3	1963.2	2085.9	2208.6	2294.5	2224.9	2090.0	1955.0	1824.1	1689.1
25°	3014.3	3329.2	3648.2	3779.1	3914.1	4012.2	3967.2	3762.7	3558.2	3357.8	3153.3
27.5°	4494.8	4936.6	5382.4	5496.9	5611.4	5697.3	5680.9	5415.1	5149.2	4883.4	4617.5
30°	5713.6	6122.6	6531.6	6646.1	6760.7	6838.4	6752.5	6486.6	6220.8	5954.9	5689.1
32.5°	6719.8	7153.3	7590.9	7742.3	7893.6	7995.8	7893.6	7574.6	7255.5	6940.6	6621.6
35°	7754.5	8282.1	8813.8	9006.0	9198.3	9321.0	9149.2	8756.6	8363.9	7975.4	7582.7
37.5°	8899.7	9541.8	10188.0	10449.8	10715.6	10899.7	10768.8	10278.0	9783.1	9292.3	8797.5
40°	10466.1	11296.4	12130.8	12601.1	13067.3	13398.6	13165.5	12597.0	12024.4	11455.9	10883.3
42.5°	13394.5	14670.6	15946.7	16621.5	17292.3	17779.0	17517.2	16817.8	16118.4	15419.1	14719.7
45°	17918.0	19549.9	21185.9	22171.5	23161.3	23889.3	23586.7	22707.3	21823.9	20944.6	20065.2
47.5°	22650.1	24596.9	26543.7	27329.0	28118.3	28731.8	28658.2	27562.1	26466.0	25374.0	24277.9
50°	26085.6	28020.2	29954.7	30629.5	31308.5	31811.5	31623.4	30228.7	28830.0	27435.3	26036.5
52.5°	27230.8	29099.9	30973.1	31778.8	32584.5	33185.7	32956.7	31386.2	29815.6	28249.2	26678.7
55°	27762.5	29705.2	31647.9	32629.5	33615.2	34335.0	34003.7	32281.9	30555.9	28834.1	27108.1
57.5°	28425.1	30506.8	32588.6	33664.3	34739.9	35517.0	35075.3	33292.1	31508.9	29729.8	27946.5
60°	28924.0	30997.6	33075.3	33938.3	34805.4	35410.7	34985.3	33251.2	31513.0	29778.8	28044.7
62.5°	27819.8	29414.8	31009.9	31652.0	32294.1	32760.4	32519.1	30874.9	29230.8	27586.6	25942.5
65°	24175.6	25279.9	26388.3	26821.8	27251.2	27582.5	27508.9	26122.4	24735.9	23353.5	21967.1
67.5°	19509.0	20367.9	21230.9	21844.4	22461.9	22940.5	22887.3	21623.5	20359.7	19095.9	17832.1
70°	15198.2	16089.8	16981.4	17754.4	18531.5	19132.7	19055.0	17881.2	16703.3	15529.5	14351.6
72.5°	12143.0	13157.3	14171.6	14613.3	15055.1	15365.9	15136.9	14249.3	13357.7	12470.2	11578.6
75°	7374.2	7905.8	8441.6	8437.5	8437.5	8388.5	8159.4	7652.3	7145.1	6638.0	6130.8
77.5°	2196.3	2429.4	2662.5	2887.5	3116.5	3288.3	3243.3	2977.5	2707.5	2441.7	2171.8
80°	605.3	666.7	732.1	760.7	789.4	826.2	920.2	854.8	789.4	728.0	662.6
82.5°	155.4	155.4	155.4	151.3	147.2	139.1	126.8	118.6	110.4	102.2	94.1
85°	24.5	20.4	20.4	20.4	16.4	16.4	16.4	16.4	12.3	12.3	8.2
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
2.5°	40.9	40.9	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	32.7
5°	49.1	49.1	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	40.9
7.5°	61.3	61.3	57.3	57.3	57.3	57.3	53.2	53.2	53.2	53.2	49.1
10°	77.7	73.6	73.6	69.5	69.5	69.5	65.4	65.4	65.4	61.3	61.3
12.5°	98.2	94.1	94.1	90.0	85.9	85.9	81.8	77.7	73.6	73.6	69.5
15°	130.9	126.8	122.7	118.6	114.5	106.3	102.2	94.1	90.0	85.9	81.8
17.5°	249.5	229.0	208.6	188.1	171.8	155.4	139.1	122.7	114.5	106.3	98.2
20°	695.3	601.2	511.2	421.3	364.0	306.7	249.5	192.2	167.7	147.2	122.7
22.5°	1505.1	1317.0	1132.9	944.8	793.4	646.2	494.9	343.6	286.3	233.1	175.9
25°	2797.5	2437.6	2081.8	1721.9	1435.6	1149.3	863.0	576.7	470.3	364.0	257.7
27.5°	4151.3	3685.0	3218.8	2752.5	2298.5	1840.5	1382.4	928.4	744.4	564.4	380.4
30°	5194.2	4699.3	4208.5	3713.7	3141.1	2568.5	1991.8	1419.2	1128.8	838.4	544.0
32.5°	6089.9	5554.1	5022.4	4486.7	3824.1	3161.5	2499.0	1836.4	1472.4	1108.4	740.3
35°	6977.4	6368.0	5762.7	5153.3	4441.7	3730.0	3018.4	2306.7	1844.6	1382.4	916.1
37.5°	8057.2	7312.8	6572.5	5832.3	5100.2	4372.1	3640.0	2907.9	2319.0	1734.1	1145.2
40°	9938.5	8989.7	8044.9	7096.0	6241.2	5390.5	4535.7	3680.9	2940.7	2200.4	1456.0
42.5°	13529.5	12339.3	11153.3	9963.1	8781.1	7599.1	6413.0	5231.0	4175.8	3124.7	2069.5
45°	18539.7	17014.1	15492.7	13967.1	12511.1	11059.2	9603.2	8147.2	6543.9	4940.6	3333.3
47.5°	22609.2	20936.4	19267.7	17594.9	15979.4	14367.9	12752.4	11136.9	9083.7	7034.7	4981.5
50°	24445.6	22850.5	21259.5	19664.4	18044.8	16421.1	14797.4	13177.8	10822.0	8470.3	6114.5
52.5°	25063.1	23443.5	21828.0	20208.4	18601.0	16993.7	15386.3	13779.0	11329.1	8883.3	6433.5
55°	25402.6	23693.0	21987.5	20277.9	18547.9	16813.7	15079.6	13349.6	10912.0	8478.4	6040.8
57.5°	26089.7	24228.8	22372.0	20511.0	18539.7	16568.3	14592.9	12621.5	10216.7	7811.8	5406.9
60°	26216.5	24384.2	22556.0	20727.8	18547.9	16367.9	14183.9	12004.0	9615.4	7231.0	4842.5
62.5°	24412.8	22883.2	21357.7	19828.0	17644.0	15460.0	13271.8	11087.8	8801.5	6515.3	4224.9
65°	20646.0	19325.0	18008.0	16686.9	14903.7	13124.6	11341.4	9558.2	7517.3	5480.5	3439.6
67.5°	16539.7	15247.3	13959.0	12666.5	11325.0	9987.6	8646.1	7304.6	5730.0	4155.4	2580.8
70°	13112.3	11869.0	10629.7	9386.4	8200.3	7010.2	5820.0	4633.9	3656.4	2683.0	1705.5
72.5°	10392.5	9202.4	8016.3	6826.1	5750.5	4674.8	3599.1	2523.5	2036.8	1554.2	1067.5
75°	5513.2	4895.7	4282.2	3664.6	3059.3	2449.9	1840.5	1235.2	1042.9	850.7	654.4
77.5°	1901.8	1631.9	1366.0	1096.1	912.1	728.0	544.0	359.9	339.5	323.1	302.7
80°	576.7	490.8	404.9	319.0	282.2	245.4	208.6	171.8	159.5	147.2	130.9
82.5°	90.0	81.8	77.7	69.5	65.4	65.4	61.3	57.3	49.1	45.0	36.8
85°	8.2	4.1	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	36.8	36.8
2.5°	32.7	32.7
5°	40.9	40.9
7.5°	49.1	49.1
10°	57.3	57.3
12.5°	65.4	65.4
15°	77.7	73.6
17.5°	90.0	85.9
20°	98.2	90.0
22.5°	118.6	102.2
25°	151.3	126.8
27.5°	196.3	155.4
30°	253.6	196.3
32.5°	376.3	274.0
35°	454.0	331.3
37.5°	556.2	384.5
40°	715.7	466.3
42.5°	1014.3	633.9
45°	1730.0	1051.1
47.5°	2932.5	1791.4
50°	3758.7	2298.5
52.5°	3987.7	2437.6
55°	3607.3	2237.2
57.5°	3002.0	1901.8
60°	2458.1	1566.4
62.5°	1938.6	1239.3
65°	1398.8	936.6
67.5°	1006.1	719.8
70°	732.1	564.4
72.5°	580.8	470.3
75°	462.2	392.6
77.5°	286.3	261.8
80°	118.6	110.4
82.5°	28.6	24.5
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066511

CATALOG NUMBER: NVN-SA3C-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-4

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-730-U-5WQ

Data in this report applies to families of products including GSS-SB1A-730-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-4
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-730-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 3000K CCT 26 LEDS

Spectral Parameters

CCT (K): 2985
 CIE u' : 0.2504
 CIE v' : 0.5243
 Duv: 0.0019
 CIE x: 0.4408
 CIE y: 0.4101
 CIE z: 0.1491
 Peak Wavelength (nm): 595
 Dominant Wavelength (nm): 582
 Purity: 55.41818
 R_f: 73.8
 R_g: 94.4

CRI (Ra): 70.8
 R1: 66.3
 R2: 80.6
 R3: 94.5
 R4: 68.2
 R5: 66.5
 R6: 74.7
 R7: 76.2
 R8: 39.6
 R9: -43.2
 R10: 57.6
 R11: 64.8
 R12: 53.5
 R13: 68.7
 R14: 97.0
 R15: 56.4



Test Conditions


Stabilization Time: 36M
 Operation Time: 1H 36M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-4

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-4

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-4

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.19

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.13

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4



TM-30-18

Summary

$R_f = 73.8$
 $R_g = 94.4$
 $CIE R_a = 70.8$
 $R_g = -43.2$





Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 63	CES51 = 86	CES76 = 61
CES02 = 62	CES27 = 83	CES52 = 86	CES77 = 81
CES03 = 31	CES28 = 86	CES53 = 75	CES78 = 64
CES04 = 71	CES29 = 58	CES54 = 81	CES79 = 86
CES05 = 49	CES30 = 61	CES55 = 80	CES80 = 86
CES06 = 51	CES31 = 63	CES56 = 71	CES81 = 70
CES07 = 41	CES32 = 61	CES57 = 69	CES82 = 94
CES08 = 40	CES33 = 65	CES58 = 72	CES83 = 88
CES09 = 29	CES34 = 77	CES59 = 85	CES84 = 90
CES10 = 76	CES35 = 88	CES60 = 93	CES85 = 80
CES11 = 59	CES36 = 89	CES61 = 86	CES86 = 60
CES12 = 65	CES37 = 85	CES62 = 81	CES87 = 78
CES13 = 43	CES38 = 69	CES63 = 73	CES88 = 75
CES14 = 74	CES39 = 93	CES64 = 72	CES89 = 66
CES15 = 71	CES40 = 89	CES65 = 67	CES90 = 72
CES16 = 47	CES41 = 83	CES66 = 70	CES91 = 95
CES17 = 50	CES42 = 87	CES67 = 68	CES92 = 59
CES18 = 56	CES43 = 77	CES68 = 73	CES93 = 76
CES19 = 73	CES44 = 99	CES69 = 83	CES94 = 48
CES20 = 66	CES45 = 83	CES70 = 66	CES95 = 70
CES21 = 87	CES46 = 77	CES71 = 66	CES96 = 76
CES22 = 79	CES47 = 74	CES72 = 88	CES97 = 82
CES23 = 92	CES48 = 62	CES73 = 59	CES98 = 73
CES24 = 91	CES49 = 77	CES74 = 93	CES99 = 60
CES25 = 73	CES50 = 85	CES75 = 67	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)