

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066512

Luminaire Tested: **NVN-SA3D-730-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066512
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA3D-730-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1200mA 3xLight Square PACKAGE
70CRI 3000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 3000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 14370.1 lumens
Efficiency: N/A
Efficacy: 89.3 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 160.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	85.5	0.0	85.5
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	14284.6	0.0	14284.6
	% Fixture	99.4	0.0	99.4
Total	Lumens	14370.0	0.0	14370.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.2	0.0
10°-20°	21.1	0.1
20°-30°	268.2	1.9
30°-40°	903.9	6.3
40°-50°	2729.9	19.0
50°-60°	4816.3	33.5
60°-70°	4243.2	29.5
70°-80°	1350.7	9.4
80°-90°	32.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	14370.0	100.0
0°-180°	14370.1	100.0



REPORT NUMBER: P1066512


CATALOG NUMBER: NVN-SA3D-730-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	280.7	2.0			
FM	(30°-60°)	8417.0	58.6			
FH	(60°-80°)	5560.4	38.7			G3/7500
FVH	(80°-90°)	26.4	0.2			G1/100
BL	(0°-30°)	12.8	0.1	B0/110		
BM	(30°-60°)	33.1	0.2	B0/220		
BH	(60°-80°)	33.5	0.2	B0/110		G0/110
BVH	(80°-90°)	6.1	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short





REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	31.5
5°	45.1	45.1	45.1	40.6	40.6	40.6	36.1	36.1	36.1	36.1	36.1
7.5°	54.1	49.6	49.6	45.1	45.1	45.1	40.6	40.6	40.6	40.6	36.1
10°	63.1	58.6	58.6	54.1	54.1	49.6	49.6	45.1	45.1	40.6	40.6
12.5°	72.1	67.6	63.1	58.6	58.6	54.1	54.1	49.6	49.6	45.1	45.1
15°	81.1	76.6	72.1	67.6	63.1	63.1	58.6	54.1	49.6	49.6	45.1
17.5°	94.6	85.6	81.1	72.1	67.6	63.1	58.6	54.1	54.1	49.6	49.6
20°	99.1	90.1	85.6	76.6	72.1	67.6	63.1	58.6	54.1	54.1	49.6
22.5°	117.2	99.1	94.6	85.6	81.1	76.6	67.6	63.1	58.6	54.1	49.6
25°	144.2	117.2	103.6	90.1	85.6	76.6	72.1	63.1	58.6	54.1	49.6
27.5°	175.8	130.7	117.2	99.1	90.1	81.1	72.1	63.1	58.6	54.1	49.6
30°	216.3	153.2	130.7	108.2	99.1	90.1	76.6	67.6	63.1	58.6	49.6
32.5°	301.9	189.3	153.2	117.2	103.6	94.6	81.1	67.6	63.1	58.6	49.6
35°	365.0	229.8	184.8	135.2	117.2	103.6	85.6	67.6	63.1	58.6	49.6
37.5°	423.6	234.3	189.3	144.2	126.2	108.2	85.6	67.6	63.1	58.6	49.6
40°	518.2	243.3	189.3	135.2	121.7	103.6	90.1	72.1	67.6	58.6	54.1
42.5°	698.5	279.4	202.8	126.2	112.7	103.6	90.1	76.6	67.6	63.1	54.1
45°	1162.7	414.6	274.9	130.7	117.2	103.6	90.1	76.6	72.1	63.1	58.6
47.5°	1978.3	721.0	428.1	135.2	121.7	103.6	90.1	72.1	67.6	63.1	54.1
50°	2532.6	923.8	540.8	157.7	135.2	117.2	94.6	72.1	67.6	63.1	58.6
52.5°	2690.3	982.4	585.8	184.8	157.7	130.7	99.1	72.1	67.6	67.6	63.1
55°	2465.0	955.4	585.8	216.3	180.3	148.7	112.7	76.6	72.1	72.1	67.6
57.5°	2095.5	883.3	558.8	234.3	198.3	157.7	121.7	81.1	76.6	76.6	72.1
60°	1726.0	743.6	504.7	261.4	220.8	180.3	139.7	99.1	94.6	90.1	81.1
62.5°	1370.0	599.4	441.6	279.4	238.8	193.8	153.2	108.2	103.6	99.1	94.6
65°	1032.0	522.7	410.1	292.9	247.9	202.8	157.7	112.7	108.2	108.2	103.6
67.5°	793.1	477.7	392.1	301.9	256.9	211.8	166.7	121.7	117.2	112.7	108.2
70°	626.4	441.6	369.5	297.4	256.9	216.3	171.2	130.7	121.7	117.2	108.2
72.5°	522.7	401.1	342.5	283.9	252.4	220.8	189.3	157.7	139.7	126.2	108.2
75°	437.1	360.5	310.9	256.9	234.3	216.3	193.8	171.2	148.7	126.2	103.6
77.5°	288.4	261.4	238.8	216.3	202.8	189.3	171.2	157.7	135.2	117.2	94.6
80°	121.7	112.7	117.2	117.2	117.2	117.2	112.7	112.7	99.1	85.6	67.6
82.5°	27.0	22.5	27.0	27.0	27.0	27.0	22.5	22.5	22.5	18.0	18.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
5°	36.1	36.1	36.1	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
7.5°	36.1	36.1	36.1	31.5	31.5	31.5	31.5	27.0	27.0	27.0	27.0
10°	36.1	36.1	36.1	31.5	31.5	31.5	31.5	27.0	27.0	27.0	27.0
12.5°	40.6	40.6	36.1	36.1	31.5	31.5	31.5	27.0	27.0	27.0	27.0
15°	40.6	40.6	36.1	36.1	31.5	31.5	31.5	27.0	27.0	27.0	27.0
17.5°	45.1	40.6	40.6	36.1	31.5	31.5	31.5	27.0	27.0	27.0	27.0
20°	45.1	40.6	40.6	36.1	31.5	31.5	31.5	27.0	27.0	27.0	27.0
22.5°	45.1	40.6	40.6	36.1	31.5	31.5	27.0	27.0	22.5	22.5	18.0
25°	45.1	40.6	40.6	36.1	31.5	31.5	27.0	27.0	22.5	18.0	18.0
27.5°	45.1	40.6	40.6	36.1	31.5	27.0	27.0	22.5	18.0	13.5	13.5
30°	45.1	40.6	40.6	36.1	31.5	27.0	22.5	18.0	13.5	13.5	9.0
32.5°	45.1	40.6	36.1	31.5	27.0	22.5	22.5	18.0	13.5	9.0	9.0
35°	45.1	40.6	36.1	31.5	27.0	22.5	22.5	18.0	13.5	9.0	9.0
37.5°	45.1	40.6	36.1	31.5	27.0	22.5	18.0	13.5	9.0	9.0	4.5
40°	45.1	40.6	36.1	31.5	27.0	22.5	18.0	13.5	9.0	9.0	4.5
42.5°	45.1	40.6	36.1	31.5	27.0	22.5	18.0	13.5	9.0	9.0	4.5
45°	49.6	45.1	40.6	31.5	27.0	22.5	22.5	18.0	13.5	9.0	9.0
47.5°	49.6	45.1	40.6	31.5	27.0	22.5	22.5	18.0	13.5	9.0	9.0
50°	54.1	49.6	45.1	36.1	31.5	27.0	22.5	13.5	9.0	9.0	4.5
52.5°	58.6	54.1	49.6	45.1	40.6	31.5	22.5	13.5	4.5	4.5	4.5
55°	63.1	58.6	58.6	54.1	49.6	36.1	27.0	13.5	0.0	0.0	0.0
57.5°	67.6	63.1	63.1	58.6	54.1	40.6	27.0	13.5	0.0	0.0	0.0
60°	76.6	72.1	67.6	58.6	54.1	40.6	27.0	13.5	0.0	0.0	0.0
62.5°	90.1	81.1	67.6	58.6	45.1	36.1	22.5	13.5	0.0	0.0	0.0
65°	99.1	85.6	72.1	54.1	40.6	31.5	22.5	9.0	0.0	0.0	0.0
67.5°	103.6	85.6	72.1	54.1	36.1	27.0	18.0	9.0	0.0	0.0	0.0
70°	99.1	81.1	67.6	49.6	31.5	22.5	18.0	9.0	0.0	0.0	0.0
72.5°	90.1	76.6	58.6	45.1	27.0	22.5	13.5	9.0	0.0	0.0	0.0
75°	81.1	67.6	49.6	36.1	18.0	13.5	9.0	4.5	0.0	0.0	0.0
77.5°	72.1	58.6	40.6	27.0	9.0	9.0	4.5	4.5	0.0	0.0	0.0
80°	54.1	40.6	27.0	13.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	13.5	9.0	9.0	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0
5°	27.0	27.0	27.0	27.0	22.5	22.5	22.5	22.5	22.5	22.5	22.5
7.5°	27.0	27.0	27.0	27.0	22.5	22.5	22.5	22.5	18.0	18.0	18.0
10°	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	18.0	18.0	18.0
12.5°	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	18.0	18.0	18.0
15°	22.5	22.5	22.5	22.5	22.5	22.5	22.5	18.0	18.0	13.5	13.5
17.5°	22.5	22.5	22.5	22.5	18.0	18.0	18.0	13.5	13.5	9.0	9.0
20°	22.5	22.5	22.5	18.0	18.0	13.5	13.5	9.0	9.0	4.5	4.5
22.5°	18.0	13.5	13.5	9.0	9.0	4.5	4.5	4.5	0.0	0.0	0.0
25°	13.5	9.0	9.0	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	9.0	4.5	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	9.0	4.5	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	27.0	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5
5°	22.5	22.5	22.5	22.5	18.0	18.0	18.0	18.0	18.0	18.0	18.0
7.5°	18.0	18.0	18.0	18.0	18.0	18.0	13.5	13.5	13.5	13.5	13.5
10°	18.0	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	9.0	9.0
12.5°	18.0	13.5	13.5	13.5	9.0	9.0	9.0	9.0	9.0	4.5	4.5
15°	13.5	9.0	9.0	9.0	4.5	4.5	4.5	4.5	4.5	0.0	0.0
17.5°	9.0	4.5	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	27.0	27.0
5°	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0
7.5°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
10°	9.0	9.0	9.0	9.0	9.0	9.0	4.5	4.5	4.5	4.5	4.5
12.5°	4.5	4.5	4.5	4.5	4.5	4.5	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	27.0	27.0	27.0	27.0	27.0	31.5	31.5	36.1	36.1	40.6	40.6
5°	18.0	18.0	22.5	22.5	22.5	22.5	27.0	27.0	27.0	31.5	31.5
7.5°	13.5	13.5	13.5	13.5	13.5	18.0	18.0	22.5	22.5	27.0	27.0
10°	4.5	4.5	9.0	9.0	9.0	9.0	13.5	13.5	13.5	18.0	22.5
12.5°	0.0	0.0	4.5	4.5	4.5	4.5	9.0	9.0	9.0	13.5	18.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	9.0	13.5
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	9.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	45.1	45.1	49.6	49.6	54.1	54.1	58.6	58.6	58.6	58.6	58.6
5°	36.1	36.1	40.6	45.1	45.1	49.6	54.1	54.1	54.1	54.1	54.1
7.5°	31.5	31.5	36.1	40.6	40.6	45.1	49.6	49.6	54.1	54.1	54.1
10°	22.5	27.0	31.5	36.1	36.1	40.6	45.1	45.1	49.6	49.6	49.6
12.5°	18.0	22.5	27.0	31.5	31.5	36.1	40.6	40.6	45.1	45.1	49.6
15°	13.5	18.0	22.5	27.0	27.0	31.5	36.1	36.1	40.6	45.1	49.6
17.5°	9.0	13.5	18.0	22.5	22.5	27.0	31.5	36.1	40.6	40.6	45.1
20°	9.0	9.0	13.5	18.0	18.0	22.5	27.0	31.5	36.1	36.1	40.6
22.5°	4.5	4.5	9.0	13.5	13.5	18.0	22.5	27.0	31.5	31.5	36.1
25°	0.0	0.0	4.5	9.0	9.0	13.5	18.0	18.0	22.5	22.5	27.0
27.5°	0.0	0.0	4.5	4.5	9.0	9.0	13.5	13.5	18.0	18.0	22.5
30°	0.0	0.0	4.5	4.5	9.0	9.0	13.5	13.5	18.0	18.0	18.0
32.5°	0.0	0.0	0.0	4.5	4.5	4.5	9.0	9.0	13.5	13.5	18.0
35°	0.0	0.0	0.0	4.5	4.5	4.5	9.0	9.0	13.5	13.5	13.5
37.5°	0.0	0.0	0.0	4.5	4.5	4.5	9.0	9.0	9.0	9.0	13.5
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	9.0	9.0	9.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	9.0	9.0	9.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	9.0	9.0	9.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	9.0	9.0	9.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	9.0	9.0	9.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	9.0	9.0	9.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	9.0	9.0	9.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	9.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	58.6	58.6
5°	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	54.1	54.1
7.5°	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	54.1	54.1
10°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
12.5°	49.6	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
15°	49.6	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
17.5°	45.1	49.6	49.6	49.6	54.1	54.1	54.1	54.1	54.1	54.1	54.1
20°	40.6	45.1	45.1	45.1	49.6	49.6	49.6	49.6	54.1	54.1	54.1
22.5°	36.1	40.6	40.6	40.6	45.1	45.1	45.1	45.1	49.6	49.6	49.6
25°	31.5	31.5	36.1	36.1	40.6	40.6	40.6	40.6	40.6	40.6	40.6
27.5°	22.5	27.0	27.0	27.0	31.5	31.5	31.5	31.5	36.1	36.1	36.1
30°	22.5	22.5	22.5	22.5	27.0	27.0	27.0	27.0	31.5	31.5	31.5
32.5°	18.0	22.5	22.5	22.5	27.0	27.0	27.0	27.0	31.5	31.5	31.5
35°	18.0	18.0	18.0	18.0	22.5	22.5	22.5	22.5	27.0	27.0	27.0
37.5°	13.5	18.0	18.0	18.0	22.5	22.5	22.5	22.5	27.0	27.0	27.0
40°	13.5	13.5	13.5	13.5	18.0	18.0	18.0	18.0	22.5	22.5	22.5
42.5°	13.5	13.5	13.5	13.5	18.0	18.0	18.0	18.0	22.5	22.5	22.5
45°	13.5	13.5	13.5	13.5	18.0	18.0	18.0	18.0	22.5	22.5	22.5
47.5°	13.5	13.5	13.5	13.5	18.0	18.0	18.0	18.0	22.5	22.5	22.5
50°	13.5	13.5	13.5	13.5	18.0	18.0	18.0	18.0	22.5	22.5	22.5
52.5°	9.0	9.0	9.0	9.0	13.5	13.5	13.5	13.5	18.0	18.0	18.0
55°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	13.5	13.5	13.5
57.5°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	13.5	13.5	13.5
60°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0
62.5°	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
65°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	4.5	4.5
67.5°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0
70°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0
72.5°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0
75°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0
77.5°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0
80°	13.5	13.5	13.5	13.5	13.5	9.0	9.0	9.0	9.0	9.0	9.0
82.5°	9.0	13.5	13.5	13.5	13.5	9.0	9.0	9.0	9.0	9.0	9.0
85°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0
87.5°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	58.6	58.6	54.1	54.1	54.1	54.1	54.1	54.1	54.1	58.6	58.6
5°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	58.6	58.6
7.5°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	58.6	58.6
10°	54.1	54.1	54.1	54.1	49.6	49.6	54.1	54.1	54.1	58.6	58.6
12.5°	54.1	54.1	54.1	54.1	49.6	49.6	54.1	54.1	58.6	58.6	63.1
15°	54.1	54.1	49.6	49.6	49.6	49.6	54.1	54.1	58.6	58.6	63.1
17.5°	54.1	54.1	49.6	49.6	49.6	49.6	54.1	54.1	58.6	58.6	63.1
20°	54.1	54.1	49.6	49.6	49.6	49.6	49.6	49.6	54.1	58.6	58.6
22.5°	49.6	49.6	49.6	49.6	45.1	45.1	49.6	49.6	54.1	58.6	58.6
25°	40.6	45.1	45.1	45.1	45.1	45.1	49.6	49.6	54.1	58.6	58.6
27.5°	36.1	40.6	40.6	40.6	40.6	45.1	45.1	49.6	54.1	58.6	58.6
30°	31.5	36.1	36.1	36.1	40.6	45.1	45.1	49.6	54.1	58.6	58.6
32.5°	31.5	36.1	36.1	36.1	40.6	40.6	45.1	45.1	49.6	54.1	58.6
35°	31.5	31.5	36.1	36.1	36.1	40.6	40.6	45.1	49.6	54.1	58.6
37.5°	31.5	31.5	36.1	36.1	36.1	40.6	40.6	45.1	49.6	54.1	58.6
40°	27.0	31.5	31.5	36.1	36.1	40.6	40.6	45.1	49.6	58.6	63.1
42.5°	27.0	27.0	31.5	31.5	36.1	40.6	40.6	45.1	49.6	58.6	63.1
45°	27.0	31.5	31.5	36.1	40.6	45.1	45.1	49.6	54.1	58.6	63.1
47.5°	27.0	31.5	31.5	36.1	45.1	45.1	49.6	49.6	54.1	58.6	63.1
50°	27.0	31.5	31.5	36.1	49.6	49.6	49.6	49.6	54.1	58.6	63.1
52.5°	22.5	27.0	27.0	31.5	40.6	45.1	49.6	54.1	58.6	63.1	67.6
55°	18.0	22.5	22.5	27.0	36.1	40.6	49.6	58.6	63.1	67.6	72.1
57.5°	18.0	18.0	22.5	22.5	31.5	40.6	54.1	63.1	67.6	72.1	76.6
60°	13.5	13.5	18.0	18.0	27.0	36.1	49.6	63.1	67.6	76.6	81.1
62.5°	9.0	13.5	13.5	18.0	22.5	36.1	49.6	63.1	72.1	81.1	85.6
65°	9.0	9.0	13.5	13.5	22.5	31.5	45.1	54.1	67.6	81.1	94.6
67.5°	13.5	13.5	18.0	18.0	22.5	31.5	45.1	54.1	67.6	85.6	99.1
70°	13.5	13.5	18.0	18.0	27.0	36.1	45.1	54.1	67.6	85.6	99.1
72.5°	13.5	13.5	18.0	18.0	27.0	31.5	40.6	49.6	63.1	76.6	90.1
75°	9.0	13.5	13.5	13.5	22.5	27.0	36.1	45.1	58.6	72.1	85.6
77.5°	9.0	9.0	9.0	9.0	18.0	22.5	31.5	36.1	49.6	63.1	76.6
80°	9.0	9.0	9.0	9.0	13.5	18.0	27.0	31.5	45.1	58.6	72.1
82.5°	9.0	9.0	4.5	4.5	9.0	13.5	18.0	22.5	36.1	45.1	58.6
85°	9.0	9.0	4.5	4.5	4.5	9.0	9.0	13.5	18.0	22.5	27.0
87.5°	9.0	9.0	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	58.6	58.6	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1
5°	58.6	63.1	63.1	67.6	67.6	67.6	72.1	72.1	72.1	72.1	72.1
7.5°	58.6	63.1	63.1	67.6	67.6	67.6	72.1	72.1	72.1	76.6	76.6
10°	58.6	63.1	63.1	67.6	67.6	72.1	76.6	76.6	81.1	81.1	81.1
12.5°	63.1	67.6	67.6	72.1	72.1	76.6	81.1	81.1	85.6	90.1	90.1
15°	63.1	67.6	72.1	72.1	76.6	81.1	85.6	85.6	90.1	94.6	99.1
17.5°	63.1	67.6	72.1	72.1	76.6	81.1	90.1	94.6	99.1	108.2	112.7
20°	63.1	67.6	72.1	72.1	76.6	85.6	90.1	99.1	103.6	112.7	121.7
22.5°	63.1	67.6	72.1	76.6	81.1	90.1	99.1	103.6	112.7	126.2	135.2
25°	63.1	67.6	72.1	76.6	81.1	90.1	99.1	108.2	117.2	135.2	153.2
27.5°	63.1	67.6	76.6	81.1	85.6	94.6	108.2	117.2	126.2	157.7	189.3
30°	63.1	67.6	76.6	81.1	85.6	99.1	112.7	121.7	135.2	189.3	238.8
32.5°	63.1	72.1	76.6	85.6	90.1	103.6	121.7	135.2	148.7	225.3	297.4
35°	63.1	72.1	76.6	85.6	90.1	108.2	126.2	144.2	162.2	274.9	387.6
37.5°	63.1	72.1	76.6	85.6	90.1	117.2	144.2	171.2	198.3	315.5	432.6
40°	67.6	76.6	81.1	90.1	94.6	121.7	148.7	175.8	202.8	320.0	437.1
42.5°	67.6	76.6	81.1	90.1	94.6	117.2	144.2	166.7	189.3	320.0	450.6
45°	67.6	76.6	85.6	90.1	99.1	121.7	144.2	162.2	184.8	351.5	513.7
47.5°	67.6	76.6	85.6	90.1	99.1	121.7	144.2	166.7	189.3	464.2	734.6
50°	67.6	76.6	85.6	90.1	99.1	126.2	153.2	180.3	207.3	694.0	1180.7
52.5°	72.1	76.6	85.6	90.1	94.6	126.2	157.7	189.3	220.8	901.3	1577.3
55°	76.6	81.1	85.6	90.1	94.6	135.2	175.8	216.3	256.9	968.9	1676.4
57.5°	81.1	85.6	90.1	90.1	94.6	144.2	198.3	247.9	297.4	964.4	1626.8
60°	85.6	90.1	94.6	99.1	103.6	153.2	207.3	256.9	306.4	874.3	1442.1
62.5°	94.6	103.6	112.7	117.2	126.2	175.8	220.8	270.4	315.5	716.5	1113.1
65°	108.2	117.2	121.7	130.7	135.2	180.3	229.8	274.9	320.0	594.9	865.2
67.5°	112.7	121.7	126.2	135.2	139.7	184.8	229.8	274.9	320.0	504.7	685.0
70°	112.7	121.7	130.7	135.2	144.2	189.3	229.8	274.9	315.5	437.1	558.8
72.5°	103.6	117.2	126.2	139.7	148.7	189.3	225.3	265.9	301.9	387.6	473.2
75°	99.1	117.2	130.7	148.7	162.2	189.3	220.8	247.9	274.9	338.0	401.1
77.5°	90.1	112.7	135.2	157.7	180.3	198.3	211.8	229.8	243.3	283.9	324.5
80°	85.6	108.2	130.7	153.2	175.8	184.8	189.3	198.3	202.8	207.3	211.8
82.5°	67.6	85.6	103.6	117.2	135.2	126.2	121.7	112.7	103.6	99.1	94.6
85°	31.5	36.1	36.1	40.6	40.6	40.6	36.1	36.1	31.5	27.0	22.5
87.5°	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	63.1	63.1	63.1	63.1	58.6	58.6	58.6	58.6	54.1	54.1	54.1
5°	72.1	72.1	72.1	72.1	67.6	67.6	67.6	67.6	63.1	63.1	63.1
7.5°	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6
10°	85.6	85.6	85.6	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1
12.5°	94.6	94.6	99.1	99.1	103.6	103.6	108.2	108.2	112.7	112.7	112.7
15°	103.6	108.2	112.7	117.2	117.2	121.7	126.2	130.7	135.2	139.7	144.2
17.5°	121.7	126.2	135.2	144.2	153.2	162.2	175.8	193.8	207.3	220.8	238.8
20°	135.2	148.7	175.8	207.3	234.3	261.4	329.0	396.6	464.2	531.8	599.4
22.5°	162.2	189.3	279.4	374.0	464.2	554.3	766.1	977.9	1185.2	1397.0	1586.3
25°	216.3	274.9	482.2	689.5	892.3	1099.6	1478.1	1861.2	2239.7	2618.2	2969.7
27.5°	297.4	405.6	743.6	1086.1	1424.0	1762.0	2311.8	2866.1	3415.9	3970.2	4461.4
30°	414.6	590.3	1095.1	1604.3	2109.0	2613.7	3307.7	4006.2	4700.2	5394.2	5844.9
32.5°	563.3	824.7	1464.6	2104.5	2744.4	3384.3	4150.4	4916.5	5678.1	6444.2	6921.9
35°	721.0	1054.5	1825.1	2600.2	3370.8	4145.9	4952.6	5759.2	6565.9	7372.5	7958.4
37.5°	811.2	1189.7	2104.5	3019.3	3929.6	4844.4	5727.7	6615.5	7498.7	8382.0	9094.0
40°	896.8	1351.9	2406.4	3460.9	4515.5	5570.0	6601.9	7633.9	8665.9	9697.9	10612.7
42.5°	1023.0	1595.3	2825.5	4055.8	5281.6	6511.8	7868.3	9229.2	10585.6	11942.1	13348.1
45°	1284.3	2054.9	3650.2	5245.5	6836.3	8431.6	10355.8	12284.6	14208.8	16137.6	17940.2
47.5°	1915.2	3091.4	5268.0	7444.6	9621.3	11797.9	14015.0	16232.2	18449.4	20666.5	22811.6
50°	2965.2	4745.3	7467.2	10189.1	12906.5	15628.3	17841.0	20053.7	22261.8	24474.5	26606.0
52.5°	3952.2	6327.0	9251.7	12180.9	15105.6	18034.8	19995.1	21955.4	23915.7	25876.0	27939.9
55°	4290.1	6899.4	9860.1	12825.3	15786.1	18751.3	20639.5	22532.2	24420.4	26308.6	28449.2
57.5°	3992.7	6358.6	9341.9	12325.1	15303.9	18287.1	20396.2	22509.7	24618.7	26732.2	29026.0
60°	3343.8	5241.0	8373.0	11509.5	14641.4	17773.4	20152.8	22532.2	24911.6	27291.0	29580.3
62.5°	2649.8	4182.0	7498.7	10815.5	14132.2	17448.9	19868.9	22293.4	24713.3	27133.3	28890.8
65°	2032.4	3199.6	6462.2	9729.4	12992.1	16259.2	18242.1	20229.4	22212.3	24199.6	25416.3
67.5°	1509.7	2334.3	5186.9	8044.0	10896.6	13749.2	15209.2	16673.8	18133.9	19598.5	20544.9
70°	1113.1	1662.9	3605.2	5547.4	7485.2	9427.5	10765.9	12104.3	13438.2	14776.6	15759.0
72.5°	770.6	1063.5	2226.2	3393.4	4556.0	5718.7	7075.1	8431.6	9783.5	11139.9	12257.5
75°	527.3	653.4	1198.7	1744.0	2289.3	2834.6	3862.0	4889.5	5917.0	6944.4	7534.8
77.5°	392.1	459.7	621.9	788.6	950.9	1113.1	1311.4	1509.7	1707.9	1906.2	2163.1
80°	216.3	216.3	238.8	256.9	279.4	297.4	351.5	410.1	464.2	522.7	594.9
82.5°	99.1	103.6	112.7	121.7	126.2	135.2	144.2	153.2	162.2	171.2	171.2
85°	27.0	31.5	31.5	27.0	27.0	22.5	22.5	27.0	27.0	27.0	27.0
87.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	54.1	49.6	49.6	49.6	45.1	45.1	45.1	45.1	45.1	45.1	45.1
5°	63.1	63.1	63.1	63.1	58.6	58.6	58.6	58.6	58.6	54.1	54.1
7.5°	76.6	72.1	72.1	72.1	72.1	72.1	72.1	72.1	72.1	67.6	67.6
10°	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	85.6	85.6
12.5°	112.7	112.7	112.7	112.7	117.2	117.2	112.7	112.7	112.7	108.2	108.2
15°	148.7	153.2	157.7	157.7	162.2	162.2	162.2	157.7	157.7	153.2	148.7
17.5°	252.4	265.9	283.9	301.9	320.0	333.5	333.5	324.5	315.5	306.4	297.4
20°	671.5	739.1	811.2	883.3	959.9	1013.9	977.9	950.9	923.8	892.3	865.2
22.5°	1780.0	1969.3	2163.1	2298.3	2433.5	2528.1	2451.5	2302.8	2154.1	2009.9	1861.2
25°	3321.2	3668.2	4019.7	4164.0	4312.7	4420.8	4371.3	4145.9	3920.6	3699.8	3474.5
27.5°	4952.6	5439.3	5930.5	6056.7	6182.8	6277.5	6259.4	5966.5	5673.6	5380.7	5087.8
30°	6295.5	6746.1	7196.8	7323.0	7449.2	7534.8	7440.1	7147.2	6854.3	6561.4	6268.5
32.5°	7404.1	7881.8	8364.0	8530.7	8697.4	8810.1	8697.4	8345.9	7994.4	7647.4	7295.9
35°	8544.2	9125.5	9711.4	9923.2	10135.0	10270.2	10080.9	9648.3	9215.7	8787.6	8354.9
37.5°	9806.0	10513.5	11225.6	11514.0	11806.9	12009.7	11865.5	11324.7	10779.4	10238.6	9693.4
40°	11532.0	12446.8	13366.1	13884.4	14398.1	14763.1	14506.2	13879.8	13248.9	12622.5	11991.6
42.5°	14758.6	16164.6	17570.6	18314.2	19053.2	19589.5	19301.1	18530.5	17759.9	16989.3	16218.7
45°	19742.7	21540.8	23343.4	24429.4	25520.0	26322.1	25988.7	25019.8	24046.4	23077.5	22108.6
47.5°	24956.7	27101.8	29246.8	30112.1	30981.8	31657.8	31576.6	30368.9	29161.2	27958.0	26750.2
50°	28742.1	30873.6	33005.2	33748.8	34496.8	35051.1	34843.8	33307.1	31765.9	30229.2	28688.0
52.5°	30003.9	32063.3	34127.3	35015.1	35902.8	36565.3	36312.9	34582.4	32852.0	31126.0	29395.5
55°	30589.7	32730.3	34870.9	35952.4	37038.5	37831.6	37466.6	35569.4	33667.6	31770.4	29868.7
57.5°	31319.8	33613.6	35907.3	37092.5	38277.7	39134.0	38647.3	36682.4	34717.6	32757.3	30792.5
60°	31869.6	34154.3	36443.6	37394.5	38349.8	39016.8	38548.1	36637.4	34722.1	32811.4	30900.7
62.5°	30652.8	32410.3	34167.9	34875.4	35582.9	36096.6	35830.7	34019.1	32207.6	30396.0	28584.4
65°	26637.6	27854.3	29075.6	29553.3	30026.4	30391.5	30310.3	28782.7	27255.0	25731.8	24204.1
67.5°	21495.7	22442.1	23392.9	24068.9	24749.4	25276.6	25218.1	23825.6	22433.1	21040.6	19648.1
70°	16745.9	17728.3	18710.8	19562.5	20418.7	21081.1	20995.5	19702.2	18404.3	17111.0	15813.1
72.5°	13379.6	14497.2	15614.8	16101.5	16588.2	16930.7	16678.3	15700.4	14718.0	13740.1	12757.7
75°	8125.1	8711.0	9301.3	9296.8	9296.8	9242.7	8990.4	8431.6	7872.8	7314.0	6755.2
77.5°	2420.0	2676.8	2933.7	3181.5	3433.9	3623.2	3573.6	3280.7	2983.3	2690.3	2392.9
80°	667.0	734.6	806.7	838.2	869.7	910.3	1013.9	941.8	869.7	802.1	730.0
82.5°	171.2	171.2	171.2	166.7	162.2	153.2	139.7	130.7	121.7	112.7	103.6
85°	27.0	22.5	22.5	22.5	18.0	18.0	18.0	18.0	13.5	13.5	9.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
2.5°	45.1	45.1	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	36.1
5°	54.1	54.1	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	45.1
7.5°	67.6	67.6	63.1	63.1	63.1	63.1	58.6	58.6	58.6	58.6	54.1
10°	85.6	81.1	81.1	76.6	76.6	76.6	72.1	72.1	72.1	67.6	67.6
12.5°	108.2	103.6	103.6	99.1	94.6	94.6	90.1	85.6	81.1	81.1	76.6
15°	144.2	139.7	135.2	130.7	126.2	117.2	112.7	103.6	99.1	94.6	90.1
17.5°	274.9	252.4	229.8	207.3	189.3	171.2	153.2	135.2	126.2	117.2	108.2
20°	766.1	662.4	563.3	464.2	401.1	338.0	274.9	211.8	184.8	162.2	135.2
22.5°	1658.4	1451.1	1248.3	1041.0	874.3	712.0	545.3	378.5	315.5	256.9	193.8
25°	3082.4	2685.8	2293.8	1897.2	1581.8	1266.3	950.9	635.4	518.2	401.1	283.9
27.5°	4574.0	4060.3	3546.6	3032.8	2532.6	2027.9	1523.2	1023.0	820.2	621.9	419.1
30°	5723.2	5177.9	4637.1	4091.9	3460.9	2830.0	2194.6	1563.7	1243.8	923.8	599.4
32.5°	6710.1	6119.8	5533.9	4943.6	4213.5	3483.5	2753.4	2023.4	1622.3	1221.2	815.7
35°	7688.0	7016.5	6349.6	5678.1	4894.0	4109.9	3325.8	2541.6	2032.4	1523.2	1009.4
37.5°	8877.7	8057.5	7241.9	6426.2	5619.5	4817.4	4010.7	3204.1	2555.2	1910.7	1261.8
40°	10950.7	9905.2	8864.2	7818.7	6876.8	5939.5	4997.6	4055.8	3240.1	2424.5	1604.3
42.5°	14907.3	13595.9	12289.1	10977.7	9675.3	8373.0	7066.1	5763.7	4601.1	3442.9	2280.3
45°	20427.7	18746.8	17070.4	15389.5	13785.2	12185.4	10581.1	8976.8	7210.3	5443.8	3672.8
47.5°	24911.6	23068.5	21229.9	19386.7	17606.7	15831.1	14051.1	12271.0	10008.8	7751.1	5488.8
50°	26935.0	25177.5	23424.5	21667.0	19882.4	18093.4	16304.3	14519.8	11924.0	9332.8	6737.1
52.5°	27615.5	25830.9	24050.9	22266.3	20495.3	18724.3	16953.2	15182.2	12482.8	9788.0	7088.6
55°	27989.5	26105.8	24226.6	22342.9	20436.7	18526.0	16615.3	14709.0	12023.2	9341.9	6656.0
57.5°	28746.6	26696.2	24650.2	22599.8	20427.7	18255.6	16079.0	13906.9	11257.1	8607.3	5957.5
60°	28886.3	26867.4	24853.0	22838.7	20436.7	18034.8	15628.3	13226.4	10594.6	7967.4	5335.6
62.5°	26899.0	25213.6	23532.6	21847.2	19440.8	17034.4	14623.4	12217.0	9697.9	7178.8	4655.2
65°	22748.5	21292.9	19841.9	18386.3	16421.5	14461.2	12496.4	10531.6	8282.8	6038.6	3789.9
67.5°	18224.1	16800.0	15380.5	13956.5	12478.3	11004.7	9526.6	8048.5	6313.5	4578.5	2843.6
70°	14447.7	13077.7	11712.2	10342.3	9035.4	7724.0	6412.7	5105.8	4028.8	2956.2	1879.2
72.5°	11450.9	10139.5	8832.6	7521.3	6336.1	5150.9	3965.7	2780.5	2244.2	1712.4	1176.2
75°	6074.7	5394.2	4718.2	4037.8	3370.8	2699.4	2027.9	1360.9	1149.1	937.3	721.0
77.5°	2095.5	1798.1	1505.2	1207.7	1004.9	802.1	599.4	396.6	374.0	356.0	333.5
80°	635.4	540.8	446.1	351.5	310.9	270.4	229.8	189.3	175.8	162.2	144.2
82.5°	99.1	90.1	85.6	76.6	72.1	72.1	67.6	63.1	54.1	49.6	40.6
85°	9.0	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066512
 CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	40.6	40.6
2.5°	36.1	36.1
5°	45.1	45.1
7.5°	54.1	54.1
10°	63.1	63.1
12.5°	72.1	72.1
15°	85.6	81.1
17.5°	99.1	94.6
20°	108.2	99.1
22.5°	130.7	112.7
25°	166.7	139.7
27.5°	216.3	171.2
30°	279.4	216.3
32.5°	414.6	301.9
35°	500.2	365.0
37.5°	612.9	423.6
40°	788.6	513.7
42.5°	1117.6	698.5
45°	1906.2	1158.2
47.5°	3231.1	1973.8
50°	4141.4	2532.6
52.5°	4393.8	2685.8
55°	3974.7	2465.0
57.5°	3307.7	2095.5
60°	2708.4	1726.0
62.5°	2136.1	1365.5
65°	1541.2	1032.0
67.5°	1108.6	793.1
70°	806.7	621.9
72.5°	639.9	518.2
75°	509.2	432.6
77.5°	315.5	288.4
80°	130.7	121.7
82.5°	31.5	27.0
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066512

CATALOG NUMBER: NVN-SA3D-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-4

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-730-U-5WQ


Data in this report applies to families of products including GSS-SB1A-730-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-4
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-730-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 3000K CCT 26 LEDS

Spectral Parameters

CCT (K):	2985	CRI (Ra):	70.8		
CIE u':	0.2504	R1:	66.3	R9:	-43.2
CIE v':	0.5243	R2:	80.6	R10:	57.6
Duv:	0.0019	R3:	94.5	R11:	64.8
CIE x:	0.4408	R4:	68.2	R12:	53.5
CIE y:	0.4101	R5:	66.5	R13:	68.7
CIE z:	0.1491	R6:	74.7	R14:	97.0
Peak Wavelength (nm):	595	R7:	76.2	R15:	56.4
Dominant Wavelength (nm):	582	R8:	39.6		
Purity:	55.41818				
Rf:	73.8				
Rg:	94.4				



Test Conditions


Stabilization Time: 36M
 Operation Time: 1H 36M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-4


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-4

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-4

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.19

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.13


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4





TM-30-18

Summary

$R_f = 73.8$
 $R_g = 94.4$
 $CIE R_a = 70.8$
 $R_g = -43.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 63	CES51 = 86	CES76 = 61
CES02 = 62	CES27 = 83	CES52 = 86	CES77 = 81
CES03 = 31	CES28 = 86	CES53 = 75	CES78 = 64
CES04 = 71	CES29 = 58	CES54 = 81	CES79 = 86
CES05 = 49	CES30 = 61	CES55 = 80	CES80 = 86
CES06 = 51	CES31 = 63	CES56 = 71	CES81 = 70
CES07 = 41	CES32 = 61	CES57 = 69	CES82 = 94
CES08 = 40	CES33 = 65	CES58 = 72	CES83 = 88
CES09 = 29	CES34 = 77	CES59 = 85	CES84 = 90
CES10 = 76	CES35 = 88	CES60 = 93	CES85 = 80
CES11 = 59	CES36 = 89	CES61 = 86	CES86 = 60
CES12 = 65	CES37 = 85	CES62 = 81	CES87 = 78
CES13 = 43	CES38 = 69	CES63 = 73	CES88 = 75
CES14 = 74	CES39 = 93	CES64 = 72	CES89 = 66
CES15 = 71	CES40 = 89	CES65 = 67	CES90 = 72
CES16 = 47	CES41 = 83	CES66 = 70	CES91 = 95
CES17 = 50	CES42 = 87	CES67 = 68	CES92 = 59
CES18 = 56	CES43 = 77	CES68 = 73	CES93 = 76
CES19 = 73	CES44 = 99	CES69 = 83	CES94 = 48
CES20 = 66	CES45 = 83	CES70 = 66	CES95 = 70
CES21 = 87	CES46 = 77	CES71 = 66	CES96 = 76
CES22 = 79	CES47 = 74	CES72 = 88	CES97 = 82
CES23 = 92	CES48 = 62	CES73 = 59	CES98 = 73
CES24 = 91	CES49 = 77	CES74 = 93	CES99 = 60
CES25 = 73	CES50 = 85	CES75 = 67	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)