

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066513

Luminaire Tested: **NVN-SA4A-730-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066513
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA4A-730-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 615mA 4xLight Square PACKAGE
70CRI 3000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 3000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 11136 lumens
Efficiency: N/A
Efficacy: 103.7 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 107.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.2 fc
 Type III - Short - N/A

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	66.3	0.0	66.3
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	11069.7	0.0	11069.7
	% Fixture	99.4	0.0	99.4
Total	Lumens	11136.0	0.0	11136.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.3	0.0
10°-20°	16.3	0.1
20°-30°	207.8	1.9
30°-40°	700.5	6.3
40°-50°	2115.5	19.0
50°-60°	3732.4	33.5
60°-70°	3288.2	29.5
70°-80°	1046.7	9.4
80°-90°	25.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	11136.0	100.0
0°-180°	11136.0	100.0



REPORT NUMBER: P1066513


CATALOG NUMBER: NVN-SA4A-730-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	217.5	2.0			
FM	(30°-60°)	6522.7	58.6			
FH	(60°-80°)	4309.0	38.7			G2/5000
FVH	(80°-90°)	20.5	0.2			G1/100
BL	(0°-30°)	9.9	0.1	B0/110		
BM	(30°-60°)	25.7	0.2	B0/220		
BH	(60°-80°)	26.0	0.2	B0/110		G0/110
BVH	(80°-90°)	4.7	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	27.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9	27.9	24.4
5°	34.9	34.9	34.9	31.4	31.4	31.4	27.9	27.9	27.9	27.9	27.9
7.5°	41.9	38.4	38.4	34.9	34.9	34.9	31.4	31.4	31.4	31.4	27.9
10°	48.9	45.4	45.4	41.9	41.9	38.4	38.4	34.9	34.9	31.4	31.4
12.5°	55.9	52.4	48.9	45.4	45.4	41.9	41.9	38.4	38.4	34.9	34.9
15°	62.9	59.4	55.9	52.4	48.9	48.9	45.4	41.9	38.4	38.4	34.9
17.5°	73.3	66.4	62.9	55.9	52.4	48.9	45.4	41.9	41.9	38.4	38.4
20°	76.8	69.8	66.4	59.4	55.9	52.4	48.9	45.4	41.9	41.9	38.4
22.5°	90.8	76.8	73.3	66.4	62.9	59.4	52.4	48.9	45.4	41.9	38.4
25°	111.8	90.8	80.3	69.8	66.4	59.4	55.9	48.9	45.4	41.9	38.4
27.5°	136.2	101.3	90.8	76.8	69.8	62.9	55.9	48.9	45.4	41.9	38.4
30°	167.6	118.7	101.3	83.8	76.8	69.8	59.4	52.4	48.9	45.4	38.4
32.5°	234.0	146.7	118.7	90.8	80.3	73.3	62.9	52.4	48.9	45.4	38.4
35°	282.9	178.1	143.2	104.8	90.8	80.3	66.4	52.4	48.9	45.4	38.4
37.5°	328.3	181.6	146.7	111.8	97.8	83.8	66.4	52.4	48.9	45.4	38.4
40°	401.6	188.6	146.7	104.8	94.3	80.3	69.8	55.9	52.4	45.4	41.9
42.5°	541.3	216.5	157.2	97.8	87.3	80.3	69.8	59.4	52.4	48.9	41.9
45°	901.0	321.3	213.0	101.3	90.8	80.3	69.8	59.4	55.9	48.9	45.4
47.5°	1533.1	558.8	331.8	104.8	94.3	80.3	69.8	55.9	52.4	48.9	41.9
50°	1962.6	715.9	419.1	122.2	104.8	90.8	73.3	55.9	52.4	48.9	45.4
52.5°	2084.9	761.3	454.0	143.2	122.2	101.3	76.8	55.9	52.4	52.4	48.9
55°	1910.2	740.4	454.0	167.6	139.7	115.2	87.3	59.4	55.9	55.9	52.4
57.5°	1623.9	684.5	433.0	181.6	153.7	122.2	94.3	62.9	59.4	59.4	55.9
60°	1337.5	576.2	391.1	202.5	171.1	139.7	108.3	76.8	73.3	69.8	62.9
62.5°	1061.6	464.5	342.2	216.5	185.1	150.2	118.7	83.8	80.3	76.8	73.3
65°	799.7	405.1	317.8	227.0	192.1	157.2	122.2	87.3	83.8	83.8	80.3
67.5°	614.6	370.2	303.8	234.0	199.1	164.1	129.2	94.3	90.8	87.3	83.8
70°	485.4	342.2	286.4	230.5	199.1	167.6	132.7	101.3	94.3	90.8	83.8
72.5°	405.1	310.8	265.4	220.0	195.6	171.1	146.7	122.2	108.3	97.8	83.8
75°	338.7	279.4	241.0	199.1	181.6	167.6	150.2	132.7	115.2	97.8	80.3
77.5°	223.5	202.5	185.1	167.6	157.2	146.7	132.7	122.2	104.8	90.8	73.3
80°	94.3	87.3	90.8	90.8	90.8	90.8	87.3	87.3	76.8	66.4	52.4
82.5°	21.0	17.5	21.0	21.0	21.0	21.0	17.5	17.5	17.5	14.0	14.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4
5°	27.9	27.9	27.9	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4
7.5°	27.9	27.9	27.9	24.4	24.4	24.4	24.4	21.0	21.0	21.0	21.0
10°	27.9	27.9	27.9	24.4	24.4	24.4	24.4	21.0	21.0	21.0	21.0
12.5°	31.4	31.4	27.9	27.9	24.4	24.4	24.4	21.0	21.0	21.0	21.0
15°	31.4	31.4	27.9	27.9	24.4	24.4	24.4	21.0	21.0	21.0	21.0
17.5°	34.9	31.4	31.4	27.9	24.4	24.4	24.4	21.0	21.0	21.0	21.0
20°	34.9	31.4	31.4	27.9	24.4	24.4	24.4	21.0	21.0	21.0	21.0
22.5°	34.9	31.4	31.4	27.9	24.4	24.4	21.0	21.0	17.5	17.5	14.0
25°	34.9	31.4	31.4	27.9	24.4	24.4	21.0	21.0	17.5	14.0	14.0
27.5°	34.9	31.4	31.4	27.9	24.4	21.0	21.0	17.5	14.0	10.5	10.5
30°	34.9	31.4	31.4	27.9	24.4	21.0	17.5	14.0	10.5	10.5	7.0
32.5°	34.9	31.4	27.9	24.4	21.0	17.5	17.5	14.0	10.5	7.0	7.0
35°	34.9	31.4	27.9	24.4	21.0	17.5	17.5	14.0	10.5	7.0	7.0
37.5°	34.9	31.4	27.9	24.4	21.0	17.5	14.0	10.5	7.0	7.0	3.5
40°	34.9	31.4	27.9	24.4	21.0	17.5	14.0	10.5	7.0	7.0	3.5
42.5°	34.9	31.4	27.9	24.4	21.0	17.5	14.0	10.5	7.0	7.0	3.5
45°	38.4	34.9	31.4	24.4	21.0	17.5	17.5	14.0	10.5	7.0	7.0
47.5°	38.4	34.9	31.4	24.4	21.0	17.5	17.5	14.0	10.5	7.0	7.0
50°	41.9	38.4	34.9	27.9	24.4	21.0	17.5	10.5	7.0	7.0	3.5
52.5°	45.4	41.9	38.4	34.9	31.4	24.4	17.5	10.5	3.5	3.5	3.5
55°	48.9	45.4	45.4	41.9	38.4	27.9	21.0	10.5	0.0	0.0	0.0
57.5°	52.4	48.9	48.9	45.4	41.9	31.4	21.0	10.5	0.0	0.0	0.0
60°	59.4	55.9	52.4	45.4	41.9	31.4	21.0	10.5	0.0	0.0	0.0
62.5°	69.8	62.9	52.4	45.4	34.9	27.9	17.5	10.5	0.0	0.0	0.0
65°	76.8	66.4	55.9	41.9	31.4	24.4	17.5	7.0	0.0	0.0	0.0
67.5°	80.3	66.4	55.9	41.9	27.9	21.0	14.0	7.0	0.0	0.0	0.0
70°	76.8	62.9	52.4	38.4	24.4	17.5	14.0	7.0	0.0	0.0	0.0
72.5°	69.8	59.4	45.4	34.9	21.0	17.5	10.5	7.0	0.0	0.0	0.0
75°	62.9	52.4	38.4	27.9	14.0	10.5	7.0	3.5	0.0	0.0	0.0
77.5°	55.9	45.4	31.4	21.0	7.0	7.0	3.5	3.5	0.0	0.0	0.0
80°	41.9	31.4	21.0	10.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	10.5	7.0	7.0	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0
5°	21.0	21.0	21.0	21.0	17.5	17.5	17.5	17.5	17.5	17.5	17.5
7.5°	21.0	21.0	21.0	21.0	17.5	17.5	17.5	17.5	14.0	14.0	14.0
10°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	14.0	14.0	14.0
12.5°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	14.0	14.0	14.0
15°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	14.0	14.0	10.5	10.5
17.5°	17.5	17.5	17.5	17.5	14.0	14.0	14.0	10.5	10.5	7.0	7.0
20°	17.5	17.5	17.5	14.0	14.0	10.5	10.5	7.0	7.0	3.5	3.5
22.5°	14.0	10.5	10.5	7.0	7.0	3.5	3.5	3.5	0.0	0.0	0.0
25°	10.5	7.0	7.0	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	7.0	3.5	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	7.0	3.5	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	21.0	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
5°	17.5	17.5	17.5	17.5	14.0	14.0	14.0	14.0	14.0	14.0	14.0
7.5°	14.0	14.0	14.0	14.0	14.0	14.0	10.5	10.5	10.5	10.5	10.5
10°	14.0	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	7.0	7.0
12.5°	14.0	10.5	10.5	10.5	7.0	7.0	7.0	7.0	7.0	3.5	3.5
15°	10.5	7.0	7.0	7.0	3.5	3.5	3.5	3.5	3.5	0.0	0.0
17.5°	7.0	3.5	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	21.0	21.0
5°	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0
7.5°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
10°	7.0	7.0	7.0	7.0	7.0	7.0	3.5	3.5	3.5	3.5	3.5
12.5°	3.5	3.5	3.5	3.5	3.5	3.5	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	21.0	21.0	21.0	21.0	21.0	24.4	24.4	27.9	27.9	31.4	31.4
5°	14.0	14.0	17.5	17.5	17.5	17.5	21.0	21.0	21.0	24.4	24.4
7.5°	10.5	10.5	10.5	10.5	10.5	14.0	14.0	17.5	17.5	21.0	21.0
10°	3.5	3.5	7.0	7.0	7.0	7.0	10.5	10.5	10.5	14.0	17.5
12.5°	0.0	0.0	3.5	3.5	3.5	3.5	7.0	7.0	7.0	10.5	14.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	7.0	10.5
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	7.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	34.9	34.9	38.4	38.4	41.9	41.9	45.4	45.4	45.4	45.4	45.4
5°	27.9	27.9	31.4	34.9	34.9	38.4	41.9	41.9	41.9	41.9	41.9
7.5°	24.4	24.4	27.9	31.4	31.4	34.9	38.4	38.4	41.9	41.9	41.9
10°	17.5	21.0	24.4	27.9	27.9	31.4	34.9	34.9	38.4	38.4	38.4
12.5°	14.0	17.5	21.0	24.4	24.4	27.9	31.4	31.4	34.9	34.9	38.4
15°	10.5	14.0	17.5	21.0	21.0	24.4	27.9	27.9	31.4	34.9	38.4
17.5°	7.0	10.5	14.0	17.5	17.5	21.0	24.4	27.9	31.4	31.4	34.9
20°	7.0	7.0	10.5	14.0	14.0	17.5	21.0	24.4	27.9	27.9	31.4
22.5°	3.5	3.5	7.0	10.5	10.5	14.0	17.5	21.0	24.4	24.4	27.9
25°	0.0	0.0	3.5	7.0	7.0	10.5	14.0	14.0	17.5	17.5	21.0
27.5°	0.0	0.0	3.5	3.5	7.0	7.0	10.5	10.5	14.0	14.0	17.5
30°	0.0	0.0	3.5	3.5	7.0	7.0	10.5	10.5	14.0	14.0	14.0
32.5°	0.0	0.0	0.0	3.5	3.5	3.5	7.0	7.0	10.5	10.5	14.0
35°	0.0	0.0	0.0	3.5	3.5	3.5	7.0	7.0	10.5	10.5	10.5
37.5°	0.0	0.0	0.0	3.5	3.5	3.5	7.0	7.0	7.0	7.0	10.5
40°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
55°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
75°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	7.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	45.4	45.4
5°	45.4	45.4	45.4	45.4	45.4	45.4	45.4	45.4	45.4	41.9	41.9
7.5°	45.4	45.4	45.4	45.4	45.4	45.4	45.4	45.4	45.4	41.9	41.9
10°	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
12.5°	38.4	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
15°	38.4	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9
17.5°	34.9	38.4	38.4	38.4	41.9	41.9	41.9	41.9	41.9	41.9	41.9
20°	31.4	34.9	34.9	34.9	38.4	38.4	38.4	38.4	41.9	41.9	41.9
22.5°	27.9	31.4	31.4	31.4	34.9	34.9	34.9	34.9	38.4	38.4	38.4
25°	24.4	24.4	27.9	27.9	31.4	31.4	31.4	31.4	31.4	31.4	31.4
27.5°	17.5	21.0	21.0	21.0	24.4	24.4	24.4	24.4	27.9	27.9	27.9
30°	17.5	17.5	17.5	17.5	21.0	21.0	21.0	21.0	24.4	24.4	24.4
32.5°	14.0	17.5	17.5	17.5	21.0	21.0	21.0	21.0	24.4	24.4	24.4
35°	14.0	14.0	14.0	14.0	17.5	17.5	17.5	17.5	21.0	21.0	21.0
37.5°	10.5	14.0	14.0	14.0	17.5	17.5	17.5	17.5	21.0	21.0	21.0
40°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
42.5°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
45°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
47.5°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
50°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
52.5°	7.0	7.0	7.0	7.0	10.5	10.5	10.5	10.5	14.0	14.0	14.0
55°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.5	10.5	10.5
57.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.5	10.5	10.5
60°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
62.5°	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
65°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	3.5	3.5
67.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
70°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
72.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
75°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
77.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
80°	10.5	10.5	10.5	10.5	10.5	7.0	7.0	7.0	7.0	7.0	7.0
82.5°	7.0	10.5	10.5	10.5	10.5	7.0	7.0	7.0	7.0	7.0	7.0
85°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
87.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	45.4	45.4	41.9	41.9	41.9	41.9	41.9	41.9	41.9	45.4	45.4
5°	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	45.4	45.4
7.5°	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	41.9	45.4	45.4
10°	41.9	41.9	41.9	41.9	38.4	38.4	41.9	41.9	41.9	45.4	45.4
12.5°	41.9	41.9	41.9	41.9	38.4	38.4	41.9	41.9	45.4	45.4	48.9
15°	41.9	41.9	38.4	38.4	38.4	38.4	41.9	41.9	45.4	45.4	48.9
17.5°	41.9	41.9	38.4	38.4	38.4	38.4	41.9	41.9	45.4	45.4	48.9
20°	41.9	41.9	38.4	38.4	38.4	38.4	38.4	38.4	41.9	45.4	45.4
22.5°	38.4	38.4	38.4	38.4	34.9	34.9	38.4	38.4	41.9	45.4	45.4
25°	31.4	34.9	34.9	34.9	34.9	34.9	38.4	38.4	41.9	45.4	45.4
27.5°	27.9	31.4	31.4	31.4	31.4	34.9	34.9	38.4	41.9	45.4	45.4
30°	24.4	27.9	27.9	27.9	31.4	34.9	34.9	38.4	41.9	45.4	45.4
32.5°	24.4	27.9	27.9	27.9	31.4	31.4	34.9	34.9	38.4	41.9	45.4
35°	24.4	24.4	27.9	27.9	27.9	31.4	31.4	34.9	38.4	41.9	45.4
37.5°	24.4	24.4	27.9	27.9	27.9	31.4	31.4	34.9	38.4	41.9	45.4
40°	21.0	24.4	24.4	27.9	27.9	31.4	31.4	34.9	38.4	45.4	48.9
42.5°	21.0	21.0	24.4	24.4	27.9	31.4	31.4	34.9	38.4	45.4	48.9
45°	21.0	24.4	24.4	27.9	31.4	34.9	34.9	38.4	41.9	45.4	48.9
47.5°	21.0	24.4	24.4	27.9	34.9	34.9	38.4	38.4	41.9	45.4	48.9
50°	21.0	24.4	24.4	27.9	38.4	38.4	38.4	38.4	41.9	45.4	48.9
52.5°	17.5	21.0	21.0	24.4	31.4	34.9	38.4	41.9	45.4	48.9	52.4
55°	14.0	17.5	17.5	21.0	27.9	31.4	38.4	45.4	48.9	52.4	55.9
57.5°	14.0	14.0	17.5	17.5	24.4	31.4	41.9	48.9	52.4	55.9	59.4
60°	10.5	10.5	14.0	14.0	21.0	27.9	38.4	48.9	52.4	59.4	62.9
62.5°	7.0	10.5	10.5	14.0	17.5	27.9	38.4	48.9	55.9	62.9	66.4
65°	7.0	7.0	10.5	10.5	17.5	24.4	34.9	41.9	52.4	62.9	73.3
67.5°	10.5	10.5	14.0	14.0	17.5	24.4	34.9	41.9	52.4	66.4	76.8
70°	10.5	10.5	14.0	14.0	21.0	27.9	34.9	41.9	52.4	66.4	76.8
72.5°	10.5	10.5	14.0	14.0	21.0	24.4	31.4	38.4	48.9	59.4	69.8
75°	7.0	10.5	10.5	10.5	17.5	21.0	27.9	34.9	45.4	55.9	66.4
77.5°	7.0	7.0	7.0	7.0	14.0	17.5	24.4	27.9	38.4	48.9	59.4
80°	7.0	7.0	7.0	7.0	10.5	14.0	21.0	24.4	34.9	45.4	55.9
82.5°	7.0	7.0	3.5	3.5	7.0	10.5	14.0	17.5	27.9	34.9	45.4
85°	7.0	7.0	3.5	3.5	3.5	7.0	7.0	10.5	14.0	17.5	21.0
87.5°	7.0	7.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	45.4	45.4	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
5°	45.4	48.9	48.9	52.4	52.4	52.4	55.9	55.9	55.9	55.9	55.9
7.5°	45.4	48.9	48.9	52.4	52.4	52.4	55.9	55.9	55.9	59.4	59.4
10°	45.4	48.9	48.9	52.4	52.4	55.9	59.4	59.4	62.9	62.9	62.9
12.5°	48.9	52.4	52.4	55.9	55.9	59.4	62.9	62.9	66.4	69.8	69.8
15°	48.9	52.4	55.9	55.9	59.4	62.9	66.4	66.4	69.8	73.3	76.8
17.5°	48.9	52.4	55.9	55.9	59.4	62.9	69.8	73.3	76.8	83.8	87.3
20°	48.9	52.4	55.9	55.9	59.4	66.4	69.8	76.8	80.3	87.3	94.3
22.5°	48.9	52.4	55.9	59.4	62.9	69.8	76.8	80.3	87.3	97.8	104.8
25°	48.9	52.4	55.9	59.4	62.9	69.8	76.8	83.8	90.8	104.8	118.7
27.5°	48.9	52.4	59.4	62.9	66.4	73.3	83.8	90.8	97.8	122.2	146.7
30°	48.9	52.4	59.4	62.9	66.4	76.8	87.3	94.3	104.8	146.7	185.1
32.5°	48.9	55.9	59.4	66.4	69.8	80.3	94.3	104.8	115.2	174.6	230.5
35°	48.9	55.9	59.4	66.4	69.8	83.8	97.8	111.8	125.7	213.0	300.3
37.5°	48.9	55.9	59.4	66.4	69.8	90.8	111.8	132.7	153.7	244.5	335.3
40°	52.4	59.4	62.9	69.8	73.3	94.3	115.2	136.2	157.2	247.9	338.7
42.5°	52.4	59.4	62.9	69.8	73.3	90.8	111.8	129.2	146.7	247.9	349.2
45°	52.4	59.4	66.4	69.8	76.8	94.3	111.8	125.7	143.2	272.4	398.1
47.5°	52.4	59.4	66.4	69.8	76.8	94.3	111.8	129.2	146.7	359.7	569.2
50°	52.4	59.4	66.4	69.8	76.8	97.8	118.7	139.7	160.6	537.8	915.0
52.5°	55.9	59.4	66.4	69.8	73.3	97.8	122.2	146.7	171.1	698.4	1222.3
55°	59.4	62.9	66.4	69.8	73.3	104.8	136.2	167.6	199.1	750.8	1299.1
57.5°	62.9	66.4	69.8	69.8	73.3	111.8	153.7	192.1	230.5	747.3	1260.7
60°	66.4	69.8	73.3	76.8	80.3	118.7	160.6	199.1	237.5	677.5	1117.5
62.5°	73.3	80.3	87.3	90.8	97.8	136.2	171.1	209.5	244.5	555.3	862.6
65°	83.8	90.8	94.3	101.3	104.8	139.7	178.1	213.0	247.9	461.0	670.5
67.5°	87.3	94.3	97.8	104.8	108.3	143.2	178.1	213.0	247.9	391.1	530.8
70°	87.3	94.3	101.3	104.8	111.8	146.7	178.1	213.0	244.5	338.7	433.0
72.5°	80.3	90.8	97.8	108.3	115.2	146.7	174.6	206.0	234.0	300.3	366.7
75°	76.8	90.8	101.3	115.2	125.7	146.7	171.1	192.1	213.0	261.9	310.8
77.5°	69.8	87.3	104.8	122.2	139.7	153.7	164.1	178.1	188.6	220.0	251.4
80°	66.4	83.8	101.3	118.7	136.2	143.2	146.7	153.7	157.2	160.6	164.1
82.5°	52.4	66.4	80.3	90.8	104.8	97.8	94.3	87.3	80.3	76.8	73.3
85°	24.4	27.9	27.9	31.4	31.4	31.4	27.9	27.9	24.4	21.0	17.5
87.5°	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	48.9	48.9	48.9	48.9	45.4	45.4	45.4	45.4	41.9	41.9	41.9
5°	55.9	55.9	55.9	55.9	52.4	52.4	52.4	52.4	48.9	48.9	48.9
7.5°	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
10°	66.4	66.4	66.4	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8
12.5°	73.3	73.3	76.8	76.8	80.3	80.3	83.8	83.8	87.3	87.3	87.3
15°	80.3	83.8	87.3	90.8	90.8	94.3	97.8	101.3	104.8	108.3	111.8
17.5°	94.3	97.8	104.8	111.8	118.7	125.7	136.2	150.2	160.6	171.1	185.1
20°	104.8	115.2	136.2	160.6	181.6	202.5	254.9	307.3	359.7	412.1	464.5
22.5°	125.7	146.7	216.5	289.9	359.7	429.5	593.7	757.8	918.5	1082.6	1229.3
25°	167.6	213.0	373.7	534.3	691.5	852.1	1145.5	1442.3	1735.6	2029.0	2301.4
27.5°	230.5	314.3	576.2	841.6	1103.5	1365.5	1791.5	2221.1	2647.1	3076.7	3457.3
30°	321.3	457.5	848.6	1243.2	1634.4	2025.5	2563.3	3104.6	3642.4	4180.2	4529.4
32.5°	436.5	639.1	1135.0	1630.9	2126.8	2622.7	3216.3	3810.0	4400.2	4993.9	5364.1
35°	558.8	817.2	1414.4	2015.0	2612.2	3212.8	3838.0	4463.1	5088.2	5713.3	6167.3
37.5°	628.6	921.9	1630.9	2339.8	3045.2	3754.1	4438.6	5126.6	5811.1	6495.5	7047.3
40°	695.0	1047.7	1864.8	2682.0	3499.2	4316.4	5116.1	5915.8	6715.6	7515.3	8224.2
42.5°	792.7	1236.2	2189.6	3143.0	4092.9	5046.3	6097.4	7152.1	8203.2	9254.4	10344.0
45°	995.3	1592.5	2828.7	4065.0	5297.7	6534.0	8025.1	9519.8	11011.0	12505.7	13902.6
47.5°	1484.2	2395.7	4082.4	5769.2	7455.9	9142.7	10860.8	12579.0	14297.2	16015.4	17677.7
50°	2297.9	3677.3	5786.6	7895.9	10001.7	12111.0	13825.7	15540.4	17251.6	18966.3	20618.1
52.5°	3062.7	4903.1	7169.5	9439.5	11705.9	13975.9	15495.0	17014.1	18533.3	20052.4	21651.8
55°	3324.6	5346.6	7641.0	9938.9	12233.3	14531.2	15994.4	17461.1	18924.4	20387.6	22046.4
57.5°	3094.1	4927.5	7239.4	9551.2	11859.6	14171.5	15805.8	17443.7	19078.0	20715.9	22493.4
60°	2591.2	4061.5	6488.6	8919.1	11346.2	13773.3	15617.2	17461.1	19305.0	21148.9	22923.0
62.5°	2053.4	3240.8	5811.1	8381.3	10951.6	13521.9	15397.2	17276.1	19151.4	21026.7	22388.7
65°	1575.0	2479.5	5007.9	7539.7	10068.1	12600.0	14136.5	15676.6	17213.2	18753.3	19696.2
67.5°	1169.9	1809.0	4019.6	6233.6	8444.2	10654.8	11786.3	12921.2	14052.7	15187.7	15921.1
70°	862.6	1288.6	2793.8	4298.9	5800.6	7305.7	8342.9	9380.1	10413.8	11451.0	12212.3
72.5°	597.2	824.2	1725.2	2629.6	3530.6	4431.6	5482.8	6534.0	7581.6	8632.8	9498.9
75°	408.6	506.4	928.9	1351.5	1774.1	2196.6	2992.8	3789.1	4585.3	5381.5	5839.0
77.5°	303.8	356.2	481.9	611.1	736.9	862.6	1016.2	1169.9	1323.6	1477.2	1676.3
80°	167.6	167.6	185.1	199.1	216.5	230.5	272.4	317.8	359.7	405.1	461.0
82.5°	76.8	80.3	87.3	94.3	97.8	104.8	111.8	118.7	125.7	132.7	132.7
85°	21.0	24.4	24.4	21.0	21.0	17.5	17.5	21.0	21.0	21.0	21.0
87.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	41.9	38.4	38.4	38.4	34.9	34.9	34.9	34.9	34.9	34.9	34.9
5°	48.9	48.9	48.9	48.9	45.4	45.4	45.4	45.4	45.4	41.9	41.9
7.5°	59.4	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	52.4	52.4
10°	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	66.4	66.4
12.5°	87.3	87.3	87.3	87.3	90.8	90.8	87.3	87.3	87.3	83.8	83.8
15°	115.2	118.7	122.2	122.2	125.7	125.7	125.7	122.2	122.2	118.7	115.2
17.5°	195.6	206.0	220.0	234.0	247.9	258.4	258.4	251.4	244.5	237.5	230.5
20°	520.3	572.7	628.6	684.5	743.8	785.8	757.8	736.9	715.9	691.5	670.5
22.5°	1379.4	1526.1	1676.3	1781.0	1885.8	1959.1	1899.8	1784.5	1669.3	1557.5	1442.3
25°	2573.8	2842.7	3115.1	3226.8	3342.1	3425.9	3387.5	3212.8	3038.2	2867.1	2692.5
27.5°	3838.0	4215.1	4595.8	4693.6	4791.3	4864.7	4850.7	4623.7	4396.7	4169.7	3942.7
30°	4878.6	5227.9	5577.1	5674.9	5772.7	5839.0	5765.7	5538.7	5311.7	5084.7	4857.7
32.5°	5737.7	6107.9	6481.6	6610.8	6740.0	6827.3	6740.0	6467.6	6195.2	5926.3	5653.9
35°	6621.3	7071.8	7525.8	7689.9	7854.0	7958.8	7812.1	7476.9	7141.6	6809.8	6474.6
37.5°	7599.1	8147.4	8699.1	8922.6	9149.6	9306.8	9195.0	8776.0	8353.4	7934.3	7511.8
40°	8936.6	9645.5	10357.9	10759.6	11157.7	11440.5	11241.5	10756.1	10267.1	9781.7	9292.8
42.5°	11437.0	12526.6	13616.2	14192.4	14765.1	15180.7	14957.2	14360.0	13762.9	13165.7	12568.5
45°	15299.4	16692.8	18089.7	18931.4	19776.5	20398.1	20139.7	19388.8	18634.5	17883.7	17132.9
47.5°	19340.0	21002.3	22664.6	23335.1	24009.1	24532.9	24470.0	23534.1	22598.2	21665.8	20729.9
50°	22273.4	23925.3	25577.1	26153.3	26733.0	27162.5	27001.9	25811.1	24616.7	23425.9	22231.5
52.5°	23251.3	24847.2	26446.6	27134.6	27822.6	28335.9	28140.4	26799.4	25458.3	24120.8	22779.8
55°	23705.2	25364.1	27022.9	27861.0	28702.6	29317.3	29034.4	27564.2	26090.4	24620.2	23146.5
57.5°	24271.0	26048.5	27826.1	28744.5	29663.0	30326.5	29949.3	28426.7	26904.1	25385.0	23862.4
60°	24697.0	26467.6	28241.6	28978.5	29718.9	30235.7	29872.5	28391.8	26907.6	25426.9	23946.2
62.5°	23754.1	25116.1	26478.1	27026.4	27574.6	27972.7	27766.7	26362.8	24959.0	23555.1	22151.2
65°	20642.6	21585.5	22531.9	22902.0	23268.7	23551.6	23488.7	22304.9	21121.0	19940.6	18756.8
67.5°	16657.9	17391.3	18128.2	18652.0	19179.3	19587.9	19542.5	18463.4	17384.3	16305.2	15226.1
70°	12977.1	13738.4	14499.7	15159.8	15823.3	16336.6	16270.3	15268.0	14262.3	13260.0	12254.2
72.5°	10368.4	11234.5	12100.6	12477.7	12854.9	13120.3	12924.7	12166.9	11405.6	10647.8	9886.5
75°	6296.5	6750.5	7208.0	7204.5	7204.5	7162.6	6967.0	6534.0	6100.9	5667.9	5234.8
77.5°	1875.3	2074.4	2273.4	2465.5	2661.1	2807.8	2769.3	2542.3	2311.9	2084.9	1854.4
80°	516.8	569.2	625.1	649.6	674.0	705.4	785.8	729.9	674.0	621.6	565.7
82.5°	132.7	132.7	132.7	129.2	125.7	118.7	108.3	101.3	94.3	87.3	80.3
85°	21.0	17.5	17.5	17.5	14.0	14.0	14.0	14.0	10.5	10.5	7.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4
2.5°	34.9	34.9	31.4	31.4	31.4	31.4	31.4	31.4	31.4	31.4	27.9
5°	41.9	41.9	38.4	38.4	38.4	38.4	38.4	38.4	38.4	38.4	34.9
7.5°	52.4	52.4	48.9	48.9	48.9	48.9	45.4	45.4	45.4	45.4	41.9
10°	66.4	62.9	62.9	59.4	59.4	59.4	55.9	55.9	55.9	52.4	52.4
12.5°	83.8	80.3	80.3	76.8	73.3	73.3	69.8	66.4	62.9	62.9	59.4
15°	111.8	108.3	104.8	101.3	97.8	90.8	87.3	80.3	76.8	73.3	69.8
17.5°	213.0	195.6	178.1	160.6	146.7	132.7	118.7	104.8	97.8	90.8	83.8
20°	593.7	513.4	436.5	359.7	310.8	261.9	213.0	164.1	143.2	125.7	104.8
22.5°	1285.1	1124.5	967.3	806.7	677.5	551.8	422.6	293.3	244.5	199.1	150.2
25°	2388.7	2081.4	1777.5	1470.2	1225.8	981.3	736.9	492.4	401.6	310.8	220.0
27.5°	3544.6	3146.5	2748.4	2350.3	1962.6	1571.5	1180.4	792.7	635.6	481.9	324.8
30°	4435.1	4012.6	3593.5	3170.9	2682.0	2193.1	1700.7	1211.8	963.9	715.9	464.5
32.5°	5199.9	4742.4	4288.5	3831.0	3265.2	2699.5	2133.8	1568.0	1257.2	946.4	632.1
35°	5957.7	5437.4	4920.5	4400.2	3792.6	3184.9	2577.3	1969.6	1575.0	1180.4	782.3
37.5°	6879.7	6244.1	5612.0	4979.9	4354.8	3733.2	3108.1	2483.0	1980.1	1480.7	977.8
40°	8486.1	7675.9	6869.2	6059.0	5329.1	4602.8	3872.9	3143.0	2510.9	1878.8	1243.2
42.5°	11552.3	10536.1	9523.3	8507.1	7497.8	6488.6	5475.8	4466.6	3565.6	2668.1	1767.1
45°	15830.3	14527.7	13228.6	11926.0	10682.7	9443.0	8199.8	6956.5	5587.6	4218.6	2846.2
47.5°	19305.0	17876.7	16451.9	15023.6	13644.1	12268.2	10888.8	9509.3	7756.2	6006.6	4253.5
50°	20873.0	19511.1	18152.6	16790.6	15407.7	14021.3	12634.9	11252.0	9240.4	7232.4	5220.9
52.5°	21400.4	20017.4	18638.0	17255.1	15882.7	14510.2	13137.8	11765.3	9673.5	7585.1	5493.3
55°	21690.2	20230.5	18774.2	17314.5	15837.3	14356.5	12875.8	11398.6	9317.3	7239.4	5158.0
57.5°	22276.9	20688.0	19102.5	17513.5	15830.3	14147.0	12460.3	10777.0	8723.6	6670.2	4616.7
60°	22385.2	20820.7	19259.6	17698.6	15837.3	13975.9	12111.0	10249.7	8210.2	6174.3	4134.8
62.5°	20845.1	19539.0	18236.4	16930.3	15065.5	13200.6	11332.3	9467.4	7515.3	5563.1	3607.5
65°	17628.8	16500.8	15376.3	14248.3	12725.7	11206.6	9683.9	8161.3	6418.7	4679.6	2937.0
67.5°	14122.6	13019.0	11919.0	10815.4	9670.0	8528.0	7382.6	6237.1	4892.6	3548.1	2203.6
70°	11196.1	10134.4	9076.3	8014.7	7001.9	5985.7	4969.4	3956.7	3122.1	2290.9	1456.3
72.5°	8873.8	7857.5	6844.8	5828.5	4910.1	3991.6	3073.2	2154.7	1739.1	1327.0	911.5
75°	4707.5	4180.2	3656.4	3129.0	2612.2	2091.8	1571.5	1054.7	890.5	726.4	558.8
77.5°	1623.9	1393.4	1166.4	935.9	778.8	621.6	464.5	307.3	289.9	275.9	258.4
80°	492.4	419.1	345.7	272.4	241.0	209.5	178.1	146.7	136.2	125.7	111.8
82.5°	76.8	69.8	66.4	59.4	55.9	55.9	52.4	48.9	41.9	38.4	31.4
85°	7.0	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066513
 CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	31.4	31.4
2.5°	27.9	27.9
5°	34.9	34.9
7.5°	41.9	41.9
10°	48.9	48.9
12.5°	55.9	55.9
15°	66.4	62.9
17.5°	76.8	73.3
20°	83.8	76.8
22.5°	101.3	87.3
25°	129.2	108.3
27.5°	167.6	132.7
30°	216.5	167.6
32.5°	321.3	234.0
35°	387.6	282.9
37.5°	474.9	328.3
40°	611.1	398.1
42.5°	866.1	541.3
45°	1477.2	897.5
47.5°	2503.9	1529.6
50°	3209.4	1962.6
52.5°	3404.9	2081.4
55°	3080.1	1910.2
57.5°	2563.3	1623.9
60°	2098.8	1337.5
62.5°	1655.3	1058.1
65°	1194.3	799.7
67.5°	859.1	614.6
70°	625.1	481.9
72.5°	495.9	401.6
75°	394.6	335.3
77.5°	244.5	223.5
80°	101.3	94.3
82.5°	24.4	21.0
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066513

CATALOG NUMBER: NVN-SA4A-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-4

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-730-U-5WQ

Data in this report applies to families of products including GSS-SB1A-730-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-4
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-730-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 3000K CCT 26 LEDS

Spectral Parameters

CCT (K): 2985
 CIE u' : 0.2504
 CIE v' : 0.5243
 Duv: 0.0019
 CIE x: 0.4408
 CIE y: 0.4101
 CIE z: 0.1491
 Peak Wavelength (nm): 595
 Dominant Wavelength (nm): 582
 Purity: 55.41818
 R_f: 73.8
 R_g: 94.4

CRI (Ra): 70.8
 R1: 66.3
 R2: 80.6
 R3: 94.5
 R4: 68.2
 R5: 66.5
 R6: 74.7
 R7: 76.2
 R8: 39.6
 R9: -43.2
 R10: 57.6
 R11: 64.8
 R12: 53.5
 R13: 68.7
 R14: 97.0
 R15: 56.4



Test Conditions


Stabilization Time: 36M
 Operation Time: 1H 36M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-4


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-4

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-4

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.19

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.13


λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4





TM-30-18

Summary

$R_f = 73.8$
 $R_g = 94.4$
 $CIE\ R_a = 70.8$
 $R_g = -43.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 63	CES51 = 86	CES76 = 61
CES02 = 62	CES27 = 83	CES52 = 86	CES77 = 81
CES03 = 31	CES28 = 86	CES53 = 75	CES78 = 64
CES04 = 71	CES29 = 58	CES54 = 81	CES79 = 86
CES05 = 49	CES30 = 61	CES55 = 80	CES80 = 86
CES06 = 51	CES31 = 63	CES56 = 71	CES81 = 70
CES07 = 41	CES32 = 61	CES57 = 69	CES82 = 94
CES08 = 40	CES33 = 65	CES58 = 72	CES83 = 88
CES09 = 29	CES34 = 77	CES59 = 85	CES84 = 90
CES10 = 76	CES35 = 88	CES60 = 93	CES85 = 80
CES11 = 59	CES36 = 89	CES61 = 86	CES86 = 60
CES12 = 65	CES37 = 85	CES62 = 81	CES87 = 78
CES13 = 43	CES38 = 69	CES63 = 73	CES88 = 75
CES14 = 74	CES39 = 93	CES64 = 72	CES89 = 66
CES15 = 71	CES40 = 89	CES65 = 67	CES90 = 72
CES16 = 47	CES41 = 83	CES66 = 70	CES91 = 95
CES17 = 50	CES42 = 87	CES67 = 68	CES92 = 59
CES18 = 56	CES43 = 77	CES68 = 73	CES93 = 76
CES19 = 73	CES44 = 99	CES69 = 83	CES94 = 48
CES20 = 66	CES45 = 83	CES70 = 66	CES95 = 70
CES21 = 87	CES46 = 77	CES71 = 66	CES96 = 76
CES22 = 79	CES47 = 74	CES72 = 88	CES97 = 82
CES23 = 92	CES48 = 62	CES73 = 59	CES98 = 73
CES24 = 91	CES49 = 77	CES74 = 93	CES99 = 60
CES25 = 73	CES50 = 85	CES75 = 67	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)