

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066514

Luminaire Tested: **NVN-SA4B-730-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066514
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA4B-730-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 4xLight Square PACKAGE
70CRI 3000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 3000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 13854 lumens
Efficiency: N/A
Efficacy: 96.1 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 144.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.7 fc
 Type III - Short - N/A

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	82.4	0.0	82.4
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	13771.6	0.0	13771.6
	% Fixture	99.4	0.0	99.4
Total	Lumens	13854.0	0.0	13854.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.1	0.0
10°-20°	20.3	0.1
20°-30°	258.6	1.9
30°-40°	871.5	6.3
40°-50°	2631.8	19.0
50°-60°	4643.4	33.5
60°-70°	4090.8	29.5
70°-80°	1302.2	9.4
80°-90°	31.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	13854.0	100.0
0°-180°	13854.0	100.0



REPORT NUMBER: P1066514


CATALOG NUMBER: NVN-SA4B-730-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	270.6	2.0			
FM	(30°-60°)	8114.8	58.6			
FH	(60°-80°)	5360.7	38.7			G3/7500
FVH	(80°-90°)	25.5	0.2			G1/100
BL	(0°-30°)	12.4	0.1	B0/110		
BM	(30°-60°)	31.9	0.2	B0/220		
BH	(60°-80°)	32.3	0.2	B0/110		G0/110
BVH	(80°-90°)	5.8	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	30.4
5°	43.4	43.4	43.4	39.1	39.1	39.1	34.8	34.8	34.8	34.8	34.8
7.5°	52.1	47.8	47.8	43.4	43.4	43.4	39.1	39.1	39.1	39.1	34.8
10°	60.8	56.5	56.5	52.1	52.1	47.8	47.8	43.4	43.4	39.1	39.1
12.5°	69.5	65.2	60.8	56.5	56.5	52.1	52.1	47.8	47.8	43.4	43.4
15°	78.2	73.9	69.5	65.2	60.8	60.8	56.5	52.1	47.8	47.8	43.4
17.5°	91.2	82.5	78.2	69.5	65.2	60.8	56.5	52.1	52.1	47.8	47.8
20°	95.6	86.9	82.5	73.9	69.5	65.2	60.8	56.5	52.1	52.1	47.8
22.5°	113.0	95.6	91.2	82.5	78.2	73.9	65.2	60.8	56.5	52.1	47.8
25°	139.0	113.0	99.9	86.9	82.5	73.9	69.5	60.8	56.5	52.1	47.8
27.5°	169.4	126.0	113.0	95.6	86.9	78.2	69.5	60.8	56.5	52.1	47.8
30°	208.5	147.7	126.0	104.3	95.6	86.9	73.9	65.2	60.8	56.5	47.8
32.5°	291.1	182.5	147.7	113.0	99.9	91.2	78.2	65.2	60.8	56.5	47.8
35°	351.9	221.6	178.1	130.3	113.0	99.9	82.5	65.2	60.8	56.5	47.8
37.5°	408.4	225.9	182.5	139.0	121.6	104.3	82.5	65.2	60.8	56.5	47.8
40°	499.6	234.6	182.5	130.3	117.3	99.9	86.9	69.5	65.2	56.5	52.1
42.5°	673.4	269.4	195.5	121.6	108.6	99.9	86.9	73.9	65.2	60.8	52.1
45°	1120.9	399.7	265.0	126.0	113.0	99.9	86.9	73.9	69.5	60.8	56.5
47.5°	1907.3	695.1	412.7	130.3	117.3	99.9	86.9	69.5	65.2	60.8	52.1
50°	2441.7	890.6	521.4	152.1	130.3	113.0	91.2	69.5	65.2	60.8	56.5
52.5°	2593.7	947.1	564.8	178.1	152.1	126.0	95.6	69.5	65.2	65.2	60.8
55°	2376.5	921.1	564.8	208.5	173.8	143.4	108.6	73.9	69.5	69.5	65.2
57.5°	2020.2	851.5	538.7	225.9	191.2	152.1	117.3	78.2	73.9	73.9	69.5
60°	1664.0	716.9	486.6	252.0	212.9	173.8	134.7	95.6	91.2	86.9	78.2
62.5°	1320.8	577.8	425.8	269.4	230.3	186.8	147.7	104.3	99.9	95.6	91.2
65°	994.9	504.0	395.4	282.4	239.0	195.5	152.1	108.6	104.3	104.3	99.9
67.5°	764.7	460.5	378.0	291.1	247.6	204.2	160.8	117.3	113.0	108.6	104.3
70°	603.9	425.8	356.3	286.7	247.6	208.5	165.1	126.0	117.3	113.0	104.3
72.5°	504.0	386.7	330.2	273.7	243.3	212.9	182.5	152.1	134.7	121.6	104.3
75°	421.4	347.6	299.8	247.6	225.9	208.5	186.8	165.1	143.4	121.6	99.9
77.5°	278.1	252.0	230.3	208.5	195.5	182.5	165.1	152.1	130.3	113.0	91.2
80°	117.3	108.6	113.0	113.0	113.0	113.0	108.6	108.6	95.6	82.5	65.2
82.5°	26.1	21.7	26.1	26.1	26.1	26.1	21.7	21.7	21.7	17.4	17.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
5°	34.8	34.8	34.8	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
7.5°	34.8	34.8	34.8	30.4	30.4	30.4	30.4	26.1	26.1	26.1	26.1
10°	34.8	34.8	34.8	30.4	30.4	30.4	30.4	26.1	26.1	26.1	26.1
12.5°	39.1	39.1	34.8	34.8	30.4	30.4	30.4	26.1	26.1	26.1	26.1
15°	39.1	39.1	34.8	34.8	30.4	30.4	30.4	26.1	26.1	26.1	26.1
17.5°	43.4	39.1	39.1	34.8	30.4	30.4	30.4	26.1	26.1	26.1	26.1
20°	43.4	39.1	39.1	34.8	30.4	30.4	30.4	26.1	26.1	26.1	26.1
22.5°	43.4	39.1	39.1	34.8	30.4	30.4	26.1	26.1	21.7	21.7	17.4
25°	43.4	39.1	39.1	34.8	30.4	30.4	26.1	26.1	21.7	17.4	17.4
27.5°	43.4	39.1	39.1	34.8	30.4	26.1	26.1	21.7	17.4	13.0	13.0
30°	43.4	39.1	39.1	34.8	30.4	26.1	21.7	17.4	13.0	13.0	8.7
32.5°	43.4	39.1	34.8	30.4	26.1	21.7	21.7	17.4	13.0	8.7	8.7
35°	43.4	39.1	34.8	30.4	26.1	21.7	21.7	17.4	13.0	8.7	8.7
37.5°	43.4	39.1	34.8	30.4	26.1	21.7	17.4	13.0	8.7	8.7	4.3
40°	43.4	39.1	34.8	30.4	26.1	21.7	17.4	13.0	8.7	8.7	4.3
42.5°	43.4	39.1	34.8	30.4	26.1	21.7	17.4	13.0	8.7	8.7	4.3
45°	47.8	43.4	39.1	30.4	26.1	21.7	21.7	17.4	13.0	8.7	8.7
47.5°	47.8	43.4	39.1	30.4	26.1	21.7	21.7	17.4	13.0	8.7	8.7
50°	52.1	47.8	43.4	34.8	30.4	26.1	21.7	13.0	8.7	8.7	4.3
52.5°	56.5	52.1	47.8	43.4	39.1	30.4	21.7	13.0	4.3	4.3	4.3
55°	60.8	56.5	56.5	52.1	47.8	34.8	26.1	13.0	0.0	0.0	0.0
57.5°	65.2	60.8	60.8	56.5	52.1	39.1	26.1	13.0	0.0	0.0	0.0
60°	73.9	69.5	65.2	56.5	52.1	39.1	26.1	13.0	0.0	0.0	0.0
62.5°	86.9	78.2	65.2	56.5	43.4	34.8	21.7	13.0	0.0	0.0	0.0
65°	95.6	82.5	69.5	52.1	39.1	30.4	21.7	8.7	0.0	0.0	0.0
67.5°	99.9	82.5	69.5	52.1	34.8	26.1	17.4	8.7	0.0	0.0	0.0
70°	95.6	78.2	65.2	47.8	30.4	21.7	17.4	8.7	0.0	0.0	0.0
72.5°	86.9	73.9	56.5	43.4	26.1	21.7	13.0	8.7	0.0	0.0	0.0
75°	78.2	65.2	47.8	34.8	17.4	13.0	8.7	4.3	0.0	0.0	0.0
77.5°	69.5	56.5	39.1	26.1	8.7	8.7	4.3	4.3	0.0	0.0	0.0
80°	52.1	39.1	26.1	13.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	13.0	8.7	8.7	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
5°	26.1	26.1	26.1	26.1	21.7	21.7	21.7	21.7	21.7	21.7	21.7
7.5°	26.1	26.1	26.1	26.1	21.7	21.7	21.7	21.7	17.4	17.4	17.4
10°	21.7	21.7	21.7	21.7	21.7	21.7	21.7	21.7	17.4	17.4	17.4
12.5°	21.7	21.7	21.7	21.7	21.7	21.7	21.7	21.7	17.4	17.4	17.4
15°	21.7	21.7	21.7	21.7	21.7	21.7	21.7	17.4	17.4	13.0	13.0
17.5°	21.7	21.7	21.7	21.7	17.4	17.4	17.4	13.0	13.0	8.7	8.7
20°	21.7	21.7	21.7	17.4	17.4	13.0	13.0	8.7	8.7	4.3	4.3
22.5°	17.4	13.0	13.0	8.7	8.7	4.3	4.3	4.3	0.0	0.0	0.0
25°	13.0	8.7	8.7	4.3	4.3	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.7	4.3	4.3	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.7	4.3	4.3	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	26.1	21.7	21.7	21.7	21.7	21.7	21.7	21.7	21.7	21.7	21.7
5°	21.7	21.7	21.7	21.7	17.4	17.4	17.4	17.4	17.4	17.4	17.4
7.5°	17.4	17.4	17.4	17.4	17.4	17.4	13.0	13.0	13.0	13.0	13.0
10°	17.4	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	8.7	8.7
12.5°	17.4	13.0	13.0	13.0	8.7	8.7	8.7	8.7	8.7	4.3	4.3
15°	13.0	8.7	8.7	8.7	4.3	4.3	4.3	4.3	4.3	0.0	0.0
17.5°	8.7	4.3	4.3	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	21.7	21.7	21.7	21.7	21.7	21.7	21.7	21.7	21.7	26.1	26.1
5°	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4
7.5°	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
10°	8.7	8.7	8.7	8.7	8.7	8.7	4.3	4.3	4.3	4.3	4.3
12.5°	4.3	4.3	4.3	4.3	4.3	4.3	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	26.1	26.1	26.1	26.1	26.1	30.4	30.4	34.8	34.8	39.1	39.1
5°	17.4	17.4	21.7	21.7	21.7	21.7	26.1	26.1	26.1	30.4	30.4
7.5°	13.0	13.0	13.0	13.0	13.0	17.4	17.4	21.7	21.7	26.1	26.1
10°	4.3	4.3	8.7	8.7	8.7	8.7	13.0	13.0	13.0	17.4	21.7
12.5°	0.0	0.0	4.3	4.3	4.3	4.3	8.7	8.7	8.7	13.0	17.4
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3	8.7	13.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	8.7
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	43.4	43.4	47.8	47.8	52.1	52.1	56.5	56.5	56.5	56.5	56.5
5°	34.8	34.8	39.1	43.4	43.4	47.8	52.1	52.1	52.1	52.1	52.1
7.5°	30.4	30.4	34.8	39.1	39.1	43.4	47.8	47.8	52.1	52.1	52.1
10°	21.7	26.1	30.4	34.8	34.8	39.1	43.4	43.4	47.8	47.8	47.8
12.5°	17.4	21.7	26.1	30.4	30.4	34.8	39.1	39.1	43.4	43.4	47.8
15°	13.0	17.4	21.7	26.1	26.1	30.4	34.8	34.8	39.1	43.4	47.8
17.5°	8.7	13.0	17.4	21.7	21.7	26.1	30.4	34.8	39.1	39.1	43.4
20°	8.7	8.7	13.0	17.4	17.4	21.7	26.1	30.4	34.8	34.8	39.1
22.5°	4.3	4.3	8.7	13.0	13.0	17.4	21.7	26.1	30.4	30.4	34.8
25°	0.0	0.0	4.3	8.7	8.7	13.0	17.4	17.4	21.7	21.7	26.1
27.5°	0.0	0.0	4.3	4.3	8.7	8.7	13.0	13.0	17.4	17.4	21.7
30°	0.0	0.0	4.3	4.3	8.7	8.7	13.0	13.0	17.4	17.4	17.4
32.5°	0.0	0.0	0.0	4.3	4.3	4.3	8.7	8.7	13.0	13.0	17.4
35°	0.0	0.0	0.0	4.3	4.3	4.3	8.7	8.7	13.0	13.0	13.0
37.5°	0.0	0.0	0.0	4.3	4.3	4.3	8.7	8.7	8.7	8.7	13.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	8.7	8.7	8.7
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	8.7	8.7	8.7
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	8.7	8.7	8.7
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	8.7	8.7	8.7
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	8.7	8.7	8.7
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3	4.3	4.3
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3	4.3	4.3
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3	4.3	4.3
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	8.7	8.7	8.7
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	8.7	8.7	8.7
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3	4.3	8.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3	4.3	4.3
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.3	4.3	4.3	4.3	4.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	60.8	60.8	60.8	60.8	60.8	60.8	60.8	60.8	60.8	56.5	56.5
5°	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	52.1	52.1
7.5°	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	52.1	52.1
10°	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1
12.5°	47.8	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1
15°	47.8	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1
17.5°	43.4	47.8	47.8	47.8	52.1	52.1	52.1	52.1	52.1	52.1	52.1
20°	39.1	43.4	43.4	43.4	47.8	47.8	47.8	47.8	52.1	52.1	52.1
22.5°	34.8	39.1	39.1	39.1	43.4	43.4	43.4	43.4	47.8	47.8	47.8
25°	30.4	30.4	34.8	34.8	39.1	39.1	39.1	39.1	39.1	39.1	39.1
27.5°	21.7	26.1	26.1	26.1	30.4	30.4	30.4	30.4	34.8	34.8	34.8
30°	21.7	21.7	21.7	21.7	26.1	26.1	26.1	26.1	30.4	30.4	30.4
32.5°	17.4	21.7	21.7	21.7	26.1	26.1	26.1	26.1	30.4	30.4	30.4
35°	17.4	17.4	17.4	17.4	21.7	21.7	21.7	21.7	26.1	26.1	26.1
37.5°	13.0	17.4	17.4	17.4	21.7	21.7	21.7	21.7	26.1	26.1	26.1
40°	13.0	13.0	13.0	13.0	17.4	17.4	17.4	17.4	21.7	21.7	21.7
42.5°	13.0	13.0	13.0	13.0	17.4	17.4	17.4	17.4	21.7	21.7	21.7
45°	13.0	13.0	13.0	13.0	17.4	17.4	17.4	17.4	21.7	21.7	21.7
47.5°	13.0	13.0	13.0	13.0	17.4	17.4	17.4	17.4	21.7	21.7	21.7
50°	13.0	13.0	13.0	13.0	17.4	17.4	17.4	17.4	21.7	21.7	21.7
52.5°	8.7	8.7	8.7	8.7	13.0	13.0	13.0	13.0	17.4	17.4	17.4
55°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	13.0	13.0	13.0
57.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	13.0	13.0	13.0
60°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
62.5°	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
65°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	4.3	4.3
67.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
70°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
72.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
75°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
77.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
80°	13.0	13.0	13.0	13.0	13.0	8.7	8.7	8.7	8.7	8.7	8.7
82.5°	8.7	13.0	13.0	13.0	13.0	8.7	8.7	8.7	8.7	8.7	8.7
85°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
87.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	56.5	56.5	52.1	52.1	52.1	52.1	52.1	52.1	52.1	56.5	56.5
5°	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	56.5	56.5
7.5°	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	56.5	56.5
10°	52.1	52.1	52.1	52.1	47.8	47.8	52.1	52.1	52.1	56.5	56.5
12.5°	52.1	52.1	52.1	52.1	47.8	47.8	52.1	52.1	56.5	56.5	60.8
15°	52.1	52.1	47.8	47.8	47.8	47.8	52.1	52.1	56.5	56.5	60.8
17.5°	52.1	52.1	47.8	47.8	47.8	47.8	52.1	52.1	56.5	56.5	60.8
20°	52.1	52.1	47.8	47.8	47.8	47.8	47.8	47.8	52.1	56.5	56.5
22.5°	47.8	47.8	47.8	47.8	43.4	43.4	47.8	47.8	52.1	56.5	56.5
25°	39.1	43.4	43.4	43.4	43.4	43.4	47.8	47.8	52.1	56.5	56.5
27.5°	34.8	39.1	39.1	39.1	39.1	43.4	43.4	47.8	52.1	56.5	56.5
30°	30.4	34.8	34.8	34.8	39.1	43.4	43.4	47.8	52.1	56.5	56.5
32.5°	30.4	34.8	34.8	34.8	39.1	39.1	43.4	43.4	47.8	52.1	56.5
35°	30.4	30.4	34.8	34.8	34.8	39.1	39.1	43.4	47.8	52.1	56.5
37.5°	30.4	30.4	34.8	34.8	34.8	39.1	39.1	43.4	47.8	52.1	56.5
40°	26.1	30.4	30.4	34.8	34.8	39.1	39.1	43.4	47.8	56.5	60.8
42.5°	26.1	26.1	30.4	30.4	34.8	39.1	39.1	43.4	47.8	56.5	60.8
45°	26.1	30.4	30.4	34.8	39.1	43.4	43.4	47.8	52.1	56.5	60.8
47.5°	26.1	30.4	30.4	34.8	43.4	43.4	47.8	47.8	52.1	56.5	60.8
50°	26.1	30.4	30.4	34.8	47.8	47.8	47.8	47.8	52.1	56.5	60.8
52.5°	21.7	26.1	26.1	30.4	39.1	43.4	47.8	52.1	56.5	60.8	65.2
55°	17.4	21.7	21.7	26.1	34.8	39.1	47.8	56.5	60.8	65.2	69.5
57.5°	17.4	17.4	21.7	21.7	30.4	39.1	52.1	60.8	65.2	69.5	73.9
60°	13.0	13.0	17.4	17.4	26.1	34.8	47.8	60.8	65.2	73.9	78.2
62.5°	8.7	13.0	13.0	17.4	21.7	34.8	47.8	60.8	69.5	78.2	82.5
65°	8.7	8.7	13.0	13.0	21.7	30.4	43.4	52.1	65.2	78.2	91.2
67.5°	13.0	13.0	17.4	17.4	21.7	30.4	43.4	52.1	65.2	82.5	95.6
70°	13.0	13.0	17.4	17.4	26.1	34.8	43.4	52.1	65.2	82.5	95.6
72.5°	13.0	13.0	17.4	17.4	26.1	30.4	39.1	47.8	60.8	73.9	86.9
75°	8.7	13.0	13.0	13.0	21.7	26.1	34.8	43.4	56.5	69.5	82.5
77.5°	8.7	8.7	8.7	8.7	17.4	21.7	30.4	34.8	47.8	60.8	73.9
80°	8.7	8.7	8.7	8.7	13.0	17.4	26.1	30.4	43.4	56.5	69.5
82.5°	8.7	8.7	4.3	4.3	8.7	13.0	17.4	21.7	34.8	43.4	56.5
85°	8.7	8.7	4.3	4.3	4.3	8.7	8.7	13.0	17.4	21.7	26.1
87.5°	8.7	8.7	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	56.5	56.5	60.8	60.8	60.8	60.8	60.8	60.8	60.8	60.8	60.8
5°	56.5	60.8	60.8	65.2	65.2	65.2	69.5	69.5	69.5	69.5	69.5
7.5°	56.5	60.8	60.8	65.2	65.2	65.2	69.5	69.5	69.5	73.9	73.9
10°	56.5	60.8	60.8	65.2	65.2	69.5	73.9	73.9	78.2	78.2	78.2
12.5°	60.8	65.2	65.2	69.5	69.5	73.9	78.2	78.2	82.5	86.9	86.9
15°	60.8	65.2	69.5	69.5	73.9	78.2	82.5	82.5	86.9	91.2	95.6
17.5°	60.8	65.2	69.5	69.5	73.9	78.2	86.9	91.2	95.6	104.3	108.6
20°	60.8	65.2	69.5	69.5	73.9	82.5	86.9	95.6	99.9	108.6	117.3
22.5°	60.8	65.2	69.5	73.9	78.2	86.9	95.6	99.9	108.6	121.6	130.3
25°	60.8	65.2	69.5	73.9	78.2	86.9	95.6	104.3	113.0	130.3	147.7
27.5°	60.8	65.2	73.9	78.2	82.5	91.2	104.3	113.0	121.6	152.1	182.5
30°	60.8	65.2	73.9	78.2	82.5	95.6	108.6	117.3	130.3	182.5	230.3
32.5°	60.8	69.5	73.9	82.5	86.9	99.9	117.3	130.3	143.4	217.2	286.7
35°	60.8	69.5	73.9	82.5	86.9	104.3	121.6	139.0	156.4	265.0	373.6
37.5°	60.8	69.5	73.9	82.5	86.9	113.0	139.0	165.1	191.2	304.1	417.1
40°	65.2	73.9	78.2	86.9	91.2	117.3	143.4	169.4	195.5	308.5	421.4
42.5°	65.2	73.9	78.2	86.9	91.2	113.0	139.0	160.8	182.5	308.5	434.5
45°	65.2	73.9	82.5	86.9	95.6	117.3	139.0	156.4	178.1	338.9	495.3
47.5°	65.2	73.9	82.5	86.9	95.6	117.3	139.0	160.8	182.5	447.5	708.2
50°	65.2	73.9	82.5	86.9	95.6	121.6	147.7	173.8	199.9	669.1	1138.3
52.5°	69.5	73.9	82.5	86.9	91.2	121.6	152.1	182.5	212.9	868.9	1520.6
55°	73.9	78.2	82.5	86.9	91.2	130.3	169.4	208.5	247.6	934.1	1616.2
57.5°	78.2	82.5	86.9	86.9	91.2	139.0	191.2	239.0	286.7	929.7	1568.4
60°	82.5	86.9	91.2	95.6	99.9	147.7	199.9	247.6	295.4	842.9	1390.3
62.5°	91.2	99.9	108.6	113.0	121.6	169.4	212.9	260.7	304.1	690.8	1073.1
65°	104.3	113.0	117.3	126.0	130.3	173.8	221.6	265.0	308.5	573.5	834.2
67.5°	108.6	117.3	121.6	130.3	134.7	178.1	221.6	265.0	308.5	486.6	660.4
70°	108.6	117.3	126.0	130.3	139.0	182.5	221.6	265.0	304.1	421.4	538.7
72.5°	99.9	113.0	121.6	134.7	143.4	182.5	217.2	256.3	291.1	373.6	456.2
75°	95.6	113.0	126.0	143.4	156.4	182.5	212.9	239.0	265.0	325.8	386.7
77.5°	86.9	108.6	130.3	152.1	173.8	191.2	204.2	221.6	234.6	273.7	312.8
80°	82.5	104.3	126.0	147.7	169.4	178.1	182.5	191.2	195.5	199.9	204.2
82.5°	65.2	82.5	99.9	113.0	130.3	121.6	117.3	108.6	99.9	95.6	91.2
85°	30.4	34.8	34.8	39.1	39.1	39.1	34.8	34.8	30.4	26.1	21.7
87.5°	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	60.8	60.8	60.8	60.8	56.5	56.5	56.5	56.5	52.1	52.1	52.1
5°	69.5	69.5	69.5	69.5	65.2	65.2	65.2	65.2	60.8	60.8	60.8
7.5°	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
10°	82.5	82.5	82.5	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9
12.5°	91.2	91.2	95.6	95.6	99.9	99.9	104.3	104.3	108.6	108.6	108.6
15°	99.9	104.3	108.6	113.0	113.0	117.3	121.6	126.0	130.3	134.7	139.0
17.5°	117.3	121.6	130.3	139.0	147.7	156.4	169.4	186.8	199.9	212.9	230.3
20°	130.3	143.4	169.4	199.9	225.9	252.0	317.2	382.3	447.5	512.7	577.8
22.5°	156.4	182.5	269.4	360.6	447.5	534.4	738.6	942.8	1142.6	1346.8	1529.3
25°	208.5	265.0	464.9	664.7	860.2	1060.1	1425.0	1794.3	2159.3	2524.2	2863.1
27.5°	286.7	391.0	716.9	1047.1	1372.9	1698.7	2228.8	2763.2	3293.2	3827.6	4301.2
30°	399.7	569.1	1055.7	1546.7	2033.3	2519.9	3188.9	3862.4	4531.4	5200.5	5635.0
32.5°	543.1	795.1	1412.0	2028.9	2645.9	3262.8	4001.4	4740.0	5474.2	6212.8	6673.3
35°	695.1	1016.6	1759.6	2506.8	3249.8	3997.0	4774.7	5552.4	6330.1	7107.8	7672.6
37.5°	782.0	1147.0	2028.9	2910.9	3788.5	4670.5	5522.0	6377.9	7229.4	8081.0	8767.4
40°	864.6	1303.4	2320.0	3336.7	4353.3	5369.9	6364.9	7359.8	8354.7	9349.6	10231.6
42.5°	986.2	1538.0	2724.1	3910.2	5091.9	6278.0	7585.7	8897.8	10205.5	11513.2	12868.7
45°	1238.2	1981.1	3519.1	5057.1	6590.8	8128.8	9983.9	11843.4	13698.6	15558.1	17295.9
47.5°	1846.5	2980.4	5078.9	7177.3	9275.7	11374.2	13511.7	15649.3	17786.8	19924.4	21992.4
50°	2858.8	4574.9	7199.0	9823.2	12443.0	15067.1	17200.3	19333.5	21462.4	23595.6	25650.6
52.5°	3810.2	6099.8	8919.5	11743.5	14563.1	17387.1	19277.0	21167.0	23056.9	24946.8	26936.6
55°	4136.1	6651.6	9506.0	12364.8	15219.2	18077.9	19898.3	21723.1	23543.5	25363.9	27427.5
57.5°	3849.3	6130.2	9006.4	11882.5	14754.3	17630.4	19663.7	21701.3	23734.6	25772.2	27983.7
60°	3223.7	5052.8	8072.3	11096.1	14115.6	17135.2	19429.1	21723.1	24017.0	26311.0	28518.0
62.5°	2554.6	4031.8	7229.4	10427.1	13624.7	16822.3	19155.4	21492.8	23825.9	26158.9	27853.3
65°	1959.4	3084.7	6230.2	9380.0	12525.5	15675.4	17587.0	19503.0	21414.6	23330.6	24503.6
67.5°	1455.4	2250.5	5000.6	7755.1	10505.3	13255.4	14663.1	16075.1	17482.7	18894.7	19807.1
70°	1073.1	1603.2	3475.7	5348.2	7216.4	9088.9	10379.3	11669.6	12955.6	14246.0	15193.1
72.5°	742.9	1025.3	2146.2	3271.5	4392.4	5513.3	6821.0	8128.8	9432.2	10739.9	11817.3
75°	508.3	630.0	1155.7	1681.4	2207.1	2732.8	3723.3	4713.9	5704.5	6695.0	7264.2
77.5°	378.0	443.2	599.6	760.3	916.7	1073.1	1264.3	1455.4	1646.6	1837.8	2085.4
80°	208.5	208.5	230.3	247.6	269.4	286.7	338.9	395.4	447.5	504.0	573.5
82.5°	95.6	99.9	108.6	117.3	121.6	130.3	139.0	147.7	156.4	165.1	165.1
85°	26.1	30.4	30.4	26.1	26.1	21.7	21.7	26.1	26.1	26.1	26.1
87.5°	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	52.1	47.8	47.8	47.8	43.4	43.4	43.4	43.4	43.4	43.4	43.4
5°	60.8	60.8	60.8	60.8	56.5	56.5	56.5	56.5	56.5	52.1	52.1
7.5°	73.9	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	65.2	65.2
10°	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	82.5	82.5
12.5°	108.6	108.6	108.6	108.6	113.0	113.0	108.6	108.6	108.6	104.3	104.3
15°	143.4	147.7	152.1	152.1	156.4	156.4	156.4	152.1	152.1	147.7	143.4
17.5°	243.3	256.3	273.7	291.1	308.5	321.5	321.5	312.8	304.1	295.4	286.7
20°	647.3	712.5	782.0	851.5	925.4	977.5	942.8	916.7	890.6	860.2	834.2
22.5°	1716.1	1898.6	2085.4	2215.8	2346.1	2437.3	2363.5	2220.1	2076.7	1937.7	1794.3
25°	3202.0	3536.5	3875.4	4014.4	4157.8	4262.1	4214.3	3997.0	3779.8	3566.9	3349.7
27.5°	4774.7	5243.9	5717.5	5839.2	5960.8	6052.0	6034.7	5752.3	5469.9	5187.5	4905.1
30°	6069.4	6503.9	6938.3	7060.0	7181.6	7264.2	7173.0	6890.6	6608.2	6325.8	6043.4
32.5°	7138.2	7598.7	8063.6	8224.4	8385.1	8493.7	8385.1	8046.2	7707.3	7372.8	7033.9
35°	8237.4	8797.8	9362.6	9566.8	9771.0	9901.4	9718.9	9301.8	8884.7	8472.0	8054.9
37.5°	9453.9	10136.0	10822.4	11100.5	11382.9	11578.4	11439.4	10918.0	10392.3	9871.0	9345.3
40°	11117.9	11999.8	12886.1	13385.8	13881.0	14233.0	13985.3	13381.4	12773.2	12169.3	11561.0
42.5°	14228.6	15584.1	16939.6	17656.5	18369.0	18886.0	18608.0	17865.0	17122.1	16379.2	15636.3
45°	19033.7	20767.3	22505.1	23552.1	24603.5	25376.9	25055.4	24121.3	23182.9	22248.8	21314.7
47.5°	24060.5	26128.5	28196.5	29030.7	29869.2	30520.9	30442.7	29278.3	28114.0	26954.0	25789.6
50°	27709.9	29764.9	31819.9	32536.8	33258.0	33792.4	33592.5	32111.0	30625.2	29143.7	27657.8
52.5°	28926.4	30911.9	32901.8	33757.6	34613.5	35252.2	35008.9	33340.6	31672.2	30008.2	28339.9
55°	29491.2	31554.9	33618.6	34661.3	35708.4	36473.0	36121.1	34292.0	32458.6	30629.5	28796.1
57.5°	30195.1	32406.5	34617.9	35760.5	36903.1	37728.6	37259.4	35365.1	33470.9	31581.0	29686.7
60°	30725.1	32927.8	35134.9	36051.6	36972.7	37615.7	37163.8	35321.7	33475.2	31633.1	29791.0
62.5°	29552.1	31246.5	32940.9	33623.0	34305.1	34800.4	34544.0	32797.5	31050.9	29304.4	27557.9
65°	25681.0	26854.1	28031.4	28492.0	28948.2	29300.1	29221.9	27749.0	26276.2	24807.7	23334.9
67.5°	20723.8	21636.2	22552.9	23204.6	23860.6	24368.9	24312.5	22970.0	21627.5	20285.0	18942.5
70°	16144.6	17091.7	18038.8	18860.0	19685.4	20324.1	20241.6	18994.6	17743.4	16496.5	15245.2
72.5°	12899.2	13976.6	15054.1	15523.3	15992.5	16322.7	16079.4	15136.6	14189.5	13246.7	12299.6
75°	7833.3	8398.1	8967.3	8962.9	8962.9	8910.8	8667.5	8128.8	7590.0	7051.3	6512.6
77.5°	2333.1	2580.7	2828.3	3067.3	3310.6	3493.1	3445.3	3162.9	2876.1	2593.7	2307.0
80°	643.0	708.2	777.7	808.1	838.5	877.6	977.5	908.0	838.5	773.3	703.8
82.5°	165.1	165.1	165.1	160.8	156.4	147.7	134.7	126.0	117.3	108.6	99.9
85°	26.1	21.7	21.7	21.7	17.4	17.4	17.4	17.4	13.0	13.0	8.7
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
2.5°	43.4	43.4	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	34.8
5°	52.1	52.1	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	43.4
7.5°	65.2	65.2	60.8	60.8	60.8	60.8	56.5	56.5	56.5	56.5	52.1
10°	82.5	78.2	78.2	73.9	73.9	73.9	69.5	69.5	69.5	65.2	65.2
12.5°	104.3	99.9	99.9	95.6	91.2	91.2	86.9	82.5	78.2	78.2	73.9
15°	139.0	134.7	130.3	126.0	121.6	113.0	108.6	99.9	95.6	91.2	86.9
17.5°	265.0	243.3	221.6	199.9	182.5	165.1	147.7	130.3	121.6	113.0	104.3
20°	738.6	638.7	543.1	447.5	386.7	325.8	265.0	204.2	178.1	156.4	130.3
22.5°	1598.8	1399.0	1203.5	1003.6	842.9	686.4	525.7	364.9	304.1	247.6	186.8
25°	2971.7	2589.4	2211.4	1829.1	1525.0	1220.8	916.7	612.6	499.6	386.7	273.7
27.5°	4409.8	3914.5	3419.2	2923.9	2441.7	1955.1	1468.5	986.2	790.7	599.6	404.0
30°	5517.7	4992.0	4470.6	3944.9	3336.7	2728.4	2115.8	1507.6	1199.1	890.6	577.8
32.5°	6469.1	5900.0	5335.2	4766.0	4062.2	3358.4	2654.6	1950.7	1564.1	1177.4	786.4
35°	7411.9	6764.6	6121.6	5474.2	4718.2	3962.3	3206.3	2450.4	1959.4	1468.5	973.2
37.5°	8558.9	7768.2	6981.8	6195.4	5417.7	4644.4	3866.7	3089.0	2463.4	1842.1	1216.5
40°	10557.4	9549.5	8545.9	7537.9	6629.9	5726.2	4818.2	3910.2	3123.8	2337.4	1546.7
42.5°	14372.0	13107.7	11847.8	10583.5	9327.9	8072.3	6812.4	5556.8	4435.8	3319.3	2198.4
45°	19694.1	18073.6	16457.4	14836.9	13290.2	11747.8	10201.2	8654.5	6951.4	5248.3	3540.9
47.5°	24017.0	22240.1	20467.5	18690.5	16974.4	15262.6	13546.5	11830.4	9649.4	7472.7	5291.7
50°	25967.8	24273.4	22583.3	20888.9	19168.4	17443.6	15718.8	13998.3	11495.8	8997.7	6495.2
52.5°	26623.8	24903.3	23187.2	21466.7	19759.3	18051.9	16344.4	14637.0	12034.6	9436.5	6834.1
55°	26984.4	25168.3	23356.6	21540.6	19702.8	17860.7	16018.6	14180.8	11591.4	9006.4	6417.0
57.5°	27714.3	25737.5	23765.0	21788.2	19694.1	17600.0	15501.6	13407.5	10852.8	8298.2	5743.6
60°	27849.0	25902.6	23960.5	22018.5	19702.8	17387.1	15067.1	12751.4	10214.2	7681.3	5144.0
62.5°	25933.0	24308.1	22687.6	21062.7	18742.7	16422.6	14098.3	11778.2	9349.6	6921.0	4488.0
65°	21931.6	20528.3	19129.3	17726.0	15831.8	13941.9	12047.6	10153.4	7985.4	5821.8	3653.8
67.5°	17569.6	16196.7	14828.2	13455.3	12030.2	10609.5	9184.5	7759.5	6086.8	4414.1	2741.5
70°	13928.8	12608.1	11291.6	9970.9	8710.9	7446.7	6182.4	4922.4	3884.1	2850.1	1811.7
72.5°	11039.7	9775.4	8515.4	7251.2	6108.5	4965.9	3823.3	2680.6	2163.6	1651.0	1133.9
75°	5856.5	5200.5	4548.8	3892.8	3249.8	2602.4	1955.1	1312.1	1107.9	903.7	695.1
77.5°	2020.2	1733.5	1451.1	1164.4	968.8	773.3	577.8	382.3	360.6	343.2	321.5
80°	612.6	521.4	430.1	338.9	299.8	260.7	221.6	182.5	169.4	156.4	139.0
82.5°	95.6	86.9	82.5	73.9	69.5	69.5	65.2	60.8	52.1	47.8	39.1
85°	8.7	4.3	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	39.1	39.1
2.5°	34.8	34.8
5°	43.4	43.4
7.5°	52.1	52.1
10°	60.8	60.8
12.5°	69.5	69.5
15°	82.5	78.2
17.5°	95.6	91.2
20°	104.3	95.6
22.5°	126.0	108.6
25°	160.8	134.7
27.5°	208.5	165.1
30°	269.4	208.5
32.5°	399.7	291.1
35°	482.3	351.9
37.5°	590.9	408.4
40°	760.3	495.3
42.5°	1077.5	673.4
45°	1837.8	1116.6
47.5°	3115.1	1902.9
50°	3992.7	2441.7
52.5°	4236.0	2589.4
55°	3831.9	2376.5
57.5°	3188.9	2020.2
60°	2611.1	1664.0
62.5°	2059.3	1316.4
65°	1485.9	994.9
67.5°	1068.8	764.7
70°	777.7	599.6
72.5°	616.9	499.6
75°	490.9	417.1
77.5°	304.1	278.1
80°	126.0	117.3
82.5°	30.4	26.1
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066514

CATALOG NUMBER: NVN-SA4B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-4

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-730-U-5WQ


Data in this report applies to families of products including GSS-SB1A-730-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-4
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-730-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 3000K CCT 26 LEDS

Spectral Parameters

CCT (K):	2985	CRI (Ra):	70.8		
CIE u':	0.2504	R1:	66.3	R9:	-43.2
CIE v':	0.5243	R2:	80.6	R10:	57.6
Duv:	0.0019	R3:	94.5	R11:	64.8
CIE x:	0.4408	R4:	68.2	R12:	53.5
CIE y:	0.4101	R5:	66.5	R13:	68.7
CIE z:	0.1491	R6:	74.7	R14:	97.0
Peak Wavelength (nm):	595	R7:	76.2	R15:	56.4
Dominant Wavelength (nm):	582	R8:	39.6		
Purity:	55.41818				
Rf:	73.8				
Rg:	94.4				



Test Conditions


Stabilization Time: 36M
 Operation Time: 1H 36M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-4


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-4

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-4

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.19

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.13


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4





TM-30-18

Summary

$R_f = 73.8$
 $R_g = 94.4$
 $CIE R_a = 70.8$
 $R_g = -43.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 63	CES51 = 86	CES76 = 61
CES02 = 62	CES27 = 83	CES52 = 86	CES77 = 81
CES03 = 31	CES28 = 86	CES53 = 75	CES78 = 64
CES04 = 71	CES29 = 58	CES54 = 81	CES79 = 86
CES05 = 49	CES30 = 61	CES55 = 80	CES80 = 86
CES06 = 51	CES31 = 63	CES56 = 71	CES81 = 70
CES07 = 41	CES32 = 61	CES57 = 69	CES82 = 94
CES08 = 40	CES33 = 65	CES58 = 72	CES83 = 88
CES09 = 29	CES34 = 77	CES59 = 85	CES84 = 90
CES10 = 76	CES35 = 88	CES60 = 93	CES85 = 80
CES11 = 59	CES36 = 89	CES61 = 86	CES86 = 60
CES12 = 65	CES37 = 85	CES62 = 81	CES87 = 78
CES13 = 43	CES38 = 69	CES63 = 73	CES88 = 75
CES14 = 74	CES39 = 93	CES64 = 72	CES89 = 66
CES15 = 71	CES40 = 89	CES65 = 67	CES90 = 72
CES16 = 47	CES41 = 83	CES66 = 70	CES91 = 95
CES17 = 50	CES42 = 87	CES67 = 68	CES92 = 59
CES18 = 56	CES43 = 77	CES68 = 73	CES93 = 76
CES19 = 73	CES44 = 99	CES69 = 83	CES94 = 48
CES20 = 66	CES45 = 83	CES70 = 66	CES95 = 70
CES21 = 87	CES46 = 77	CES71 = 66	CES96 = 76
CES22 = 79	CES47 = 74	CES72 = 88	CES97 = 82
CES23 = 92	CES48 = 62	CES73 = 59	CES98 = 73
CES24 = 91	CES49 = 77	CES74 = 93	CES99 = 60
CES25 = 73	CES50 = 85	CES75 = 67	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)