

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066518

Luminaire Tested: **NVN-SA5B-730-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066518
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5B-730-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 5xLight Square PACKAGE
70CRI 3000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 3000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 17467.9 lumens
Efficiency: N/A
Efficacy: 97.7 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 178.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3.4 fc
 Type III - Short - N/A

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	103.9	0.0	103.9
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	17363.9	0.0	17363.9
	% Fixture	99.4	0.0	99.4
Total	Lumens	17467.8	0.0	17467.8
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	5.2	0.0
10°-20°	25.6	0.1
20°-30°	326.0	1.9
30°-40°	1098.8	6.3
40°-50°	3318.3	19.0
50°-60°	5854.6	33.5
60°-70°	5157.9	29.5
70°-80°	1641.9	9.4
80°-90°	39.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	17467.8	100.0
0°-180°	17467.9	100.0



REPORT NUMBER: P1066518


CATALOG NUMBER: NVN-SA5B-730-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	341.2	2.0			
FM	(30°-60°)	10231.5	58.6			
FH	(60°-80°)	6759.1	38.7			G3/7500
FVH	(80°-90°)	32.2	0.2			G1/100
BL	(0°-30°)	15.6	0.1	B0/110		
BM	(30°-60°)	40.3	0.2	B0/220		
BH	(60°-80°)	40.7	0.2	B0/110		G0/110
BVH	(80°-90°)	7.4	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8	38.3
5°	54.8	54.8	54.8	49.3	49.3	49.3	43.8	43.8	43.8	43.8	43.8
7.5°	65.7	60.3	60.3	54.8	54.8	54.8	49.3	49.3	49.3	49.3	43.8
10°	76.7	71.2	71.2	65.7	65.7	60.3	60.3	54.8	54.8	49.3	49.3
12.5°	87.6	82.2	76.7	71.2	71.2	65.7	65.7	60.3	60.3	54.8	54.8
15°	98.6	93.1	87.6	82.2	76.7	76.7	71.2	65.7	60.3	60.3	54.8
17.5°	115.0	104.1	98.6	87.6	82.2	76.7	71.2	65.7	65.7	60.3	60.3
20°	120.5	109.6	104.1	93.1	87.6	82.2	76.7	71.2	65.7	65.7	60.3
22.5°	142.4	120.5	115.0	104.1	98.6	93.1	82.2	76.7	71.2	65.7	60.3
25°	175.3	142.4	126.0	109.6	104.1	93.1	87.6	76.7	71.2	65.7	60.3
27.5°	213.6	158.9	142.4	120.5	109.6	98.6	87.6	76.7	71.2	65.7	60.3
30°	262.9	186.2	158.9	131.5	120.5	109.6	93.1	82.2	76.7	71.2	60.3
32.5°	367.0	230.1	186.2	142.4	126.0	115.0	98.6	82.2	76.7	71.2	60.3
35°	443.7	279.4	224.6	164.3	142.4	126.0	104.1	82.2	76.7	71.2	60.3
37.5°	514.9	284.9	230.1	175.3	153.4	131.5	104.1	82.2	76.7	71.2	60.3
40°	630.0	295.8	230.1	164.3	147.9	126.0	109.6	87.6	82.2	71.2	65.7
42.5°	849.1	339.6	246.5	153.4	136.9	126.0	109.6	93.1	82.2	76.7	65.7
45°	1413.3	504.0	334.2	158.9	142.4	126.0	109.6	93.1	87.6	76.7	71.2
47.5°	2404.8	876.5	520.4	164.3	147.9	126.0	109.6	87.6	82.2	76.7	65.7
50°	3078.6	1123.0	657.3	191.7	164.3	142.4	115.0	87.6	82.2	76.7	71.2
52.5°	3270.3	1194.2	712.1	224.6	191.7	158.9	120.5	87.6	82.2	82.2	76.7
55°	2996.4	1161.3	712.1	262.9	219.1	180.8	136.9	93.1	87.6	87.6	82.2
57.5°	2547.2	1073.7	679.3	284.9	241.0	191.7	147.9	98.6	93.1	93.1	87.6
60°	2098.0	903.9	613.5	317.7	268.4	219.1	169.8	120.5	115.0	109.6	98.6
62.5°	1665.3	728.6	536.8	339.6	290.3	235.5	186.2	131.5	126.0	120.5	115.0
65°	1254.4	635.4	498.5	356.1	301.3	246.5	191.7	136.9	131.5	131.5	126.0
67.5°	964.1	580.7	476.6	367.0	312.2	257.5	202.7	147.9	142.4	136.9	131.5
70°	761.4	536.8	449.2	361.5	312.2	262.9	208.2	158.9	147.9	142.4	131.5
72.5°	635.4	487.5	416.3	345.1	306.8	268.4	230.1	191.7	169.8	153.4	131.5
75°	531.4	438.2	378.0	312.2	284.9	262.9	235.5	208.2	180.8	153.4	126.0
77.5°	350.6	317.7	290.3	262.9	246.5	230.1	208.2	191.7	164.3	142.4	115.0
80°	147.9	136.9	142.4	142.4	142.4	142.4	136.9	136.9	120.5	104.1	82.2
82.5°	32.9	27.4	32.9	32.9	32.9	32.9	27.4	27.4	27.4	21.9	21.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3
5°	43.8	43.8	43.8	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3
7.5°	43.8	43.8	43.8	38.3	38.3	38.3	38.3	32.9	32.9	32.9	32.9
10°	43.8	43.8	43.8	38.3	38.3	38.3	38.3	32.9	32.9	32.9	32.9
12.5°	49.3	49.3	43.8	43.8	38.3	38.3	38.3	32.9	32.9	32.9	32.9
15°	49.3	49.3	43.8	43.8	38.3	38.3	38.3	32.9	32.9	32.9	32.9
17.5°	54.8	49.3	49.3	43.8	38.3	38.3	38.3	32.9	32.9	32.9	32.9
20°	54.8	49.3	49.3	43.8	38.3	38.3	38.3	32.9	32.9	32.9	32.9
22.5°	54.8	49.3	49.3	43.8	38.3	38.3	32.9	32.9	27.4	27.4	21.9
25°	54.8	49.3	49.3	43.8	38.3	38.3	32.9	32.9	27.4	21.9	21.9
27.5°	54.8	49.3	49.3	43.8	38.3	32.9	32.9	27.4	21.9	16.4	16.4
30°	54.8	49.3	49.3	43.8	38.3	32.9	27.4	21.9	16.4	16.4	11.0
32.5°	54.8	49.3	43.8	38.3	32.9	27.4	27.4	21.9	16.4	11.0	11.0
35°	54.8	49.3	43.8	38.3	32.9	27.4	27.4	21.9	16.4	11.0	11.0
37.5°	54.8	49.3	43.8	38.3	32.9	27.4	21.9	16.4	11.0	11.0	5.5
40°	54.8	49.3	43.8	38.3	32.9	27.4	21.9	16.4	11.0	11.0	5.5
42.5°	54.8	49.3	43.8	38.3	32.9	27.4	21.9	16.4	11.0	11.0	5.5
45°	60.3	54.8	49.3	38.3	32.9	27.4	27.4	21.9	16.4	11.0	11.0
47.5°	60.3	54.8	49.3	38.3	32.9	27.4	27.4	21.9	16.4	11.0	11.0
50°	65.7	60.3	54.8	43.8	38.3	32.9	27.4	16.4	11.0	11.0	5.5
52.5°	71.2	65.7	60.3	54.8	49.3	38.3	27.4	16.4	5.5	5.5	5.5
55°	76.7	71.2	71.2	65.7	60.3	43.8	32.9	16.4	0.0	0.0	0.0
57.5°	82.2	76.7	76.7	71.2	65.7	49.3	32.9	16.4	0.0	0.0	0.0
60°	93.1	87.6	82.2	71.2	65.7	49.3	32.9	16.4	0.0	0.0	0.0
62.5°	109.6	98.6	82.2	71.2	54.8	43.8	27.4	16.4	0.0	0.0	0.0
65°	120.5	104.1	87.6	65.7	49.3	38.3	27.4	11.0	0.0	0.0	0.0
67.5°	126.0	104.1	87.6	65.7	43.8	32.9	21.9	11.0	0.0	0.0	0.0
70°	120.5	98.6	82.2	60.3	38.3	27.4	21.9	11.0	0.0	0.0	0.0
72.5°	109.6	93.1	71.2	54.8	32.9	27.4	16.4	11.0	0.0	0.0	0.0
75°	98.6	82.2	60.3	43.8	21.9	16.4	11.0	5.5	0.0	0.0	0.0
77.5°	87.6	71.2	49.3	32.9	11.0	11.0	5.5	5.5	0.0	0.0	0.0
80°	65.7	49.3	32.9	16.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	16.4	11.0	11.0	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9	32.9
5°	32.9	32.9	32.9	32.9	27.4	27.4	27.4	27.4	27.4	27.4	27.4
7.5°	32.9	32.9	32.9	32.9	27.4	27.4	27.4	27.4	21.9	21.9	21.9
10°	27.4	27.4	27.4	27.4	27.4	27.4	27.4	27.4	21.9	21.9	21.9
12.5°	27.4	27.4	27.4	27.4	27.4	27.4	27.4	27.4	21.9	21.9	21.9
15°	27.4	27.4	27.4	27.4	27.4	27.4	27.4	21.9	21.9	16.4	16.4
17.5°	27.4	27.4	27.4	27.4	21.9	21.9	21.9	16.4	16.4	11.0	11.0
20°	27.4	27.4	27.4	21.9	21.9	16.4	16.4	11.0	11.0	5.5	5.5
22.5°	21.9	16.4	16.4	11.0	11.0	5.5	5.5	5.5	0.0	0.0	0.0
25°	16.4	11.0	11.0	5.5	5.5	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	11.0	5.5	5.5	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	11.0	5.5	5.5	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	32.9	27.4	27.4	27.4	27.4	27.4	27.4	27.4	27.4	27.4	27.4
5°	27.4	27.4	27.4	27.4	21.9	21.9	21.9	21.9	21.9	21.9	21.9
7.5°	21.9	21.9	21.9	21.9	21.9	21.9	16.4	16.4	16.4	16.4	16.4
10°	21.9	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4	11.0	11.0
12.5°	21.9	16.4	16.4	16.4	11.0	11.0	11.0	11.0	11.0	5.5	5.5
15°	16.4	11.0	11.0	11.0	5.5	5.5	5.5	5.5	5.5	0.0	0.0
17.5°	11.0	5.5	5.5	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	27.4	27.4	27.4	27.4	27.4	27.4	27.4	27.4	27.4	32.9	32.9
5°	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9
7.5°	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4	16.4
10°	11.0	11.0	11.0	11.0	11.0	11.0	5.5	5.5	5.5	5.5	5.5
12.5°	5.5	5.5	5.5	5.5	5.5	5.5	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	32.9	32.9	32.9	32.9	32.9	38.3	38.3	43.8	43.8	49.3	49.3
5°	21.9	21.9	27.4	27.4	27.4	27.4	32.9	32.9	32.9	38.3	38.3
7.5°	16.4	16.4	16.4	16.4	16.4	21.9	21.9	27.4	27.4	32.9	32.9
10°	5.5	5.5	11.0	11.0	11.0	11.0	16.4	16.4	16.4	21.9	27.4
12.5°	0.0	0.0	5.5	5.5	5.5	5.5	11.0	11.0	11.0	16.4	21.9
15°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5	11.0	16.4
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5	11.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	54.8	54.8	60.3	60.3	65.7	65.7	71.2	71.2	71.2	71.2	71.2
5°	43.8	43.8	49.3	54.8	54.8	60.3	65.7	65.7	65.7	65.7	65.7
7.5°	38.3	38.3	43.8	49.3	49.3	54.8	60.3	60.3	65.7	65.7	65.7
10°	27.4	32.9	38.3	43.8	43.8	49.3	54.8	54.8	60.3	60.3	60.3
12.5°	21.9	27.4	32.9	38.3	38.3	43.8	49.3	49.3	54.8	54.8	60.3
15°	16.4	21.9	27.4	32.9	32.9	38.3	43.8	43.8	49.3	54.8	60.3
17.5°	11.0	16.4	21.9	27.4	27.4	32.9	38.3	43.8	49.3	49.3	54.8
20°	11.0	11.0	16.4	21.9	21.9	27.4	32.9	38.3	43.8	43.8	49.3
22.5°	5.5	5.5	11.0	16.4	16.4	21.9	27.4	32.9	38.3	38.3	43.8
25°	0.0	0.0	5.5	11.0	11.0	16.4	21.9	21.9	27.4	27.4	32.9
27.5°	0.0	0.0	5.5	5.5	11.0	11.0	16.4	16.4	21.9	21.9	27.4
30°	0.0	0.0	5.5	5.5	11.0	11.0	16.4	16.4	21.9	21.9	21.9
32.5°	0.0	0.0	0.0	5.5	5.5	5.5	11.0	11.0	16.4	16.4	21.9
35°	0.0	0.0	0.0	5.5	5.5	5.5	11.0	11.0	16.4	16.4	16.4
37.5°	0.0	0.0	0.0	5.5	5.5	5.5	11.0	11.0	11.0	11.0	16.4
40°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	11.0	11.0	11.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	11.0	11.0	11.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	11.0	11.0	11.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	11.0	11.0	11.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	11.0	11.0	11.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5	5.5	5.5
55°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5	5.5	5.5
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5	5.5	5.5
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5
75°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5	5.5	5.5
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	11.0	11.0	11.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	11.0	11.0	11.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5	5.5	11.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5	5.5	5.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.5	5.5	5.5	5.5	5.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7	71.2	71.2
5°	71.2	71.2	71.2	71.2	71.2	71.2	71.2	71.2	71.2	65.7	65.7
7.5°	71.2	71.2	71.2	71.2	71.2	71.2	71.2	71.2	71.2	65.7	65.7
10°	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7
12.5°	60.3	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7
15°	60.3	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7
17.5°	54.8	60.3	60.3	60.3	65.7	65.7	65.7	65.7	65.7	65.7	65.7
20°	49.3	54.8	54.8	54.8	60.3	60.3	60.3	60.3	65.7	65.7	65.7
22.5°	43.8	49.3	49.3	49.3	54.8	54.8	54.8	54.8	60.3	60.3	60.3
25°	38.3	38.3	43.8	43.8	49.3	49.3	49.3	49.3	49.3	49.3	49.3
27.5°	27.4	32.9	32.9	32.9	38.3	38.3	38.3	38.3	43.8	43.8	43.8
30°	27.4	27.4	27.4	27.4	32.9	32.9	32.9	32.9	38.3	38.3	38.3
32.5°	21.9	27.4	27.4	27.4	32.9	32.9	32.9	32.9	38.3	38.3	38.3
35°	21.9	21.9	21.9	21.9	27.4	27.4	27.4	27.4	32.9	32.9	32.9
37.5°	16.4	21.9	21.9	21.9	27.4	27.4	27.4	27.4	32.9	32.9	32.9
40°	16.4	16.4	16.4	16.4	21.9	21.9	21.9	21.9	27.4	27.4	27.4
42.5°	16.4	16.4	16.4	16.4	21.9	21.9	21.9	21.9	27.4	27.4	27.4
45°	16.4	16.4	16.4	16.4	21.9	21.9	21.9	21.9	27.4	27.4	27.4
47.5°	16.4	16.4	16.4	16.4	21.9	21.9	21.9	21.9	27.4	27.4	27.4
50°	16.4	16.4	16.4	16.4	21.9	21.9	21.9	21.9	27.4	27.4	27.4
52.5°	11.0	11.0	11.0	11.0	16.4	16.4	16.4	16.4	21.9	21.9	21.9
55°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	16.4	16.4	16.4
57.5°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	16.4	16.4	16.4
60°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
62.5°	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5
65°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	5.5	5.5
67.5°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
70°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
72.5°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
75°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
77.5°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
80°	16.4	16.4	16.4	16.4	16.4	11.0	11.0	11.0	11.0	11.0	11.0
82.5°	11.0	16.4	16.4	16.4	16.4	11.0	11.0	11.0	11.0	11.0	11.0
85°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
87.5°	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	71.2	71.2	65.7	65.7	65.7	65.7	65.7	65.7	65.7	71.2	71.2
5°	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	71.2	71.2
7.5°	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	71.2	71.2
10°	65.7	65.7	65.7	65.7	60.3	60.3	65.7	65.7	65.7	71.2	71.2
12.5°	65.7	65.7	65.7	65.7	60.3	60.3	65.7	65.7	71.2	71.2	76.7
15°	65.7	65.7	60.3	60.3	60.3	60.3	65.7	65.7	71.2	71.2	76.7
17.5°	65.7	65.7	60.3	60.3	60.3	60.3	65.7	65.7	71.2	71.2	76.7
20°	65.7	65.7	60.3	60.3	60.3	60.3	60.3	60.3	65.7	71.2	71.2
22.5°	60.3	60.3	60.3	60.3	54.8	54.8	60.3	60.3	65.7	71.2	71.2
25°	49.3	54.8	54.8	54.8	54.8	54.8	60.3	60.3	65.7	71.2	71.2
27.5°	43.8	49.3	49.3	49.3	49.3	54.8	54.8	60.3	65.7	71.2	71.2
30°	38.3	43.8	43.8	43.8	49.3	54.8	54.8	60.3	65.7	71.2	71.2
32.5°	38.3	43.8	43.8	43.8	49.3	49.3	54.8	54.8	60.3	65.7	71.2
35°	38.3	38.3	43.8	43.8	43.8	49.3	49.3	54.8	60.3	65.7	71.2
37.5°	38.3	38.3	43.8	43.8	43.8	49.3	49.3	54.8	60.3	65.7	71.2
40°	32.9	38.3	38.3	43.8	43.8	49.3	49.3	54.8	60.3	71.2	76.7
42.5°	32.9	32.9	38.3	38.3	43.8	49.3	49.3	54.8	60.3	71.2	76.7
45°	32.9	38.3	38.3	43.8	49.3	54.8	54.8	60.3	65.7	71.2	76.7
47.5°	32.9	38.3	38.3	43.8	54.8	54.8	60.3	60.3	65.7	71.2	76.7
50°	32.9	38.3	38.3	43.8	60.3	60.3	60.3	60.3	65.7	71.2	76.7
52.5°	27.4	32.9	32.9	38.3	49.3	54.8	60.3	65.7	71.2	76.7	82.2
55°	21.9	27.4	27.4	32.9	43.8	49.3	60.3	71.2	76.7	82.2	87.6
57.5°	21.9	21.9	27.4	27.4	38.3	49.3	65.7	76.7	82.2	87.6	93.1
60°	16.4	16.4	21.9	21.9	32.9	43.8	60.3	76.7	82.2	93.1	98.6
62.5°	11.0	16.4	16.4	21.9	27.4	43.8	60.3	76.7	87.6	98.6	104.1
65°	11.0	11.0	16.4	16.4	27.4	38.3	54.8	65.7	82.2	98.6	115.0
67.5°	16.4	16.4	21.9	21.9	27.4	38.3	54.8	65.7	82.2	104.1	120.5
70°	16.4	16.4	21.9	21.9	32.9	43.8	54.8	65.7	82.2	104.1	120.5
72.5°	16.4	16.4	21.9	21.9	32.9	38.3	49.3	60.3	76.7	93.1	109.6
75°	11.0	16.4	16.4	16.4	27.4	32.9	43.8	54.8	71.2	87.6	104.1
77.5°	11.0	11.0	11.0	11.0	21.9	27.4	38.3	43.8	60.3	76.7	93.1
80°	11.0	11.0	11.0	11.0	16.4	21.9	32.9	38.3	54.8	71.2	87.6
82.5°	11.0	11.0	5.5	5.5	11.0	16.4	21.9	27.4	43.8	54.8	71.2
85°	11.0	11.0	5.5	5.5	5.5	11.0	11.0	16.4	21.9	27.4	32.9
87.5°	11.0	11.0	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	71.2	71.2	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7
5°	71.2	76.7	76.7	82.2	82.2	82.2	87.6	87.6	87.6	87.6	87.6
7.5°	71.2	76.7	76.7	82.2	82.2	82.2	87.6	87.6	87.6	93.1	93.1
10°	71.2	76.7	76.7	82.2	82.2	87.6	93.1	93.1	98.6	98.6	98.6
12.5°	76.7	82.2	82.2	87.6	87.6	93.1	98.6	98.6	104.1	109.6	109.6
15°	76.7	82.2	87.6	87.6	93.1	98.6	104.1	104.1	109.6	115.0	120.5
17.5°	76.7	82.2	87.6	87.6	93.1	98.6	109.6	115.0	120.5	131.5	136.9
20°	76.7	82.2	87.6	87.6	93.1	104.1	109.6	120.5	126.0	136.9	147.9
22.5°	76.7	82.2	87.6	93.1	98.6	109.6	120.5	126.0	136.9	153.4	164.3
25°	76.7	82.2	87.6	93.1	98.6	109.6	120.5	131.5	142.4	164.3	186.2
27.5°	76.7	82.2	93.1	98.6	104.1	115.0	131.5	142.4	153.4	191.7	230.1
30°	76.7	82.2	93.1	98.6	104.1	120.5	136.9	147.9	164.3	230.1	290.3
32.5°	76.7	87.6	93.1	104.1	109.6	126.0	147.9	164.3	180.8	273.9	361.5
35°	76.7	87.6	93.1	104.1	109.6	131.5	153.4	175.3	197.2	334.2	471.1
37.5°	76.7	87.6	93.1	104.1	109.6	142.4	175.3	208.2	241.0	383.5	525.9
40°	82.2	93.1	98.6	109.6	115.0	147.9	180.8	213.6	246.5	388.9	531.4
42.5°	82.2	93.1	98.6	109.6	115.0	142.4	175.3	202.7	230.1	388.9	547.8
45°	82.2	93.1	104.1	109.6	120.5	147.9	175.3	197.2	224.6	427.3	624.5
47.5°	82.2	93.1	104.1	109.6	120.5	147.9	175.3	202.7	230.1	564.2	892.9
50°	82.2	93.1	104.1	109.6	120.5	153.4	186.2	219.1	252.0	843.6	1435.2
52.5°	87.6	93.1	104.1	109.6	115.0	153.4	191.7	230.1	268.4	1095.6	1917.3
55°	93.1	98.6	104.1	109.6	115.0	164.3	213.6	262.9	312.2	1177.7	2037.8
57.5°	98.6	104.1	109.6	109.6	115.0	175.3	241.0	301.3	361.5	1172.3	1977.5
60°	104.1	109.6	115.0	120.5	126.0	186.2	252.0	312.2	372.5	1062.7	1752.9
62.5°	115.0	126.0	136.9	142.4	153.4	213.6	268.4	328.7	383.5	871.0	1353.0
65°	131.5	142.4	147.9	158.9	164.3	219.1	279.4	334.2	388.9	723.1	1051.8
67.5°	136.9	147.9	153.4	164.3	169.8	224.6	279.4	334.2	388.9	613.5	832.6
70°	136.9	147.9	158.9	164.3	175.3	230.1	279.4	334.2	383.5	531.4	679.3
72.5°	126.0	142.4	153.4	169.8	180.8	230.1	273.9	323.2	367.0	471.1	575.2
75°	120.5	142.4	158.9	180.8	197.2	230.1	268.4	301.3	334.2	410.8	487.5
77.5°	109.6	136.9	164.3	191.7	219.1	241.0	257.5	279.4	295.8	345.1	394.4
80°	104.1	131.5	158.9	186.2	213.6	224.6	230.1	241.0	246.5	252.0	257.5
82.5°	82.2	104.1	126.0	142.4	164.3	153.4	147.9	136.9	126.0	120.5	115.0
85°	38.3	43.8	43.8	49.3	49.3	49.3	43.8	43.8	38.3	32.9	27.4
87.5°	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	76.7	76.7	76.7	76.7	71.2	71.2	71.2	71.2	65.7	65.7	65.7
5°	87.6	87.6	87.6	87.6	82.2	82.2	82.2	82.2	76.7	76.7	76.7
7.5°	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1
10°	104.1	104.1	104.1	109.6	109.6	109.6	109.6	109.6	109.6	109.6	109.6
12.5°	115.0	115.0	120.5	120.5	126.0	126.0	131.5	131.5	136.9	136.9	136.9
15°	126.0	131.5	136.9	142.4	142.4	147.9	153.4	158.9	164.3	169.8	175.3
17.5°	147.9	153.4	164.3	175.3	186.2	197.2	213.6	235.5	252.0	268.4	290.3
20°	164.3	180.8	213.6	252.0	284.9	317.7	399.9	482.1	564.2	646.4	728.6
22.5°	197.2	230.1	339.6	454.7	564.2	673.8	931.2	1188.7	1440.7	1698.1	1928.2
25°	262.9	334.2	586.1	838.1	1084.6	1336.6	1796.8	2262.4	2722.5	3182.7	3609.9
27.5°	361.5	493.0	903.9	1320.2	1731.0	2141.9	2810.2	3483.9	4152.2	4826.0	5423.1
30°	504.0	717.6	1331.1	1950.1	2563.7	3177.2	4020.8	4869.9	5713.4	6557.0	7104.8
32.5°	684.7	1002.5	1780.3	2558.2	3336.0	4113.9	5045.1	5976.4	6902.2	7833.4	8414.1
35°	876.5	1281.8	2218.5	3160.7	4097.5	5039.7	6020.2	7000.8	7981.3	8961.8	9674.0
37.5°	986.0	1446.2	2558.2	3670.2	4776.7	5888.7	6962.4	8041.6	9115.2	10188.9	11054.4
40°	1090.1	1643.4	2925.2	4207.0	5488.9	6770.7	8025.1	9279.6	10534.0	11788.4	12900.4
42.5°	1243.5	1939.2	3434.6	4930.1	6420.1	7915.6	9564.4	11218.7	12867.6	14516.4	16225.5
45°	1561.2	2497.9	4437.1	6376.3	8310.0	10249.1	12588.2	14932.7	17271.8	19616.4	21807.5
47.5°	2328.1	3757.8	6403.7	9049.5	11695.3	14341.1	17036.3	19731.4	22426.5	25121.6	27729.1
50°	3604.5	5768.2	9076.9	12385.5	15688.7	18997.3	21687.0	24376.6	27060.8	29750.5	32341.5
52.5°	4804.1	7691.0	11246.1	14806.8	18361.9	21922.5	24305.4	26688.3	29071.2	31454.1	33963.0
55°	5215.0	8386.7	11985.6	15590.1	19189.1	22793.5	25088.8	27389.5	29684.7	31980.0	34582.0
57.5°	4853.4	7729.3	11355.7	14982.1	18602.9	22229.3	24793.0	27362.1	29925.8	32494.9	35283.1
60°	4064.6	6370.8	10177.9	13990.6	17797.7	21604.8	24497.2	27389.5	30281.8	33174.1	35956.9
62.5°	3221.0	5083.5	9115.2	13147.0	17178.7	21210.4	24152.1	27099.2	30040.8	32982.4	35118.8
65°	2470.5	3889.3	7855.3	11826.8	15792.8	19764.3	22174.5	24590.3	27000.6	29416.3	30895.3
67.5°	1835.1	2837.6	6305.1	9778.0	13245.6	16713.1	18487.9	20268.2	22043.1	23823.4	24973.7
70°	1353.0	2021.3	4382.3	6743.3	9098.8	11459.8	13086.7	14713.6	16335.1	17962.0	19156.2
72.5°	936.7	1292.8	2706.1	4124.9	5538.2	6951.5	8600.3	10249.1	11892.5	13541.4	14899.9
75°	640.9	794.3	1457.1	2119.9	2782.8	3445.6	4694.6	5943.5	7192.5	8441.4	9159.0
77.5°	476.6	558.7	755.9	958.6	1155.8	1353.0	1594.1	1835.1	2076.1	2317.2	2629.4
80°	262.9	262.9	290.3	312.2	339.6	361.5	427.3	498.5	564.2	635.4	723.1
82.5°	120.5	126.0	136.9	147.9	153.4	164.3	175.3	186.2	197.2	208.2	208.2
85°	32.9	38.3	38.3	32.9	32.9	27.4	27.4	32.9	32.9	32.9	32.9
87.5°	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	65.7	60.3	60.3	60.3	54.8	54.8	54.8	54.8	54.8	54.8	54.8
5°	76.7	76.7	76.7	76.7	71.2	71.2	71.2	71.2	71.2	65.7	65.7
7.5°	93.1	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	82.2	82.2
10°	109.6	109.6	109.6	109.6	109.6	109.6	109.6	109.6	109.6	104.1	104.1
12.5°	136.9	136.9	136.9	136.9	142.4	142.4	136.9	136.9	136.9	131.5	131.5
15°	180.8	186.2	191.7	191.7	197.2	197.2	197.2	191.7	191.7	186.2	180.8
17.5°	306.8	323.2	345.1	367.0	388.9	405.4	405.4	394.4	383.5	372.5	361.5
20°	816.2	898.4	986.0	1073.7	1166.8	1232.5	1188.7	1155.8	1123.0	1084.6	1051.8
22.5°	2163.8	2393.8	2629.4	2793.7	2958.1	3073.1	2980.0	2799.2	2618.4	2443.1	2262.4
25°	4037.2	4459.0	4886.3	5061.6	5242.3	5373.8	5313.6	5039.7	4765.8	4497.4	4223.5
27.5°	6020.2	6611.8	7208.9	7362.3	7515.7	7630.7	7608.8	7252.7	6896.7	6540.6	6184.5
30°	7652.6	8200.4	8748.2	8901.6	9055.0	9159.0	9044.0	8687.9	8331.9	7975.8	7619.8
32.5°	9000.2	9580.8	10167.0	10369.7	10572.3	10709.3	10572.3	10145.1	9717.8	9296.0	8868.7
35°	10386.1	11092.7	11804.9	12062.3	12319.8	12484.1	12254.1	11728.2	11202.3	10681.9	10156.0
37.5°	11919.9	12779.9	13645.4	13996.0	14352.1	14598.6	14423.3	13766.0	13103.1	12445.8	11783.0
40°	14017.9	15130.0	16247.4	16877.4	17501.9	17945.6	17633.4	16871.9	16105.0	15343.6	14576.7
42.5°	17940.1	19649.2	21358.3	22262.2	23160.6	23812.4	23461.8	22525.1	21588.4	20651.7	19715.0
45°	23998.7	26184.4	28375.5	29695.7	31021.3	31996.4	31591.0	30413.3	29230.1	28052.3	26874.6
47.5°	30336.6	32944.1	35551.6	36603.3	37660.5	38482.2	38383.6	36915.6	35447.5	33984.9	32516.8
50°	34938.0	37529.1	40120.1	41024.0	41933.3	42607.1	42355.1	40487.1	38613.7	36745.7	34872.3
52.5°	36471.8	38975.2	41484.1	42563.3	43642.4	44447.7	44140.9	42037.4	39933.9	37835.8	35732.3
55°	37184.0	39786.0	42388.0	43702.7	45022.8	45987.0	45543.2	43237.0	40925.4	38619.2	36307.5
57.5°	38071.4	40859.6	43647.9	45088.6	46529.3	47570.1	46978.5	44590.1	42201.7	39818.8	37430.5
60°	38739.7	41517.0	44299.8	45455.6	46616.9	47427.6	46857.9	44535.3	42207.2	39884.6	37561.9
62.5°	37260.7	39397.0	41533.4	42393.5	43253.5	43878.0	43554.8	41352.7	39150.5	36948.4	34746.3
65°	32379.9	33858.9	35343.4	35924.1	36499.2	36942.9	36844.3	34987.3	33130.3	31278.8	29421.8
67.5°	26129.6	27279.9	28435.8	29257.5	30084.6	30725.5	30654.3	28961.6	27269.0	25576.3	23883.6
70°	20355.9	21550.1	22744.2	23779.6	24820.4	25625.6	25521.5	23949.4	22371.7	20799.6	19221.9
72.5°	16263.9	17622.4	18980.9	19572.5	20164.1	20580.5	20273.7	19085.0	17890.8	16702.1	15507.9
75°	9876.6	10588.8	11306.4	11300.9	11300.9	11235.2	10928.4	10249.1	9569.9	8890.6	8211.4
77.5°	2941.6	3253.9	3566.1	3867.4	4174.2	4404.2	4344.0	3987.9	3626.4	3270.3	2908.8
80°	810.7	892.9	980.5	1018.9	1057.2	1106.5	1232.5	1144.9	1057.2	975.1	887.4
82.5°	208.2	208.2	208.2	202.7	197.2	186.2	169.8	158.9	147.9	136.9	126.0
85°	32.9	27.4	27.4	27.4	21.9	21.9	21.9	21.9	16.4	16.4	11.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3
2.5°	54.8	54.8	49.3	49.3	49.3	49.3	49.3	49.3	49.3	49.3	43.8
5°	65.7	65.7	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	54.8
7.5°	82.2	82.2	76.7	76.7	76.7	76.7	71.2	71.2	71.2	71.2	65.7
10°	104.1	98.6	98.6	93.1	93.1	93.1	87.6	87.6	87.6	82.2	82.2
12.5°	131.5	126.0	126.0	120.5	115.0	115.0	109.6	104.1	98.6	98.6	93.1
15°	175.3	169.8	164.3	158.9	153.4	142.4	136.9	126.0	120.5	115.0	109.6
17.5°	334.2	306.8	279.4	252.0	230.1	208.2	186.2	164.3	153.4	142.4	131.5
20°	931.2	805.3	684.7	564.2	487.5	410.8	334.2	257.5	224.6	197.2	164.3
22.5°	2015.9	1763.9	1517.4	1265.4	1062.7	865.5	662.8	460.1	383.5	312.2	235.5
25°	3746.9	3264.8	2788.3	2306.2	1922.7	1539.3	1155.8	772.4	630.0	487.5	345.1
27.5°	5560.1	4935.6	4311.1	3686.6	3078.6	2465.1	1851.5	1243.5	997.0	755.9	509.4
30°	6956.9	6294.1	5636.8	4973.9	4207.0	3440.1	2667.7	1900.8	1511.9	1123.0	728.6
32.5°	8156.6	7439.0	6726.9	6009.3	5121.8	4234.4	3347.0	2459.6	1972.0	1484.5	991.5
35°	9345.3	8529.1	7718.4	6902.2	5949.0	4995.8	4042.7	3089.5	2470.5	1851.5	1227.0
37.5°	10791.5	9794.5	8803.0	7811.5	6830.9	5855.9	4875.3	3894.8	3106.0	2322.6	1533.8
40°	13311.3	12040.4	10775.0	9504.2	8359.3	7219.9	6075.0	4930.1	3938.6	2947.1	1950.1
42.5°	18120.9	16526.8	14938.2	13344.2	11761.0	10177.9	8589.3	7006.2	5592.9	4185.1	2771.8
45°	24831.3	22788.1	20750.3	18707.0	16756.9	14812.2	12862.1	10912.0	8764.6	6617.3	4464.5
47.5°	30281.8	28041.4	25806.4	23565.9	21402.1	19243.9	17080.1	14916.3	12166.4	9422.0	6672.1
50°	32741.4	30605.0	28474.1	26337.7	24168.5	21993.8	19819.0	17649.8	14494.5	11344.7	8189.5
52.5°	33568.6	31399.3	29235.5	27066.3	24913.5	22760.7	20607.9	18455.0	15173.8	11898.0	8616.7
55°	34023.2	31733.5	29449.2	27159.4	24842.3	22519.6	20197.0	17879.9	14615.0	11355.7	8090.9
57.5°	34943.5	32451.1	29964.1	27471.7	24831.3	22191.0	19545.1	16904.8	13683.8	10462.8	7241.8
60°	35113.3	32659.2	30210.6	27762.0	24842.3	21922.5	18997.3	16077.6	12878.5	9684.9	6485.8
62.5°	32697.6	30648.8	28605.6	26556.8	23631.7	20706.5	17775.8	14850.6	11788.4	8726.3	5658.7
65°	27652.4	25883.1	24119.2	22349.8	19961.5	17578.6	15190.2	12801.8	10068.4	7340.4	4606.9
67.5°	22152.6	20421.6	18696.1	16965.0	15168.3	13377.0	11580.3	9783.5	7674.5	5565.5	3456.6
70°	17562.1	15896.9	14237.1	12571.8	10983.2	9389.1	7795.0	6206.5	4897.2	3593.5	2284.3
72.5°	13919.3	12325.3	10736.7	9142.6	7701.9	6261.2	4820.6	3379.9	2728.0	2081.6	1429.7
75°	7384.2	6557.0	5735.4	4908.2	4097.5	3281.3	2465.1	1654.3	1396.9	1139.4	876.5
77.5°	2547.2	2185.7	1829.6	1468.1	1221.6	975.1	728.6	482.1	454.7	432.8	405.4
80°	772.4	657.3	542.3	427.3	378.0	328.7	279.4	230.1	213.6	197.2	175.3
82.5°	120.5	109.6	104.1	93.1	87.6	87.6	82.2	76.7	65.7	60.3	49.3
85°	11.0	5.5	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	49.3	49.3
2.5°	43.8	43.8
5°	54.8	54.8
7.5°	65.7	65.7
10°	76.7	76.7
12.5°	87.6	87.6
15°	104.1	98.6
17.5°	120.5	115.0
20°	131.5	120.5
22.5°	158.9	136.9
25°	202.7	169.8
27.5°	262.9	208.2
30°	339.6	262.9
32.5°	504.0	367.0
35°	608.0	443.7
37.5°	745.0	514.9
40°	958.6	624.5
42.5°	1358.5	849.1
45°	2317.2	1407.8
47.5°	3927.7	2399.3
50°	5034.2	3078.6
52.5°	5341.0	3264.8
55°	4831.5	2996.4
57.5°	4020.8	2547.2
60°	3292.2	2098.0
62.5°	2596.5	1659.8
65°	1873.4	1254.4
67.5°	1347.6	964.1
70°	980.5	755.9
72.5°	777.9	630.0
75°	619.0	525.9
77.5°	383.5	350.6
80°	158.9	147.9
82.5°	38.3	32.9
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066518

CATALOG NUMBER: NVN-SA5B-730-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-4

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-730-U-5WQ

Data in this report applies to families of products including GSS-SB1A-730-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-4
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-730-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 3000K CCT 26 LEDS

Spectral Parameters

CCT (K): 2985
 CIE u' : 0.2504
 CIE v' : 0.5243
 Duv: 0.0019
 CIE x: 0.4408
 CIE y: 0.4101
 CIE z: 0.1491
 Peak Wavelength (nm): 595
 Dominant Wavelength (nm): 582
 Purity: 55.41818
 R_f: 73.8
 R_g: 94.4

CRI (Ra): 70.8
 R1: 66.3
 R2: 80.6
 R3: 94.5
 R4: 68.2
 R5: 66.5
 R6: 74.7
 R7: 76.2
 R8: 39.6
 R9: -43.2
 R10: 57.6
 R11: 64.8
 R12: 53.5
 R13: 68.7
 R14: 97.0
 R15: 56.4



Test Conditions

Stabilization Time: 36M
 Operation Time: 1H 36M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-4

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-4

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-4

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.19

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.13

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	142	NR	620	803	NR	750	17	NR	880	0	NR
365	0	NR	495	189	NR	625	734	NR	755	15	NR	885	0	NR
370	0	NR	500	240	NR	630	670	NR	760	13	NR	890	0	NR
375	0	NR	505	290	NR	635	600	NR	765	11	NR	895	0	NR
380	0	NR	510	335	NR	640	535	NR	770	9	NR	900	0	NR
385	0	NR	515	375	NR	645	473	NR	775	8	NR	905	0	NR
390	1	NR	520	408	NR	650	415	NR	780	7	NR	910	0	NR
395	2	NR	525	434	NR	655	362	NR	785	6	NR	915	0	NR
400	4	NR	530	461	NR	660	313	NR	790	5	NR	920	0	NR
405	8	NR	535	486	NR	665	271	NR	795	4	NR	925	0	NR
410	16	NR	540	514	NR	670	231	NR	800	4	NR	930	0	NR
415	33	NR	545	549	NR	675	198	NR	805	3	NR	935	0	NR
420	69	NR	550	591	NR	680	169	NR	810	3	NR	940	0	NR
425	131	NR	555	640	NR	685	144	NR	815	2	NR	945	0	NR
430	227	NR	560	695	NR	690	123	NR	820	2	NR	950	0	NR
435	369	NR	565	757	NR	695	104	NR	825	2	NR	955	0	NR
440	517	NR	570	822	NR	700	88	NR	830	2	NR	960	0	NR
445	498	NR	575	882	NR	705	75	NR	835	1	NR	965	0	NR
450	315	NR	580	935	NR	710	63	NR	840	1	NR	970	0	NR
455	204	NR	585	972	NR	715	54	NR	845	1	NR	975	0	NR
460	145	NR	590	996	NR	720	46	NR	850	1	NR	980	0	NR
465	100	NR	595	1000	NR	725	39	NR	855	1	NR	985	0	NR
470	78	NR	600	989	NR	730	33	NR	860	1	NR	990	0	NR
475	76	NR	605	960	NR	735	28	NR	865	1	NR	995	0	NR
480	83	NR	610	918	NR	740	24	NR	870	1	NR	1000	0	NR
485	105	NR	615	864	NR	745	20	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-4


TM-30-18

Summary

$R_f = 73.8$
 $R_g = 94.4$
 $CIE R_a = 70.8$
 $R_g = -43.2$



Color Vector Graphics




Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 63	CES51 = 86	CES76 = 61
CES02 = 62	CES27 = 83	CES52 = 86	CES77 = 81
CES03 = 31	CES28 = 86	CES53 = 75	CES78 = 64
CES04 = 71	CES29 = 58	CES54 = 81	CES79 = 86
CES05 = 49	CES30 = 61	CES55 = 80	CES80 = 86
CES06 = 51	CES31 = 63	CES56 = 71	CES81 = 70
CES07 = 41	CES32 = 61	CES57 = 69	CES82 = 94
CES08 = 40	CES33 = 65	CES58 = 72	CES83 = 88
CES09 = 29	CES34 = 77	CES59 = 85	CES84 = 90
CES10 = 76	CES35 = 88	CES60 = 93	CES85 = 80
CES11 = 59	CES36 = 89	CES61 = 86	CES86 = 60
CES12 = 65	CES37 = 85	CES62 = 81	CES87 = 78
CES13 = 43	CES38 = 69	CES63 = 73	CES88 = 75
CES14 = 74	CES39 = 93	CES64 = 72	CES89 = 66
CES15 = 71	CES40 = 89	CES65 = 67	CES90 = 72
CES16 = 47	CES41 = 83	CES66 = 70	CES91 = 95
CES17 = 50	CES42 = 87	CES67 = 68	CES92 = 59
CES18 = 56	CES43 = 77	CES68 = 73	CES93 = 76
CES19 = 73	CES44 = 99	CES69 = 83	CES94 = 48
CES20 = 66	CES45 = 83	CES70 = 66	CES95 = 70
CES21 = 87	CES46 = 77	CES71 = 66	CES96 = 76
CES22 = 79	CES47 = 74	CES72 = 88	CES97 = 82
CES23 = 92	CES48 = 62	CES73 = 59	CES98 = 73
CES24 = 91	CES49 = 77	CES74 = 93	CES99 = 60
CES25 = 73	CES50 = 85	CES75 = 67	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)