

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066531

Luminaire Tested: **NVN-SA2C-735-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066531
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA2C-735-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1050mA 2xLight Square PACKAGE
70CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (28) 3500K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8976.4 lumens
Efficiency: N/A
Efficacy: 93.3 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 96.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 1.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	53.4	0.0	53.4
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	8923.0	0.0	8923.0
	% Fixture	99.4	0.0	99.4
Total	Lumens	8976.4	0.0	8976.4
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2.7	0.0
10°-20°	13.2	0.1
20°-30°	167.5	1.9
30°-40°	564.6	6.3
40°-50°	1705.2	19.0
50°-60°	3008.6	33.5
60°-70°	2650.6	29.5
70°-80°	843.7	9.4
80°-90°	20.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	8976.4	100.0
0°-180°	8976.4	100.0



REPORT NUMBER: P1066531


CATALOG NUMBER: NVN-SA2C-735-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	175.4	2.0			
FM	(30°-60°)	5257.8	58.6			
FH	(60°-80°)	3473.4	38.7			G2/5000
FVH	(80°-90°)	16.5	0.2			G1/100
BL	(0°-30°)	8.0	0.1	B0/110		
BM	(30°-60°)	20.7	0.2	B0/220		
BH	(60°-80°)	20.9	0.2	B0/110		G0/110
BVH	(80°-90°)	3.8	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	22.5	19.7
5°	28.2	28.2	28.2	25.3	25.3	25.3	22.5	22.5	22.5	22.5	22.5
7.5°	33.8	31.0	31.0	28.2	28.2	28.2	25.3	25.3	25.3	25.3	22.5
10°	39.4	36.6	36.6	33.8	33.8	31.0	31.0	28.2	28.2	25.3	25.3
12.5°	45.0	42.2	39.4	36.6	36.6	33.8	33.8	31.0	31.0	28.2	28.2
15°	50.7	47.9	45.0	42.2	39.4	39.4	36.6	33.8	31.0	31.0	28.2
17.5°	59.1	53.5	50.7	45.0	42.2	39.4	36.6	33.8	33.8	31.0	31.0
20°	61.9	56.3	53.5	47.9	45.0	42.2	39.4	36.6	33.8	33.8	31.0
22.5°	73.2	61.9	59.1	53.5	50.7	47.9	42.2	39.4	36.6	33.8	31.0
25°	90.1	73.2	64.7	56.3	53.5	47.9	45.0	39.4	36.6	33.8	31.0
27.5°	109.8	81.6	73.2	61.9	56.3	50.7	45.0	39.4	36.6	33.8	31.0
30°	135.1	95.7	81.6	67.6	61.9	56.3	47.9	42.2	39.4	36.6	31.0
32.5°	188.6	118.2	95.7	73.2	64.7	59.1	50.7	42.2	39.4	36.6	31.0
35°	228.0	143.6	115.4	84.5	73.2	64.7	53.5	42.2	39.4	36.6	31.0
37.5°	264.6	146.4	118.2	90.1	78.8	67.6	53.5	42.2	39.4	36.6	31.0
40°	323.7	152.0	118.2	84.5	76.0	64.7	56.3	45.0	42.2	36.6	33.8
42.5°	436.3	174.5	126.7	78.8	70.4	64.7	56.3	47.9	42.2	39.4	33.8
45°	726.3	259.0	171.7	81.6	73.2	64.7	56.3	47.9	45.0	39.4	36.6
47.5°	1235.8	450.4	267.4	84.5	76.0	64.7	56.3	45.0	42.2	39.4	33.8
50°	1582.0	577.1	337.8	98.5	84.5	73.2	59.1	45.0	42.2	39.4	36.6
52.5°	1680.6	613.7	366.0	115.4	98.5	81.6	61.9	45.0	42.2	42.2	39.4
55°	1539.8	596.8	366.0	135.1	112.6	92.9	70.4	47.9	45.0	45.0	42.2
57.5°	1309.0	551.7	349.1	146.4	123.9	98.5	76.0	50.7	47.9	47.9	45.0
60°	1078.1	464.5	315.3	163.3	137.9	112.6	87.3	61.9	59.1	56.3	50.7
62.5°	855.8	374.4	275.9	174.5	149.2	121.0	95.7	67.6	64.7	61.9	59.1
65°	644.6	326.5	256.2	183.0	154.8	126.7	98.5	70.4	67.6	67.6	64.7
67.5°	495.4	298.4	244.9	188.6	160.5	132.3	104.2	76.0	73.2	70.4	67.6
70°	391.3	275.9	230.8	185.8	160.5	135.1	107.0	81.6	76.0	73.2	67.6
72.5°	326.5	250.5	213.9	177.3	157.6	137.9	118.2	98.5	87.3	78.8	67.6
75°	273.1	225.2	194.2	160.5	146.4	135.1	121.0	107.0	92.9	78.8	64.7
77.5°	180.2	163.3	149.2	135.1	126.7	118.2	107.0	98.5	84.5	73.2	59.1
80°	76.0	70.4	73.2	73.2	73.2	73.2	70.4	70.4	61.9	53.5	42.2
82.5°	16.9	14.1	16.9	16.9	16.9	16.9	14.1	14.1	14.1	11.3	11.3
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7
5°	22.5	22.5	22.5	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7
7.5°	22.5	22.5	22.5	19.7	19.7	19.7	19.7	16.9	16.9	16.9	16.9
10°	22.5	22.5	22.5	19.7	19.7	19.7	19.7	16.9	16.9	16.9	16.9
12.5°	25.3	25.3	22.5	22.5	19.7	19.7	19.7	16.9	16.9	16.9	16.9
15°	25.3	25.3	22.5	22.5	19.7	19.7	19.7	16.9	16.9	16.9	16.9
17.5°	28.2	25.3	25.3	22.5	19.7	19.7	19.7	16.9	16.9	16.9	16.9
20°	28.2	25.3	25.3	22.5	19.7	19.7	19.7	16.9	16.9	16.9	16.9
22.5°	28.2	25.3	25.3	22.5	19.7	19.7	16.9	16.9	14.1	14.1	11.3
25°	28.2	25.3	25.3	22.5	19.7	19.7	16.9	16.9	14.1	11.3	11.3
27.5°	28.2	25.3	25.3	22.5	19.7	16.9	16.9	14.1	11.3	8.4	8.4
30°	28.2	25.3	25.3	22.5	19.7	16.9	14.1	11.3	8.4	8.4	5.6
32.5°	28.2	25.3	22.5	19.7	16.9	14.1	14.1	11.3	8.4	5.6	5.6
35°	28.2	25.3	22.5	19.7	16.9	14.1	14.1	11.3	8.4	5.6	5.6
37.5°	28.2	25.3	22.5	19.7	16.9	14.1	11.3	8.4	5.6	5.6	2.8
40°	28.2	25.3	22.5	19.7	16.9	14.1	11.3	8.4	5.6	5.6	2.8
42.5°	28.2	25.3	22.5	19.7	16.9	14.1	11.3	8.4	5.6	5.6	2.8
45°	31.0	28.2	25.3	19.7	16.9	14.1	14.1	11.3	8.4	5.6	5.6
47.5°	31.0	28.2	25.3	19.7	16.9	14.1	14.1	11.3	8.4	5.6	5.6
50°	33.8	31.0	28.2	22.5	19.7	16.9	14.1	8.4	5.6	5.6	2.8
52.5°	36.6	33.8	31.0	28.2	25.3	19.7	14.1	8.4	2.8	2.8	2.8
55°	39.4	36.6	36.6	33.8	31.0	22.5	16.9	8.4	0.0	0.0	0.0
57.5°	42.2	39.4	39.4	36.6	33.8	25.3	16.9	8.4	0.0	0.0	0.0
60°	47.9	45.0	42.2	36.6	33.8	25.3	16.9	8.4	0.0	0.0	0.0
62.5°	56.3	50.7	42.2	36.6	28.2	22.5	14.1	8.4	0.0	0.0	0.0
65°	61.9	53.5	45.0	33.8	25.3	19.7	14.1	5.6	0.0	0.0	0.0
67.5°	64.7	53.5	45.0	33.8	22.5	16.9	11.3	5.6	0.0	0.0	0.0
70°	61.9	50.7	42.2	31.0	19.7	14.1	11.3	5.6	0.0	0.0	0.0
72.5°	56.3	47.9	36.6	28.2	16.9	14.1	8.4	5.6	0.0	0.0	0.0
75°	50.7	42.2	31.0	22.5	11.3	8.4	5.6	2.8	0.0	0.0	0.0
77.5°	45.0	36.6	25.3	16.9	5.6	5.6	2.8	2.8	0.0	0.0	0.0
80°	33.8	25.3	16.9	8.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	8.4	5.6	5.6	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9
5°	16.9	16.9	16.9	16.9	14.1	14.1	14.1	14.1	14.1	14.1	14.1
7.5°	16.9	16.9	16.9	16.9	14.1	14.1	14.1	14.1	11.3	11.3	11.3
10°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	11.3	11.3	11.3
12.5°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	11.3	11.3	11.3
15°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	11.3	11.3	8.4	8.4
17.5°	14.1	14.1	14.1	14.1	11.3	11.3	11.3	8.4	8.4	5.6	5.6
20°	14.1	14.1	14.1	11.3	11.3	8.4	8.4	5.6	5.6	2.8	2.8
22.5°	11.3	8.4	8.4	5.6	5.6	2.8	2.8	2.8	0.0	0.0	0.0
25°	8.4	5.6	5.6	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	16.9	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1
5°	14.1	14.1	14.1	14.1	11.3	11.3	11.3	11.3	11.3	11.3	11.3
7.5°	11.3	11.3	11.3	11.3	11.3	11.3	8.4	8.4	8.4	8.4	8.4
10°	11.3	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	5.6	5.6
12.5°	11.3	8.4	8.4	8.4	5.6	5.6	5.6	5.6	5.6	2.8	2.8
15°	8.4	5.6	5.6	5.6	2.8	2.8	2.8	2.8	2.8	0.0	0.0
17.5°	5.6	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	16.9	16.9
5°	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3
7.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
10°	5.6	5.6	5.6	5.6	5.6	5.6	2.8	2.8	2.8	2.8	2.8
12.5°	2.8	2.8	2.8	2.8	2.8	2.8	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	16.9	16.9	16.9	16.9	16.9	19.7	19.7	22.5	22.5	25.3	25.3
5°	11.3	11.3	14.1	14.1	14.1	14.1	16.9	16.9	16.9	19.7	19.7
7.5°	8.4	8.4	8.4	8.4	8.4	11.3	11.3	14.1	14.1	16.9	16.9
10°	2.8	2.8	5.6	5.6	5.6	5.6	8.4	8.4	8.4	11.3	14.1
12.5°	0.0	0.0	2.8	2.8	2.8	2.8	5.6	5.6	5.6	8.4	11.3
15°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	5.6	8.4
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	5.6
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	28.2	28.2	31.0	31.0	33.8	33.8	36.6	36.6	36.6	36.6	36.6
5°	22.5	22.5	25.3	28.2	28.2	31.0	33.8	33.8	33.8	33.8	33.8
7.5°	19.7	19.7	22.5	25.3	25.3	28.2	31.0	31.0	33.8	33.8	33.8
10°	14.1	16.9	19.7	22.5	22.5	25.3	28.2	28.2	31.0	31.0	31.0
12.5°	11.3	14.1	16.9	19.7	19.7	22.5	25.3	25.3	28.2	28.2	31.0
15°	8.4	11.3	14.1	16.9	16.9	19.7	22.5	22.5	25.3	28.2	31.0
17.5°	5.6	8.4	11.3	14.1	14.1	16.9	19.7	22.5	25.3	25.3	28.2
20°	5.6	5.6	8.4	11.3	11.3	14.1	16.9	19.7	22.5	22.5	25.3
22.5°	2.8	2.8	5.6	8.4	8.4	11.3	14.1	16.9	19.7	19.7	22.5
25°	0.0	0.0	2.8	5.6	5.6	8.4	11.3	11.3	14.1	14.1	16.9
27.5°	0.0	0.0	2.8	2.8	5.6	5.6	8.4	8.4	11.3	11.3	14.1
30°	0.0	0.0	2.8	2.8	5.6	5.6	8.4	8.4	11.3	11.3	11.3
32.5°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	8.4	8.4	11.3
35°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	8.4	8.4	8.4
37.5°	0.0	0.0	0.0	2.8	2.8	2.8	5.6	5.6	5.6	5.6	8.4
40°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
45°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
50°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
55°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8
75°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
80°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	5.6	5.6	5.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	5.6
85°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	36.6	36.6
5°	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	33.8	33.8
7.5°	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	33.8	33.8
10°	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
12.5°	31.0	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
15°	31.0	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
17.5°	28.2	31.0	31.0	31.0	33.8	33.8	33.8	33.8	33.8	33.8	33.8
20°	25.3	28.2	28.2	28.2	31.0	31.0	31.0	31.0	33.8	33.8	33.8
22.5°	22.5	25.3	25.3	25.3	28.2	28.2	28.2	28.2	31.0	31.0	31.0
25°	19.7	19.7	22.5	22.5	25.3	25.3	25.3	25.3	25.3	25.3	25.3
27.5°	14.1	16.9	16.9	16.9	19.7	19.7	19.7	19.7	22.5	22.5	22.5
30°	14.1	14.1	14.1	14.1	16.9	16.9	16.9	16.9	19.7	19.7	19.7
32.5°	11.3	14.1	14.1	14.1	16.9	16.9	16.9	16.9	19.7	19.7	19.7
35°	11.3	11.3	11.3	11.3	14.1	14.1	14.1	14.1	16.9	16.9	16.9
37.5°	8.4	11.3	11.3	11.3	14.1	14.1	14.1	14.1	16.9	16.9	16.9
40°	8.4	8.4	8.4	8.4	11.3	11.3	11.3	11.3	14.1	14.1	14.1
42.5°	8.4	8.4	8.4	8.4	11.3	11.3	11.3	11.3	14.1	14.1	14.1
45°	8.4	8.4	8.4	8.4	11.3	11.3	11.3	11.3	14.1	14.1	14.1
47.5°	8.4	8.4	8.4	8.4	11.3	11.3	11.3	11.3	14.1	14.1	14.1
50°	8.4	8.4	8.4	8.4	11.3	11.3	11.3	11.3	14.1	14.1	14.1
52.5°	5.6	5.6	5.6	5.6	8.4	8.4	8.4	8.4	11.3	11.3	11.3
55°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	8.4	8.4	8.4
57.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	8.4	8.4	8.4
60°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
62.5°	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
65°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	2.8	2.8
67.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
70°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
72.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
75°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
77.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
80°	8.4	8.4	8.4	8.4	8.4	5.6	5.6	5.6	5.6	5.6	5.6
82.5°	5.6	8.4	8.4	8.4	8.4	5.6	5.6	5.6	5.6	5.6	5.6
85°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
87.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	36.6	36.6	33.8	33.8	33.8	33.8	33.8	33.8	33.8	36.6	36.6
5°	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	36.6	36.6
7.5°	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	36.6	36.6
10°	33.8	33.8	33.8	33.8	31.0	31.0	33.8	33.8	33.8	36.6	36.6
12.5°	33.8	33.8	33.8	33.8	31.0	31.0	33.8	33.8	36.6	36.6	39.4
15°	33.8	33.8	31.0	31.0	31.0	31.0	33.8	33.8	36.6	36.6	39.4
17.5°	33.8	33.8	31.0	31.0	31.0	31.0	33.8	33.8	36.6	36.6	39.4
20°	33.8	33.8	31.0	31.0	31.0	31.0	31.0	31.0	33.8	36.6	36.6
22.5°	31.0	31.0	31.0	31.0	28.2	28.2	31.0	31.0	33.8	36.6	36.6
25°	25.3	28.2	28.2	28.2	28.2	28.2	31.0	31.0	33.8	36.6	36.6
27.5°	22.5	25.3	25.3	25.3	25.3	28.2	28.2	31.0	33.8	36.6	36.6
30°	19.7	22.5	22.5	22.5	25.3	28.2	28.2	31.0	33.8	36.6	36.6
32.5°	19.7	22.5	22.5	22.5	25.3	25.3	28.2	28.2	31.0	33.8	36.6
35°	19.7	19.7	22.5	22.5	22.5	25.3	25.3	28.2	31.0	33.8	36.6
37.5°	19.7	19.7	22.5	22.5	22.5	25.3	25.3	28.2	31.0	33.8	36.6
40°	16.9	19.7	19.7	22.5	22.5	25.3	25.3	28.2	31.0	36.6	39.4
42.5°	16.9	16.9	19.7	19.7	22.5	25.3	25.3	28.2	31.0	36.6	39.4
45°	16.9	19.7	19.7	22.5	25.3	28.2	28.2	31.0	33.8	36.6	39.4
47.5°	16.9	19.7	19.7	22.5	28.2	28.2	31.0	31.0	33.8	36.6	39.4
50°	16.9	19.7	19.7	22.5	31.0	31.0	31.0	31.0	33.8	36.6	39.4
52.5°	14.1	16.9	16.9	19.7	25.3	28.2	31.0	33.8	36.6	39.4	42.2
55°	11.3	14.1	14.1	16.9	22.5	25.3	31.0	36.6	39.4	42.2	45.0
57.5°	11.3	11.3	14.1	14.1	19.7	25.3	33.8	39.4	42.2	45.0	47.9
60°	8.4	8.4	11.3	11.3	16.9	22.5	31.0	39.4	42.2	47.9	50.7
62.5°	5.6	8.4	8.4	11.3	14.1	22.5	31.0	39.4	45.0	50.7	53.5
65°	5.6	5.6	8.4	8.4	14.1	19.7	28.2	33.8	42.2	50.7	59.1
67.5°	8.4	8.4	11.3	11.3	14.1	19.7	28.2	33.8	42.2	53.5	61.9
70°	8.4	8.4	11.3	11.3	16.9	22.5	28.2	33.8	42.2	53.5	61.9
72.5°	8.4	8.4	11.3	11.3	16.9	19.7	25.3	31.0	39.4	47.9	56.3
75°	5.6	8.4	8.4	8.4	14.1	16.9	22.5	28.2	36.6	45.0	53.5
77.5°	5.6	5.6	5.6	5.6	11.3	14.1	19.7	22.5	31.0	39.4	47.9
80°	5.6	5.6	5.6	5.6	8.4	11.3	16.9	19.7	28.2	36.6	45.0
82.5°	5.6	5.6	2.8	2.8	5.6	8.4	11.3	14.1	22.5	28.2	36.6
85°	5.6	5.6	2.8	2.8	2.8	5.6	5.6	8.4	11.3	14.1	16.9
87.5°	5.6	5.6	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	36.6	36.6	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
5°	36.6	39.4	39.4	42.2	42.2	42.2	45.0	45.0	45.0	45.0	45.0
7.5°	36.6	39.4	39.4	42.2	42.2	42.2	45.0	45.0	45.0	47.9	47.9
10°	36.6	39.4	39.4	42.2	42.2	45.0	47.9	47.9	50.7	50.7	50.7
12.5°	39.4	42.2	42.2	45.0	45.0	47.9	50.7	50.7	53.5	56.3	56.3
15°	39.4	42.2	45.0	45.0	47.9	50.7	53.5	53.5	56.3	59.1	61.9
17.5°	39.4	42.2	45.0	45.0	47.9	50.7	56.3	59.1	61.9	67.6	70.4
20°	39.4	42.2	45.0	45.0	47.9	53.5	56.3	61.9	64.7	70.4	76.0
22.5°	39.4	42.2	45.0	47.9	50.7	56.3	61.9	64.7	70.4	78.8	84.5
25°	39.4	42.2	45.0	47.9	50.7	56.3	61.9	67.6	73.2	84.5	95.7
27.5°	39.4	42.2	47.9	50.7	53.5	59.1	67.6	73.2	78.8	98.5	118.2
30°	39.4	42.2	47.9	50.7	53.5	61.9	70.4	76.0	84.5	118.2	149.2
32.5°	39.4	45.0	47.9	53.5	56.3	64.7	76.0	84.5	92.9	140.8	185.8
35°	39.4	45.0	47.9	53.5	56.3	67.6	78.8	90.1	101.3	171.7	242.1
37.5°	39.4	45.0	47.9	53.5	56.3	73.2	90.1	107.0	123.9	197.1	270.2
40°	42.2	47.9	50.7	56.3	59.1	76.0	92.9	109.8	126.7	199.9	273.1
42.5°	42.2	47.9	50.7	56.3	59.1	73.2	90.1	104.2	118.2	199.9	281.5
45°	42.2	47.9	53.5	56.3	61.9	76.0	90.1	101.3	115.4	219.6	320.9
47.5°	42.2	47.9	53.5	56.3	61.9	76.0	90.1	104.2	118.2	289.9	458.8
50°	42.2	47.9	53.5	56.3	61.9	78.8	95.7	112.6	129.5	433.5	737.5
52.5°	45.0	47.9	53.5	56.3	59.1	78.8	98.5	118.2	137.9	563.0	985.3
55°	47.9	50.7	53.5	56.3	59.1	84.5	109.8	135.1	160.5	605.2	1047.2
57.5°	50.7	53.5	56.3	56.3	59.1	90.1	123.9	154.8	185.8	602.4	1016.2
60°	53.5	56.3	59.1	61.9	64.7	95.7	129.5	160.5	191.4	546.1	900.8
62.5°	59.1	64.7	70.4	73.2	78.8	109.8	137.9	168.9	197.1	447.6	695.3
65°	67.6	73.2	76.0	81.6	84.5	112.6	143.6	171.7	199.9	371.6	540.5
67.5°	70.4	76.0	78.8	84.5	87.3	115.4	143.6	171.7	199.9	315.3	427.9
70°	70.4	76.0	81.6	84.5	90.1	118.2	143.6	171.7	197.1	273.1	349.1
72.5°	64.7	73.2	78.8	87.3	92.9	118.2	140.8	166.1	188.6	242.1	295.6
75°	61.9	73.2	81.6	92.9	101.3	118.2	137.9	154.8	171.7	211.1	250.5
77.5°	56.3	70.4	84.5	98.5	112.6	123.9	132.3	143.6	152.0	177.3	202.7
80°	53.5	67.6	81.6	95.7	109.8	115.4	118.2	123.9	126.7	129.5	132.3
82.5°	42.2	53.5	64.7	73.2	84.5	78.8	76.0	70.4	64.7	61.9	59.1
85°	19.7	22.5	22.5	25.3	25.3	25.3	22.5	22.5	19.7	16.9	14.1
87.5°	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	39.4	39.4	39.4	39.4	36.6	36.6	36.6	36.6	33.8	33.8	33.8
5°	45.0	45.0	45.0	45.0	42.2	42.2	42.2	42.2	39.4	39.4	39.4
7.5°	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9	47.9
10°	53.5	53.5	53.5	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3
12.5°	59.1	59.1	61.9	61.9	64.7	64.7	67.6	67.6	70.4	70.4	70.4
15°	64.7	67.6	70.4	73.2	73.2	76.0	78.8	81.6	84.5	87.3	90.1
17.5°	76.0	78.8	84.5	90.1	95.7	101.3	109.8	121.0	129.5	137.9	149.2
20°	84.5	92.9	109.8	129.5	146.4	163.3	205.5	247.7	289.9	332.2	374.4
22.5°	101.3	118.2	174.5	233.6	289.9	346.2	478.6	610.9	740.3	872.7	990.9
25°	135.1	171.7	301.2	430.7	557.4	686.9	923.3	1162.6	1399.1	1635.5	1855.1
27.5°	185.8	253.4	464.5	678.4	889.5	1100.7	1444.1	1790.3	2133.8	2480.0	2786.9
30°	259.0	368.8	684.0	1002.1	1317.4	1632.7	2066.2	2502.5	2936.1	3369.6	3651.1
32.5°	351.9	515.1	914.9	1314.6	1714.3	2114.1	2592.6	3071.2	3546.9	4025.5	4323.8
35°	450.4	658.7	1140.1	1624.3	2105.6	2589.8	3093.7	3597.6	4101.5	4605.3	4971.3
37.5°	506.7	743.2	1314.6	1886.1	2454.7	3026.1	3577.9	4132.4	4684.2	5235.9	5680.7
40°	560.2	844.5	1503.2	2161.9	2820.6	3479.3	4124.0	4768.6	5413.3	6057.9	6629.3
42.5°	639.0	996.5	1765.0	2533.5	3299.2	4067.7	4915.0	5765.1	6612.4	7459.8	8338.0
45°	802.3	1283.6	2280.2	3276.7	4270.4	5266.9	6468.9	7673.7	8875.7	10080.5	11206.5
47.5°	1196.4	1931.1	3290.7	4650.4	6010.0	7369.7	8754.7	10139.6	11524.6	12909.6	14249.6
50°	1852.3	2964.2	4664.5	6364.7	8062.2	9762.4	11144.6	12526.8	13906.1	15288.3	16619.8
52.5°	2468.8	3952.3	5779.2	7609.0	9435.9	11265.7	12490.2	13714.7	14939.2	16163.8	17453.0
55°	2679.9	4309.8	6159.2	8011.5	9861.0	11713.2	12892.7	14075.0	15254.5	16434.0	17771.1
57.5°	2494.1	3972.0	5835.5	7699.0	9559.8	11423.3	12740.7	14061.0	15378.4	16698.6	18131.4
60°	2088.7	3273.9	5230.3	7189.5	9146.0	11102.4	12588.7	14075.0	15561.3	17047.7	18477.7
62.5°	1655.2	2612.3	4684.2	6756.0	8827.9	10899.7	12411.4	13925.8	15437.5	16949.1	18047.0
65°	1269.6	1998.7	4036.7	6077.6	8115.7	10156.5	11395.1	12636.6	13875.2	15116.6	15876.6
67.5°	943.0	1458.2	3240.1	5024.8	6806.7	8588.6	9500.6	10415.5	11327.6	12242.5	12833.6
70°	695.3	1038.7	2252.0	3465.3	4675.7	5889.0	6725.0	7561.1	8394.3	9230.4	9844.1
72.5°	481.4	664.3	1390.6	2119.7	2846.0	3572.2	4419.6	5266.9	6111.4	6958.7	7656.8
75°	329.4	408.2	748.8	1089.4	1430.0	1770.6	2412.5	3054.3	3696.1	4337.9	4706.7
77.5°	244.9	287.1	388.5	492.6	594.0	695.3	819.2	943.0	1066.9	1190.7	1351.2
80°	135.1	135.1	149.2	160.5	174.5	185.8	219.6	256.2	289.9	326.5	371.6
82.5°	61.9	64.7	70.4	76.0	78.8	84.5	90.1	95.7	101.3	107.0	107.0
85°	16.9	19.7	19.7	16.9	16.9	14.1	14.1	16.9	16.9	16.9	16.9
87.5°	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	33.8	31.0	31.0	31.0	28.2	28.2	28.2	28.2	28.2	28.2	28.2
5°	39.4	39.4	39.4	39.4	36.6	36.6	36.6	36.6	36.6	33.8	33.8
7.5°	47.9	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	42.2	42.2
10°	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	53.5	53.5
12.5°	70.4	70.4	70.4	70.4	73.2	73.2	70.4	70.4	70.4	67.6	67.6
15°	92.9	95.7	98.5	98.5	101.3	101.3	101.3	98.5	98.5	95.7	92.9
17.5°	157.6	166.1	177.3	188.6	199.9	208.3	208.3	202.7	197.1	191.4	185.8
20°	419.4	461.7	506.7	551.7	599.6	633.4	610.9	594.0	577.1	557.4	540.5
22.5°	1111.9	1230.2	1351.2	1435.7	1520.1	1579.2	1531.4	1438.5	1345.6	1255.5	1162.6
25°	2074.7	2291.4	2511.0	2601.1	2694.0	2761.5	2730.6	2589.8	2449.1	2311.1	2170.4
27.5°	3093.7	3397.7	3704.5	3783.4	3862.2	3921.3	3910.0	3727.1	3544.1	3361.1	3178.1
30°	3932.6	4214.1	4495.6	4574.4	4653.2	4706.7	4647.6	4464.6	4281.6	4098.6	3915.7
32.5°	4625.1	4923.4	5224.6	5328.8	5433.0	5503.3	5433.0	5213.4	4993.8	4777.1	4557.5
35°	5337.3	5700.4	6066.3	6198.6	6330.9	6415.4	6297.2	6026.9	5756.7	5489.3	5219.0
37.5°	6125.5	6567.4	7012.2	7192.3	7375.3	7502.0	7411.9	7074.1	6733.5	6395.7	6055.1
40°	7203.6	7775.0	8349.3	8673.0	8993.9	9222.0	9061.5	8670.2	8276.1	7884.8	7490.7
42.5°	9219.1	10097.4	10975.7	11440.2	11901.8	12236.8	12056.7	11575.3	11093.9	10612.6	10131.2
45°	12332.5	13455.7	14581.7	15260.1	15941.4	16442.4	16234.1	15628.9	15020.9	14415.6	13810.4
47.5°	15589.5	16929.4	18269.4	18809.9	19353.2	19775.4	19724.7	18970.3	18215.9	17464.3	16709.9
50°	17954.1	19285.6	20617.1	21081.6	21548.9	21895.1	21765.6	20805.7	19843.0	18883.1	17920.3
52.5°	18742.3	20028.8	21318.0	21872.6	22427.1	22841.0	22683.3	21602.4	20521.4	19443.2	18362.3
55°	19108.3	20445.4	21782.5	22458.1	23136.5	23632.0	23404.0	22218.8	21030.9	19845.8	18657.9
57.5°	19564.3	20997.1	22430.0	23170.3	23910.7	24445.5	24141.5	22914.1	21686.8	20462.3	19234.9
60°	19907.7	21334.9	22764.9	23358.9	23955.7	24372.3	24079.6	22886.0	21689.6	20496.1	19302.5
62.5°	19147.7	20245.5	21343.4	21785.3	22227.3	22548.2	22382.1	21250.5	20118.8	18987.2	17855.6
65°	16639.5	17399.5	18162.4	18460.8	18756.4	18984.4	18933.7	17979.4	17025.2	16073.7	15119.4
67.5°	13427.6	14018.7	14612.7	15034.9	15460.0	15789.4	15752.8	14882.9	14013.1	13143.3	12273.4
70°	10460.6	11074.2	11687.9	12219.9	12754.8	13168.6	13115.1	12307.2	11496.5	10688.6	9877.9
72.5°	8357.8	9055.9	9754.0	10058.0	10362.0	10576.0	10418.3	9807.5	9193.8	8583.0	7969.3
75°	5075.5	5441.4	5810.2	5807.4	5807.4	5773.6	5615.9	5266.9	4917.8	4568.8	4219.7
77.5°	1511.7	1672.1	1832.6	1987.4	2145.0	2263.3	2232.3	2049.3	1863.5	1680.6	1494.8
80°	416.6	458.8	503.9	523.6	543.3	568.6	633.4	588.3	543.3	501.1	456.0
82.5°	107.0	107.0	107.0	104.2	101.3	95.7	87.3	81.6	76.0	70.4	64.7
85°	16.9	14.1	14.1	14.1	11.3	11.3	11.3	11.3	8.4	8.4	5.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
2.5°	28.2	28.2	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	22.5
5°	33.8	33.8	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	28.2
7.5°	42.2	42.2	39.4	39.4	39.4	39.4	36.6	36.6	36.6	36.6	33.8
10°	53.5	50.7	50.7	47.9	47.9	47.9	45.0	45.0	45.0	42.2	42.2
12.5°	67.6	64.7	64.7	61.9	59.1	59.1	56.3	53.5	50.7	50.7	47.9
15°	90.1	87.3	84.5	81.6	78.8	73.2	70.4	64.7	61.9	59.1	56.3
17.5°	171.7	157.6	143.6	129.5	118.2	107.0	95.7	84.5	78.8	73.2	67.6
20°	478.6	413.8	351.9	289.9	250.5	211.1	171.7	132.3	115.4	101.3	84.5
22.5°	1035.9	906.4	779.8	650.3	546.1	444.8	340.6	236.5	197.1	160.5	121.0
25°	1925.5	1677.7	1432.8	1185.1	988.1	791.0	594.0	396.9	323.7	250.5	177.3
27.5°	2857.2	2536.3	2215.4	1894.5	1582.0	1266.8	951.5	639.0	512.3	388.5	261.8
30°	3575.1	3234.4	2896.6	2556.0	2161.9	1767.8	1370.9	976.8	776.9	577.1	374.4
32.5°	4191.5	3822.8	3456.8	3088.1	2632.0	2176.0	1720.0	1263.9	1013.4	762.9	509.5
35°	4802.4	4383.0	3966.3	3546.9	3057.1	2567.3	2077.5	1587.7	1269.6	951.5	630.6
37.5°	5545.6	5033.2	4523.7	4014.2	3510.3	3009.2	2505.4	2001.5	1596.1	1193.6	788.2
40°	6840.5	6187.4	5537.1	4884.0	4295.7	3710.2	3121.8	2533.5	2024.0	1514.5	1002.1
42.5°	9312.0	8492.9	7676.5	6857.4	6043.8	5230.3	4413.9	3600.4	2874.1	2150.7	1424.4
45°	12760.4	11710.4	10663.2	9613.2	8611.1	7611.8	6609.6	5607.5	4504.0	3400.5	2294.2
47.5°	15561.3	14410.0	13261.5	12110.2	10998.2	9889.1	8777.2	7665.3	6252.1	4841.8	3428.7
50°	16825.3	15727.4	14632.4	13534.5	12419.8	11302.2	10184.7	9069.9	7448.5	5829.9	4208.4
52.5°	17250.4	16135.6	15023.7	13908.9	12802.6	11696.3	10590.0	9483.8	7797.6	6114.2	4428.0
55°	17484.0	16307.3	15133.5	13956.8	12766.0	11572.5	10378.9	9188.2	7510.4	5835.5	4157.8
57.5°	17956.9	16676.1	15398.1	14117.3	12760.4	11403.6	10043.9	8687.1	7031.9	5376.7	3721.4
60°	18044.2	16783.1	15524.8	14266.4	12766.0	11265.7	9762.4	8262.0	6618.1	4976.9	3333.0
62.5°	16802.8	15750.0	14700.0	13647.1	12143.9	10640.7	9134.7	7631.5	6057.9	4484.3	2907.9
65°	14210.1	13300.9	12394.5	11485.2	10257.9	9033.4	7806.0	6578.7	5174.0	3772.1	2367.4
67.5°	11383.9	10494.3	9607.6	8718.1	7794.7	6874.2	5950.9	5027.6	3943.8	2860.0	1776.3
70°	9024.9	8169.1	7316.2	6460.4	5644.1	4824.9	4005.8	3189.4	2516.6	1846.6	1173.9
72.5°	7152.9	6333.8	5517.4	4698.2	3957.9	3217.6	2477.2	1736.9	1401.9	1069.7	734.7
75°	3794.6	3369.6	2947.3	2522.2	2105.6	1686.2	1266.8	850.1	717.8	585.5	450.4
77.5°	1309.0	1123.2	940.2	754.4	627.7	501.1	374.4	247.7	233.6	222.4	208.3
80°	396.9	337.8	278.7	219.6	194.2	168.9	143.6	118.2	109.8	101.3	90.1
82.5°	61.9	56.3	53.5	47.9	45.0	45.0	42.2	39.4	33.8	31.0	25.3
85°	5.6	2.8	2.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	25.3	25.3
2.5°	22.5	22.5
5°	28.2	28.2
7.5°	33.8	33.8
10°	39.4	39.4
12.5°	45.0	45.0
15°	53.5	50.7
17.5°	61.9	59.1
20°	67.6	61.9
22.5°	81.6	70.4
25°	104.2	87.3
27.5°	135.1	107.0
30°	174.5	135.1
32.5°	259.0	188.6
35°	312.5	228.0
37.5°	382.8	264.6
40°	492.6	320.9
42.5°	698.1	436.3
45°	1190.7	723.5
47.5°	2018.4	1233.0
50°	2587.0	1582.0
52.5°	2744.6	1677.7
55°	2482.8	1539.8
57.5°	2066.2	1309.0
60°	1691.8	1078.1
62.5°	1334.3	852.9
65°	962.7	644.6
67.5°	692.5	495.4
70°	503.9	388.5
72.5°	399.7	323.7
75°	318.1	270.2
77.5°	197.1	180.2
80°	81.6	76.0
82.5°	19.7	16.9
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066531

CATALOG NUMBER: NVN-SA2C-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-5

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-735-U-5WQ

Data in this report applies to families of products including GSS-SB1A-735-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-735-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3369
 CIE u' : 0.2386
 CIE v' : 0.5156
 Duv: 0.0013
 CIE x: 0.4143
 CIE y: 0.3980
 CIE z: 0.1877
 Peak Wavelength (nm): 590
 Dominant Wavelength (nm): 580
 Purity: 43.80166
 R_f: 71.4
 R_g: 96

CRI (Ra): 70.1
 R1: 66.6
 R2: 77.6
 R3: 88.5
 R4: 69.5
 R5: 66.4
 R6: 69.6
 R7: 77.5
 R8: 44.9
 R9: -40.2
 R10: 49.1
 R11: 66.3
 R12: 45.7
 R13: 68.0
 R14: 93.4
 R15: 57.6



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-5


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-5

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-5

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.29

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Melanopic Flux vs. Wavelength

Melanopic Lumens: NR
M/P: 2.36


λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5





TM-30-18

Summary

$R_f = 71.4$
 $R_g = 96$
 CIE $R_a = 70.1$
 $R_g = -40.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 57	CES51 = 84	CES76 = 50
CES02 = 62	CES27 = 80	CES52 = 86	CES77 = 74
CES03 = 31	CES28 = 81	CES53 = 72	CES78 = 54
CES04 = 70	CES29 = 50	CES54 = 79	CES79 = 81
CES05 = 48	CES30 = 55	CES55 = 78	CES80 = 79
CES06 = 51	CES31 = 56	CES56 = 67	CES81 = 74
CES07 = 40	CES32 = 54	CES57 = 65	CES82 = 91
CES08 = 39	CES33 = 60	CES58 = 68	CES83 = 86
CES09 = 29	CES34 = 69	CES59 = 85	CES84 = 89
CES10 = 75	CES35 = 83	CES60 = 91	CES85 = 83
CES11 = 58	CES36 = 88	CES61 = 85	CES86 = 66
CES12 = 64	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 43	CES38 = 64	CES63 = 71	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 70	CES89 = 68
CES15 = 71	CES40 = 86	CES65 = 64	CES90 = 72
CES16 = 47	CES41 = 81	CES66 = 65	CES91 = 95
CES17 = 50	CES42 = 79	CES67 = 63	CES92 = 62
CES18 = 56	CES43 = 71	CES68 = 69	CES93 = 78
CES19 = 72	CES44 = 98	CES69 = 80	CES94 = 51
CES20 = 65	CES45 = 80	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 75	CES71 = 58	CES96 = 76
CES22 = 79	CES47 = 71	CES72 = 85	CES97 = 82
CES23 = 92	CES48 = 61	CES73 = 51	CES98 = 72
CES24 = 91	CES49 = 74	CES74 = 94	CES99 = 60
CES25 = 72	CES50 = 83	CES75 = 57	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)