

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066532

Luminaire Tested: **NVN-SA2D-735-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066532
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA2D-735-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1200mA 2xLight Square PACKAGE
70CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (28) 3500K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 9856.3 lumens
Efficiency: N/A
Efficacy: 92.1 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 107
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 1.9 fc
 Type III - Short - N/A

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	58.6	0.0	58.6
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	9797.6	0.0	9797.6
	% Fixture	99.4	0.0	99.4
Total	Lumens	9856.2	0.0	9856.2
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2.9	0.0
10°-20°	14.5	0.1
20°-30°	184.0	1.9
30°-40°	620.0	6.3
40°-50°	1872.4	19.0
50°-60°	3303.5	33.5
60°-70°	2910.4	29.5
70°-80°	926.4	9.4
80°-90°	22.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	9856.2	100.0
0°-180°	9856.3	100.0



REPORT NUMBER: P1066532


CATALOG NUMBER: NVN-SA2D-735-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	192.5	2.0			
FM	(30°-60°)	5773.1	58.6			
FH	(60°-80°)	3813.8	38.7			G2/5000
FVH	(80°-90°)	18.1	0.2			G1/100
BL	(0°-30°)	8.8	0.1	B0/110		
BM	(30°-60°)	22.7	0.2	B0/220		
BH	(60°-80°)	23.0	0.2	B0/110		G0/110
BVH	(80°-90°)	4.2	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	24.7	24.7	24.7	24.7	24.7	24.7	24.7	24.7	24.7	24.7	21.6
5°	30.9	30.9	30.9	27.8	27.8	27.8	24.7	24.7	24.7	24.7	24.7
7.5°	37.1	34.0	34.0	30.9	30.9	30.9	27.8	27.8	27.8	27.8	24.7
10°	43.3	40.2	40.2	37.1	37.1	34.0	34.0	30.9	30.9	27.8	27.8
12.5°	49.5	46.4	43.3	40.2	40.2	37.1	37.1	34.0	34.0	30.9	30.9
15°	55.6	52.5	49.5	46.4	43.3	43.3	40.2	37.1	34.0	34.0	30.9
17.5°	64.9	58.7	55.6	49.5	46.4	43.3	40.2	37.1	37.1	34.0	34.0
20°	68.0	61.8	58.7	52.5	49.5	46.4	43.3	40.2	37.1	37.1	34.0
22.5°	80.4	68.0	64.9	58.7	55.6	52.5	46.4	43.3	40.2	37.1	34.0
25°	98.9	80.4	71.1	61.8	58.7	52.5	49.5	43.3	40.2	37.1	34.0
27.5°	120.5	89.6	80.4	68.0	61.8	55.6	49.5	43.3	40.2	37.1	34.0
30°	148.4	105.1	89.6	74.2	68.0	61.8	52.5	46.4	43.3	40.2	34.0
32.5°	207.1	129.8	105.1	80.4	71.1	64.9	55.6	46.4	43.3	40.2	34.0
35°	250.4	157.6	126.7	92.7	80.4	71.1	58.7	46.4	43.3	40.2	34.0
37.5°	290.5	160.7	129.8	98.9	86.5	74.2	58.7	46.4	43.3	40.2	34.0
40°	355.5	166.9	129.8	92.7	83.5	71.1	61.8	49.5	46.4	40.2	37.1
42.5°	479.1	191.6	139.1	86.5	77.3	71.1	61.8	52.5	46.4	43.3	37.1
45°	797.5	284.4	188.5	89.6	80.4	71.1	61.8	52.5	49.5	43.3	40.2
47.5°	1356.9	494.5	293.6	92.7	83.5	71.1	61.8	49.5	46.4	43.3	37.1
50°	1737.1	633.6	370.9	108.2	92.7	80.4	64.9	49.5	46.4	43.3	40.2
52.5°	1845.3	673.8	401.8	126.7	108.2	89.6	68.0	49.5	46.4	46.4	43.3
55°	1690.7	655.3	401.8	148.4	123.6	102.0	77.3	52.5	49.5	49.5	46.4
57.5°	1437.3	605.8	383.3	160.7	136.0	108.2	83.5	55.6	52.5	52.5	49.5
60°	1183.8	510.0	346.2	179.3	151.5	123.6	95.8	68.0	64.9	61.8	55.6
62.5°	939.6	411.1	302.9	191.6	163.8	132.9	105.1	74.2	71.1	68.0	64.9
65°	707.8	358.5	281.3	200.9	170.0	139.1	108.2	77.3	74.2	74.2	71.1
67.5°	544.0	327.6	268.9	207.1	176.2	145.3	114.4	83.5	80.4	77.3	74.2
70°	429.6	302.9	253.5	204.0	176.2	148.4	117.5	89.6	83.5	80.4	74.2
72.5°	358.5	275.1	234.9	194.7	173.1	151.5	129.8	108.2	95.8	86.5	74.2
75°	299.8	247.3	213.3	176.2	160.7	148.4	132.9	117.5	102.0	86.5	71.1
77.5°	197.8	179.3	163.8	148.4	139.1	129.8	117.5	108.2	92.7	80.4	64.9
80°	83.5	77.3	80.4	80.4	80.4	80.4	77.3	77.3	68.0	58.7	46.4
82.5°	18.5	15.5	18.5	18.5	18.5	18.5	15.5	15.5	15.5	12.4	12.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	21.6	21.6	21.6	21.6	21.6	21.6	21.6	21.6	21.6	21.6	21.6
5°	24.7	24.7	24.7	21.6	21.6	21.6	21.6	21.6	21.6	21.6	21.6
7.5°	24.7	24.7	24.7	21.6	21.6	21.6	21.6	18.5	18.5	18.5	18.5
10°	24.7	24.7	24.7	21.6	21.6	21.6	21.6	18.5	18.5	18.5	18.5
12.5°	27.8	27.8	24.7	24.7	21.6	21.6	21.6	18.5	18.5	18.5	18.5
15°	27.8	27.8	24.7	24.7	21.6	21.6	21.6	18.5	18.5	18.5	18.5
17.5°	30.9	27.8	27.8	24.7	21.6	21.6	21.6	18.5	18.5	18.5	18.5
20°	30.9	27.8	27.8	24.7	21.6	21.6	21.6	18.5	18.5	18.5	18.5
22.5°	30.9	27.8	27.8	24.7	21.6	21.6	18.5	18.5	15.5	15.5	12.4
25°	30.9	27.8	27.8	24.7	21.6	21.6	18.5	18.5	15.5	12.4	12.4
27.5°	30.9	27.8	27.8	24.7	21.6	18.5	18.5	15.5	12.4	9.3	9.3
30°	30.9	27.8	27.8	24.7	21.6	18.5	15.5	12.4	9.3	9.3	6.2
32.5°	30.9	27.8	24.7	21.6	18.5	15.5	15.5	12.4	9.3	6.2	6.2
35°	30.9	27.8	24.7	21.6	18.5	15.5	15.5	12.4	9.3	6.2	6.2
37.5°	30.9	27.8	24.7	21.6	18.5	15.5	12.4	9.3	6.2	6.2	3.1
40°	30.9	27.8	24.7	21.6	18.5	15.5	12.4	9.3	6.2	6.2	3.1
42.5°	30.9	27.8	24.7	21.6	18.5	15.5	12.4	9.3	6.2	6.2	3.1
45°	34.0	30.9	27.8	21.6	18.5	15.5	15.5	12.4	9.3	6.2	6.2
47.5°	34.0	30.9	27.8	21.6	18.5	15.5	15.5	12.4	9.3	6.2	6.2
50°	37.1	34.0	30.9	24.7	21.6	18.5	15.5	9.3	6.2	6.2	3.1
52.5°	40.2	37.1	34.0	30.9	27.8	21.6	15.5	9.3	3.1	3.1	3.1
55°	43.3	40.2	40.2	37.1	34.0	24.7	18.5	9.3	0.0	0.0	0.0
57.5°	46.4	43.3	43.3	40.2	37.1	27.8	18.5	9.3	0.0	0.0	0.0
60°	52.5	49.5	46.4	40.2	37.1	27.8	18.5	9.3	0.0	0.0	0.0
62.5°	61.8	55.6	46.4	40.2	30.9	24.7	15.5	9.3	0.0	0.0	0.0
65°	68.0	58.7	49.5	37.1	27.8	21.6	15.5	6.2	0.0	0.0	0.0
67.5°	71.1	58.7	49.5	37.1	24.7	18.5	12.4	6.2	0.0	0.0	0.0
70°	68.0	55.6	46.4	34.0	21.6	15.5	12.4	6.2	0.0	0.0	0.0
72.5°	61.8	52.5	40.2	30.9	18.5	15.5	9.3	6.2	0.0	0.0	0.0
75°	55.6	46.4	34.0	24.7	12.4	9.3	6.2	3.1	0.0	0.0	0.0
77.5°	49.5	40.2	27.8	18.5	6.2	6.2	3.1	3.1	0.0	0.0	0.0
80°	37.1	27.8	18.5	9.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	9.3	6.2	6.2	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5
5°	18.5	18.5	18.5	18.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5
7.5°	18.5	18.5	18.5	18.5	15.5	15.5	15.5	15.5	12.4	12.4	12.4
10°	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	12.4	12.4	12.4
12.5°	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	12.4	12.4	12.4
15°	15.5	15.5	15.5	15.5	15.5	15.5	15.5	12.4	12.4	9.3	9.3
17.5°	15.5	15.5	15.5	15.5	12.4	12.4	12.4	9.3	9.3	6.2	6.2
20°	15.5	15.5	15.5	12.4	12.4	9.3	9.3	6.2	6.2	3.1	3.1
22.5°	12.4	9.3	9.3	6.2	6.2	3.1	3.1	3.1	0.0	0.0	0.0
25°	9.3	6.2	6.2	3.1	3.1	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	6.2	3.1	3.1	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	6.2	3.1	3.1	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	18.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5
5°	15.5	15.5	15.5	15.5	12.4	12.4	12.4	12.4	12.4	12.4	12.4
7.5°	12.4	12.4	12.4	12.4	12.4	12.4	9.3	9.3	9.3	9.3	9.3
10°	12.4	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3	6.2	6.2
12.5°	12.4	9.3	9.3	9.3	6.2	6.2	6.2	6.2	6.2	3.1	3.1
15°	9.3	6.2	6.2	6.2	3.1	3.1	3.1	3.1	3.1	0.0	0.0
17.5°	6.2	3.1	3.1	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	18.5	18.5
5°	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4
7.5°	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3
10°	6.2	6.2	6.2	6.2	6.2	6.2	3.1	3.1	3.1	3.1	3.1
12.5°	3.1	3.1	3.1	3.1	3.1	3.1	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	18.5	18.5	18.5	18.5	18.5	21.6	21.6	24.7	24.7	27.8	27.8
5°	12.4	12.4	15.5	15.5	15.5	15.5	18.5	18.5	18.5	21.6	21.6
7.5°	9.3	9.3	9.3	9.3	9.3	12.4	12.4	15.5	15.5	18.5	18.5
10°	3.1	3.1	6.2	6.2	6.2	6.2	9.3	9.3	9.3	12.4	15.5
12.5°	0.0	0.0	3.1	3.1	3.1	3.1	6.2	6.2	6.2	9.3	12.4
15°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1	6.2	9.3
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	6.2
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	30.9	30.9	34.0	34.0	37.1	37.1	40.2	40.2	40.2	40.2	40.2
5°	24.7	24.7	27.8	30.9	30.9	34.0	37.1	37.1	37.1	37.1	37.1
7.5°	21.6	21.6	24.7	27.8	27.8	30.9	34.0	34.0	37.1	37.1	37.1
10°	15.5	18.5	21.6	24.7	24.7	27.8	30.9	30.9	34.0	34.0	34.0
12.5°	12.4	15.5	18.5	21.6	21.6	24.7	27.8	27.8	30.9	30.9	34.0
15°	9.3	12.4	15.5	18.5	18.5	21.6	24.7	24.7	27.8	30.9	34.0
17.5°	6.2	9.3	12.4	15.5	15.5	18.5	21.6	24.7	27.8	27.8	30.9
20°	6.2	6.2	9.3	12.4	12.4	15.5	18.5	21.6	24.7	24.7	27.8
22.5°	3.1	3.1	6.2	9.3	9.3	12.4	15.5	18.5	21.6	21.6	24.7
25°	0.0	0.0	3.1	6.2	6.2	9.3	12.4	12.4	15.5	15.5	18.5
27.5°	0.0	0.0	3.1	3.1	6.2	6.2	9.3	9.3	12.4	12.4	15.5
30°	0.0	0.0	3.1	3.1	6.2	6.2	9.3	9.3	12.4	12.4	12.4
32.5°	0.0	0.0	0.0	3.1	3.1	3.1	6.2	6.2	9.3	9.3	12.4
35°	0.0	0.0	0.0	3.1	3.1	3.1	6.2	6.2	9.3	9.3	9.3
37.5°	0.0	0.0	0.0	3.1	3.1	3.1	6.2	6.2	6.2	6.2	9.3
40°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	6.2	6.2	6.2
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	6.2	6.2	6.2
45°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	6.2	6.2	6.2
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	6.2	6.2	6.2
50°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	6.2	6.2	6.2
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1	3.1	3.1
55°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1	3.1	3.1
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1
75°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1	3.1	3.1
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	6.2	6.2	6.2
80°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	6.2	6.2	6.2
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1	3.1	6.2
85°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1	3.1	3.1
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.1	3.1	3.1	3.1	3.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	40.2	40.2
5°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	37.1	37.1
7.5°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	37.1	37.1
10°	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1
12.5°	34.0	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1
15°	34.0	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1
17.5°	30.9	34.0	34.0	34.0	37.1	37.1	37.1	37.1	37.1	37.1	37.1
20°	27.8	30.9	30.9	30.9	34.0	34.0	34.0	34.0	37.1	37.1	37.1
22.5°	24.7	27.8	27.8	27.8	30.9	30.9	30.9	30.9	34.0	34.0	34.0
25°	21.6	21.6	24.7	24.7	27.8	27.8	27.8	27.8	27.8	27.8	27.8
27.5°	15.5	18.5	18.5	18.5	21.6	21.6	21.6	21.6	24.7	24.7	24.7
30°	15.5	15.5	15.5	15.5	18.5	18.5	18.5	18.5	21.6	21.6	21.6
32.5°	12.4	15.5	15.5	15.5	18.5	18.5	18.5	18.5	21.6	21.6	21.6
35°	12.4	12.4	12.4	12.4	15.5	15.5	15.5	15.5	18.5	18.5	18.5
37.5°	9.3	12.4	12.4	12.4	15.5	15.5	15.5	15.5	18.5	18.5	18.5
40°	9.3	9.3	9.3	9.3	12.4	12.4	12.4	12.4	15.5	15.5	15.5
42.5°	9.3	9.3	9.3	9.3	12.4	12.4	12.4	12.4	15.5	15.5	15.5
45°	9.3	9.3	9.3	9.3	12.4	12.4	12.4	12.4	15.5	15.5	15.5
47.5°	9.3	9.3	9.3	9.3	12.4	12.4	12.4	12.4	15.5	15.5	15.5
50°	9.3	9.3	9.3	9.3	12.4	12.4	12.4	12.4	15.5	15.5	15.5
52.5°	6.2	6.2	6.2	6.2	9.3	9.3	9.3	9.3	12.4	12.4	12.4
55°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	9.3	9.3	9.3
57.5°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	9.3	9.3	9.3
60°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
62.5°	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
65°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	3.1	3.1
67.5°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
70°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
72.5°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
75°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
77.5°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
80°	9.3	9.3	9.3	9.3	9.3	6.2	6.2	6.2	6.2	6.2	6.2
82.5°	6.2	9.3	9.3	9.3	9.3	6.2	6.2	6.2	6.2	6.2	6.2
85°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
87.5°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	40.2	40.2	37.1	37.1	37.1	37.1	37.1	37.1	37.1	40.2	40.2
5°	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	40.2	40.2
7.5°	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	40.2	40.2
10°	37.1	37.1	37.1	37.1	34.0	34.0	37.1	37.1	37.1	40.2	40.2
12.5°	37.1	37.1	37.1	37.1	34.0	34.0	37.1	37.1	40.2	40.2	43.3
15°	37.1	37.1	34.0	34.0	34.0	34.0	37.1	37.1	40.2	40.2	43.3
17.5°	37.1	37.1	34.0	34.0	34.0	34.0	37.1	37.1	40.2	40.2	43.3
20°	37.1	37.1	34.0	34.0	34.0	34.0	34.0	34.0	37.1	40.2	40.2
22.5°	34.0	34.0	34.0	34.0	30.9	30.9	34.0	34.0	37.1	40.2	40.2
25°	27.8	30.9	30.9	30.9	30.9	30.9	34.0	34.0	37.1	40.2	40.2
27.5°	24.7	27.8	27.8	27.8	27.8	30.9	30.9	34.0	37.1	40.2	40.2
30°	21.6	24.7	24.7	24.7	27.8	30.9	30.9	34.0	37.1	40.2	40.2
32.5°	21.6	24.7	24.7	24.7	27.8	27.8	30.9	30.9	34.0	37.1	40.2
35°	21.6	21.6	24.7	24.7	24.7	27.8	27.8	30.9	34.0	37.1	40.2
37.5°	21.6	21.6	24.7	24.7	24.7	27.8	27.8	30.9	34.0	37.1	40.2
40°	18.5	21.6	21.6	24.7	24.7	27.8	27.8	30.9	34.0	40.2	43.3
42.5°	18.5	18.5	21.6	21.6	24.7	27.8	27.8	30.9	34.0	40.2	43.3
45°	18.5	21.6	21.6	24.7	27.8	30.9	30.9	34.0	37.1	40.2	43.3
47.5°	18.5	21.6	21.6	24.7	30.9	30.9	34.0	34.0	37.1	40.2	43.3
50°	18.5	21.6	21.6	24.7	34.0	34.0	34.0	34.0	37.1	40.2	43.3
52.5°	15.5	18.5	18.5	21.6	27.8	30.9	34.0	37.1	40.2	43.3	46.4
55°	12.4	15.5	15.5	18.5	24.7	27.8	34.0	40.2	43.3	46.4	49.5
57.5°	12.4	12.4	15.5	15.5	21.6	27.8	37.1	43.3	46.4	49.5	52.5
60°	9.3	9.3	12.4	12.4	18.5	24.7	34.0	43.3	46.4	52.5	55.6
62.5°	6.2	9.3	9.3	12.4	15.5	24.7	34.0	43.3	49.5	55.6	58.7
65°	6.2	6.2	9.3	9.3	15.5	21.6	30.9	37.1	46.4	55.6	64.9
67.5°	9.3	9.3	12.4	12.4	15.5	21.6	30.9	37.1	46.4	58.7	68.0
70°	9.3	9.3	12.4	12.4	18.5	24.7	30.9	37.1	46.4	58.7	68.0
72.5°	9.3	9.3	12.4	12.4	18.5	21.6	27.8	34.0	43.3	52.5	61.8
75°	6.2	9.3	9.3	9.3	15.5	18.5	24.7	30.9	40.2	49.5	58.7
77.5°	6.2	6.2	6.2	6.2	12.4	15.5	21.6	24.7	34.0	43.3	52.5
80°	6.2	6.2	6.2	6.2	9.3	12.4	18.5	21.6	30.9	40.2	49.5
82.5°	6.2	6.2	3.1	3.1	6.2	9.3	12.4	15.5	24.7	30.9	40.2
85°	6.2	6.2	3.1	3.1	3.1	6.2	6.2	9.3	12.4	15.5	18.5
87.5°	6.2	6.2	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	40.2	40.2	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3
5°	40.2	43.3	43.3	46.4	46.4	46.4	49.5	49.5	49.5	49.5	49.5
7.5°	40.2	43.3	43.3	46.4	46.4	46.4	49.5	49.5	49.5	52.5	52.5
10°	40.2	43.3	43.3	46.4	46.4	49.5	52.5	52.5	55.6	55.6	55.6
12.5°	43.3	46.4	46.4	49.5	49.5	52.5	55.6	55.6	58.7	61.8	61.8
15°	43.3	46.4	49.5	49.5	52.5	55.6	58.7	58.7	61.8	64.9	68.0
17.5°	43.3	46.4	49.5	49.5	52.5	55.6	61.8	64.9	68.0	74.2	77.3
20°	43.3	46.4	49.5	49.5	52.5	58.7	61.8	68.0	71.1	77.3	83.5
22.5°	43.3	46.4	49.5	52.5	55.6	61.8	68.0	71.1	77.3	86.5	92.7
25°	43.3	46.4	49.5	52.5	55.6	61.8	68.0	74.2	80.4	92.7	105.1
27.5°	43.3	46.4	52.5	55.6	58.7	64.9	74.2	80.4	86.5	108.2	129.8
30°	43.3	46.4	52.5	55.6	58.7	68.0	77.3	83.5	92.7	129.8	163.8
32.5°	43.3	49.5	52.5	58.7	61.8	71.1	83.5	92.7	102.0	154.5	204.0
35°	43.3	49.5	52.5	58.7	61.8	74.2	86.5	98.9	111.3	188.5	265.8
37.5°	43.3	49.5	52.5	58.7	61.8	80.4	98.9	117.5	136.0	216.4	296.7
40°	46.4	52.5	55.6	61.8	64.9	83.5	102.0	120.5	139.1	219.5	299.8
42.5°	46.4	52.5	55.6	61.8	64.9	80.4	98.9	114.4	129.8	219.5	309.1
45°	46.4	52.5	58.7	61.8	68.0	83.5	98.9	111.3	126.7	241.1	352.4
47.5°	46.4	52.5	58.7	61.8	68.0	83.5	98.9	114.4	129.8	318.4	503.8
50°	46.4	52.5	58.7	61.8	68.0	86.5	105.1	123.6	142.2	476.0	809.8
52.5°	49.5	52.5	58.7	61.8	64.9	86.5	108.2	129.8	151.5	618.2	1081.8
55°	52.5	55.6	58.7	61.8	64.9	92.7	120.5	148.4	176.2	664.5	1149.8
57.5°	55.6	58.7	61.8	61.8	64.9	98.9	136.0	170.0	204.0	661.5	1115.8
60°	58.7	61.8	64.9	68.0	71.1	105.1	142.2	176.2	210.2	599.6	989.1
62.5°	64.9	71.1	77.3	80.4	86.5	120.5	151.5	185.5	216.4	491.5	763.5
65°	74.2	80.4	83.5	89.6	92.7	123.6	157.6	188.5	219.5	408.0	593.5
67.5°	77.3	83.5	86.5	92.7	95.8	126.7	157.6	188.5	219.5	346.2	469.8
70°	77.3	83.5	89.6	92.7	98.9	129.8	157.6	188.5	216.4	299.8	383.3
72.5°	71.1	80.4	86.5	95.8	102.0	129.8	154.5	182.4	207.1	265.8	324.5
75°	68.0	80.4	89.6	102.0	111.3	129.8	151.5	170.0	188.5	231.8	275.1
77.5°	61.8	77.3	92.7	108.2	123.6	136.0	145.3	157.6	166.9	194.7	222.5
80°	58.7	74.2	89.6	105.1	120.5	126.7	129.8	136.0	139.1	142.2	145.3
82.5°	46.4	58.7	71.1	80.4	92.7	86.5	83.5	77.3	71.1	68.0	64.9
85°	21.6	24.7	24.7	27.8	27.8	27.8	24.7	24.7	21.6	18.5	15.5
87.5°	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	43.3	43.3	43.3	43.3	40.2	40.2	40.2	40.2	37.1	37.1	37.1
5°	49.5	49.5	49.5	49.5	46.4	46.4	46.4	46.4	43.3	43.3	43.3
7.5°	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5
10°	58.7	58.7	58.7	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8
12.5°	64.9	64.9	68.0	68.0	71.1	71.1	74.2	74.2	77.3	77.3	77.3
15°	71.1	74.2	77.3	80.4	80.4	83.5	86.5	89.6	92.7	95.8	98.9
17.5°	83.5	86.5	92.7	98.9	105.1	111.3	120.5	132.9	142.2	151.5	163.8
20°	92.7	102.0	120.5	142.2	160.7	179.3	225.6	272.0	318.4	364.7	411.1
22.5°	111.3	129.8	191.6	256.5	318.4	380.2	525.5	670.7	812.9	958.2	1088.0
25°	148.4	188.5	330.7	472.9	612.0	754.2	1013.8	1276.5	1536.2	1795.8	2036.9
27.5°	204.0	278.2	510.0	744.9	976.7	1208.5	1585.6	1965.8	2342.9	2723.1	3060.0
30°	284.4	404.9	751.1	1100.4	1446.5	1792.7	2268.7	2747.8	3223.8	3699.8	4008.9
32.5°	386.4	565.6	1004.5	1443.5	1882.4	2321.3	2846.7	3372.2	3894.5	4420.0	4747.6
35°	494.5	723.3	1251.8	1783.5	2312.0	2843.6	3396.9	3950.2	4503.5	5056.7	5458.5
37.5°	556.4	816.0	1443.5	2070.9	2695.3	3322.7	3928.5	4537.5	5143.3	5749.1	6237.5
40°	615.1	927.3	1650.5	2373.8	3097.1	3820.4	4528.2	5236.0	5943.8	6651.6	7279.1
42.5°	701.6	1094.2	1938.0	2781.8	3622.5	4466.4	5396.7	6330.2	7260.5	8190.9	9155.3
45°	880.9	1409.5	2503.6	3597.8	4688.9	5783.1	7102.9	8425.8	9745.6	11068.6	12304.9
47.5°	1313.6	2120.4	3613.3	5106.2	6599.1	8092.0	9612.7	11133.5	12654.2	14174.9	15646.2
50°	2033.8	3254.7	5121.6	6988.5	8852.4	10719.3	12236.9	13754.6	15269.1	16786.7	18248.7
52.5°	2710.7	4339.6	6345.6	8354.7	10360.7	12369.8	13714.4	15058.9	16403.5	17748.0	19163.6
55°	2942.5	4732.2	6762.9	8796.7	10827.5	12861.3	14156.4	15454.6	16749.6	18044.7	19512.9
57.5°	2738.5	4361.3	6407.5	8453.6	10496.7	12542.9	13989.5	15439.1	16885.6	18335.3	19908.6
60°	2293.5	3594.7	5742.9	7894.2	10042.4	12190.6	13822.6	15454.6	17086.6	18718.6	20288.7
62.5°	1817.5	2868.4	5143.3	7418.2	9693.1	11968.0	13627.8	15290.7	16950.6	18610.4	19815.8
65°	1394.0	2194.5	4432.4	6673.3	8911.1	11152.0	12512.0	13875.1	15235.1	16598.2	17432.7
67.5°	1035.5	1601.1	3557.6	5517.3	7473.8	9430.4	10431.8	11436.4	12437.8	13442.4	14091.5
70°	763.5	1140.5	2472.7	3804.9	5134.0	6466.2	7384.2	8302.2	9217.1	10135.1	10808.9
72.5°	528.5	729.5	1526.9	2327.5	3124.9	3922.4	4852.7	5783.1	6710.4	7640.7	8407.3
75°	361.6	448.2	822.2	1196.2	1570.2	1944.2	2648.9	3353.6	4058.4	4763.1	5168.0
77.5°	268.9	315.3	426.5	540.9	652.2	763.5	899.5	1035.5	1171.5	1307.5	1483.6
80°	148.4	148.4	163.8	176.2	191.6	204.0	241.1	281.3	318.4	358.5	408.0
82.5°	68.0	71.1	77.3	83.5	86.5	92.7	98.9	105.1	111.3	117.5	117.5
85°	18.5	21.6	21.6	18.5	18.5	15.5	15.5	18.5	18.5	18.5	18.5
87.5°	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	37.1	34.0	34.0	34.0	30.9	30.9	30.9	30.9	30.9	30.9	30.9
5°	43.3	43.3	43.3	43.3	40.2	40.2	40.2	40.2	40.2	37.1	37.1
7.5°	52.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	46.4	46.4
10°	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8	58.7	58.7
12.5°	77.3	77.3	77.3	77.3	80.4	80.4	77.3	77.3	77.3	74.2	74.2
15°	102.0	105.1	108.2	108.2	111.3	111.3	111.3	108.2	108.2	105.1	102.0
17.5°	173.1	182.4	194.7	207.1	219.5	228.7	228.7	222.5	216.4	210.2	204.0
20°	460.5	506.9	556.4	605.8	658.4	695.5	670.7	652.2	633.6	612.0	593.5
22.5°	1220.9	1350.7	1483.6	1576.4	1669.1	1734.0	1681.5	1579.5	1477.5	1378.5	1276.5
25°	2278.0	2516.0	2757.1	2856.0	2958.0	3032.2	2998.2	2843.6	2689.1	2537.6	2383.1
27.5°	3396.9	3730.7	4067.6	4154.2	4240.7	4305.6	4293.3	4092.4	3891.5	3690.5	3489.6
30°	4318.0	4627.1	4936.2	5022.7	5109.3	5168.0	5103.1	4902.2	4701.3	4500.4	4299.5
32.5°	5078.4	5406.0	5736.7	5851.1	5965.5	6042.7	5965.5	5724.4	5483.3	5245.3	5004.2
35°	5860.4	6259.1	6660.9	6806.2	6951.5	7044.2	6914.4	6617.6	6320.9	6027.3	5730.5
37.5°	6725.8	7211.1	7699.5	7897.3	8098.2	8237.3	8138.4	7767.5	7393.5	7022.5	6648.5
40°	7909.6	8537.1	9167.6	9523.1	9875.5	10125.8	9949.6	9520.0	9087.3	8657.6	8224.9
42.5°	10122.7	11087.1	12051.5	12561.5	13068.4	13436.2	13238.4	12709.8	12181.3	11652.7	11124.2
45°	13541.3	14774.6	16010.9	16755.8	17503.8	18054.0	17825.3	17160.7	16493.1	15828.6	15164.0
47.5°	17117.5	18588.7	20060.0	20653.5	21250.0	21713.6	21658.0	20829.6	20001.3	19176.0	18347.6
50°	19713.8	21175.8	22637.8	23147.8	23660.9	24041.1	23898.9	22844.9	21787.8	20733.8	19676.7
52.5°	20579.3	21991.8	23407.5	24016.4	24625.3	25079.6	24906.6	23719.6	22532.7	21348.9	20162.0
55°	20981.1	22449.3	23917.5	24659.3	25404.2	25948.2	25697.8	24396.6	23092.2	21790.9	20486.6
57.5°	21481.8	23055.1	24628.4	25441.3	26254.2	26841.5	26507.6	25160.0	23812.4	22467.8	21120.2
60°	21858.9	23426.0	24996.2	25648.4	26303.6	26761.1	26439.6	25129.1	23815.5	22504.9	21194.4
62.5°	21024.4	22229.8	23435.3	23920.6	24405.8	24758.2	24575.8	23333.3	22090.7	20848.2	19605.6
65°	18270.4	19104.9	19942.6	20270.2	20594.7	20845.1	20789.5	19741.6	18693.8	17649.1	16601.3
67.5°	14743.6	15392.7	16044.9	16508.6	16975.3	17336.9	17296.7	16341.6	15386.6	14431.5	13476.4
70°	11485.8	12159.6	12833.5	13417.6	14004.9	14459.3	14400.6	13513.5	12623.3	11736.2	10846.0
72.5°	9176.9	9943.5	10710.0	11043.8	11377.6	11612.6	11439.5	10768.7	10094.9	9424.2	8750.4
75°	5572.9	5974.7	6379.6	6376.5	6376.5	6339.5	6166.4	5783.1	5399.8	5016.5	4633.3
77.5°	1659.8	1836.0	2012.2	2182.2	2355.3	2485.1	2451.1	2250.2	2046.2	1845.3	1641.3
80°	457.5	503.8	553.3	574.9	596.5	624.4	695.5	646.0	596.5	550.2	500.7
82.5°	117.5	117.5	117.5	114.4	111.3	105.1	95.8	89.6	83.5	77.3	71.1
85°	18.5	15.5	15.5	15.5	12.4	12.4	12.4	12.4	9.3	9.3	6.2
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8
2.5°	30.9	30.9	27.8	27.8	27.8	27.8	27.8	27.8	27.8	27.8	24.7
5°	37.1	37.1	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0	30.9
7.5°	46.4	46.4	43.3	43.3	43.3	43.3	40.2	40.2	40.2	40.2	37.1
10°	58.7	55.6	55.6	52.5	52.5	52.5	49.5	49.5	49.5	46.4	46.4
12.5°	74.2	71.1	71.1	68.0	64.9	64.9	61.8	58.7	55.6	55.6	52.5
15°	98.9	95.8	92.7	89.6	86.5	80.4	77.3	71.1	68.0	64.9	61.8
17.5°	188.5	173.1	157.6	142.2	129.8	117.5	105.1	92.7	86.5	80.4	74.2
20°	525.5	454.4	386.4	318.4	275.1	231.8	188.5	145.3	126.7	111.3	92.7
22.5°	1137.5	995.3	856.2	714.0	599.6	488.4	374.0	259.6	216.4	176.2	132.9
25°	2114.2	1842.2	1573.3	1301.3	1084.9	868.5	652.2	435.8	355.5	275.1	194.7
27.5°	3137.3	2784.9	2432.5	2080.2	1737.1	1390.9	1044.7	701.6	562.5	426.5	287.5
30°	3925.5	3551.5	3180.5	2806.5	2373.8	1941.1	1505.3	1072.5	853.1	633.6	411.1
32.5°	4602.4	4197.5	3795.6	3390.7	2890.0	2389.3	1888.5	1387.8	1112.7	837.6	559.5
35°	5273.1	4812.5	4355.1	3894.5	3356.7	2818.9	2281.1	1743.3	1394.0	1044.7	692.4
37.5°	6089.1	5526.5	4967.1	4407.6	3854.4	3304.2	2750.9	2197.6	1752.5	1310.5	865.5
40°	7510.9	6793.8	6079.8	5362.7	4716.7	4073.8	3427.8	2781.8	2222.4	1662.9	1100.4
42.5°	10224.7	9325.3	8428.9	7529.5	6636.2	5742.9	4846.5	3953.3	3155.8	2361.5	1564.0
45°	14011.1	12858.2	11708.4	10555.5	9455.1	8357.8	7257.5	6157.1	4945.5	3733.8	2519.1
47.5°	17086.6	15822.4	14561.3	13297.1	12076.2	10858.4	9637.5	8416.5	6864.9	5316.4	3764.7
50°	18474.4	17268.9	16066.6	14861.1	13637.1	12410.0	11182.9	9958.9	8178.5	6401.3	4620.9
52.5°	18941.1	17717.1	16496.2	15272.2	14057.5	12842.7	11628.0	10413.3	8561.8	6713.5	4862.0
55°	19197.6	17905.6	16616.7	15324.7	14017.3	12706.7	11396.2	10088.7	8246.5	6407.5	4565.3
57.5°	19716.9	18310.6	16907.3	15500.9	14011.1	12521.3	11028.4	9538.5	7721.1	5903.6	4086.2
60°	19812.7	18428.0	17046.4	15664.7	14017.3	12369.8	10719.3	9071.8	7266.7	5464.7	3659.6
62.5°	18449.6	17293.6	16140.7	14984.7	13334.2	11683.6	10030.0	8379.5	6651.6	4923.8	3192.9
65°	15602.9	14604.6	13609.3	12610.9	11263.3	9918.7	8571.1	7223.5	5681.1	4141.8	2599.5
67.5°	12499.6	11522.9	10549.3	9572.5	8558.7	7548.0	6534.2	5520.4	4330.4	3140.4	1950.4
70°	9909.5	8969.8	8033.3	7093.6	6197.3	5297.8	4398.4	3502.0	2763.3	2027.6	1288.9
72.5°	7854.0	6954.5	6058.2	5158.7	4345.8	3532.9	2720.0	1907.1	1539.3	1174.5	806.7
75°	4166.5	3699.8	3236.2	2769.5	2312.0	1851.5	1390.9	933.5	788.2	642.9	494.5
77.5°	1437.3	1233.3	1032.4	828.4	689.3	550.2	411.1	272.0	256.5	244.2	228.7
80°	435.8	370.9	306.0	241.1	213.3	185.5	157.6	129.8	120.5	111.3	98.9
82.5°	68.0	61.8	58.7	52.5	49.5	49.5	46.4	43.3	37.1	34.0	27.8
85°	6.2	3.1	3.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066532
 CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	27.8	27.8
2.5°	24.7	24.7
5°	30.9	30.9
7.5°	37.1	37.1
10°	43.3	43.3
12.5°	49.5	49.5
15°	58.7	55.6
17.5°	68.0	64.9
20°	74.2	68.0
22.5°	89.6	77.3
25°	114.4	95.8
27.5°	148.4	117.5
30°	191.6	148.4
32.5°	284.4	207.1
35°	343.1	250.4
37.5°	420.4	290.5
40°	540.9	352.4
42.5°	766.5	479.1
45°	1307.5	794.4
47.5°	2216.2	1353.8
50°	2840.5	1737.1
52.5°	3013.6	1842.2
55°	2726.2	1690.7
57.5°	2268.7	1437.3
60°	1857.6	1183.8
62.5°	1465.1	936.5
65°	1057.1	707.8
67.5°	760.4	544.0
70°	553.3	426.5
72.5°	438.9	355.5
75°	349.3	296.7
77.5°	216.4	197.8
80°	89.6	83.5
82.5°	21.6	18.5
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066532

CATALOG NUMBER: NVN-SA2D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-5

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-735-U-5WQ

Data in this report applies to families of products including GSS-SB1A-735-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-735-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3369
 CIE u' : 0.2386
 CIE v' : 0.5156
 Duv: 0.0013
 CIE x: 0.4143
 CIE y: 0.3980
 CIE z: 0.1877
 Peak Wavelength (nm): 590
 Dominant Wavelength (nm): 580
 Purity: 43.80166
 R_f: 71.4
 R_g: 96

CRI (Ra): 70.1
 R1: 66.6
 R2: 77.6
 R3: 88.5
 R4: 69.5
 R5: 66.4
 R6: 69.6
 R7: 77.5
 R8: 44.9
 R9: -40.2
 R10: 49.1
 R11: 66.3
 R12: 45.7
 R13: 68.0
 R14: 93.4
 R15: 57.6



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-5

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-5

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.29

λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.36


λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5





TM-30-18

Summary

$R_f = 71.4$
 $R_g = 96$
 CIE $R_a = 70.1$
 $R_g = -40.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 57	CES51 = 84	CES76 = 50
CES02 = 62	CES27 = 80	CES52 = 86	CES77 = 74
CES03 = 31	CES28 = 81	CES53 = 72	CES78 = 54
CES04 = 70	CES29 = 50	CES54 = 79	CES79 = 81
CES05 = 48	CES30 = 55	CES55 = 78	CES80 = 79
CES06 = 51	CES31 = 56	CES56 = 67	CES81 = 74
CES07 = 40	CES32 = 54	CES57 = 65	CES82 = 91
CES08 = 39	CES33 = 60	CES58 = 68	CES83 = 86
CES09 = 29	CES34 = 69	CES59 = 85	CES84 = 89
CES10 = 75	CES35 = 83	CES60 = 91	CES85 = 83
CES11 = 58	CES36 = 88	CES61 = 85	CES86 = 66
CES12 = 64	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 43	CES38 = 64	CES63 = 71	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 70	CES89 = 68
CES15 = 71	CES40 = 86	CES65 = 64	CES90 = 72
CES16 = 47	CES41 = 81	CES66 = 65	CES91 = 95
CES17 = 50	CES42 = 79	CES67 = 63	CES92 = 62
CES18 = 56	CES43 = 71	CES68 = 69	CES93 = 78
CES19 = 72	CES44 = 98	CES69 = 80	CES94 = 51
CES20 = 65	CES45 = 80	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 75	CES71 = 58	CES96 = 76
CES22 = 79	CES47 = 71	CES72 = 85	CES97 = 82
CES23 = 92	CES48 = 61	CES73 = 51	CES98 = 72
CES24 = 91	CES49 = 74	CES74 = 94	CES99 = 60
CES25 = 72	CES50 = 83	CES75 = 57	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)