

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066534

Luminaire Tested: **NVN-SA3B-735-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066534
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA3B-735-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 3xLight Square PACKAGE
70CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 3500K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 10766.8 lumens
Efficiency: N/A
Efficacy: 101.4 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 106.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.1 fc
 Type III - Short - N/A

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	64.1	0.0	64.1
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	10702.8	0.0	10702.8
	% Fixture	99.4	0.0	99.4
Total	Lumens	10766.8	0.0	10766.8
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.2	0.0
10°-20°	15.8	0.1
20°-30°	201.0	1.9
30°-40°	677.3	6.3
40°-50°	2045.4	19.0
50°-60°	3608.7	33.5
60°-70°	3179.2	29.5
70°-80°	1012.0	9.4
80°-90°	24.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	10766.8	100.0
0°-180°	10766.8	100.0



REPORT NUMBER: P1066534


CATALOG NUMBER: NVN-SA3B-735-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	210.3	2.0			
FM	(30°-60°)	6306.5	58.6			
FH	(60°-80°)	4166.2	38.7			G2/5000
FVH	(80°-90°)	19.8	0.2			G1/100
BL	(0°-30°)	9.6	0.1	B0/110		
BM	(30°-60°)	24.8	0.2	B0/220		
BH	(60°-80°)	25.1	0.2	B0/110		G0/110
BVH	(80°-90°)	4.5	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0	23.6
5°	33.8	33.8	33.8	30.4	30.4	30.4	27.0	27.0	27.0	27.0	27.0
7.5°	40.5	37.1	37.1	33.8	33.8	33.8	30.4	30.4	30.4	30.4	27.0
10°	47.3	43.9	43.9	40.5	40.5	37.1	37.1	33.8	33.8	30.4	30.4
12.5°	54.0	50.6	47.3	43.9	43.9	40.5	40.5	37.1	37.1	33.8	33.8
15°	60.8	57.4	54.0	50.6	47.3	47.3	43.9	40.5	37.1	37.1	33.8
17.5°	70.9	64.2	60.8	54.0	50.6	47.3	43.9	40.5	40.5	37.1	37.1
20°	74.3	67.5	64.2	57.4	54.0	50.6	47.3	43.9	40.5	40.5	37.1
22.5°	87.8	74.3	70.9	64.2	60.8	57.4	50.6	47.3	43.9	40.5	37.1
25°	108.0	87.8	77.7	67.5	64.2	57.4	54.0	47.3	43.9	40.5	37.1
27.5°	131.7	97.9	87.8	74.3	67.5	60.8	54.0	47.3	43.9	40.5	37.1
30°	162.1	114.8	97.9	81.0	74.3	67.5	57.4	50.6	47.3	43.9	37.1
32.5°	226.2	141.8	114.8	87.8	77.7	70.9	60.8	50.6	47.3	43.9	37.1
35°	273.5	172.2	138.4	101.3	87.8	77.7	64.2	50.6	47.3	43.9	37.1
37.5°	317.4	175.6	141.8	108.0	94.5	81.0	64.2	50.6	47.3	43.9	37.1
40°	388.3	182.3	141.8	101.3	91.2	77.7	67.5	54.0	50.6	43.9	40.5
42.5°	523.4	209.3	151.9	94.5	84.4	77.7	67.5	57.4	50.6	47.3	40.5
45°	871.1	310.6	206.0	97.9	87.8	77.7	67.5	57.4	54.0	47.3	43.9
47.5°	1482.3	540.2	320.8	101.3	91.2	77.7	67.5	54.0	50.6	47.3	40.5
50°	1897.6	692.2	405.2	118.2	101.3	87.8	70.9	54.0	50.6	47.3	43.9
52.5°	2015.7	736.1	438.9	138.4	118.2	97.9	74.3	54.0	50.6	50.6	47.3
55°	1846.9	715.8	438.9	162.1	135.1	111.4	84.4	57.4	54.0	54.0	50.6
57.5°	1570.1	661.8	418.7	175.6	148.6	118.2	91.2	60.8	57.4	57.4	54.0
60°	1293.2	557.1	378.2	195.8	165.4	135.1	104.7	74.3	70.9	67.5	60.8
62.5°	1026.4	449.1	330.9	209.3	179.0	145.2	114.8	81.0	77.7	74.3	70.9
65°	773.2	391.7	307.3	219.5	185.7	151.9	118.2	84.4	81.0	81.0	77.7
67.5°	594.3	357.9	293.8	226.2	192.5	158.7	124.9	91.2	87.8	84.4	81.0
70°	469.3	330.9	276.9	222.8	192.5	162.1	128.3	97.9	91.2	87.8	81.0
72.5°	391.7	300.5	256.6	212.7	189.1	165.4	141.8	118.2	104.7	94.5	81.0
75°	327.5	270.1	233.0	192.5	175.6	162.1	145.2	128.3	111.4	94.5	77.7
77.5°	216.1	195.8	179.0	162.1	151.9	141.8	128.3	118.2	101.3	87.8	70.9
80°	91.2	84.4	87.8	87.8	87.8	87.8	84.4	84.4	74.3	64.2	50.6
82.5°	20.3	16.9	20.3	20.3	20.3	20.3	16.9	16.9	16.9	13.5	13.5
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6
5°	27.0	27.0	27.0	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6
7.5°	27.0	27.0	27.0	23.6	23.6	23.6	23.6	20.3	20.3	20.3	20.3
10°	27.0	27.0	27.0	23.6	23.6	23.6	23.6	20.3	20.3	20.3	20.3
12.5°	30.4	30.4	27.0	27.0	23.6	23.6	23.6	20.3	20.3	20.3	20.3
15°	30.4	30.4	27.0	27.0	23.6	23.6	23.6	20.3	20.3	20.3	20.3
17.5°	33.8	30.4	30.4	27.0	23.6	23.6	23.6	20.3	20.3	20.3	20.3
20°	33.8	30.4	30.4	27.0	23.6	23.6	23.6	20.3	20.3	20.3	20.3
22.5°	33.8	30.4	30.4	27.0	23.6	23.6	20.3	20.3	16.9	16.9	13.5
25°	33.8	30.4	30.4	27.0	23.6	23.6	20.3	20.3	16.9	13.5	13.5
27.5°	33.8	30.4	30.4	27.0	23.6	20.3	20.3	16.9	13.5	10.1	10.1
30°	33.8	30.4	30.4	27.0	23.6	20.3	16.9	13.5	10.1	10.1	6.8
32.5°	33.8	30.4	27.0	23.6	20.3	16.9	16.9	13.5	10.1	6.8	6.8
35°	33.8	30.4	27.0	23.6	20.3	16.9	16.9	13.5	10.1	6.8	6.8
37.5°	33.8	30.4	27.0	23.6	20.3	16.9	13.5	10.1	6.8	6.8	3.4
40°	33.8	30.4	27.0	23.6	20.3	16.9	13.5	10.1	6.8	6.8	3.4
42.5°	33.8	30.4	27.0	23.6	20.3	16.9	13.5	10.1	6.8	6.8	3.4
45°	37.1	33.8	30.4	23.6	20.3	16.9	16.9	13.5	10.1	6.8	6.8
47.5°	37.1	33.8	30.4	23.6	20.3	16.9	16.9	13.5	10.1	6.8	6.8
50°	40.5	37.1	33.8	27.0	23.6	20.3	16.9	10.1	6.8	6.8	3.4
52.5°	43.9	40.5	37.1	33.8	30.4	23.6	16.9	10.1	3.4	3.4	3.4
55°	47.3	43.9	43.9	40.5	37.1	27.0	20.3	10.1	0.0	0.0	0.0
57.5°	50.6	47.3	47.3	43.9	40.5	30.4	20.3	10.1	0.0	0.0	0.0
60°	57.4	54.0	50.6	43.9	40.5	30.4	20.3	10.1	0.0	0.0	0.0
62.5°	67.5	60.8	50.6	43.9	33.8	27.0	16.9	10.1	0.0	0.0	0.0
65°	74.3	64.2	54.0	40.5	30.4	23.6	16.9	6.8	0.0	0.0	0.0
67.5°	77.7	64.2	54.0	40.5	27.0	20.3	13.5	6.8	0.0	0.0	0.0
70°	74.3	60.8	50.6	37.1	23.6	16.9	13.5	6.8	0.0	0.0	0.0
72.5°	67.5	57.4	43.9	33.8	20.3	16.9	10.1	6.8	0.0	0.0	0.0
75°	60.8	50.6	37.1	27.0	13.5	10.1	6.8	3.4	0.0	0.0	0.0
77.5°	54.0	43.9	30.4	20.3	6.8	6.8	3.4	3.4	0.0	0.0	0.0
80°	40.5	30.4	20.3	10.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	10.1	6.8	6.8	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3
5°	20.3	20.3	20.3	20.3	16.9	16.9	16.9	16.9	16.9	16.9	16.9
7.5°	20.3	20.3	20.3	20.3	16.9	16.9	16.9	16.9	13.5	13.5	13.5
10°	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	13.5	13.5	13.5
12.5°	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	13.5	13.5	13.5
15°	16.9	16.9	16.9	16.9	16.9	16.9	16.9	13.5	13.5	10.1	10.1
17.5°	16.9	16.9	16.9	16.9	13.5	13.5	13.5	10.1	10.1	6.8	6.8
20°	16.9	16.9	16.9	13.5	13.5	10.1	10.1	6.8	6.8	3.4	3.4
22.5°	13.5	10.1	10.1	6.8	6.8	3.4	3.4	3.4	0.0	0.0	0.0
25°	10.1	6.8	6.8	3.4	3.4	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	6.8	3.4	3.4	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	6.8	3.4	3.4	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	20.3	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9
5°	16.9	16.9	16.9	16.9	13.5	13.5	13.5	13.5	13.5	13.5	13.5
7.5°	13.5	13.5	13.5	13.5	13.5	13.5	10.1	10.1	10.1	10.1	10.1
10°	13.5	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1	6.8	6.8
12.5°	13.5	10.1	10.1	10.1	6.8	6.8	6.8	6.8	6.8	3.4	3.4
15°	10.1	6.8	6.8	6.8	3.4	3.4	3.4	3.4	3.4	0.0	0.0
17.5°	6.8	3.4	3.4	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	16.9	20.3	20.3
5°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
7.5°	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1
10°	6.8	6.8	6.8	6.8	6.8	6.8	3.4	3.4	3.4	3.4	3.4
12.5°	3.4	3.4	3.4	3.4	3.4	3.4	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	20.3	20.3	20.3	20.3	20.3	23.6	23.6	27.0	27.0	30.4	30.4
5°	13.5	13.5	16.9	16.9	16.9	16.9	20.3	20.3	20.3	23.6	23.6
7.5°	10.1	10.1	10.1	10.1	10.1	13.5	13.5	16.9	16.9	20.3	20.3
10°	3.4	3.4	6.8	6.8	6.8	6.8	10.1	10.1	10.1	13.5	16.9
12.5°	0.0	0.0	3.4	3.4	3.4	3.4	6.8	6.8	6.8	10.1	13.5
15°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4	6.8	10.1
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	6.8
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	33.8	33.8	37.1	37.1	40.5	40.5	43.9	43.9	43.9	43.9	43.9
5°	27.0	27.0	30.4	33.8	33.8	37.1	40.5	40.5	40.5	40.5	40.5
7.5°	23.6	23.6	27.0	30.4	30.4	33.8	37.1	37.1	40.5	40.5	40.5
10°	16.9	20.3	23.6	27.0	27.0	30.4	33.8	33.8	37.1	37.1	37.1
12.5°	13.5	16.9	20.3	23.6	23.6	27.0	30.4	30.4	33.8	33.8	37.1
15°	10.1	13.5	16.9	20.3	20.3	23.6	27.0	27.0	30.4	33.8	37.1
17.5°	6.8	10.1	13.5	16.9	16.9	20.3	23.6	27.0	30.4	30.4	33.8
20°	6.8	6.8	10.1	13.5	13.5	16.9	20.3	23.6	27.0	27.0	30.4
22.5°	3.4	3.4	6.8	10.1	10.1	13.5	16.9	20.3	23.6	23.6	27.0
25°	0.0	0.0	3.4	6.8	6.8	10.1	13.5	13.5	16.9	16.9	20.3
27.5°	0.0	0.0	3.4	3.4	6.8	6.8	10.1	10.1	13.5	13.5	16.9
30°	0.0	0.0	3.4	3.4	6.8	6.8	10.1	10.1	13.5	13.5	13.5
32.5°	0.0	0.0	0.0	3.4	3.4	3.4	6.8	6.8	10.1	10.1	13.5
35°	0.0	0.0	0.0	3.4	3.4	3.4	6.8	6.8	10.1	10.1	10.1
37.5°	0.0	0.0	0.0	3.4	3.4	3.4	6.8	6.8	6.8	6.8	10.1
40°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	6.8	6.8	6.8
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	6.8	6.8	6.8
45°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	6.8	6.8	6.8
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	6.8	6.8	6.8
50°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	6.8	6.8	6.8
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4	3.4	3.4
55°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4	3.4	3.4
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4
75°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4	3.4	3.4
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	6.8	6.8	6.8
80°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	6.8	6.8	6.8
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4	3.4	6.8
85°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4	3.4	3.4
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.4	3.4	3.4	3.4	3.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	43.9	43.9
5°	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	40.5	40.5
7.5°	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	40.5	40.5
10°	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5
12.5°	37.1	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5
15°	37.1	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5
17.5°	33.8	37.1	37.1	37.1	40.5	40.5	40.5	40.5	40.5	40.5	40.5
20°	30.4	33.8	33.8	33.8	37.1	37.1	37.1	37.1	40.5	40.5	40.5
22.5°	27.0	30.4	30.4	30.4	33.8	33.8	33.8	33.8	37.1	37.1	37.1
25°	23.6	23.6	27.0	27.0	30.4	30.4	30.4	30.4	30.4	30.4	30.4
27.5°	16.9	20.3	20.3	20.3	23.6	23.6	23.6	23.6	27.0	27.0	27.0
30°	16.9	16.9	16.9	16.9	20.3	20.3	20.3	20.3	23.6	23.6	23.6
32.5°	13.5	16.9	16.9	16.9	20.3	20.3	20.3	20.3	23.6	23.6	23.6
35°	13.5	13.5	13.5	13.5	16.9	16.9	16.9	16.9	20.3	20.3	20.3
37.5°	10.1	13.5	13.5	13.5	16.9	16.9	16.9	16.9	20.3	20.3	20.3
40°	10.1	10.1	10.1	10.1	13.5	13.5	13.5	13.5	16.9	16.9	16.9
42.5°	10.1	10.1	10.1	10.1	13.5	13.5	13.5	13.5	16.9	16.9	16.9
45°	10.1	10.1	10.1	10.1	13.5	13.5	13.5	13.5	16.9	16.9	16.9
47.5°	10.1	10.1	10.1	10.1	13.5	13.5	13.5	13.5	16.9	16.9	16.9
50°	10.1	10.1	10.1	10.1	13.5	13.5	13.5	13.5	16.9	16.9	16.9
52.5°	6.8	6.8	6.8	6.8	10.1	10.1	10.1	10.1	13.5	13.5	13.5
55°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	10.1	10.1	10.1
57.5°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	10.1	10.1	10.1
60°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
62.5°	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4
65°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	3.4	3.4
67.5°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
70°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
72.5°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
75°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
77.5°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
80°	10.1	10.1	10.1	10.1	10.1	6.8	6.8	6.8	6.8	6.8	6.8
82.5°	6.8	10.1	10.1	10.1	10.1	6.8	6.8	6.8	6.8	6.8	6.8
85°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
87.5°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	43.9	43.9	40.5	40.5	40.5	40.5	40.5	40.5	40.5	43.9	43.9
5°	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	43.9	43.9
7.5°	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	43.9	43.9
10°	40.5	40.5	40.5	40.5	37.1	37.1	40.5	40.5	40.5	43.9	43.9
12.5°	40.5	40.5	40.5	40.5	37.1	37.1	40.5	40.5	43.9	43.9	47.3
15°	40.5	40.5	37.1	37.1	37.1	37.1	40.5	40.5	43.9	43.9	47.3
17.5°	40.5	40.5	37.1	37.1	37.1	37.1	40.5	40.5	43.9	43.9	47.3
20°	40.5	40.5	37.1	37.1	37.1	37.1	37.1	37.1	40.5	43.9	43.9
22.5°	37.1	37.1	37.1	37.1	33.8	33.8	37.1	37.1	40.5	43.9	43.9
25°	30.4	33.8	33.8	33.8	33.8	33.8	37.1	37.1	40.5	43.9	43.9
27.5°	27.0	30.4	30.4	30.4	30.4	33.8	33.8	37.1	40.5	43.9	43.9
30°	23.6	27.0	27.0	27.0	30.4	33.8	33.8	37.1	40.5	43.9	43.9
32.5°	23.6	27.0	27.0	27.0	30.4	30.4	33.8	33.8	37.1	40.5	43.9
35°	23.6	23.6	27.0	27.0	27.0	30.4	30.4	33.8	37.1	40.5	43.9
37.5°	23.6	23.6	27.0	27.0	27.0	30.4	30.4	33.8	37.1	40.5	43.9
40°	20.3	23.6	23.6	27.0	27.0	30.4	30.4	33.8	37.1	43.9	47.3
42.5°	20.3	20.3	23.6	23.6	27.0	30.4	30.4	33.8	37.1	43.9	47.3
45°	20.3	23.6	23.6	27.0	30.4	33.8	33.8	37.1	40.5	43.9	47.3
47.5°	20.3	23.6	23.6	27.0	33.8	33.8	37.1	37.1	40.5	43.9	47.3
50°	20.3	23.6	23.6	27.0	37.1	37.1	37.1	37.1	40.5	43.9	47.3
52.5°	16.9	20.3	20.3	23.6	30.4	33.8	37.1	40.5	43.9	47.3	50.6
55°	13.5	16.9	16.9	20.3	27.0	30.4	37.1	43.9	47.3	50.6	54.0
57.5°	13.5	13.5	16.9	16.9	23.6	30.4	40.5	47.3	50.6	54.0	57.4
60°	10.1	10.1	13.5	13.5	20.3	27.0	37.1	47.3	50.6	57.4	60.8
62.5°	6.8	10.1	10.1	13.5	16.9	27.0	37.1	47.3	54.0	60.8	64.2
65°	6.8	6.8	10.1	10.1	16.9	23.6	33.8	40.5	50.6	60.8	70.9
67.5°	10.1	10.1	13.5	13.5	16.9	23.6	33.8	40.5	50.6	64.2	74.3
70°	10.1	10.1	13.5	13.5	20.3	27.0	33.8	40.5	50.6	64.2	74.3
72.5°	10.1	10.1	13.5	13.5	20.3	23.6	30.4	37.1	47.3	57.4	67.5
75°	6.8	10.1	10.1	10.1	16.9	20.3	27.0	33.8	43.9	54.0	64.2
77.5°	6.8	6.8	6.8	6.8	13.5	16.9	23.6	27.0	37.1	47.3	57.4
80°	6.8	6.8	6.8	6.8	10.1	13.5	20.3	23.6	33.8	43.9	54.0
82.5°	6.8	6.8	3.4	3.4	6.8	10.1	13.5	16.9	27.0	33.8	43.9
85°	6.8	6.8	3.4	3.4	3.4	6.8	6.8	10.1	13.5	16.9	20.3
87.5°	6.8	6.8	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	43.9	43.9	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
5°	43.9	47.3	47.3	50.6	50.6	50.6	54.0	54.0	54.0	54.0	54.0
7.5°	43.9	47.3	47.3	50.6	50.6	50.6	54.0	54.0	54.0	57.4	57.4
10°	43.9	47.3	47.3	50.6	50.6	54.0	57.4	57.4	60.8	60.8	60.8
12.5°	47.3	50.6	50.6	54.0	54.0	57.4	60.8	60.8	64.2	67.5	67.5
15°	47.3	50.6	54.0	54.0	57.4	60.8	64.2	64.2	67.5	70.9	74.3
17.5°	47.3	50.6	54.0	54.0	57.4	60.8	67.5	70.9	74.3	81.0	84.4
20°	47.3	50.6	54.0	54.0	57.4	64.2	67.5	74.3	77.7	84.4	91.2
22.5°	47.3	50.6	54.0	57.4	60.8	67.5	74.3	77.7	84.4	94.5	101.3
25°	47.3	50.6	54.0	57.4	60.8	67.5	74.3	81.0	87.8	101.3	114.8
27.5°	47.3	50.6	57.4	60.8	64.2	70.9	81.0	87.8	94.5	118.2	141.8
30°	47.3	50.6	57.4	60.8	64.2	74.3	84.4	91.2	101.3	141.8	179.0
32.5°	47.3	54.0	57.4	64.2	67.5	77.7	91.2	101.3	111.4	168.8	222.8
35°	47.3	54.0	57.4	64.2	67.5	81.0	94.5	108.0	121.6	206.0	290.4
37.5°	47.3	54.0	57.4	64.2	67.5	87.8	108.0	128.3	148.6	236.4	324.1
40°	50.6	57.4	60.8	67.5	70.9	91.2	111.4	131.7	151.9	239.7	327.5
42.5°	50.6	57.4	60.8	67.5	70.9	87.8	108.0	124.9	141.8	239.7	337.6
45°	50.6	57.4	64.2	67.5	74.3	91.2	108.0	121.6	138.4	263.4	384.9
47.5°	50.6	57.4	64.2	67.5	74.3	91.2	108.0	124.9	141.8	347.8	550.4
50°	50.6	57.4	64.2	67.5	74.3	94.5	114.8	135.1	155.3	520.0	884.6
52.5°	54.0	57.4	64.2	67.5	70.9	94.5	118.2	141.8	165.4	675.3	1181.8
55°	57.4	60.8	64.2	67.5	70.9	101.3	131.7	162.1	192.5	725.9	1256.0
57.5°	60.8	64.2	67.5	67.5	70.9	108.0	148.6	185.7	222.8	722.6	1218.9
60°	64.2	67.5	70.9	74.3	77.7	114.8	155.3	192.5	229.6	655.0	1080.5
62.5°	70.9	77.7	84.4	87.8	94.5	131.7	165.4	202.6	236.4	536.9	834.0
65°	81.0	87.8	91.2	97.9	101.3	135.1	172.2	206.0	239.7	445.7	648.3
67.5°	84.4	91.2	94.5	101.3	104.7	138.4	172.2	206.0	239.7	378.2	513.2
70°	84.4	91.2	97.9	101.3	108.0	141.8	172.2	206.0	236.4	327.5	418.7
72.5°	77.7	87.8	94.5	104.7	111.4	141.8	168.8	199.2	226.2	290.4	354.5
75°	74.3	87.8	97.9	111.4	121.6	141.8	165.4	185.7	206.0	253.2	300.5
77.5°	67.5	84.4	101.3	118.2	135.1	148.6	158.7	172.2	182.3	212.7	243.1
80°	64.2	81.0	97.9	114.8	131.7	138.4	141.8	148.6	151.9	155.3	158.7
82.5°	50.6	64.2	77.7	87.8	101.3	94.5	91.2	84.4	77.7	74.3	70.9
85°	23.6	27.0	27.0	30.4	30.4	30.4	27.0	27.0	23.6	20.3	16.9
87.5°	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	47.3	47.3	47.3	47.3	43.9	43.9	43.9	43.9	40.5	40.5	40.5
5°	54.0	54.0	54.0	54.0	50.6	50.6	50.6	50.6	47.3	47.3	47.3
7.5°	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4
10°	64.2	64.2	64.2	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5
12.5°	70.9	70.9	74.3	74.3	77.7	77.7	81.0	81.0	84.4	84.4	84.4
15°	77.7	81.0	84.4	87.8	87.8	91.2	94.5	97.9	101.3	104.7	108.0
17.5°	91.2	94.5	101.3	108.0	114.8	121.6	131.7	145.2	155.3	165.4	179.0
20°	101.3	111.4	131.7	155.3	175.6	195.8	246.5	297.1	347.8	398.4	449.1
22.5°	121.6	141.8	209.3	280.2	347.8	415.3	574.0	732.7	888.0	1046.7	1188.5
25°	162.1	206.0	361.3	516.6	668.5	823.9	1107.5	1394.5	1678.1	1961.7	2225.1
27.5°	222.8	303.9	557.1	813.7	1067.0	1320.2	1732.1	2147.4	2559.4	2974.7	3342.7
30°	310.6	442.3	820.5	1202.0	1580.2	1958.3	2478.3	3001.7	3521.7	4041.6	4379.3
32.5°	422.1	617.9	1097.4	1576.8	2056.3	2535.7	3109.7	3683.7	4254.3	4828.3	5186.2
35°	540.2	790.1	1367.5	1948.2	2525.6	3106.3	3710.7	4315.1	4919.5	5523.9	5962.8
37.5°	607.8	891.4	1576.8	2262.2	2944.3	3629.7	4291.5	4956.6	5618.4	6280.2	6813.7
40°	671.9	1012.9	1803.0	2593.1	3383.2	4173.3	4946.5	5719.7	6492.9	7266.1	7951.6
42.5°	766.5	1195.3	2117.0	3038.8	3957.2	4879.0	5895.3	6915.0	7931.3	8947.6	10001.1
45°	962.3	1539.7	2734.9	3930.2	5122.1	6317.4	7759.1	9204.2	10646.0	12091.1	13441.7
47.5°	1435.0	2316.3	3947.1	5577.9	7208.7	8839.6	10500.8	12162.0	13823.2	15484.5	17091.7
50°	2221.7	3555.4	5594.8	7634.2	9670.2	11709.6	13367.4	15025.3	16679.7	18337.6	19934.6
52.5°	2961.2	4740.6	6931.9	9126.6	11317.9	13512.6	14981.4	16450.1	17918.9	19387.6	20934.1
55°	3214.4	5169.4	7387.7	9609.4	11827.7	14049.5	15464.2	16882.3	18297.1	19711.8	21315.6
57.5°	2991.5	4764.2	6999.4	9234.6	11466.5	13701.7	15281.9	16865.4	18445.6	20029.2	21747.8
60°	2505.3	3926.8	6273.5	8623.5	10970.1	13316.8	15099.5	16882.3	18665.1	20447.9	22163.1
62.5°	1985.4	3133.4	5618.4	8103.5	10588.6	13073.7	14886.8	16703.4	18516.5	20329.7	21646.5
65°	1522.8	2397.3	4841.8	7289.8	9734.3	12182.3	13667.9	15156.9	16642.6	18131.6	19043.3
67.5°	1131.1	1749.0	3886.3	6027.0	8164.3	10301.6	11395.6	12492.9	13586.9	14684.2	15393.3
70°	834.0	1245.9	2701.2	4156.4	5608.3	7063.6	8066.4	9069.2	10068.6	11071.4	11807.5
72.5°	577.4	796.8	1668.0	2542.5	3413.6	4284.7	5301.0	6317.4	7330.3	8346.6	9184.0
75°	395.0	489.6	898.1	1306.7	1715.2	2123.8	2893.6	3663.5	4433.3	5203.1	5645.4
77.5°	293.8	344.4	466.0	590.9	712.4	834.0	982.6	1131.1	1279.7	1428.2	1620.7
80°	162.1	162.1	179.0	192.5	209.3	222.8	263.4	307.3	347.8	391.7	445.7
82.5°	74.3	77.7	84.4	91.2	94.5	101.3	108.0	114.8	121.6	128.3	128.3
85°	20.3	23.6	23.6	20.3	20.3	16.9	16.9	20.3	20.3	20.3	20.3
87.5°	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	40.5	37.1	37.1	37.1	33.8	33.8	33.8	33.8	33.8	33.8	33.8
5°	47.3	47.3	47.3	47.3	43.9	43.9	43.9	43.9	43.9	40.5	40.5
7.5°	57.4	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	50.6	50.6
10°	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	64.2	64.2
12.5°	84.4	84.4	84.4	84.4	87.8	87.8	84.4	84.4	84.4	81.0	81.0
15°	111.4	114.8	118.2	118.2	121.6	121.6	121.6	118.2	118.2	114.8	111.4
17.5°	189.1	199.2	212.7	226.2	239.7	249.9	249.9	243.1	236.4	229.6	222.8
20°	503.1	553.7	607.8	661.8	719.2	759.7	732.7	712.4	692.2	668.5	648.3
22.5°	1333.7	1475.5	1620.7	1722.0	1823.3	1894.2	1836.8	1725.4	1613.9	1505.9	1394.5
25°	2488.5	2748.4	3011.8	3119.9	3231.3	3312.3	3275.2	3106.3	2937.5	2772.1	2603.3
27.5°	3710.7	4075.4	4443.4	4538.0	4632.5	4703.4	4689.9	4470.4	4251.0	4031.5	3812.0
30°	4716.9	5054.6	5392.2	5486.8	5581.3	5645.4	5574.5	5355.1	5135.6	4916.1	4696.7
32.5°	5547.5	5905.4	6266.7	6391.6	6516.6	6601.0	6516.6	6253.2	5989.8	5729.9	5466.5
35°	6401.8	6837.3	7276.3	7435.0	7593.7	7695.0	7553.1	7229.0	6904.9	6584.1	6260.0
37.5°	7347.2	7877.3	8410.8	8626.9	8846.3	8998.3	8890.2	8485.1	8076.5	7671.3	7262.8
40°	8640.4	9325.8	10014.6	10402.9	10787.8	11061.3	10868.8	10399.5	9926.8	9457.5	8984.8
42.5°	11057.9	12111.4	13164.8	13721.9	14275.7	14677.5	14461.4	13884.0	13306.6	12729.3	12151.9
45°	14792.3	16139.5	17490.1	18303.8	19120.9	19721.9	19472.1	18746.1	18016.8	17290.9	16564.9
47.5°	18698.9	20306.0	21913.2	22561.5	23213.2	23719.7	23658.9	22754.0	21849.1	20947.6	20042.7
50°	21535.1	23132.1	24729.2	25286.3	25846.8	26262.1	26106.8	24955.4	23800.7	22649.3	21494.6
52.5°	22480.5	24023.5	25570.0	26235.1	26900.3	27396.6	27207.5	25911.0	24614.4	23321.2	22024.7
55°	22919.4	24523.2	26127.1	26937.4	27751.1	28345.4	28071.9	26650.4	25225.6	23804.1	22379.2
57.5°	23466.4	25185.0	26903.7	27791.7	28679.7	29321.2	28956.5	27484.4	26012.3	24543.5	23071.4
60°	23878.3	25590.2	27305.5	28017.9	28733.7	29233.4	28882.3	27450.6	26015.6	24584.0	23152.4
62.5°	22966.7	24283.5	25600.3	26130.4	26660.6	27045.5	26846.3	25488.9	24131.6	22774.2	21416.9
65°	19958.3	20869.9	21784.9	22142.8	22497.4	22770.9	22710.1	21565.5	20420.8	19279.6	18135.0
67.5°	16105.7	16814.8	17527.2	18033.7	18543.5	18938.6	18894.7	17851.4	16808.0	15764.7	14721.4
70°	12546.9	13283.0	14019.1	14657.2	15298.8	15795.1	15730.9	14761.9	13789.5	12820.4	11848.0
72.5°	10024.7	10862.1	11699.4	12064.1	12428.8	12685.4	12496.3	11763.6	11027.5	10294.8	9558.8
75°	6087.8	6526.7	6969.0	6965.6	6965.6	6925.1	6736.0	6317.4	5898.7	5480.0	5061.3
77.5°	1813.2	2005.6	2198.1	2383.8	2572.9	2714.7	2677.5	2458.1	2235.2	2015.7	1792.9
80°	499.7	550.4	604.4	628.0	651.7	682.0	759.7	705.7	651.7	601.0	547.0
82.5°	128.3	128.3	128.3	124.9	121.6	114.8	104.7	97.9	91.2	84.4	77.7
85°	20.3	16.9	16.9	16.9	13.5	13.5	13.5	13.5	10.1	10.1	6.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4
2.5°	33.8	33.8	30.4	30.4	30.4	30.4	30.4	30.4	30.4	30.4	27.0
5°	40.5	40.5	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1	33.8
7.5°	50.6	50.6	47.3	47.3	47.3	47.3	43.9	43.9	43.9	43.9	40.5
10°	64.2	60.8	60.8	57.4	57.4	57.4	54.0	54.0	54.0	50.6	50.6
12.5°	81.0	77.7	77.7	74.3	70.9	70.9	67.5	64.2	60.8	60.8	57.4
15°	108.0	104.7	101.3	97.9	94.5	87.8	84.4	77.7	74.3	70.9	67.5
17.5°	206.0	189.1	172.2	155.3	141.8	128.3	114.8	101.3	94.5	87.8	81.0
20°	574.0	496.3	422.1	347.8	300.5	253.2	206.0	158.7	138.4	121.6	101.3
22.5°	1242.5	1087.2	935.3	780.0	655.0	533.5	408.6	283.6	236.4	192.5	145.2
25°	2309.5	2012.4	1718.6	1421.5	1185.1	948.8	712.4	476.1	388.3	300.5	212.7
27.5°	3427.1	3042.2	2657.3	2272.4	1897.6	1519.4	1141.2	766.5	614.5	466.0	314.0
30°	4288.1	3879.6	3474.4	3065.8	2593.1	2120.4	1644.3	1171.6	931.9	692.2	449.1
32.5°	5027.6	4585.2	4146.3	3704.0	3157.0	2610.0	2063.0	1516.0	1215.5	915.0	611.1
35°	5760.2	5257.2	4757.4	4254.3	3666.8	3079.3	2491.8	1904.3	1522.8	1141.2	756.3
37.5°	6651.6	6037.1	5426.0	4814.8	4210.4	3609.4	3005.1	2400.7	1914.5	1431.6	945.4
40°	8204.8	7421.5	6641.5	5858.2	5152.5	4450.2	3744.5	3038.8	2427.7	1816.5	1202.0
42.5°	11169.3	10186.8	9207.6	8225.1	7249.3	6273.5	5294.3	4318.5	3447.4	2579.6	1708.5
45°	15305.5	14046.1	12790.0	11530.6	10328.6	9130.0	7927.9	6725.9	5402.3	4078.8	2751.8
47.5°	18665.1	17284.1	15906.5	14525.5	13191.8	11861.5	10527.8	9194.1	7499.1	5807.5	4112.5
50°	20181.1	18864.3	17550.9	16234.0	14897.0	13556.5	12216.0	10879.0	8934.1	6992.7	5047.8
52.5°	20691.0	19353.9	18020.2	16683.1	15356.2	14029.2	12702.3	11375.3	9352.8	7333.7	5311.2
55°	20971.2	19559.8	18151.9	16740.5	15312.3	13880.6	12449.0	11020.8	9008.4	6999.4	4987.0
57.5°	21538.5	20002.2	18469.3	16933.0	15305.5	13678.1	12047.2	10419.8	8434.4	6449.0	4463.7
60°	21643.1	20130.5	18621.2	17111.9	15312.3	13512.6	11709.6	9909.9	7938.1	5969.6	3997.7
62.5°	20154.1	18891.3	17631.9	16369.1	14566.1	12763.0	10956.6	9153.6	7266.1	5378.7	3487.9
65°	17044.4	15953.8	14866.6	13776.0	12303.8	10835.1	9362.9	7890.8	6205.9	4524.5	2839.6
67.5°	13654.4	12587.5	11523.9	10456.9	9349.4	8245.3	7137.8	6030.4	4730.4	3430.5	2130.5
70°	10824.9	9798.5	8775.4	7749.0	6769.8	5787.3	4804.7	3825.5	3018.6	2215.0	1408.0
72.5°	8579.6	7597.0	6617.9	5635.3	4747.3	3859.3	2971.3	2083.3	1681.5	1283.1	881.3
75°	4551.5	4041.6	3535.2	3025.3	2525.6	2022.5	1519.4	1019.7	861.0	702.3	540.2
77.5°	1570.1	1347.2	1127.7	904.9	753.0	601.0	449.1	297.1	280.2	266.7	249.9
80°	476.1	405.2	334.3	263.4	233.0	202.6	172.2	141.8	131.7	121.6	108.0
82.5°	74.3	67.5	64.2	57.4	54.0	54.0	50.6	47.3	40.5	37.1	30.4
85°	6.8	3.4	3.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	30.4	30.4
2.5°	27.0	27.0
5°	33.8	33.8
7.5°	40.5	40.5
10°	47.3	47.3
12.5°	54.0	54.0
15°	64.2	60.8
17.5°	74.3	70.9
20°	81.0	74.3
22.5°	97.9	84.4
25°	124.9	104.7
27.5°	162.1	128.3
30°	209.3	162.1
32.5°	310.6	226.2
35°	374.8	273.5
37.5°	459.2	317.4
40°	590.9	384.9
42.5°	837.4	523.4
45°	1428.2	867.8
47.5°	2420.9	1478.9
50°	3103.0	1897.6
52.5°	3292.1	2012.4
55°	2978.0	1846.9
57.5°	2478.3	1570.1
60°	2029.3	1293.2
62.5°	1600.4	1023.1
65°	1154.8	773.2
67.5°	830.6	594.3
70°	604.4	466.0
72.5°	479.5	388.3
75°	381.5	324.1
77.5°	236.4	216.1
80°	97.9	91.2
82.5°	23.6	20.3
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066534

CATALOG NUMBER: NVN-SA3B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-5

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-735-U-5WQ

Data in this report applies to families of products including GSS-SB1A-735-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-735-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3369
 CIE u' : 0.2386
 CIE v' : 0.5156
 Duv: 0.0013
 CIE x: 0.4143
 CIE y: 0.3980
 CIE z: 0.1877
 Peak Wavelength (nm): 590
 Dominant Wavelength (nm): 580
 Purity: 43.80166
 R_f: 71.4
 R_g: 96

CRI (Ra): 70.1
 R1: 66.6
 R2: 77.6
 R3: 88.5
 R4: 69.5
 R5: 66.4
 R6: 69.6
 R7: 77.5
 R8: 44.9
 R9: -40.2
 R10: 49.1
 R11: 66.3
 R12: 45.7
 R13: 68.0
 R14: 93.4
 R15: 57.6



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-5


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-5

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-5

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.29

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.36


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5





TM-30-18

Summary

$R_f = 71.4$
 $R_g = 96$
 CIE $R_a = 70.1$
 $R_g = -40.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 86	CES26 = 57	CES51 = 84	CES76 = 50
CES02 = 62	CES27 = 80	CES52 = 86	CES77 = 74
CES03 = 31	CES28 = 81	CES53 = 72	CES78 = 54
CES04 = 70	CES29 = 50	CES54 = 79	CES79 = 81
CES05 = 48	CES30 = 55	CES55 = 78	CES80 = 79
CES06 = 51	CES31 = 56	CES56 = 67	CES81 = 74
CES07 = 40	CES32 = 54	CES57 = 65	CES82 = 91
CES08 = 39	CES33 = 60	CES58 = 68	CES83 = 86
CES09 = 29	CES34 = 69	CES59 = 85	CES84 = 89
CES10 = 75	CES35 = 83	CES60 = 91	CES85 = 83
CES11 = 58	CES36 = 88	CES61 = 85	CES86 = 66
CES12 = 64	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 43	CES38 = 64	CES63 = 71	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 70	CES89 = 68
CES15 = 71	CES40 = 86	CES65 = 64	CES90 = 72
CES16 = 47	CES41 = 81	CES66 = 65	CES91 = 95
CES17 = 50	CES42 = 79	CES67 = 63	CES92 = 62
CES18 = 56	CES43 = 71	CES68 = 69	CES93 = 78
CES19 = 72	CES44 = 98	CES69 = 80	CES94 = 51
CES20 = 65	CES45 = 80	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 75	CES71 = 58	CES96 = 76
CES22 = 79	CES47 = 71	CES72 = 85	CES97 = 82
CES23 = 92	CES48 = 61	CES73 = 51	CES98 = 72
CES24 = 91	CES49 = 74	CES74 = 94	CES99 = 60
CES25 = 72	CES50 = 83	CES75 = 57	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)