

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066536

Luminaire Tested: **NVN-SA3D-735-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066536
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA3D-735-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1200mA 3xLight Square PACKAGE
70CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 3500K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 14669.8 lumens
Efficiency: N/A
Efficacy: 91.2 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 160.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.9 fc
 Type III - Short - N/A

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	87.3	0.0	87.3
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	14582.5	0.0	14582.5
	% Fixture	99.4	0.0	99.4
Total	Lumens	14669.7	0.0	14669.7
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.3	0.0
10°-20°	21.5	0.1
20°-30°	273.8	1.9
30°-40°	922.8	6.3
40°-50°	2786.8	19.0
50°-60°	4916.8	33.5
60°-70°	4331.7	29.5
70°-80°	1378.9	9.4
80°-90°	33.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	14669.7	100.0
0°-180°	14669.8	100.0



REPORT NUMBER: P1066536


CATALOG NUMBER: NVN-SA3D-735-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	286.6	2.0			
FM	(30°-60°)	8592.6	58.6			
FH	(60°-80°)	5676.4	38.7			G3/7500
FVH	(80°-90°)	27.0	0.2			G1/100
BL	(0°-30°)	13.1	0.1	B0/110		
BM	(30°-60°)	33.8	0.2	B0/220		
BH	(60°-80°)	34.2	0.2	B0/110		G0/110
BVH	(80°-90°)	6.2	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	32.2
5°	46.0	46.0	46.0	41.4	41.4	41.4	36.8	36.8	36.8	36.8	36.8
7.5°	55.2	50.6	50.6	46.0	46.0	46.0	41.4	41.4	41.4	41.4	36.8
10°	64.4	59.8	59.8	55.2	55.2	50.6	50.6	46.0	46.0	41.4	41.4
12.5°	73.6	69.0	64.4	59.8	59.8	55.2	55.2	50.6	50.6	46.0	46.0
15°	82.8	78.2	73.6	69.0	64.4	64.4	59.8	55.2	50.6	50.6	46.0
17.5°	96.6	87.4	82.8	73.6	69.0	64.4	59.8	55.2	55.2	50.6	50.6
20°	101.2	92.0	87.4	78.2	73.6	69.0	64.4	59.8	55.2	55.2	50.6
22.5°	119.6	101.2	96.6	87.4	82.8	78.2	69.0	64.4	59.8	55.2	50.6
25°	147.2	119.6	105.8	92.0	87.4	78.2	73.6	64.4	59.8	55.2	50.6
27.5°	179.4	133.4	119.6	101.2	92.0	82.8	73.6	64.4	59.8	55.2	50.6
30°	220.8	156.4	133.4	110.4	101.2	92.0	78.2	69.0	64.4	59.8	50.6
32.5°	308.2	193.2	156.4	119.6	105.8	96.6	82.8	69.0	64.4	59.8	50.6
35°	372.6	234.6	188.6	138.0	119.6	105.8	87.4	69.0	64.4	59.8	50.6
37.5°	432.4	239.2	193.2	147.2	128.8	110.4	87.4	69.0	64.4	59.8	50.6
40°	529.0	248.4	193.2	138.0	124.2	105.8	92.0	73.6	69.0	59.8	55.2
42.5°	713.1	285.2	207.0	128.8	115.0	105.8	92.0	78.2	69.0	64.4	55.2
45°	1186.9	423.2	280.6	133.4	119.6	105.8	92.0	78.2	73.6	64.4	59.8
47.5°	2019.6	736.1	437.0	138.0	124.2	105.8	92.0	73.6	69.0	64.4	55.2
50°	2585.4	943.1	552.1	161.0	138.0	119.6	96.6	73.6	69.0	64.4	59.8
52.5°	2746.5	1002.9	598.1	188.6	161.0	133.4	101.2	73.6	69.0	69.0	64.4
55°	2516.4	975.3	598.1	220.8	184.0	151.8	115.0	78.2	73.6	73.6	69.0
57.5°	2139.2	901.7	570.5	239.2	202.4	161.0	124.2	82.8	78.2	78.2	73.6
60°	1762.0	759.1	515.2	266.8	225.4	184.0	142.6	101.2	96.6	92.0	82.8
62.5°	1398.5	611.9	450.8	285.2	243.8	197.8	156.4	110.4	105.8	101.2	96.6
65°	1053.5	533.6	418.6	299.0	253.0	207.0	161.0	115.0	110.4	110.4	105.8
67.5°	809.7	487.6	400.2	308.2	262.2	216.2	170.2	124.2	119.6	115.0	110.4
70°	639.5	450.8	377.2	303.6	262.2	220.8	174.8	133.4	124.2	119.6	110.4
72.5°	533.6	409.4	349.6	289.8	257.6	225.4	193.2	161.0	142.6	128.8	110.4
75°	446.2	368.0	317.4	262.2	239.2	220.8	197.8	174.8	151.8	128.8	105.8
77.5°	294.4	266.8	243.8	220.8	207.0	193.2	174.8	161.0	138.0	119.6	96.6
80°	124.2	115.0	119.6	119.6	119.6	119.6	115.0	115.0	101.2	87.4	69.0
82.5°	27.6	23.0	27.6	27.6	27.6	27.6	23.0	23.0	23.0	18.4	18.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2
5°	36.8	36.8	36.8	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2
7.5°	36.8	36.8	36.8	32.2	32.2	32.2	32.2	27.6	27.6	27.6	27.6
10°	36.8	36.8	36.8	32.2	32.2	32.2	32.2	27.6	27.6	27.6	27.6
12.5°	41.4	41.4	36.8	36.8	32.2	32.2	32.2	27.6	27.6	27.6	27.6
15°	41.4	41.4	36.8	36.8	32.2	32.2	32.2	27.6	27.6	27.6	27.6
17.5°	46.0	41.4	41.4	36.8	32.2	32.2	32.2	27.6	27.6	27.6	27.6
20°	46.0	41.4	41.4	36.8	32.2	32.2	32.2	27.6	27.6	27.6	27.6
22.5°	46.0	41.4	41.4	36.8	32.2	32.2	27.6	27.6	23.0	23.0	18.4
25°	46.0	41.4	41.4	36.8	32.2	32.2	27.6	27.6	23.0	18.4	18.4
27.5°	46.0	41.4	41.4	36.8	32.2	27.6	27.6	23.0	18.4	13.8	13.8
30°	46.0	41.4	41.4	36.8	32.2	27.6	23.0	18.4	13.8	13.8	9.2
32.5°	46.0	41.4	36.8	32.2	27.6	23.0	23.0	18.4	13.8	9.2	9.2
35°	46.0	41.4	36.8	32.2	27.6	23.0	23.0	18.4	13.8	9.2	9.2
37.5°	46.0	41.4	36.8	32.2	27.6	23.0	18.4	13.8	9.2	9.2	4.6
40°	46.0	41.4	36.8	32.2	27.6	23.0	18.4	13.8	9.2	9.2	4.6
42.5°	46.0	41.4	36.8	32.2	27.6	23.0	18.4	13.8	9.2	9.2	4.6
45°	50.6	46.0	41.4	32.2	27.6	23.0	23.0	18.4	13.8	9.2	9.2
47.5°	50.6	46.0	41.4	32.2	27.6	23.0	23.0	18.4	13.8	9.2	9.2
50°	55.2	50.6	46.0	36.8	32.2	27.6	23.0	13.8	9.2	9.2	4.6
52.5°	59.8	55.2	50.6	46.0	41.4	32.2	23.0	13.8	4.6	4.6	4.6
55°	64.4	59.8	59.8	55.2	50.6	36.8	27.6	13.8	0.0	0.0	0.0
57.5°	69.0	64.4	64.4	59.8	55.2	41.4	27.6	13.8	0.0	0.0	0.0
60°	78.2	73.6	69.0	59.8	55.2	41.4	27.6	13.8	0.0	0.0	0.0
62.5°	92.0	82.8	69.0	59.8	46.0	36.8	23.0	13.8	0.0	0.0	0.0
65°	101.2	87.4	73.6	55.2	41.4	32.2	23.0	9.2	0.0	0.0	0.0
67.5°	105.8	87.4	73.6	55.2	36.8	27.6	18.4	9.2	0.0	0.0	0.0
70°	101.2	82.8	69.0	50.6	32.2	23.0	18.4	9.2	0.0	0.0	0.0
72.5°	92.0	78.2	59.8	46.0	27.6	23.0	13.8	9.2	0.0	0.0	0.0
75°	82.8	69.0	50.6	36.8	18.4	13.8	9.2	4.6	0.0	0.0	0.0
77.5°	73.6	59.8	41.4	27.6	9.2	9.2	4.6	4.6	0.0	0.0	0.0
80°	55.2	41.4	27.6	13.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	13.8	9.2	9.2	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6
5°	27.6	27.6	27.6	27.6	23.0	23.0	23.0	23.0	23.0	23.0	23.0
7.5°	27.6	27.6	27.6	27.6	23.0	23.0	23.0	23.0	18.4	18.4	18.4
10°	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	18.4	18.4	18.4
12.5°	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	18.4	18.4	18.4
15°	23.0	23.0	23.0	23.0	23.0	23.0	23.0	18.4	18.4	13.8	13.8
17.5°	23.0	23.0	23.0	23.0	18.4	18.4	18.4	13.8	13.8	9.2	9.2
20°	23.0	23.0	23.0	18.4	18.4	13.8	13.8	9.2	9.2	4.6	4.6
22.5°	18.4	13.8	13.8	9.2	9.2	4.6	4.6	4.6	0.0	0.0	0.0
25°	13.8	9.2	9.2	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	9.2	4.6	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	9.2	4.6	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	27.6	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0
5°	23.0	23.0	23.0	23.0	18.4	18.4	18.4	18.4	18.4	18.4	18.4
7.5°	18.4	18.4	18.4	18.4	18.4	18.4	13.8	13.8	13.8	13.8	13.8
10°	18.4	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8	9.2	9.2
12.5°	18.4	13.8	13.8	13.8	9.2	9.2	9.2	9.2	9.2	4.6	4.6
15°	13.8	9.2	9.2	9.2	4.6	4.6	4.6	4.6	4.6	0.0	0.0
17.5°	9.2	4.6	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	27.6	27.6
5°	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4
7.5°	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8
10°	9.2	9.2	9.2	9.2	9.2	9.2	4.6	4.6	4.6	4.6	4.6
12.5°	4.6	4.6	4.6	4.6	4.6	4.6	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	27.6	27.6	27.6	27.6	27.6	32.2	32.2	36.8	36.8	41.4	41.4
5°	18.4	18.4	23.0	23.0	23.0	23.0	27.6	27.6	27.6	32.2	32.2
7.5°	13.8	13.8	13.8	13.8	13.8	18.4	18.4	23.0	23.0	27.6	27.6
10°	4.6	4.6	9.2	9.2	9.2	9.2	13.8	13.8	13.8	18.4	23.0
12.5°	0.0	0.0	4.6	4.6	4.6	4.6	9.2	9.2	9.2	13.8	18.4
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	9.2	13.8
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	9.2
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	46.0	46.0	50.6	50.6	55.2	55.2	59.8	59.8	59.8	59.8	59.8
5°	36.8	36.8	41.4	46.0	46.0	50.6	55.2	55.2	55.2	55.2	55.2
7.5°	32.2	32.2	36.8	41.4	41.4	46.0	50.6	50.6	55.2	55.2	55.2
10°	23.0	27.6	32.2	36.8	36.8	41.4	46.0	46.0	50.6	50.6	50.6
12.5°	18.4	23.0	27.6	32.2	32.2	36.8	41.4	41.4	46.0	46.0	50.6
15°	13.8	18.4	23.0	27.6	27.6	32.2	36.8	36.8	41.4	46.0	50.6
17.5°	9.2	13.8	18.4	23.0	23.0	27.6	32.2	36.8	41.4	41.4	46.0
20°	9.2	9.2	13.8	18.4	18.4	23.0	27.6	32.2	36.8	36.8	41.4
22.5°	4.6	4.6	9.2	13.8	13.8	18.4	23.0	27.6	32.2	32.2	36.8
25°	0.0	0.0	4.6	9.2	9.2	13.8	18.4	18.4	23.0	23.0	27.6
27.5°	0.0	0.0	4.6	4.6	9.2	9.2	13.8	13.8	18.4	18.4	23.0
30°	0.0	0.0	4.6	4.6	9.2	9.2	13.8	13.8	18.4	18.4	18.4
32.5°	0.0	0.0	0.0	4.6	4.6	4.6	9.2	9.2	13.8	13.8	18.4
35°	0.0	0.0	0.0	4.6	4.6	4.6	9.2	9.2	13.8	13.8	13.8
37.5°	0.0	0.0	0.0	4.6	4.6	4.6	9.2	9.2	9.2	9.2	13.8
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	9.2
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	59.8	59.8
5°	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	55.2	55.2
7.5°	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	55.2	55.2
10°	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
12.5°	50.6	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
15°	50.6	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
17.5°	46.0	50.6	50.6	50.6	55.2	55.2	55.2	55.2	55.2	55.2	55.2
20°	41.4	46.0	46.0	46.0	50.6	50.6	50.6	50.6	55.2	55.2	55.2
22.5°	36.8	41.4	41.4	41.4	46.0	46.0	46.0	46.0	50.6	50.6	50.6
25°	32.2	32.2	36.8	36.8	41.4	41.4	41.4	41.4	41.4	41.4	41.4
27.5°	23.0	27.6	27.6	27.6	32.2	32.2	32.2	32.2	36.8	36.8	36.8
30°	23.0	23.0	23.0	23.0	27.6	27.6	27.6	27.6	32.2	32.2	32.2
32.5°	18.4	23.0	23.0	23.0	27.6	27.6	27.6	27.6	32.2	32.2	32.2
35°	18.4	18.4	18.4	18.4	23.0	23.0	23.0	23.0	27.6	27.6	27.6
37.5°	13.8	18.4	18.4	18.4	23.0	23.0	23.0	23.0	27.6	27.6	27.6
40°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
42.5°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
45°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
47.5°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
50°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
52.5°	9.2	9.2	9.2	9.2	13.8	13.8	13.8	13.8	18.4	18.4	18.4
55°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	13.8	13.8	13.8
57.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	13.8	13.8	13.8
60°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
62.5°	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
65°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	4.6	4.6
67.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
70°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
72.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
75°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
77.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
80°	13.8	13.8	13.8	13.8	13.8	9.2	9.2	9.2	9.2	9.2	9.2
82.5°	9.2	13.8	13.8	13.8	13.8	9.2	9.2	9.2	9.2	9.2	9.2
85°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
87.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	59.8	59.8	55.2	55.2	55.2	55.2	55.2	55.2	55.2	59.8	59.8
5°	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	59.8	59.8
7.5°	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	59.8	59.8
10°	55.2	55.2	55.2	55.2	50.6	50.6	55.2	55.2	55.2	59.8	59.8
12.5°	55.2	55.2	55.2	55.2	50.6	50.6	55.2	55.2	59.8	59.8	64.4
15°	55.2	55.2	50.6	50.6	50.6	50.6	55.2	55.2	59.8	59.8	64.4
17.5°	55.2	55.2	50.6	50.6	50.6	50.6	55.2	55.2	59.8	59.8	64.4
20°	55.2	55.2	50.6	50.6	50.6	50.6	50.6	50.6	55.2	59.8	59.8
22.5°	50.6	50.6	50.6	50.6	46.0	46.0	50.6	50.6	55.2	59.8	59.8
25°	41.4	46.0	46.0	46.0	46.0	46.0	50.6	50.6	55.2	59.8	59.8
27.5°	36.8	41.4	41.4	41.4	41.4	46.0	46.0	50.6	55.2	59.8	59.8
30°	32.2	36.8	36.8	36.8	41.4	46.0	46.0	50.6	55.2	59.8	59.8
32.5°	32.2	36.8	36.8	36.8	41.4	41.4	46.0	46.0	50.6	55.2	59.8
35°	32.2	32.2	36.8	36.8	36.8	41.4	41.4	46.0	50.6	55.2	59.8
37.5°	32.2	32.2	36.8	36.8	36.8	41.4	41.4	46.0	50.6	55.2	59.8
40°	27.6	32.2	32.2	36.8	36.8	41.4	41.4	46.0	50.6	59.8	64.4
42.5°	27.6	27.6	32.2	32.2	36.8	41.4	41.4	46.0	50.6	59.8	64.4
45°	27.6	32.2	32.2	36.8	41.4	46.0	46.0	50.6	55.2	59.8	64.4
47.5°	27.6	32.2	32.2	36.8	46.0	46.0	50.6	50.6	55.2	59.8	64.4
50°	27.6	32.2	32.2	36.8	50.6	50.6	50.6	50.6	55.2	59.8	64.4
52.5°	23.0	27.6	27.6	32.2	41.4	46.0	50.6	55.2	59.8	64.4	69.0
55°	18.4	23.0	23.0	27.6	36.8	41.4	50.6	59.8	64.4	69.0	73.6
57.5°	18.4	18.4	23.0	23.0	32.2	41.4	55.2	64.4	69.0	73.6	78.2
60°	13.8	13.8	18.4	18.4	27.6	36.8	50.6	64.4	69.0	78.2	82.8
62.5°	9.2	13.8	13.8	18.4	23.0	36.8	50.6	64.4	73.6	82.8	87.4
65°	9.2	9.2	13.8	13.8	23.0	32.2	46.0	55.2	69.0	82.8	96.6
67.5°	13.8	13.8	18.4	18.4	23.0	32.2	46.0	55.2	69.0	87.4	101.2
70°	13.8	13.8	18.4	18.4	27.6	36.8	46.0	55.2	69.0	87.4	101.2
72.5°	13.8	13.8	18.4	18.4	27.6	32.2	41.4	50.6	64.4	78.2	92.0
75°	9.2	13.8	13.8	13.8	23.0	27.6	36.8	46.0	59.8	73.6	87.4
77.5°	9.2	9.2	9.2	9.2	18.4	23.0	32.2	36.8	50.6	64.4	78.2
80°	9.2	9.2	9.2	9.2	13.8	18.4	27.6	32.2	46.0	59.8	73.6
82.5°	9.2	9.2	4.6	4.6	9.2	13.8	18.4	23.0	36.8	46.0	59.8
85°	9.2	9.2	4.6	4.6	4.6	9.2	9.2	13.8	18.4	23.0	27.6
87.5°	9.2	9.2	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	59.8	59.8	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
5°	59.8	64.4	64.4	69.0	69.0	69.0	73.6	73.6	73.6	73.6	73.6
7.5°	59.8	64.4	64.4	69.0	69.0	69.0	73.6	73.6	73.6	78.2	78.2
10°	59.8	64.4	64.4	69.0	69.0	73.6	78.2	78.2	82.8	82.8	82.8
12.5°	64.4	69.0	69.0	73.6	73.6	78.2	82.8	82.8	87.4	92.0	92.0
15°	64.4	69.0	73.6	73.6	78.2	82.8	87.4	87.4	92.0	96.6	101.2
17.5°	64.4	69.0	73.6	73.6	78.2	82.8	92.0	96.6	101.2	110.4	115.0
20°	64.4	69.0	73.6	73.6	78.2	87.4	92.0	101.2	105.8	115.0	124.2
22.5°	64.4	69.0	73.6	78.2	82.8	92.0	101.2	105.8	115.0	128.8	138.0
25°	64.4	69.0	73.6	78.2	82.8	92.0	101.2	110.4	119.6	138.0	156.4
27.5°	64.4	69.0	78.2	82.8	87.4	96.6	110.4	119.6	128.8	161.0	193.2
30°	64.4	69.0	78.2	82.8	87.4	101.2	115.0	124.2	138.0	193.2	243.8
32.5°	64.4	73.6	78.2	87.4	92.0	105.8	124.2	138.0	151.8	230.0	303.6
35°	64.4	73.6	78.2	87.4	92.0	110.4	128.8	147.2	165.6	280.6	395.6
37.5°	64.4	73.6	78.2	87.4	92.0	119.6	147.2	174.8	202.4	322.0	441.6
40°	69.0	78.2	82.8	92.0	96.6	124.2	151.8	179.4	207.0	326.6	446.2
42.5°	69.0	78.2	82.8	92.0	96.6	119.6	147.2	170.2	193.2	326.6	460.0
45°	69.0	78.2	87.4	92.0	101.2	124.2	147.2	165.6	188.6	358.8	524.4
47.5°	69.0	78.2	87.4	92.0	101.2	124.2	147.2	170.2	193.2	473.8	749.9
50°	69.0	78.2	87.4	92.0	101.2	128.8	156.4	184.0	211.6	708.5	1205.3
52.5°	73.6	78.2	87.4	92.0	96.6	128.8	161.0	193.2	225.4	920.1	1610.2
55°	78.2	82.8	87.4	92.0	96.6	138.0	179.4	220.8	262.2	989.1	1711.4
57.5°	82.8	87.4	92.0	92.0	96.6	147.2	202.4	253.0	303.6	984.5	1660.8
60°	87.4	92.0	96.6	101.2	105.8	156.4	211.6	262.2	312.8	892.5	1472.1
62.5°	96.6	105.8	115.0	119.6	128.8	179.4	225.4	276.0	322.0	731.5	1136.3
65°	110.4	119.6	124.2	133.4	138.0	184.0	234.6	280.6	326.6	607.3	883.3
67.5°	115.0	124.2	128.8	138.0	142.6	188.6	234.6	280.6	326.6	515.2	699.3
70°	115.0	124.2	133.4	138.0	147.2	193.2	234.6	280.6	322.0	446.2	570.5
72.5°	105.8	119.6	128.8	142.6	151.8	193.2	230.0	271.4	308.2	395.6	483.0
75°	101.2	119.6	133.4	151.8	165.6	193.2	225.4	253.0	280.6	345.0	409.4
77.5°	92.0	115.0	138.0	161.0	184.0	202.4	216.2	234.6	248.4	289.8	331.2
80°	87.4	110.4	133.4	156.4	179.4	188.6	193.2	202.4	207.0	211.6	216.2
82.5°	69.0	87.4	105.8	119.6	138.0	128.8	124.2	115.0	105.8	101.2	96.6
85°	32.2	36.8	36.8	41.4	41.4	41.4	36.8	36.8	32.2	27.6	23.0
87.5°	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	64.4	64.4	64.4	64.4	59.8	59.8	59.8	59.8	55.2	55.2	55.2
5°	73.6	73.6	73.6	73.6	69.0	69.0	69.0	69.0	64.4	64.4	64.4
7.5°	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2
10°	87.4	87.4	87.4	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0
12.5°	96.6	96.6	101.2	101.2	105.8	105.8	110.4	110.4	115.0	115.0	115.0
15°	105.8	110.4	115.0	119.6	119.6	124.2	128.8	133.4	138.0	142.6	147.2
17.5°	124.2	128.8	138.0	147.2	156.4	165.6	179.4	197.8	211.6	225.4	243.8
20°	138.0	151.8	179.4	211.6	239.2	266.8	335.8	404.8	473.8	542.9	611.9
22.5°	165.6	193.2	285.2	381.8	473.8	565.9	782.1	998.3	1209.9	1426.1	1619.4
25°	220.8	280.6	492.2	703.9	910.9	1122.5	1508.9	1900.0	2286.4	2672.9	3031.7
27.5°	303.6	414.0	759.1	1108.7	1453.7	1798.8	2360.0	2925.9	3487.1	4053.0	4554.4
30°	423.2	602.7	1117.9	1637.8	2153.0	2668.2	3376.7	4089.8	4798.2	5506.7	5966.8
32.5°	575.1	841.9	1495.1	2148.4	2801.7	3454.9	4237.0	5019.1	5796.5	6578.6	7066.3
35°	736.1	1076.5	1863.2	2654.4	3441.1	4232.4	5055.9	5879.4	6702.8	7526.3	8124.4
37.5°	828.1	1214.5	2148.4	3082.3	4011.6	4945.5	5847.1	6753.4	7655.1	8556.8	9283.7
40°	915.5	1380.1	2456.6	3533.1	4609.6	5686.1	6739.6	7793.1	8846.6	9900.1	10834.0
42.5°	1044.3	1628.6	2884.5	4140.4	5391.7	6647.6	8032.4	9421.7	10806.4	12191.1	13626.5
45°	1311.1	2097.8	3726.3	5354.9	6978.9	8607.4	10571.8	12540.8	14505.2	16474.1	18314.3
47.5°	1955.2	3155.9	5377.9	7599.9	9821.9	12043.9	14307.3	16570.8	18834.2	21097.6	23287.4
50°	3027.1	4844.3	7622.9	10401.6	13175.6	15954.3	18213.1	20471.9	22726.1	24984.9	27160.9
52.5°	4034.6	6459.0	9444.7	12435.0	15420.6	18410.9	20412.1	22413.3	24414.5	26415.7	28522.7
55°	4379.6	7043.3	10065.7	13092.8	16115.3	19142.4	21070.0	23002.2	24929.7	26857.3	29042.5
57.5°	4076.0	6491.2	9536.7	12582.2	15623.1	18668.5	20821.5	22979.2	25132.2	27289.8	29631.4
60°	3413.5	5350.3	8547.6	11749.5	14946.8	18144.1	20573.1	23002.2	25431.2	27860.2	30197.2
62.5°	2705.1	4269.2	7655.1	11041.0	14427.0	17812.9	20283.3	22758.3	25228.8	27699.2	29493.4
65°	2074.8	3266.3	6597.0	9932.3	13263.0	16598.4	18622.5	20651.3	22675.5	24704.3	25946.4
67.5°	1541.1	2383.0	5295.1	8211.8	11123.8	14035.9	15526.5	17021.6	18512.1	20007.3	20973.4
70°	1136.3	1697.6	3680.3	5663.1	7641.3	9624.1	10990.4	12356.8	13718.5	15084.8	16087.7
72.5°	786.7	1085.7	2272.6	3464.1	4651.0	5837.9	7222.7	8607.4	9987.5	11372.3	12513.2
75°	538.3	667.1	1223.7	1780.4	2337.0	2893.7	3942.6	4991.5	6040.4	7089.3	7691.9
77.5°	400.2	469.2	634.9	805.1	970.7	1136.3	1338.7	1541.1	1743.6	1946.0	2208.2
80°	220.8	220.8	243.8	262.2	285.2	303.6	358.8	418.6	473.8	533.6	607.3
82.5°	101.2	105.8	115.0	124.2	128.8	138.0	147.2	156.4	165.6	174.8	174.8
85°	27.6	32.2	32.2	27.6	27.6	23.0	23.0	27.6	27.6	27.6	27.6
87.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	55.2	50.6	50.6	50.6	46.0	46.0	46.0	46.0	46.0	46.0	46.0
5°	64.4	64.4	64.4	64.4	59.8	59.8	59.8	59.8	59.8	55.2	55.2
7.5°	78.2	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	69.0	69.0
10°	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	87.4	87.4
12.5°	115.0	115.0	115.0	115.0	119.6	119.6	115.0	115.0	115.0	110.4	110.4
15°	151.8	156.4	161.0	161.0	165.6	165.6	165.6	161.0	161.0	156.4	151.8
17.5°	257.6	271.4	289.8	308.2	326.6	340.4	340.4	331.2	322.0	312.8	303.6
20°	685.5	754.5	828.1	901.7	979.9	1035.1	998.3	970.7	943.1	910.9	883.3
22.5°	1817.2	2010.4	2208.2	2346.2	2484.2	2580.8	2502.6	2350.8	2199.0	2051.8	1900.0
25°	3390.5	3744.8	4103.6	4250.8	4402.6	4513.0	4462.4	4232.4	4002.4	3777.0	3546.9
27.5°	5055.9	5552.7	6054.2	6183.0	6311.8	6408.4	6390.0	6091.0	5791.9	5492.9	5193.9
30°	6426.8	6886.8	7346.9	7475.7	7604.5	7691.9	7595.3	7296.3	6997.3	6698.2	6399.2
32.5°	7558.5	8046.2	8538.4	8708.6	8878.8	8993.8	8878.8	8520.0	8161.2	7806.9	7448.1
35°	8722.4	9315.9	9913.9	10130.1	10346.4	10484.4	10291.2	9849.5	9407.9	8970.8	8529.2
37.5°	10010.5	10732.8	11459.7	11754.1	12053.1	12260.1	12112.9	11560.9	11004.2	10452.2	9895.5
40°	11772.5	12706.4	13644.9	14173.9	14698.4	15071.0	14808.8	14169.3	13525.3	12885.8	12241.7
42.5°	15066.4	16501.7	17937.1	18696.2	19450.6	19998.1	19703.6	18917.0	18130.3	17343.6	16556.9
45°	20154.5	21990.1	23830.2	24938.9	26052.2	26871.1	26530.7	25541.6	24547.9	23558.8	22569.7
47.5°	25477.2	27667.0	29856.8	30740.1	31628.0	32318.0	32235.2	31002.3	29769.4	28541.1	27308.2
50°	29341.5	31517.6	33693.6	34452.6	35216.3	35782.1	35570.5	34001.8	32428.4	30859.7	29286.3
52.5°	30629.7	32732.1	34839.1	35745.3	36651.6	37327.9	37070.3	35303.7	33537.1	31775.2	30008.6
55°	31227.7	33412.9	35598.1	36702.2	37810.9	38620.6	38248.0	36311.2	34369.8	32433.0	30491.7
57.5°	31973.0	34314.6	36656.2	37866.1	39076.1	39950.1	39453.3	37447.5	35441.7	33440.5	31434.7
60°	32534.2	34866.7	37203.7	38174.4	39149.7	39830.5	39352.1	37401.5	35446.3	33495.7	31545.2
62.5°	31292.1	33086.3	34880.5	35602.7	36325.0	36849.4	36578.0	34728.7	32879.3	31029.9	29180.5
65°	27193.1	28435.3	29682.0	30169.6	30652.7	31025.3	30942.5	29383.0	27823.4	26268.5	24708.9
67.5°	21944.1	22910.1	23880.8	24570.9	25265.6	25803.8	25744.0	24322.5	22900.9	21479.4	20057.9
70°	17095.2	18098.1	19101.0	19970.5	20844.6	21520.8	21433.4	20113.1	18788.2	17467.8	16142.9
72.5°	13658.7	14799.6	15940.5	16437.3	16934.2	17283.8	17026.2	16027.9	15025.0	14026.7	13023.8
75°	8294.6	8892.6	9495.3	9490.7	9490.7	9435.5	9177.9	8607.4	8037.0	7466.5	6896.0
77.5°	2470.4	2732.7	2994.9	3247.9	3505.5	3698.7	3648.1	3349.1	3045.5	2746.5	2442.8
80°	680.9	749.9	823.5	855.7	887.9	929.3	1035.1	961.5	887.9	818.9	745.3
82.5°	174.8	174.8	174.8	170.2	165.6	156.4	142.6	133.4	124.2	115.0	105.8
85°	27.6	23.0	23.0	23.0	18.4	18.4	18.4	18.4	13.8	13.8	9.2
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	46.0	46.0	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	36.8
5°	55.2	55.2	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6	46.0
7.5°	69.0	69.0	64.4	64.4	64.4	64.4	59.8	59.8	59.8	59.8	55.2
10°	87.4	82.8	82.8	78.2	78.2	78.2	73.6	73.6	73.6	69.0	69.0
12.5°	110.4	105.8	105.8	101.2	96.6	96.6	92.0	87.4	82.8	82.8	78.2
15°	147.2	142.6	138.0	133.4	128.8	119.6	115.0	105.8	101.2	96.6	92.0
17.5°	280.6	257.6	234.6	211.6	193.2	174.8	156.4	138.0	128.8	119.6	110.4
20°	782.1	676.3	575.1	473.8	409.4	345.0	280.6	216.2	188.6	165.6	138.0
22.5°	1693.0	1481.3	1274.3	1062.7	892.5	726.9	556.7	386.4	322.0	262.2	197.8
25°	3146.7	2741.9	2341.6	1936.8	1614.8	1292.7	970.7	648.7	529.0	409.4	289.8
27.5°	4669.4	4145.0	3620.5	3096.1	2585.4	2070.2	1554.9	1044.3	837.3	634.9	427.8
30°	5842.5	5285.9	4733.8	4177.2	3533.1	2889.1	2240.4	1596.3	1269.7	943.1	611.9
32.5°	6850.0	6247.4	5649.3	5046.7	4301.4	3556.1	2810.9	2065.6	1656.2	1246.7	832.7
35°	7848.3	7162.9	6482.0	5796.5	4996.1	4195.6	3395.1	2594.6	2074.8	1554.9	1030.5
37.5°	9062.8	8225.6	7392.9	6560.2	5736.7	4917.9	4094.4	3270.9	2608.4	1950.6	1288.1
40°	11179.0	10111.7	9049.0	7981.7	7020.3	6063.4	5101.9	4140.4	3307.7	2475.0	1637.8
42.5°	15218.2	13879.5	12545.4	11206.6	9877.1	8547.6	7213.5	5884.0	4697.0	3514.7	2327.8
45°	20853.8	19137.8	17426.4	15710.5	14072.7	12439.6	10801.8	9164.1	7360.7	5557.3	3749.4
47.5°	25431.2	23549.6	21672.6	19791.1	17973.9	16161.3	14344.1	12527.0	10217.6	7912.7	5603.3
50°	27496.8	25702.6	23913.0	22118.9	20297.1	18470.7	16644.4	14822.6	12172.7	9527.5	6877.6
52.5°	28191.4	26369.7	24552.5	22730.7	20922.8	19114.8	17306.8	15498.9	12743.2	9992.1	7236.5
55°	28573.3	26650.3	24731.9	22808.9	20863.0	18912.4	16961.8	15015.8	12273.9	9536.7	6794.8
57.5°	29346.1	27253.0	25164.4	23071.2	20853.8	18636.3	16414.3	14196.9	11491.9	8786.8	6081.8
60°	29488.8	27427.8	25371.4	23315.0	20863.0	18410.9	15954.3	13502.3	10815.6	8133.6	5446.9
62.5°	27460.0	25739.4	24023.4	22302.9	19846.3	17389.6	14928.4	12471.8	9900.1	7328.5	4752.2
65°	23223.0	21737.0	20255.7	18769.8	16764.0	14762.8	12757.0	10751.2	8455.6	6164.6	3869.0
67.5°	18604.1	17150.4	15701.3	14247.5	12738.6	11234.3	9725.3	8216.4	6445.2	4674.0	2902.9
70°	14749.0	13350.4	11956.5	10558.0	9223.9	7885.1	6546.4	5212.3	4112.8	3017.9	1918.4
72.5°	11689.7	10351.0	9016.8	7678.1	6468.2	5258.3	4048.4	2838.5	2291.0	1748.2	1200.7
75°	6201.4	5506.7	4816.7	4122.0	3441.1	2755.7	2070.2	1389.3	1173.1	956.9	736.1
77.5°	2139.2	1835.6	1536.5	1232.9	1025.9	818.9	611.9	404.8	381.8	363.4	340.4
80°	648.7	552.1	455.4	358.8	317.4	276.0	234.6	193.2	179.4	165.6	147.2
82.5°	101.2	92.0	87.4	78.2	73.6	73.6	69.0	64.4	55.2	50.6	41.4
85°	9.2	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066536
 CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	41.4	41.4
2.5°	36.8	36.8
5°	46.0	46.0
7.5°	55.2	55.2
10°	64.4	64.4
12.5°	73.6	73.6
15°	87.4	82.8
17.5°	101.2	96.6
20°	110.4	101.2
22.5°	133.4	115.0
25°	170.2	142.6
27.5°	220.8	174.8
30°	285.2	220.8
32.5°	423.2	308.2
35°	510.6	372.6
37.5°	625.7	432.4
40°	805.1	524.4
42.5°	1140.9	713.1
45°	1946.0	1182.3
47.5°	3298.5	2015.0
50°	4227.8	2585.4
52.5°	4485.4	2741.9
55°	4057.6	2516.4
57.5°	3376.7	2139.2
60°	2764.9	1762.0
62.5°	2180.6	1393.9
65°	1573.3	1053.5
67.5°	1131.7	809.7
70°	823.5	634.9
72.5°	653.3	529.0
75°	519.8	441.6
77.5°	322.0	294.4
80°	133.4	124.2
82.5°	32.2	27.6
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066536

CATALOG NUMBER: NVN-SA3D-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-5

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-735-U-5WQ

Data in this report applies to families of products including GSS-SB1A-735-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-735-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3369
 CIE u' : 0.2386
 CIE v' : 0.5156
 Duv: 0.0013
 CIE x: 0.4143
 CIE y: 0.3980
 CIE z: 0.1877
 Peak Wavelength (nm): 590
 Dominant Wavelength (nm): 580
 Purity: 43.80166
 R_f: 71.4
 R_g: 96

CRI (Ra): 70.1
 R1: 66.6
 R2: 77.6
 R3: 88.5
 R4: 69.5
 R5: 66.4
 R6: 69.6
 R7: 77.5
 R8: 44.9
 R9: -40.2
 R10: 49.1
 R11: 66.3
 R12: 45.7
 R13: 68.0
 R14: 93.4
 R15: 57.6



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-5

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-5

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-5

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.29

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Melanopic Flux vs. Wavelength

Melanopic Lumens: NR
M/P: 2.36


λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5



TM-30-18

Summary

$R_f = 71.4$
 $R_g = 96$
 CIE $R_a = 70.1$
 $R_g = -40.2$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 57	CES51 = 84	CES76 = 50
CES02 = 62	CES27 = 80	CES52 = 86	CES77 = 74
CES03 = 31	CES28 = 81	CES53 = 72	CES78 = 54
CES04 = 70	CES29 = 50	CES54 = 79	CES79 = 81
CES05 = 48	CES30 = 55	CES55 = 78	CES80 = 79
CES06 = 51	CES31 = 56	CES56 = 67	CES81 = 74
CES07 = 40	CES32 = 54	CES57 = 65	CES82 = 91
CES08 = 39	CES33 = 60	CES58 = 68	CES83 = 86
CES09 = 29	CES34 = 69	CES59 = 85	CES84 = 89
CES10 = 75	CES35 = 83	CES60 = 91	CES85 = 83
CES11 = 58	CES36 = 88	CES61 = 85	CES86 = 66
CES12 = 64	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 43	CES38 = 64	CES63 = 71	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 70	CES89 = 68
CES15 = 71	CES40 = 86	CES65 = 64	CES90 = 72
CES16 = 47	CES41 = 81	CES66 = 65	CES91 = 95
CES17 = 50	CES42 = 79	CES67 = 63	CES92 = 62
CES18 = 56	CES43 = 71	CES68 = 69	CES93 = 78
CES19 = 72	CES44 = 98	CES69 = 80	CES94 = 51
CES20 = 65	CES45 = 80	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 75	CES71 = 58	CES96 = 76
CES22 = 79	CES47 = 71	CES72 = 85	CES97 = 82
CES23 = 92	CES48 = 61	CES73 = 51	CES98 = 72
CES24 = 91	CES49 = 74	CES74 = 94	CES99 = 60
CES25 = 72	CES50 = 83	CES75 = 57	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)