

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066538

Luminaire Tested: **NVN-SA4B-735-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066538
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA4B-735-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 4xLight Square PACKAGE
70CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 3500K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 14143 lumens
Efficiency: N/A
Efficacy: 98.1 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 144.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	84.1	0.0	84.1
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	14058.8	0.0	14058.8
	% Fixture	99.4	0.0	99.4
Total	Lumens	14143.0	0.0	14143.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.2	0.0
10°-20°	20.7	0.1
20°-30°	264.0	1.9
30°-40°	889.6	6.3
40°-50°	2686.7	19.0
50°-60°	4740.2	33.5
60°-70°	4176.1	29.5
70°-80°	1329.4	9.4
80°-90°	32.0	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	14143.0	100.0
0°-180°	14143.0	100.0



REPORT NUMBER: P1066538


CATALOG NUMBER: NVN-SA4B-735-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	276.3	2.0			
FM	(30°-60°)	8284.0	58.6			
FH	(60°-80°)	5472.5	38.7			G3/7500
FVH	(80°-90°)	26.0	0.2			G1/100
BL	(0°-30°)	12.6	0.1	B0/110		
BM	(30°-60°)	32.6	0.2	B0/220		
BH	(60°-80°)	33.0	0.2	B0/110		G0/110
BVH	(80°-90°)	6.0	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5	31.0
5°	44.4	44.4	44.4	39.9	39.9	39.9	35.5	35.5	35.5	35.5	35.5
7.5°	53.2	48.8	48.8	44.4	44.4	44.4	39.9	39.9	39.9	39.9	35.5
10°	62.1	57.7	57.7	53.2	53.2	48.8	48.8	44.4	44.4	39.9	39.9
12.5°	71.0	66.5	62.1	57.7	57.7	53.2	53.2	48.8	48.8	44.4	44.4
15°	79.8	75.4	71.0	66.5	62.1	62.1	57.7	53.2	48.8	48.8	44.4
17.5°	93.1	84.3	79.8	71.0	66.5	62.1	57.7	53.2	53.2	48.8	48.8
20°	97.6	88.7	84.3	75.4	71.0	66.5	62.1	57.7	53.2	53.2	48.8
22.5°	115.3	97.6	93.1	84.3	79.8	75.4	66.5	62.1	57.7	53.2	48.8
25°	141.9	115.3	102.0	88.7	84.3	75.4	71.0	62.1	57.7	53.2	48.8
27.5°	173.0	128.6	115.3	97.6	88.7	79.8	71.0	62.1	57.7	53.2	48.8
30°	212.9	150.8	128.6	106.4	97.6	88.7	75.4	66.5	62.1	57.7	48.8
32.5°	297.2	186.3	150.8	115.3	102.0	93.1	79.8	66.5	62.1	57.7	48.8
35°	359.3	226.2	181.8	133.1	115.3	102.0	84.3	66.5	62.1	57.7	48.8
37.5°	416.9	230.6	186.3	141.9	124.2	106.4	84.3	66.5	62.1	57.7	48.8
40°	510.1	239.5	186.3	133.1	119.8	102.0	88.7	71.0	66.5	57.7	53.2
42.5°	687.5	275.0	199.6	124.2	110.9	102.0	88.7	75.4	66.5	62.1	53.2
45°	1144.3	408.0	270.5	128.6	115.3	102.0	88.7	75.4	71.0	62.1	57.7
47.5°	1947.1	709.6	421.3	133.1	119.8	102.0	88.7	71.0	66.5	62.1	53.2
50°	2492.6	909.2	532.2	155.2	133.1	115.3	93.1	71.0	66.5	62.1	57.7
52.5°	2647.8	966.9	576.6	181.8	155.2	128.6	97.6	71.0	66.5	66.5	62.1
55°	2426.1	940.3	576.6	212.9	177.4	146.4	110.9	75.4	71.0	71.0	66.5
57.5°	2062.4	869.3	550.0	230.6	195.1	155.2	119.8	79.8	75.4	75.4	71.0
60°	1698.7	731.8	496.7	257.2	217.3	177.4	137.5	97.6	93.1	88.7	79.8
62.5°	1348.3	589.9	434.7	275.0	235.1	190.7	150.8	106.4	102.0	97.6	93.1
65°	1015.7	514.5	403.6	288.3	243.9	199.6	155.2	110.9	106.4	106.4	102.0
67.5°	780.6	470.1	385.9	297.2	252.8	208.5	164.1	119.8	115.3	110.9	106.4
70°	616.5	434.7	363.7	292.7	252.8	212.9	168.5	128.6	119.8	115.3	106.4
72.5°	514.5	394.7	337.1	279.4	248.4	217.3	186.3	155.2	137.5	124.2	106.4
75°	430.2	354.8	306.0	252.8	230.6	212.9	190.7	168.5	146.4	124.2	102.0
77.5°	283.9	257.2	235.1	212.9	199.6	186.3	168.5	155.2	133.1	115.3	93.1
80°	119.8	110.9	115.3	115.3	115.3	115.3	110.9	110.9	97.6	84.3	66.5
82.5°	26.6	22.2	26.6	26.6	26.6	26.6	22.2	22.2	22.2	17.7	17.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0
5°	35.5	35.5	35.5	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0
7.5°	35.5	35.5	35.5	31.0	31.0	31.0	31.0	26.6	26.6	26.6	26.6
10°	35.5	35.5	35.5	31.0	31.0	31.0	31.0	26.6	26.6	26.6	26.6
12.5°	39.9	39.9	35.5	35.5	31.0	31.0	31.0	26.6	26.6	26.6	26.6
15°	39.9	39.9	35.5	35.5	31.0	31.0	31.0	26.6	26.6	26.6	26.6
17.5°	44.4	39.9	39.9	35.5	31.0	31.0	31.0	26.6	26.6	26.6	26.6
20°	44.4	39.9	39.9	35.5	31.0	31.0	31.0	26.6	26.6	26.6	26.6
22.5°	44.4	39.9	39.9	35.5	31.0	31.0	26.6	26.6	22.2	22.2	17.7
25°	44.4	39.9	39.9	35.5	31.0	31.0	26.6	26.6	22.2	17.7	17.7
27.5°	44.4	39.9	39.9	35.5	31.0	26.6	26.6	22.2	17.7	13.3	13.3
30°	44.4	39.9	39.9	35.5	31.0	26.6	22.2	17.7	13.3	13.3	8.9
32.5°	44.4	39.9	35.5	31.0	26.6	22.2	22.2	17.7	13.3	8.9	8.9
35°	44.4	39.9	35.5	31.0	26.6	22.2	22.2	17.7	13.3	8.9	8.9
37.5°	44.4	39.9	35.5	31.0	26.6	22.2	17.7	13.3	8.9	8.9	4.4
40°	44.4	39.9	35.5	31.0	26.6	22.2	17.7	13.3	8.9	8.9	4.4
42.5°	44.4	39.9	35.5	31.0	26.6	22.2	17.7	13.3	8.9	8.9	4.4
45°	48.8	44.4	39.9	31.0	26.6	22.2	22.2	17.7	13.3	8.9	8.9
47.5°	48.8	44.4	39.9	31.0	26.6	22.2	22.2	17.7	13.3	8.9	8.9
50°	53.2	48.8	44.4	35.5	31.0	26.6	22.2	13.3	8.9	8.9	4.4
52.5°	57.7	53.2	48.8	44.4	39.9	31.0	22.2	13.3	4.4	4.4	4.4
55°	62.1	57.7	57.7	53.2	48.8	35.5	26.6	13.3	0.0	0.0	0.0
57.5°	66.5	62.1	62.1	57.7	53.2	39.9	26.6	13.3	0.0	0.0	0.0
60°	75.4	71.0	66.5	57.7	53.2	39.9	26.6	13.3	0.0	0.0	0.0
62.5°	88.7	79.8	66.5	57.7	44.4	35.5	22.2	13.3	0.0	0.0	0.0
65°	97.6	84.3	71.0	53.2	39.9	31.0	22.2	8.9	0.0	0.0	0.0
67.5°	102.0	84.3	71.0	53.2	35.5	26.6	17.7	8.9	0.0	0.0	0.0
70°	97.6	79.8	66.5	48.8	31.0	22.2	17.7	8.9	0.0	0.0	0.0
72.5°	88.7	75.4	57.7	44.4	26.6	22.2	13.3	8.9	0.0	0.0	0.0
75°	79.8	66.5	48.8	35.5	17.7	13.3	8.9	4.4	0.0	0.0	0.0
77.5°	71.0	57.7	39.9	26.6	8.9	8.9	4.4	4.4	0.0	0.0	0.0
80°	53.2	39.9	26.6	13.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	13.3	8.9	8.9	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6
5°	26.6	26.6	26.6	26.6	22.2	22.2	22.2	22.2	22.2	22.2	22.2
7.5°	26.6	26.6	26.6	26.6	22.2	22.2	22.2	22.2	17.7	17.7	17.7
10°	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	17.7	17.7	17.7
12.5°	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	17.7	17.7	17.7
15°	22.2	22.2	22.2	22.2	22.2	22.2	22.2	17.7	17.7	13.3	13.3
17.5°	22.2	22.2	22.2	22.2	17.7	17.7	17.7	13.3	13.3	8.9	8.9
20°	22.2	22.2	22.2	17.7	17.7	13.3	13.3	8.9	8.9	4.4	4.4
22.5°	17.7	13.3	13.3	8.9	8.9	4.4	4.4	4.4	0.0	0.0	0.0
25°	13.3	8.9	8.9	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.9	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.9	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	26.6	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2
5°	22.2	22.2	22.2	22.2	17.7	17.7	17.7	17.7	17.7	17.7	17.7
7.5°	17.7	17.7	17.7	17.7	17.7	17.7	13.3	13.3	13.3	13.3	13.3
10°	17.7	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	8.9	8.9
12.5°	17.7	13.3	13.3	13.3	8.9	8.9	8.9	8.9	8.9	4.4	4.4
15°	13.3	8.9	8.9	8.9	4.4	4.4	4.4	4.4	4.4	0.0	0.0
17.5°	8.9	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	26.6	26.6
5°	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7	17.7
7.5°	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3
10°	8.9	8.9	8.9	8.9	8.9	8.9	4.4	4.4	4.4	4.4	4.4
12.5°	4.4	4.4	4.4	4.4	4.4	4.4	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	26.6	26.6	26.6	26.6	26.6	31.0	31.0	35.5	35.5	39.9	39.9
5°	17.7	17.7	22.2	22.2	22.2	22.2	26.6	26.6	26.6	31.0	31.0
7.5°	13.3	13.3	13.3	13.3	13.3	17.7	17.7	22.2	22.2	26.6	26.6
10°	4.4	4.4	8.9	8.9	8.9	8.9	13.3	13.3	13.3	17.7	22.2
12.5°	0.0	0.0	4.4	4.4	4.4	4.4	8.9	8.9	8.9	13.3	17.7
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	8.9	13.3
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	8.9
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	44.4	44.4	48.8	48.8	53.2	53.2	57.7	57.7	57.7	57.7	57.7
5°	35.5	35.5	39.9	44.4	44.4	48.8	53.2	53.2	53.2	53.2	53.2
7.5°	31.0	31.0	35.5	39.9	39.9	44.4	48.8	48.8	53.2	53.2	53.2
10°	22.2	26.6	31.0	35.5	35.5	39.9	44.4	44.4	48.8	48.8	48.8
12.5°	17.7	22.2	26.6	31.0	31.0	35.5	39.9	39.9	44.4	44.4	48.8
15°	13.3	17.7	22.2	26.6	26.6	31.0	35.5	35.5	39.9	44.4	48.8
17.5°	8.9	13.3	17.7	22.2	22.2	26.6	31.0	35.5	39.9	39.9	44.4
20°	8.9	8.9	13.3	17.7	17.7	22.2	26.6	31.0	35.5	35.5	39.9
22.5°	4.4	4.4	8.9	13.3	13.3	17.7	22.2	26.6	31.0	31.0	35.5
25°	0.0	0.0	4.4	8.9	8.9	13.3	17.7	17.7	22.2	22.2	26.6
27.5°	0.0	0.0	4.4	4.4	8.9	8.9	13.3	13.3	17.7	17.7	22.2
30°	0.0	0.0	4.4	4.4	8.9	8.9	13.3	13.3	17.7	17.7	17.7
32.5°	0.0	0.0	0.0	4.4	4.4	4.4	8.9	8.9	13.3	13.3	17.7
35°	0.0	0.0	0.0	4.4	4.4	4.4	8.9	8.9	13.3	13.3	13.3
37.5°	0.0	0.0	0.0	4.4	4.4	4.4	8.9	8.9	8.9	8.9	13.3
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.9	8.9	8.9
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.9	8.9	8.9
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.9	8.9	8.9
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.9	8.9	8.9
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.9	8.9	8.9
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.9	8.9	8.9
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	8.9	8.9	8.9
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	8.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	57.7	57.7
5°	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	53.2	53.2
7.5°	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	53.2	53.2
10°	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
12.5°	48.8	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
15°	48.8	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
17.5°	44.4	48.8	48.8	48.8	53.2	53.2	53.2	53.2	53.2	53.2	53.2
20°	39.9	44.4	44.4	44.4	48.8	48.8	48.8	48.8	53.2	53.2	53.2
22.5°	35.5	39.9	39.9	39.9	44.4	44.4	44.4	44.4	48.8	48.8	48.8
25°	31.0	31.0	35.5	35.5	39.9	39.9	39.9	39.9	39.9	39.9	39.9
27.5°	22.2	26.6	26.6	26.6	31.0	31.0	31.0	31.0	35.5	35.5	35.5
30°	22.2	22.2	22.2	22.2	26.6	26.6	26.6	26.6	31.0	31.0	31.0
32.5°	17.7	22.2	22.2	22.2	26.6	26.6	26.6	26.6	31.0	31.0	31.0
35°	17.7	17.7	17.7	17.7	22.2	22.2	22.2	22.2	26.6	26.6	26.6
37.5°	13.3	17.7	17.7	17.7	22.2	22.2	22.2	22.2	26.6	26.6	26.6
40°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.2	22.2	22.2
42.5°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.2	22.2	22.2
45°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.2	22.2	22.2
47.5°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.2	22.2	22.2
50°	13.3	13.3	13.3	13.3	17.7	17.7	17.7	17.7	22.2	22.2	22.2
52.5°	8.9	8.9	8.9	8.9	13.3	13.3	13.3	13.3	17.7	17.7	17.7
55°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	13.3	13.3	13.3
57.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	13.3	13.3	13.3
60°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
62.5°	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
65°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	4.4	4.4
67.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
70°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
72.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
75°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
77.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
80°	13.3	13.3	13.3	13.3	13.3	8.9	8.9	8.9	8.9	8.9	8.9
82.5°	8.9	13.3	13.3	13.3	13.3	8.9	8.9	8.9	8.9	8.9	8.9
85°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
87.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	57.7	57.7	53.2	53.2	53.2	53.2	53.2	53.2	53.2	57.7	57.7
5°	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	57.7	57.7
7.5°	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	57.7	57.7
10°	53.2	53.2	53.2	53.2	48.8	48.8	53.2	53.2	53.2	57.7	57.7
12.5°	53.2	53.2	53.2	53.2	48.8	48.8	53.2	53.2	57.7	57.7	62.1
15°	53.2	53.2	48.8	48.8	48.8	48.8	53.2	53.2	57.7	57.7	62.1
17.5°	53.2	53.2	48.8	48.8	48.8	48.8	53.2	53.2	57.7	57.7	62.1
20°	53.2	53.2	48.8	48.8	48.8	48.8	48.8	48.8	53.2	57.7	57.7
22.5°	48.8	48.8	48.8	48.8	44.4	44.4	48.8	48.8	53.2	57.7	57.7
25°	39.9	44.4	44.4	44.4	44.4	44.4	48.8	48.8	53.2	57.7	57.7
27.5°	35.5	39.9	39.9	39.9	39.9	44.4	44.4	48.8	53.2	57.7	57.7
30°	31.0	35.5	35.5	35.5	39.9	44.4	44.4	48.8	53.2	57.7	57.7
32.5°	31.0	35.5	35.5	35.5	39.9	39.9	44.4	44.4	48.8	53.2	57.7
35°	31.0	31.0	35.5	35.5	35.5	39.9	39.9	44.4	48.8	53.2	57.7
37.5°	31.0	31.0	35.5	35.5	35.5	39.9	39.9	44.4	48.8	53.2	57.7
40°	26.6	31.0	31.0	35.5	35.5	39.9	39.9	44.4	48.8	57.7	62.1
42.5°	26.6	26.6	31.0	31.0	35.5	39.9	39.9	44.4	48.8	57.7	62.1
45°	26.6	31.0	31.0	35.5	39.9	44.4	44.4	48.8	53.2	57.7	62.1
47.5°	26.6	31.0	31.0	35.5	44.4	44.4	48.8	48.8	53.2	57.7	62.1
50°	26.6	31.0	31.0	35.5	48.8	48.8	48.8	48.8	53.2	57.7	62.1
52.5°	22.2	26.6	26.6	31.0	39.9	44.4	48.8	53.2	57.7	62.1	66.5
55°	17.7	22.2	22.2	26.6	35.5	39.9	48.8	57.7	62.1	66.5	71.0
57.5°	17.7	17.7	22.2	22.2	31.0	39.9	53.2	62.1	66.5	71.0	75.4
60°	13.3	13.3	17.7	17.7	26.6	35.5	48.8	62.1	66.5	75.4	79.8
62.5°	8.9	13.3	13.3	17.7	22.2	35.5	48.8	62.1	71.0	79.8	84.3
65°	8.9	8.9	13.3	13.3	22.2	31.0	44.4	53.2	66.5	79.8	93.1
67.5°	13.3	13.3	17.7	17.7	22.2	31.0	44.4	53.2	66.5	84.3	97.6
70°	13.3	13.3	17.7	17.7	26.6	35.5	44.4	53.2	66.5	84.3	97.6
72.5°	13.3	13.3	17.7	17.7	26.6	31.0	39.9	48.8	62.1	75.4	88.7
75°	8.9	13.3	13.3	13.3	22.2	26.6	35.5	44.4	57.7	71.0	84.3
77.5°	8.9	8.9	8.9	8.9	17.7	22.2	31.0	35.5	48.8	62.1	75.4
80°	8.9	8.9	8.9	8.9	13.3	17.7	26.6	31.0	44.4	57.7	71.0
82.5°	8.9	8.9	4.4	4.4	8.9	13.3	17.7	22.2	35.5	44.4	57.7
85°	8.9	8.9	4.4	4.4	4.4	8.9	8.9	13.3	17.7	22.2	26.6
87.5°	8.9	8.9	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	57.7	57.7	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1
5°	57.7	62.1	62.1	66.5	66.5	66.5	71.0	71.0	71.0	71.0	71.0
7.5°	57.7	62.1	62.1	66.5	66.5	66.5	71.0	71.0	71.0	75.4	75.4
10°	57.7	62.1	62.1	66.5	66.5	71.0	75.4	75.4	79.8	79.8	79.8
12.5°	62.1	66.5	66.5	71.0	71.0	75.4	79.8	79.8	84.3	88.7	88.7
15°	62.1	66.5	71.0	71.0	75.4	79.8	84.3	84.3	88.7	93.1	97.6
17.5°	62.1	66.5	71.0	71.0	75.4	79.8	88.7	93.1	97.6	106.4	110.9
20°	62.1	66.5	71.0	71.0	75.4	84.3	88.7	97.6	102.0	110.9	119.8
22.5°	62.1	66.5	71.0	75.4	79.8	88.7	97.6	102.0	110.9	124.2	133.1
25°	62.1	66.5	71.0	75.4	79.8	88.7	97.6	106.4	115.3	133.1	150.8
27.5°	62.1	66.5	75.4	79.8	84.3	93.1	106.4	115.3	124.2	155.2	186.3
30°	62.1	66.5	75.4	79.8	84.3	97.6	110.9	119.8	133.1	186.3	235.1
32.5°	62.1	71.0	75.4	84.3	88.7	102.0	119.8	133.1	146.4	221.8	292.7
35°	62.1	71.0	75.4	84.3	88.7	106.4	124.2	141.9	159.7	270.5	381.4
37.5°	62.1	71.0	75.4	84.3	88.7	115.3	141.9	168.5	195.1	310.5	425.8
40°	66.5	75.4	79.8	88.7	93.1	119.8	146.4	173.0	199.6	314.9	430.2
42.5°	66.5	75.4	79.8	88.7	93.1	115.3	141.9	164.1	186.3	314.9	443.5
45°	66.5	75.4	84.3	88.7	97.6	119.8	141.9	159.7	181.8	345.9	505.6
47.5°	66.5	75.4	84.3	88.7	97.6	119.8	141.9	164.1	186.3	456.8	722.9
50°	66.5	75.4	84.3	88.7	97.6	124.2	150.8	177.4	204.0	683.0	1162.0
52.5°	71.0	75.4	84.3	88.7	93.1	124.2	155.2	186.3	217.3	887.0	1552.3
55°	75.4	79.8	84.3	88.7	93.1	133.1	173.0	212.9	252.8	953.6	1649.9
57.5°	79.8	84.3	88.7	88.7	93.1	141.9	195.1	243.9	292.7	949.1	1601.1
60°	84.3	88.7	93.1	97.6	102.0	150.8	204.0	252.8	301.6	860.4	1419.3
62.5°	93.1	102.0	110.9	115.3	124.2	173.0	217.3	266.1	310.5	705.2	1095.5
65°	106.4	115.3	119.8	128.6	133.1	177.4	226.2	270.5	314.9	585.4	851.6
67.5°	110.9	119.8	124.2	133.1	137.5	181.8	226.2	270.5	314.9	496.7	674.2
70°	110.9	119.8	128.6	133.1	141.9	186.3	226.2	270.5	310.5	430.2	550.0
72.5°	102.0	115.3	124.2	137.5	146.4	186.3	221.8	261.7	297.2	381.4	465.7
75°	97.6	115.3	128.6	146.4	159.7	186.3	217.3	243.9	270.5	332.6	394.7
77.5°	88.7	110.9	133.1	155.2	177.4	195.1	208.5	226.2	239.5	279.4	319.3
80°	84.3	106.4	128.6	150.8	173.0	181.8	186.3	195.1	199.6	204.0	208.5
82.5°	66.5	84.3	102.0	115.3	133.1	124.2	119.8	110.9	102.0	97.6	93.1
85°	31.0	35.5	35.5	39.9	39.9	39.9	35.5	35.5	31.0	26.6	22.2
87.5°	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	62.1	62.1	62.1	62.1	57.7	57.7	57.7	57.7	53.2	53.2	53.2
5°	71.0	71.0	71.0	71.0	66.5	66.5	66.5	66.5	62.1	62.1	62.1
7.5°	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4
10°	84.3	84.3	84.3	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7
12.5°	93.1	93.1	97.6	97.6	102.0	102.0	106.4	106.4	110.9	110.9	110.9
15°	102.0	106.4	110.9	115.3	115.3	119.8	124.2	128.6	133.1	137.5	141.9
17.5°	119.8	124.2	133.1	141.9	150.8	159.7	173.0	190.7	204.0	217.3	235.1
20°	133.1	146.4	173.0	204.0	230.6	257.2	323.8	390.3	456.8	523.4	589.9
22.5°	159.7	186.3	275.0	368.1	456.8	545.5	754.0	962.4	1166.5	1374.9	1561.2
25°	212.9	270.5	474.6	678.6	878.2	1082.2	1454.8	1831.7	2204.3	2576.9	2922.8
27.5°	292.7	399.2	731.8	1068.9	1401.5	1734.2	2275.3	2820.8	3361.9	3907.4	4390.9
30°	408.0	581.0	1077.8	1578.9	2075.7	2572.4	3255.5	3942.9	4625.9	5309.0	5752.5
32.5°	554.4	811.6	1441.4	2071.3	2701.1	3330.9	4084.8	4838.8	5588.4	6342.4	6812.5
35°	709.6	1037.8	1796.3	2559.1	3317.5	4080.4	4874.3	5668.2	6462.1	7256.0	7832.6
37.5°	798.3	1170.9	2071.3	2971.6	3867.5	4767.9	5637.2	6510.9	7380.2	8249.5	8950.3
40°	882.6	1330.6	2368.4	3406.3	4444.1	5481.9	6497.6	7513.3	8528.9	9544.6	10445.0
42.5°	1006.8	1570.1	2780.9	3991.7	5198.1	6408.9	7743.9	9083.3	10418.3	11753.3	13137.1
45°	1264.0	2022.5	3592.5	5162.6	6728.2	8298.3	10192.1	12090.4	13984.3	15882.5	17656.6
47.5°	1885.0	3042.6	5184.8	7327.0	9469.2	11611.4	13793.6	15975.7	18157.8	20339.9	22451.1
50°	2918.4	4670.3	7349.2	10028.0	12702.5	15381.4	17559.1	19736.8	21910.0	24087.7	26185.6
52.5°	3889.7	6227.1	9105.5	11988.4	14866.9	17749.8	19679.1	21608.4	23537.7	25467.1	27498.4
55°	4222.3	6790.3	9704.3	12622.7	15536.6	18455.0	20313.3	22176.1	24034.5	25892.8	27999.6
57.5°	3929.6	6258.1	9194.2	12130.3	15062.0	17998.1	20073.8	22153.9	24229.6	26309.8	28567.3
60°	3290.9	5158.2	8240.6	11327.6	14410.0	17492.5	19834.3	22176.1	24517.9	26859.7	29112.8
62.5°	2607.9	4115.9	7380.2	10644.5	13908.9	17173.2	19554.9	21941.1	24322.8	26704.5	28434.2
65°	2000.3	3149.0	6360.1	9575.7	12786.8	16002.3	17953.8	19909.7	21861.2	23817.2	25014.7
67.5°	1485.8	2297.4	5104.9	7916.9	10724.4	13531.9	14968.9	16410.3	17847.3	19288.8	20220.2
70°	1095.5	1636.6	3548.2	5459.8	7366.9	9278.5	10595.8	11913.0	13225.8	14543.1	15510.0
72.5°	758.4	1046.7	2191.0	3339.7	4484.0	5628.3	6963.3	8298.3	9628.9	10963.9	12063.8
75°	518.9	643.1	1179.8	1716.4	2253.1	2789.8	3801.0	4812.2	5823.5	6834.7	7415.7
77.5°	385.9	452.4	612.1	776.2	935.8	1095.5	1290.7	1485.8	1681.0	1876.1	2128.9
80°	212.9	212.9	235.1	252.8	275.0	292.7	345.9	403.6	456.8	514.5	585.4
82.5°	97.6	102.0	110.9	119.8	124.2	133.1	141.9	150.8	159.7	168.5	168.5
85°	26.6	31.0	31.0	26.6	26.6	22.2	22.2	26.6	26.6	26.6	26.6
87.5°	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	53.2	48.8	48.8	48.8	44.4	44.4	44.4	44.4	44.4	44.4	44.4
5°	62.1	62.1	62.1	62.1	57.7	57.7	57.7	57.7	57.7	53.2	53.2
7.5°	75.4	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	66.5	66.5
10°	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	84.3	84.3
12.5°	110.9	110.9	110.9	110.9	115.3	115.3	110.9	110.9	110.9	106.4	106.4
15°	146.4	150.8	155.2	155.2	159.7	159.7	159.7	155.2	155.2	150.8	146.4
17.5°	248.4	261.7	279.4	297.2	314.9	328.2	328.2	319.3	310.5	301.6	292.7
20°	660.8	727.4	798.3	869.3	944.7	997.9	962.4	935.8	909.2	878.2	851.6
22.5°	1751.9	1938.2	2128.9	2262.0	2395.0	2488.2	2412.8	2266.4	2120.0	1978.1	1831.7
25°	3268.8	3610.3	3956.2	4098.1	4244.5	4351.0	4302.2	4080.4	3858.6	3641.3	3419.6
27.5°	4874.3	5353.3	5836.8	5960.9	6085.1	6178.3	6160.5	5872.2	5583.9	5295.7	5007.4
30°	6196.0	6639.5	7083.1	7207.2	7331.4	7415.7	7322.6	7034.3	6746.0	6457.7	6169.4
32.5°	7287.1	7757.2	8231.8	8395.9	8560.0	8670.9	8560.0	8214.0	7868.1	7526.6	7180.6
35°	8409.2	8981.3	9557.9	9766.4	9974.8	10107.9	9921.6	9495.8	9070.0	8648.7	8222.9
37.5°	9651.0	10347.4	11048.1	11332.0	11620.3	11819.9	11677.9	11145.7	10609.1	10076.8	9540.2
40°	11349.7	12250.1	13154.9	13664.9	14170.5	14529.8	14277.0	13660.5	13039.6	12423.1	11802.1
42.5°	14525.4	15909.2	17292.9	18024.8	18752.1	19279.9	18996.1	18237.6	17479.2	16720.8	15962.4
45°	19430.7	21200.4	22974.5	24043.4	25116.7	25906.1	25577.9	24624.4	23666.4	22712.8	21759.2
47.5°	24562.3	26673.4	28784.6	29636.2	30492.2	31157.5	31077.6	29889.0	28700.3	27516.1	26327.5
50°	28287.9	30385.7	32483.6	33215.4	33951.6	34497.2	34293.2	32780.7	31263.9	29751.5	28234.6
52.5°	29529.7	31556.6	33588.0	34461.7	35335.4	35987.4	35739.0	34035.9	32332.8	30634.1	28931.0
55°	30106.3	32213.0	34319.8	35384.2	36453.1	37233.7	36874.5	35007.2	33135.6	31268.3	29396.7
57.5°	30824.8	33082.3	35339.9	36506.3	37672.8	38515.5	38036.5	36102.7	34169.0	32239.7	30305.9
60°	31365.9	33614.6	35867.7	36803.5	37743.8	38400.2	37938.9	36058.4	34173.4	32292.9	30412.3
62.5°	30168.4	31898.1	33627.9	34324.2	35020.5	35526.2	35264.5	33481.5	31698.6	29915.6	28132.6
65°	26216.6	27414.1	28616.1	29086.2	29551.9	29911.2	29831.3	28327.8	26824.2	25325.1	23821.6
67.5°	21156.0	22087.4	23023.3	23688.5	24358.3	24877.2	24819.5	23449.0	22078.6	20708.1	19337.6
70°	16481.3	17448.2	18415.1	19253.3	20096.0	20748.0	20663.7	19390.8	18113.5	16840.5	15563.2
72.5°	13168.2	14268.1	15368.1	15847.1	16326.1	16663.1	16414.8	15452.3	14485.4	13523.0	12556.1
75°	7996.7	8573.3	9154.3	9149.9	9149.9	9096.6	8848.3	8298.3	7748.3	7198.4	6648.4
77.5°	2381.7	2634.5	2887.3	3131.3	3379.6	3565.9	3517.1	3228.8	2936.1	2647.8	2355.1
80°	656.4	722.9	793.9	825.0	856.0	895.9	997.9	927.0	856.0	789.5	718.5
82.5°	168.5	168.5	168.5	164.1	159.7	150.8	137.5	128.6	119.8	110.9	102.0
85°	26.6	22.2	22.2	22.2	17.7	17.7	17.7	17.7	13.3	13.3	8.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
2.5°	44.4	44.4	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	35.5
5°	53.2	53.2	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8	44.4
7.5°	66.5	66.5	62.1	62.1	62.1	62.1	57.7	57.7	57.7	57.7	53.2
10°	84.3	79.8	79.8	75.4	75.4	75.4	71.0	71.0	71.0	66.5	66.5
12.5°	106.4	102.0	102.0	97.6	93.1	93.1	88.7	84.3	79.8	79.8	75.4
15°	141.9	137.5	133.1	128.6	124.2	115.3	110.9	102.0	97.6	93.1	88.7
17.5°	270.5	248.4	226.2	204.0	186.3	168.5	150.8	133.1	124.2	115.3	106.4
20°	754.0	652.0	554.4	456.8	394.7	332.6	270.5	208.5	181.8	159.7	133.1
22.5°	1632.2	1428.1	1228.6	1024.5	860.4	700.8	536.7	372.6	310.5	252.8	190.7
25°	3033.7	2643.4	2257.5	1867.2	1556.8	1246.3	935.8	625.4	510.1	394.7	279.4
27.5°	4501.8	3996.1	3490.5	2984.9	2492.6	1995.9	1499.1	1006.8	807.2	612.1	412.5
30°	5632.7	5096.1	4563.8	4027.2	3406.3	2785.3	2160.0	1539.0	1224.1	909.2	589.9
32.5°	6604.1	6023.0	5446.5	4865.4	4146.9	3428.4	2709.9	1991.4	1596.7	1201.9	802.8
35°	7566.5	6905.6	6249.2	5588.4	4816.7	4044.9	3273.2	2501.5	2000.3	1499.1	993.5
37.5°	8737.4	7930.2	7127.4	6324.6	5530.7	4741.3	3947.4	3153.4	2514.8	1880.5	1241.9
40°	10777.6	9748.6	8724.1	7695.1	6768.2	5845.6	4918.7	3991.7	3188.9	2386.2	1578.9
42.5°	14671.7	13381.1	12094.9	10804.2	9522.4	8240.6	6954.4	5672.7	4528.4	3388.5	2244.2
45°	20104.9	18450.5	16800.6	15146.3	13567.4	11992.8	10413.9	8835.0	7096.4	5357.8	3614.7
47.5°	24517.9	22703.9	20894.3	19080.3	17328.4	15580.9	13829.0	12077.1	9850.6	7628.6	5402.1
50°	26509.3	24779.6	23054.3	21324.6	19568.2	17807.4	16046.6	14290.3	11735.6	9185.4	6630.7
52.5°	27179.1	25422.7	23670.8	21914.4	20171.4	18428.4	16685.3	14942.3	12285.6	9633.3	6976.6
55°	27547.2	25693.3	23843.8	21989.8	20113.7	18233.2	16352.7	14476.6	11833.2	9194.2	6550.8
57.5°	28292.3	26274.3	24260.7	22242.7	20104.9	17967.1	15824.9	13687.1	11079.2	8471.3	5863.4
60°	28429.8	26442.8	24460.3	22477.7	20113.7	17749.8	15381.4	13017.4	10427.2	7841.5	5251.3
62.5°	26473.9	24815.1	23160.7	21502.0	19133.6	16765.2	14392.3	12023.9	9544.6	7065.3	4581.6
65°	22389.0	20956.4	19528.3	18095.7	16162.0	14232.6	12298.9	10365.1	8151.9	5943.2	3730.0
67.5°	17936.1	16534.5	15137.4	13735.9	12281.1	10830.8	9376.1	7921.3	6213.8	4506.2	2798.6
70°	14219.3	12871.0	11527.2	10178.8	8892.6	7602.0	6311.3	5025.1	3965.1	2909.5	1849.5
72.5°	11269.9	9979.3	8693.0	7402.4	6235.9	5069.5	3903.0	2736.5	2208.7	1685.4	1157.6
75°	5978.7	5309.0	4643.7	3974.0	3317.5	2656.7	1995.9	1339.4	1131.0	922.5	709.6
77.5°	2062.4	1769.7	1481.4	1188.6	989.1	789.5	589.9	390.3	368.1	350.4	328.2
80°	625.4	532.2	439.1	345.9	306.0	266.1	226.2	186.3	173.0	159.7	141.9
82.5°	97.6	88.7	84.3	75.4	71.0	71.0	66.5	62.1	53.2	48.8	39.9
85°	8.9	4.4	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	39.9	39.9
2.5°	35.5	35.5
5°	44.4	44.4
7.5°	53.2	53.2
10°	62.1	62.1
12.5°	71.0	71.0
15°	84.3	79.8
17.5°	97.6	93.1
20°	106.4	97.6
22.5°	128.6	110.9
25°	164.1	137.5
27.5°	212.9	168.5
30°	275.0	212.9
32.5°	408.0	297.2
35°	492.3	359.3
37.5°	603.2	416.9
40°	776.2	505.6
42.5°	1099.9	687.5
45°	1876.1	1139.9
47.5°	3180.1	1942.6
50°	4076.0	2492.6
52.5°	4324.3	2643.4
55°	3911.9	2426.1
57.5°	3255.5	2062.4
60°	2665.6	1698.7
62.5°	2102.3	1343.9
65°	1516.8	1015.7
67.5°	1091.1	780.6
70°	793.9	612.1
72.5°	629.8	510.1
75°	501.2	425.8
77.5°	310.5	283.9
80°	128.6	119.8
82.5°	31.0	26.6
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066538

CATALOG NUMBER: NVN-SA4B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-5

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-735-U-5WQ


Data in this report applies to families of products including GSS-SB1A-735-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-735-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 3500K CCT 26 LEDS

Spectral Parameters

CCT (K):	3369	CRI (Ra):	70.1		
CIE u':	0.2386	R1:	66.6	R9:	-40.2
CIE v':	0.5156	R2:	77.6	R10:	49.1
Duv:	0.0013	R3:	88.5	R11:	66.3
CIE x:	0.4143	R4:	69.5	R12:	45.7
CIE y:	0.3980	R5:	66.4	R13:	68.0
CIE z:	0.1877	R6:	69.6	R14:	93.4
Peak Wavelength (nm):	590	R7:	77.5	R15:	57.6
Dominant Wavelength (nm):	580	R8:	44.9		
Purity:	43.80166				
Rf:	71.4				
Rg:	96				



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-5


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-5

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-5

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.29

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.36


λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5





TM-30-18

Summary

$R_f = 71.4$
 $R_g = 96$
 $CIE R_a = 70.1$
 $R_g = -40.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 86	CES26 = 57	CES51 = 84	CES76 = 50
CES02 = 62	CES27 = 80	CES52 = 86	CES77 = 74
CES03 = 31	CES28 = 81	CES53 = 72	CES78 = 54
CES04 = 70	CES29 = 50	CES54 = 79	CES79 = 81
CES05 = 48	CES30 = 55	CES55 = 78	CES80 = 79
CES06 = 51	CES31 = 56	CES56 = 67	CES81 = 74
CES07 = 40	CES32 = 54	CES57 = 65	CES82 = 91
CES08 = 39	CES33 = 60	CES58 = 68	CES83 = 86
CES09 = 29	CES34 = 69	CES59 = 85	CES84 = 89
CES10 = 75	CES35 = 83	CES60 = 91	CES85 = 83
CES11 = 58	CES36 = 88	CES61 = 85	CES86 = 66
CES12 = 64	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 43	CES38 = 64	CES63 = 71	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 70	CES89 = 68
CES15 = 71	CES40 = 86	CES65 = 64	CES90 = 72
CES16 = 47	CES41 = 81	CES66 = 65	CES91 = 95
CES17 = 50	CES42 = 79	CES67 = 63	CES92 = 62
CES18 = 56	CES43 = 71	CES68 = 69	CES93 = 78
CES19 = 72	CES44 = 98	CES69 = 80	CES94 = 51
CES20 = 65	CES45 = 80	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 75	CES71 = 58	CES96 = 76
CES22 = 79	CES47 = 71	CES72 = 85	CES97 = 82
CES23 = 92	CES48 = 61	CES73 = 51	CES98 = 72
CES24 = 91	CES49 = 74	CES74 = 94	CES99 = 60
CES25 = 72	CES50 = 83	CES75 = 57	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)