

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066541

Luminaire Tested: **NVN-SA5A-735-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066541
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5A-735-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 615mA 5xLight Square PACKAGE
70CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 3500K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 14243 lumens
Efficiency: N/A
Efficacy: 103.7 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 137.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SASA-735-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	84.7	0.0	84.7
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	14158.2	0.0	14158.2
	% Fixture	99.4	0.0	99.4
Total	Lumens	14242.9	0.0	14242.9
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.2	0.0
10°-20°	20.9	0.1
20°-30°	265.8	1.9
30°-40°	895.9	6.3
40°-50°	2705.7	19.0
50°-60°	4773.7	33.5
60°-70°	4205.7	29.5
70°-80°	1338.8	9.4
80°-90°	32.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	14242.9	100.0
0°-180°	14243.0	100.0



REPORT NUMBER: P1066541


CATALOG NUMBER: NVN-SA5A-735-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	278.2	2.0			
FM	(30°-60°)	8342.6	58.6			
FH	(60°-80°)	5511.2	38.7			G3/7500
FVH	(80°-90°)	26.2	0.2			G1/100
BL	(0°-30°)	12.7	0.1	B0/110		
BM	(30°-60°)	32.8	0.2	B0/220		
BH	(60°-80°)	33.2	0.2	B0/110		G0/110
BVH	(80°-90°)	6.0	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	35.7	35.7	35.7	35.7	35.7	35.7	35.7	35.7	35.7	35.7	31.3
5°	44.7	44.7	44.7	40.2	40.2	40.2	35.7	35.7	35.7	35.7	35.7
7.5°	53.6	49.1	49.1	44.7	44.7	44.7	40.2	40.2	40.2	40.2	35.7
10°	62.5	58.1	58.1	53.6	53.6	49.1	49.1	44.7	44.7	40.2	40.2
12.5°	71.5	67.0	62.5	58.1	58.1	53.6	53.6	49.1	49.1	44.7	44.7
15°	80.4	75.9	71.5	67.0	62.5	62.5	58.1	53.6	49.1	49.1	44.7
17.5°	93.8	84.9	80.4	71.5	67.0	62.5	58.1	53.6	53.6	49.1	49.1
20°	98.3	89.3	84.9	75.9	71.5	67.0	62.5	58.1	53.6	53.6	49.1
22.5°	116.1	98.3	93.8	84.9	80.4	75.9	67.0	62.5	58.1	53.6	49.1
25°	142.9	116.1	102.7	89.3	84.9	75.9	71.5	62.5	58.1	53.6	49.1
27.5°	174.2	129.5	116.1	98.3	89.3	80.4	71.5	62.5	58.1	53.6	49.1
30°	214.4	151.9	129.5	107.2	98.3	89.3	75.9	67.0	62.5	58.1	49.1
32.5°	299.3	187.6	151.9	116.1	102.7	93.8	80.4	67.0	62.5	58.1	49.1
35°	361.8	227.8	183.1	134.0	116.1	102.7	84.9	67.0	62.5	58.1	49.1
37.5°	419.9	232.3	187.6	142.9	125.1	107.2	84.9	67.0	62.5	58.1	49.1
40°	513.7	241.2	187.6	134.0	120.6	102.7	89.3	71.5	67.0	58.1	53.6
42.5°	692.3	276.9	201.0	125.1	111.7	102.7	89.3	75.9	67.0	62.5	53.6
45°	1152.4	410.9	272.5	129.5	116.1	102.7	89.3	75.9	71.5	62.5	58.1
47.5°	1960.8	714.7	424.3	134.0	120.6	102.7	89.3	71.5	67.0	62.5	53.6
50°	2510.2	915.6	536.0	156.3	134.0	116.1	93.8	71.5	67.0	62.5	58.1
52.5°	2666.5	973.7	580.7	183.1	156.3	129.5	98.3	71.5	67.0	67.0	62.5
55°	2443.2	946.9	580.7	214.4	178.7	147.4	111.7	75.9	71.5	71.5	67.0
57.5°	2077.0	875.4	553.9	232.3	196.5	156.3	120.6	80.4	75.9	75.9	71.5
60°	1710.7	737.0	500.3	259.1	218.9	178.7	138.5	98.3	93.8	89.3	80.4
62.5°	1357.8	594.1	437.7	276.9	236.7	192.1	151.9	107.2	102.7	98.3	93.8
65°	1022.8	518.1	406.5	290.3	245.7	201.0	156.3	111.7	107.2	107.2	102.7
67.5°	786.1	473.5	388.6	299.3	254.6	209.9	165.3	120.6	116.1	111.7	107.2
70°	620.9	437.7	366.3	294.8	254.6	214.4	169.7	129.5	120.6	116.1	107.2
72.5°	518.1	397.5	339.5	281.4	250.1	218.9	187.6	156.3	138.5	125.1	107.2
75°	433.3	357.3	308.2	254.6	232.3	214.4	192.1	169.7	147.4	125.1	102.7
77.5°	285.9	259.1	236.7	214.4	201.0	187.6	169.7	156.3	134.0	116.1	93.8
80°	120.6	111.7	116.1	116.1	116.1	116.1	111.7	111.7	98.3	84.9	67.0
82.5°	26.8	22.3	26.8	26.8	26.8	26.8	22.3	22.3	22.3	17.9	17.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	31.3	31.3	31.3	31.3	31.3	31.3	31.3	31.3	31.3	31.3	31.3
5°	35.7	35.7	35.7	31.3	31.3	31.3	31.3	31.3	31.3	31.3	31.3
7.5°	35.7	35.7	35.7	31.3	31.3	31.3	31.3	26.8	26.8	26.8	26.8
10°	35.7	35.7	35.7	31.3	31.3	31.3	31.3	26.8	26.8	26.8	26.8
12.5°	40.2	40.2	35.7	35.7	31.3	31.3	31.3	26.8	26.8	26.8	26.8
15°	40.2	40.2	35.7	35.7	31.3	31.3	31.3	26.8	26.8	26.8	26.8
17.5°	44.7	40.2	40.2	35.7	31.3	31.3	31.3	26.8	26.8	26.8	26.8
20°	44.7	40.2	40.2	35.7	31.3	31.3	31.3	26.8	26.8	26.8	26.8
22.5°	44.7	40.2	40.2	35.7	31.3	31.3	26.8	26.8	22.3	22.3	17.9
25°	44.7	40.2	40.2	35.7	31.3	31.3	26.8	26.8	22.3	17.9	17.9
27.5°	44.7	40.2	40.2	35.7	31.3	26.8	26.8	22.3	17.9	13.4	13.4
30°	44.7	40.2	40.2	35.7	31.3	26.8	22.3	17.9	13.4	13.4	8.9
32.5°	44.7	40.2	35.7	31.3	26.8	22.3	22.3	17.9	13.4	8.9	8.9
35°	44.7	40.2	35.7	31.3	26.8	22.3	22.3	17.9	13.4	8.9	8.9
37.5°	44.7	40.2	35.7	31.3	26.8	22.3	17.9	13.4	8.9	8.9	4.5
40°	44.7	40.2	35.7	31.3	26.8	22.3	17.9	13.4	8.9	8.9	4.5
42.5°	44.7	40.2	35.7	31.3	26.8	22.3	17.9	13.4	8.9	8.9	4.5
45°	49.1	44.7	40.2	31.3	26.8	22.3	22.3	17.9	13.4	8.9	8.9
47.5°	49.1	44.7	40.2	31.3	26.8	22.3	22.3	17.9	13.4	8.9	8.9
50°	53.6	49.1	44.7	35.7	31.3	26.8	22.3	13.4	8.9	8.9	4.5
52.5°	58.1	53.6	49.1	44.7	40.2	31.3	22.3	13.4	4.5	4.5	4.5
55°	62.5	58.1	58.1	53.6	49.1	35.7	26.8	13.4	0.0	0.0	0.0
57.5°	67.0	62.5	62.5	58.1	53.6	40.2	26.8	13.4	0.0	0.0	0.0
60°	75.9	71.5	67.0	58.1	53.6	40.2	26.8	13.4	0.0	0.0	0.0
62.5°	89.3	80.4	67.0	58.1	44.7	35.7	22.3	13.4	0.0	0.0	0.0
65°	98.3	84.9	71.5	53.6	40.2	31.3	22.3	8.9	0.0	0.0	0.0
67.5°	102.7	84.9	71.5	53.6	35.7	26.8	17.9	8.9	0.0	0.0	0.0
70°	98.3	80.4	67.0	49.1	31.3	22.3	17.9	8.9	0.0	0.0	0.0
72.5°	89.3	75.9	58.1	44.7	26.8	22.3	13.4	8.9	0.0	0.0	0.0
75°	80.4	67.0	49.1	35.7	17.9	13.4	8.9	4.5	0.0	0.0	0.0
77.5°	71.5	58.1	40.2	26.8	8.9	8.9	4.5	4.5	0.0	0.0	0.0
80°	53.6	40.2	26.8	13.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	13.4	8.9	8.9	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	26.8	26.8	26.8	26.8	26.8	26.8	26.8	26.8	26.8	26.8	26.8
5°	26.8	26.8	26.8	26.8	22.3	22.3	22.3	22.3	22.3	22.3	22.3
7.5°	26.8	26.8	26.8	26.8	22.3	22.3	22.3	22.3	17.9	17.9	17.9
10°	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	17.9	17.9	17.9
12.5°	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	17.9	17.9	17.9
15°	22.3	22.3	22.3	22.3	22.3	22.3	22.3	17.9	17.9	13.4	13.4
17.5°	22.3	22.3	22.3	22.3	17.9	17.9	17.9	13.4	13.4	8.9	8.9
20°	22.3	22.3	22.3	17.9	17.9	13.4	13.4	8.9	8.9	4.5	4.5
22.5°	17.9	13.4	13.4	8.9	8.9	4.5	4.5	4.5	0.0	0.0	0.0
25°	13.4	8.9	8.9	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.9	4.5	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.9	4.5	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	26.8	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3
5°	22.3	22.3	22.3	22.3	17.9	17.9	17.9	17.9	17.9	17.9	17.9
7.5°	17.9	17.9	17.9	17.9	17.9	17.9	13.4	13.4	13.4	13.4	13.4
10°	17.9	13.4	13.4	13.4	13.4	13.4	13.4	13.4	13.4	8.9	8.9
12.5°	17.9	13.4	13.4	13.4	8.9	8.9	8.9	8.9	8.9	4.5	4.5
15°	13.4	8.9	8.9	8.9	4.5	4.5	4.5	4.5	4.5	0.0	0.0
17.5°	8.9	4.5	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	26.8	26.8
5°	17.9	17.9	17.9	17.9	17.9	17.9	17.9	17.9	17.9	17.9	17.9
7.5°	13.4	13.4	13.4	13.4	13.4	13.4	13.4	13.4	13.4	13.4	13.4
10°	8.9	8.9	8.9	8.9	8.9	8.9	4.5	4.5	4.5	4.5	4.5
12.5°	4.5	4.5	4.5	4.5	4.5	4.5	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	26.8	26.8	26.8	26.8	26.8	31.3	31.3	35.7	35.7	40.2	40.2
5°	17.9	17.9	22.3	22.3	22.3	22.3	26.8	26.8	26.8	31.3	31.3
7.5°	13.4	13.4	13.4	13.4	13.4	17.9	17.9	22.3	22.3	26.8	26.8
10°	4.5	4.5	8.9	8.9	8.9	8.9	13.4	13.4	13.4	17.9	22.3
12.5°	0.0	0.0	4.5	4.5	4.5	4.5	8.9	8.9	8.9	13.4	17.9
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	8.9	13.4
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	8.9
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	44.7	44.7	49.1	49.1	53.6	53.6	58.1	58.1	58.1	58.1	58.1
5°	35.7	35.7	40.2	44.7	44.7	49.1	53.6	53.6	53.6	53.6	53.6
7.5°	31.3	31.3	35.7	40.2	40.2	44.7	49.1	49.1	53.6	53.6	53.6
10°	22.3	26.8	31.3	35.7	35.7	40.2	44.7	44.7	49.1	49.1	49.1
12.5°	17.9	22.3	26.8	31.3	31.3	35.7	40.2	40.2	44.7	44.7	49.1
15°	13.4	17.9	22.3	26.8	26.8	31.3	35.7	35.7	40.2	44.7	49.1
17.5°	8.9	13.4	17.9	22.3	22.3	26.8	31.3	35.7	40.2	40.2	44.7
20°	8.9	8.9	13.4	17.9	17.9	22.3	26.8	31.3	35.7	35.7	40.2
22.5°	4.5	4.5	8.9	13.4	13.4	17.9	22.3	26.8	31.3	31.3	35.7
25°	0.0	0.0	4.5	8.9	8.9	13.4	17.9	17.9	22.3	22.3	26.8
27.5°	0.0	0.0	4.5	4.5	8.9	8.9	13.4	13.4	17.9	17.9	22.3
30°	0.0	0.0	4.5	4.5	8.9	8.9	13.4	13.4	17.9	17.9	17.9
32.5°	0.0	0.0	0.0	4.5	4.5	4.5	8.9	8.9	13.4	13.4	17.9
35°	0.0	0.0	0.0	4.5	4.5	4.5	8.9	8.9	13.4	13.4	13.4
37.5°	0.0	0.0	0.0	4.5	4.5	4.5	8.9	8.9	8.9	8.9	13.4
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	8.9	8.9	8.9
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	8.9	8.9	8.9
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	8.9	8.9	8.9
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	8.9	8.9	8.9
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	8.9	8.9	8.9
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	8.9	8.9	8.9
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	8.9	8.9	8.9
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	8.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.5	4.5	4.5	4.5	4.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	58.1	58.1
5°	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	53.6	53.6
7.5°	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	53.6	53.6
10°	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6
12.5°	49.1	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6
15°	49.1	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6
17.5°	44.7	49.1	49.1	49.1	53.6	53.6	53.6	53.6	53.6	53.6	53.6
20°	40.2	44.7	44.7	44.7	49.1	49.1	49.1	49.1	53.6	53.6	53.6
22.5°	35.7	40.2	40.2	40.2	44.7	44.7	44.7	44.7	49.1	49.1	49.1
25°	31.3	31.3	35.7	35.7	40.2	40.2	40.2	40.2	40.2	40.2	40.2
27.5°	22.3	26.8	26.8	26.8	31.3	31.3	31.3	31.3	35.7	35.7	35.7
30°	22.3	22.3	22.3	22.3	26.8	26.8	26.8	26.8	31.3	31.3	31.3
32.5°	17.9	22.3	22.3	22.3	26.8	26.8	26.8	26.8	31.3	31.3	31.3
35°	17.9	17.9	17.9	17.9	22.3	22.3	22.3	22.3	26.8	26.8	26.8
37.5°	13.4	17.9	17.9	17.9	22.3	22.3	22.3	22.3	26.8	26.8	26.8
40°	13.4	13.4	13.4	13.4	17.9	17.9	17.9	17.9	22.3	22.3	22.3
42.5°	13.4	13.4	13.4	13.4	17.9	17.9	17.9	17.9	22.3	22.3	22.3
45°	13.4	13.4	13.4	13.4	17.9	17.9	17.9	17.9	22.3	22.3	22.3
47.5°	13.4	13.4	13.4	13.4	17.9	17.9	17.9	17.9	22.3	22.3	22.3
50°	13.4	13.4	13.4	13.4	17.9	17.9	17.9	17.9	22.3	22.3	22.3
52.5°	8.9	8.9	8.9	8.9	13.4	13.4	13.4	13.4	17.9	17.9	17.9
55°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	13.4	13.4	13.4
57.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	13.4	13.4	13.4
60°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
62.5°	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
65°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	4.5	4.5
67.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
70°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
72.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
75°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
77.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
80°	13.4	13.4	13.4	13.4	13.4	8.9	8.9	8.9	8.9	8.9	8.9
82.5°	8.9	13.4	13.4	13.4	13.4	8.9	8.9	8.9	8.9	8.9	8.9
85°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
87.5°	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	58.1	58.1	53.6	53.6	53.6	53.6	53.6	53.6	53.6	58.1	58.1
5°	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	58.1	58.1
7.5°	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	58.1	58.1
10°	53.6	53.6	53.6	53.6	49.1	49.1	53.6	53.6	53.6	58.1	58.1
12.5°	53.6	53.6	53.6	53.6	49.1	49.1	53.6	53.6	58.1	58.1	62.5
15°	53.6	53.6	49.1	49.1	49.1	49.1	53.6	53.6	58.1	58.1	62.5
17.5°	53.6	53.6	49.1	49.1	49.1	49.1	53.6	53.6	58.1	58.1	62.5
20°	53.6	53.6	49.1	49.1	49.1	49.1	49.1	49.1	53.6	58.1	58.1
22.5°	49.1	49.1	49.1	49.1	44.7	44.7	49.1	49.1	53.6	58.1	58.1
25°	40.2	44.7	44.7	44.7	44.7	44.7	49.1	49.1	53.6	58.1	58.1
27.5°	35.7	40.2	40.2	40.2	40.2	44.7	44.7	49.1	53.6	58.1	58.1
30°	31.3	35.7	35.7	35.7	40.2	44.7	44.7	49.1	53.6	58.1	58.1
32.5°	31.3	35.7	35.7	35.7	40.2	40.2	44.7	44.7	49.1	53.6	58.1
35°	31.3	31.3	35.7	35.7	35.7	40.2	40.2	44.7	49.1	53.6	58.1
37.5°	31.3	31.3	35.7	35.7	35.7	40.2	40.2	44.7	49.1	53.6	58.1
40°	26.8	31.3	31.3	35.7	35.7	40.2	40.2	44.7	49.1	58.1	62.5
42.5°	26.8	26.8	31.3	31.3	35.7	40.2	40.2	44.7	49.1	58.1	62.5
45°	26.8	31.3	31.3	35.7	40.2	44.7	44.7	49.1	53.6	58.1	62.5
47.5°	26.8	31.3	31.3	35.7	44.7	44.7	49.1	49.1	53.6	58.1	62.5
50°	26.8	31.3	31.3	35.7	49.1	49.1	49.1	49.1	53.6	58.1	62.5
52.5°	22.3	26.8	26.8	31.3	40.2	44.7	49.1	53.6	58.1	62.5	67.0
55°	17.9	22.3	22.3	26.8	35.7	40.2	49.1	58.1	62.5	67.0	71.5
57.5°	17.9	17.9	22.3	22.3	31.3	40.2	53.6	62.5	67.0	71.5	75.9
60°	13.4	13.4	17.9	17.9	26.8	35.7	49.1	62.5	67.0	75.9	80.4
62.5°	8.9	13.4	13.4	17.9	22.3	35.7	49.1	62.5	71.5	80.4	84.9
65°	8.9	8.9	13.4	13.4	22.3	31.3	44.7	53.6	67.0	80.4	93.8
67.5°	13.4	13.4	17.9	17.9	22.3	31.3	44.7	53.6	67.0	84.9	98.3
70°	13.4	13.4	17.9	17.9	26.8	35.7	44.7	53.6	67.0	84.9	98.3
72.5°	13.4	13.4	17.9	17.9	26.8	31.3	40.2	49.1	62.5	75.9	89.3
75°	8.9	13.4	13.4	13.4	22.3	26.8	35.7	44.7	58.1	71.5	84.9
77.5°	8.9	8.9	8.9	8.9	17.9	22.3	31.3	35.7	49.1	62.5	75.9
80°	8.9	8.9	8.9	8.9	13.4	17.9	26.8	31.3	44.7	58.1	71.5
82.5°	8.9	8.9	4.5	4.5	8.9	13.4	17.9	22.3	35.7	44.7	58.1
85°	8.9	8.9	4.5	4.5	4.5	8.9	8.9	13.4	17.9	22.3	26.8
87.5°	8.9	8.9	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	58.1	58.1	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5
5°	58.1	62.5	62.5	67.0	67.0	67.0	71.5	71.5	71.5	71.5	71.5
7.5°	58.1	62.5	62.5	67.0	67.0	67.0	71.5	71.5	71.5	75.9	75.9
10°	58.1	62.5	62.5	67.0	67.0	71.5	75.9	75.9	80.4	80.4	80.4
12.5°	62.5	67.0	67.0	71.5	71.5	75.9	80.4	80.4	84.9	89.3	89.3
15°	62.5	67.0	71.5	71.5	75.9	80.4	84.9	84.9	89.3	93.8	98.3
17.5°	62.5	67.0	71.5	71.5	75.9	80.4	89.3	93.8	98.3	107.2	111.7
20°	62.5	67.0	71.5	71.5	75.9	84.9	89.3	98.3	102.7	111.7	120.6
22.5°	62.5	67.0	71.5	75.9	80.4	89.3	98.3	102.7	111.7	125.1	134.0
25°	62.5	67.0	71.5	75.9	80.4	89.3	98.3	107.2	116.1	134.0	151.9
27.5°	62.5	67.0	75.9	80.4	84.9	93.8	107.2	116.1	125.1	156.3	187.6
30°	62.5	67.0	75.9	80.4	84.9	98.3	111.7	120.6	134.0	187.6	236.7
32.5°	62.5	71.5	75.9	84.9	89.3	102.7	120.6	134.0	147.4	223.3	294.8
35°	62.5	71.5	75.9	84.9	89.3	107.2	125.1	142.9	160.8	272.5	384.1
37.5°	62.5	71.5	75.9	84.9	89.3	116.1	142.9	169.7	196.5	312.7	428.8
40°	67.0	75.9	80.4	89.3	93.8	120.6	147.4	174.2	201.0	317.1	433.3
42.5°	67.0	75.9	80.4	89.3	93.8	116.1	142.9	165.3	187.6	317.1	446.7
45°	67.0	75.9	84.9	89.3	98.3	120.6	142.9	160.8	183.1	348.4	509.2
47.5°	67.0	75.9	84.9	89.3	98.3	120.6	142.9	165.3	187.6	460.1	728.1
50°	67.0	75.9	84.9	89.3	98.3	125.1	151.9	178.7	205.5	687.9	1170.2
52.5°	71.5	75.9	84.9	89.3	93.8	125.1	156.3	187.6	218.9	893.3	1563.3
55°	75.9	80.4	84.9	89.3	93.8	134.0	174.2	214.4	254.6	960.3	1661.6
57.5°	80.4	84.9	89.3	89.3	93.8	142.9	196.5	245.7	294.8	955.8	1612.4
60°	84.9	89.3	93.8	98.3	102.7	151.9	205.5	254.6	303.7	866.5	1429.3
62.5°	93.8	102.7	111.7	116.1	125.1	174.2	218.9	268.0	312.7	710.2	1103.2
65°	107.2	116.1	120.6	129.5	134.0	178.7	227.8	272.5	317.1	589.6	857.6
67.5°	111.7	120.6	125.1	134.0	138.5	183.1	227.8	272.5	317.1	500.3	678.9
70°	111.7	120.6	129.5	134.0	142.9	187.6	227.8	272.5	312.7	433.3	553.9
72.5°	102.7	116.1	125.1	138.5	147.4	187.6	223.3	263.5	299.3	384.1	469.0
75°	98.3	116.1	129.5	147.4	160.8	187.6	218.9	245.7	272.5	335.0	397.5
77.5°	89.3	111.7	134.0	156.3	178.7	196.5	209.9	227.8	241.2	281.4	321.6
80°	84.9	107.2	129.5	151.9	174.2	183.1	187.6	196.5	201.0	205.5	209.9
82.5°	67.0	84.9	102.7	116.1	134.0	125.1	120.6	111.7	102.7	98.3	93.8
85°	31.3	35.7	35.7	40.2	40.2	40.2	35.7	35.7	31.3	26.8	22.3
87.5°	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	62.5	62.5	62.5	62.5	58.1	58.1	58.1	58.1	53.6	53.6	53.6
5°	71.5	71.5	71.5	71.5	67.0	67.0	67.0	67.0	62.5	62.5	62.5
7.5°	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9
10°	84.9	84.9	84.9	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3
12.5°	93.8	93.8	98.3	98.3	102.7	102.7	107.2	107.2	111.7	111.7	111.7
15°	102.7	107.2	111.7	116.1	116.1	120.6	125.1	129.5	134.0	138.5	142.9
17.5°	120.6	125.1	134.0	142.9	151.9	160.8	174.2	192.1	205.5	218.9	236.7
20°	134.0	147.4	174.2	205.5	232.3	259.1	326.1	393.1	460.1	527.1	594.1
22.5°	160.8	187.6	276.9	370.7	460.1	549.4	759.3	969.2	1174.7	1384.6	1572.2
25°	214.4	272.5	477.9	683.4	884.4	1089.8	1465.0	1844.7	2219.9	2595.1	2943.5
27.5°	294.8	402.0	737.0	1076.4	1411.4	1746.4	2291.4	2840.7	3385.7	3935.1	4421.9
30°	410.9	585.1	1085.4	1590.1	2090.4	2590.6	3278.5	3970.8	4658.6	5346.5	5793.2
32.5°	558.3	817.4	1451.6	2085.9	2720.1	3354.4	4113.7	4873.0	5627.9	6387.2	6860.7
35°	714.7	1045.2	1809.0	2577.2	3341.0	4109.3	4908.8	5708.3	6507.8	7307.3	7888.0
37.5°	804.0	1179.2	2085.9	2992.6	3894.9	4801.6	5677.0	6556.9	7432.4	8307.8	9013.6
40°	888.8	1340.0	2385.2	3430.3	4475.5	5520.7	6543.5	7566.4	8589.2	9612.1	10518.8
42.5°	1013.9	1581.2	2800.5	4019.9	5234.8	6454.2	7798.6	9147.6	10492.0	11836.4	13230.0
45°	1273.0	2036.8	3617.9	5199.1	6775.8	8357.0	10264.2	12175.9	14083.1	15994.8	17781.4
47.5°	1898.3	3064.1	5221.4	7378.8	9536.1	11693.5	13891.1	16088.6	18286.2	20483.7	22609.8
50°	2939.0	4703.3	7401.1	10098.9	12792.3	15490.1	17683.2	19876.3	22064.9	24258.0	26370.7
52.5°	3917.2	6271.1	9169.9	12073.2	14972.0	17875.2	19818.2	21761.2	23704.1	25647.1	27692.8
55°	4252.2	6838.3	9772.9	12711.9	15646.4	18585.4	20456.9	22332.9	24204.4	26075.9	28197.5
57.5°	3957.4	6302.3	9259.2	12216.1	15168.5	18125.4	20215.7	22310.6	24400.9	26495.7	28769.2
60°	3314.2	5194.6	8298.9	11407.6	14511.9	17616.2	19974.5	22332.9	24691.2	27049.6	29318.6
62.5°	2626.3	4145.0	7432.4	10719.8	14007.2	17294.6	19693.1	22096.2	24494.7	26893.3	28635.2
65°	2014.4	3171.3	6405.1	9643.3	12877.1	16115.4	18080.7	20050.5	22015.8	23985.5	25191.5
67.5°	1496.3	2313.7	5141.0	7972.8	10800.2	13627.5	15074.7	16526.3	17973.5	19425.1	20363.1
70°	1103.2	1648.2	3573.3	5498.4	7419.0	9344.1	10670.7	11997.2	13319.3	14645.9	15619.6
72.5°	763.8	1054.1	2206.5	3363.3	4515.7	5668.1	7012.5	8357.0	9696.9	11041.4	12149.1
75°	522.6	647.7	1188.1	1728.6	2269.0	2809.5	3827.9	4846.2	5864.6	6883.0	7468.1
77.5°	388.6	455.6	616.4	781.7	942.4	1103.2	1299.8	1496.3	1692.8	1889.4	2144.0
80°	214.4	214.4	236.7	254.6	276.9	294.8	348.4	406.5	460.1	518.1	589.6
82.5°	98.3	102.7	111.7	120.6	125.1	134.0	142.9	151.9	160.8	169.7	169.7
85°	26.8	31.3	31.3	26.8	26.8	22.3	22.3	26.8	26.8	26.8	26.8
87.5°	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	53.6	49.1	49.1	49.1	44.7	44.7	44.7	44.7	44.7	44.7	44.7
5°	62.5	62.5	62.5	62.5	58.1	58.1	58.1	58.1	58.1	53.6	53.6
7.5°	75.9	71.5	71.5	71.5	71.5	71.5	71.5	71.5	71.5	67.0	67.0
10°	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	84.9	84.9
12.5°	111.7	111.7	111.7	111.7	116.1	116.1	111.7	111.7	111.7	107.2	107.2
15°	147.4	151.9	156.3	156.3	160.8	160.8	160.8	156.3	156.3	151.9	147.4
17.5°	250.1	263.5	281.4	299.3	317.1	330.5	330.5	321.6	312.7	303.7	294.8
20°	665.5	732.5	804.0	875.4	951.4	1005.0	969.2	942.4	915.6	884.4	857.6
22.5°	1764.3	1951.9	2144.0	2278.0	2412.0	2505.8	2429.8	2282.4	2135.0	1992.1	1844.7
25°	3291.9	3635.8	3984.2	4127.1	4274.5	4381.7	4332.6	4109.3	3885.9	3667.1	3443.7
27.5°	4908.8	5391.2	5878.0	6003.1	6128.1	6221.9	6204.1	5913.7	5623.4	5333.1	5042.8
30°	6239.8	6686.5	7133.1	7258.2	7383.3	7468.1	7374.3	7084.0	6793.7	6503.3	6213.0
32.5°	7338.6	7812.0	8290.0	8455.2	8620.5	8732.2	8620.5	8272.1	7923.7	7579.8	7231.4
35°	8468.6	9044.8	9625.5	9835.4	10045.3	10179.3	9991.7	9562.9	9134.2	8709.8	8281.0
37.5°	9719.3	10420.5	11126.2	11412.1	11702.4	11903.4	11760.5	11224.5	10684.1	10148.1	9607.6
40°	11430.0	12336.7	13247.9	13761.5	14270.7	14632.5	14377.9	13757.1	13131.7	12510.9	11885.6
42.5°	14628.0	16021.6	17415.2	18152.2	18884.7	19416.2	19130.4	18366.6	17602.8	16839.0	16075.2
45°	19568.1	21350.2	23136.9	24213.3	25294.2	26089.3	25758.8	24798.4	23833.7	22873.3	21913.0
47.5°	24735.9	26862.0	28988.1	29845.7	30707.7	31377.7	31297.3	30100.3	28903.2	27710.6	26513.6
50°	28487.8	30600.5	32713.2	33450.2	34191.7	34741.0	34535.6	33012.5	31484.9	29961.8	28434.2
52.5°	29738.5	31779.7	33825.4	34705.3	35585.2	36241.8	35991.7	34276.5	32561.4	30850.7	29135.5
55°	30319.1	32440.8	34562.4	35634.4	36710.8	37496.9	37135.1	35254.7	33369.8	31489.4	29604.5
57.5°	31042.7	33316.2	35589.7	36764.4	37939.1	38787.8	38305.4	36357.9	34410.5	32467.6	30520.1
60°	31587.6	33852.2	36121.2	37063.7	38010.6	38671.6	38207.1	36313.3	34415.0	32521.2	30627.3
62.5°	30381.7	32123.6	33865.6	34566.8	35268.1	35777.3	35513.8	33718.2	31922.6	30127.1	28331.5
65°	26401.9	27607.9	28818.4	29291.8	29760.8	30122.6	30042.2	28528.0	27013.9	25504.2	23990.0
67.5°	21305.6	22243.6	23186.0	23856.0	24530.4	25053.0	24995.0	23614.8	22234.6	20854.5	19474.3
70°	16597.8	17571.5	18545.2	19389.4	20238.1	20894.7	20809.8	19527.9	18241.5	16959.6	15673.2
72.5°	13261.3	14369.0	15476.7	15959.1	16441.5	16780.9	16530.8	15561.6	14587.8	13618.6	12644.9
75°	8053.2	8633.9	9219.0	9214.6	9214.6	9161.0	8910.8	8357.0	7803.1	7249.3	6695.4
77.5°	2398.6	2653.1	2907.7	3153.4	3403.5	3591.1	3542.0	3251.7	2956.9	2666.5	2371.8
80°	661.1	728.1	799.5	830.8	862.0	902.2	1005.0	933.5	862.0	795.1	723.6
82.5°	169.7	169.7	169.7	165.3	160.8	151.9	138.5	129.5	120.6	111.7	102.7
85°	26.8	22.3	22.3	22.3	17.9	17.9	17.9	17.9	13.4	13.4	8.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
2.5°	44.7	44.7	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	35.7
5°	53.6	53.6	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	44.7
7.5°	67.0	67.0	62.5	62.5	62.5	62.5	58.1	58.1	58.1	58.1	53.6
10°	84.9	80.4	80.4	75.9	75.9	75.9	71.5	71.5	71.5	67.0	67.0
12.5°	107.2	102.7	102.7	98.3	93.8	93.8	89.3	84.9	80.4	80.4	75.9
15°	142.9	138.5	134.0	129.5	125.1	116.1	111.7	102.7	98.3	93.8	89.3
17.5°	272.5	250.1	227.8	205.5	187.6	169.7	151.9	134.0	125.1	116.1	107.2
20°	759.3	656.6	558.3	460.1	397.5	335.0	272.5	209.9	183.1	160.8	134.0
22.5°	1643.7	1438.2	1237.2	1031.8	866.5	705.7	540.5	375.2	312.7	254.6	192.1
25°	3055.1	2662.1	2273.5	1880.4	1567.8	1255.1	942.4	629.8	513.7	397.5	281.4
27.5°	4533.6	4024.4	3515.2	3006.0	2510.2	2010.0	1509.7	1013.9	812.9	616.4	415.4
30°	5672.6	5132.1	4596.1	4055.7	3430.3	2805.0	2175.2	1549.9	1232.8	915.6	594.1
32.5°	6650.7	6065.6	5485.0	4899.8	4176.3	3452.7	2729.1	2005.5	1608.0	1210.4	808.5
35°	7620.0	6954.5	6293.4	5627.9	4850.7	4073.5	3296.3	2519.1	2014.4	1509.7	1000.5
37.5°	8799.2	7986.2	7177.8	6369.3	5569.8	4774.8	3975.3	3175.7	2532.5	1893.8	1250.6
40°	10853.8	9817.5	8785.8	7749.5	6816.0	5886.9	4953.4	4019.9	3211.5	2403.0	1590.1
42.5°	14775.4	13475.7	12180.4	10880.6	9589.7	8298.9	7003.6	5712.8	4560.4	3412.5	2260.1
45°	20247.0	18581.0	16919.4	15253.4	13663.3	12077.6	10487.5	8897.4	7146.5	5395.6	3640.3
47.5°	24691.2	22864.4	21042.0	19215.2	17450.9	15691.1	13926.8	12162.5	9920.3	7682.5	5440.3
50°	26696.7	24954.8	23217.3	21475.3	19706.5	17933.3	16160.1	14391.3	11818.6	9250.3	6677.5
52.5°	27371.2	25602.4	23838.1	22069.4	20314.0	18558.6	16803.3	15047.9	12372.4	9701.4	7025.9
55°	27741.9	25874.9	24012.3	22145.3	20255.9	18362.1	16468.3	14578.9	11916.8	9259.2	6597.1
57.5°	28492.3	26460.0	24432.2	22399.9	20247.0	18094.1	15936.8	13783.9	11157.5	8531.2	5904.8
60°	28630.8	26629.7	24633.2	22636.6	20255.9	17875.2	15490.1	13109.4	10500.9	7896.9	5288.4
62.5°	26661.0	24990.5	23324.5	21654.0	19268.8	16883.7	14494.0	12108.9	9612.1	7115.3	4614.0
65°	22547.3	21104.6	19666.3	18223.6	16276.2	14333.2	12385.8	10438.4	8209.6	5985.2	3756.4
67.5°	18062.8	16651.4	15244.4	13833.0	12368.0	10907.4	9442.3	7977.3	6257.7	4538.0	2818.4
70°	14319.8	12962.0	11608.6	10250.8	8955.5	7655.7	6355.9	5060.6	3993.1	2930.1	1862.6
72.5°	11349.6	10049.8	8754.5	7454.7	6280.0	5105.3	3930.6	2755.9	2224.4	1697.3	1165.8
75°	6020.9	5346.5	4676.5	4002.1	3341.0	2675.5	2010.0	1348.9	1139.0	929.0	714.7
77.5°	2077.0	1782.2	1491.8	1197.0	996.0	795.1	594.1	393.1	370.7	352.9	330.5
80°	629.8	536.0	442.2	348.4	308.2	268.0	227.8	187.6	174.2	160.8	142.9
82.5°	98.3	89.3	84.9	75.9	71.5	71.5	67.0	62.5	53.6	49.1	40.2
85°	8.9	4.5	4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066541
 CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	40.2	40.2
2.5°	35.7	35.7
5°	44.7	44.7
7.5°	53.6	53.6
10°	62.5	62.5
12.5°	71.5	71.5
15°	84.9	80.4
17.5°	98.3	93.8
20°	107.2	98.3
22.5°	129.5	111.7
25°	165.3	138.5
27.5°	214.4	169.7
30°	276.9	214.4
32.5°	410.9	299.3
35°	495.8	361.8
37.5°	607.5	419.9
40°	781.7	509.2
42.5°	1107.7	692.3
45°	1889.4	1147.9
47.5°	3202.5	1956.4
50°	4104.8	2510.2
52.5°	4354.9	2662.1
55°	3939.5	2443.2
57.5°	3278.5	2077.0
60°	2684.4	1710.7
62.5°	2117.2	1353.4
65°	1527.6	1022.8
67.5°	1098.8	786.1
70°	799.5	616.4
72.5°	634.3	513.7
75°	504.7	428.8
77.5°	312.7	285.9
80°	129.5	120.6
82.5°	31.3	26.8
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066541

CATALOG NUMBER: NVN-SA5A-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-5

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-735-U-5WQ

Data in this report applies to families of products including GSS-SB1A-735-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-735-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3369
 CIE u' : 0.2386
 CIE v' : 0.5156
 Duv: 0.0013
 CIE x: 0.4143
 CIE y: 0.3980
 CIE z: 0.1877
 Peak Wavelength (nm): 590
 Dominant Wavelength (nm): 580
 Purity: 43.80166
 R_f: 71.4
 R_g: 96

CRI (Ra): 70.1
 R1: 66.6
 R2: 77.6
 R3: 88.5
 R4: 69.5
 R5: 66.4
 R6: 69.6
 R7: 77.5
 R8: 44.9
 R9: -40.2
 R10: 49.1
 R11: 66.3
 R12: 45.7
 R13: 68.0
 R14: 93.4
 R15: 57.6



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-5


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-5

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-5

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5


Scotopic Flux vs. Wavelength


Scotopic Lumens: NR
S/P: 1.29

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.36


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5





TM-30-18

Summary

$R_f = 71.4$
 $R_g = 96$
 $CIE R_a = 70.1$
 $R_g = -40.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 57	CES51 = 84	CES76 = 50
CES02 = 62	CES27 = 80	CES52 = 86	CES77 = 74
CES03 = 31	CES28 = 81	CES53 = 72	CES78 = 54
CES04 = 70	CES29 = 50	CES54 = 79	CES79 = 81
CES05 = 48	CES30 = 55	CES55 = 78	CES80 = 79
CES06 = 51	CES31 = 56	CES56 = 67	CES81 = 74
CES07 = 40	CES32 = 54	CES57 = 65	CES82 = 91
CES08 = 39	CES33 = 60	CES58 = 68	CES83 = 86
CES09 = 29	CES34 = 69	CES59 = 85	CES84 = 89
CES10 = 75	CES35 = 83	CES60 = 91	CES85 = 83
CES11 = 58	CES36 = 88	CES61 = 85	CES86 = 66
CES12 = 64	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 43	CES38 = 64	CES63 = 71	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 70	CES89 = 68
CES15 = 71	CES40 = 86	CES65 = 64	CES90 = 72
CES16 = 47	CES41 = 81	CES66 = 65	CES91 = 95
CES17 = 50	CES42 = 79	CES67 = 63	CES92 = 62
CES18 = 56	CES43 = 71	CES68 = 69	CES93 = 78
CES19 = 72	CES44 = 98	CES69 = 80	CES94 = 51
CES20 = 65	CES45 = 80	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 75	CES71 = 58	CES96 = 76
CES22 = 79	CES47 = 71	CES72 = 85	CES97 = 82
CES23 = 92	CES48 = 61	CES73 = 51	CES98 = 72
CES24 = 91	CES49 = 74	CES74 = 94	CES99 = 60
CES25 = 72	CES50 = 83	CES75 = 57	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)