

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066542

Luminaire Tested: **NVN-SA5B-735-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066542
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5B-735-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 5xLight Square PACKAGE
70CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 3500K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 17832.2 lumens
Efficiency: N/A
Efficacy: 99.7 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 178.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3.5 fc
 Type III - Short - N/A

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	106.1	0.0	106.1
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	17726.0	0.0	17726.0
	% Fixture	99.4	0.0	99.4
Total	Lumens	17832.1	0.0	17832.1
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	5.3	0.0
10°-20°	26.2	0.1
20°-30°	332.8	1.9
30°-40°	1121.7	6.3
40°-50°	3387.6	19.0
50°-60°	5976.7	33.5
60°-70°	5265.5	29.5
70°-80°	1676.1	9.4
80°-90°	40.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	17832.1	100.0
0°-180°	17832.2	100.0



REPORT NUMBER: P1066542


CATALOG NUMBER: NVN-SA5B-735-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	348.4	2.0			
FM	(30°-60°)	10444.9	58.6			
FH	(60°-80°)	6900.1	38.7			G3/7500
FVH	(80°-90°)	32.8	0.2			G1/100
BL	(0°-30°)	15.9	0.1	B0/110		
BM	(30°-60°)	41.1	0.2	B0/220		
BH	(60°-80°)	41.6	0.2	B0/110		G0/110
BVH	(80°-90°)	7.5	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	44.7	44.7	44.7	44.7	44.7	44.7	44.7	44.7	44.7	44.7	39.1
5°	55.9	55.9	55.9	50.3	50.3	50.3	44.7	44.7	44.7	44.7	44.7
7.5°	67.1	61.5	61.5	55.9	55.9	55.9	50.3	50.3	50.3	50.3	44.7
10°	78.3	72.7	72.7	67.1	67.1	61.5	61.5	55.9	55.9	50.3	50.3
12.5°	89.5	83.9	78.3	72.7	72.7	67.1	67.1	61.5	61.5	55.9	55.9
15°	100.7	95.1	89.5	83.9	78.3	78.3	72.7	67.1	61.5	61.5	55.9
17.5°	117.4	106.3	100.7	89.5	83.9	78.3	72.7	67.1	67.1	61.5	61.5
20°	123.0	111.8	106.3	95.1	89.5	83.9	78.3	72.7	67.1	67.1	61.5
22.5°	145.4	123.0	117.4	106.3	100.7	95.1	83.9	78.3	72.7	67.1	61.5
25°	178.9	145.4	128.6	111.8	106.3	95.1	89.5	78.3	72.7	67.1	61.5
27.5°	218.1	162.2	145.4	123.0	111.8	100.7	89.5	78.3	72.7	67.1	61.5
30°	268.4	190.1	162.2	134.2	123.0	111.8	95.1	83.9	78.3	72.7	61.5
32.5°	374.7	234.9	190.1	145.4	128.6	117.4	100.7	83.9	78.3	72.7	61.5
35°	453.0	285.2	229.3	167.8	145.4	128.6	106.3	83.9	78.3	72.7	61.5
37.5°	525.7	290.8	234.9	178.9	156.6	134.2	106.3	83.9	78.3	72.7	61.5
40°	643.1	302.0	234.9	167.8	151.0	128.6	111.8	89.5	83.9	72.7	67.1
42.5°	866.8	346.7	251.6	156.6	139.8	128.6	111.8	95.1	83.9	78.3	67.1
45°	1442.8	514.5	341.1	162.2	145.4	128.6	111.8	95.1	89.5	78.3	72.7
47.5°	2455.0	894.7	531.3	167.8	151.0	128.6	111.8	89.5	83.9	78.3	67.1
50°	3142.8	1146.4	671.1	195.7	167.8	145.4	117.4	89.5	83.9	78.3	72.7
52.5°	3338.5	1219.1	727.0	229.3	195.7	162.2	123.0	89.5	83.9	83.9	78.3
55°	3058.9	1185.5	727.0	268.4	223.7	184.5	139.8	95.1	89.5	89.5	83.9
57.5°	2600.3	1096.1	693.4	290.8	246.1	195.7	151.0	100.7	95.1	95.1	89.5
60°	2141.8	922.7	626.3	324.3	274.0	223.7	173.4	123.0	117.4	111.8	100.7
62.5°	1700.0	743.8	548.0	346.7	296.4	240.5	190.1	134.2	128.6	123.0	117.4
65°	1280.6	648.7	508.9	363.5	307.6	251.6	195.7	139.8	134.2	134.2	128.6
67.5°	984.2	592.8	486.5	374.7	318.8	262.8	206.9	151.0	145.4	139.8	134.2
70°	777.3	548.0	458.6	369.1	318.8	268.4	212.5	162.2	151.0	145.4	134.2
72.5°	648.7	497.7	425.0	352.3	313.2	274.0	234.9	195.7	173.4	156.6	134.2
75°	542.4	447.4	385.9	318.8	290.8	268.4	240.5	212.5	184.5	156.6	128.6
77.5°	357.9	324.3	296.4	268.4	251.6	234.9	212.5	195.7	167.8	145.4	117.4
80°	151.0	139.8	145.4	145.4	145.4	145.4	139.8	139.8	123.0	106.3	83.9
82.5°	33.6	28.0	33.6	33.6	33.6	33.6	28.0	28.0	28.0	22.4	22.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
5°	44.7	44.7	44.7	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
7.5°	44.7	44.7	44.7	39.1	39.1	39.1	39.1	33.6	33.6	33.6	33.6
10°	44.7	44.7	44.7	39.1	39.1	39.1	39.1	33.6	33.6	33.6	33.6
12.5°	50.3	50.3	44.7	44.7	39.1	39.1	39.1	33.6	33.6	33.6	33.6
15°	50.3	50.3	44.7	44.7	39.1	39.1	39.1	33.6	33.6	33.6	33.6
17.5°	55.9	50.3	50.3	44.7	39.1	39.1	39.1	33.6	33.6	33.6	33.6
20°	55.9	50.3	50.3	44.7	39.1	39.1	39.1	33.6	33.6	33.6	33.6
22.5°	55.9	50.3	50.3	44.7	39.1	39.1	33.6	33.6	28.0	28.0	22.4
25°	55.9	50.3	50.3	44.7	39.1	39.1	33.6	33.6	28.0	22.4	22.4
27.5°	55.9	50.3	50.3	44.7	39.1	33.6	33.6	28.0	22.4	16.8	16.8
30°	55.9	50.3	50.3	44.7	39.1	33.6	28.0	22.4	16.8	16.8	11.2
32.5°	55.9	50.3	44.7	39.1	33.6	28.0	28.0	22.4	16.8	11.2	11.2
35°	55.9	50.3	44.7	39.1	33.6	28.0	28.0	22.4	16.8	11.2	11.2
37.5°	55.9	50.3	44.7	39.1	33.6	28.0	22.4	16.8	11.2	11.2	5.6
40°	55.9	50.3	44.7	39.1	33.6	28.0	22.4	16.8	11.2	11.2	5.6
42.5°	55.9	50.3	44.7	39.1	33.6	28.0	22.4	16.8	11.2	11.2	5.6
45°	61.5	55.9	50.3	39.1	33.6	28.0	28.0	22.4	16.8	11.2	11.2
47.5°	61.5	55.9	50.3	39.1	33.6	28.0	28.0	22.4	16.8	11.2	11.2
50°	67.1	61.5	55.9	44.7	39.1	33.6	28.0	16.8	11.2	11.2	5.6
52.5°	72.7	67.1	61.5	55.9	50.3	39.1	28.0	16.8	5.6	5.6	5.6
55°	78.3	72.7	72.7	67.1	61.5	44.7	33.6	16.8	0.0	0.0	0.0
57.5°	83.9	78.3	78.3	72.7	67.1	50.3	33.6	16.8	0.0	0.0	0.0
60°	95.1	89.5	83.9	72.7	67.1	50.3	33.6	16.8	0.0	0.0	0.0
62.5°	111.8	100.7	83.9	72.7	55.9	44.7	28.0	16.8	0.0	0.0	0.0
65°	123.0	106.3	89.5	67.1	50.3	39.1	28.0	11.2	0.0	0.0	0.0
67.5°	128.6	106.3	89.5	67.1	44.7	33.6	22.4	11.2	0.0	0.0	0.0
70°	123.0	100.7	83.9	61.5	39.1	28.0	22.4	11.2	0.0	0.0	0.0
72.5°	111.8	95.1	72.7	55.9	33.6	28.0	16.8	11.2	0.0	0.0	0.0
75°	100.7	83.9	61.5	44.7	22.4	16.8	11.2	5.6	0.0	0.0	0.0
77.5°	89.5	72.7	50.3	33.6	11.2	11.2	5.6	5.6	0.0	0.0	0.0
80°	67.1	50.3	33.6	16.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	16.8	11.2	11.2	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6
5°	33.6	33.6	33.6	33.6	28.0	28.0	28.0	28.0	28.0	28.0	28.0
7.5°	33.6	33.6	33.6	33.6	28.0	28.0	28.0	28.0	22.4	22.4	22.4
10°	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	22.4	22.4	22.4
12.5°	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	22.4	22.4	22.4
15°	28.0	28.0	28.0	28.0	28.0	28.0	28.0	22.4	22.4	16.8	16.8
17.5°	28.0	28.0	28.0	28.0	22.4	22.4	22.4	16.8	16.8	11.2	11.2
20°	28.0	28.0	28.0	22.4	22.4	16.8	16.8	11.2	11.2	5.6	5.6
22.5°	22.4	16.8	16.8	11.2	11.2	5.6	5.6	5.6	0.0	0.0	0.0
25°	16.8	11.2	11.2	5.6	5.6	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	11.2	5.6	5.6	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	11.2	5.6	5.6	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	33.6	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
5°	28.0	28.0	28.0	28.0	22.4	22.4	22.4	22.4	22.4	22.4	22.4
7.5°	22.4	22.4	22.4	22.4	22.4	22.4	16.8	16.8	16.8	16.8	16.8
10°	22.4	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	11.2	11.2
12.5°	22.4	16.8	16.8	16.8	11.2	11.2	11.2	11.2	11.2	5.6	5.6
15°	16.8	11.2	11.2	11.2	5.6	5.6	5.6	5.6	5.6	0.0	0.0
17.5°	11.2	5.6	5.6	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	33.6	33.6
5°	22.4	22.4	22.4	22.4	22.4	22.4	22.4	22.4	22.4	22.4	22.4
7.5°	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8
10°	11.2	11.2	11.2	11.2	11.2	11.2	5.6	5.6	5.6	5.6	5.6
12.5°	5.6	5.6	5.6	5.6	5.6	5.6	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	33.6	33.6	33.6	33.6	33.6	39.1	39.1	44.7	44.7	50.3	50.3
5°	22.4	22.4	28.0	28.0	28.0	28.0	33.6	33.6	33.6	39.1	39.1
7.5°	16.8	16.8	16.8	16.8	16.8	22.4	22.4	28.0	28.0	33.6	33.6
10°	5.6	5.6	11.2	11.2	11.2	11.2	16.8	16.8	16.8	22.4	28.0
12.5°	0.0	0.0	5.6	5.6	5.6	5.6	11.2	11.2	11.2	16.8	22.4
15°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6	11.2	16.8
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6	11.2
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	55.9	55.9	61.5	61.5	67.1	67.1	72.7	72.7	72.7	72.7	72.7
5°	44.7	44.7	50.3	55.9	55.9	61.5	67.1	67.1	67.1	67.1	67.1
7.5°	39.1	39.1	44.7	50.3	50.3	55.9	61.5	61.5	67.1	67.1	67.1
10°	28.0	33.6	39.1	44.7	44.7	50.3	55.9	55.9	61.5	61.5	61.5
12.5°	22.4	28.0	33.6	39.1	39.1	44.7	50.3	50.3	55.9	55.9	61.5
15°	16.8	22.4	28.0	33.6	33.6	39.1	44.7	44.7	50.3	55.9	61.5
17.5°	11.2	16.8	22.4	28.0	28.0	33.6	39.1	44.7	50.3	50.3	55.9
20°	11.2	11.2	16.8	22.4	22.4	28.0	33.6	39.1	44.7	44.7	50.3
22.5°	5.6	5.6	11.2	16.8	16.8	22.4	28.0	33.6	39.1	39.1	44.7
25°	0.0	0.0	5.6	11.2	11.2	16.8	22.4	22.4	28.0	28.0	33.6
27.5°	0.0	0.0	5.6	5.6	11.2	11.2	16.8	16.8	22.4	22.4	28.0
30°	0.0	0.0	5.6	5.6	11.2	11.2	16.8	16.8	22.4	22.4	22.4
32.5°	0.0	0.0	0.0	5.6	5.6	5.6	11.2	11.2	16.8	16.8	22.4
35°	0.0	0.0	0.0	5.6	5.6	5.6	11.2	11.2	16.8	16.8	16.8
37.5°	0.0	0.0	0.0	5.6	5.6	5.6	11.2	11.2	11.2	11.2	16.8
40°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	11.2	11.2	11.2
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	11.2	11.2	11.2
45°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	11.2	11.2	11.2
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	11.2	11.2	11.2
50°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	11.2	11.2	11.2
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6	5.6	5.6
55°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6	5.6	5.6
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6	5.6	5.6
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6
75°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6	5.6	5.6
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	11.2	11.2	11.2
80°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	11.2	11.2	11.2
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6	5.6	11.2
85°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6	5.6	5.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.6	5.6	5.6	5.6	5.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	72.7	72.7
5°	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	67.1	67.1
7.5°	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	72.7	67.1	67.1
10°	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1
12.5°	61.5	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1
15°	61.5	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1
17.5°	55.9	61.5	61.5	61.5	67.1	67.1	67.1	67.1	67.1	67.1	67.1
20°	50.3	55.9	55.9	55.9	61.5	61.5	61.5	61.5	67.1	67.1	67.1
22.5°	44.7	50.3	50.3	50.3	55.9	55.9	55.9	55.9	61.5	61.5	61.5
25°	39.1	39.1	44.7	44.7	50.3	50.3	50.3	50.3	50.3	50.3	50.3
27.5°	28.0	33.6	33.6	33.6	39.1	39.1	39.1	39.1	44.7	44.7	44.7
30°	28.0	28.0	28.0	28.0	33.6	33.6	33.6	33.6	39.1	39.1	39.1
32.5°	22.4	28.0	28.0	28.0	33.6	33.6	33.6	33.6	39.1	39.1	39.1
35°	22.4	22.4	22.4	22.4	28.0	28.0	28.0	28.0	33.6	33.6	33.6
37.5°	16.8	22.4	22.4	22.4	28.0	28.0	28.0	28.0	33.6	33.6	33.6
40°	16.8	16.8	16.8	16.8	22.4	22.4	22.4	22.4	28.0	28.0	28.0
42.5°	16.8	16.8	16.8	16.8	22.4	22.4	22.4	22.4	28.0	28.0	28.0
45°	16.8	16.8	16.8	16.8	22.4	22.4	22.4	22.4	28.0	28.0	28.0
47.5°	16.8	16.8	16.8	16.8	22.4	22.4	22.4	22.4	28.0	28.0	28.0
50°	16.8	16.8	16.8	16.8	22.4	22.4	22.4	22.4	28.0	28.0	28.0
52.5°	11.2	11.2	11.2	11.2	16.8	16.8	16.8	16.8	22.4	22.4	22.4
55°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	16.8	16.8	16.8
57.5°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	16.8	16.8	16.8
60°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2
62.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
65°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	5.6	5.6
67.5°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2
70°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2
72.5°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2
75°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2
77.5°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2
80°	16.8	16.8	16.8	16.8	16.8	11.2	11.2	11.2	11.2	11.2	11.2
82.5°	11.2	16.8	16.8	16.8	16.8	11.2	11.2	11.2	11.2	11.2	11.2
85°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2
87.5°	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	72.7	72.7	67.1	67.1	67.1	67.1	67.1	67.1	67.1	72.7	72.7
5°	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	72.7	72.7
7.5°	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	72.7	72.7
10°	67.1	67.1	67.1	67.1	61.5	61.5	67.1	67.1	67.1	72.7	72.7
12.5°	67.1	67.1	67.1	67.1	61.5	61.5	67.1	67.1	72.7	72.7	78.3
15°	67.1	67.1	61.5	61.5	61.5	61.5	67.1	67.1	72.7	72.7	78.3
17.5°	67.1	67.1	61.5	61.5	61.5	61.5	67.1	67.1	72.7	72.7	78.3
20°	67.1	67.1	61.5	61.5	61.5	61.5	61.5	61.5	67.1	72.7	72.7
22.5°	61.5	61.5	61.5	61.5	55.9	55.9	61.5	61.5	67.1	72.7	72.7
25°	50.3	55.9	55.9	55.9	55.9	55.9	61.5	61.5	67.1	72.7	72.7
27.5°	44.7	50.3	50.3	50.3	50.3	55.9	55.9	61.5	67.1	72.7	72.7
30°	39.1	44.7	44.7	44.7	50.3	55.9	55.9	61.5	67.1	72.7	72.7
32.5°	39.1	44.7	44.7	44.7	50.3	50.3	55.9	55.9	61.5	67.1	72.7
35°	39.1	39.1	44.7	44.7	44.7	50.3	50.3	55.9	61.5	67.1	72.7
37.5°	39.1	39.1	44.7	44.7	44.7	50.3	50.3	55.9	61.5	67.1	72.7
40°	33.6	39.1	39.1	44.7	44.7	50.3	50.3	55.9	61.5	72.7	78.3
42.5°	33.6	33.6	39.1	39.1	44.7	50.3	50.3	55.9	61.5	72.7	78.3
45°	33.6	39.1	39.1	44.7	50.3	55.9	55.9	61.5	67.1	72.7	78.3
47.5°	33.6	39.1	39.1	44.7	55.9	55.9	61.5	61.5	67.1	72.7	78.3
50°	33.6	39.1	39.1	44.7	61.5	61.5	61.5	61.5	67.1	72.7	78.3
52.5°	28.0	33.6	33.6	39.1	50.3	55.9	61.5	67.1	72.7	78.3	83.9
55°	22.4	28.0	28.0	33.6	44.7	50.3	61.5	72.7	78.3	83.9	89.5
57.5°	22.4	22.4	28.0	28.0	39.1	50.3	67.1	78.3	83.9	89.5	95.1
60°	16.8	16.8	22.4	22.4	33.6	44.7	61.5	78.3	83.9	95.1	100.7
62.5°	11.2	16.8	16.8	22.4	28.0	44.7	61.5	78.3	89.5	100.7	106.3
65°	11.2	11.2	16.8	16.8	28.0	39.1	55.9	67.1	83.9	100.7	117.4
67.5°	16.8	16.8	22.4	22.4	28.0	39.1	55.9	67.1	83.9	106.3	123.0
70°	16.8	16.8	22.4	22.4	33.6	44.7	55.9	67.1	83.9	106.3	123.0
72.5°	16.8	16.8	22.4	22.4	33.6	39.1	50.3	61.5	78.3	95.1	111.8
75°	11.2	16.8	16.8	16.8	28.0	33.6	44.7	55.9	72.7	89.5	106.3
77.5°	11.2	11.2	11.2	11.2	22.4	28.0	39.1	44.7	61.5	78.3	95.1
80°	11.2	11.2	11.2	11.2	16.8	22.4	33.6	39.1	55.9	72.7	89.5
82.5°	11.2	11.2	5.6	5.6	11.2	16.8	22.4	28.0	44.7	55.9	72.7
85°	11.2	11.2	5.6	5.6	5.6	11.2	11.2	16.8	22.4	28.0	33.6
87.5°	11.2	11.2	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	72.7	72.7	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3
5°	72.7	78.3	78.3	83.9	83.9	83.9	89.5	89.5	89.5	89.5	89.5
7.5°	72.7	78.3	78.3	83.9	83.9	83.9	89.5	89.5	89.5	95.1	95.1
10°	72.7	78.3	78.3	83.9	83.9	89.5	95.1	95.1	100.7	100.7	100.7
12.5°	78.3	83.9	83.9	89.5	89.5	95.1	100.7	100.7	106.3	111.8	111.8
15°	78.3	83.9	89.5	89.5	95.1	100.7	106.3	106.3	111.8	117.4	123.0
17.5°	78.3	83.9	89.5	89.5	95.1	100.7	111.8	117.4	123.0	134.2	139.8
20°	78.3	83.9	89.5	89.5	95.1	106.3	111.8	123.0	128.6	139.8	151.0
22.5°	78.3	83.9	89.5	95.1	100.7	111.8	123.0	128.6	139.8	156.6	167.8
25°	78.3	83.9	89.5	95.1	100.7	111.8	123.0	134.2	145.4	167.8	190.1
27.5°	78.3	83.9	95.1	100.7	106.3	117.4	134.2	145.4	156.6	195.7	234.9
30°	78.3	83.9	95.1	100.7	106.3	123.0	139.8	151.0	167.8	234.9	296.4
32.5°	78.3	89.5	95.1	106.3	111.8	128.6	151.0	167.8	184.5	279.6	369.1
35°	78.3	89.5	95.1	106.3	111.8	134.2	156.6	178.9	201.3	341.1	480.9
37.5°	78.3	89.5	95.1	106.3	111.8	145.4	178.9	212.5	246.1	391.5	536.8
40°	83.9	95.1	100.7	111.8	117.4	151.0	184.5	218.1	251.6	397.0	542.4
42.5°	83.9	95.1	100.7	111.8	117.4	145.4	178.9	206.9	234.9	397.0	559.2
45°	83.9	95.1	106.3	111.8	123.0	151.0	178.9	201.3	229.3	436.2	637.5
47.5°	83.9	95.1	106.3	111.8	123.0	151.0	178.9	206.9	234.9	576.0	911.5
50°	83.9	95.1	106.3	111.8	123.0	156.6	190.1	223.7	257.2	861.2	1465.1
52.5°	89.5	95.1	106.3	111.8	117.4	156.6	195.7	234.9	274.0	1118.4	1957.3
55°	95.1	100.7	106.3	111.8	117.4	167.8	218.1	268.4	318.8	1202.3	2080.3
57.5°	100.7	106.3	111.8	111.8	117.4	178.9	246.1	307.6	369.1	1196.7	2018.8
60°	106.3	111.8	117.4	123.0	128.6	190.1	257.2	318.8	380.3	1084.9	1789.5
62.5°	117.4	128.6	139.8	145.4	156.6	218.1	274.0	335.5	391.5	889.2	1381.3
65°	134.2	145.4	151.0	162.2	167.8	223.7	285.2	341.1	397.0	738.2	1073.7
67.5°	139.8	151.0	156.6	167.8	173.4	229.3	285.2	341.1	397.0	626.3	850.0
70°	139.8	151.0	162.2	167.8	178.9	234.9	285.2	341.1	391.5	542.4	693.4
72.5°	128.6	145.4	156.6	173.4	184.5	234.9	279.6	329.9	374.7	480.9	587.2
75°	123.0	145.4	162.2	184.5	201.3	234.9	274.0	307.6	341.1	419.4	497.7
77.5°	111.8	139.8	167.8	195.7	223.7	246.1	262.8	285.2	302.0	352.3	402.6
80°	106.3	134.2	162.2	190.1	218.1	229.3	234.9	246.1	251.6	257.2	262.8
82.5°	83.9	106.3	128.6	145.4	167.8	156.6	151.0	139.8	128.6	123.0	117.4
85°	39.1	44.7	44.7	50.3	50.3	50.3	44.7	44.7	39.1	33.6	28.0
87.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	78.3	78.3	78.3	78.3	72.7	72.7	72.7	72.7	67.1	67.1	67.1
5°	89.5	89.5	89.5	89.5	83.9	83.9	83.9	83.9	78.3	78.3	78.3
7.5°	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
10°	106.3	106.3	106.3	111.8	111.8	111.8	111.8	111.8	111.8	111.8	111.8
12.5°	117.4	117.4	123.0	123.0	128.6	128.6	134.2	134.2	139.8	139.8	139.8
15°	128.6	134.2	139.8	145.4	145.4	151.0	156.6	162.2	167.8	173.4	178.9
17.5°	151.0	156.6	167.8	178.9	190.1	201.3	218.1	240.5	257.2	274.0	296.4
20°	167.8	184.5	218.1	257.2	290.8	324.3	408.2	492.1	576.0	659.9	743.8
22.5°	201.3	234.9	346.7	464.1	576.0	687.8	950.7	1213.5	1470.7	1733.6	1968.4
25°	268.4	341.1	598.4	855.6	1107.2	1364.5	1834.2	2309.6	2779.3	3249.0	3685.2
27.5°	369.1	503.3	922.7	1347.7	1767.1	2186.5	2868.8	3556.6	4238.8	4926.7	5536.2
30°	514.5	732.6	1358.9	1990.8	2617.1	3243.4	4104.6	4971.4	5832.6	6693.8	7253.0
32.5°	699.0	1023.4	1817.4	2611.5	3405.6	4199.7	5150.4	6101.0	7046.1	7996.8	8589.5
35°	894.7	1308.6	2264.8	3226.7	4182.9	5144.8	6145.8	7146.8	8147.8	9148.8	9875.7
37.5°	1006.6	1476.3	2611.5	3746.7	4876.4	6011.6	7107.6	8209.3	9305.3	10401.4	11285.0
40°	1112.8	1677.6	2986.2	4294.8	5603.3	6911.9	8192.5	9473.1	10753.7	12034.3	13169.5
42.5°	1269.4	1979.6	3506.3	5032.9	6554.0	8080.7	9763.9	11452.7	13136.0	14819.2	16563.9
45°	1593.8	2550.0	4529.6	6509.3	8483.3	10462.9	12850.8	15244.2	17632.0	20025.5	22262.3
47.5°	2376.7	3836.2	6537.2	9238.2	11939.2	14640.2	17391.6	20142.9	22894.2	25645.6	28307.4
50°	3679.6	5888.5	9266.2	12643.8	16015.9	19393.6	22139.3	24885.0	27625.2	30370.9	33016.0
52.5°	4904.3	7851.4	11480.7	15115.6	18744.9	22379.8	24812.4	27244.9	29677.5	32110.1	34671.3
55°	5323.7	8561.6	12235.6	15915.2	19589.3	23268.9	25612.0	27960.7	30303.8	32646.9	35303.2
57.5°	4954.6	7890.5	11592.5	15294.5	18990.9	22692.9	25310.1	27932.8	30549.9	33172.6	36019.0
60°	4149.4	6503.7	10390.2	14282.3	18168.9	22055.4	25008.1	27960.7	30913.4	33866.0	36706.8
62.5°	3288.2	5189.5	9305.3	13421.2	17537.0	21652.8	24655.8	27664.3	30667.3	33670.3	35851.2
65°	2522.1	3970.4	8019.1	12073.4	16122.2	20176.5	22637.0	25103.1	27563.7	30029.8	31539.7
67.5°	1873.4	2896.7	6436.6	9982.0	13521.8	17061.6	18873.5	20690.9	22502.8	24320.2	25494.6
70°	1381.3	2063.5	4473.7	6883.9	9288.6	11698.8	13359.6	15020.5	16675.8	18336.6	19555.7
72.5°	956.3	1319.7	2762.5	4210.9	5653.7	7096.4	8779.7	10462.9	12140.5	13823.8	15210.6
75°	654.3	810.9	1487.5	2164.2	2840.8	3517.5	4792.5	6067.5	7342.5	8617.5	9350.1
77.5°	486.5	570.4	771.7	978.6	1179.9	1381.3	1627.3	1873.4	2119.4	2365.5	2684.2
80°	268.4	268.4	296.4	318.8	346.7	369.1	436.2	508.9	576.0	648.7	738.2
82.5°	123.0	128.6	139.8	151.0	156.6	167.8	178.9	190.1	201.3	212.5	212.5
85°	33.6	39.1	39.1	33.6	33.6	28.0	28.0	33.6	33.6	33.6	33.6
87.5°	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	67.1	61.5	61.5	61.5	55.9	55.9	55.9	55.9	55.9	55.9	55.9
5°	78.3	78.3	78.3	78.3	72.7	72.7	72.7	72.7	72.7	67.1	67.1
7.5°	95.1	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	83.9	83.9
10°	111.8	111.8	111.8	111.8	111.8	111.8	111.8	111.8	111.8	106.3	106.3
12.5°	139.8	139.8	139.8	139.8	145.4	145.4	139.8	139.8	139.8	134.2	134.2
15°	184.5	190.1	195.7	195.7	201.3	201.3	201.3	195.7	195.7	190.1	184.5
17.5°	313.2	329.9	352.3	374.7	397.0	413.8	413.8	402.6	391.5	380.3	369.1
20°	833.2	917.1	1006.6	1096.1	1191.1	1258.2	1213.5	1179.9	1146.4	1107.2	1073.7
22.5°	2208.9	2443.8	2684.2	2852.0	3019.8	3137.2	3042.1	2857.6	2673.0	2494.1	2309.6
25°	4121.4	4552.0	4988.2	5167.1	5351.7	5485.9	5424.4	5144.8	4865.2	4591.2	4311.5
27.5°	6145.8	6749.7	7359.3	7515.8	7672.4	7789.9	7767.5	7404.0	7040.5	6677.0	6313.5
30°	7812.2	8371.4	8930.7	9087.2	9243.8	9350.1	9232.6	8869.1	8505.7	8142.2	7778.7
32.5°	9187.9	9780.7	10379.0	10585.9	10792.8	10932.6	10792.8	10356.7	9920.5	9489.9	9053.7
35°	10602.7	11324.1	12051.1	12313.9	12576.7	12744.5	12509.6	11972.8	11435.9	10904.7	10367.8
37.5°	12168.5	13046.5	13930.0	14287.9	14651.4	14903.1	14724.1	14053.1	13376.4	12705.4	12028.7
40°	14310.3	15445.5	16586.3	17229.4	17866.9	18319.9	18001.1	17223.8	16440.9	15663.6	14880.7
42.5°	18314.3	20059.0	21803.8	22726.5	23643.6	24309.1	23951.2	22994.9	22038.6	21082.4	20126.1
45°	24499.2	26730.5	28967.3	30315.0	31668.3	32663.7	32249.9	31047.6	29839.7	28637.4	27435.1
47.5°	30969.3	33631.2	36293.0	37366.7	38446.0	39284.8	39184.2	37685.5	36186.8	34693.7	33195.0
50°	35666.7	38311.8	40956.9	41879.6	42807.9	43495.7	43238.5	41331.6	39419.0	37512.1	35599.6
52.5°	37232.5	39788.1	42349.3	43451.0	44552.6	45374.7	45061.5	42914.1	40766.7	38625.0	36477.6
55°	37959.5	40615.8	43272.0	44614.1	45961.8	46946.1	46493.1	44138.8	41778.9	39424.6	37064.7
57.5°	38865.4	41711.8	44558.2	46029.0	47499.7	48562.2	47958.2	45520.1	43081.9	40649.3	38211.1
60°	39547.7	42382.9	45223.7	46403.6	47589.2	48416.8	47835.2	45464.1	43087.5	40716.4	38345.3
62.5°	38037.8	40218.7	42399.7	43277.6	44155.6	44793.1	44463.2	42215.1	39967.1	37719.0	35471.0
65°	33055.2	34565.1	36080.5	36673.3	37260.5	37713.4	37612.8	35717.0	33821.3	31931.2	30035.4
67.5°	26674.5	27848.9	29028.8	29867.7	30712.1	31366.3	31293.6	29565.7	27837.7	26109.7	24381.8
70°	20780.4	21999.5	23218.6	24275.5	25338.0	26160.1	26053.8	24448.9	22838.3	21233.4	19622.8
72.5°	16603.1	17989.9	19376.8	19980.7	20584.7	21009.7	20696.5	19483.0	18263.9	17050.5	15831.4
75°	10082.6	10809.6	11542.2	11536.6	11536.6	11469.5	11156.3	10462.9	9769.5	9076.1	8382.6
77.5°	3003.0	3321.7	3640.5	3948.1	4261.2	4496.1	4434.6	4071.1	3702.0	3338.5	2969.4
80°	827.6	911.5	1001.0	1040.1	1079.3	1129.6	1258.2	1168.8	1079.3	995.4	905.9
82.5°	212.5	212.5	212.5	206.9	201.3	190.1	173.4	162.2	151.0	139.8	128.6
85°	33.6	28.0	28.0	28.0	22.4	22.4	22.4	22.4	16.8	16.8	11.2
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3
2.5°	55.9	55.9	50.3	50.3	50.3	50.3	50.3	50.3	50.3	50.3	44.7
5°	67.1	67.1	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	55.9
7.5°	83.9	83.9	78.3	78.3	78.3	78.3	72.7	72.7	72.7	72.7	67.1
10°	106.3	100.7	100.7	95.1	95.1	95.1	89.5	89.5	89.5	83.9	83.9
12.5°	134.2	128.6	128.6	123.0	117.4	117.4	111.8	106.3	100.7	100.7	95.1
15°	178.9	173.4	167.8	162.2	156.6	145.4	139.8	128.6	123.0	117.4	111.8
17.5°	341.1	313.2	285.2	257.2	234.9	212.5	190.1	167.8	156.6	145.4	134.2
20°	950.7	822.0	699.0	576.0	497.7	419.4	341.1	262.8	229.3	201.3	167.8
22.5°	2057.9	1800.7	1549.0	1291.8	1084.9	883.6	676.6	469.7	391.5	318.8	240.5
25°	3825.0	3332.9	2846.4	2354.3	1962.8	1571.4	1179.9	788.5	643.1	497.7	352.3
27.5°	5676.0	5038.5	4401.0	3763.5	3142.8	2516.5	1890.1	1269.4	1017.8	771.7	520.1
30°	7102.0	6425.4	5754.3	5077.7	4294.8	3511.9	2723.4	1940.5	1543.4	1146.4	743.8
32.5°	8326.7	7594.1	6867.2	6134.6	5228.7	4322.7	3416.8	2510.9	2013.2	1515.5	1012.2
35°	9540.2	8707.0	7879.3	7046.1	6073.1	5100.0	4127.0	3154.0	2522.1	1890.1	1252.6
37.5°	11016.5	9998.8	8986.6	7974.4	6973.4	5978.0	4977.0	3976.0	3170.7	2371.1	1565.8
40°	13588.9	12291.5	10999.8	9702.4	8533.6	7370.4	6201.7	5032.9	4020.8	3008.6	1990.8
42.5°	18498.8	16871.5	15249.8	13622.5	12006.3	10390.2	8768.5	7152.4	5709.6	4272.4	2829.6
45°	25349.2	23263.3	21183.0	19097.2	17106.4	15121.2	13130.4	11139.6	8947.4	6755.3	4557.6
47.5°	30913.4	28626.2	26344.6	24057.4	21848.5	19645.2	17436.3	15227.4	12420.2	9618.5	6811.2
50°	33424.3	31243.3	29068.0	26887.0	24672.5	22452.5	20232.4	18017.9	14796.8	11581.3	8360.3
52.5°	34268.7	32054.2	29845.3	27630.8	25433.1	23235.4	21037.7	18839.9	15490.2	12146.1	8796.4
55°	34732.8	32395.3	30063.4	27725.9	25360.4	22989.3	20618.2	18252.8	14919.8	11592.5	8259.6
57.5°	35672.3	33127.9	30589.0	28044.6	25349.2	22653.8	19952.8	17257.4	13969.2	10681.0	7392.8
60°	35845.7	33340.4	30840.7	28341.0	25360.4	22379.8	19393.6	16412.9	13147.1	9886.9	6621.1
62.5°	33379.5	31288.1	29202.2	27110.7	24124.5	21138.3	18146.5	15160.3	12034.3	8908.3	5776.7
65°	28229.2	26422.9	24622.2	22816.0	20377.8	17945.2	15507.0	13068.8	10278.4	7493.5	4703.0
67.5°	22614.6	20847.5	19086.0	17318.9	15484.7	13656.0	11821.8	9987.6	7834.6	5681.6	3528.6
70°	17928.4	16228.4	14534.0	12834.0	11212.3	9584.9	7957.6	6335.9	4999.4	3668.4	2331.9
72.5°	14209.6	12582.3	10960.6	9333.3	7862.6	6391.8	4921.1	3450.4	2784.9	2125.0	1459.6
75°	7538.2	6693.8	5855.0	5010.6	4182.9	3349.7	2516.5	1688.8	1426.0	1163.2	894.7
77.5°	2600.3	2231.3	1867.8	1498.7	1247.0	995.4	743.8	492.1	464.1	441.8	413.8
80°	788.5	671.1	553.6	436.2	385.9	335.5	285.2	234.9	218.1	201.3	178.9
82.5°	123.0	111.8	106.3	95.1	89.5	89.5	83.9	78.3	67.1	61.5	50.3
85°	11.2	5.6	5.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	50.3	50.3
2.5°	44.7	44.7
5°	55.9	55.9
7.5°	67.1	67.1
10°	78.3	78.3
12.5°	89.5	89.5
15°	106.3	100.7
17.5°	123.0	117.4
20°	134.2	123.0
22.5°	162.2	139.8
25°	206.9	173.4
27.5°	268.4	212.5
30°	346.7	268.4
32.5°	514.5	374.7
35°	620.7	453.0
37.5°	760.5	525.7
40°	978.6	637.5
42.5°	1386.9	866.8
45°	2365.5	1437.2
47.5°	4009.6	2449.4
50°	5139.2	3142.8
52.5°	5452.3	3332.9
55°	4932.3	3058.9
57.5°	4104.6	2600.3
60°	3360.9	2141.8
62.5°	2650.7	1694.4
65°	1912.5	1280.6
67.5°	1375.7	984.2
70°	1001.0	771.7
72.5°	794.1	643.1
75°	631.9	536.8
77.5°	391.5	357.9
80°	162.2	151.0
82.5°	39.1	33.6
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066542

CATALOG NUMBER: NVN-SA5B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-5

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-735-U-5WQ

Data in this report applies to families of products including GSS-SB1A-735-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-735-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3369
 CIE u' : 0.2386
 CIE v' : 0.5156
 Duv: 0.0013
 CIE x: 0.4143
 CIE y: 0.3980
 CIE z: 0.1877
 Peak Wavelength (nm): 590
 Dominant Wavelength (nm): 580
 Purity: 43.80166
 R_f: 71.4
 R_g: 96

CRI (Ra): 70.1
 R1: 66.6
 R2: 77.6
 R3: 88.5
 R4: 69.5
 R5: 66.4
 R6: 69.6
 R7: 77.5
 R8: 44.9
 R9: -40.2
 R10: 49.1
 R11: 66.3
 R12: 45.7
 R13: 68.0
 R14: 93.4
 R15: 57.6



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-5


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-5

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-5

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5


Scotopic Flux vs. Wavelength


Scotopic Lumens: NR
S/P: 1.29

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.36


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5





TM-30-18

Summary

$R_f = 71.4$
 $R_g = 96$
 $CIE R_a = 70.1$
 $R_g = -40.2$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 57	CES51 = 84	CES76 = 50
CES02 = 62	CES27 = 80	CES52 = 86	CES77 = 74
CES03 = 31	CES28 = 81	CES53 = 72	CES78 = 54
CES04 = 70	CES29 = 50	CES54 = 79	CES79 = 81
CES05 = 48	CES30 = 55	CES55 = 78	CES80 = 79
CES06 = 51	CES31 = 56	CES56 = 67	CES81 = 74
CES07 = 40	CES32 = 54	CES57 = 65	CES82 = 91
CES08 = 39	CES33 = 60	CES58 = 68	CES83 = 86
CES09 = 29	CES34 = 69	CES59 = 85	CES84 = 89
CES10 = 75	CES35 = 83	CES60 = 91	CES85 = 83
CES11 = 58	CES36 = 88	CES61 = 85	CES86 = 66
CES12 = 64	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 43	CES38 = 64	CES63 = 71	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 70	CES89 = 68
CES15 = 71	CES40 = 86	CES65 = 64	CES90 = 72
CES16 = 47	CES41 = 81	CES66 = 65	CES91 = 95
CES17 = 50	CES42 = 79	CES67 = 63	CES92 = 62
CES18 = 56	CES43 = 71	CES68 = 69	CES93 = 78
CES19 = 72	CES44 = 98	CES69 = 80	CES94 = 51
CES20 = 65	CES45 = 80	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 75	CES71 = 58	CES96 = 76
CES22 = 79	CES47 = 71	CES72 = 85	CES97 = 82
CES23 = 92	CES48 = 61	CES73 = 51	CES98 = 72
CES24 = 91	CES49 = 74	CES74 = 94	CES99 = 60
CES25 = 72	CES50 = 83	CES75 = 57	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)