

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066546

Luminaire Tested: **NVN-SA6B-735-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066546
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA6B-735-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 6xLight Square PACKAGE
70CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (84) 3500K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 21451.4 lumens
Efficiency: N/A
Efficacy: 101.7 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G4

Input Watts (W): 211
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 4.2 fc
 Type III - Short - N/A

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	127.6	0.0	127.6
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	21323.7	0.0	21323.7
	% Fixture	99.4	0.0	99.4
Total	Lumens	21451.3	0.0	21451.3
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	6.3	0.0
10°-20°	31.5	0.1
20°-30°	400.4	1.9
30°-40°	1349.4	6.3
40°-50°	4075.1	19.0
50°-60°	7189.7	33.5
60°-70°	6334.2	29.5
70°-80°	2016.3	9.4
80°-90°	48.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	21451.3	100.0
0°-180°	21451.4	100.0



REPORT NUMBER: P1066546


CATALOG NUMBER: NVN-SA6B-735-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	419.1	2.0			
FM	(30°-60°)	12564.7	58.6			
FH	(60°-80°)	8300.5	38.7			G4/12000
FVH	(80°-90°)	39.5	0.2			G1/100
BL	(0°-30°)	19.1	0.1	B0/110		
BM	(30°-60°)	49.4	0.2	B0/220		
BH	(60°-80°)	50.0	0.2	B0/110		G0/110
BVH	(80°-90°)	9.1	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G4

Type III Short



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	53.8	47.1
5°	67.3	67.3	67.3	60.5	60.5	60.5	53.8	53.8	53.8	53.8	53.8
7.5°	80.7	74.0	74.0	67.3	67.3	67.3	60.5	60.5	60.5	60.5	53.8
10°	94.2	87.5	87.5	80.7	80.7	74.0	74.0	67.3	67.3	60.5	60.5
12.5°	107.6	100.9	94.2	87.5	87.5	80.7	80.7	74.0	74.0	67.3	67.3
15°	121.1	114.4	107.6	100.9	94.2	94.2	87.5	80.7	74.0	74.0	67.3
17.5°	141.3	127.8	121.1	107.6	100.9	94.2	87.5	80.7	80.7	74.0	74.0
20°	148.0	134.5	127.8	114.4	107.6	100.9	94.2	87.5	80.7	80.7	74.0
22.5°	174.9	148.0	141.3	127.8	121.1	114.4	100.9	94.2	87.5	80.7	74.0
25°	215.3	174.9	154.7	134.5	127.8	114.4	107.6	94.2	87.5	80.7	74.0
27.5°	262.4	195.1	174.9	148.0	134.5	121.1	107.6	94.2	87.5	80.7	74.0
30°	322.9	228.7	195.1	161.5	148.0	134.5	114.4	100.9	94.2	87.5	74.0
32.5°	450.7	282.5	228.7	174.9	154.7	141.3	121.1	100.9	94.2	87.5	74.0
35°	544.9	343.1	275.8	201.8	174.9	154.7	127.8	100.9	94.2	87.5	74.0
37.5°	632.3	349.8	282.5	215.3	188.4	161.5	127.8	100.9	94.2	87.5	74.0
40°	773.6	363.3	282.5	201.8	181.6	154.7	134.5	107.6	100.9	87.5	80.7
42.5°	1042.7	417.1	302.7	188.4	168.2	154.7	134.5	114.4	100.9	94.2	80.7
45°	1735.6	618.9	410.4	195.1	174.9	154.7	134.5	114.4	107.6	94.2	87.5
47.5°	2953.2	1076.3	639.1	201.8	181.6	154.7	134.5	107.6	100.9	94.2	80.7
50°	3780.6	1379.1	807.3	235.4	201.8	174.9	141.3	107.6	100.9	94.2	87.5
52.5°	4016.1	1466.5	874.5	275.8	235.4	195.1	148.0	107.6	100.9	100.9	94.2
55°	3679.7	1426.1	874.5	322.9	269.1	222.0	168.2	114.4	107.6	107.6	100.9
57.5°	3128.1	1318.5	834.2	349.8	296.0	235.4	181.6	121.1	114.4	114.4	107.6
60°	2576.5	1110.0	753.4	390.2	329.6	269.1	208.5	148.0	141.3	134.5	121.1
62.5°	2045.0	894.7	659.3	417.1	356.5	289.3	228.7	161.5	154.7	148.0	141.3
65°	1540.5	780.3	612.2	437.3	370.0	302.7	235.4	168.2	161.5	161.5	154.7
67.5°	1184.0	713.1	585.3	450.7	383.4	316.2	248.9	181.6	174.9	168.2	161.5
70°	935.1	659.3	551.6	444.0	383.4	322.9	255.6	195.1	181.6	174.9	161.5
72.5°	780.3	598.7	511.3	423.8	376.7	329.6	282.5	235.4	208.5	188.4	161.5
75°	652.5	538.2	464.2	383.4	349.8	322.9	289.3	255.6	222.0	188.4	154.7
77.5°	430.5	390.2	356.5	322.9	302.7	282.5	255.6	235.4	201.8	174.9	141.3
80°	181.6	168.2	174.9	174.9	174.9	174.9	168.2	168.2	148.0	127.8	100.9
82.5°	40.4	33.6	40.4	40.4	40.4	40.4	33.6	33.6	33.6	26.9	26.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1
5°	53.8	53.8	53.8	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1
7.5°	53.8	53.8	53.8	47.1	47.1	47.1	47.1	40.4	40.4	40.4	40.4
10°	53.8	53.8	53.8	47.1	47.1	47.1	47.1	40.4	40.4	40.4	40.4
12.5°	60.5	60.5	53.8	53.8	47.1	47.1	47.1	40.4	40.4	40.4	40.4
15°	60.5	60.5	53.8	53.8	47.1	47.1	47.1	40.4	40.4	40.4	40.4
17.5°	67.3	60.5	60.5	53.8	47.1	47.1	47.1	40.4	40.4	40.4	40.4
20°	67.3	60.5	60.5	53.8	47.1	47.1	47.1	40.4	40.4	40.4	40.4
22.5°	67.3	60.5	60.5	53.8	47.1	47.1	40.4	40.4	33.6	33.6	26.9
25°	67.3	60.5	60.5	53.8	47.1	47.1	40.4	40.4	33.6	26.9	26.9
27.5°	67.3	60.5	60.5	53.8	47.1	40.4	40.4	33.6	26.9	20.2	20.2
30°	67.3	60.5	60.5	53.8	47.1	40.4	33.6	26.9	20.2	20.2	13.5
32.5°	67.3	60.5	53.8	47.1	40.4	33.6	33.6	26.9	20.2	13.5	13.5
35°	67.3	60.5	53.8	47.1	40.4	33.6	33.6	26.9	20.2	13.5	13.5
37.5°	67.3	60.5	53.8	47.1	40.4	33.6	26.9	20.2	13.5	13.5	6.7
40°	67.3	60.5	53.8	47.1	40.4	33.6	26.9	20.2	13.5	13.5	6.7
42.5°	67.3	60.5	53.8	47.1	40.4	33.6	26.9	20.2	13.5	13.5	6.7
45°	74.0	67.3	60.5	47.1	40.4	33.6	33.6	26.9	20.2	13.5	13.5
47.5°	74.0	67.3	60.5	47.1	40.4	33.6	33.6	26.9	20.2	13.5	13.5
50°	80.7	74.0	67.3	53.8	47.1	40.4	33.6	20.2	13.5	13.5	6.7
52.5°	87.5	80.7	74.0	67.3	60.5	47.1	33.6	20.2	6.7	6.7	6.7
55°	94.2	87.5	87.5	80.7	74.0	53.8	40.4	20.2	0.0	0.0	0.0
57.5°	100.9	94.2	94.2	87.5	80.7	60.5	40.4	20.2	0.0	0.0	0.0
60°	114.4	107.6	100.9	87.5	80.7	60.5	40.4	20.2	0.0	0.0	0.0
62.5°	134.5	121.1	100.9	87.5	67.3	53.8	33.6	20.2	0.0	0.0	0.0
65°	148.0	127.8	107.6	80.7	60.5	47.1	33.6	13.5	0.0	0.0	0.0
67.5°	154.7	127.8	107.6	80.7	53.8	40.4	26.9	13.5	0.0	0.0	0.0
70°	148.0	121.1	100.9	74.0	47.1	33.6	26.9	13.5	0.0	0.0	0.0
72.5°	134.5	114.4	87.5	67.3	40.4	33.6	20.2	13.5	0.0	0.0	0.0
75°	121.1	100.9	74.0	53.8	26.9	20.2	13.5	6.7	0.0	0.0	0.0
77.5°	107.6	87.5	60.5	40.4	13.5	13.5	6.7	6.7	0.0	0.0	0.0
80°	80.7	60.5	40.4	20.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	20.2	13.5	13.5	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4
5°	40.4	40.4	40.4	40.4	33.6	33.6	33.6	33.6	33.6	33.6	33.6
7.5°	40.4	40.4	40.4	40.4	33.6	33.6	33.6	33.6	26.9	26.9	26.9
10°	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	26.9	26.9	26.9
12.5°	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	26.9	26.9	26.9
15°	33.6	33.6	33.6	33.6	33.6	33.6	33.6	26.9	26.9	20.2	20.2
17.5°	33.6	33.6	33.6	33.6	26.9	26.9	26.9	20.2	20.2	13.5	13.5
20°	33.6	33.6	33.6	26.9	26.9	20.2	20.2	13.5	13.5	6.7	6.7
22.5°	26.9	20.2	20.2	13.5	13.5	6.7	6.7	6.7	0.0	0.0	0.0
25°	20.2	13.5	13.5	6.7	6.7	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	13.5	6.7	6.7	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	13.5	6.7	6.7	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	40.4	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6
5°	33.6	33.6	33.6	33.6	26.9	26.9	26.9	26.9	26.9	26.9	26.9
7.5°	26.9	26.9	26.9	26.9	26.9	26.9	20.2	20.2	20.2	20.2	20.2
10°	26.9	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2	13.5	13.5
12.5°	26.9	20.2	20.2	20.2	13.5	13.5	13.5	13.5	13.5	6.7	6.7
15°	20.2	13.5	13.5	13.5	6.7	6.7	6.7	6.7	6.7	0.0	0.0
17.5°	13.5	6.7	6.7	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	40.4	40.4
5°	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9
7.5°	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2	20.2
10°	13.5	13.5	13.5	13.5	13.5	13.5	6.7	6.7	6.7	6.7	6.7
12.5°	6.7	6.7	6.7	6.7	6.7	6.7	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	40.4	40.4	40.4	40.4	40.4	47.1	47.1	53.8	53.8	60.5	60.5
5°	26.9	26.9	33.6	33.6	33.6	33.6	40.4	40.4	40.4	47.1	47.1
7.5°	20.2	20.2	20.2	20.2	20.2	26.9	26.9	33.6	33.6	40.4	40.4
10°	6.7	6.7	13.5	13.5	13.5	13.5	20.2	20.2	20.2	26.9	33.6
12.5°	0.0	0.0	6.7	6.7	6.7	6.7	13.5	13.5	13.5	20.2	26.9
15°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7	13.5	20.2
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	13.5
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	67.3	67.3	74.0	74.0	80.7	80.7	87.5	87.5	87.5	87.5	87.5
5°	53.8	53.8	60.5	67.3	67.3	74.0	80.7	80.7	80.7	80.7	80.7
7.5°	47.1	47.1	53.8	60.5	60.5	67.3	74.0	74.0	80.7	80.7	80.7
10°	33.6	40.4	47.1	53.8	53.8	60.5	67.3	67.3	74.0	74.0	74.0
12.5°	26.9	33.6	40.4	47.1	47.1	53.8	60.5	60.5	67.3	67.3	74.0
15°	20.2	26.9	33.6	40.4	40.4	47.1	53.8	53.8	60.5	67.3	74.0
17.5°	13.5	20.2	26.9	33.6	33.6	40.4	47.1	53.8	60.5	60.5	67.3
20°	13.5	13.5	20.2	26.9	26.9	33.6	40.4	47.1	53.8	53.8	60.5
22.5°	6.7	6.7	13.5	20.2	20.2	26.9	33.6	40.4	47.1	47.1	53.8
25°	0.0	0.0	6.7	13.5	13.5	20.2	26.9	26.9	33.6	33.6	40.4
27.5°	0.0	0.0	6.7	6.7	13.5	13.5	20.2	20.2	26.9	26.9	33.6
30°	0.0	0.0	6.7	6.7	13.5	13.5	20.2	20.2	26.9	26.9	26.9
32.5°	0.0	0.0	0.0	6.7	6.7	6.7	13.5	13.5	20.2	20.2	26.9
35°	0.0	0.0	0.0	6.7	6.7	6.7	13.5	13.5	20.2	20.2	20.2
37.5°	0.0	0.0	0.0	6.7	6.7	6.7	13.5	13.5	13.5	13.5	20.2
40°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	13.5	13.5	13.5
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	13.5	13.5	13.5
45°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	13.5	13.5	13.5
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	13.5	13.5	13.5
50°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	13.5	13.5	13.5
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7	6.7	6.7
55°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7	6.7	6.7
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7	6.7	6.7
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7
75°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7	6.7	6.7
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	13.5	13.5	13.5
80°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	13.5	13.5	13.5
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7	6.7	13.5
85°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7	6.7	6.7
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.7	6.7	6.7	6.7	6.7
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	87.5	87.5
5°	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	80.7	80.7
7.5°	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	80.7	80.7
10°	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7
12.5°	74.0	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7
15°	74.0	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7
17.5°	67.3	74.0	74.0	74.0	80.7	80.7	80.7	80.7	80.7	80.7	80.7
20°	60.5	67.3	67.3	67.3	74.0	74.0	74.0	74.0	80.7	80.7	80.7
22.5°	53.8	60.5	60.5	60.5	67.3	67.3	67.3	67.3	74.0	74.0	74.0
25°	47.1	47.1	53.8	53.8	60.5	60.5	60.5	60.5	60.5	60.5	60.5
27.5°	33.6	40.4	40.4	40.4	47.1	47.1	47.1	47.1	53.8	53.8	53.8
30°	33.6	33.6	33.6	33.6	40.4	40.4	40.4	40.4	47.1	47.1	47.1
32.5°	26.9	33.6	33.6	33.6	40.4	40.4	40.4	40.4	47.1	47.1	47.1
35°	26.9	26.9	26.9	26.9	33.6	33.6	33.6	33.6	40.4	40.4	40.4
37.5°	20.2	26.9	26.9	26.9	33.6	33.6	33.6	33.6	40.4	40.4	40.4
40°	20.2	20.2	20.2	20.2	26.9	26.9	26.9	26.9	33.6	33.6	33.6
42.5°	20.2	20.2	20.2	20.2	26.9	26.9	26.9	26.9	33.6	33.6	33.6
45°	20.2	20.2	20.2	20.2	26.9	26.9	26.9	26.9	33.6	33.6	33.6
47.5°	20.2	20.2	20.2	20.2	26.9	26.9	26.9	26.9	33.6	33.6	33.6
50°	20.2	20.2	20.2	20.2	26.9	26.9	26.9	26.9	33.6	33.6	33.6
52.5°	13.5	13.5	13.5	13.5	20.2	20.2	20.2	20.2	26.9	26.9	26.9
55°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	20.2	20.2	20.2
57.5°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	20.2	20.2	20.2
60°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
62.5°	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7
65°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	6.7	6.7
67.5°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
70°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
72.5°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
75°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
77.5°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
80°	20.2	20.2	20.2	20.2	20.2	13.5	13.5	13.5	13.5	13.5	13.5
82.5°	13.5	20.2	20.2	20.2	20.2	13.5	13.5	13.5	13.5	13.5	13.5
85°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
87.5°	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	87.5	87.5	80.7	80.7	80.7	80.7	80.7	80.7	80.7	87.5	87.5
5°	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	87.5	87.5
7.5°	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	87.5	87.5
10°	80.7	80.7	80.7	80.7	74.0	74.0	80.7	80.7	80.7	87.5	87.5
12.5°	80.7	80.7	80.7	80.7	74.0	74.0	80.7	80.7	87.5	87.5	94.2
15°	80.7	80.7	74.0	74.0	74.0	74.0	80.7	80.7	87.5	87.5	94.2
17.5°	80.7	80.7	74.0	74.0	74.0	74.0	80.7	80.7	87.5	87.5	94.2
20°	80.7	80.7	74.0	74.0	74.0	74.0	74.0	74.0	80.7	87.5	87.5
22.5°	74.0	74.0	74.0	74.0	67.3	67.3	74.0	74.0	80.7	87.5	87.5
25°	60.5	67.3	67.3	67.3	67.3	67.3	74.0	74.0	80.7	87.5	87.5
27.5°	53.8	60.5	60.5	60.5	60.5	67.3	67.3	74.0	80.7	87.5	87.5
30°	47.1	53.8	53.8	53.8	60.5	67.3	67.3	74.0	80.7	87.5	87.5
32.5°	47.1	53.8	53.8	53.8	60.5	60.5	67.3	67.3	74.0	80.7	87.5
35°	47.1	47.1	53.8	53.8	53.8	60.5	60.5	67.3	74.0	80.7	87.5
37.5°	47.1	47.1	53.8	53.8	53.8	60.5	60.5	67.3	74.0	80.7	87.5
40°	40.4	47.1	47.1	53.8	53.8	60.5	60.5	67.3	74.0	87.5	94.2
42.5°	40.4	40.4	47.1	47.1	53.8	60.5	60.5	67.3	74.0	87.5	94.2
45°	40.4	47.1	47.1	53.8	60.5	67.3	67.3	74.0	80.7	87.5	94.2
47.5°	40.4	47.1	47.1	53.8	67.3	67.3	74.0	74.0	80.7	87.5	94.2
50°	40.4	47.1	47.1	53.8	74.0	74.0	74.0	74.0	80.7	87.5	94.2
52.5°	33.6	40.4	40.4	47.1	60.5	67.3	74.0	80.7	87.5	94.2	100.9
55°	26.9	33.6	33.6	40.4	53.8	60.5	74.0	87.5	94.2	100.9	107.6
57.5°	26.9	26.9	33.6	33.6	47.1	60.5	80.7	94.2	100.9	107.6	114.4
60°	20.2	20.2	26.9	26.9	40.4	53.8	74.0	94.2	100.9	114.4	121.1
62.5°	13.5	20.2	20.2	26.9	33.6	53.8	74.0	94.2	107.6	121.1	127.8
65°	13.5	13.5	20.2	20.2	33.6	47.1	67.3	80.7	100.9	121.1	141.3
67.5°	20.2	20.2	26.9	26.9	33.6	47.1	67.3	80.7	100.9	127.8	148.0
70°	20.2	20.2	26.9	26.9	40.4	53.8	67.3	80.7	100.9	127.8	148.0
72.5°	20.2	20.2	26.9	26.9	40.4	47.1	60.5	74.0	94.2	114.4	134.5
75°	13.5	20.2	20.2	20.2	33.6	40.4	53.8	67.3	87.5	107.6	127.8
77.5°	13.5	13.5	13.5	13.5	26.9	33.6	47.1	53.8	74.0	94.2	114.4
80°	13.5	13.5	13.5	13.5	20.2	26.9	40.4	47.1	67.3	87.5	107.6
82.5°	13.5	13.5	6.7	6.7	13.5	20.2	26.9	33.6	53.8	67.3	87.5
85°	13.5	13.5	6.7	6.7	6.7	13.5	13.5	20.2	26.9	33.6	40.4
87.5°	13.5	13.5	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	87.5	87.5	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
5°	87.5	94.2	94.2	100.9	100.9	100.9	107.6	107.6	107.6	107.6	107.6
7.5°	87.5	94.2	94.2	100.9	100.9	100.9	107.6	107.6	107.6	114.4	114.4
10°	87.5	94.2	94.2	100.9	100.9	107.6	114.4	114.4	121.1	121.1	121.1
12.5°	94.2	100.9	100.9	107.6	107.6	114.4	121.1	121.1	127.8	134.5	134.5
15°	94.2	100.9	107.6	107.6	114.4	121.1	127.8	127.8	134.5	141.3	148.0
17.5°	94.2	100.9	107.6	107.6	114.4	121.1	134.5	141.3	148.0	161.5	168.2
20°	94.2	100.9	107.6	107.6	114.4	127.8	134.5	148.0	154.7	168.2	181.6
22.5°	94.2	100.9	107.6	114.4	121.1	134.5	148.0	154.7	168.2	188.4	201.8
25°	94.2	100.9	107.6	114.4	121.1	134.5	148.0	161.5	174.9	201.8	228.7
27.5°	94.2	100.9	114.4	121.1	127.8	141.3	161.5	174.9	188.4	235.4	282.5
30°	94.2	100.9	114.4	121.1	127.8	148.0	168.2	181.6	201.8	282.5	356.5
32.5°	94.2	107.6	114.4	127.8	134.5	154.7	181.6	201.8	222.0	336.4	444.0
35°	94.2	107.6	114.4	127.8	134.5	161.5	188.4	215.3	242.2	410.4	578.5
37.5°	94.2	107.6	114.4	127.8	134.5	174.9	215.3	255.6	296.0	470.9	645.8
40°	100.9	114.4	121.1	134.5	141.3	181.6	222.0	262.4	302.7	477.6	652.5
42.5°	100.9	114.4	121.1	134.5	141.3	174.9	215.3	248.9	282.5	477.6	672.7
45°	100.9	114.4	127.8	134.5	148.0	181.6	215.3	242.2	275.8	524.7	766.9
47.5°	100.9	114.4	127.8	134.5	148.0	181.6	215.3	248.9	282.5	692.9	1096.5
50°	100.9	114.4	127.8	134.5	148.0	188.4	228.7	269.1	309.4	1036.0	1762.5
52.5°	107.6	114.4	127.8	134.5	141.3	188.4	235.4	282.5	329.6	1345.4	2354.5
55°	114.4	121.1	127.8	134.5	141.3	201.8	262.4	322.9	383.4	1446.3	2502.5
57.5°	121.1	127.8	134.5	134.5	141.3	215.3	296.0	370.0	444.0	1439.6	2428.5
60°	127.8	134.5	141.3	148.0	154.7	228.7	309.4	383.4	457.4	1305.1	2152.7
62.5°	141.3	154.7	168.2	174.9	188.4	262.4	329.6	403.6	470.9	1069.6	1661.6
65°	161.5	174.9	181.6	195.1	201.8	269.1	343.1	410.4	477.6	888.0	1291.6
67.5°	168.2	181.6	188.4	201.8	208.5	275.8	343.1	410.4	477.6	753.4	1022.5
70°	168.2	181.6	195.1	201.8	215.3	282.5	343.1	410.4	470.9	652.5	834.2
72.5°	154.7	174.9	188.4	208.5	222.0	282.5	336.4	396.9	450.7	578.5	706.3
75°	148.0	174.9	195.1	222.0	242.2	282.5	329.6	370.0	410.4	504.5	598.7
77.5°	134.5	168.2	201.8	235.4	269.1	296.0	316.2	343.1	363.3	423.8	484.4
80°	127.8	161.5	195.1	228.7	262.4	275.8	282.5	296.0	302.7	309.4	316.2
82.5°	100.9	127.8	154.7	174.9	201.8	188.4	181.6	168.2	154.7	148.0	141.3
85°	47.1	53.8	53.8	60.5	60.5	60.5	53.8	53.8	47.1	40.4	33.6
87.5°	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	94.2	94.2	94.2	94.2	87.5	87.5	87.5	87.5	80.7	80.7	80.7
5°	107.6	107.6	107.6	107.6	100.9	100.9	100.9	100.9	94.2	94.2	94.2
7.5°	114.4	114.4	114.4	114.4	114.4	114.4	114.4	114.4	114.4	114.4	114.4
10°	127.8	127.8	127.8	134.5	134.5	134.5	134.5	134.5	134.5	134.5	134.5
12.5°	141.3	141.3	148.0	148.0	154.7	154.7	161.5	161.5	168.2	168.2	168.2
15°	154.7	161.5	168.2	174.9	174.9	181.6	188.4	195.1	201.8	208.5	215.3
17.5°	181.6	188.4	201.8	215.3	228.7	242.2	262.4	289.3	309.4	329.6	356.5
20°	201.8	222.0	262.4	309.4	349.8	390.2	491.1	592.0	692.9	793.8	894.7
22.5°	242.2	282.5	417.1	558.4	692.9	827.4	1143.6	1459.8	1769.2	2085.4	2367.9
25°	322.9	410.4	719.8	1029.2	1332.0	1641.4	2206.5	2778.3	3343.4	3908.5	4433.2
27.5°	444.0	605.4	1110.0	1621.2	2125.8	2630.3	3451.0	4278.4	5099.2	5926.6	6659.8
30°	618.9	881.3	1634.7	2394.9	3148.3	3901.7	4937.7	5980.4	7016.4	8052.4	8725.1
32.5°	840.9	1231.1	2186.3	3141.6	4096.8	5052.1	6195.7	7339.3	8476.2	9619.8	10332.9
35°	1076.3	1574.1	2724.5	3881.5	5031.9	6189.0	7393.1	8597.3	9801.4	11005.6	11880.1
37.5°	1210.9	1776.0	3141.6	4507.2	5866.0	7231.7	8550.2	9875.4	11193.9	12512.4	13575.3
40°	1338.7	2018.1	3592.3	5166.4	6740.6	8314.7	9855.2	11395.7	12936.3	14476.8	15842.4
42.5°	1527.1	2381.4	4217.9	6054.4	7884.2	9720.7	11745.6	13777.1	15802.0	17826.9	19925.7
45°	1917.2	3067.6	5449.0	7830.4	10205.0	12586.4	15458.9	18338.1	21210.6	24089.8	26780.7
47.5°	2859.0	4614.8	7864.0	11113.2	14362.4	17611.6	20921.3	24231.1	27540.8	30850.6	34052.7
50°	4426.4	7083.7	11146.8	15210.0	19266.5	23329.7	26632.7	29935.7	33232.0	36535.0	39716.9
52.5°	5899.7	9444.9	13810.8	18183.4	22549.3	26921.9	29848.2	32774.5	35700.8	38627.1	41708.1
55°	6404.2	10299.2	14718.9	19145.4	23565.1	27991.5	30810.2	33635.6	36454.3	39272.9	42468.3
57.5°	5960.2	9492.0	13945.3	18398.7	22845.3	27298.7	30446.9	33602.0	36750.3	39905.3	43329.4
60°	4991.5	7823.6	12499.0	17181.1	21856.4	26531.8	30083.7	33635.6	37187.5	40739.4	44156.8
62.5°	3955.5	6242.8	11193.9	16145.1	21096.2	26047.4	29659.9	33279.1	36891.5	40504.0	43127.6
65°	3033.9	4776.3	9646.7	14523.9	19394.3	24271.4	27231.4	30198.0	33158.0	36124.6	37941.0
67.5°	2253.6	3484.6	7742.9	12007.9	16266.2	20524.4	22704.0	24890.3	27069.9	29256.2	30668.9
70°	1661.6	2482.3	5381.7	8281.1	11173.7	14073.1	16071.1	18069.0	20060.3	22058.2	23524.7
72.5°	1150.3	1587.6	3323.2	5065.5	6801.1	8536.7	10561.6	12586.4	14604.6	16629.4	18297.8
75°	787.1	975.4	1789.4	2603.4	3417.4	4231.4	5765.1	7298.9	8832.7	10366.5	11247.7
77.5°	585.3	686.2	928.3	1177.2	1419.4	1661.6	1957.6	2253.6	2549.6	2845.6	3229.0
80°	322.9	322.9	356.5	383.4	417.1	444.0	524.7	612.2	692.9	780.3	888.0
82.5°	148.0	154.7	168.2	181.6	188.4	201.8	215.3	228.7	242.2	255.6	255.6
85°	40.4	47.1	47.1	40.4	40.4	33.6	33.6	40.4	40.4	40.4	40.4
87.5°	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	80.7	74.0	74.0	74.0	67.3	67.3	67.3	67.3	67.3	67.3	67.3
5°	94.2	94.2	94.2	94.2	87.5	87.5	87.5	87.5	87.5	80.7	80.7
7.5°	114.4	107.6	107.6	107.6	107.6	107.6	107.6	107.6	107.6	100.9	100.9
10°	134.5	134.5	134.5	134.5	134.5	134.5	134.5	134.5	134.5	127.8	127.8
12.5°	168.2	168.2	168.2	168.2	174.9	174.9	168.2	168.2	168.2	161.5	161.5
15°	222.0	228.7	235.4	235.4	242.2	242.2	242.2	235.4	235.4	228.7	222.0
17.5°	376.7	396.9	423.8	450.7	477.6	497.8	497.8	484.4	470.9	457.4	444.0
20°	1002.3	1103.2	1210.9	1318.5	1432.9	1513.6	1459.8	1419.4	1379.1	1332.0	1291.6
22.5°	2657.2	2939.8	3229.0	3430.8	3632.6	3773.9	3659.6	3437.6	3215.6	3000.3	2778.3
25°	4957.9	5475.9	6000.6	6215.9	6437.9	6599.3	6525.3	6189.0	5852.6	5523.0	5186.6
27.5°	7393.1	8119.6	8852.9	9041.2	9229.6	9370.9	9344.0	8906.7	8469.4	8032.2	7594.9
30°	9397.8	10070.5	10743.2	10931.6	11119.9	11247.7	11106.5	10669.2	10231.9	9794.7	9357.4
32.5°	11052.7	11765.7	12485.5	12734.4	12983.3	13151.5	12983.3	12458.6	11933.9	11415.9	10891.2
35°	12754.6	13622.4	14496.9	14813.1	15129.3	15331.1	15048.6	14402.8	13757.0	13117.9	12472.1
37.5°	14638.2	15694.4	16757.3	17187.8	17625.1	17927.8	17712.5	16905.3	16091.3	15284.0	14470.0
40°	17214.7	18580.3	19952.6	20726.3	21493.1	22038.0	21654.6	20719.5	19777.7	18842.7	17900.9
42.5°	22031.3	24130.2	26229.0	27339.0	28442.3	29242.8	28812.3	27661.9	26511.6	25361.2	24210.9
45°	29471.5	32155.6	34846.5	36467.7	38095.7	39293.1	38795.3	37349.0	35895.9	34449.6	33003.3
47.5°	37254.8	40456.9	43659.0	44950.6	46248.9	47258.0	47136.9	45334.1	43531.2	41735.1	39932.2
50°	42905.6	46087.5	49269.4	50379.4	51496.1	52323.5	52014.1	49720.1	47419.5	45125.5	42824.8
52.5°	44789.2	47863.5	50944.5	52269.7	53595.0	54583.9	54207.1	51623.9	49040.7	46464.2	43881.0
55°	45663.7	48859.1	52054.5	53669.0	55290.2	56474.2	55929.3	53097.2	50258.3	47426.2	44587.4
57.5°	46753.5	50177.6	53601.7	55370.9	57140.2	58418.3	57691.8	54758.8	51825.7	48899.4	45966.4
60°	47574.2	50984.8	54402.2	55821.6	57247.8	58243.4	57543.8	54691.5	51832.5	48980.2	46127.9
62.5°	45757.9	48381.4	51005.0	52061.2	53117.3	53884.2	53487.3	50783.0	48078.7	45374.4	42670.1
65°	39764.0	41580.3	43403.4	44116.5	44822.8	45367.7	45246.6	42966.1	40685.6	38411.9	36131.4
67.5°	32088.4	33501.1	34920.5	35929.5	36945.3	37732.4	37645.0	35566.3	33487.6	31408.9	29330.2
70°	24998.0	26464.5	27931.0	29202.4	30480.6	31469.5	31341.7	29411.0	27473.6	25542.9	23605.5
72.5°	19972.8	21641.1	23309.5	24036.0	24762.5	25273.8	24897.1	23437.3	21970.8	20511.0	19044.5
75°	12129.0	13003.5	13884.8	13878.0	13878.0	13797.3	13420.6	12586.4	11752.3	10918.1	10084.0
77.5°	3612.5	3995.9	4379.4	4749.3	5126.1	5408.6	5334.6	4897.3	4453.4	4016.1	3572.1
80°	995.6	1096.5	1204.2	1251.2	1298.3	1358.9	1513.6	1406.0	1298.3	1197.4	1089.8
82.5°	255.6	255.6	255.6	248.9	242.2	228.7	208.5	195.1	181.6	168.2	154.7
85°	40.4	33.6	33.6	33.6	26.9	26.9	26.9	26.9	20.2	20.2	13.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
2.5°	67.3	67.3	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	53.8
5°	80.7	80.7	74.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0	67.3
7.5°	100.9	100.9	94.2	94.2	94.2	94.2	87.5	87.5	87.5	87.5	80.7
10°	127.8	121.1	121.1	114.4	114.4	114.4	107.6	107.6	107.6	100.9	100.9
12.5°	161.5	154.7	154.7	148.0	141.3	141.3	134.5	127.8	121.1	121.1	114.4
15°	215.3	208.5	201.8	195.1	188.4	174.9	168.2	154.7	148.0	141.3	134.5
17.5°	410.4	376.7	343.1	309.4	282.5	255.6	228.7	201.8	188.4	174.9	161.5
20°	1143.6	988.9	840.9	692.9	598.7	504.5	410.4	316.2	275.8	242.2	201.8
22.5°	2475.6	2166.1	1863.4	1554.0	1305.1	1062.9	814.0	565.1	470.9	383.4	289.3
25°	4601.3	4009.4	3424.1	2832.1	2361.2	1890.3	1419.4	948.5	773.6	598.7	423.8
27.5°	6828.0	6061.1	5294.2	4527.4	3780.6	3027.2	2273.8	1527.1	1224.3	928.3	625.6
30°	8543.4	7729.5	6922.2	6108.2	5166.4	4224.6	3276.1	2334.3	1856.7	1379.1	894.7
32.5°	10016.7	9135.4	8260.9	7379.7	6289.9	5200.1	4110.3	3020.5	2421.8	1823.0	1217.6
35°	11476.5	10474.1	9478.5	8476.2	7305.7	6135.1	4964.6	3794.1	3033.9	2273.8	1506.9
37.5°	13252.4	12028.1	10810.5	9592.9	8388.7	7191.3	5987.1	4783.0	3814.3	2852.3	1883.6
40°	16346.9	14786.2	13232.2	11671.6	10265.6	8866.3	7460.4	6054.4	4836.8	3619.2	2394.9
42.5°	22253.3	20295.7	18344.9	16387.3	14443.1	12499.0	10548.1	8604.0	6868.4	5139.5	3403.9
45°	30494.0	27984.8	25482.3	22973.1	20578.3	18190.1	15795.3	13400.4	10763.4	8126.4	5482.6
47.5°	37187.5	34436.1	31691.5	28940.1	26282.9	23632.4	20975.2	18317.9	14940.9	11570.6	8193.6
50°	40208.0	37584.4	34967.6	32344.0	29680.1	27009.4	24338.7	21674.8	17800.0	13931.9	10057.0
52.5°	41223.8	38559.9	35902.6	33238.7	30594.9	27951.2	25307.4	22663.7	18634.1	14611.3	10581.8
55°	41782.1	38970.2	36165.0	33353.1	30507.5	27655.2	24802.9	21957.3	17948.0	13945.3	9936.0
57.5°	42912.3	39851.5	36797.3	33736.5	30494.0	27251.6	24002.4	20759.9	16804.3	12848.8	8893.3
60°	43120.8	40107.1	37100.1	34093.0	30507.5	26921.9	23329.7	19744.1	15815.5	11893.5	7964.9
62.5°	40154.2	37638.2	35129.0	32613.1	29020.8	25428.5	21829.5	18237.2	14476.8	10716.3	6949.1
65°	33958.5	31785.6	29619.5	27446.6	24513.6	21587.3	18654.3	15721.3	12364.4	9014.3	5657.5
67.5°	27204.5	25078.7	22959.7	20833.9	18627.4	16427.6	14221.1	12014.6	9424.7	6834.8	4244.8
70°	21567.1	19522.1	17483.8	15438.7	13487.9	11530.3	9572.7	7621.8	6014.0	4413.0	2805.2
72.5°	17093.6	15136.0	13185.2	11227.6	9458.3	7689.1	5919.9	4150.6	3350.1	2556.3	1755.8
75°	9068.2	8052.4	7043.3	6027.5	5031.9	4029.5	3027.2	2031.6	1715.4	1399.2	1076.3
77.5°	3128.1	2684.1	2246.9	1802.9	1500.1	1197.4	894.7	592.0	558.4	531.4	497.8
80°	948.5	807.3	666.0	524.7	464.2	403.6	343.1	282.5	262.4	242.2	215.3
82.5°	148.0	134.5	127.8	114.4	107.6	107.6	100.9	94.2	80.7	74.0	60.5
85°	13.5	6.7	6.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	60.5	60.5
2.5°	53.8	53.8
5°	67.3	67.3
7.5°	80.7	80.7
10°	94.2	94.2
12.5°	107.6	107.6
15°	127.8	121.1
17.5°	148.0	141.3
20°	161.5	148.0
22.5°	195.1	168.2
25°	248.9	208.5
27.5°	322.9	255.6
30°	417.1	322.9
32.5°	618.9	450.7
35°	746.7	544.9
37.5°	914.9	632.3
40°	1177.2	766.9
42.5°	1668.3	1042.7
45°	2845.6	1728.9
47.5°	4823.3	2946.5
50°	6182.2	3780.6
52.5°	6558.9	4009.4
55°	5933.3	3679.7
57.5°	4937.7	3128.1
60°	4043.0	2576.5
62.5°	3188.7	2038.3
65°	2300.7	1540.5
67.5°	1654.9	1184.0
70°	1204.2	928.3
72.5°	955.3	773.6
75°	760.2	645.8
77.5°	470.9	430.5
80°	195.1	181.6
82.5°	47.1	40.4
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066546

CATALOG NUMBER: NVN-SA6B-735-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-5

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-735-U-5WQ

Data in this report applies to families of products including GSS-SB1A-735-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-735-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3369
 CIE u' : 0.2386
 CIE v' : 0.5156
 Duv: 0.0013
 CIE x: 0.4143
 CIE y: 0.3980
 CIE z: 0.1877
 Peak Wavelength (nm): 590
 Dominant Wavelength (nm): 580
 Purity: 43.80166
 R_f: 71.4
 R_g: 96

CRI (Ra): 70.1
 R1: 66.6
 R2: 77.6
 R3: 88.5
 R4: 69.5
 R5: 66.4
 R6: 69.6
 R7: 77.5
 R8: 44.9
 R9: -40.2
 R10: 49.1
 R11: 66.3
 R12: 45.7
 R13: 68.0
 R14: 93.4
 R15: 57.6



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-5

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-5

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-5

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.29

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.36


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	119	NR	620	778	NR	750	19	NR	880	1	NR
365	0	NR	495	173	NR	625	711	NR	755	16	NR	885	0	NR
370	0	NR	500	239	NR	630	648	NR	760	14	NR	890	0	NR
375	0	NR	505	313	NR	635	582	NR	765	12	NR	895	0	NR
380	0	NR	510	383	NR	640	520	NR	770	11	NR	900	0	NR
385	0	NR	515	448	NR	645	460	NR	775	9	NR	905	0	NR
390	2	NR	520	500	NR	650	406	NR	780	8	NR	910	0	NR
395	4	NR	525	539	NR	655	355	NR	785	7	NR	915	0	NR
400	6	NR	530	575	NR	660	309	NR	790	6	NR	920	0	NR
405	11	NR	535	606	NR	665	269	NR	795	5	NR	925	0	NR
410	22	NR	540	633	NR	670	231	NR	800	4	NR	930	0	NR
415	45	NR	545	666	NR	675	199	NR	805	4	NR	935	0	NR
420	96	NR	550	701	NR	680	171	NR	810	3	NR	940	0	NR
425	193	NR	555	743	NR	685	147	NR	815	3	NR	945	0	NR
430	341	NR	560	788	NR	690	126	NR	820	3	NR	950	0	NR
435	547	NR	565	837	NR	695	107	NR	825	2	NR	955	0	NR
440	799	NR	570	887	NR	700	92	NR	830	2	NR	960	0	NR
445	831	NR	575	931	NR	705	78	NR	835	2	NR	965	0	NR
450	461	NR	580	967	NR	710	67	NR	840	2	NR	970	0	NR
455	256	NR	585	990	NR	715	57	NR	845	1	NR	975	0	NR
460	176	NR	590	1000	NR	720	49	NR	850	1	NR	980	0	NR
465	107	NR	595	994	NR	725	42	NR	855	1	NR	985	0	NR
470	74	NR	600	973	NR	730	36	NR	860	1	NR	990	0	NR
475	67	NR	605	938	NR	735	31	NR	865	1	NR	995	0	NR
480	68	NR	610	892	NR	740	26	NR	870	1	NR	1000	0	NR
485	84	NR	615	838	NR	745	22	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-5



TM-30-18

Summary

$R_f = 71.4$
 $R_g = 96$
 CIE $R_a = 70.1$
 $R_g = -40.2$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 57	CES51 = 84	CES76 = 50
CES02 = 62	CES27 = 80	CES52 = 86	CES77 = 74
CES03 = 31	CES28 = 81	CES53 = 72	CES78 = 54
CES04 = 70	CES29 = 50	CES54 = 79	CES79 = 81
CES05 = 48	CES30 = 55	CES55 = 78	CES80 = 79
CES06 = 51	CES31 = 56	CES56 = 67	CES81 = 74
CES07 = 40	CES32 = 54	CES57 = 65	CES82 = 91
CES08 = 39	CES33 = 60	CES58 = 68	CES83 = 86
CES09 = 29	CES34 = 69	CES59 = 85	CES84 = 89
CES10 = 75	CES35 = 83	CES60 = 91	CES85 = 83
CES11 = 58	CES36 = 88	CES61 = 85	CES86 = 66
CES12 = 64	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 43	CES38 = 64	CES63 = 71	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 70	CES89 = 68
CES15 = 71	CES40 = 86	CES65 = 64	CES90 = 72
CES16 = 47	CES41 = 81	CES66 = 65	CES91 = 95
CES17 = 50	CES42 = 79	CES67 = 63	CES92 = 62
CES18 = 56	CES43 = 71	CES68 = 69	CES93 = 78
CES19 = 72	CES44 = 98	CES69 = 80	CES94 = 51
CES20 = 65	CES45 = 80	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 75	CES71 = 58	CES96 = 76
CES22 = 79	CES47 = 71	CES72 = 85	CES97 = 82
CES23 = 92	CES48 = 61	CES73 = 51	CES98 = 72
CES24 = 91	CES49 = 74	CES74 = 94	CES99 = 60
CES25 = 72	CES50 = 83	CES75 = 57	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)