

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066437

Luminaire Tested: **NVN-SA3A-740-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066437
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA3A-740-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 615mA 3xLight Square PACKAGE
70CRI 4000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 4000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 9262.6 lumens
Efficiency: N/A
Efficacy: 113.0 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 82
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 1.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	55.1	0.0	55.1
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	9207.5	0.0	9207.5
	% Fixture	99.4	0.0	99.4
Total	Lumens	9262.6	0.0	9262.6
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2.7	0.0
10°-20°	13.6	0.1
20°-30°	172.9	1.9
30°-40°	582.6	6.3
40°-50°	1759.6	19.0
50°-60°	3104.5	33.5
60°-70°	2735.1	29.5
70°-80°	870.6	9.4
80°-90°	21.0	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	9262.6	100.0
0°-180°	9262.6	100.0



REPORT NUMBER: P1066437


CATALOG NUMBER: NVN-SA3A-740-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	180.9	2.0			
FM	(30°-60°)	5425.4	58.6			
FH	(60°-80°)	3584.1	38.7			G2/5000
FVH	(80°-90°)	17.0	0.2			G1/100
BL	(0°-30°)	8.3	0.1	B0/110		
BM	(30°-60°)	21.3	0.2	B0/220		
BH	(60°-80°)	21.6	0.2	B0/110		G0/110
BVH	(80°-90°)	3.9	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	23.2	23.2	23.2	23.2	23.2	23.2	23.2	23.2	23.2	23.2	20.3
5°	29.0	29.0	29.0	26.1	26.1	26.1	23.2	23.2	23.2	23.2	23.2
7.5°	34.9	32.0	32.0	29.0	29.0	29.0	26.1	26.1	26.1	26.1	23.2
10°	40.7	37.8	37.8	34.9	34.9	32.0	32.0	29.0	29.0	26.1	26.1
12.5°	46.5	43.6	40.7	37.8	37.8	34.9	34.9	32.0	32.0	29.0	29.0
15°	52.3	49.4	46.5	43.6	40.7	40.7	37.8	34.9	32.0	32.0	29.0
17.5°	61.0	55.2	52.3	46.5	43.6	40.7	37.8	34.9	34.9	32.0	32.0
20°	63.9	58.1	55.2	49.4	46.5	43.6	40.7	37.8	34.9	34.9	32.0
22.5°	75.5	63.9	61.0	55.2	52.3	49.4	43.6	40.7	37.8	34.9	32.0
25°	93.0	75.5	66.8	58.1	55.2	49.4	46.5	40.7	37.8	34.9	32.0
27.5°	113.3	84.2	75.5	63.9	58.1	52.3	46.5	40.7	37.8	34.9	32.0
30°	139.4	98.8	84.2	69.7	63.9	58.1	49.4	43.6	40.7	37.8	32.0
32.5°	194.6	122.0	98.8	75.5	66.8	61.0	52.3	43.6	40.7	37.8	32.0
35°	235.3	148.1	119.1	87.1	75.5	66.8	55.2	43.6	40.7	37.8	32.0
37.5°	273.0	151.0	122.0	93.0	81.3	69.7	55.2	43.6	40.7	37.8	32.0
40°	334.0	156.9	122.0	87.1	78.4	66.8	58.1	46.5	43.6	37.8	34.9
42.5°	450.2	180.1	130.7	81.3	72.6	66.8	58.1	49.4	43.6	40.7	34.9
45°	749.4	267.2	177.2	84.2	75.5	66.8	58.1	49.4	46.5	40.7	37.8
47.5°	1275.2	464.8	276.0	87.1	78.4	66.8	58.1	46.5	43.6	40.7	34.9
50°	1632.5	595.5	348.6	101.7	87.1	75.5	61.0	46.5	43.6	40.7	37.8
52.5°	1734.1	633.2	377.6	119.1	101.7	84.2	63.9	46.5	43.6	43.6	40.7
55°	1588.9	615.8	377.6	139.4	116.2	95.9	72.6	49.4	46.5	46.5	43.6
57.5°	1350.7	569.3	360.2	151.0	127.8	101.7	78.4	52.3	49.4	49.4	46.5
60°	1112.5	479.3	325.3	168.5	142.3	116.2	90.0	63.9	61.0	58.1	52.3
62.5°	883.0	386.3	284.7	180.1	154.0	124.9	98.8	69.7	66.8	63.9	61.0
65°	665.2	337.0	264.3	188.8	159.8	130.7	101.7	72.6	69.7	69.7	66.8
67.5°	511.2	307.9	252.7	194.6	165.6	136.5	107.5	78.4	75.5	72.6	69.7
70°	403.8	284.7	238.2	191.7	165.6	139.4	110.4	84.2	78.4	75.5	69.7
72.5°	337.0	258.5	220.8	183.0	162.7	142.3	122.0	101.7	90.0	81.3	69.7
75°	281.8	232.4	200.4	165.6	151.0	139.4	124.9	110.4	95.9	81.3	66.8
77.5°	185.9	168.5	154.0	139.4	130.7	122.0	110.4	101.7	87.1	75.5	61.0
80°	78.4	72.6	75.5	75.5	75.5	75.5	72.6	72.6	63.9	55.2	43.6
82.5°	17.4	14.5	17.4	17.4	17.4	17.4	14.5	14.5	14.5	11.6	11.6
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3
5°	23.2	23.2	23.2	20.3	20.3	20.3	20.3	20.3	20.3	20.3	20.3
7.5°	23.2	23.2	23.2	20.3	20.3	20.3	20.3	17.4	17.4	17.4	17.4
10°	23.2	23.2	23.2	20.3	20.3	20.3	20.3	17.4	17.4	17.4	17.4
12.5°	26.1	26.1	23.2	23.2	20.3	20.3	20.3	17.4	17.4	17.4	17.4
15°	26.1	26.1	23.2	23.2	20.3	20.3	20.3	17.4	17.4	17.4	17.4
17.5°	29.0	26.1	26.1	23.2	20.3	20.3	20.3	17.4	17.4	17.4	17.4
20°	29.0	26.1	26.1	23.2	20.3	20.3	20.3	17.4	17.4	17.4	17.4
22.5°	29.0	26.1	26.1	23.2	20.3	20.3	17.4	17.4	14.5	14.5	11.6
25°	29.0	26.1	26.1	23.2	20.3	20.3	17.4	17.4	14.5	11.6	11.6
27.5°	29.0	26.1	26.1	23.2	20.3	17.4	17.4	14.5	11.6	8.7	8.7
30°	29.0	26.1	26.1	23.2	20.3	17.4	14.5	11.6	8.7	8.7	5.8
32.5°	29.0	26.1	23.2	20.3	17.4	14.5	14.5	11.6	8.7	5.8	5.8
35°	29.0	26.1	23.2	20.3	17.4	14.5	14.5	11.6	8.7	5.8	5.8
37.5°	29.0	26.1	23.2	20.3	17.4	14.5	11.6	8.7	5.8	5.8	2.9
40°	29.0	26.1	23.2	20.3	17.4	14.5	11.6	8.7	5.8	5.8	2.9
42.5°	29.0	26.1	23.2	20.3	17.4	14.5	11.6	8.7	5.8	5.8	2.9
45°	32.0	29.0	26.1	20.3	17.4	14.5	14.5	11.6	8.7	5.8	5.8
47.5°	32.0	29.0	26.1	20.3	17.4	14.5	14.5	11.6	8.7	5.8	5.8
50°	34.9	32.0	29.0	23.2	20.3	17.4	14.5	8.7	5.8	5.8	2.9
52.5°	37.8	34.9	32.0	29.0	26.1	20.3	14.5	8.7	2.9	2.9	2.9
55°	40.7	37.8	37.8	34.9	32.0	23.2	17.4	8.7	0.0	0.0	0.0
57.5°	43.6	40.7	40.7	37.8	34.9	26.1	17.4	8.7	0.0	0.0	0.0
60°	49.4	46.5	43.6	37.8	34.9	26.1	17.4	8.7	0.0	0.0	0.0
62.5°	58.1	52.3	43.6	37.8	29.0	23.2	14.5	8.7	0.0	0.0	0.0
65°	63.9	55.2	46.5	34.9	26.1	20.3	14.5	5.8	0.0	0.0	0.0
67.5°	66.8	55.2	46.5	34.9	23.2	17.4	11.6	5.8	0.0	0.0	0.0
70°	63.9	52.3	43.6	32.0	20.3	14.5	11.6	5.8	0.0	0.0	0.0
72.5°	58.1	49.4	37.8	29.0	17.4	14.5	8.7	5.8	0.0	0.0	0.0
75°	52.3	43.6	32.0	23.2	11.6	8.7	5.8	2.9	0.0	0.0	0.0
77.5°	46.5	37.8	26.1	17.4	5.8	5.8	2.9	2.9	0.0	0.0	0.0
80°	34.9	26.1	17.4	8.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	8.7	5.8	5.8	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4
5°	17.4	17.4	17.4	17.4	14.5	14.5	14.5	14.5	14.5	14.5	14.5
7.5°	17.4	17.4	17.4	17.4	14.5	14.5	14.5	14.5	11.6	11.6	11.6
10°	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	11.6	11.6	11.6
12.5°	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	11.6	11.6	11.6
15°	14.5	14.5	14.5	14.5	14.5	14.5	14.5	11.6	11.6	8.7	8.7
17.5°	14.5	14.5	14.5	14.5	11.6	11.6	11.6	8.7	8.7	5.8	5.8
20°	14.5	14.5	14.5	11.6	11.6	8.7	8.7	5.8	5.8	2.9	2.9
22.5°	11.6	8.7	8.7	5.8	5.8	2.9	2.9	2.9	0.0	0.0	0.0
25°	8.7	5.8	5.8	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	5.8	2.9	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	5.8	2.9	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	17.4	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5
5°	14.5	14.5	14.5	14.5	11.6	11.6	11.6	11.6	11.6	11.6	11.6
7.5°	11.6	11.6	11.6	11.6	11.6	11.6	8.7	8.7	8.7	8.7	8.7
10°	11.6	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	5.8	5.8
12.5°	11.6	8.7	8.7	8.7	5.8	5.8	5.8	5.8	5.8	2.9	2.9
15°	8.7	5.8	5.8	5.8	2.9	2.9	2.9	2.9	2.9	0.0	0.0
17.5°	5.8	2.9	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	17.4	17.4
5°	11.6	11.6	11.6	11.6	11.6	11.6	11.6	11.6	11.6	11.6	11.6
7.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
10°	5.8	5.8	5.8	5.8	5.8	5.8	2.9	2.9	2.9	2.9	2.9
12.5°	2.9	2.9	2.9	2.9	2.9	2.9	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	17.4	17.4	17.4	17.4	17.4	20.3	20.3	23.2	23.2	26.1	26.1
5°	11.6	11.6	14.5	14.5	14.5	14.5	17.4	17.4	17.4	20.3	20.3
7.5°	8.7	8.7	8.7	8.7	8.7	11.6	11.6	14.5	14.5	17.4	17.4
10°	2.9	2.9	5.8	5.8	5.8	5.8	8.7	8.7	8.7	11.6	14.5
12.5°	0.0	0.0	2.9	2.9	2.9	2.9	5.8	5.8	5.8	8.7	11.6
15°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	5.8	8.7
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	5.8
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	29.0	29.0	32.0	32.0	34.9	34.9	37.8	37.8	37.8	37.8	37.8
5°	23.2	23.2	26.1	29.0	29.0	32.0	34.9	34.9	34.9	34.9	34.9
7.5°	20.3	20.3	23.2	26.1	26.1	29.0	32.0	32.0	34.9	34.9	34.9
10°	14.5	17.4	20.3	23.2	23.2	26.1	29.0	29.0	32.0	32.0	32.0
12.5°	11.6	14.5	17.4	20.3	20.3	23.2	26.1	26.1	29.0	29.0	32.0
15°	8.7	11.6	14.5	17.4	17.4	20.3	23.2	23.2	26.1	29.0	32.0
17.5°	5.8	8.7	11.6	14.5	14.5	17.4	20.3	23.2	26.1	26.1	29.0
20°	5.8	5.8	8.7	11.6	11.6	14.5	17.4	20.3	23.2	23.2	26.1
22.5°	2.9	2.9	5.8	8.7	8.7	11.6	14.5	17.4	20.3	20.3	23.2
25°	0.0	0.0	2.9	5.8	5.8	8.7	11.6	11.6	14.5	14.5	17.4
27.5°	0.0	0.0	2.9	2.9	5.8	5.8	8.7	8.7	11.6	11.6	14.5
30°	0.0	0.0	2.9	2.9	5.8	5.8	8.7	8.7	11.6	11.6	11.6
32.5°	0.0	0.0	0.0	2.9	2.9	2.9	5.8	5.8	8.7	8.7	11.6
35°	0.0	0.0	0.0	2.9	2.9	2.9	5.8	5.8	8.7	8.7	8.7
37.5°	0.0	0.0	0.0	2.9	2.9	2.9	5.8	5.8	5.8	5.8	8.7
40°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
45°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
50°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
55°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
75°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
80°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	5.8
85°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	40.7	40.7	40.7	40.7	40.7	40.7	40.7	40.7	40.7	37.8	37.8
5°	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	34.9	34.9
7.5°	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	34.9	34.9
10°	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9
12.5°	32.0	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9
15°	32.0	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9
17.5°	29.0	32.0	32.0	32.0	34.9	34.9	34.9	34.9	34.9	34.9	34.9
20°	26.1	29.0	29.0	29.0	32.0	32.0	32.0	32.0	34.9	34.9	34.9
22.5°	23.2	26.1	26.1	26.1	29.0	29.0	29.0	29.0	32.0	32.0	32.0
25°	20.3	20.3	23.2	23.2	26.1	26.1	26.1	26.1	26.1	26.1	26.1
27.5°	14.5	17.4	17.4	17.4	20.3	20.3	20.3	20.3	23.2	23.2	23.2
30°	14.5	14.5	14.5	14.5	17.4	17.4	17.4	17.4	20.3	20.3	20.3
32.5°	11.6	14.5	14.5	14.5	17.4	17.4	17.4	17.4	20.3	20.3	20.3
35°	11.6	11.6	11.6	11.6	14.5	14.5	14.5	14.5	17.4	17.4	17.4
37.5°	8.7	11.6	11.6	11.6	14.5	14.5	14.5	14.5	17.4	17.4	17.4
40°	8.7	8.7	8.7	8.7	11.6	11.6	11.6	11.6	14.5	14.5	14.5
42.5°	8.7	8.7	8.7	8.7	11.6	11.6	11.6	11.6	14.5	14.5	14.5
45°	8.7	8.7	8.7	8.7	11.6	11.6	11.6	11.6	14.5	14.5	14.5
47.5°	8.7	8.7	8.7	8.7	11.6	11.6	11.6	11.6	14.5	14.5	14.5
50°	8.7	8.7	8.7	8.7	11.6	11.6	11.6	11.6	14.5	14.5	14.5
52.5°	5.8	5.8	5.8	5.8	8.7	8.7	8.7	8.7	11.6	11.6	11.6
55°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	8.7	8.7	8.7
57.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	8.7	8.7	8.7
60°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
62.5°	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9
65°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	2.9	2.9
67.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
70°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
72.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
75°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
77.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
80°	8.7	8.7	8.7	8.7	8.7	5.8	5.8	5.8	5.8	5.8	5.8
82.5°	5.8	8.7	8.7	8.7	8.7	5.8	5.8	5.8	5.8	5.8	5.8
85°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
87.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	37.8	37.8	34.9	34.9	34.9	34.9	34.9	34.9	34.9	37.8	37.8
5°	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	37.8	37.8
7.5°	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	34.9	37.8	37.8
10°	34.9	34.9	34.9	34.9	32.0	32.0	34.9	34.9	34.9	37.8	37.8
12.5°	34.9	34.9	34.9	34.9	32.0	32.0	34.9	34.9	37.8	37.8	40.7
15°	34.9	34.9	32.0	32.0	32.0	32.0	34.9	34.9	37.8	37.8	40.7
17.5°	34.9	34.9	32.0	32.0	32.0	32.0	34.9	34.9	37.8	37.8	40.7
20°	34.9	34.9	32.0	32.0	32.0	32.0	32.0	32.0	34.9	37.8	37.8
22.5°	32.0	32.0	32.0	32.0	29.0	29.0	32.0	32.0	34.9	37.8	37.8
25°	26.1	29.0	29.0	29.0	29.0	29.0	32.0	32.0	34.9	37.8	37.8
27.5°	23.2	26.1	26.1	26.1	26.1	29.0	29.0	32.0	34.9	37.8	37.8
30°	20.3	23.2	23.2	23.2	26.1	29.0	29.0	32.0	34.9	37.8	37.8
32.5°	20.3	23.2	23.2	23.2	26.1	26.1	29.0	29.0	32.0	34.9	37.8
35°	20.3	20.3	23.2	23.2	23.2	26.1	26.1	29.0	32.0	34.9	37.8
37.5°	20.3	20.3	23.2	23.2	23.2	26.1	26.1	29.0	32.0	34.9	37.8
40°	17.4	20.3	20.3	23.2	23.2	26.1	26.1	29.0	32.0	37.8	40.7
42.5°	17.4	17.4	20.3	20.3	23.2	26.1	26.1	29.0	32.0	37.8	40.7
45°	17.4	20.3	20.3	23.2	26.1	29.0	29.0	32.0	34.9	37.8	40.7
47.5°	17.4	20.3	20.3	23.2	29.0	29.0	32.0	32.0	34.9	37.8	40.7
50°	17.4	20.3	20.3	23.2	32.0	32.0	32.0	32.0	34.9	37.8	40.7
52.5°	14.5	17.4	17.4	20.3	26.1	29.0	32.0	34.9	37.8	40.7	43.6
55°	11.6	14.5	14.5	17.4	23.2	26.1	32.0	37.8	40.7	43.6	46.5
57.5°	11.6	11.6	14.5	14.5	20.3	26.1	34.9	40.7	43.6	46.5	49.4
60°	8.7	8.7	11.6	11.6	17.4	23.2	32.0	40.7	43.6	49.4	52.3
62.5°	5.8	8.7	8.7	11.6	14.5	23.2	32.0	40.7	46.5	52.3	55.2
65°	5.8	5.8	8.7	8.7	14.5	20.3	29.0	34.9	43.6	52.3	61.0
67.5°	8.7	8.7	11.6	11.6	14.5	20.3	29.0	34.9	43.6	55.2	63.9
70°	8.7	8.7	11.6	11.6	17.4	23.2	29.0	34.9	43.6	55.2	63.9
72.5°	8.7	8.7	11.6	11.6	17.4	20.3	26.1	32.0	40.7	49.4	58.1
75°	5.8	8.7	8.7	8.7	14.5	17.4	23.2	29.0	37.8	46.5	55.2
77.5°	5.8	5.8	5.8	5.8	11.6	14.5	20.3	23.2	32.0	40.7	49.4
80°	5.8	5.8	5.8	5.8	8.7	11.6	17.4	20.3	29.0	37.8	46.5
82.5°	5.8	5.8	2.9	2.9	5.8	8.7	11.6	14.5	23.2	29.0	37.8
85°	5.8	5.8	2.9	2.9	2.9	5.8	5.8	8.7	11.6	14.5	17.4
87.5°	5.8	5.8	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	37.8	37.8	40.7	40.7	40.7	40.7	40.7	40.7	40.7	40.7	40.7
5°	37.8	40.7	40.7	43.6	43.6	43.6	46.5	46.5	46.5	46.5	46.5
7.5°	37.8	40.7	40.7	43.6	43.6	43.6	46.5	46.5	46.5	49.4	49.4
10°	37.8	40.7	40.7	43.6	43.6	46.5	49.4	49.4	52.3	52.3	52.3
12.5°	40.7	43.6	43.6	46.5	46.5	49.4	52.3	52.3	55.2	58.1	58.1
15°	40.7	43.6	46.5	46.5	49.4	52.3	55.2	55.2	58.1	61.0	63.9
17.5°	40.7	43.6	46.5	46.5	49.4	52.3	58.1	61.0	63.9	69.7	72.6
20°	40.7	43.6	46.5	46.5	49.4	55.2	58.1	63.9	66.8	72.6	78.4
22.5°	40.7	43.6	46.5	49.4	52.3	58.1	63.9	66.8	72.6	81.3	87.1
25°	40.7	43.6	46.5	49.4	52.3	58.1	63.9	69.7	75.5	87.1	98.8
27.5°	40.7	43.6	49.4	52.3	55.2	61.0	69.7	75.5	81.3	101.7	122.0
30°	40.7	43.6	49.4	52.3	55.2	63.9	72.6	78.4	87.1	122.0	154.0
32.5°	40.7	46.5	49.4	55.2	58.1	66.8	78.4	87.1	95.9	145.2	191.7
35°	40.7	46.5	49.4	55.2	58.1	69.7	81.3	93.0	104.6	177.2	249.8
37.5°	40.7	46.5	49.4	55.2	58.1	75.5	93.0	110.4	127.8	203.3	278.9
40°	43.6	49.4	52.3	58.1	61.0	78.4	95.9	113.3	130.7	206.2	281.8
42.5°	43.6	49.4	52.3	58.1	61.0	75.5	93.0	107.5	122.0	206.2	290.5
45°	43.6	49.4	55.2	58.1	63.9	78.4	93.0	104.6	119.1	226.6	331.1
47.5°	43.6	49.4	55.2	58.1	63.9	78.4	93.0	107.5	122.0	299.2	473.5
50°	43.6	49.4	55.2	58.1	63.9	81.3	98.8	116.2	133.6	447.3	761.0
52.5°	46.5	49.4	55.2	58.1	61.0	81.3	101.7	122.0	142.3	580.9	1016.7
55°	49.4	52.3	55.2	58.1	61.0	87.1	113.3	139.4	165.6	624.5	1080.6
57.5°	52.3	55.2	58.1	58.1	61.0	93.0	127.8	159.8	191.7	621.6	1048.6
60°	55.2	58.1	61.0	63.9	66.8	98.8	133.6	165.6	197.5	563.5	929.5
62.5°	61.0	66.8	72.6	75.5	81.3	113.3	142.3	174.3	203.3	461.9	717.5
65°	69.7	75.5	78.4	84.2	87.1	116.2	148.1	177.2	206.2	383.4	557.7
67.5°	72.6	78.4	81.3	87.1	90.0	119.1	148.1	177.2	206.2	325.3	441.5
70°	72.6	78.4	84.2	87.1	93.0	122.0	148.1	177.2	203.3	281.8	360.2
72.5°	66.8	75.5	81.3	90.0	95.9	122.0	145.2	171.4	194.6	249.8	305.0
75°	63.9	75.5	84.2	95.9	104.6	122.0	142.3	159.8	177.2	217.9	258.5
77.5°	58.1	72.6	87.1	101.7	116.2	127.8	136.5	148.1	156.9	183.0	209.1
80°	55.2	69.7	84.2	98.8	113.3	119.1	122.0	127.8	130.7	133.6	136.5
82.5°	43.6	55.2	66.8	75.5	87.1	81.3	78.4	72.6	66.8	63.9	61.0
85°	20.3	23.2	23.2	26.1	26.1	26.1	23.2	23.2	20.3	17.4	14.5
87.5°	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	40.7	40.7	40.7	40.7	37.8	37.8	37.8	37.8	34.9	34.9	34.9
5°	46.5	46.5	46.5	46.5	43.6	43.6	43.6	43.6	40.7	40.7	40.7
7.5°	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4
10°	55.2	55.2	55.2	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1
12.5°	61.0	61.0	63.9	63.9	66.8	66.8	69.7	69.7	72.6	72.6	72.6
15°	66.8	69.7	72.6	75.5	75.5	78.4	81.3	84.2	87.1	90.0	93.0
17.5°	78.4	81.3	87.1	93.0	98.8	104.6	113.3	124.9	133.6	142.3	154.0
20°	87.1	95.9	113.3	133.6	151.0	168.5	212.0	255.6	299.2	342.8	386.3
22.5°	104.6	122.0	180.1	241.1	299.2	357.3	493.8	630.3	763.9	900.5	1022.5
25°	139.4	177.2	310.8	444.4	575.1	708.8	952.8	1199.7	1443.7	1687.7	1914.2
27.5°	191.7	261.4	479.3	700.0	917.9	1135.8	1490.1	1847.4	2201.8	2559.1	2875.7
30°	267.2	380.5	705.9	1034.1	1359.4	1684.8	2132.1	2582.3	3029.6	3477.0	3767.5
32.5°	363.1	531.6	944.0	1356.5	1769.0	2181.5	2675.3	3169.1	3660.0	4153.8	4461.7
35°	464.8	679.7	1176.4	1676.0	2172.7	2672.4	3192.3	3712.3	4232.2	4752.2	5129.8
37.5°	522.9	766.9	1356.5	1946.2	2532.9	3122.6	3691.9	4264.2	4833.5	5402.8	5861.8
40°	578.0	871.4	1551.1	2230.8	2910.6	3590.3	4255.4	4920.6	5585.8	6251.0	6840.7
42.5°	659.4	1028.3	1821.3	2614.3	3404.4	4197.4	5071.7	5948.9	6823.2	7697.6	8603.9
45°	827.9	1324.6	2352.8	3381.1	4406.5	5434.8	6675.1	7918.3	9158.7	10401.9	11563.8
47.5°	1234.5	1992.7	3395.6	4798.6	6201.6	7604.6	9033.8	10462.9	11892.0	13321.2	14703.8
50°	1911.3	3058.7	4813.2	6567.6	8319.2	10073.7	11499.9	12926.1	14349.4	15775.7	17149.6
52.5°	2547.5	4078.3	5963.4	7851.5	9736.7	11624.8	12888.3	14151.9	15415.5	16679.0	18009.4
55°	2765.3	4447.2	6355.6	8266.9	10175.3	12086.6	13303.7	14523.7	15740.8	16957.9	18337.6
57.5°	2573.6	4098.6	6021.5	7944.5	9864.5	11787.4	13146.9	14509.2	15868.6	17230.9	18709.5
60°	2155.3	3378.2	5397.0	7418.7	9437.5	11456.3	12990.0	14523.7	16057.4	17591.1	19066.7
62.5°	1708.0	2695.6	4833.5	6971.4	9109.3	11247.2	12807.0	14369.8	15929.6	17489.5	18622.3
65°	1310.0	2062.4	4165.4	6271.3	8374.4	10480.3	11758.4	13039.4	14317.5	15598.5	16382.8
67.5°	973.1	1504.7	3343.4	5185.0	7023.7	8862.4	9803.5	10747.6	11688.7	12632.7	13242.7
70°	717.5	1071.9	2323.8	3575.7	4824.8	6076.7	6939.4	7802.1	8661.9	9524.7	10157.9
72.5°	496.7	685.5	1434.9	2187.3	2936.7	3686.1	4560.4	5434.8	6306.2	7180.5	7900.9
75°	339.9	421.2	772.7	1124.1	1475.6	1827.1	2489.4	3151.6	3813.9	4476.2	4856.7
77.5°	252.7	296.3	400.9	508.3	612.9	717.5	845.3	973.1	1100.9	1228.7	1394.3
80°	139.4	139.4	154.0	165.6	180.1	191.7	226.6	264.3	299.2	337.0	383.4
82.5°	63.9	66.8	72.6	78.4	81.3	87.1	93.0	98.8	104.6	110.4	110.4
85°	17.4	20.3	20.3	17.4	17.4	14.5	14.5	17.4	17.4	17.4	17.4
87.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	34.9	32.0	32.0	32.0	29.0	29.0	29.0	29.0	29.0	29.0	29.0
5°	40.7	40.7	40.7	40.7	37.8	37.8	37.8	37.8	37.8	34.9	34.9
7.5°	49.4	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5	43.6	43.6
10°	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	55.2	55.2
12.5°	72.6	72.6	72.6	72.6	75.5	75.5	72.6	72.6	72.6	69.7	69.7
15°	95.9	98.8	101.7	101.7	104.6	104.6	104.6	101.7	101.7	98.8	95.9
17.5°	162.7	171.4	183.0	194.6	206.2	215.0	215.0	209.1	203.3	197.5	191.7
20°	432.8	476.4	522.9	569.3	618.7	653.6	630.3	612.9	595.5	575.1	557.7
22.5°	1147.4	1269.4	1394.3	1481.4	1568.6	1629.6	1580.2	1484.3	1388.5	1295.5	1199.7
25°	2140.8	2364.5	2591.0	2684.0	2779.8	2849.6	2817.6	2672.4	2527.1	2384.8	2239.6
27.5°	3192.3	3506.0	3822.6	3904.0	3985.3	4046.3	4034.7	3845.9	3657.1	3468.3	3279.5
30°	4057.9	4348.4	4638.9	4720.2	4801.5	4856.7	4795.7	4606.9	4418.1	4229.3	4040.5
32.5°	4772.5	5080.4	5391.2	5498.7	5606.2	5678.8	5606.2	5379.6	5153.0	4929.3	4702.8
35°	5507.4	5882.1	6259.7	6396.2	6532.8	6619.9	6497.9	6219.1	5940.2	5664.2	5385.4
37.5°	6320.7	6776.8	7235.7	7421.6	7610.4	7741.1	7648.2	7299.6	6948.1	6599.6	6248.1
40°	7433.2	8022.9	8615.5	8949.5	9280.7	9515.9	9350.4	8946.6	8539.9	8136.2	7729.5
42.5°	9513.0	10419.3	11325.6	11804.9	12281.3	12626.9	12441.0	11944.3	11447.6	10950.9	10454.2
45°	12725.7	13884.7	15046.6	15746.6	16449.6	16966.6	16751.7	16127.1	15499.7	14875.2	14250.7
47.5°	16086.5	17469.1	18851.8	19409.5	19970.1	20405.8	20353.5	19575.1	18796.6	18021.0	17242.6
50°	18526.5	19900.4	21274.3	21753.6	22235.8	22593.1	22459.5	21469.0	20475.5	19485.0	18491.6
52.5°	19339.8	20667.2	21997.6	22569.9	23142.1	23569.1	23406.4	22291.0	21175.6	20063.1	18947.6
55°	19717.4	21097.2	22476.9	23174.0	23874.1	24385.3	24150.0	22927.1	21701.3	20478.4	19252.6
57.5°	20188.0	21666.5	23145.0	23908.9	24672.9	25224.8	24911.1	23644.6	22378.1	21114.6	19848.1
60°	20542.3	22015.1	23490.7	24103.6	24719.4	25149.3	24847.2	23615.6	22381.0	21149.4	19917.8
62.5°	19758.1	20890.9	22023.8	22479.8	22935.9	23267.0	23095.6	21927.9	20760.2	19592.5	18424.8
65°	17169.9	17954.2	18741.4	19049.3	19354.3	19589.6	19537.3	18552.6	17567.9	16586.1	15601.4
67.5°	13855.6	14465.6	15078.5	15514.2	15952.9	16292.7	16254.9	15357.4	14459.8	13562.2	12664.7
70°	10794.0	11427.3	12060.5	12609.5	13161.4	13588.4	13533.2	12699.5	11863.0	11029.3	10192.7
72.5°	8624.2	9344.6	10064.9	10378.6	10692.4	10913.1	10750.5	10120.1	9486.9	8856.6	8223.3
75°	5237.3	5614.9	5995.4	5992.5	5992.5	5957.6	5795.0	5434.8	5074.6	4714.4	4354.2
77.5°	1559.8	1725.4	1891.0	2050.7	2213.4	2335.4	2303.5	2114.7	1922.9	1734.1	1542.4
80°	429.9	473.5	519.9	540.3	560.6	586.8	653.6	607.1	560.6	517.0	470.6
82.5°	110.4	110.4	110.4	107.5	104.6	98.8	90.0	84.2	78.4	72.6	66.8
85°	17.4	14.5	14.5	14.5	11.6	11.6	11.6	11.6	8.7	8.7	5.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
2.5°	29.0	29.0	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	23.2
5°	34.9	34.9	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0	29.0
7.5°	43.6	43.6	40.7	40.7	40.7	40.7	37.8	37.8	37.8	37.8	34.9
10°	55.2	52.3	52.3	49.4	49.4	49.4	46.5	46.5	46.5	43.6	43.6
12.5°	69.7	66.8	66.8	63.9	61.0	61.0	58.1	55.2	52.3	52.3	49.4
15°	93.0	90.0	87.1	84.2	81.3	75.5	72.6	66.8	63.9	61.0	58.1
17.5°	177.2	162.7	148.1	133.6	122.0	110.4	98.8	87.1	81.3	75.5	69.7
20°	493.8	427.0	363.1	299.2	258.5	217.9	177.2	136.5	119.1	104.6	87.1
22.5°	1068.9	935.3	804.6	671.0	563.5	458.9	351.5	244.0	203.3	165.6	124.9
25°	1986.8	1731.2	1478.5	1222.9	1019.6	816.2	612.9	409.6	334.0	258.5	183.0
27.5°	2948.3	2617.2	2286.0	1954.9	1632.5	1307.1	981.8	659.4	528.7	400.9	270.1
30°	3689.0	3337.6	2989.0	2637.5	2230.8	1824.2	1414.6	1007.9	801.7	595.5	386.3
32.5°	4325.2	3944.6	3567.0	3186.5	2715.9	2245.4	1774.8	1304.2	1045.7	787.2	525.8
35°	4955.5	4522.7	4092.8	3660.0	3154.6	2649.1	2143.7	1638.3	1310.0	981.8	650.7
37.5°	5722.3	5193.7	4667.9	4142.2	3622.2	3105.2	2585.2	2065.3	1647.0	1231.6	813.3
40°	7058.5	6384.6	5713.6	5039.7	4432.6	3828.5	3221.4	2614.3	2088.5	1562.8	1034.1
42.5°	9608.9	8763.6	7921.2	7076.0	6236.5	5397.0	4554.6	3715.2	2965.7	2219.2	1469.8
45°	13167.2	12083.7	11003.2	9919.7	8885.6	7854.4	6820.3	5786.2	4647.6	3508.9	2367.4
47.5°	16057.4	14869.4	13684.2	12496.2	11348.8	10204.4	9057.0	7909.6	6451.4	4996.2	3538.0
50°	17361.7	16228.8	15098.9	13966.0	12815.7	11662.5	10509.4	9359.1	7686.0	6015.7	4342.6
52.5°	17800.3	16650.0	15502.6	14352.3	13210.8	12069.2	10927.6	9786.1	8046.1	6309.1	4569.2
55°	18041.4	16827.2	15615.9	14401.7	13173.0	11941.4	10709.8	9481.1	7749.9	6021.5	4290.3
57.5°	18529.4	17207.7	15888.9	14567.3	13167.2	11767.1	10364.1	8964.0	7256.0	5548.1	3840.1
60°	18619.4	17318.1	16019.7	14721.2	13173.0	11624.8	10073.7	8525.4	6829.1	5135.6	3439.2
62.5°	17338.4	16252.0	15168.6	14082.2	12531.1	10979.9	9425.9	7874.8	6251.0	4627.3	3000.6
65°	14663.1	13724.9	12789.6	11851.4	10584.9	9321.3	8054.9	6788.4	5338.9	3892.4	2442.9
67.5°	11746.8	10828.9	9913.9	8996.0	8043.2	7093.4	6140.6	5187.9	4069.5	2951.2	1832.9
70°	9312.6	8429.6	7549.4	6666.4	5824.0	4978.7	4133.4	3291.1	2596.8	1905.5	1211.3
72.5°	7381.0	6535.7	5693.3	4848.0	4084.1	3320.1	2556.2	1792.2	1446.6	1103.8	758.1
75°	3915.6	3477.0	3041.3	2602.7	2172.7	1739.9	1307.1	877.2	740.7	604.2	464.8
77.5°	1350.7	1159.0	970.2	778.5	647.8	517.0	386.3	255.6	241.1	229.5	215.0
80°	409.6	348.6	287.6	226.6	200.4	174.3	148.1	122.0	113.3	104.6	93.0
82.5°	63.9	58.1	55.2	49.4	46.5	46.5	43.6	40.7	34.9	32.0	26.1
85°	5.8	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066437
 CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	26.1	26.1
2.5°	23.2	23.2
5°	29.0	29.0
7.5°	34.9	34.9
10°	40.7	40.7
12.5°	46.5	46.5
15°	55.2	52.3
17.5°	63.9	61.0
20°	69.7	63.9
22.5°	84.2	72.6
25°	107.5	90.0
27.5°	139.4	110.4
30°	180.1	139.4
32.5°	267.2	194.6
35°	322.4	235.3
37.5°	395.0	273.0
40°	508.3	331.1
42.5°	720.4	450.2
45°	1228.7	746.5
47.5°	2082.7	1272.3
50°	2669.5	1632.5
52.5°	2832.1	1731.2
55°	2562.0	1588.9
57.5°	2132.1	1350.7
60°	1745.8	1112.5
62.5°	1376.8	880.1
65°	993.4	665.2
67.5°	714.6	511.2
70°	519.9	400.9
72.5°	412.5	334.0
75°	328.2	278.9
77.5°	203.3	185.9
80°	84.2	78.4
82.5°	20.3	17.4
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066437

CATALOG NUMBER: NVN-SA3A-740-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-1

Test Date: 10/09/2024

Luminaire Tested: GSS-SB1A-740-U-5WQ


Data in this report applies to families of products including GSS-SB1A-740-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-1
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-740-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 4000K CCT 26 LEDS

Spectral Parameters

CCT (K):	3949	CRI (Ra):	70.7		
CIE u':	0.2248	R1:	68.0	R9:	-36.7
CIE v':	0.5053	R2:	76.0	R10:	45.1
Duv:	0.0022	R3:	84.3	R11:	70.7
CIE x:	0.3844	R4:	72.0	R12:	47.1
CIE y:	0.3840	R5:	68.6	R13:	68.5
CIE z:	0.2316	R6:	68.3	R14:	91.1
Peak Wavelength (nm):	440	R7:	77.9	R15:	58.7
Dominant Wavelength (nm):	578	R8:	50.3		
Purity:	30.60026				
Rf:	71.8				
Rg:	96.5				



Test Conditions

Stabilization Time: 34M
 Operation Time: 1H 34M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-1

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-1

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 4000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-1

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	139	NR	620	607	NR	750	15	NR	880	0	NR
365	0	NR	495	198	NR	625	554	NR	755	13	NR	885	0	NR
370	0	NR	500	267	NR	630	504	NR	760	11	NR	890	0	NR
375	0	NR	505	343	NR	635	452	NR	765	10	NR	895	0	NR
380	0	NR	510	410	NR	640	403	NR	770	8	NR	900	0	NR
385	2	NR	515	470	NR	645	357	NR	775	7	NR	905	0	NR
390	4	NR	520	516	NR	650	314	NR	780	6	NR	910	0	NR
395	7	NR	525	550	NR	655	275	NR	785	5	NR	915	0	NR
400	10	NR	530	578	NR	660	240	NR	790	5	NR	920	0	NR
405	17	NR	535	601	NR	665	208	NR	795	4	NR	925	0	NR
410	35	NR	540	620	NR	670	179	NR	800	4	NR	930	0	NR
415	70	NR	545	641	NR	675	155	NR	805	3	NR	935	0	NR
420	147	NR	550	664	NR	680	133	NR	810	3	NR	940	0	NR
425	285	NR	555	689	NR	685	114	NR	815	2	NR	945	0	NR
430	487	NR	560	715	NR	690	98	NR	820	2	NR	950	0	NR
435	787	NR	565	743	NR	695	84	NR	825	2	NR	955	0	NR
440	1000	NR	570	771	NR	700	72	NR	830	2	NR	960	0	NR
445	783	NR	575	794	NR	705	61	NR	835	1	NR	965	0	NR
450	417	NR	580	811	NR	710	52	NR	840	1	NR	970	0	NR
455	261	NR	585	817	NR	715	45	NR	845	1	NR	975	0	NR
460	167	NR	590	815	NR	720	39	NR	850	1	NR	980	0	NR
465	104	NR	595	801	NR	725	33	NR	855	1	NR	985	0	NR
470	79	NR	600	777	NR	730	28	NR	860	1	NR	990	0	NR
475	73	NR	605	744	NR	735	24	NR	865	1	NR	995	0	NR
480	76	NR	610	704	NR	740	21	NR	870	1	NR	1000	0	NR
485	98	NR	615	657	NR	745	18	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-1

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.47

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	139	NR	620	607	NR	750	15	NR	880	0	NR
365	0	NR	495	198	NR	625	554	NR	755	13	NR	885	0	NR
370	0	NR	500	267	NR	630	504	NR	760	11	NR	890	0	NR
375	0	NR	505	343	NR	635	452	NR	765	10	NR	895	0	NR
380	0	NR	510	410	NR	640	403	NR	770	8	NR	900	0	NR
385	2	NR	515	470	NR	645	357	NR	775	7	NR	905	0	NR
390	4	NR	520	516	NR	650	314	NR	780	6	NR	910	0	NR
395	7	NR	525	550	NR	655	275	NR	785	5	NR	915	0	NR
400	10	NR	530	578	NR	660	240	NR	790	5	NR	920	0	NR
405	17	NR	535	601	NR	665	208	NR	795	4	NR	925	0	NR
410	35	NR	540	620	NR	670	179	NR	800	4	NR	930	0	NR
415	70	NR	545	641	NR	675	155	NR	805	3	NR	935	0	NR
420	147	NR	550	664	NR	680	133	NR	810	3	NR	940	0	NR
425	285	NR	555	689	NR	685	114	NR	815	2	NR	945	0	NR
430	487	NR	560	715	NR	690	98	NR	820	2	NR	950	0	NR
435	787	NR	565	743	NR	695	84	NR	825	2	NR	955	0	NR
440	1000	NR	570	771	NR	700	72	NR	830	2	NR	960	0	NR
445	783	NR	575	794	NR	705	61	NR	835	1	NR	965	0	NR
450	417	NR	580	811	NR	710	52	NR	840	1	NR	970	0	NR
455	261	NR	585	817	NR	715	45	NR	845	1	NR	975	0	NR
460	167	NR	590	815	NR	720	39	NR	850	1	NR	980	0	NR
465	104	NR	595	801	NR	725	33	NR	855	1	NR	985	0	NR
470	79	NR	600	777	NR	730	28	NR	860	1	NR	990	0	NR
475	73	NR	605	744	NR	735	24	NR	865	1	NR	995	0	NR
480	76	NR	610	704	NR	740	21	NR	870	1	NR	1000	0	NR
485	98	NR	615	657	NR	745	18	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-1

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.78

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	139	NR	620	607	NR	750	15	NR	880	0	NR
365	0	NR	495	198	NR	625	554	NR	755	13	NR	885	0	NR
370	0	NR	500	267	NR	630	504	NR	760	11	NR	890	0	NR
375	0	NR	505	343	NR	635	452	NR	765	10	NR	895	0	NR
380	0	NR	510	410	NR	640	403	NR	770	8	NR	900	0	NR
385	2	NR	515	470	NR	645	357	NR	775	7	NR	905	0	NR
390	4	NR	520	516	NR	650	314	NR	780	6	NR	910	0	NR
395	7	NR	525	550	NR	655	275	NR	785	5	NR	915	0	NR
400	10	NR	530	578	NR	660	240	NR	790	5	NR	920	0	NR
405	17	NR	535	601	NR	665	208	NR	795	4	NR	925	0	NR
410	35	NR	540	620	NR	670	179	NR	800	4	NR	930	0	NR
415	70	NR	545	641	NR	675	155	NR	805	3	NR	935	0	NR
420	147	NR	550	664	NR	680	133	NR	810	3	NR	940	0	NR
425	285	NR	555	689	NR	685	114	NR	815	2	NR	945	0	NR
430	487	NR	560	715	NR	690	98	NR	820	2	NR	950	0	NR
435	787	NR	565	743	NR	695	84	NR	825	2	NR	955	0	NR
440	1000	NR	570	771	NR	700	72	NR	830	2	NR	960	0	NR
445	783	NR	575	794	NR	705	61	NR	835	1	NR	965	0	NR
450	417	NR	580	811	NR	710	52	NR	840	1	NR	970	0	NR
455	261	NR	585	817	NR	715	45	NR	845	1	NR	975	0	NR
460	167	NR	590	815	NR	720	39	NR	850	1	NR	980	0	NR
465	104	NR	595	801	NR	725	33	NR	855	1	NR	985	0	NR
470	79	NR	600	777	NR	730	28	NR	860	1	NR	990	0	NR
475	73	NR	605	744	NR	735	24	NR	865	1	NR	995	0	NR
480	76	NR	610	704	NR	740	21	NR	870	1	NR	1000	0	NR
485	98	NR	615	657	NR	745	18	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-1

TM-30-18

Summary

$R_f = 71.8$
 $R_g = 96.5$
 $CIE R_a = 70.7$
 $R_g = -36.7$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 85	CES26 = 56	CES51 = 86	CES76 = 48
CES02 = 61	CES27 = 79	CES52 = 88	CES77 = 71
CES03 = 30	CES28 = 80	CES53 = 73	CES78 = 52
CES04 = 70	CES29 = 49	CES54 = 79	CES79 = 79
CES05 = 47	CES30 = 53	CES55 = 77	CES80 = 77
CES06 = 50	CES31 = 55	CES56 = 67	CES81 = 75
CES07 = 40	CES32 = 53	CES57 = 64	CES82 = 90
CES08 = 39	CES33 = 59	CES58 = 67	CES83 = 84
CES09 = 29	CES34 = 67	CES59 = 87	CES84 = 89
CES10 = 74	CES35 = 82	CES60 = 91	CES85 = 86
CES11 = 57	CES36 = 86	CES61 = 87	CES86 = 71
CES12 = 63	CES37 = 76	CES62 = 76	CES87 = 78
CES13 = 42	CES38 = 62	CES63 = 73	CES88 = 76
CES14 = 74	CES39 = 91	CES64 = 71	CES89 = 72
CES15 = 71	CES40 = 84	CES65 = 64	CES90 = 72
CES16 = 46	CES41 = 81	CES66 = 67	CES91 = 97
CES17 = 49	CES42 = 76	CES67 = 65	CES92 = 66
CES18 = 56	CES43 = 71	CES68 = 72	CES93 = 81
CES19 = 72	CES44 = 98	CES69 = 82	CES94 = 55
CES20 = 65	CES45 = 80	CES70 = 61	CES95 = 73
CES21 = 86	CES46 = 76	CES71 = 59	CES96 = 78
CES22 = 78	CES47 = 71	CES72 = 86	CES97 = 83
CES23 = 92	CES48 = 61	CES73 = 52	CES98 = 72
CES24 = 91	CES49 = 76	CES74 = 93	CES99 = 60
CES25 = 72	CES50 = 84	CES75 = 56	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)