

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066562

Luminaire Tested: **NVN-SA4B-750-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066562
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA4B-750-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 4xLight Square PACKAGE
70CRI 5000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 5000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 15207.5 lumens
Efficiency: N/A
Efficacy: 105.5 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 144.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3 fc
 Type III - Short - N/A

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	90.5	0.0	90.5
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	15117.0	0.0	15117.0
	% Fixture	99.4	0.0	99.4
Total	Lumens	15207.5	0.0	15207.5
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.5	0.0
10°-20°	22.3	0.1
20°-30°	283.8	1.9
30°-40°	956.6	6.3
40°-50°	2888.9	19.0
50°-60°	5097.0	33.5
60°-70°	4490.5	29.5
70°-80°	1429.4	9.4
80°-90°	34.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	15207.5	100.0
0°-180°	15207.5	100.0



REPORT NUMBER: P1066562


CATALOG NUMBER: NVN-SA4B-750-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	297.1	2.0			
FM	(30°-60°)	8907.5	58.6			
FH	(60°-80°)	5884.5	38.7			G3/7500
FVH	(80°-90°)	28.0	0.2			G1/100
BL	(0°-30°)	13.6	0.1	B0/110		
BM	(30°-60°)	35.1	0.2	B0/220		
BH	(60°-80°)	35.4	0.2	B0/110		G0/110
BVH	(80°-90°)	6.4	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	33.4
5°	47.7	47.7	47.7	42.9	42.9	42.9	38.2	38.2	38.2	38.2	38.2
7.5°	57.2	52.5	52.5	47.7	47.7	47.7	42.9	42.9	42.9	42.9	38.2
10°	66.8	62.0	62.0	57.2	57.2	52.5	52.5	47.7	47.7	42.9	42.9
12.5°	76.3	71.5	66.8	62.0	62.0	57.2	57.2	52.5	52.5	47.7	47.7
15°	85.8	81.1	76.3	71.5	66.8	66.8	62.0	57.2	52.5	52.5	47.7
17.5°	100.2	90.6	85.8	76.3	71.5	66.8	62.0	57.2	57.2	52.5	52.5
20°	104.9	95.4	90.6	81.1	76.3	71.5	66.8	62.0	57.2	57.2	52.5
22.5°	124.0	104.9	100.2	90.6	85.8	81.1	71.5	66.8	62.0	57.2	52.5
25°	152.6	124.0	109.7	95.4	90.6	81.1	76.3	66.8	62.0	57.2	52.5
27.5°	186.0	138.3	124.0	104.9	95.4	85.8	76.3	66.8	62.0	57.2	52.5
30°	228.9	162.1	138.3	114.5	104.9	95.4	81.1	71.5	66.8	62.0	52.5
32.5°	319.5	200.3	162.1	124.0	109.7	100.2	85.8	71.5	66.8	62.0	52.5
35°	386.3	243.2	195.5	143.1	124.0	109.7	90.6	71.5	66.8	62.0	52.5
37.5°	448.3	248.0	200.3	152.6	133.5	114.5	90.6	71.5	66.8	62.0	52.5
40°	548.4	257.5	200.3	143.1	128.8	109.7	95.4	76.3	71.5	62.0	57.2
42.5°	739.2	295.7	214.6	133.5	119.2	109.7	95.4	81.1	71.5	66.8	57.2
45°	1230.4	438.8	290.9	138.3	124.0	109.7	95.4	81.1	76.3	66.8	62.0
47.5°	2093.6	763.0	453.1	143.1	128.8	109.7	95.4	76.3	71.5	66.8	57.2
50°	2680.2	977.7	572.3	166.9	143.1	124.0	100.2	76.3	71.5	66.8	62.0
52.5°	2847.1	1039.7	620.0	195.5	166.9	138.3	104.9	76.3	71.5	71.5	66.8
55°	2608.7	1011.0	620.0	228.9	190.8	157.4	119.2	81.1	76.3	76.3	71.5
57.5°	2217.6	934.7	591.4	248.0	209.8	166.9	128.8	85.8	81.1	81.1	76.3
60°	1826.5	786.9	534.1	276.6	233.7	190.8	147.8	104.9	100.2	95.4	85.8
62.5°	1449.8	634.3	467.4	295.7	252.8	205.1	162.1	114.5	109.7	104.9	100.2
65°	1092.1	553.2	434.0	310.0	262.3	214.6	166.9	119.2	114.5	114.5	109.7
67.5°	839.4	505.5	414.9	319.5	271.8	224.1	176.5	128.8	124.0	119.2	114.5
70°	662.9	467.4	391.1	314.8	271.8	228.9	181.2	138.3	128.8	124.0	114.5
72.5°	553.2	424.4	362.4	300.5	267.1	233.7	200.3	166.9	147.8	133.5	114.5
75°	462.6	381.5	329.1	271.8	248.0	228.9	205.1	181.2	157.4	133.5	109.7
77.5°	305.2	276.6	252.8	228.9	214.6	200.3	181.2	166.9	143.1	124.0	100.2
80°	128.8	119.2	124.0	124.0	124.0	124.0	119.2	119.2	104.9	90.6	71.5
82.5°	28.6	23.8	28.6	28.6	28.6	28.6	23.8	23.8	23.8	19.1	19.1
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4
5°	38.2	38.2	38.2	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4
7.5°	38.2	38.2	38.2	33.4	33.4	33.4	33.4	28.6	28.6	28.6	28.6
10°	38.2	38.2	38.2	33.4	33.4	33.4	33.4	28.6	28.6	28.6	28.6
12.5°	42.9	42.9	38.2	38.2	33.4	33.4	33.4	28.6	28.6	28.6	28.6
15°	42.9	42.9	38.2	38.2	33.4	33.4	33.4	28.6	28.6	28.6	28.6
17.5°	47.7	42.9	42.9	38.2	33.4	33.4	33.4	28.6	28.6	28.6	28.6
20°	47.7	42.9	42.9	38.2	33.4	33.4	33.4	28.6	28.6	28.6	28.6
22.5°	47.7	42.9	42.9	38.2	33.4	33.4	28.6	28.6	23.8	23.8	19.1
25°	47.7	42.9	42.9	38.2	33.4	33.4	28.6	28.6	23.8	19.1	19.1
27.5°	47.7	42.9	42.9	38.2	33.4	28.6	28.6	23.8	19.1	14.3	14.3
30°	47.7	42.9	42.9	38.2	33.4	28.6	23.8	19.1	14.3	14.3	9.5
32.5°	47.7	42.9	38.2	33.4	28.6	23.8	23.8	19.1	14.3	9.5	9.5
35°	47.7	42.9	38.2	33.4	28.6	23.8	23.8	19.1	14.3	9.5	9.5
37.5°	47.7	42.9	38.2	33.4	28.6	23.8	19.1	14.3	9.5	9.5	4.8
40°	47.7	42.9	38.2	33.4	28.6	23.8	19.1	14.3	9.5	9.5	4.8
42.5°	47.7	42.9	38.2	33.4	28.6	23.8	19.1	14.3	9.5	9.5	4.8
45°	52.5	47.7	42.9	33.4	28.6	23.8	23.8	19.1	14.3	9.5	9.5
47.5°	52.5	47.7	42.9	33.4	28.6	23.8	23.8	19.1	14.3	9.5	9.5
50°	57.2	52.5	47.7	38.2	33.4	28.6	23.8	14.3	9.5	9.5	4.8
52.5°	62.0	57.2	52.5	47.7	42.9	33.4	23.8	14.3	4.8	4.8	4.8
55°	66.8	62.0	62.0	57.2	52.5	38.2	28.6	14.3	0.0	0.0	0.0
57.5°	71.5	66.8	66.8	62.0	57.2	42.9	28.6	14.3	0.0	0.0	0.0
60°	81.1	76.3	71.5	62.0	57.2	42.9	28.6	14.3	0.0	0.0	0.0
62.5°	95.4	85.8	71.5	62.0	47.7	38.2	23.8	14.3	0.0	0.0	0.0
65°	104.9	90.6	76.3	57.2	42.9	33.4	23.8	9.5	0.0	0.0	0.0
67.5°	109.7	90.6	76.3	57.2	38.2	28.6	19.1	9.5	0.0	0.0	0.0
70°	104.9	85.8	71.5	52.5	33.4	23.8	19.1	9.5	0.0	0.0	0.0
72.5°	95.4	81.1	62.0	47.7	28.6	23.8	14.3	9.5	0.0	0.0	0.0
75°	85.8	71.5	52.5	38.2	19.1	14.3	9.5	4.8	0.0	0.0	0.0
77.5°	76.3	62.0	42.9	28.6	9.5	9.5	4.8	4.8	0.0	0.0	0.0
80°	57.2	42.9	28.6	14.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	14.3	9.5	9.5	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6	28.6
5°	28.6	28.6	28.6	28.6	23.8	23.8	23.8	23.8	23.8	23.8	23.8
7.5°	28.6	28.6	28.6	28.6	23.8	23.8	23.8	23.8	19.1	19.1	19.1
10°	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	19.1	19.1	19.1
12.5°	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	19.1	19.1	19.1
15°	23.8	23.8	23.8	23.8	23.8	23.8	23.8	19.1	19.1	14.3	14.3
17.5°	23.8	23.8	23.8	23.8	19.1	19.1	19.1	14.3	14.3	9.5	9.5
20°	23.8	23.8	23.8	19.1	19.1	14.3	14.3	9.5	9.5	4.8	4.8
22.5°	19.1	14.3	14.3	9.5	9.5	4.8	4.8	4.8	0.0	0.0	0.0
25°	14.3	9.5	9.5	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	9.5	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	9.5	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	28.6	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8
5°	23.8	23.8	23.8	23.8	19.1	19.1	19.1	19.1	19.1	19.1	19.1
7.5°	19.1	19.1	19.1	19.1	19.1	19.1	14.3	14.3	14.3	14.3	14.3
10°	19.1	14.3	14.3	14.3	14.3	14.3	14.3	14.3	14.3	9.5	9.5
12.5°	19.1	14.3	14.3	14.3	9.5	9.5	9.5	9.5	9.5	4.8	4.8
15°	14.3	9.5	9.5	9.5	4.8	4.8	4.8	4.8	4.8	0.0	0.0
17.5°	9.5	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	28.6	28.6
5°	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1
7.5°	14.3	14.3	14.3	14.3	14.3	14.3	14.3	14.3	14.3	14.3	14.3
10°	9.5	9.5	9.5	9.5	9.5	9.5	4.8	4.8	4.8	4.8	4.8
12.5°	4.8	4.8	4.8	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	28.6	28.6	28.6	28.6	28.6	33.4	33.4	38.2	38.2	42.9	42.9
5°	19.1	19.1	23.8	23.8	23.8	23.8	28.6	28.6	28.6	33.4	33.4
7.5°	14.3	14.3	14.3	14.3	14.3	19.1	19.1	23.8	23.8	28.6	28.6
10°	4.8	4.8	9.5	9.5	9.5	9.5	14.3	14.3	14.3	19.1	23.8
12.5°	0.0	0.0	4.8	4.8	4.8	4.8	9.5	9.5	9.5	14.3	19.1
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	9.5	14.3
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	9.5
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	47.7	47.7	52.5	52.5	57.2	57.2	62.0	62.0	62.0	62.0	62.0
5°	38.2	38.2	42.9	47.7	47.7	52.5	57.2	57.2	57.2	57.2	57.2
7.5°	33.4	33.4	38.2	42.9	42.9	47.7	52.5	52.5	57.2	57.2	57.2
10°	23.8	28.6	33.4	38.2	38.2	42.9	47.7	47.7	52.5	52.5	52.5
12.5°	19.1	23.8	28.6	33.4	33.4	38.2	42.9	42.9	47.7	47.7	52.5
15°	14.3	19.1	23.8	28.6	28.6	33.4	38.2	38.2	42.9	47.7	52.5
17.5°	9.5	14.3	19.1	23.8	23.8	28.6	33.4	38.2	42.9	42.9	47.7
20°	9.5	9.5	14.3	19.1	19.1	23.8	28.6	33.4	38.2	38.2	42.9
22.5°	4.8	4.8	9.5	14.3	14.3	19.1	23.8	28.6	33.4	33.4	38.2
25°	0.0	0.0	4.8	9.5	9.5	14.3	19.1	19.1	23.8	23.8	28.6
27.5°	0.0	0.0	4.8	4.8	9.5	9.5	14.3	14.3	19.1	19.1	23.8
30°	0.0	0.0	4.8	4.8	9.5	9.5	14.3	14.3	19.1	19.1	19.1
32.5°	0.0	0.0	0.0	4.8	4.8	4.8	9.5	9.5	14.3	14.3	19.1
35°	0.0	0.0	0.0	4.8	4.8	4.8	9.5	9.5	14.3	14.3	14.3
37.5°	0.0	0.0	0.0	4.8	4.8	4.8	9.5	9.5	9.5	9.5	14.3
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.5	9.5	9.5
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.5	9.5	9.5
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.5	9.5	9.5
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.5	9.5	9.5
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.5	9.5	9.5
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.5	9.5	9.5
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.5	9.5	9.5
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	9.5
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	62.0	62.0
5°	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	57.2	57.2
7.5°	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	57.2	57.2
10°	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2
12.5°	52.5	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2
15°	52.5	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2
17.5°	47.7	52.5	52.5	52.5	57.2	57.2	57.2	57.2	57.2	57.2	57.2
20°	42.9	47.7	47.7	47.7	52.5	52.5	52.5	52.5	57.2	57.2	57.2
22.5°	38.2	42.9	42.9	42.9	47.7	47.7	47.7	47.7	52.5	52.5	52.5
25°	33.4	33.4	38.2	38.2	42.9	42.9	42.9	42.9	42.9	42.9	42.9
27.5°	23.8	28.6	28.6	28.6	33.4	33.4	33.4	33.4	38.2	38.2	38.2
30°	23.8	23.8	23.8	23.8	28.6	28.6	28.6	28.6	33.4	33.4	33.4
32.5°	19.1	23.8	23.8	23.8	28.6	28.6	28.6	28.6	33.4	33.4	33.4
35°	19.1	19.1	19.1	19.1	23.8	23.8	23.8	23.8	28.6	28.6	28.6
37.5°	14.3	19.1	19.1	19.1	23.8	23.8	23.8	23.8	28.6	28.6	28.6
40°	14.3	14.3	14.3	14.3	19.1	19.1	19.1	19.1	23.8	23.8	23.8
42.5°	14.3	14.3	14.3	14.3	19.1	19.1	19.1	19.1	23.8	23.8	23.8
45°	14.3	14.3	14.3	14.3	19.1	19.1	19.1	19.1	23.8	23.8	23.8
47.5°	14.3	14.3	14.3	14.3	19.1	19.1	19.1	19.1	23.8	23.8	23.8
50°	14.3	14.3	14.3	14.3	19.1	19.1	19.1	19.1	23.8	23.8	23.8
52.5°	9.5	9.5	9.5	9.5	14.3	14.3	14.3	14.3	19.1	19.1	19.1
55°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	14.3	14.3	14.3
57.5°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	14.3	14.3	14.3
60°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5
62.5°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
65°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	4.8	4.8
67.5°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5
70°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5
72.5°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5
75°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5
77.5°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5
80°	14.3	14.3	14.3	14.3	14.3	9.5	9.5	9.5	9.5	9.5	9.5
82.5°	9.5	14.3	14.3	14.3	14.3	9.5	9.5	9.5	9.5	9.5	9.5
85°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5
87.5°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	62.0	62.0	57.2	57.2	57.2	57.2	57.2	57.2	57.2	62.0	62.0
5°	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	62.0	62.0
7.5°	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	62.0	62.0
10°	57.2	57.2	57.2	57.2	52.5	52.5	57.2	57.2	57.2	62.0	62.0
12.5°	57.2	57.2	57.2	57.2	52.5	52.5	57.2	57.2	62.0	62.0	66.8
15°	57.2	57.2	52.5	52.5	52.5	52.5	57.2	57.2	62.0	62.0	66.8
17.5°	57.2	57.2	52.5	52.5	52.5	52.5	57.2	57.2	62.0	62.0	66.8
20°	57.2	57.2	52.5	52.5	52.5	52.5	52.5	52.5	57.2	62.0	62.0
22.5°	52.5	52.5	52.5	52.5	47.7	47.7	52.5	52.5	57.2	62.0	62.0
25°	42.9	47.7	47.7	47.7	47.7	47.7	52.5	52.5	57.2	62.0	62.0
27.5°	38.2	42.9	42.9	42.9	42.9	47.7	47.7	52.5	57.2	62.0	62.0
30°	33.4	38.2	38.2	38.2	42.9	47.7	47.7	52.5	57.2	62.0	62.0
32.5°	33.4	38.2	38.2	38.2	42.9	42.9	47.7	47.7	52.5	57.2	62.0
35°	33.4	33.4	38.2	38.2	38.2	42.9	42.9	47.7	52.5	57.2	62.0
37.5°	33.4	33.4	38.2	38.2	38.2	42.9	42.9	47.7	52.5	57.2	62.0
40°	28.6	33.4	33.4	38.2	38.2	42.9	42.9	47.7	52.5	62.0	66.8
42.5°	28.6	28.6	33.4	33.4	38.2	42.9	42.9	47.7	52.5	62.0	66.8
45°	28.6	33.4	33.4	38.2	42.9	47.7	47.7	52.5	57.2	62.0	66.8
47.5°	28.6	33.4	33.4	38.2	47.7	47.7	52.5	52.5	57.2	62.0	66.8
50°	28.6	33.4	33.4	38.2	52.5	52.5	52.5	52.5	57.2	62.0	66.8
52.5°	23.8	28.6	28.6	33.4	42.9	47.7	52.5	57.2	62.0	66.8	71.5
55°	19.1	23.8	23.8	28.6	38.2	42.9	52.5	62.0	66.8	71.5	76.3
57.5°	19.1	19.1	23.8	23.8	33.4	42.9	57.2	66.8	71.5	76.3	81.1
60°	14.3	14.3	19.1	19.1	28.6	38.2	52.5	66.8	71.5	81.1	85.8
62.5°	9.5	14.3	14.3	19.1	23.8	38.2	52.5	66.8	76.3	85.8	90.6
65°	9.5	9.5	14.3	14.3	23.8	33.4	47.7	57.2	71.5	85.8	100.2
67.5°	14.3	14.3	19.1	19.1	23.8	33.4	47.7	57.2	71.5	90.6	104.9
70°	14.3	14.3	19.1	19.1	28.6	38.2	47.7	57.2	71.5	90.6	104.9
72.5°	14.3	14.3	19.1	19.1	28.6	33.4	42.9	52.5	66.8	81.1	95.4
75°	9.5	14.3	14.3	14.3	23.8	28.6	38.2	47.7	62.0	76.3	90.6
77.5°	9.5	9.5	9.5	9.5	19.1	23.8	33.4	38.2	52.5	66.8	81.1
80°	9.5	9.5	9.5	9.5	14.3	19.1	28.6	33.4	47.7	62.0	76.3
82.5°	9.5	9.5	4.8	4.8	9.5	14.3	19.1	23.8	38.2	47.7	62.0
85°	9.5	9.5	4.8	4.8	4.8	9.5	9.5	14.3	19.1	23.8	28.6
87.5°	9.5	9.5	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	62.0	62.0	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8
5°	62.0	66.8	66.8	71.5	71.5	71.5	76.3	76.3	76.3	76.3	76.3
7.5°	62.0	66.8	66.8	71.5	71.5	71.5	76.3	76.3	76.3	81.1	81.1
10°	62.0	66.8	66.8	71.5	71.5	76.3	81.1	81.1	85.8	85.8	85.8
12.5°	66.8	71.5	71.5	76.3	76.3	81.1	85.8	85.8	90.6	95.4	95.4
15°	66.8	71.5	76.3	76.3	81.1	85.8	90.6	90.6	95.4	100.2	104.9
17.5°	66.8	71.5	76.3	76.3	81.1	85.8	95.4	100.2	104.9	114.5	119.2
20°	66.8	71.5	76.3	76.3	81.1	90.6	95.4	104.9	109.7	119.2	128.8
22.5°	66.8	71.5	76.3	81.1	85.8	95.4	104.9	109.7	119.2	133.5	143.1
25°	66.8	71.5	76.3	81.1	85.8	95.4	104.9	114.5	124.0	143.1	162.1
27.5°	66.8	71.5	81.1	85.8	90.6	100.2	114.5	124.0	133.5	166.9	200.3
30°	66.8	71.5	81.1	85.8	90.6	104.9	119.2	128.8	143.1	200.3	252.8
32.5°	66.8	76.3	81.1	90.6	95.4	109.7	128.8	143.1	157.4	238.5	314.8
35°	66.8	76.3	81.1	90.6	95.4	114.5	133.5	152.6	171.7	290.9	410.1
37.5°	66.8	76.3	81.1	90.6	95.4	124.0	152.6	181.2	209.8	333.8	457.8
40°	71.5	81.1	85.8	95.4	100.2	128.8	157.4	186.0	214.6	338.6	462.6
42.5°	71.5	81.1	85.8	95.4	100.2	124.0	152.6	176.5	200.3	338.6	476.9
45°	71.5	81.1	90.6	95.4	104.9	128.8	152.6	171.7	195.5	372.0	543.7
47.5°	71.5	81.1	90.6	95.4	104.9	128.8	152.6	176.5	200.3	491.2	777.4
50°	71.5	81.1	90.6	95.4	104.9	133.5	162.1	190.8	219.4	734.4	1249.5
52.5°	76.3	81.1	90.6	95.4	100.2	133.5	166.9	200.3	233.7	953.8	1669.2
55°	81.1	85.8	90.6	95.4	100.2	143.1	186.0	228.9	271.8	1025.3	1774.1
57.5°	85.8	90.6	95.4	95.4	100.2	152.6	209.8	262.3	314.8	1020.6	1721.6
60°	90.6	95.4	100.2	104.9	109.7	162.1	219.4	271.8	324.3	925.2	1526.1
62.5°	100.2	109.7	119.2	124.0	133.5	186.0	233.7	286.1	333.8	758.3	1178.0
65°	114.5	124.0	128.8	138.3	143.1	190.8	243.2	290.9	338.6	629.5	915.7
67.5°	119.2	128.8	133.5	143.1	147.8	195.5	243.2	290.9	338.6	534.1	724.9
70°	119.2	128.8	138.3	143.1	152.6	200.3	243.2	290.9	333.8	462.6	591.4
72.5°	109.7	124.0	133.5	147.8	157.4	200.3	238.5	281.4	319.5	410.1	500.8
75°	104.9	124.0	138.3	157.4	171.7	200.3	233.7	262.3	290.9	357.7	424.4
77.5°	95.4	119.2	143.1	166.9	190.8	209.8	224.1	243.2	257.5	300.5	343.4
80°	90.6	114.5	138.3	162.1	186.0	195.5	200.3	209.8	214.6	219.4	224.1
82.5°	71.5	90.6	109.7	124.0	143.1	133.5	128.8	119.2	109.7	104.9	100.2
85°	33.4	38.2	38.2	42.9	42.9	42.9	38.2	38.2	33.4	28.6	23.8
87.5°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	66.8	66.8	66.8	66.8	62.0	62.0	62.0	62.0	57.2	57.2	57.2
5°	76.3	76.3	76.3	76.3	71.5	71.5	71.5	71.5	66.8	66.8	66.8
7.5°	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1
10°	90.6	90.6	90.6	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
12.5°	100.2	100.2	104.9	104.9	109.7	109.7	114.5	114.5	119.2	119.2	119.2
15°	109.7	114.5	119.2	124.0	124.0	128.8	133.5	138.3	143.1	147.8	152.6
17.5°	128.8	133.5	143.1	152.6	162.1	171.7	186.0	205.1	219.4	233.7	252.8
20°	143.1	157.4	186.0	219.4	248.0	276.6	348.1	419.7	491.2	562.7	634.3
22.5°	171.7	200.3	295.7	395.8	491.2	586.6	810.7	1034.9	1254.3	1478.4	1678.7
25°	228.9	290.9	510.3	729.7	944.3	1163.7	1564.3	1969.6	2370.2	2770.8	3142.8
27.5°	314.8	429.2	786.9	1149.3	1507.0	1864.7	2446.5	3033.1	3614.9	4201.5	4721.4
30°	438.8	624.7	1158.9	1697.8	2231.9	2766.1	3500.5	4239.7	4974.1	5708.6	6185.5
32.5°	596.1	872.7	1549.9	2227.2	2904.4	3581.6	4392.3	5203.0	6009.0	6819.8	7325.3
35°	763.0	1116.0	1931.5	2751.7	3567.3	4387.5	5241.2	6094.9	6948.5	7802.2	8422.2
37.5°	858.4	1259.0	2227.2	3195.3	4158.6	5126.7	6061.5	7001.0	7935.7	8870.5	9624.0
40°	949.0	1430.7	2546.7	3662.6	4778.6	5894.6	6986.7	8078.8	9170.9	10263.0	11231.1
42.5°	1082.6	1688.2	2990.2	4292.2	5589.3	6891.3	8326.8	9767.0	11202.5	12638.0	14126.0
45°	1359.2	2174.7	3862.9	5551.2	7234.7	8922.9	10959.3	13000.5	15036.8	17078.0	18985.6
47.5°	2026.9	3271.6	5575.0	7878.5	10181.9	12485.4	14831.8	17178.2	19524.5	21870.9	24141.0
50°	3138.0	5021.8	7902.3	10782.8	13658.6	16539.1	18880.7	21222.3	23559.2	25900.8	28156.5
52.5°	4182.5	6695.8	9790.9	12890.8	15985.9	19085.8	21160.3	23234.9	25309.4	27383.9	29568.2
55°	4540.1	7301.4	10434.7	13572.7	16706.0	19844.1	21842.3	23845.3	25843.5	27841.8	30107.1
57.5°	4225.4	6729.1	9886.3	13043.4	16195.7	19352.8	21584.8	23821.5	26053.4	28290.1	30717.5
60°	3538.6	5546.4	8860.9	12180.2	15494.7	18809.2	21327.2	23845.3	26363.4	28881.4	31304.1
62.5°	2804.2	4425.7	7935.7	11445.7	14955.8	18465.8	21026.8	23592.5	26153.5	28714.5	30574.4
65°	2150.8	3386.0	6838.8	10296.4	13749.2	17206.8	19305.2	21408.3	23506.7	25609.8	26897.5
67.5°	1597.6	2470.4	5489.2	8512.8	11531.6	14550.4	16095.6	17645.5	19190.7	20740.6	21742.1
70°	1178.0	1759.8	3815.2	5870.7	7921.4	9976.9	11393.3	12809.7	14221.3	15637.7	16677.4
72.5°	815.5	1125.5	2355.9	3591.1	4821.5	6051.9	7487.4	8922.9	10353.6	11789.1	12971.8
75°	558.0	691.5	1268.6	1845.6	2422.7	2999.7	4087.1	5174.4	6261.8	7349.1	7973.9
77.5°	414.9	486.4	658.1	834.6	1006.3	1178.0	1387.8	1597.6	1807.5	2017.3	2289.1
80°	228.9	228.9	252.8	271.8	295.7	314.8	372.0	434.0	491.2	553.2	629.5
82.5°	104.9	109.7	119.2	128.8	133.5	143.1	152.6	162.1	171.7	181.2	181.2
85°	28.6	33.4	33.4	28.6	28.6	23.8	23.8	28.6	28.6	28.6	28.6
87.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	57.2	52.5	52.5	52.5	47.7	47.7	47.7	47.7	47.7	47.7	47.7
5°	66.8	66.8	66.8	66.8	62.0	62.0	62.0	62.0	62.0	57.2	57.2
7.5°	81.1	76.3	76.3	76.3	76.3	76.3	76.3	76.3	76.3	71.5	71.5
10°	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	90.6	90.6
12.5°	119.2	119.2	119.2	119.2	124.0	124.0	119.2	119.2	119.2	114.5	114.5
15°	157.4	162.1	166.9	166.9	171.7	171.7	171.7	166.9	166.9	162.1	157.4
17.5°	267.1	281.4	300.5	319.5	338.6	352.9	352.9	343.4	333.8	324.3	314.8
20°	710.6	782.1	858.4	934.7	1015.8	1073.0	1034.9	1006.3	977.7	944.3	915.7
22.5°	1883.8	2084.1	2289.1	2432.2	2575.3	2675.4	2594.4	2437.0	2279.6	2127.0	1969.6
25°	3514.8	3882.0	4254.0	4406.6	4564.0	4678.4	4626.0	4387.5	4149.1	3915.4	3676.9
27.5°	5241.2	5756.3	6276.1	6409.6	6543.1	6643.3	6624.2	6314.2	6004.2	5694.3	5384.3
30°	6662.4	7139.3	7616.2	7749.7	7883.3	7973.9	7873.7	7563.7	7253.7	6943.8	6633.8
32.5°	7835.6	8341.1	8851.4	9027.8	9204.3	9323.5	9204.3	8832.3	8460.3	8093.1	7721.1
35°	9042.1	9657.3	10277.3	10501.5	10725.6	10868.7	10668.4	10210.6	9752.7	9299.7	8841.8
37.5°	10377.5	11126.2	11879.7	12184.9	12494.9	12709.5	12556.9	11984.6	11407.6	10835.3	10258.2
40°	12204.0	13172.1	14145.0	14693.5	15237.1	15623.4	15351.6	14688.7	14021.0	13358.1	12690.5
42.5°	15618.7	17106.6	18594.6	19381.5	20163.6	20731.1	20425.9	19610.4	18794.9	17979.4	17163.8
45°	20893.2	22796.1	24703.7	25853.1	27007.2	27856.1	27503.2	26477.8	25447.7	24422.4	23397.0
47.5°	26411.1	28681.1	30951.2	31866.9	32787.3	33502.6	33416.8	32138.7	30860.6	29587.2	28309.1
50°	30417.1	32672.8	34928.6	35715.5	36507.1	37093.7	36874.4	35248.1	33617.1	31990.8	30359.8
52.5°	31752.4	33931.9	36116.1	37055.6	37995.1	38696.1	38429.1	36597.8	34766.4	32939.9	31108.6
55°	32372.4	34637.7	36903.0	38047.6	39196.9	40036.3	39650.0	37642.2	35629.6	33621.9	31609.3
57.5°	33145.0	35572.4	37999.9	39254.1	40508.4	41414.5	40899.5	38820.1	36740.8	34666.3	32587.0
60°	33726.8	36144.7	38567.4	39573.7	40584.7	41290.5	40794.5	38772.5	36745.6	34723.5	32701.4
62.5°	32439.1	34299.1	36159.0	36907.7	37656.5	38200.2	37918.8	36001.6	34084.5	32167.3	30250.1
65°	28189.9	29477.6	30770.0	31275.5	31776.2	32162.5	32076.7	30460.0	28843.3	27231.3	25614.6
67.5°	22748.4	23749.9	24756.2	25471.5	26191.7	26749.7	26687.7	25214.0	23740.4	22266.7	20793.1
70°	17721.8	18761.5	19801.1	20702.5	21608.6	22309.7	22219.0	20850.3	19476.8	18108.1	16734.6
72.5°	14159.3	15342.1	16524.8	17039.8	17554.9	17917.4	17650.3	16615.4	15575.7	14540.9	13501.2
75°	8598.6	9218.6	9843.3	9838.6	9838.6	9781.3	9514.3	8922.9	8331.5	7740.2	7148.8
77.5°	2561.0	2832.8	3104.7	3367.0	3634.0	3834.3	3781.9	3471.9	3157.1	2847.1	2532.4
80°	705.8	777.4	853.7	887.0	920.4	963.3	1073.0	996.7	920.4	848.9	772.6
82.5°	181.2	181.2	181.2	176.5	171.7	162.1	147.8	138.3	128.8	119.2	109.7
85°	28.6	23.8	23.8	23.8	19.1	19.1	19.1	19.1	14.3	14.3	9.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
2.5°	47.7	47.7	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	38.2
5°	57.2	57.2	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	47.7
7.5°	71.5	71.5	66.8	66.8	66.8	66.8	62.0	62.0	62.0	62.0	57.2
10°	90.6	85.8	85.8	81.1	81.1	81.1	76.3	76.3	76.3	71.5	71.5
12.5°	114.5	109.7	109.7	104.9	100.2	100.2	95.4	90.6	85.8	85.8	81.1
15°	152.6	147.8	143.1	138.3	133.5	124.0	119.2	109.7	104.9	100.2	95.4
17.5°	290.9	267.1	243.2	219.4	200.3	181.2	162.1	143.1	133.5	124.0	114.5
20°	810.7	701.1	596.1	491.2	424.4	357.7	290.9	224.1	195.5	171.7	143.1
22.5°	1755.0	1535.6	1321.0	1101.7	925.2	753.5	577.1	400.6	333.8	271.8	205.1
25°	3262.0	2842.4	2427.5	2007.8	1673.9	1340.1	1006.3	672.4	548.4	424.4	300.5
27.5°	4840.6	4296.9	3753.2	3209.6	2680.2	2146.1	1611.9	1082.6	868.0	658.1	443.5
30°	6056.7	5479.6	4907.4	4330.3	3662.6	2995.0	2322.5	1654.9	1316.3	977.7	634.3
32.5°	7101.1	6476.4	5856.4	5231.7	4459.1	3686.5	2913.9	2141.3	1716.9	1292.4	863.2
35°	8136.0	7425.4	6719.6	6009.0	5179.2	4349.4	3519.6	2689.7	2150.8	1611.9	1068.3
37.5°	9395.0	8527.1	7663.9	6800.7	5947.0	5098.1	4244.5	3390.8	2704.1	2022.1	1335.3
40°	11588.8	10482.4	9380.7	8274.3	7277.6	6285.6	5288.9	4292.2	3429.0	2565.8	1697.8
42.5°	15776.0	14388.3	13005.2	11617.4	10239.2	8860.9	7477.9	6099.6	4869.2	3643.6	2413.1
45°	21618.1	19839.3	18065.2	16286.3	14588.6	12895.5	11197.8	9500.0	7630.5	5761.0	3886.8
47.5°	26363.4	24412.8	22467.0	20516.5	18632.7	16753.7	14869.9	12986.1	10592.1	8202.8	5808.7
50°	28504.7	26644.7	24789.6	22929.6	21041.1	19147.8	17254.5	15365.9	12618.9	9876.7	7129.7
52.5°	29224.8	27336.2	25452.5	23563.9	21689.7	19815.4	17941.2	16067.0	13210.3	10358.4	7501.7
55°	29620.6	27627.2	25638.5	23645.0	21627.7	19605.6	17583.5	15566.2	12723.9	9886.3	7043.9
57.5°	30421.8	28251.9	26086.8	23916.8	21618.1	19319.5	17016.0	14717.3	11913.1	9108.9	6304.7
60°	30569.7	28433.1	26301.4	24169.6	21627.7	19085.8	16539.1	13997.2	11212.1	8431.7	5646.6
62.5°	28466.5	26682.9	24904.0	23120.4	20573.7	18027.0	15475.6	12928.9	10263.0	7597.1	4926.4
65°	24074.2	22533.8	20998.2	19457.8	17378.5	15303.9	13224.6	11145.3	8765.5	6390.5	4010.8
67.5°	19286.1	17779.1	16276.8	14769.8	13205.5	11646.0	10081.8	8517.5	6681.5	4845.4	3009.3
70°	15289.6	13839.8	12394.8	10945.0	9562.0	8174.2	6786.4	5403.3	4263.5	3128.5	1988.7
72.5°	12118.2	10730.4	9347.4	7959.6	6705.3	5451.0	4196.8	2942.5	2375.0	1812.2	1244.7
75°	6428.7	5708.6	4993.2	4273.1	3567.3	2856.7	2146.1	1440.3	1216.1	992.0	763.0
77.5°	2217.6	1902.9	1592.9	1278.1	1063.5	848.9	634.3	419.7	395.8	376.8	352.9
80°	672.4	572.3	472.1	372.0	329.1	286.1	243.2	200.3	186.0	171.7	152.6
82.5°	104.9	95.4	90.6	81.1	76.3	76.3	71.5	66.8	57.2	52.5	42.9
85°	9.5	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	42.9	42.9
2.5°	38.2	38.2
5°	47.7	47.7
7.5°	57.2	57.2
10°	66.8	66.8
12.5°	76.3	76.3
15°	90.6	85.8
17.5°	104.9	100.2
20°	114.5	104.9
22.5°	138.3	119.2
25°	176.5	147.8
27.5°	228.9	181.2
30°	295.7	228.9
32.5°	438.8	319.5
35°	529.4	386.3
37.5°	648.6	448.3
40°	834.6	543.7
42.5°	1182.7	739.2
45°	2017.3	1225.6
47.5°	3419.4	2088.8
50°	4382.8	2680.2
52.5°	4649.8	2842.4
55°	4206.3	2608.7
57.5°	3500.5	2217.6
60°	2866.2	1826.5
62.5°	2260.5	1445.0
65°	1631.0	1092.1
67.5°	1173.2	839.4
70°	853.7	658.1
72.5°	677.2	548.4
75°	538.9	457.8
77.5°	333.8	305.2
80°	138.3	128.8
82.5°	33.4	28.6
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066562

CATALOG NUMBER: NVN-SA4B-750-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-6

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-750-U-5WQ


Data in this report applies to families of products including GSS-SB1A-750-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-6
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-750-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 5000K CCT 26 LEDS

Spectral Parameters

CCT (K):	4896	CRI (Ra):	70.2		
CIE u':	0.2101	R1:	68.1	R9:	-35.1
CIE v':	0.4901	R2:	73.9	R10:	39.3
Duv:	0.0035	R3:	79.4	R11:	71.1
CIE x:	0.3489	R4:	72.1	R12:	43.8
CIE y:	0.3618	R5:	69.2	R13:	68.1
CIE z:	0.2893	R6:	65.7	R14:	88.4
Peak Wavelength (nm):	443	R7:	78.1	R15:	59.7
Dominant Wavelength (nm):	570	R8:	55.3		
Purity:	13.25435				
Rf:	70.7				
Rg:	96.8				



Test Conditions


Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-6


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-6

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 5000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-6

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	118	NR	620	401	NR	750	12	NR	880	0	NR
365	0	NR	495	168	NR	625	365	NR	755	10	NR	885	0	NR
370	0	NR	500	230	NR	630	331	NR	760	9	NR	890	0	NR
375	0	NR	505	299	NR	635	298	NR	765	8	NR	895	0	NR
380	0	NR	510	362	NR	640	266	NR	770	6	NR	900	0	NR
385	2	NR	515	418	NR	645	236	NR	775	6	NR	905	0	NR
390	4	NR	520	461	NR	650	209	NR	780	5	NR	910	0	NR
395	6	NR	525	491	NR	655	184	NR	785	4	NR	915	0	NR
400	9	NR	530	514	NR	660	160	NR	790	4	NR	920	0	NR
405	14	NR	535	530	NR	665	140	NR	795	3	NR	925	0	NR
410	27	NR	540	539	NR	670	122	NR	800	3	NR	930	0	NR
415	55	NR	545	549	NR	675	106	NR	805	2	NR	935	0	NR
420	115	NR	550	557	NR	680	92	NR	810	2	NR	940	0	NR
425	226	NR	555	565	NR	685	79	NR	815	2	NR	945	0	NR
430	395	NR	560	572	NR	690	68	NR	820	2	NR	950	0	NR
435	648	NR	565	580	NR	695	59	NR	825	1	NR	955	0	NR
440	937	NR	570	586	NR	700	51	NR	830	1	NR	960	0	NR
445	953	NR	575	588	NR	705	44	NR	835	1	NR	965	0	NR
450	591	NR	580	588	NR	710	38	NR	840	1	NR	970	0	NR
455	334	NR	585	580	NR	715	32	NR	845	1	NR	975	0	NR
460	221	NR	590	568	NR	720	28	NR	850	1	NR	980	0	NR
465	140	NR	595	550	NR	725	24	NR	855	1	NR	985	0	NR
470	93	NR	600	527	NR	730	21	NR	860	1	NR	990	0	NR
475	79	NR	605	499	NR	735	18	NR	865	0	NR	995	0	NR
480	76	NR	610	469	NR	740	15	NR	870	0	NR	1000	0	NR
485	87	NR	615	435	NR	745	13	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-6

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.7

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	118	NR	620	401	NR	750	12	NR	880	0	NR
365	0	NR	495	168	NR	625	365	NR	755	10	NR	885	0	NR
370	0	NR	500	230	NR	630	331	NR	760	9	NR	890	0	NR
375	0	NR	505	299	NR	635	298	NR	765	8	NR	895	0	NR
380	0	NR	510	362	NR	640	266	NR	770	6	NR	900	0	NR
385	2	NR	515	418	NR	645	236	NR	775	6	NR	905	0	NR
390	4	NR	520	461	NR	650	209	NR	780	5	NR	910	0	NR
395	6	NR	525	491	NR	655	184	NR	785	4	NR	915	0	NR
400	9	NR	530	514	NR	660	160	NR	790	4	NR	920	0	NR
405	14	NR	535	530	NR	665	140	NR	795	3	NR	925	0	NR
410	27	NR	540	539	NR	670	122	NR	800	3	NR	930	0	NR
415	55	NR	545	549	NR	675	106	NR	805	2	NR	935	0	NR
420	115	NR	550	557	NR	680	92	NR	810	2	NR	940	0	NR
425	226	NR	555	565	NR	685	79	NR	815	2	NR	945	0	NR
430	395	NR	560	572	NR	690	68	NR	820	2	NR	950	0	NR
435	648	NR	565	580	NR	695	59	NR	825	1	NR	955	0	NR
440	937	NR	570	586	NR	700	51	NR	830	1	NR	960	0	NR
445	953	NR	575	588	NR	705	44	NR	835	1	NR	965	0	NR
450	591	NR	580	588	NR	710	38	NR	840	1	NR	970	0	NR
455	334	NR	585	580	NR	715	32	NR	845	1	NR	975	0	NR
460	221	NR	590	568	NR	720	28	NR	850	1	NR	980	0	NR
465	140	NR	595	550	NR	725	24	NR	855	1	NR	985	0	NR
470	93	NR	600	527	NR	730	21	NR	860	1	NR	990	0	NR
475	79	NR	605	499	NR	735	18	NR	865	0	NR	995	0	NR
480	76	NR	610	469	NR	740	15	NR	870	0	NR	1000	0	NR
485	87	NR	615	435	NR	745	13	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-6

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 3.37


λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	118	NR	620	401	NR	750	12	NR	880	0	NR
365	0	NR	495	168	NR	625	365	NR	755	10	NR	885	0	NR
370	0	NR	500	230	NR	630	331	NR	760	9	NR	890	0	NR
375	0	NR	505	299	NR	635	298	NR	765	8	NR	895	0	NR
380	0	NR	510	362	NR	640	266	NR	770	6	NR	900	0	NR
385	2	NR	515	418	NR	645	236	NR	775	6	NR	905	0	NR
390	4	NR	520	461	NR	650	209	NR	780	5	NR	910	0	NR
395	6	NR	525	491	NR	655	184	NR	785	4	NR	915	0	NR
400	9	NR	530	514	NR	660	160	NR	790	4	NR	920	0	NR
405	14	NR	535	530	NR	665	140	NR	795	3	NR	925	0	NR
410	27	NR	540	539	NR	670	122	NR	800	3	NR	930	0	NR
415	55	NR	545	549	NR	675	106	NR	805	2	NR	935	0	NR
420	115	NR	550	557	NR	680	92	NR	810	2	NR	940	0	NR
425	226	NR	555	565	NR	685	79	NR	815	2	NR	945	0	NR
430	395	NR	560	572	NR	690	68	NR	820	2	NR	950	0	NR
435	648	NR	565	580	NR	695	59	NR	825	1	NR	955	0	NR
440	937	NR	570	586	NR	700	51	NR	830	1	NR	960	0	NR
445	953	NR	575	588	NR	705	44	NR	835	1	NR	965	0	NR
450	591	NR	580	588	NR	710	38	NR	840	1	NR	970	0	NR
455	334	NR	585	580	NR	715	32	NR	845	1	NR	975	0	NR
460	221	NR	590	568	NR	720	28	NR	850	1	NR	980	0	NR
465	140	NR	595	550	NR	725	24	NR	855	1	NR	985	0	NR
470	93	NR	600	527	NR	730	21	NR	860	1	NR	990	0	NR
475	79	NR	605	499	NR	735	18	NR	865	0	NR	995	0	NR
480	76	NR	610	469	NR	740	15	NR	870	0	NR	1000	0	NR
485	87	NR	615	435	NR	745	13	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-6





TM-30-18

Summary

$R_f = 70.7$
 $R_g = 96.8$
 $CIE R_a = 70.2$
 $R_g = -35.1$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 85	CES26 = 53	CES51 = 87	CES76 = 42
CES02 = 59	CES27 = 78	CES52 = 88	CES77 = 64
CES03 = 30	CES28 = 76	CES53 = 74	CES78 = 45
CES04 = 69	CES29 = 48	CES54 = 80	CES79 = 74
CES05 = 46	CES30 = 56	CES55 = 79	CES80 = 71
CES06 = 50	CES31 = 54	CES56 = 68	CES81 = 72
CES07 = 39	CES32 = 50	CES57 = 65	CES82 = 88
CES08 = 38	CES33 = 60	CES58 = 67	CES83 = 82
CES09 = 29	CES34 = 62	CES59 = 87	CES84 = 87
CES10 = 72	CES35 = 79	CES60 = 91	CES85 = 84
CES11 = 56	CES36 = 90	CES61 = 87	CES86 = 74
CES12 = 61	CES37 = 72	CES62 = 79	CES87 = 75
CES13 = 41	CES38 = 66	CES63 = 72	CES88 = 76
CES14 = 74	CES39 = 91	CES64 = 70	CES89 = 74
CES15 = 70	CES40 = 83	CES65 = 63	CES90 = 73
CES16 = 46	CES41 = 83	CES66 = 64	CES91 = 92
CES17 = 49	CES42 = 70	CES67 = 62	CES92 = 67
CES18 = 55	CES43 = 68	CES68 = 69	CES93 = 81
CES19 = 71	CES44 = 98	CES69 = 80	CES94 = 56
CES20 = 64	CES45 = 78	CES70 = 56	CES95 = 71
CES21 = 85	CES46 = 77	CES71 = 53	CES96 = 77
CES22 = 77	CES47 = 73	CES72 = 84	CES97 = 82
CES23 = 91	CES48 = 65	CES73 = 46	CES98 = 71
CES24 = 90	CES49 = 76	CES74 = 94	CES99 = 59
CES25 = 71	CES50 = 85	CES75 = 49	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)