

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066565

Luminaire Tested: **NVN-SA5A-750-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066565
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5A-750-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 615mA 5xLight Square PACKAGE
70CRI 5000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 5000K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 15315 lumens
Efficiency: N/A
Efficacy: 111.5 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 137.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3 fc
 Type III - Short - N/A

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	91.1	0.0	91.1
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	15223.9	0.0	15223.9
	% Fixture	99.4	0.0	99.4
Total	Lumens	15315.0	0.0	15315.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.5	0.0
10°-20°	22.5	0.1
20°-30°	285.8	1.9
30°-40°	963.4	6.3
40°-50°	2909.4	19.0
50°-60°	5133.1	33.5
60°-70°	4522.2	29.5
70°-80°	1439.5	9.4
80°-90°	34.6	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	15315.0	100.0
0°-180°	15315.0	100.0



REPORT NUMBER: P1066565


CATALOG NUMBER: NVN-SA5A-750-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	299.2	2.0			
FM	(30°-60°)	8970.5	58.6			
FH	(60°-80°)	5926.1	38.7			G3/7500
FVH	(80°-90°)	28.2	0.2			G1/100
BL	(0°-30°)	13.7	0.1	B0/110		
BM	(30°-60°)	35.3	0.2	B0/220		
BH	(60°-80°)	35.7	0.2	B0/110		G0/110
BVH	(80°-90°)	6.5	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	38.4	38.4	38.4	38.4	38.4	38.4	38.4	38.4	38.4	38.4	33.6
5°	48.0	48.0	48.0	43.2	43.2	43.2	38.4	38.4	38.4	38.4	38.4
7.5°	57.6	52.8	52.8	48.0	48.0	48.0	43.2	43.2	43.2	43.2	38.4
10°	67.2	62.4	62.4	57.6	57.6	52.8	52.8	48.0	48.0	43.2	43.2
12.5°	76.8	72.0	67.2	62.4	62.4	57.6	57.6	52.8	52.8	48.0	48.0
15°	86.4	81.6	76.8	72.0	67.2	67.2	62.4	57.6	52.8	52.8	48.0
17.5°	100.9	91.3	86.4	76.8	72.0	67.2	62.4	57.6	57.6	52.8	52.8
20°	105.7	96.1	91.3	81.6	76.8	72.0	67.2	62.4	57.6	57.6	52.8
22.5°	124.9	105.7	100.9	91.3	86.4	81.6	72.0	67.2	62.4	57.6	52.8
25°	153.7	124.9	110.5	96.1	91.3	81.6	76.8	67.2	62.4	57.6	52.8
27.5°	187.3	139.3	124.9	105.7	96.1	86.4	76.8	67.2	62.4	57.6	52.8
30°	230.5	163.3	139.3	115.3	105.7	96.1	81.6	72.0	67.2	62.4	52.8
32.5°	321.8	201.7	163.3	124.9	110.5	100.9	86.4	72.0	67.2	62.4	52.8
35°	389.0	244.9	196.9	144.1	124.9	110.5	91.3	72.0	67.2	62.4	52.8
37.5°	451.5	249.7	201.7	153.7	134.5	115.3	91.3	72.0	67.2	62.4	52.8
40°	552.3	259.3	201.7	144.1	129.7	110.5	96.1	76.8	72.0	62.4	57.6
42.5°	744.4	297.8	216.1	134.5	120.1	110.5	96.1	81.6	72.0	67.2	57.6
45°	1239.1	441.9	293.0	139.3	124.9	110.5	96.1	81.6	76.8	67.2	62.4
47.5°	2108.4	768.4	456.3	144.1	129.7	110.5	96.1	76.8	72.0	67.2	57.6
50°	2699.2	984.6	576.3	168.1	144.1	124.9	100.9	76.8	72.0	67.2	62.4
52.5°	2867.3	1047.0	624.4	196.9	168.1	139.3	105.7	76.8	72.0	72.0	67.2
55°	2627.1	1018.2	624.4	230.5	192.1	158.5	120.1	81.6	76.8	76.8	72.0
57.5°	2233.3	941.3	595.5	249.7	211.3	168.1	129.7	86.4	81.6	81.6	76.8
60°	1839.5	792.5	537.9	278.6	235.3	192.1	148.9	105.7	100.9	96.1	86.4
62.5°	1460.0	638.8	470.7	297.8	254.5	206.5	163.3	115.3	110.5	105.7	100.9
65°	1099.8	557.1	437.1	312.2	264.2	216.1	168.1	120.1	115.3	115.3	110.5
67.5°	845.3	509.1	417.8	321.8	273.8	225.7	177.7	129.7	124.9	120.1	115.3
70°	667.6	470.7	393.8	317.0	273.8	230.5	182.5	139.3	129.7	124.9	115.3
72.5°	557.1	427.4	365.0	302.6	269.0	235.3	201.7	168.1	148.9	134.5	115.3
75°	465.9	384.2	331.4	273.8	249.7	230.5	206.5	182.5	158.5	134.5	110.5
77.5°	307.4	278.6	254.5	230.5	216.1	201.7	182.5	168.1	144.1	124.9	100.9
80°	129.7	120.1	124.9	124.9	124.9	124.9	120.1	120.1	105.7	91.3	72.0
82.5°	28.8	24.0	28.8	28.8	28.8	28.8	24.0	24.0	24.0	19.2	19.2
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6
5°	38.4	38.4	38.4	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6
7.5°	38.4	38.4	38.4	33.6	33.6	33.6	33.6	28.8	28.8	28.8	28.8
10°	38.4	38.4	38.4	33.6	33.6	33.6	33.6	28.8	28.8	28.8	28.8
12.5°	43.2	43.2	38.4	38.4	33.6	33.6	33.6	28.8	28.8	28.8	28.8
15°	43.2	43.2	38.4	38.4	33.6	33.6	33.6	28.8	28.8	28.8	28.8
17.5°	48.0	43.2	43.2	38.4	33.6	33.6	33.6	28.8	28.8	28.8	28.8
20°	48.0	43.2	43.2	38.4	33.6	33.6	33.6	28.8	28.8	28.8	28.8
22.5°	48.0	43.2	43.2	38.4	33.6	33.6	28.8	28.8	24.0	24.0	19.2
25°	48.0	43.2	43.2	38.4	33.6	33.6	28.8	28.8	24.0	19.2	19.2
27.5°	48.0	43.2	43.2	38.4	33.6	28.8	28.8	24.0	19.2	14.4	14.4
30°	48.0	43.2	43.2	38.4	33.6	28.8	24.0	19.2	14.4	14.4	9.6
32.5°	48.0	43.2	38.4	33.6	28.8	24.0	24.0	19.2	14.4	9.6	9.6
35°	48.0	43.2	38.4	33.6	28.8	24.0	24.0	19.2	14.4	9.6	9.6
37.5°	48.0	43.2	38.4	33.6	28.8	24.0	19.2	14.4	9.6	9.6	4.8
40°	48.0	43.2	38.4	33.6	28.8	24.0	19.2	14.4	9.6	9.6	4.8
42.5°	48.0	43.2	38.4	33.6	28.8	24.0	19.2	14.4	9.6	9.6	4.8
45°	52.8	48.0	43.2	33.6	28.8	24.0	24.0	19.2	14.4	9.6	9.6
47.5°	52.8	48.0	43.2	33.6	28.8	24.0	24.0	19.2	14.4	9.6	9.6
50°	57.6	52.8	48.0	38.4	33.6	28.8	24.0	14.4	9.6	9.6	4.8
52.5°	62.4	57.6	52.8	48.0	43.2	33.6	24.0	14.4	4.8	4.8	4.8
55°	67.2	62.4	62.4	57.6	52.8	38.4	28.8	14.4	0.0	0.0	0.0
57.5°	72.0	67.2	67.2	62.4	57.6	43.2	28.8	14.4	0.0	0.0	0.0
60°	81.6	76.8	72.0	62.4	57.6	43.2	28.8	14.4	0.0	0.0	0.0
62.5°	96.1	86.4	72.0	62.4	48.0	38.4	24.0	14.4	0.0	0.0	0.0
65°	105.7	91.3	76.8	57.6	43.2	33.6	24.0	9.6	0.0	0.0	0.0
67.5°	110.5	91.3	76.8	57.6	38.4	28.8	19.2	9.6	0.0	0.0	0.0
70°	105.7	86.4	72.0	52.8	33.6	24.0	19.2	9.6	0.0	0.0	0.0
72.5°	96.1	81.6	62.4	48.0	28.8	24.0	14.4	9.6	0.0	0.0	0.0
75°	86.4	72.0	52.8	38.4	19.2	14.4	9.6	4.8	0.0	0.0	0.0
77.5°	76.8	62.4	43.2	28.8	9.6	9.6	4.8	4.8	0.0	0.0	0.0
80°	57.6	43.2	28.8	14.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	14.4	9.6	9.6	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	28.8	28.8	28.8	28.8	28.8	28.8	28.8	28.8	28.8	28.8	28.8
5°	28.8	28.8	28.8	28.8	24.0	24.0	24.0	24.0	24.0	24.0	24.0
7.5°	28.8	28.8	28.8	28.8	24.0	24.0	24.0	24.0	19.2	19.2	19.2
10°	24.0	24.0	24.0	24.0	24.0	24.0	24.0	24.0	19.2	19.2	19.2
12.5°	24.0	24.0	24.0	24.0	24.0	24.0	24.0	24.0	19.2	19.2	19.2
15°	24.0	24.0	24.0	24.0	24.0	24.0	24.0	19.2	19.2	14.4	14.4
17.5°	24.0	24.0	24.0	24.0	19.2	19.2	19.2	14.4	14.4	9.6	9.6
20°	24.0	24.0	24.0	19.2	19.2	14.4	14.4	9.6	9.6	4.8	4.8
22.5°	19.2	14.4	14.4	9.6	9.6	4.8	4.8	4.8	0.0	0.0	0.0
25°	14.4	9.6	9.6	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	9.6	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	9.6	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	28.8	24.0	24.0	24.0	24.0	24.0	24.0	24.0	24.0	24.0	24.0
5°	24.0	24.0	24.0	24.0	19.2	19.2	19.2	19.2	19.2	19.2	19.2
7.5°	19.2	19.2	19.2	19.2	19.2	19.2	14.4	14.4	14.4	14.4	14.4
10°	19.2	14.4	14.4	14.4	14.4	14.4	14.4	14.4	14.4	9.6	9.6
12.5°	19.2	14.4	14.4	14.4	9.6	9.6	9.6	9.6	9.6	4.8	4.8
15°	14.4	9.6	9.6	9.6	4.8	4.8	4.8	4.8	4.8	0.0	0.0
17.5°	9.6	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	24.0	24.0	24.0	24.0	24.0	24.0	24.0	24.0	24.0	28.8	28.8
5°	19.2	19.2	19.2	19.2	19.2	19.2	19.2	19.2	19.2	19.2	19.2
7.5°	14.4	14.4	14.4	14.4	14.4	14.4	14.4	14.4	14.4	14.4	14.4
10°	9.6	9.6	9.6	9.6	9.6	9.6	4.8	4.8	4.8	4.8	4.8
12.5°	4.8	4.8	4.8	4.8	4.8	4.8	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	28.8	28.8	28.8	28.8	28.8	33.6	33.6	38.4	38.4	43.2	43.2
5°	19.2	19.2	24.0	24.0	24.0	24.0	28.8	28.8	28.8	33.6	33.6
7.5°	14.4	14.4	14.4	14.4	14.4	19.2	19.2	24.0	24.0	28.8	28.8
10°	4.8	4.8	9.6	9.6	9.6	9.6	14.4	14.4	14.4	19.2	24.0
12.5°	0.0	0.0	4.8	4.8	4.8	4.8	9.6	9.6	9.6	14.4	19.2
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	9.6	14.4
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	9.6
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	48.0	48.0	52.8	52.8	57.6	57.6	62.4	62.4	62.4	62.4	62.4
5°	38.4	38.4	43.2	48.0	48.0	52.8	57.6	57.6	57.6	57.6	57.6
7.5°	33.6	33.6	38.4	43.2	43.2	48.0	52.8	52.8	57.6	57.6	57.6
10°	24.0	28.8	33.6	38.4	38.4	43.2	48.0	48.0	52.8	52.8	52.8
12.5°	19.2	24.0	28.8	33.6	33.6	38.4	43.2	43.2	48.0	48.0	52.8
15°	14.4	19.2	24.0	28.8	28.8	33.6	38.4	38.4	43.2	48.0	52.8
17.5°	9.6	14.4	19.2	24.0	24.0	28.8	33.6	38.4	43.2	43.2	48.0
20°	9.6	9.6	14.4	19.2	19.2	24.0	28.8	33.6	38.4	38.4	43.2
22.5°	4.8	4.8	9.6	14.4	14.4	19.2	24.0	28.8	33.6	33.6	38.4
25°	0.0	0.0	4.8	9.6	9.6	14.4	19.2	19.2	24.0	24.0	28.8
27.5°	0.0	0.0	4.8	4.8	9.6	9.6	14.4	14.4	19.2	19.2	24.0
30°	0.0	0.0	4.8	4.8	9.6	9.6	14.4	14.4	19.2	19.2	19.2
32.5°	0.0	0.0	0.0	4.8	4.8	4.8	9.6	9.6	14.4	14.4	19.2
35°	0.0	0.0	0.0	4.8	4.8	4.8	9.6	9.6	14.4	14.4	14.4
37.5°	0.0	0.0	0.0	4.8	4.8	4.8	9.6	9.6	9.6	9.6	14.4
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.6	9.6	9.6
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.6	9.6	9.6
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.6	9.6	9.6
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.6	9.6	9.6
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.6	9.6	9.6
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.6	9.6	9.6
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	9.6	9.6	9.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	9.6
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	62.4	62.4
5°	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	57.6	57.6
7.5°	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	57.6	57.6
10°	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6
12.5°	52.8	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6
15°	52.8	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6
17.5°	48.0	52.8	52.8	52.8	57.6	57.6	57.6	57.6	57.6	57.6	57.6
20°	43.2	48.0	48.0	48.0	52.8	52.8	52.8	52.8	57.6	57.6	57.6
22.5°	38.4	43.2	43.2	43.2	48.0	48.0	48.0	48.0	52.8	52.8	52.8
25°	33.6	33.6	38.4	38.4	43.2	43.2	43.2	43.2	43.2	43.2	43.2
27.5°	24.0	28.8	28.8	28.8	33.6	33.6	33.6	33.6	38.4	38.4	38.4
30°	24.0	24.0	24.0	24.0	28.8	28.8	28.8	28.8	33.6	33.6	33.6
32.5°	19.2	24.0	24.0	24.0	28.8	28.8	28.8	28.8	33.6	33.6	33.6
35°	19.2	19.2	19.2	19.2	24.0	24.0	24.0	24.0	28.8	28.8	28.8
37.5°	14.4	19.2	19.2	19.2	24.0	24.0	24.0	24.0	28.8	28.8	28.8
40°	14.4	14.4	14.4	14.4	19.2	19.2	19.2	19.2	24.0	24.0	24.0
42.5°	14.4	14.4	14.4	14.4	19.2	19.2	19.2	19.2	24.0	24.0	24.0
45°	14.4	14.4	14.4	14.4	19.2	19.2	19.2	19.2	24.0	24.0	24.0
47.5°	14.4	14.4	14.4	14.4	19.2	19.2	19.2	19.2	24.0	24.0	24.0
50°	14.4	14.4	14.4	14.4	19.2	19.2	19.2	19.2	24.0	24.0	24.0
52.5°	9.6	9.6	9.6	9.6	14.4	14.4	14.4	14.4	19.2	19.2	19.2
55°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	14.4	14.4	14.4
57.5°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	14.4	14.4	14.4
60°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
62.5°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
65°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	4.8	4.8
67.5°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
70°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
72.5°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
75°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
77.5°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
80°	14.4	14.4	14.4	14.4	14.4	9.6	9.6	9.6	9.6	9.6	9.6
82.5°	9.6	14.4	14.4	14.4	14.4	9.6	9.6	9.6	9.6	9.6	9.6
85°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
87.5°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	62.4	62.4	57.6	57.6	57.6	57.6	57.6	57.6	57.6	62.4	62.4
5°	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	62.4	62.4
7.5°	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	62.4	62.4
10°	57.6	57.6	57.6	57.6	52.8	52.8	57.6	57.6	57.6	62.4	62.4
12.5°	57.6	57.6	57.6	57.6	52.8	52.8	57.6	57.6	62.4	62.4	67.2
15°	57.6	57.6	52.8	52.8	52.8	52.8	57.6	57.6	62.4	62.4	67.2
17.5°	57.6	57.6	52.8	52.8	52.8	52.8	57.6	57.6	62.4	62.4	67.2
20°	57.6	57.6	52.8	52.8	52.8	52.8	52.8	52.8	57.6	62.4	62.4
22.5°	52.8	52.8	52.8	52.8	48.0	48.0	52.8	52.8	57.6	62.4	62.4
25°	43.2	48.0	48.0	48.0	48.0	48.0	52.8	52.8	57.6	62.4	62.4
27.5°	38.4	43.2	43.2	43.2	43.2	48.0	48.0	52.8	57.6	62.4	62.4
30°	33.6	38.4	38.4	38.4	43.2	48.0	48.0	52.8	57.6	62.4	62.4
32.5°	33.6	38.4	38.4	38.4	43.2	43.2	48.0	48.0	52.8	57.6	62.4
35°	33.6	33.6	38.4	38.4	38.4	43.2	43.2	48.0	52.8	57.6	62.4
37.5°	33.6	33.6	38.4	38.4	38.4	43.2	43.2	48.0	52.8	57.6	62.4
40°	28.8	33.6	33.6	38.4	38.4	43.2	43.2	48.0	52.8	62.4	67.2
42.5°	28.8	28.8	33.6	33.6	38.4	43.2	43.2	48.0	52.8	62.4	67.2
45°	28.8	33.6	33.6	38.4	43.2	48.0	48.0	52.8	57.6	62.4	67.2
47.5°	28.8	33.6	33.6	38.4	48.0	48.0	52.8	52.8	57.6	62.4	67.2
50°	28.8	33.6	33.6	38.4	52.8	52.8	52.8	52.8	57.6	62.4	67.2
52.5°	24.0	28.8	28.8	33.6	43.2	48.0	52.8	57.6	62.4	67.2	72.0
55°	19.2	24.0	24.0	28.8	38.4	43.2	52.8	62.4	67.2	72.0	76.8
57.5°	19.2	19.2	24.0	24.0	33.6	43.2	57.6	67.2	72.0	76.8	81.6
60°	14.4	14.4	19.2	19.2	28.8	38.4	52.8	67.2	72.0	81.6	86.4
62.5°	9.6	14.4	14.4	19.2	24.0	38.4	52.8	67.2	76.8	86.4	91.3
65°	9.6	9.6	14.4	14.4	24.0	33.6	48.0	57.6	72.0	86.4	100.9
67.5°	14.4	14.4	19.2	19.2	24.0	33.6	48.0	57.6	72.0	91.3	105.7
70°	14.4	14.4	19.2	19.2	28.8	38.4	48.0	57.6	72.0	91.3	105.7
72.5°	14.4	14.4	19.2	19.2	28.8	33.6	43.2	52.8	67.2	81.6	96.1
75°	9.6	14.4	14.4	14.4	24.0	28.8	38.4	48.0	62.4	76.8	91.3
77.5°	9.6	9.6	9.6	9.6	19.2	24.0	33.6	38.4	52.8	67.2	81.6
80°	9.6	9.6	9.6	9.6	14.4	19.2	28.8	33.6	48.0	62.4	76.8
82.5°	9.6	9.6	4.8	4.8	9.6	14.4	19.2	24.0	38.4	48.0	62.4
85°	9.6	9.6	4.8	4.8	4.8	9.6	9.6	14.4	19.2	24.0	28.8
87.5°	9.6	9.6	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	62.4	62.4	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2
5°	62.4	67.2	67.2	72.0	72.0	72.0	76.8	76.8	76.8	76.8	76.8
7.5°	62.4	67.2	67.2	72.0	72.0	72.0	76.8	76.8	76.8	81.6	81.6
10°	62.4	67.2	67.2	72.0	72.0	76.8	81.6	81.6	86.4	86.4	86.4
12.5°	67.2	72.0	72.0	76.8	76.8	81.6	86.4	86.4	91.3	96.1	96.1
15°	67.2	72.0	76.8	76.8	81.6	86.4	91.3	91.3	96.1	100.9	105.7
17.5°	67.2	72.0	76.8	76.8	81.6	86.4	96.1	100.9	105.7	115.3	120.1
20°	67.2	72.0	76.8	76.8	81.6	91.3	96.1	105.7	110.5	120.1	129.7
22.5°	67.2	72.0	76.8	81.6	86.4	96.1	105.7	110.5	120.1	134.5	144.1
25°	67.2	72.0	76.8	81.6	86.4	96.1	105.7	115.3	124.9	144.1	163.3
27.5°	67.2	72.0	81.6	86.4	91.3	100.9	115.3	124.9	134.5	168.1	201.7
30°	67.2	72.0	81.6	86.4	91.3	105.7	120.1	129.7	144.1	201.7	254.5
32.5°	67.2	76.8	81.6	91.3	96.1	110.5	129.7	144.1	158.5	240.1	317.0
35°	67.2	76.8	81.6	91.3	96.1	115.3	134.5	153.7	172.9	293.0	413.0
37.5°	67.2	76.8	81.6	91.3	96.1	124.9	153.7	182.5	211.3	336.2	461.1
40°	72.0	81.6	86.4	96.1	100.9	129.7	158.5	187.3	216.1	341.0	465.9
42.5°	72.0	81.6	86.4	96.1	100.9	124.9	153.7	177.7	201.7	341.0	480.3
45°	72.0	81.6	91.3	96.1	105.7	129.7	153.7	172.9	196.9	374.6	547.5
47.5°	72.0	81.6	91.3	96.1	105.7	129.7	153.7	177.7	201.7	494.7	782.9
50°	72.0	81.6	91.3	96.1	105.7	134.5	163.3	192.1	220.9	739.6	1258.3
52.5°	76.8	81.6	91.3	96.1	100.9	134.5	168.1	201.7	235.3	960.6	1681.0
55°	81.6	86.4	91.3	96.1	100.9	144.1	187.3	230.5	273.8	1032.6	1786.6
57.5°	86.4	91.3	96.1	96.1	100.9	153.7	211.3	264.2	317.0	1027.8	1733.8
60°	91.3	96.1	100.9	105.7	110.5	163.3	220.9	273.8	326.6	931.7	1536.9
62.5°	100.9	110.5	120.1	124.9	134.5	187.3	235.3	288.2	336.2	763.6	1186.3
65°	115.3	124.9	129.7	139.3	144.1	192.1	244.9	293.0	341.0	634.0	922.1
67.5°	120.1	129.7	134.5	144.1	148.9	196.9	244.9	293.0	341.0	537.9	730.0
70°	120.1	129.7	139.3	144.1	153.7	201.7	244.9	293.0	336.2	465.9	595.5
72.5°	110.5	124.9	134.5	148.9	158.5	201.7	240.1	283.4	321.8	413.0	504.3
75°	105.7	124.9	139.3	158.5	172.9	201.7	235.3	264.2	293.0	360.2	427.4
77.5°	96.1	120.1	144.1	168.1	192.1	211.3	225.7	244.9	259.3	302.6	345.8
80°	91.3	115.3	139.3	163.3	187.3	196.9	201.7	211.3	216.1	220.9	225.7
82.5°	72.0	91.3	110.5	124.9	144.1	134.5	129.7	120.1	110.5	105.7	100.9
85°	33.6	38.4	38.4	43.2	43.2	43.2	38.4	38.4	33.6	28.8	24.0
87.5°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	67.2	67.2	67.2	67.2	62.4	62.4	62.4	62.4	57.6	57.6	57.6
5°	76.8	76.8	76.8	76.8	72.0	72.0	72.0	72.0	67.2	67.2	67.2
7.5°	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6
10°	91.3	91.3	91.3	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
12.5°	100.9	100.9	105.7	105.7	110.5	110.5	115.3	115.3	120.1	120.1	120.1
15°	110.5	115.3	120.1	124.9	124.9	129.7	134.5	139.3	144.1	148.9	153.7
17.5°	129.7	134.5	144.1	153.7	163.3	172.9	187.3	206.5	220.9	235.3	254.5
20°	144.1	158.5	187.3	220.9	249.7	278.6	350.6	422.6	494.7	566.7	638.8
22.5°	172.9	201.7	297.8	398.6	494.7	590.7	816.5	1042.2	1263.1	1488.9	1690.6
25°	230.5	293.0	513.9	734.8	950.9	1171.9	1575.3	1983.5	2387.0	2790.4	3165.0
27.5°	317.0	432.2	792.5	1157.5	1517.7	1877.9	2463.8	3054.6	3640.5	4231.2	4754.7
30°	441.9	629.2	1167.1	1709.8	2247.7	2785.6	3525.2	4269.7	5009.3	5748.9	6229.2
32.5°	600.3	878.9	1560.9	2242.9	2924.9	3606.9	4423.4	5239.8	6051.5	6868.0	7377.1
35°	768.4	1123.8	1945.1	2771.2	3592.5	4418.6	5278.2	6137.9	6997.6	7857.3	8481.7
37.5°	864.5	1267.9	2242.9	3217.9	4188.0	5163.0	6104.3	7050.5	7991.8	8933.2	9692.0
40°	955.8	1440.8	2564.7	3688.5	4812.4	5936.2	7036.1	8135.9	9235.7	10335.6	11310.5
42.5°	1090.2	1700.2	3011.3	4322.5	5628.8	6940.0	8385.6	9836.1	11281.7	12727.3	14225.8
45°	1368.8	2190.1	3890.2	5590.4	7285.8	8986.0	11036.8	13092.4	15143.1	17198.7	19119.8
47.5°	2041.2	3294.7	5614.4	7934.2	10253.9	12573.7	14936.6	17299.6	19662.5	22025.5	24311.6
50°	3160.2	5057.3	7958.2	10859.1	13755.1	16656.0	19014.2	21372.3	23725.7	26083.9	28355.6
52.5°	4212.0	6743.1	9860.1	12981.9	16098.9	19220.7	21309.9	23399.1	25488.3	27577.5	29777.2
55°	4572.2	7353.0	10508.5	13668.7	16824.1	19984.3	21996.7	24013.9	26026.2	28038.6	30319.9
57.5°	4255.3	6776.7	9956.1	13135.6	16310.2	19489.6	21737.3	23989.8	26237.5	28490.0	30934.7
60°	3563.7	5585.6	8923.6	12266.3	15604.2	18942.1	21478.0	24013.9	26549.7	29085.6	31525.4
62.5°	2824.0	4457.0	7991.8	11526.7	15061.5	18596.3	21175.4	23759.3	26338.4	28917.5	30790.6
65°	2166.1	3410.0	6887.2	10369.2	13846.4	17328.4	19441.6	21559.6	23672.9	25790.9	27087.6
67.5°	1608.9	2487.8	5528.0	8572.9	11613.1	14653.3	16209.4	17770.3	19326.4	20887.3	21895.8
70°	1186.3	1772.2	3842.2	5912.2	7977.4	10047.4	11473.8	12900.2	14321.9	15748.3	16795.3
72.5°	821.3	1133.5	2372.6	3616.5	4855.6	6094.7	7540.4	8986.0	10426.8	11872.5	13063.5
75°	561.9	696.4	1277.5	1858.7	2439.8	3020.9	4116.0	5211.0	6306.0	7401.1	8030.2
77.5°	417.8	489.9	662.8	840.5	1013.4	1186.3	1397.6	1608.9	1820.3	2031.6	2305.3
80°	230.5	230.5	254.5	273.8	297.8	317.0	374.6	437.1	494.7	557.1	634.0
82.5°	105.7	110.5	120.1	129.7	134.5	144.1	153.7	163.3	172.9	182.5	182.5
85°	28.8	33.6	33.6	28.8	28.8	24.0	24.0	28.8	28.8	28.8	28.8
87.5°	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	57.6	52.8	52.8	52.8	48.0	48.0	48.0	48.0	48.0	48.0	48.0
5°	67.2	67.2	67.2	67.2	62.4	62.4	62.4	62.4	62.4	57.6	57.6
7.5°	81.6	76.8	76.8	76.8	76.8	76.8	76.8	76.8	76.8	72.0	72.0
10°	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	91.3	91.3
12.5°	120.1	120.1	120.1	120.1	124.9	124.9	120.1	120.1	120.1	115.3	115.3
15°	158.5	163.3	168.1	168.1	172.9	172.9	172.9	168.1	168.1	163.3	158.5
17.5°	269.0	283.4	302.6	321.8	341.0	355.4	355.4	345.8	336.2	326.6	317.0
20°	715.6	787.7	864.5	941.3	1023.0	1080.6	1042.2	1013.4	984.6	950.9	922.1
22.5°	1897.1	2098.8	2305.3	2449.4	2593.5	2694.4	2612.7	2454.2	2295.7	2142.0	1983.5
25°	3539.6	3909.5	4284.1	4437.8	4596.3	4711.5	4658.7	4418.6	4178.4	3943.1	3702.9
27.5°	5278.2	5796.9	6320.4	6454.9	6589.4	6690.3	6671.1	6358.9	6046.7	5734.5	5422.3
30°	6709.5	7189.7	7670.0	7804.5	7939.0	8030.2	7929.4	7617.2	7305.0	6992.8	6680.7
32.5°	7891.0	8400.0	8913.9	9091.6	9269.4	9389.4	9269.4	8894.7	8520.1	8150.3	7775.7
35°	9106.1	9725.6	10350.0	10575.7	10801.4	10945.5	10743.8	10282.7	9821.7	9365.4	8904.3
37.5°	10450.8	11204.9	11963.7	12271.1	12583.3	12799.4	12645.7	12069.4	11488.2	10911.9	10330.8
40°	12290.3	13265.3	14245.0	14797.3	15344.9	15733.9	15460.1	14792.5	14120.1	13452.6	12780.2
42.5°	15729.1	17227.5	18726.0	19518.5	20306.1	20877.7	20570.3	19749.0	18927.7	18106.5	17285.2
45°	21040.9	22957.3	24878.4	26035.8	27198.1	28053.0	27697.6	26665.0	25627.6	24595.0	23562.4
47.5°	26597.8	28883.9	31170.0	32092.1	33019.1	33739.5	33653.0	32365.9	31078.7	29796.4	28509.3
50°	30632.1	32903.8	35175.5	35968.0	36765.2	37356.0	37135.0	35497.3	33854.7	32217.0	30574.4
52.5°	31976.9	34171.7	36371.4	37317.5	38263.7	38969.7	38700.7	36856.5	35012.2	33172.7	31328.5
55°	32601.2	34882.5	37163.8	38316.5	39474.0	40319.3	39930.2	37908.3	35881.5	33859.5	31832.8
57.5°	33379.3	35823.9	38268.5	39531.6	40794.7	41707.3	41188.6	39094.6	37000.6	34911.3	32817.3
60°	33965.2	36400.2	38840.0	39853.4	40871.6	41582.4	41082.9	39046.5	37005.4	34969.0	32932.6
62.5°	32668.5	34541.5	36414.6	37168.7	37922.7	38470.2	38186.8	36256.1	34325.4	32394.7	30464.0
65°	28389.2	29685.9	30987.5	31496.6	32000.9	32389.9	32303.4	30675.3	29047.2	27423.8	25795.7
67.5°	22909.2	23917.8	24931.2	25651.6	26376.8	26938.7	26876.3	25392.3	23908.2	22424.1	20940.1
70°	17847.1	18894.1	19941.1	20848.8	21761.4	22467.4	22376.1	20997.7	19614.5	18236.1	16852.9
72.5°	14259.4	15450.5	16641.6	17160.3	17679.0	18044.0	17775.1	16732.9	15685.9	14643.7	13596.6
75°	8659.4	9283.8	9912.9	9908.1	9908.1	9850.5	9581.5	8986.0	8390.4	7794.9	7199.4
77.5°	2579.1	2852.8	3126.6	3390.8	3659.7	3861.4	3808.6	3496.4	3179.4	2867.3	2550.3
80°	710.8	782.9	859.7	893.3	926.9	970.2	1080.6	1003.8	926.9	854.9	778.0
82.5°	182.5	182.5	182.5	177.7	172.9	163.3	148.9	139.3	129.7	120.1	110.5
85°	28.8	24.0	24.0	24.0	19.2	19.2	19.2	19.2	14.4	14.4	9.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
2.5°	48.0	48.0	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2	38.4
5°	57.6	57.6	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	48.0
7.5°	72.0	72.0	67.2	67.2	67.2	67.2	62.4	62.4	62.4	62.4	57.6
10°	91.3	86.4	86.4	81.6	81.6	81.6	76.8	76.8	76.8	72.0	72.0
12.5°	115.3	110.5	110.5	105.7	100.9	100.9	96.1	91.3	86.4	86.4	81.6
15°	153.7	148.9	144.1	139.3	134.5	124.9	120.1	110.5	105.7	100.9	96.1
17.5°	293.0	269.0	244.9	220.9	201.7	182.5	163.3	144.1	134.5	124.9	115.3
20°	816.5	706.0	600.3	494.7	427.4	360.2	293.0	225.7	196.9	172.9	144.1
22.5°	1767.4	1546.5	1330.4	1109.4	931.7	758.8	581.1	403.4	336.2	273.8	206.5
25°	3285.1	2862.5	2444.6	2022.0	1685.8	1349.6	1013.4	677.2	552.3	427.4	302.6
27.5°	4874.8	4327.3	3779.8	3232.3	2699.2	2161.2	1623.3	1090.2	874.1	662.8	446.7
30°	6099.5	5518.4	4942.1	4360.9	3688.5	3016.1	2338.9	1666.6	1325.6	984.6	638.8
32.5°	7151.3	6522.2	5897.8	5268.6	4490.6	3712.5	2934.5	2156.4	1729.0	1301.6	869.3
35°	8193.5	7477.9	6767.1	6051.5	5215.8	4380.1	3544.4	2708.8	2166.1	1623.3	1075.8
37.5°	9461.5	8587.4	7718.1	6848.8	5989.1	5134.2	4274.5	3414.8	2723.2	2036.4	1344.8
40°	11670.7	10556.5	9447.1	8332.8	7329.0	6330.1	5326.3	4322.5	3453.2	2583.9	1709.8
42.5°	15887.6	14490.0	13097.2	11699.6	10311.6	8923.6	7530.7	6142.7	4903.6	3669.3	2430.2
45°	21771.0	19979.5	18192.9	16401.5	14691.7	12986.7	11276.9	9567.1	7684.4	5801.7	3914.3
47.5°	26549.7	24585.4	22625.9	20661.5	18764.4	16872.1	14975.0	13077.9	10667.0	8260.8	5849.8
50°	28706.2	26833.1	24964.8	23091.7	21189.8	19283.1	17376.4	15474.5	12708.1	9946.5	7180.1
52.5°	29431.4	27529.5	25632.4	23730.5	21843.0	19955.5	18068.0	16180.5	13303.7	10431.6	7554.8
55°	29830.0	27822.5	25819.7	23812.1	21780.6	19744.2	17707.8	15676.2	12813.8	9956.1	7093.7
57.5°	30636.9	28451.6	26271.2	24085.9	21771.0	19456.0	17136.3	14821.4	11997.3	9173.3	6349.3
60°	30785.8	28634.1	26487.3	24340.4	21780.6	19220.7	16656.0	14096.1	11291.3	8491.3	5686.5
62.5°	28667.7	26871.5	25080.1	23283.8	20719.2	18154.5	15585.0	13020.3	10335.6	7650.8	4961.3
65°	24244.4	22693.1	21146.6	19595.3	17501.3	15412.1	13318.1	11224.1	8827.5	6435.7	4039.1
67.5°	19422.4	17904.7	16391.9	14874.2	13298.9	11728.4	10153.1	8577.8	6728.7	4879.6	3030.5
70°	15397.7	13937.6	12482.4	11022.4	9629.6	8232.0	6834.3	5441.5	4293.7	3150.6	2002.8
72.5°	12203.8	10806.2	9413.4	8015.8	6752.7	5489.6	4226.4	2963.3	2391.8	1825.1	1253.5
75°	6474.1	5748.9	5028.5	4303.3	3592.5	2876.9	2161.2	1450.4	1224.7	999.0	768.4
77.5°	2233.3	1916.3	1604.1	1287.1	1071.0	854.9	638.8	422.6	398.6	379.4	355.4
80°	677.2	576.3	475.5	374.6	331.4	288.2	244.9	201.7	187.3	172.9	153.7
82.5°	105.7	96.1	91.3	81.6	76.8	76.8	72.0	67.2	57.6	52.8	43.2
85°	9.6	4.8	4.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066565
 CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	43.2	43.2
2.5°	38.4	38.4
5°	48.0	48.0
7.5°	57.6	57.6
10°	67.2	67.2
12.5°	76.8	76.8
15°	91.3	86.4
17.5°	105.7	100.9
20°	115.3	105.7
22.5°	139.3	120.1
25°	177.7	148.9
27.5°	230.5	182.5
30°	297.8	230.5
32.5°	441.9	321.8
35°	533.1	389.0
37.5°	653.2	451.5
40°	840.5	547.5
42.5°	1191.1	744.4
45°	2031.6	1234.3
47.5°	3443.6	2103.6
50°	4413.7	2699.2
52.5°	4682.7	2862.5
55°	4236.0	2627.1
57.5°	3525.2	2233.3
60°	2886.5	1839.5
62.5°	2276.5	1455.2
65°	1642.5	1099.8
67.5°	1181.5	845.3
70°	859.7	662.8
72.5°	682.0	552.3
75°	542.7	461.1
77.5°	336.2	307.4
80°	139.3	129.7
82.5°	33.6	28.8
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066565

CATALOG NUMBER: NVN-SA5A-750-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-6

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-750-U-5WQ

Data in this report applies to families of products including GSS-SB1A-750-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-6
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-750-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI
 5000K CCT 26 LEDS

Spectral Parameters

CCT (K):	4896	CRI (Ra):	70.2		
CIE u':	0.2101	R1:	68.1	R9:	-35.1
CIE v':	0.4901	R2:	73.9	R10:	39.3
Duv:	0.0035	R3:	79.4	R11:	71.1
CIE x:	0.3489	R4:	72.1	R12:	43.8
CIE y:	0.3618	R5:	69.2	R13:	68.1
CIE z:	0.2893	R6:	65.7	R14:	88.4
Peak Wavelength (nm):	443	R7:	78.1	R15:	59.7
Dominant Wavelength (nm):	570	R8:	55.3		
Purity:	13.25435				
Rf:	70.7				
Rg:	96.8				



Test Conditions

Stabilization Time: 21M
 Operation Time: 1H 21M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-6

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-6

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 5000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-6

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	118	NR	620	401	NR	750	12	NR	880	0	NR
365	0	NR	495	168	NR	625	365	NR	755	10	NR	885	0	NR
370	0	NR	500	230	NR	630	331	NR	760	9	NR	890	0	NR
375	0	NR	505	299	NR	635	298	NR	765	8	NR	895	0	NR
380	0	NR	510	362	NR	640	266	NR	770	6	NR	900	0	NR
385	2	NR	515	418	NR	645	236	NR	775	6	NR	905	0	NR
390	4	NR	520	461	NR	650	209	NR	780	5	NR	910	0	NR
395	6	NR	525	491	NR	655	184	NR	785	4	NR	915	0	NR
400	9	NR	530	514	NR	660	160	NR	790	4	NR	920	0	NR
405	14	NR	535	530	NR	665	140	NR	795	3	NR	925	0	NR
410	27	NR	540	539	NR	670	122	NR	800	3	NR	930	0	NR
415	55	NR	545	549	NR	675	106	NR	805	2	NR	935	0	NR
420	115	NR	550	557	NR	680	92	NR	810	2	NR	940	0	NR
425	226	NR	555	565	NR	685	79	NR	815	2	NR	945	0	NR
430	395	NR	560	572	NR	690	68	NR	820	2	NR	950	0	NR
435	648	NR	565	580	NR	695	59	NR	825	1	NR	955	0	NR
440	937	NR	570	586	NR	700	51	NR	830	1	NR	960	0	NR
445	953	NR	575	588	NR	705	44	NR	835	1	NR	965	0	NR
450	591	NR	580	588	NR	710	38	NR	840	1	NR	970	0	NR
455	334	NR	585	580	NR	715	32	NR	845	1	NR	975	0	NR
460	221	NR	590	568	NR	720	28	NR	850	1	NR	980	0	NR
465	140	NR	595	550	NR	725	24	NR	855	1	NR	985	0	NR
470	93	NR	600	527	NR	730	21	NR	860	1	NR	990	0	NR
475	79	NR	605	499	NR	735	18	NR	865	0	NR	995	0	NR
480	76	NR	610	469	NR	740	15	NR	870	0	NR	1000	0	NR
485	87	NR	615	435	NR	745	13	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-6

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.7

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	118	NR	620	401	NR	750	12	NR	880	0	NR
365	0	NR	495	168	NR	625	365	NR	755	10	NR	885	0	NR
370	0	NR	500	230	NR	630	331	NR	760	9	NR	890	0	NR
375	0	NR	505	299	NR	635	298	NR	765	8	NR	895	0	NR
380	0	NR	510	362	NR	640	266	NR	770	6	NR	900	0	NR
385	2	NR	515	418	NR	645	236	NR	775	6	NR	905	0	NR
390	4	NR	520	461	NR	650	209	NR	780	5	NR	910	0	NR
395	6	NR	525	491	NR	655	184	NR	785	4	NR	915	0	NR
400	9	NR	530	514	NR	660	160	NR	790	4	NR	920	0	NR
405	14	NR	535	530	NR	665	140	NR	795	3	NR	925	0	NR
410	27	NR	540	539	NR	670	122	NR	800	3	NR	930	0	NR
415	55	NR	545	549	NR	675	106	NR	805	2	NR	935	0	NR
420	115	NR	550	557	NR	680	92	NR	810	2	NR	940	0	NR
425	226	NR	555	565	NR	685	79	NR	815	2	NR	945	0	NR
430	395	NR	560	572	NR	690	68	NR	820	2	NR	950	0	NR
435	648	NR	565	580	NR	695	59	NR	825	1	NR	955	0	NR
440	937	NR	570	586	NR	700	51	NR	830	1	NR	960	0	NR
445	953	NR	575	588	NR	705	44	NR	835	1	NR	965	0	NR
450	591	NR	580	588	NR	710	38	NR	840	1	NR	970	0	NR
455	334	NR	585	580	NR	715	32	NR	845	1	NR	975	0	NR
460	221	NR	590	568	NR	720	28	NR	850	1	NR	980	0	NR
465	140	NR	595	550	NR	725	24	NR	855	1	NR	985	0	NR
470	93	NR	600	527	NR	730	21	NR	860	1	NR	990	0	NR
475	79	NR	605	499	NR	735	18	NR	865	0	NR	995	0	NR
480	76	NR	610	469	NR	740	15	NR	870	0	NR	1000	0	NR
485	87	NR	615	435	NR	745	13	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-6

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 3.37

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	118	NR	620	401	NR	750	12	NR	880	0	NR
365	0	NR	495	168	NR	625	365	NR	755	10	NR	885	0	NR
370	0	NR	500	230	NR	630	331	NR	760	9	NR	890	0	NR
375	0	NR	505	299	NR	635	298	NR	765	8	NR	895	0	NR
380	0	NR	510	362	NR	640	266	NR	770	6	NR	900	0	NR
385	2	NR	515	418	NR	645	236	NR	775	6	NR	905	0	NR
390	4	NR	520	461	NR	650	209	NR	780	5	NR	910	0	NR
395	6	NR	525	491	NR	655	184	NR	785	4	NR	915	0	NR
400	9	NR	530	514	NR	660	160	NR	790	4	NR	920	0	NR
405	14	NR	535	530	NR	665	140	NR	795	3	NR	925	0	NR
410	27	NR	540	539	NR	670	122	NR	800	3	NR	930	0	NR
415	55	NR	545	549	NR	675	106	NR	805	2	NR	935	0	NR
420	115	NR	550	557	NR	680	92	NR	810	2	NR	940	0	NR
425	226	NR	555	565	NR	685	79	NR	815	2	NR	945	0	NR
430	395	NR	560	572	NR	690	68	NR	820	2	NR	950	0	NR
435	648	NR	565	580	NR	695	59	NR	825	1	NR	955	0	NR
440	937	NR	570	586	NR	700	51	NR	830	1	NR	960	0	NR
445	953	NR	575	588	NR	705	44	NR	835	1	NR	965	0	NR
450	591	NR	580	588	NR	710	38	NR	840	1	NR	970	0	NR
455	334	NR	585	580	NR	715	32	NR	845	1	NR	975	0	NR
460	221	NR	590	568	NR	720	28	NR	850	1	NR	980	0	NR
465	140	NR	595	550	NR	725	24	NR	855	1	NR	985	0	NR
470	93	NR	600	527	NR	730	21	NR	860	1	NR	990	0	NR
475	79	NR	605	499	NR	735	18	NR	865	0	NR	995	0	NR
480	76	NR	610	469	NR	740	15	NR	870	0	NR	1000	0	NR
485	87	NR	615	435	NR	745	13	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-6



TM-30-18

Summary

$R_f = 70.7$
 $R_g = 96.8$
 CIE $R_a = 70.2$
 $R_g = -35.1$



Color Vector Graphics




Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 85	CES26 = 53	CES51 = 87	CES76 = 42
CES02 = 59	CES27 = 78	CES52 = 88	CES77 = 64
CES03 = 30	CES28 = 76	CES53 = 74	CES78 = 45
CES04 = 69	CES29 = 48	CES54 = 80	CES79 = 74
CES05 = 46	CES30 = 56	CES55 = 79	CES80 = 71
CES06 = 50	CES31 = 54	CES56 = 68	CES81 = 72
CES07 = 39	CES32 = 50	CES57 = 65	CES82 = 88
CES08 = 38	CES33 = 60	CES58 = 67	CES83 = 82
CES09 = 29	CES34 = 62	CES59 = 87	CES84 = 87
CES10 = 72	CES35 = 79	CES60 = 91	CES85 = 84
CES11 = 56	CES36 = 90	CES61 = 87	CES86 = 74
CES12 = 61	CES37 = 72	CES62 = 79	CES87 = 75
CES13 = 41	CES38 = 66	CES63 = 72	CES88 = 76
CES14 = 74	CES39 = 91	CES64 = 70	CES89 = 74
CES15 = 70	CES40 = 83	CES65 = 63	CES90 = 73
CES16 = 46	CES41 = 83	CES66 = 64	CES91 = 92
CES17 = 49	CES42 = 70	CES67 = 62	CES92 = 67
CES18 = 55	CES43 = 68	CES68 = 69	CES93 = 81
CES19 = 71	CES44 = 98	CES69 = 80	CES94 = 56
CES20 = 64	CES45 = 78	CES70 = 56	CES95 = 71
CES21 = 85	CES46 = 77	CES71 = 53	CES96 = 77
CES22 = 77	CES47 = 73	CES72 = 84	CES97 = 82
CES23 = 91	CES48 = 65	CES73 = 46	CES98 = 71
CES24 = 90	CES49 = 76	CES74 = 94	CES99 = 59
CES25 = 71	CES50 = 85	CES75 = 49	



Color Rendition by Hue-Angle Bin



Measure Comparisons


(END OF REPORT)