

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066590

Luminaire Tested: **NVN-SA5B-760-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066590
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5B-760-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 5xLight Square PACKAGE
70CRI 5700K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 5700K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 19174.4 lumens
Efficiency: N/A
Efficacy: 107.2 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 178.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	114.0	0.0	114.0
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	19060.3	0.0	19060.3
	% Fixture	99.4	0.0	99.4
Total	Lumens	19174.3	0.0	19174.3
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	5.7	0.0
10°-20°	28.1	0.1
20°-30°	357.9	1.9
30°-40°	1206.1	6.3
40°-50°	3642.5	19.0
50°-60°	6426.6	33.5
60°-70°	5661.8	29.5
70°-80°	1802.3	9.4
80°-90°	43.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	19174.3	100.0
0°-180°	19174.4	100.0



REPORT NUMBER: P1066590


CATALOG NUMBER: NVN-SA5B-760-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	374.6	2.0			
FM	(30°-60°)	11231.0	58.6			
FH	(60°-80°)	7419.4	38.7			G3/7500
FVH	(80°-90°)	35.3	0.2			G1/100
BL	(0°-30°)	17.1	0.1	B0/110		
BM	(30°-60°)	44.2	0.2	B0/220		
BH	(60°-80°)	44.7	0.2	B0/110		G0/110
BVH	(80°-90°)	8.1	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	42.1
5°	60.1	60.1	60.1	54.1	54.1	54.1	48.1	48.1	48.1	48.1	48.1
7.5°	72.2	66.1	66.1	60.1	60.1	60.1	54.1	54.1	54.1	54.1	48.1
10°	84.2	78.2	78.2	72.2	72.2	66.1	66.1	60.1	60.1	54.1	54.1
12.5°	96.2	90.2	84.2	78.2	78.2	72.2	72.2	66.1	66.1	60.1	60.1
15°	108.2	102.2	96.2	90.2	84.2	84.2	78.2	72.2	66.1	66.1	60.1
17.5°	126.3	114.2	108.2	96.2	90.2	84.2	78.2	72.2	72.2	66.1	66.1
20°	132.3	120.3	114.2	102.2	96.2	90.2	84.2	78.2	72.2	72.2	66.1
22.5°	156.3	132.3	126.3	114.2	108.2	102.2	90.2	84.2	78.2	72.2	66.1
25°	192.4	156.3	138.3	120.3	114.2	102.2	96.2	84.2	78.2	72.2	66.1
27.5°	234.5	174.4	156.3	132.3	120.3	108.2	96.2	84.2	78.2	72.2	66.1
30°	288.6	204.4	174.4	144.3	132.3	120.3	102.2	90.2	84.2	78.2	66.1
32.5°	402.9	252.5	204.4	156.3	138.3	126.3	108.2	90.2	84.2	78.2	66.1
35°	487.1	306.7	246.5	180.4	156.3	138.3	114.2	90.2	84.2	78.2	66.1
37.5°	565.2	312.7	252.5	192.4	168.4	144.3	114.2	90.2	84.2	78.2	66.1
40°	691.5	324.7	252.5	180.4	162.4	138.3	120.3	96.2	90.2	78.2	72.2
42.5°	932.0	372.8	270.6	168.4	150.3	138.3	120.3	102.2	90.2	84.2	72.2
45°	1551.4	553.2	366.8	174.4	156.3	138.3	120.3	102.2	96.2	84.2	78.2
47.5°	2639.7	962.1	571.2	180.4	162.4	138.3	120.3	96.2	90.2	84.2	72.2
50°	3379.3	1232.7	721.6	210.5	180.4	156.3	126.3	96.2	90.2	84.2	78.2
52.5°	3589.8	1310.8	781.7	246.5	210.5	174.4	132.3	96.2	90.2	90.2	84.2
55°	3289.1	1274.8	781.7	288.6	240.5	198.4	150.3	102.2	96.2	96.2	90.2
57.5°	2796.1	1178.6	745.6	312.7	264.6	210.5	162.4	108.2	102.2	102.2	96.2
60°	2303.0	992.2	673.5	348.8	294.6	240.5	186.4	132.3	126.3	120.3	108.2
62.5°	1828.0	799.7	589.3	372.8	318.7	258.6	204.4	144.3	138.3	132.3	126.3
65°	1377.0	697.5	547.2	390.8	330.7	270.6	210.5	150.3	144.3	144.3	138.3
67.5°	1058.3	637.4	523.1	402.9	342.7	282.6	222.5	162.4	156.3	150.3	144.3
70°	835.8	589.3	493.1	396.9	342.7	288.6	228.5	174.4	162.4	156.3	144.3
72.5°	697.5	535.2	457.0	378.8	336.7	294.6	252.5	210.5	186.4	168.4	144.3
75°	583.3	481.0	414.9	342.7	312.7	288.6	258.6	228.5	198.4	168.4	138.3
77.5°	384.8	348.8	318.7	288.6	270.6	252.5	228.5	210.5	180.4	156.3	126.3
80°	162.4	150.3	156.3	156.3	156.3	156.3	150.3	150.3	132.3	114.2	90.2
82.5°	36.1	30.1	36.1	36.1	36.1	36.1	30.1	30.1	30.1	24.1	24.1
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
5°	48.1	48.1	48.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
7.5°	48.1	48.1	48.1	42.1	42.1	42.1	42.1	36.1	36.1	36.1	36.1
10°	48.1	48.1	48.1	42.1	42.1	42.1	42.1	36.1	36.1	36.1	36.1
12.5°	54.1	54.1	48.1	48.1	42.1	42.1	42.1	36.1	36.1	36.1	36.1
15°	54.1	54.1	48.1	48.1	42.1	42.1	42.1	36.1	36.1	36.1	36.1
17.5°	60.1	54.1	54.1	48.1	42.1	42.1	42.1	36.1	36.1	36.1	36.1
20°	60.1	54.1	54.1	48.1	42.1	42.1	42.1	36.1	36.1	36.1	36.1
22.5°	60.1	54.1	54.1	48.1	42.1	42.1	36.1	36.1	30.1	30.1	24.1
25°	60.1	54.1	54.1	48.1	42.1	42.1	36.1	36.1	30.1	24.1	24.1
27.5°	60.1	54.1	54.1	48.1	42.1	36.1	36.1	30.1	24.1	18.0	18.0
30°	60.1	54.1	54.1	48.1	42.1	36.1	30.1	24.1	18.0	18.0	12.0
32.5°	60.1	54.1	48.1	42.1	36.1	30.1	30.1	24.1	18.0	12.0	12.0
35°	60.1	54.1	48.1	42.1	36.1	30.1	30.1	24.1	18.0	12.0	12.0
37.5°	60.1	54.1	48.1	42.1	36.1	30.1	24.1	18.0	12.0	12.0	6.0
40°	60.1	54.1	48.1	42.1	36.1	30.1	24.1	18.0	12.0	12.0	6.0
42.5°	60.1	54.1	48.1	42.1	36.1	30.1	24.1	18.0	12.0	12.0	6.0
45°	66.1	60.1	54.1	42.1	36.1	30.1	30.1	24.1	18.0	12.0	12.0
47.5°	66.1	60.1	54.1	42.1	36.1	30.1	30.1	24.1	18.0	12.0	12.0
50°	72.2	66.1	60.1	48.1	42.1	36.1	30.1	18.0	12.0	12.0	6.0
52.5°	78.2	72.2	66.1	60.1	54.1	42.1	30.1	18.0	6.0	6.0	6.0
55°	84.2	78.2	78.2	72.2	66.1	48.1	36.1	18.0	0.0	0.0	0.0
57.5°	90.2	84.2	84.2	78.2	72.2	54.1	36.1	18.0	0.0	0.0	0.0
60°	102.2	96.2	90.2	78.2	72.2	54.1	36.1	18.0	0.0	0.0	0.0
62.5°	120.3	108.2	90.2	78.2	60.1	48.1	30.1	18.0	0.0	0.0	0.0
65°	132.3	114.2	96.2	72.2	54.1	42.1	30.1	12.0	0.0	0.0	0.0
67.5°	138.3	114.2	96.2	72.2	48.1	36.1	24.1	12.0	0.0	0.0	0.0
70°	132.3	108.2	90.2	66.1	42.1	30.1	24.1	12.0	0.0	0.0	0.0
72.5°	120.3	102.2	78.2	60.1	36.1	30.1	18.0	12.0	0.0	0.0	0.0
75°	108.2	90.2	66.1	48.1	24.1	18.0	12.0	6.0	0.0	0.0	0.0
77.5°	96.2	78.2	54.1	36.1	12.0	12.0	6.0	6.0	0.0	0.0	0.0
80°	72.2	54.1	36.1	18.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	18.0	12.0	12.0	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1
5°	36.1	36.1	36.1	36.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1
7.5°	36.1	36.1	36.1	36.1	30.1	30.1	30.1	30.1	24.1	24.1	24.1
10°	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	24.1	24.1	24.1
12.5°	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	24.1	24.1	24.1
15°	30.1	30.1	30.1	30.1	30.1	30.1	30.1	24.1	24.1	18.0	18.0
17.5°	30.1	30.1	30.1	30.1	24.1	24.1	24.1	18.0	18.0	12.0	12.0
20°	30.1	30.1	30.1	24.1	24.1	18.0	18.0	12.0	12.0	6.0	6.0
22.5°	24.1	18.0	18.0	12.0	12.0	6.0	6.0	6.0	0.0	0.0	0.0
25°	18.0	12.0	12.0	6.0	6.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	12.0	6.0	6.0	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	12.0	6.0	6.0	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	36.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1
5°	30.1	30.1	30.1	30.1	24.1	24.1	24.1	24.1	24.1	24.1	24.1
7.5°	24.1	24.1	24.1	24.1	24.1	24.1	18.0	18.0	18.0	18.0	18.0
10°	24.1	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	12.0	12.0
12.5°	24.1	18.0	18.0	18.0	12.0	12.0	12.0	12.0	12.0	6.0	6.0
15°	18.0	12.0	12.0	12.0	6.0	6.0	6.0	6.0	6.0	0.0	0.0
17.5°	12.0	6.0	6.0	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	36.1	36.1
5°	24.1	24.1	24.1	24.1	24.1	24.1	24.1	24.1	24.1	24.1	24.1
7.5°	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0
10°	12.0	12.0	12.0	12.0	12.0	12.0	6.0	6.0	6.0	6.0	6.0
12.5°	6.0	6.0	6.0	6.0	6.0	6.0	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	36.1	36.1	36.1	36.1	36.1	42.1	42.1	48.1	48.1	54.1	54.1
5°	24.1	24.1	30.1	30.1	30.1	30.1	36.1	36.1	36.1	42.1	42.1
7.5°	18.0	18.0	18.0	18.0	18.0	24.1	24.1	30.1	30.1	36.1	36.1
10°	6.0	6.0	12.0	12.0	12.0	12.0	18.0	18.0	18.0	24.1	30.1
12.5°	0.0	0.0	6.0	6.0	6.0	6.0	12.0	12.0	12.0	18.0	24.1
15°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0	12.0	18.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0	12.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	60.1	60.1	66.1	66.1	72.2	72.2	78.2	78.2	78.2	78.2	78.2
5°	48.1	48.1	54.1	60.1	60.1	66.1	72.2	72.2	72.2	72.2	72.2
7.5°	42.1	42.1	48.1	54.1	54.1	60.1	66.1	66.1	72.2	72.2	72.2
10°	30.1	36.1	42.1	48.1	48.1	54.1	60.1	60.1	66.1	66.1	66.1
12.5°	24.1	30.1	36.1	42.1	42.1	48.1	54.1	54.1	60.1	60.1	66.1
15°	18.0	24.1	30.1	36.1	36.1	42.1	48.1	48.1	54.1	60.1	66.1
17.5°	12.0	18.0	24.1	30.1	30.1	36.1	42.1	48.1	54.1	54.1	60.1
20°	12.0	12.0	18.0	24.1	24.1	30.1	36.1	42.1	48.1	48.1	54.1
22.5°	6.0	6.0	12.0	18.0	18.0	24.1	30.1	36.1	42.1	42.1	48.1
25°	0.0	0.0	6.0	12.0	12.0	18.0	24.1	24.1	30.1	30.1	36.1
27.5°	0.0	0.0	6.0	6.0	12.0	12.0	18.0	18.0	24.1	24.1	30.1
30°	0.0	0.0	6.0	6.0	12.0	12.0	18.0	18.0	24.1	24.1	24.1
32.5°	0.0	0.0	0.0	6.0	6.0	6.0	12.0	12.0	18.0	18.0	24.1
35°	0.0	0.0	0.0	6.0	6.0	6.0	12.0	12.0	18.0	18.0	18.0
37.5°	0.0	0.0	0.0	6.0	6.0	6.0	12.0	12.0	12.0	12.0	18.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	12.0	12.0	12.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	12.0	12.0	12.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	12.0	12.0	12.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	12.0	12.0	12.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	12.0	12.0	12.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0	6.0	6.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0	6.0	6.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0	6.0	6.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0	6.0	6.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	12.0	12.0	12.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	12.0	12.0	12.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0	6.0	12.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0	6.0	6.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	6.0	6.0	6.0	6.0	6.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	78.2	78.2
5°	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	72.2	72.2
7.5°	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	72.2	72.2
10°	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
12.5°	66.1	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
15°	66.1	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
17.5°	60.1	66.1	66.1	66.1	72.2	72.2	72.2	72.2	72.2	72.2	72.2
20°	54.1	60.1	60.1	60.1	66.1	66.1	66.1	66.1	72.2	72.2	72.2
22.5°	48.1	54.1	54.1	54.1	60.1	60.1	60.1	60.1	66.1	66.1	66.1
25°	42.1	42.1	48.1	48.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
27.5°	30.1	36.1	36.1	36.1	42.1	42.1	42.1	42.1	48.1	48.1	48.1
30°	30.1	30.1	30.1	30.1	36.1	36.1	36.1	36.1	42.1	42.1	42.1
32.5°	24.1	30.1	30.1	30.1	36.1	36.1	36.1	36.1	42.1	42.1	42.1
35°	24.1	24.1	24.1	24.1	30.1	30.1	30.1	30.1	36.1	36.1	36.1
37.5°	18.0	24.1	24.1	24.1	30.1	30.1	30.1	30.1	36.1	36.1	36.1
40°	18.0	18.0	18.0	18.0	24.1	24.1	24.1	24.1	30.1	30.1	30.1
42.5°	18.0	18.0	18.0	18.0	24.1	24.1	24.1	24.1	30.1	30.1	30.1
45°	18.0	18.0	18.0	18.0	24.1	24.1	24.1	24.1	30.1	30.1	30.1
47.5°	18.0	18.0	18.0	18.0	24.1	24.1	24.1	24.1	30.1	30.1	30.1
50°	18.0	18.0	18.0	18.0	24.1	24.1	24.1	24.1	30.1	30.1	30.1
52.5°	12.0	12.0	12.0	12.0	18.0	18.0	18.0	18.0	24.1	24.1	24.1
55°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	18.0	18.0	18.0
57.5°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	18.0	18.0	18.0
60°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
62.5°	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
65°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	6.0	6.0
67.5°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
70°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
72.5°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
75°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
77.5°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
80°	18.0	18.0	18.0	18.0	18.0	12.0	12.0	12.0	12.0	12.0	12.0
82.5°	12.0	18.0	18.0	18.0	18.0	12.0	12.0	12.0	12.0	12.0	12.0
85°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
87.5°	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	78.2	78.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	78.2	78.2
5°	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	78.2	78.2
7.5°	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	78.2	78.2
10°	72.2	72.2	72.2	72.2	66.1	66.1	72.2	72.2	72.2	78.2	78.2
12.5°	72.2	72.2	72.2	72.2	66.1	66.1	72.2	72.2	78.2	78.2	84.2
15°	72.2	72.2	66.1	66.1	66.1	66.1	72.2	72.2	78.2	78.2	84.2
17.5°	72.2	72.2	66.1	66.1	66.1	66.1	72.2	72.2	78.2	78.2	84.2
20°	72.2	72.2	66.1	66.1	66.1	66.1	66.1	66.1	72.2	78.2	78.2
22.5°	66.1	66.1	66.1	66.1	60.1	60.1	66.1	66.1	72.2	78.2	78.2
25°	54.1	60.1	60.1	60.1	60.1	60.1	66.1	66.1	72.2	78.2	78.2
27.5°	48.1	54.1	54.1	54.1	54.1	60.1	60.1	66.1	72.2	78.2	78.2
30°	42.1	48.1	48.1	48.1	54.1	60.1	60.1	66.1	72.2	78.2	78.2
32.5°	42.1	48.1	48.1	48.1	54.1	54.1	60.1	60.1	66.1	72.2	78.2
35°	42.1	42.1	48.1	48.1	48.1	54.1	54.1	60.1	66.1	72.2	78.2
37.5°	42.1	42.1	48.1	48.1	48.1	54.1	54.1	60.1	66.1	72.2	78.2
40°	36.1	42.1	42.1	48.1	48.1	54.1	54.1	60.1	66.1	78.2	84.2
42.5°	36.1	36.1	42.1	42.1	48.1	54.1	54.1	60.1	66.1	78.2	84.2
45°	36.1	42.1	42.1	48.1	54.1	60.1	60.1	66.1	72.2	78.2	84.2
47.5°	36.1	42.1	42.1	48.1	60.1	60.1	66.1	66.1	72.2	78.2	84.2
50°	36.1	42.1	42.1	48.1	66.1	66.1	66.1	66.1	72.2	78.2	84.2
52.5°	30.1	36.1	36.1	42.1	54.1	60.1	66.1	72.2	78.2	84.2	90.2
55°	24.1	30.1	30.1	36.1	48.1	54.1	66.1	78.2	84.2	90.2	96.2
57.5°	24.1	24.1	30.1	30.1	42.1	54.1	72.2	84.2	90.2	96.2	102.2
60°	18.0	18.0	24.1	24.1	36.1	48.1	66.1	84.2	90.2	102.2	108.2
62.5°	12.0	18.0	18.0	24.1	30.1	48.1	66.1	84.2	96.2	108.2	114.2
65°	12.0	12.0	18.0	18.0	30.1	42.1	60.1	72.2	90.2	108.2	126.3
67.5°	18.0	18.0	24.1	24.1	30.1	42.1	60.1	72.2	90.2	114.2	132.3
70°	18.0	18.0	24.1	24.1	36.1	48.1	60.1	72.2	90.2	114.2	132.3
72.5°	18.0	18.0	24.1	24.1	36.1	42.1	54.1	66.1	84.2	102.2	120.3
75°	12.0	18.0	18.0	18.0	30.1	36.1	48.1	60.1	78.2	96.2	114.2
77.5°	12.0	12.0	12.0	12.0	24.1	30.1	42.1	48.1	66.1	84.2	102.2
80°	12.0	12.0	12.0	12.0	18.0	24.1	36.1	42.1	60.1	78.2	96.2
82.5°	12.0	12.0	6.0	6.0	12.0	18.0	24.1	30.1	48.1	60.1	78.2
85°	12.0	12.0	6.0	6.0	6.0	12.0	12.0	18.0	24.1	30.1	36.1
87.5°	12.0	12.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	78.2	78.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2
5°	78.2	84.2	84.2	90.2	90.2	90.2	96.2	96.2	96.2	96.2	96.2
7.5°	78.2	84.2	84.2	90.2	90.2	90.2	96.2	96.2	96.2	102.2	102.2
10°	78.2	84.2	84.2	90.2	90.2	96.2	102.2	102.2	108.2	108.2	108.2
12.5°	84.2	90.2	90.2	96.2	96.2	102.2	108.2	108.2	114.2	120.3	120.3
15°	84.2	90.2	96.2	96.2	102.2	108.2	114.2	114.2	120.3	126.3	132.3
17.5°	84.2	90.2	96.2	96.2	102.2	108.2	120.3	126.3	132.3	144.3	150.3
20°	84.2	90.2	96.2	96.2	102.2	114.2	120.3	132.3	138.3	150.3	162.4
22.5°	84.2	90.2	96.2	102.2	108.2	120.3	132.3	138.3	150.3	168.4	180.4
25°	84.2	90.2	96.2	102.2	108.2	120.3	132.3	144.3	156.3	180.4	204.4
27.5°	84.2	90.2	102.2	108.2	114.2	126.3	144.3	156.3	168.4	210.5	252.5
30°	84.2	90.2	102.2	108.2	114.2	132.3	150.3	162.4	180.4	252.5	318.7
32.5°	84.2	96.2	102.2	114.2	120.3	138.3	162.4	180.4	198.4	300.7	396.9
35°	84.2	96.2	102.2	114.2	120.3	144.3	168.4	192.4	216.5	366.8	517.1
37.5°	84.2	96.2	102.2	114.2	120.3	156.3	192.4	228.5	264.6	420.9	577.3
40°	90.2	102.2	108.2	120.3	126.3	162.4	198.4	234.5	270.6	426.9	583.3
42.5°	90.2	102.2	108.2	120.3	126.3	156.3	192.4	222.5	252.5	426.9	601.3
45°	90.2	102.2	114.2	120.3	132.3	162.4	192.4	216.5	246.5	469.0	685.5
47.5°	90.2	102.2	114.2	120.3	132.3	162.4	192.4	222.5	252.5	619.3	980.1
50°	90.2	102.2	114.2	120.3	132.3	168.4	204.4	240.5	276.6	926.0	1575.4
52.5°	96.2	102.2	114.2	120.3	126.3	168.4	210.5	252.5	294.6	1202.6	2104.6
55°	102.2	108.2	114.2	120.3	126.3	180.4	234.5	288.6	342.7	1292.8	2236.9
57.5°	108.2	114.2	120.3	120.3	126.3	192.4	264.6	330.7	396.9	1286.8	2170.7
60°	114.2	120.3	126.3	132.3	138.3	204.4	276.6	342.7	408.9	1166.5	1924.2
62.5°	126.3	138.3	150.3	156.3	168.4	234.5	294.6	360.8	420.9	956.1	1485.2
65°	144.3	156.3	162.4	174.4	180.4	240.5	306.7	366.8	426.9	793.7	1154.5
67.5°	150.3	162.4	168.4	180.4	186.4	246.5	306.7	366.8	426.9	673.5	914.0
70°	150.3	162.4	174.4	180.4	192.4	252.5	306.7	366.8	420.9	583.3	745.6
72.5°	138.3	156.3	168.4	186.4	198.4	252.5	300.7	354.8	402.9	517.1	631.4
75°	132.3	156.3	174.4	198.4	216.5	252.5	294.6	330.7	366.8	451.0	535.2
77.5°	120.3	150.3	180.4	210.5	240.5	264.6	282.6	306.7	324.7	378.8	432.9
80°	114.2	144.3	174.4	204.4	234.5	246.5	252.5	264.6	270.6	276.6	282.6
82.5°	90.2	114.2	138.3	156.3	180.4	168.4	162.4	150.3	138.3	132.3	126.3
85°	42.1	48.1	48.1	54.1	54.1	54.1	48.1	48.1	42.1	36.1	30.1
87.5°	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	84.2	84.2	84.2	84.2	78.2	78.2	78.2	78.2	72.2	72.2	72.2
5°	96.2	96.2	96.2	96.2	90.2	90.2	90.2	90.2	84.2	84.2	84.2
7.5°	102.2	102.2	102.2	102.2	102.2	102.2	102.2	102.2	102.2	102.2	102.2
10°	114.2	114.2	114.2	120.3	120.3	120.3	120.3	120.3	120.3	120.3	120.3
12.5°	126.3	126.3	132.3	132.3	138.3	138.3	144.3	144.3	150.3	150.3	150.3
15°	138.3	144.3	150.3	156.3	156.3	162.4	168.4	174.4	180.4	186.4	192.4
17.5°	162.4	168.4	180.4	192.4	204.4	216.5	234.5	258.6	276.6	294.6	318.7
20°	180.4	198.4	234.5	276.6	312.7	348.8	439.0	529.1	619.3	709.5	799.7
22.5°	216.5	252.5	372.8	499.1	619.3	739.6	1022.2	1304.8	1581.4	1864.0	2116.6
25°	288.6	366.8	643.4	920.0	1190.6	1467.2	1972.3	2483.4	2988.5	3493.6	3962.6
27.5°	396.9	541.2	992.2	1449.1	1900.1	2351.1	3084.7	3824.3	4557.9	5297.5	5952.9
30°	553.2	787.7	1461.2	2140.6	2814.1	3487.6	4413.6	5345.6	6271.6	7197.6	7798.9
32.5°	751.6	1100.4	1954.2	2808.1	3662.0	4515.8	5538.0	6560.2	7576.5	8598.7	9236.1
35°	962.1	1407.1	2435.3	3469.5	4497.8	5532.0	6608.4	7684.7	8761.0	9837.4	10619.1
37.5°	1082.4	1587.4	2808.1	4028.8	5243.4	6464.0	7642.6	8827.2	10005.7	11184.3	12134.4
40°	1196.6	1803.9	3211.0	4618.0	6025.1	7432.1	8809.1	10186.1	11563.1	12940.1	14160.8
42.5°	1365.0	2128.6	3770.2	5411.8	7047.3	8688.9	10498.8	12314.7	14124.7	15934.6	17810.7
45°	1713.7	2742.0	4870.6	6999.2	9121.8	11250.4	13818.0	16391.6	18959.2	21532.8	23938.0
47.5°	2555.6	4125.0	7029.3	9933.6	12837.9	15742.2	18700.6	21659.0	24617.5	27575.9	30438.1
50°	3956.6	6331.8	9963.6	13595.5	17221.4	20853.3	23805.7	26758.1	29704.5	32656.9	35501.1
52.5°	5273.5	8442.3	12344.8	16253.3	20155.8	24064.3	26679.9	29295.6	31911.3	34527.0	37281.0
55°	5724.4	9206.0	13156.6	17113.2	21063.7	25020.3	27539.8	30065.3	32584.8	35104.2	37960.4
57.5°	5327.6	8484.4	12465.1	16445.7	20420.4	24401.0	27215.1	30035.2	32849.3	35669.5	38730.1
60°	4461.7	6993.2	11172.3	15357.4	19536.4	23715.5	26890.4	30065.3	33240.2	36415.1	39469.7
62.5°	3535.7	5580.1	10005.7	14431.3	18857.0	23282.6	26511.6	29746.6	32975.6	36204.6	38549.7
65°	2711.9	4269.3	8622.7	12982.2	17335.7	21695.1	24340.9	26992.6	29638.4	32290.1	33913.7
67.5°	2014.4	3114.8	6921.0	10733.3	14539.6	18345.8	20294.1	22248.3	24196.6	26150.8	27413.5
70°	1485.2	2218.8	4810.4	7402.1	9987.7	12579.3	14365.2	16151.1	17930.9	19716.8	21027.7
72.5°	1028.2	1419.1	2970.5	4527.8	6079.2	7630.6	9440.5	11250.4	13054.4	14864.3	16355.5
75°	703.5	871.9	1599.5	2327.1	3054.6	3782.2	5153.2	6524.2	7895.1	9266.1	10053.8
77.5°	523.1	613.3	829.8	1052.3	1268.8	1485.2	1749.8	2014.4	2278.9	2543.5	2886.3
80°	288.6	288.6	318.7	342.7	372.8	396.9	469.0	547.2	619.3	697.5	793.7
82.5°	132.3	138.3	150.3	162.4	168.4	180.4	192.4	204.4	216.5	228.5	228.5
85°	36.1	42.1	42.1	36.1	36.1	30.1	30.1	36.1	36.1	36.1	36.1
87.5°	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	72.2	66.1	66.1	66.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1
5°	84.2	84.2	84.2	84.2	78.2	78.2	78.2	78.2	78.2	72.2	72.2
7.5°	102.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	90.2	90.2
10°	120.3	120.3	120.3	120.3	120.3	120.3	120.3	120.3	120.3	114.2	114.2
12.5°	150.3	150.3	150.3	150.3	156.3	156.3	150.3	150.3	150.3	144.3	144.3
15°	198.4	204.4	210.5	210.5	216.5	216.5	216.5	210.5	210.5	204.4	198.4
17.5°	336.7	354.8	378.8	402.9	426.9	445.0	445.0	432.9	420.9	408.9	396.9
20°	895.9	986.1	1082.4	1178.6	1280.8	1352.9	1304.8	1268.8	1232.7	1190.6	1154.5
22.5°	2375.2	2627.7	2886.3	3066.7	3247.1	3373.3	3271.1	3072.7	2874.2	2681.8	2483.4
25°	4431.6	4894.6	5363.6	5556.1	5754.5	5898.8	5832.7	5532.0	5231.4	4936.7	4636.1
27.5°	6608.4	7257.8	7913.2	8081.6	8249.9	8376.2	8352.1	7961.3	7570.4	7179.6	6788.7
30°	8400.2	9001.6	9602.9	9771.2	9939.6	10053.8	9927.6	9536.7	9145.9	8755.0	8364.2
32.5°	9879.5	10516.8	11160.2	11382.7	11605.2	11755.5	11605.2	11136.2	10667.2	10204.2	9735.1
35°	11400.8	12176.4	12958.1	13240.8	13523.4	13703.8	13451.2	12874.0	12296.7	11725.5	11148.2
37.5°	13084.4	14028.5	14978.5	15363.4	15754.2	16024.8	15832.4	15110.8	14383.2	13661.7	12934.1
40°	15387.4	16608.1	17834.7	18526.2	19211.7	19698.8	19356.0	18520.2	17678.4	16842.6	16000.8
42.5°	19692.8	21568.8	23444.9	24437.1	25423.2	26138.8	25753.9	24725.7	23697.5	22669.2	21641.0
45°	26343.2	28742.4	31147.7	32596.8	34052.0	35122.3	34677.3	33384.5	32085.7	30792.9	29500.1
47.5°	33300.3	36162.5	39024.8	40179.3	41339.8	42241.7	42133.5	40522.0	38910.5	37305.0	35693.5
50°	38351.3	41195.5	44039.7	45031.8	46030.0	46769.6	46493.0	44442.5	42386.1	40335.6	38279.1
52.5°	40035.0	42782.9	45536.9	46721.5	47906.1	48790.0	48453.2	46144.2	43835.2	41532.2	39223.2
55°	40816.7	43672.9	46529.1	47972.2	49421.3	50479.6	49992.6	47461.1	44923.6	42392.1	39854.6
57.5°	41790.8	44851.4	47912.1	49493.5	51074.9	52217.4	51568.0	48946.3	46324.6	43708.9	41087.2
60°	42524.4	45573.0	48627.6	49896.4	51171.1	52061.1	51435.7	48886.2	46330.6	43781.1	41231.6
62.5°	40900.8	43245.9	45591.0	46535.1	47479.1	48164.6	47809.8	45392.6	42975.3	40558.1	38140.8
65°	35543.2	37166.7	38796.3	39433.6	40065.0	40552.1	40443.8	38405.4	36367.0	34334.6	32296.1
67.5°	28682.3	29945.0	31213.8	32115.8	33023.7	33727.3	33649.1	31791.0	29933.0	28075.0	26216.9
70°	22344.5	23655.4	24966.2	26102.7	27245.2	28129.1	28014.8	26289.1	24557.3	22831.6	21099.8
72.5°	17852.8	19344.0	20835.3	21484.7	22134.1	22591.1	22254.3	20949.5	19638.7	18333.8	17023.0
75°	10841.5	11623.2	12411.0	12404.9	12404.9	12332.8	11996.1	11250.4	10504.8	9759.2	9013.6
77.5°	3229.0	3571.8	3914.5	4245.2	4582.0	4834.5	4768.4	4377.5	3980.6	3589.8	3192.9
80°	889.9	980.1	1076.3	1118.4	1160.5	1214.6	1352.9	1256.7	1160.5	1070.3	974.1
82.5°	228.5	228.5	228.5	222.5	216.5	204.4	186.4	174.4	162.4	150.3	138.3
85°	36.1	30.1	30.1	30.1	24.1	24.1	24.1	24.1	18.0	18.0	12.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
2.5°	60.1	60.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	48.1
5°	72.2	72.2	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	60.1
7.5°	90.2	90.2	84.2	84.2	84.2	84.2	78.2	78.2	78.2	78.2	72.2
10°	114.2	108.2	108.2	102.2	102.2	102.2	96.2	96.2	96.2	90.2	90.2
12.5°	144.3	138.3	138.3	132.3	126.3	126.3	120.3	114.2	108.2	108.2	102.2
15°	192.4	186.4	180.4	174.4	168.4	156.3	150.3	138.3	132.3	126.3	120.3
17.5°	366.8	336.7	306.7	276.6	252.5	228.5	204.4	180.4	168.4	156.3	144.3
20°	1022.2	883.9	751.6	619.3	535.2	451.0	366.8	282.6	246.5	216.5	180.4
22.5°	2212.8	1936.2	1665.6	1389.0	1166.5	950.1	727.6	505.1	420.9	342.7	258.6
25°	4112.9	3583.8	3060.6	2531.5	2110.6	1689.7	1268.8	847.8	691.5	535.2	378.8
27.5°	6103.3	5417.8	4732.3	4046.8	3379.3	2705.9	2032.4	1365.0	1094.4	829.8	559.2
30°	7636.6	6909.0	6187.4	5459.9	4618.0	3776.2	2928.4	2086.5	1659.6	1232.7	799.7
32.5°	8953.4	8165.7	7384.0	6596.3	5622.2	4648.1	3674.0	2699.9	2164.7	1629.5	1088.4
35°	10258.3	9362.3	8472.4	7576.5	6530.2	5483.9	4437.6	3391.4	2711.9	2032.4	1346.9
37.5°	11845.7	10751.4	9663.0	8574.6	7498.3	6428.0	5351.6	4275.3	3409.4	2549.5	1683.7
40°	14611.7	13216.7	11827.7	10432.7	9175.9	7925.2	6668.5	5411.8	4323.4	3235.0	2140.6
42.5°	19891.2	18141.4	16397.6	14647.8	12910.0	11172.3	9428.5	7690.7	6139.3	4594.0	3042.6
45°	27257.2	25014.3	22777.5	20534.6	18394.0	16259.3	14118.7	11978.0	9620.9	7263.8	4900.6
47.5°	33240.2	30780.9	28327.5	25868.2	23493.0	21123.9	18748.7	16373.6	13355.0	10342.5	7323.9
50°	35940.1	33595.0	31255.9	28910.8	26529.6	24142.4	21755.3	19374.1	15910.6	12453.0	8989.5
52.5°	36848.0	34466.9	32091.7	29710.5	27347.4	24984.3	22621.1	20258.0	16656.2	13060.4	9458.5
55°	37347.1	34833.7	32326.2	29812.8	27269.2	24719.7	22170.2	19626.6	16042.8	12465.1	8881.3
57.5°	38357.3	35621.4	32891.4	30155.5	27257.2	24358.9	21454.6	18556.3	15020.6	11484.9	7949.3
60°	38543.7	35849.9	33162.0	30474.2	27269.2	24064.3	20853.3	17648.3	14136.7	10631.1	7119.5
62.5°	35892.0	33643.1	31400.2	29151.3	25940.3	22729.4	19512.4	16301.4	12940.1	9578.8	6211.5
65°	30353.9	28411.7	26475.5	24533.3	21911.6	19295.9	16674.2	14052.5	11052.0	8057.5	5057.0
67.5°	24316.8	22416.7	20522.6	18622.4	16650.2	14683.9	12711.6	10739.3	8424.3	6109.3	3794.2
70°	19277.9	17449.9	15627.9	13800.0	12056.2	10306.4	8556.6	6812.8	5375.7	3944.6	2507.4
72.5°	15279.2	13529.4	11785.6	10035.8	8454.4	6872.9	5291.5	3710.1	2994.5	2285.0	1569.4
75°	8105.6	7197.6	6295.7	5387.7	4497.8	3601.8	2705.9	1815.9	1533.3	1250.7	962.1
77.5°	2796.1	2399.2	2008.4	1611.5	1340.9	1070.3	799.7	529.1	499.1	475.0	445.0
80°	847.8	721.6	595.3	469.0	414.9	360.8	306.7	252.5	234.5	216.5	192.4
82.5°	132.3	120.3	114.2	102.2	96.2	96.2	90.2	84.2	72.2	66.1	54.1
85°	12.0	6.0	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	54.1	54.1
2.5°	48.1	48.1
5°	60.1	60.1
7.5°	72.2	72.2
10°	84.2	84.2
12.5°	96.2	96.2
15°	114.2	108.2
17.5°	132.3	126.3
20°	144.3	132.3
22.5°	174.4	150.3
25°	222.5	186.4
27.5°	288.6	228.5
30°	372.8	288.6
32.5°	553.2	402.9
35°	667.4	487.1
37.5°	817.8	565.2
40°	1052.3	685.5
42.5°	1491.2	932.0
45°	2543.5	1545.4
47.5°	4311.4	2633.7
50°	5526.0	3379.3
52.5°	5862.7	3583.8
55°	5303.5	3289.1
57.5°	4413.6	2796.1
60°	3613.8	2303.0
62.5°	2850.2	1822.0
65°	2056.5	1377.0
67.5°	1479.2	1058.3
70°	1076.3	829.8
72.5°	853.9	691.5
75°	679.5	577.3
77.5°	420.9	384.8
80°	174.4	162.4
82.5°	42.1	36.1
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066590

CATALOG NUMBER: NVN-SA5B-760-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-7

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-757-U-5WQ

Data in this report applies to families of products including GSS-SB1A-757-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-7
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-757-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI 5700K CCT 26 LEDS

Spectral Parameters

CCT (K):	5571	CRI (Ra):	69.9		
CIE u':	0.2033	R1:	68.8	R9:	-35.4
CIE v':	0.4806	R2:	72.5	R10:	36.7
Duv:	0.0041	R3:	76.8	R11:	73.9
CIE x:	0.3308	R4:	72.0	R12:	47.8
CIE y:	0.3476	R5:	70.9	R13:	68.0
CIE z:	0.3216	R6:	65.6	R14:	87.0
Peak Wavelength (nm):	442	R7:	75.5	R15:	59.8
Dominant Wavelength (nm):	544	R8:	56.8		
Purity:	3.635698				
Rf:	70.4				
Rg:	97.1				



Test Conditions

Stabilization Time: 20M
 Operation Time: 1H 20M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-7

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-7

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 5700K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-7

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	120	NR	620	298	NR	750	9	NR	880	0	NR
365	0	NR	495	167	NR	625	270	NR	755	7	NR	885	0	NR
370	0	NR	500	222	NR	630	245	NR	760	6	NR	890	0	NR
375	0	NR	505	279	NR	635	219	NR	765	6	NR	895	0	NR
380	1	NR	510	329	NR	640	196	NR	770	5	NR	900	0	NR
385	2	NR	515	371	NR	645	173	NR	775	4	NR	905	0	NR
390	4	NR	520	403	NR	650	153	NR	780	4	NR	910	0	NR
395	6	NR	525	424	NR	655	135	NR	785	3	NR	915	0	NR
400	9	NR	530	439	NR	660	117	NR	790	3	NR	920	0	NR
405	14	NR	535	449	NR	665	103	NR	795	2	NR	925	0	NR
410	28	NR	540	454	NR	670	89	NR	800	2	NR	930	0	NR
415	55	NR	545	459	NR	675	77	NR	805	2	NR	935	0	NR
420	118	NR	550	463	NR	680	67	NR	810	2	NR	940	0	NR
425	237	NR	555	466	NR	685	58	NR	815	1	NR	945	0	NR
430	420	NR	560	467	NR	690	50	NR	820	1	NR	950	0	NR
435	677	NR	565	469	NR	695	43	NR	825	1	NR	955	0	NR
440	962	NR	570	469	NR	700	37	NR	830	1	NR	960	0	NR
445	894	NR	575	466	NR	705	32	NR	835	1	NR	965	0	NR
450	472	NR	580	461	NR	710	28	NR	840	1	NR	970	0	NR
455	275	NR	585	450	NR	715	24	NR	845	1	NR	975	0	NR
460	180	NR	590	437	NR	720	21	NR	850	1	NR	980	0	NR
465	107	NR	595	420	NR	725	18	NR	855	0	NR	985	0	NR
470	76	NR	600	400	NR	730	15	NR	860	0	NR	990	0	NR
475	68	NR	605	376	NR	735	13	NR	865	0	NR	995	0	NR
480	69	NR	610	352	NR	740	11	NR	870	0	NR	1000	0	NR
485	86	NR	615	325	NR	745	10	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-7

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.84

λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)	λ (nm)	Power W [^] /nm	Lumens (Φ/nm)
360	0	NR	490	120	NR	620	298	NR	750	9	NR	880	0	NR
365	0	NR	495	167	NR	625	270	NR	755	7	NR	885	0	NR
370	0	NR	500	222	NR	630	245	NR	760	6	NR	890	0	NR
375	0	NR	505	279	NR	635	219	NR	765	6	NR	895	0	NR
380	1	NR	510	329	NR	640	196	NR	770	5	NR	900	0	NR
385	2	NR	515	371	NR	645	173	NR	775	4	NR	905	0	NR
390	4	NR	520	403	NR	650	153	NR	780	4	NR	910	0	NR
395	6	NR	525	424	NR	655	135	NR	785	3	NR	915	0	NR
400	9	NR	530	439	NR	660	117	NR	790	3	NR	920	0	NR
405	14	NR	535	449	NR	665	103	NR	795	2	NR	925	0	NR
410	28	NR	540	454	NR	670	89	NR	800	2	NR	930	0	NR
415	55	NR	545	459	NR	675	77	NR	805	2	NR	935	0	NR
420	118	NR	550	463	NR	680	67	NR	810	2	NR	940	0	NR
425	237	NR	555	466	NR	685	58	NR	815	1	NR	945	0	NR
430	420	NR	560	467	NR	690	50	NR	820	1	NR	950	0	NR
435	677	NR	565	469	NR	695	43	NR	825	1	NR	955	0	NR
440	962	NR	570	469	NR	700	37	NR	830	1	NR	960	0	NR
445	894	NR	575	466	NR	705	32	NR	835	1	NR	965	0	NR
450	472	NR	580	461	NR	710	28	NR	840	1	NR	970	0	NR
455	275	NR	585	450	NR	715	24	NR	845	1	NR	975	0	NR
460	180	NR	590	437	NR	720	21	NR	850	1	NR	980	0	NR
465	107	NR	595	420	NR	725	18	NR	855	0	NR	985	0	NR
470	76	NR	600	400	NR	730	15	NR	860	0	NR	990	0	NR
475	68	NR	605	376	NR	735	13	NR	865	0	NR	995	0	NR
480	69	NR	610	352	NR	740	11	NR	870	0	NR	1000	0	NR
485	86	NR	615	325	NR	745	10	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-7

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 3.71

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	120	NR	620	298	NR	750	9	NR	880	0	NR
365	0	NR	495	167	NR	625	270	NR	755	7	NR	885	0	NR
370	0	NR	500	222	NR	630	245	NR	760	6	NR	890	0	NR
375	0	NR	505	279	NR	635	219	NR	765	6	NR	895	0	NR
380	1	NR	510	329	NR	640	196	NR	770	5	NR	900	0	NR
385	2	NR	515	371	NR	645	173	NR	775	4	NR	905	0	NR
390	4	NR	520	403	NR	650	153	NR	780	4	NR	910	0	NR
395	6	NR	525	424	NR	655	135	NR	785	3	NR	915	0	NR
400	9	NR	530	439	NR	660	117	NR	790	3	NR	920	0	NR
405	14	NR	535	449	NR	665	103	NR	795	2	NR	925	0	NR
410	28	NR	540	454	NR	670	89	NR	800	2	NR	930	0	NR
415	55	NR	545	459	NR	675	77	NR	805	2	NR	935	0	NR
420	118	NR	550	463	NR	680	67	NR	810	2	NR	940	0	NR
425	237	NR	555	466	NR	685	58	NR	815	1	NR	945	0	NR
430	420	NR	560	467	NR	690	50	NR	820	1	NR	950	0	NR
435	677	NR	565	469	NR	695	43	NR	825	1	NR	955	0	NR
440	962	NR	570	469	NR	700	37	NR	830	1	NR	960	0	NR
445	894	NR	575	466	NR	705	32	NR	835	1	NR	965	0	NR
450	472	NR	580	461	NR	710	28	NR	840	1	NR	970	0	NR
455	275	NR	585	450	NR	715	24	NR	845	1	NR	975	0	NR
460	180	NR	590	437	NR	720	21	NR	850	1	NR	980	0	NR
465	107	NR	595	420	NR	725	18	NR	855	0	NR	985	0	NR
470	76	NR	600	400	NR	730	15	NR	860	0	NR	990	0	NR
475	68	NR	605	376	NR	735	13	NR	865	0	NR	995	0	NR
480	69	NR	610	352	NR	740	11	NR	870	0	NR	1000	0	NR
485	86	NR	615	325	NR	745	10	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-7


TM-30-18

Summary

$R_f = 70.4$
 $R_g = 97.1$
 $CIE R_a = 69.9$
 $R_g = -35.4$




Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 85	CES26 = 52	CES51 = 87	CES76 = 40
CES02 = 59	CES27 = 77	CES52 = 88	CES77 = 62
CES03 = 30	CES28 = 76	CES53 = 74	CES78 = 43
CES04 = 68	CES29 = 46	CES54 = 79	CES79 = 72
CES05 = 45	CES30 = 54	CES55 = 78	CES80 = 68
CES06 = 49	CES31 = 52	CES56 = 67	CES81 = 70
CES07 = 38	CES32 = 49	CES57 = 64	CES82 = 87
CES08 = 37	CES33 = 59	CES58 = 66	CES83 = 81
CES09 = 29	CES34 = 61	CES59 = 87	CES84 = 87
CES10 = 72	CES35 = 78	CES60 = 91	CES85 = 83
CES11 = 55	CES36 = 88	CES61 = 88	CES86 = 75
CES12 = 61	CES37 = 71	CES62 = 77	CES87 = 74
CES13 = 41	CES38 = 64	CES63 = 74	CES88 = 76
CES14 = 74	CES39 = 90	CES64 = 71	CES89 = 75
CES15 = 70	CES40 = 81	CES65 = 63	CES90 = 73
CES16 = 46	CES41 = 82	CES66 = 66	CES91 = 93
CES17 = 48	CES42 = 69	CES67 = 63	CES92 = 69
CES18 = 55	CES43 = 67	CES68 = 71	CES93 = 82
CES19 = 70	CES44 = 98	CES69 = 81	CES94 = 58
CES20 = 63	CES45 = 77	CES70 = 57	CES95 = 72
CES21 = 85	CES46 = 76	CES71 = 54	CES96 = 78
CES22 = 77	CES47 = 73	CES72 = 84	CES97 = 82
CES23 = 91	CES48 = 65	CES73 = 45	CES98 = 70
CES24 = 90	CES49 = 77	CES74 = 92	CES99 = 59
CES25 = 71	CES50 = 85	CES75 = 49	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)