

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066610

Luminaire Tested: **NVN-SA4B-827-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066610
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA4B-827-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 4xLight Square PACKAGE
80CRI 2700K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 2700K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 11177.5 lumens
Efficiency: N/A
Efficacy: 77.6 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 144.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.2 fc
 Type III - Short - N/A

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	66.5	0.0	66.5
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	11111.0	0.0	11111.0
	% Fixture	99.4	0.0	99.4
Total	Lumens	11177.5	0.0	11177.5
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.3	0.0
10°-20°	16.4	0.1
20°-30°	208.6	1.9
30°-40°	703.1	6.3
40°-50°	2123.4	19.0
50°-60°	3746.3	33.5
60°-70°	3300.5	29.5
70°-80°	1050.6	9.4
80°-90°	25.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	11177.5	100.0
0°-180°	11177.5	100.0



REPORT NUMBER: P1066610


CATALOG NUMBER: NVN-SA4B-827-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	218.4	2.0			
FM	(30°-60°)	6547.0	58.6			
FH	(60°-80°)	4325.1	38.7			G2/5000
FVH	(80°-90°)	20.6	0.2			G1/100
BL	(0°-30°)	10.0	0.1	B0/110		
BM	(30°-60°)	25.8	0.2	B0/220		
BH	(60°-80°)	26.0	0.2	B0/110		G0/110
BVH	(80°-90°)	4.7	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	24.5
5°	35.1	35.1	35.1	31.5	31.5	31.5	28.0	28.0	28.0	28.0	28.0
7.5°	42.1	38.6	38.6	35.1	35.1	35.1	31.5	31.5	31.5	31.5	28.0
10°	49.1	45.6	45.6	42.1	42.1	38.6	38.6	35.1	35.1	31.5	31.5
12.5°	56.1	52.6	49.1	45.6	45.6	42.1	42.1	38.6	38.6	35.1	35.1
15°	63.1	59.6	56.1	52.6	49.1	49.1	45.6	42.1	38.6	38.6	35.1
17.5°	73.6	66.6	63.1	56.1	52.6	49.1	45.6	42.1	42.1	38.6	38.6
20°	77.1	70.1	66.6	59.6	56.1	52.6	49.1	45.6	42.1	42.1	38.6
22.5°	91.1	77.1	73.6	66.6	63.1	59.6	52.6	49.1	45.6	42.1	38.6
25°	112.2	91.1	80.6	70.1	66.6	59.6	56.1	49.1	45.6	42.1	38.6
27.5°	136.7	101.7	91.1	77.1	70.1	63.1	56.1	49.1	45.6	42.1	38.6
30°	168.3	119.2	101.7	84.1	77.1	70.1	59.6	52.6	49.1	45.6	38.6
32.5°	234.9	147.2	119.2	91.1	80.6	73.6	63.1	52.6	49.1	45.6	38.6
35°	283.9	178.8	143.7	105.2	91.1	80.6	66.6	52.6	49.1	45.6	38.6
37.5°	329.5	182.3	147.2	112.2	98.1	84.1	66.6	52.6	49.1	45.6	38.6
40°	403.1	189.3	147.2	105.2	94.6	80.6	70.1	56.1	52.6	45.6	42.1
42.5°	543.3	217.3	157.7	98.1	87.6	80.6	70.1	59.6	52.6	49.1	42.1
45°	904.4	322.5	213.8	101.7	91.1	80.6	70.1	59.6	56.1	49.1	45.6
47.5°	1538.8	560.8	333.0	105.2	94.6	80.6	70.1	56.1	52.6	49.1	42.1
50°	1970.0	718.6	420.6	122.7	105.2	91.1	73.6	56.1	52.6	49.1	45.6
52.5°	2092.6	764.1	455.7	143.7	122.7	101.7	77.1	56.1	52.6	52.6	49.1
55°	1917.4	743.1	455.7	168.3	140.2	115.7	87.6	59.6	56.1	56.1	52.6
57.5°	1629.9	687.0	434.7	182.3	154.2	122.7	94.6	63.1	59.6	59.6	56.1
60°	1342.5	578.4	392.6	203.3	171.8	140.2	108.7	77.1	73.6	70.1	63.1
62.5°	1065.6	466.2	343.5	217.3	185.8	150.7	119.2	84.1	80.6	77.1	73.6
65°	802.7	406.6	319.0	227.8	192.8	157.7	122.7	87.6	84.1	84.1	80.6
67.5°	616.9	371.6	305.0	234.9	199.8	164.7	129.7	94.6	91.1	87.6	84.1
70°	487.2	343.5	287.4	231.3	199.8	168.3	133.2	101.7	94.6	91.1	84.1
72.5°	406.6	312.0	266.4	220.8	196.3	171.8	147.2	122.7	108.7	98.1	84.1
75°	340.0	280.4	241.9	199.8	182.3	168.3	150.7	133.2	115.7	98.1	80.6
77.5°	224.3	203.3	185.8	168.3	157.7	147.2	133.2	122.7	105.2	91.1	73.6
80°	94.6	87.6	91.1	91.1	91.1	91.1	87.6	87.6	77.1	66.6	52.6
82.5°	21.0	17.5	21.0	21.0	21.0	21.0	17.5	17.5	17.5	14.0	14.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5
5°	28.0	28.0	28.0	24.5	24.5	24.5	24.5	24.5	24.5	24.5	24.5
7.5°	28.0	28.0	28.0	24.5	24.5	24.5	24.5	21.0	21.0	21.0	21.0
10°	28.0	28.0	28.0	24.5	24.5	24.5	24.5	21.0	21.0	21.0	21.0
12.5°	31.5	31.5	28.0	28.0	24.5	24.5	24.5	21.0	21.0	21.0	21.0
15°	31.5	31.5	28.0	28.0	24.5	24.5	24.5	21.0	21.0	21.0	21.0
17.5°	35.1	31.5	31.5	28.0	24.5	24.5	24.5	21.0	21.0	21.0	21.0
20°	35.1	31.5	31.5	28.0	24.5	24.5	24.5	21.0	21.0	21.0	21.0
22.5°	35.1	31.5	31.5	28.0	24.5	24.5	21.0	21.0	17.5	17.5	14.0
25°	35.1	31.5	31.5	28.0	24.5	24.5	21.0	21.0	17.5	14.0	14.0
27.5°	35.1	31.5	31.5	28.0	24.5	21.0	21.0	17.5	14.0	10.5	10.5
30°	35.1	31.5	31.5	28.0	24.5	21.0	17.5	14.0	10.5	10.5	7.0
32.5°	35.1	31.5	28.0	24.5	21.0	17.5	17.5	14.0	10.5	7.0	7.0
35°	35.1	31.5	28.0	24.5	21.0	17.5	17.5	14.0	10.5	7.0	7.0
37.5°	35.1	31.5	28.0	24.5	21.0	17.5	14.0	10.5	7.0	7.0	3.5
40°	35.1	31.5	28.0	24.5	21.0	17.5	14.0	10.5	7.0	7.0	3.5
42.5°	35.1	31.5	28.0	24.5	21.0	17.5	14.0	10.5	7.0	7.0	3.5
45°	38.6	35.1	31.5	24.5	21.0	17.5	17.5	14.0	10.5	7.0	7.0
47.5°	38.6	35.1	31.5	24.5	21.0	17.5	17.5	14.0	10.5	7.0	7.0
50°	42.1	38.6	35.1	28.0	24.5	21.0	17.5	10.5	7.0	7.0	3.5
52.5°	45.6	42.1	38.6	35.1	31.5	24.5	17.5	10.5	3.5	3.5	3.5
55°	49.1	45.6	45.6	42.1	38.6	28.0	21.0	10.5	0.0	0.0	0.0
57.5°	52.6	49.1	49.1	45.6	42.1	31.5	21.0	10.5	0.0	0.0	0.0
60°	59.6	56.1	52.6	45.6	42.1	31.5	21.0	10.5	0.0	0.0	0.0
62.5°	70.1	63.1	52.6	45.6	35.1	28.0	17.5	10.5	0.0	0.0	0.0
65°	77.1	66.6	56.1	42.1	31.5	24.5	17.5	7.0	0.0	0.0	0.0
67.5°	80.6	66.6	56.1	42.1	28.0	21.0	14.0	7.0	0.0	0.0	0.0
70°	77.1	63.1	52.6	38.6	24.5	17.5	14.0	7.0	0.0	0.0	0.0
72.5°	70.1	59.6	45.6	35.1	21.0	17.5	10.5	7.0	0.0	0.0	0.0
75°	63.1	52.6	38.6	28.0	14.0	10.5	7.0	3.5	0.0	0.0	0.0
77.5°	56.1	45.6	31.5	21.0	7.0	7.0	3.5	3.5	0.0	0.0	0.0
80°	42.1	31.5	21.0	10.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	10.5	7.0	7.0	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0
5°	21.0	21.0	21.0	21.0	17.5	17.5	17.5	17.5	17.5	17.5	17.5
7.5°	21.0	21.0	21.0	21.0	17.5	17.5	17.5	17.5	14.0	14.0	14.0
10°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	14.0	14.0	14.0
12.5°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	14.0	14.0	14.0
15°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	14.0	14.0	10.5	10.5
17.5°	17.5	17.5	17.5	17.5	14.0	14.0	14.0	10.5	10.5	7.0	7.0
20°	17.5	17.5	17.5	14.0	14.0	10.5	10.5	7.0	7.0	3.5	3.5
22.5°	14.0	10.5	10.5	7.0	7.0	3.5	3.5	3.5	0.0	0.0	0.0
25°	10.5	7.0	7.0	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	7.0	3.5	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	7.0	3.5	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	21.0	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
5°	17.5	17.5	17.5	17.5	14.0	14.0	14.0	14.0	14.0	14.0	14.0
7.5°	14.0	14.0	14.0	14.0	14.0	14.0	10.5	10.5	10.5	10.5	10.5
10°	14.0	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	7.0	7.0
12.5°	14.0	10.5	10.5	10.5	7.0	7.0	7.0	7.0	7.0	3.5	3.5
15°	10.5	7.0	7.0	7.0	3.5	3.5	3.5	3.5	3.5	0.0	0.0
17.5°	7.0	3.5	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	21.0	21.0
5°	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0
7.5°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
10°	7.0	7.0	7.0	7.0	7.0	7.0	3.5	3.5	3.5	3.5	3.5
12.5°	3.5	3.5	3.5	3.5	3.5	3.5	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	21.0	21.0	21.0	21.0	21.0	24.5	24.5	28.0	28.0	31.5	31.5
5°	14.0	14.0	17.5	17.5	17.5	17.5	21.0	21.0	21.0	24.5	24.5
7.5°	10.5	10.5	10.5	10.5	10.5	14.0	14.0	17.5	17.5	21.0	21.0
10°	3.5	3.5	7.0	7.0	7.0	7.0	10.5	10.5	10.5	14.0	17.5
12.5°	0.0	0.0	3.5	3.5	3.5	3.5	7.0	7.0	7.0	10.5	14.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	7.0	10.5
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	7.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	35.1	35.1	38.6	38.6	42.1	42.1	45.6	45.6	45.6	45.6	45.6
5°	28.0	28.0	31.5	35.1	35.1	38.6	42.1	42.1	42.1	42.1	42.1
7.5°	24.5	24.5	28.0	31.5	31.5	35.1	38.6	38.6	42.1	42.1	42.1
10°	17.5	21.0	24.5	28.0	28.0	31.5	35.1	35.1	38.6	38.6	38.6
12.5°	14.0	17.5	21.0	24.5	24.5	28.0	31.5	31.5	35.1	35.1	38.6
15°	10.5	14.0	17.5	21.0	21.0	24.5	28.0	28.0	31.5	35.1	38.6
17.5°	7.0	10.5	14.0	17.5	17.5	21.0	24.5	28.0	31.5	31.5	35.1
20°	7.0	7.0	10.5	14.0	14.0	17.5	21.0	24.5	28.0	28.0	31.5
22.5°	3.5	3.5	7.0	10.5	10.5	14.0	17.5	21.0	24.5	24.5	28.0
25°	0.0	0.0	3.5	7.0	7.0	10.5	14.0	14.0	17.5	17.5	21.0
27.5°	0.0	0.0	3.5	3.5	7.0	7.0	10.5	10.5	14.0	14.0	17.5
30°	0.0	0.0	3.5	3.5	7.0	7.0	10.5	10.5	14.0	14.0	14.0
32.5°	0.0	0.0	0.0	3.5	3.5	3.5	7.0	7.0	10.5	10.5	14.0
35°	0.0	0.0	0.0	3.5	3.5	3.5	7.0	7.0	10.5	10.5	10.5
37.5°	0.0	0.0	0.0	3.5	3.5	3.5	7.0	7.0	7.0	7.0	10.5
40°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
55°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5
75°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	7.0	7.0	7.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	7.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.5	3.5	3.5	3.5	3.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	45.6	45.6
5°	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	42.1	42.1
7.5°	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	42.1	42.1
10°	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
12.5°	38.6	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
15°	38.6	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
17.5°	35.1	38.6	38.6	38.6	42.1	42.1	42.1	42.1	42.1	42.1	42.1
20°	31.5	35.1	35.1	35.1	38.6	38.6	38.6	38.6	42.1	42.1	42.1
22.5°	28.0	31.5	31.5	31.5	35.1	35.1	35.1	35.1	38.6	38.6	38.6
25°	24.5	24.5	28.0	28.0	31.5	31.5	31.5	31.5	31.5	31.5	31.5
27.5°	17.5	21.0	21.0	21.0	24.5	24.5	24.5	24.5	28.0	28.0	28.0
30°	17.5	17.5	17.5	17.5	21.0	21.0	21.0	21.0	24.5	24.5	24.5
32.5°	14.0	17.5	17.5	17.5	21.0	21.0	21.0	21.0	24.5	24.5	24.5
35°	14.0	14.0	14.0	14.0	17.5	17.5	17.5	17.5	21.0	21.0	21.0
37.5°	10.5	14.0	14.0	14.0	17.5	17.5	17.5	17.5	21.0	21.0	21.0
40°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
42.5°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
45°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
47.5°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
50°	10.5	10.5	10.5	10.5	14.0	14.0	14.0	14.0	17.5	17.5	17.5
52.5°	7.0	7.0	7.0	7.0	10.5	10.5	10.5	10.5	14.0	14.0	14.0
55°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.5	10.5	10.5
57.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.5	10.5	10.5
60°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
62.5°	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
65°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	3.5	3.5
67.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
70°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
72.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
75°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
77.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
80°	10.5	10.5	10.5	10.5	10.5	7.0	7.0	7.0	7.0	7.0	7.0
82.5°	7.0	10.5	10.5	10.5	10.5	7.0	7.0	7.0	7.0	7.0	7.0
85°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
87.5°	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	45.6	45.6	42.1	42.1	42.1	42.1	42.1	42.1	42.1	45.6	45.6
5°	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	45.6	45.6
7.5°	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	45.6	45.6
10°	42.1	42.1	42.1	42.1	38.6	38.6	42.1	42.1	42.1	45.6	45.6
12.5°	42.1	42.1	42.1	42.1	38.6	38.6	42.1	42.1	45.6	45.6	49.1
15°	42.1	42.1	38.6	38.6	38.6	38.6	42.1	42.1	45.6	45.6	49.1
17.5°	42.1	42.1	38.6	38.6	38.6	38.6	42.1	42.1	45.6	45.6	49.1
20°	42.1	42.1	38.6	38.6	38.6	38.6	38.6	38.6	42.1	45.6	45.6
22.5°	38.6	38.6	38.6	38.6	35.1	35.1	38.6	38.6	42.1	45.6	45.6
25°	31.5	35.1	35.1	35.1	35.1	35.1	38.6	38.6	42.1	45.6	45.6
27.5°	28.0	31.5	31.5	31.5	31.5	35.1	35.1	38.6	42.1	45.6	45.6
30°	24.5	28.0	28.0	28.0	31.5	35.1	35.1	38.6	42.1	45.6	45.6
32.5°	24.5	28.0	28.0	28.0	31.5	31.5	35.1	35.1	38.6	42.1	45.6
35°	24.5	24.5	28.0	28.0	28.0	31.5	31.5	35.1	38.6	42.1	45.6
37.5°	24.5	24.5	28.0	28.0	28.0	31.5	31.5	35.1	38.6	42.1	45.6
40°	21.0	24.5	24.5	28.0	28.0	31.5	31.5	35.1	38.6	45.6	49.1
42.5°	21.0	21.0	24.5	24.5	28.0	31.5	31.5	35.1	38.6	45.6	49.1
45°	21.0	24.5	24.5	28.0	31.5	35.1	35.1	38.6	42.1	45.6	49.1
47.5°	21.0	24.5	24.5	28.0	35.1	35.1	38.6	38.6	42.1	45.6	49.1
50°	21.0	24.5	24.5	28.0	38.6	38.6	38.6	38.6	42.1	45.6	49.1
52.5°	17.5	21.0	21.0	24.5	31.5	35.1	38.6	42.1	45.6	49.1	52.6
55°	14.0	17.5	17.5	21.0	28.0	31.5	38.6	45.6	49.1	52.6	56.1
57.5°	14.0	14.0	17.5	17.5	24.5	31.5	42.1	49.1	52.6	56.1	59.6
60°	10.5	10.5	14.0	14.0	21.0	28.0	38.6	49.1	52.6	59.6	63.1
62.5°	7.0	10.5	10.5	14.0	17.5	28.0	38.6	49.1	56.1	63.1	66.6
65°	7.0	7.0	10.5	10.5	17.5	24.5	35.1	42.1	52.6	63.1	73.6
67.5°	10.5	10.5	14.0	14.0	17.5	24.5	35.1	42.1	52.6	66.6	77.1
70°	10.5	10.5	14.0	14.0	21.0	28.0	35.1	42.1	52.6	66.6	77.1
72.5°	10.5	10.5	14.0	14.0	21.0	24.5	31.5	38.6	49.1	59.6	70.1
75°	7.0	10.5	10.5	10.5	17.5	21.0	28.0	35.1	45.6	56.1	66.6
77.5°	7.0	7.0	7.0	7.0	14.0	17.5	24.5	28.0	38.6	49.1	59.6
80°	7.0	7.0	7.0	7.0	10.5	14.0	21.0	24.5	35.1	45.6	56.1
82.5°	7.0	7.0	3.5	3.5	7.0	10.5	14.0	17.5	28.0	35.1	45.6
85°	7.0	7.0	3.5	3.5	3.5	7.0	7.0	10.5	14.0	17.5	21.0
87.5°	7.0	7.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	45.6	45.6	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1
5°	45.6	49.1	49.1	52.6	52.6	52.6	56.1	56.1	56.1	56.1	56.1
7.5°	45.6	49.1	49.1	52.6	52.6	52.6	56.1	56.1	56.1	59.6	59.6
10°	45.6	49.1	49.1	52.6	52.6	56.1	59.6	59.6	63.1	63.1	63.1
12.5°	49.1	52.6	52.6	56.1	56.1	59.6	63.1	63.1	66.6	70.1	70.1
15°	49.1	52.6	56.1	56.1	59.6	63.1	66.6	66.6	70.1	73.6	77.1
17.5°	49.1	52.6	56.1	56.1	59.6	63.1	70.1	73.6	77.1	84.1	87.6
20°	49.1	52.6	56.1	56.1	59.6	66.6	70.1	77.1	80.6	87.6	94.6
22.5°	49.1	52.6	56.1	59.6	63.1	70.1	77.1	80.6	87.6	98.1	105.2
25°	49.1	52.6	56.1	59.6	63.1	70.1	77.1	84.1	91.1	105.2	119.2
27.5°	49.1	52.6	59.6	63.1	66.6	73.6	84.1	91.1	98.1	122.7	147.2
30°	49.1	52.6	59.6	63.1	66.6	77.1	87.6	94.6	105.2	147.2	185.8
32.5°	49.1	56.1	59.6	66.6	70.1	80.6	94.6	105.2	115.7	175.3	231.3
35°	49.1	56.1	59.6	66.6	70.1	84.1	98.1	112.2	126.2	213.8	301.5
37.5°	49.1	56.1	59.6	66.6	70.1	91.1	112.2	133.2	154.2	245.4	336.5
40°	52.6	59.6	63.1	70.1	73.6	94.6	115.7	136.7	157.7	248.9	340.0
42.5°	52.6	59.6	63.1	70.1	73.6	91.1	112.2	129.7	147.2	248.9	350.5
45°	52.6	59.6	66.6	70.1	77.1	94.6	112.2	126.2	143.7	273.4	399.6
47.5°	52.6	59.6	66.6	70.1	77.1	94.6	112.2	129.7	147.2	361.0	571.4
50°	52.6	59.6	66.6	70.1	77.1	98.1	119.2	140.2	161.2	539.8	918.4
52.5°	56.1	59.6	66.6	70.1	73.6	98.1	122.7	147.2	171.8	701.1	1226.8
55°	59.6	63.1	66.6	70.1	73.6	105.2	136.7	168.3	199.8	753.6	1304.0
57.5°	63.1	66.6	70.1	70.1	73.6	112.2	154.2	192.8	231.3	750.1	1265.4
60°	66.6	70.1	73.6	77.1	80.6	119.2	161.2	199.8	238.4	680.0	1121.7
62.5°	73.6	80.6	87.6	91.1	98.1	136.7	171.8	210.3	245.4	557.3	865.8
65°	84.1	91.1	94.6	101.7	105.2	140.2	178.8	213.8	248.9	462.7	673.0
67.5°	87.6	94.6	98.1	105.2	108.7	143.7	178.8	213.8	248.9	392.6	532.8
70°	87.6	94.6	101.7	105.2	112.2	147.2	178.8	213.8	245.4	340.0	434.7
72.5°	80.6	91.1	98.1	108.7	115.7	147.2	175.3	206.8	234.9	301.5	368.1
75°	77.1	91.1	101.7	115.7	126.2	147.2	171.8	192.8	213.8	262.9	312.0
77.5°	70.1	87.6	105.2	122.7	140.2	154.2	164.7	178.8	189.3	220.8	252.4
80°	66.6	84.1	101.7	119.2	136.7	143.7	147.2	154.2	157.7	161.2	164.7
82.5°	52.6	66.6	80.6	91.1	105.2	98.1	94.6	87.6	80.6	77.1	73.6
85°	24.5	28.0	28.0	31.5	31.5	31.5	28.0	28.0	24.5	21.0	17.5
87.5°	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	49.1	49.1	49.1	49.1	45.6	45.6	45.6	45.6	42.1	42.1	42.1
5°	56.1	56.1	56.1	56.1	52.6	52.6	52.6	52.6	49.1	49.1	49.1
7.5°	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
10°	66.6	66.6	66.6	70.1	70.1	70.1	70.1	70.1	70.1	70.1	70.1
12.5°	73.6	73.6	77.1	77.1	80.6	80.6	84.1	84.1	87.6	87.6	87.6
15°	80.6	84.1	87.6	91.1	91.1	94.6	98.1	101.7	105.2	108.7	112.2
17.5°	94.6	98.1	105.2	112.2	119.2	126.2	136.7	150.7	161.2	171.8	185.8
20°	105.2	115.7	136.7	161.2	182.3	203.3	255.9	308.5	361.0	413.6	466.2
22.5°	126.2	147.2	217.3	290.9	361.0	431.1	595.9	760.6	921.9	1086.6	1233.9
25°	168.3	213.8	375.1	536.3	694.0	855.3	1149.7	1447.7	1742.1	2036.6	2310.0
27.5°	231.3	315.5	578.4	844.8	1107.7	1370.6	1798.2	2229.3	2657.0	3088.1	3470.2
30°	322.5	459.2	851.8	1247.9	1640.5	2033.0	2572.9	3116.2	3656.0	4195.8	4546.3
32.5°	438.2	641.5	1139.2	1637.0	2134.7	2632.4	3228.3	3824.2	4416.6	5012.5	5384.1
35°	560.8	820.2	1419.6	2022.5	2621.9	3224.8	3852.3	4479.7	5107.2	5734.6	6190.3
37.5°	630.9	925.4	1637.0	2348.5	3056.6	3768.2	4455.2	5145.7	5832.8	6519.8	7073.6
40°	697.5	1051.6	1871.8	2692.0	3512.3	4332.5	5135.2	5937.9	6740.6	7543.3	8254.9
42.5°	795.7	1240.9	2197.8	3154.7	4108.2	5065.1	6120.2	7178.8	8233.9	9288.9	10382.6
45°	999.0	1598.4	2839.3	4080.1	5317.5	6558.3	8055.1	9555.3	11052.1	12552.3	13954.4
47.5°	1489.7	2404.6	4097.6	5790.7	7483.7	9176.8	10901.4	12625.9	14350.5	16075.1	17743.6
50°	2306.5	3691.0	5808.2	7925.4	10039.1	12156.2	13877.3	15598.4	17316.0	19037.1	20695.0
52.5°	3074.1	4921.4	7196.3	9474.7	11749.6	14028.0	15552.8	17077.6	18602.4	20127.2	21732.6
55°	3337.0	5366.6	7669.5	9976.0	12278.9	14585.4	16054.1	17526.3	18995.0	20463.7	22128.7
57.5°	3105.7	4945.9	7266.4	9586.9	11903.9	14224.3	15864.8	17508.8	19149.2	20793.2	22577.4
60°	2600.9	4076.6	6512.8	8952.4	11388.6	13824.7	15675.5	17526.3	19377.1	21227.8	23008.5
62.5°	2061.1	3252.9	5832.8	8412.6	10992.5	13572.4	15454.7	17340.5	19222.8	21105.2	22472.2
65°	1580.9	2488.7	5026.5	7567.9	10105.7	12647.0	14189.3	15735.1	17277.4	18823.2	19769.7
67.5°	1174.3	1815.7	4034.6	6256.9	8475.7	10694.5	11830.2	12969.5	14105.2	15244.4	15980.5
70°	865.8	1293.4	2804.2	4315.0	5822.2	7333.0	8374.1	9415.1	10452.7	11493.7	12257.9
72.5°	599.4	827.2	1731.6	2639.5	3543.8	4448.2	5503.3	6558.3	7609.9	8665.0	9534.3
75°	410.1	508.3	932.4	1356.5	1780.7	2204.8	3004.0	3803.2	4602.4	5401.6	5860.8
77.5°	305.0	357.5	483.7	613.4	739.6	865.8	1020.0	1174.3	1328.5	1482.7	1682.5
80°	168.3	168.3	185.8	199.8	217.3	231.3	273.4	319.0	361.0	406.6	462.7
82.5°	77.1	80.6	87.6	94.6	98.1	105.2	112.2	119.2	126.2	133.2	133.2
85°	21.0	24.5	24.5	21.0	21.0	17.5	17.5	21.0	21.0	21.0	21.0
87.5°	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	42.1	38.6	38.6	38.6	35.1	35.1	35.1	35.1	35.1	35.1	35.1
5°	49.1	49.1	49.1	49.1	45.6	45.6	45.6	45.6	45.6	42.1	42.1
7.5°	59.6	56.1	56.1	56.1	56.1	56.1	56.1	56.1	56.1	52.6	52.6
10°	70.1	70.1	70.1	70.1	70.1	70.1	70.1	70.1	70.1	66.6	66.6
12.5°	87.6	87.6	87.6	87.6	91.1	91.1	87.6	87.6	87.6	84.1	84.1
15°	115.7	119.2	122.7	122.7	126.2	126.2	126.2	122.7	122.7	119.2	115.7
17.5°	196.3	206.8	220.8	234.9	248.9	259.4	259.4	252.4	245.4	238.4	231.3
20°	522.3	574.9	630.9	687.0	746.6	788.7	760.6	739.6	718.6	694.0	673.0
22.5°	1384.6	1531.8	1682.5	1787.7	1892.8	1966.5	1906.9	1791.2	1675.5	1563.3	1447.7
25°	2583.4	2853.3	3126.7	3238.9	3354.5	3438.7	3400.1	3224.8	3049.6	2877.8	2702.6
27.5°	3852.3	4230.8	4612.9	4711.1	4809.2	4882.8	4868.8	4641.0	4413.1	4185.3	3957.4
30°	4896.8	5247.4	5597.9	5696.0	5794.2	5860.8	5787.2	5559.3	5331.5	5103.7	4875.8
32.5°	5759.1	6130.7	6505.8	6635.5	6765.1	6852.8	6765.1	6491.7	6218.3	5948.4	5675.0
35°	6646.0	7098.1	7553.8	7718.6	7883.3	7988.5	7841.3	7504.8	7168.3	6835.3	6498.7
37.5°	7627.4	8177.8	8731.6	8955.9	9183.8	9341.5	9229.3	8808.7	8384.6	7963.9	7539.8
40°	8970.0	9681.5	10396.6	10799.7	11199.3	11483.2	11283.4	10796.2	10305.5	9818.2	9327.5
42.5°	11479.7	12573.4	13667.0	14245.4	14820.2	15237.4	15013.0	14413.6	13814.2	13214.8	12615.4
45°	15356.5	16755.1	18157.2	19002.0	19850.3	20474.2	20214.8	19461.2	18704.1	17950.4	17196.8
47.5°	19412.1	21080.6	22749.1	23422.1	24098.7	24624.4	24561.3	23621.9	22682.5	21746.6	20807.2
50°	22356.5	24014.5	25672.5	26250.9	26832.8	27263.9	27102.7	25907.4	24708.6	23513.3	22314.5
52.5°	23338.0	24939.9	26545.3	27235.9	27926.4	28441.7	28245.4	26899.4	25553.3	24210.8	22864.8
55°	23793.7	25458.7	27123.7	27965.0	28809.7	29426.6	29142.7	27667.0	26187.8	24712.1	23232.9
57.5°	24361.5	26145.7	27929.9	28851.8	29773.7	30439.7	30061.1	28532.8	27004.5	25479.7	23951.4
60°	24789.2	26566.4	28347.0	29086.6	29829.8	30348.5	29984.0	28497.8	27008.0	25521.8	24035.6
62.5°	23842.8	25209.8	26576.9	27127.2	27677.5	28077.1	27870.3	26461.2	25052.1	23643.0	22233.9
65°	20719.6	21666.0	22615.9	22987.5	23355.5	23639.5	23576.4	22388.1	21199.8	20015.0	18826.7
67.5°	16720.1	17456.2	18195.8	18721.6	19250.9	19661.0	19615.4	18532.3	17449.2	16366.1	15282.9
70°	13025.5	13789.7	14553.8	15216.3	15882.3	16397.6	16331.0	15325.0	14315.5	13309.5	12300.0
72.5°	10407.1	11276.4	12145.7	12524.3	12902.9	13169.3	12973.0	12212.3	11448.2	10687.5	9923.4
75°	6320.0	6775.7	7234.9	7231.3	7231.3	7189.3	6993.0	6558.3	6123.7	5689.0	5254.4
77.5°	1882.3	2082.1	2281.9	2474.7	2671.0	2818.2	2779.7	2551.8	2320.5	2092.6	1861.3
80°	518.8	571.4	627.4	652.0	676.5	708.1	788.7	732.6	676.5	623.9	567.9
82.5°	133.2	133.2	133.2	129.7	126.2	119.2	108.7	101.7	94.6	87.6	80.6
85°	21.0	17.5	17.5	17.5	14.0	14.0	14.0	14.0	10.5	10.5	7.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
2.5°	35.1	35.1	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	28.0
5°	42.1	42.1	38.6	38.6	38.6	38.6	38.6	38.6	38.6	38.6	35.1
7.5°	52.6	52.6	49.1	49.1	49.1	49.1	45.6	45.6	45.6	45.6	42.1
10°	66.6	63.1	63.1	59.6	59.6	59.6	56.1	56.1	56.1	52.6	52.6
12.5°	84.1	80.6	80.6	77.1	73.6	73.6	70.1	66.6	63.1	63.1	59.6
15°	112.2	108.7	105.2	101.7	98.1	91.1	87.6	80.6	77.1	73.6	70.1
17.5°	213.8	196.3	178.8	161.2	147.2	133.2	119.2	105.2	98.1	91.1	84.1
20°	595.9	515.3	438.2	361.0	312.0	262.9	213.8	164.7	143.7	126.2	105.2
22.5°	1289.9	1128.7	971.0	809.7	680.0	553.8	424.1	294.4	245.4	199.8	150.7
25°	2397.6	2089.1	1784.2	1475.7	1230.3	985.0	739.6	494.2	403.1	312.0	220.8
27.5°	3557.8	3158.2	2758.6	2359.0	1970.0	1577.4	1184.8	795.7	638.0	483.7	326.0
30°	4451.7	4027.5	3606.9	3182.8	2692.0	2201.3	1707.1	1216.3	967.5	718.6	466.2
32.5°	5219.3	4760.1	4304.5	3845.3	3277.4	2709.6	2141.7	1573.9	1261.9	949.9	634.5
35°	5980.0	5457.7	4938.9	4416.6	3806.7	3196.8	2586.9	1977.0	1580.9	1184.8	785.2
37.5°	6905.4	6267.4	5633.0	4998.5	4371.1	3747.1	3119.7	2492.2	1987.5	1486.2	981.5
40°	8517.8	7704.6	6894.8	6081.6	5349.0	4619.9	3887.3	3154.7	2520.3	1885.8	1247.9
42.5°	11595.4	10575.4	9558.8	8538.8	7525.8	6512.8	5496.2	4483.2	3578.9	2678.0	1773.7
45°	15889.3	14581.9	13277.9	11970.5	10722.6	9478.2	8230.3	6982.5	5608.4	4234.4	2856.8
47.5°	19377.1	17943.4	16513.3	15079.6	13695.0	12314.0	10929.4	9544.8	7785.2	6029.0	4269.4
50°	20950.9	19583.9	18220.3	16853.3	15465.2	14073.6	12682.0	11293.9	9274.9	7259.4	5240.4
52.5°	21480.2	20092.1	18707.6	17319.5	15941.9	14564.3	13186.8	11809.2	9709.6	7613.4	5513.8
55°	21771.2	20306.0	18844.3	17379.1	15896.3	14410.1	12923.9	11441.2	9352.0	7266.4	5177.3
57.5°	22360.0	20765.2	19173.8	17578.9	15889.3	14199.8	12506.8	10817.2	8756.1	6695.0	4634.0
60°	22468.7	20898.4	19331.5	17764.7	15896.3	14028.0	12156.2	10287.9	8240.9	6197.3	4150.2
62.5°	20922.9	19611.9	18304.5	16993.5	15121.7	13249.9	11374.6	9502.8	7543.3	5583.9	3620.9
65°	17694.5	16562.3	15433.7	14301.5	12773.2	11248.4	9720.1	8191.8	6442.7	4697.0	2947.9
67.5°	14175.3	13067.6	11963.4	10855.8	9706.1	8559.8	7410.1	6260.4	4910.9	3561.3	2211.8
70°	11237.9	10172.3	9110.2	8044.6	7028.0	6008.0	4988.0	3971.5	3133.7	2299.4	1461.7
72.5°	8906.9	7886.8	6870.3	5850.3	4928.4	4006.5	3084.6	2162.7	1745.6	1332.0	914.9
75°	4725.1	4195.8	3670.0	3140.7	2621.9	2099.6	1577.4	1058.6	893.8	729.1	560.8
77.5°	1629.9	1398.6	1170.8	939.4	781.7	623.9	466.2	308.5	290.9	276.9	259.4
80°	494.2	420.6	347.0	273.4	241.9	210.3	178.8	147.2	136.7	126.2	112.2
82.5°	77.1	70.1	66.6	59.6	56.1	56.1	52.6	49.1	42.1	38.6	31.5
85°	7.0	3.5	3.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	31.5	31.5
2.5°	28.0	28.0
5°	35.1	35.1
7.5°	42.1	42.1
10°	49.1	49.1
12.5°	56.1	56.1
15°	66.6	63.1
17.5°	77.1	73.6
20°	84.1	77.1
22.5°	101.7	87.6
25°	129.7	108.7
27.5°	168.3	133.2
30°	217.3	168.3
32.5°	322.5	234.9
35°	389.1	283.9
37.5°	476.7	329.5
40°	613.4	399.6
42.5°	869.3	543.3
45°	1482.7	900.9
47.5°	2513.3	1535.3
50°	3221.3	1970.0
52.5°	3417.6	2089.1
55°	3091.6	1917.4
57.5°	2572.9	1629.9
60°	2106.7	1342.5
62.5°	1661.5	1062.1
65°	1198.8	802.7
67.5°	862.3	616.9
70°	627.4	483.7
72.5°	497.7	403.1
75°	396.1	336.5
77.5°	245.4	224.3
80°	101.7	94.6
82.5°	24.5	21.0
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066610

CATALOG NUMBER: NVN-SA4B-827-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-8

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-827-U-5WQ

Data in this report applies to families of products including GSS-SB1A-827-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-8
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-827-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI
 2700K CCT 26 LEDS

Spectral Parameters

CCT (K): 2756
 CIE u' : 0.2599
 CIE v' : 0.5271
 Duv: 0.0006
 CIE x: 0.4563
 CIE y: 0.4112
 CIE z: 0.1325
 Peak Wavelength (nm): 609
 Dominant Wavelength (nm): 583
 Purity: 60.41121
 R_f: 82.2
 R_g: 99.9

CRI (Ra): 82.9
 R1: 81.6
 R2: 88.8
 R3: 96.0
 R4: 83.4
 R5: 81.4
 R6: 87.0
 R7: 84.0
 R8: 60.8
 R9: 10.8
 R10: 74.8
 R11: 84.3
 R12: 72.1
 R13: 82.9
 R14: 97.3
 R15: 73.7



Test Conditions

Stabilization Time: 29M
 Operation Time: 1H 29M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-8

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-8

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2700K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-8

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	158	NR	620	959	NR	750	35	NR	880	1	NR
365	0	NR	495	211	NR	625	918	NR	755	30	NR	885	1	NR
370	0	NR	500	264	NR	630	873	NR	760	26	NR	890	1	NR
375	0	NR	505	318	NR	635	816	NR	765	22	NR	895	1	NR
380	0	NR	510	363	NR	640	755	NR	770	19	NR	900	1	NR
385	0	NR	515	403	NR	645	689	NR	775	16	NR	905	1	NR
390	0	NR	520	435	NR	650	626	NR	780	14	NR	910	0	NR
395	1	NR	525	459	NR	655	564	NR	785	12	NR	915	0	NR
400	3	NR	530	481	NR	660	503	NR	790	10	NR	920	0	NR
405	6	NR	535	501	NR	665	447	NR	795	9	NR	925	0	NR
410	13	NR	540	519	NR	670	392	NR	800	8	NR	930	0	NR
415	26	NR	545	542	NR	675	343	NR	805	7	NR	935	0	NR
420	51	NR	550	565	NR	680	299	NR	810	6	NR	940	0	NR
425	93	NR	555	593	NR	685	260	NR	815	5	NR	945	0	NR
430	156	NR	560	624	NR	690	225	NR	820	4	NR	950	0	NR
435	250	NR	565	662	NR	695	194	NR	825	4	NR	955	0	NR
440	391	NR	570	707	NR	700	166	NR	830	3	NR	960	0	NR
445	460	NR	575	756	NR	705	143	NR	835	3	NR	965	0	NR
450	293	NR	580	810	NR	710	122	NR	840	2	NR	970	0	NR
455	188	NR	585	860	NR	715	105	NR	845	2	NR	975	0	NR
460	149	NR	590	910	NR	720	90	NR	850	2	NR	980	0	NR
465	103	NR	595	950	NR	725	77	NR	855	2	NR	985	0	NR
470	80	NR	600	980	NR	730	66	NR	860	1	NR	990	0	NR
475	82	NR	605	995	NR	735	56	NR	865	1	NR	995	0	NR
480	92	NR	610	998	NR	740	48	NR	870	1	NR	1000	0	NR
485	116	NR	615	985	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-8

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.2

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	158	NR	620	959	NR	750	35	NR	880	1	NR
365	0	NR	495	211	NR	625	918	NR	755	30	NR	885	1	NR
370	0	NR	500	264	NR	630	873	NR	760	26	NR	890	1	NR
375	0	NR	505	318	NR	635	816	NR	765	22	NR	895	1	NR
380	0	NR	510	363	NR	640	755	NR	770	19	NR	900	1	NR
385	0	NR	515	403	NR	645	689	NR	775	16	NR	905	1	NR
390	0	NR	520	435	NR	650	626	NR	780	14	NR	910	0	NR
395	1	NR	525	459	NR	655	564	NR	785	12	NR	915	0	NR
400	3	NR	530	481	NR	660	503	NR	790	10	NR	920	0	NR
405	6	NR	535	501	NR	665	447	NR	795	9	NR	925	0	NR
410	13	NR	540	519	NR	670	392	NR	800	8	NR	930	0	NR
415	26	NR	545	542	NR	675	343	NR	805	7	NR	935	0	NR
420	51	NR	550	565	NR	680	299	NR	810	6	NR	940	0	NR
425	93	NR	555	593	NR	685	260	NR	815	5	NR	945	0	NR
430	156	NR	560	624	NR	690	225	NR	820	4	NR	950	0	NR
435	250	NR	565	662	NR	695	194	NR	825	4	NR	955	0	NR
440	391	NR	570	707	NR	700	166	NR	830	3	NR	960	0	NR
445	460	NR	575	756	NR	705	143	NR	835	3	NR	965	0	NR
450	293	NR	580	810	NR	710	122	NR	840	2	NR	970	0	NR
455	188	NR	585	860	NR	715	105	NR	845	2	NR	975	0	NR
460	149	NR	590	910	NR	720	90	NR	850	2	NR	980	0	NR
465	103	NR	595	950	NR	725	77	NR	855	2	NR	985	0	NR
470	80	NR	600	980	NR	730	66	NR	860	1	NR	990	0	NR
475	82	NR	605	995	NR	735	56	NR	865	1	NR	995	0	NR
480	92	NR	610	998	NR	740	48	NR	870	1	NR	1000	0	NR
485	116	NR	615	985	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-8

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.16

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	158	NR	620	959	NR	750	35	NR	880	1	NR
365	0	NR	495	211	NR	625	918	NR	755	30	NR	885	1	NR
370	0	NR	500	264	NR	630	873	NR	760	26	NR	890	1	NR
375	0	NR	505	318	NR	635	816	NR	765	22	NR	895	1	NR
380	0	NR	510	363	NR	640	755	NR	770	19	NR	900	1	NR
385	0	NR	515	403	NR	645	689	NR	775	16	NR	905	1	NR
390	0	NR	520	435	NR	650	626	NR	780	14	NR	910	0	NR
395	1	NR	525	459	NR	655	564	NR	785	12	NR	915	0	NR
400	3	NR	530	481	NR	660	503	NR	790	10	NR	920	0	NR
405	6	NR	535	501	NR	665	447	NR	795	9	NR	925	0	NR
410	13	NR	540	519	NR	670	392	NR	800	8	NR	930	0	NR
415	26	NR	545	542	NR	675	343	NR	805	7	NR	935	0	NR
420	51	NR	550	565	NR	680	299	NR	810	6	NR	940	0	NR
425	93	NR	555	593	NR	685	260	NR	815	5	NR	945	0	NR
430	156	NR	560	624	NR	690	225	NR	820	4	NR	950	0	NR
435	250	NR	565	662	NR	695	194	NR	825	4	NR	955	0	NR
440	391	NR	570	707	NR	700	166	NR	830	3	NR	960	0	NR
445	460	NR	575	756	NR	705	143	NR	835	3	NR	965	0	NR
450	293	NR	580	810	NR	710	122	NR	840	2	NR	970	0	NR
455	188	NR	585	860	NR	715	105	NR	845	2	NR	975	0	NR
460	149	NR	590	910	NR	720	90	NR	850	2	NR	980	0	NR
465	103	NR	595	950	NR	725	77	NR	855	2	NR	985	0	NR
470	80	NR	600	980	NR	730	66	NR	860	1	NR	990	0	NR
475	82	NR	605	995	NR	735	56	NR	865	1	NR	995	0	NR
480	92	NR	610	998	NR	740	48	NR	870	1	NR	1000	0	NR
485	116	NR	615	985	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-8

TM-30-18

Summary

$R_f = 82.2$
 $R_g = 99.9$
 $CIE R_a = 82.9$
 $R_9 = 10.8$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 76	CES51 = 89	CES76 = 75
CES02 = 63	CES27 = 89	CES52 = 91	CES77 = 87
CES03 = 31	CES28 = 90	CES53 = 82	CES78 = 76
CES04 = 71	CES29 = 68	CES54 = 88	CES79 = 91
CES05 = 50	CES30 = 69	CES55 = 87	CES80 = 90
CES06 = 52	CES31 = 72	CES56 = 80	CES81 = 74
CES07 = 43	CES32 = 71	CES57 = 78	CES82 = 95
CES08 = 42	CES33 = 71	CES58 = 80	CES83 = 90
CES09 = 29	CES34 = 84	CES59 = 93	CES84 = 94
CES10 = 77	CES35 = 92	CES60 = 96	CES85 = 83
CES11 = 59	CES36 = 92	CES61 = 94	CES86 = 69
CES12 = 66	CES37 = 89	CES62 = 84	CES87 = 85
CES13 = 44	CES38 = 75	CES63 = 79	CES88 = 84
CES14 = 74	CES39 = 93	CES64 = 85	CES89 = 74
CES15 = 72	CES40 = 89	CES65 = 79	CES90 = 81
CES16 = 48	CES41 = 85	CES66 = 83	CES91 = 96
CES17 = 50	CES42 = 88	CES67 = 82	CES92 = 72
CES18 = 57	CES43 = 81	CES68 = 86	CES93 = 84
CES19 = 73	CES44 = 98	CES69 = 92	CES94 = 63
CES20 = 67	CES45 = 87	CES70 = 81	CES95 = 80
CES21 = 87	CES46 = 82	CES71 = 81	CES96 = 85
CES22 = 79	CES47 = 76	CES72 = 93	CES97 = 87
CES23 = 92	CES48 = 71	CES73 = 75	CES98 = 82
CES24 = 91	CES49 = 81	CES74 = 91	CES99 = 76
CES25 = 72	CES50 = 88	CES75 = 79	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)