

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066639

Luminaire Tested: **NVN-SA5C-830-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066639
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5C-830-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1050mA 5xLight Square PACKAGE
80CRI 3000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 3000K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 18950.2 lumens
Efficiency: N/A
Efficacy: 80.3 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 236
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3.7 fc
 Type III - Short - N/A

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	112.7	0.0	112.7
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	18837.4	0.0	18837.4
	% Fixture	99.4	0.0	99.4
Total	Lumens	18950.1	0.0	18950.1
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	5.6	0.0
10°-20°	27.8	0.1
20°-30°	353.7	1.9
30°-40°	1192.0	6.3
40°-50°	3599.9	19.0
50°-60°	6351.4	33.5
60°-70°	5595.6	29.5
70°-80°	1781.2	9.4
80°-90°	42.9	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	18950.1	100.0
0°-180°	18950.2	100.0



REPORT NUMBER: P1066639


CATALOG NUMBER: NVN-SA5C-830-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	370.2	2.0			
FM	(30°-60°)	11099.7	58.6			
FH	(60°-80°)	7332.7	38.7			G3/7500
FVH	(80°-90°)	34.9	0.2			G1/100
BL	(0°-30°)	16.9	0.1	B0/110		
BM	(30°-60°)	43.7	0.2	B0/220		
BH	(60°-80°)	44.2	0.2	B0/110		G0/110
BVH	(80°-90°)	8.0	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	41.6
5°	59.4	59.4	59.4	53.5	53.5	53.5	47.5	47.5	47.5	47.5	47.5
7.5°	71.3	65.4	65.4	59.4	59.4	59.4	53.5	53.5	53.5	53.5	47.5
10°	83.2	77.3	77.3	71.3	71.3	65.4	65.4	59.4	59.4	53.5	53.5
12.5°	95.1	89.1	83.2	77.3	77.3	71.3	71.3	65.4	65.4	59.4	59.4
15°	107.0	101.0	95.1	89.1	83.2	83.2	77.3	71.3	65.4	65.4	59.4
17.5°	124.8	112.9	107.0	95.1	89.1	83.2	77.3	71.3	71.3	65.4	65.4
20°	130.7	118.9	112.9	101.0	95.1	89.1	83.2	77.3	71.3	71.3	65.4
22.5°	154.5	130.7	124.8	112.9	107.0	101.0	89.1	83.2	77.3	71.3	65.4
25°	190.2	154.5	136.7	118.9	112.9	101.0	95.1	83.2	77.3	71.3	65.4
27.5°	231.8	172.3	154.5	130.7	118.9	107.0	95.1	83.2	77.3	71.3	65.4
30°	285.3	202.1	172.3	142.6	130.7	118.9	101.0	89.1	83.2	77.3	65.4
32.5°	398.2	249.6	202.1	154.5	136.7	124.8	107.0	89.1	83.2	77.3	65.4
35°	481.4	303.1	243.7	178.3	154.5	136.7	112.9	89.1	83.2	77.3	65.4
37.5°	558.6	309.0	249.6	190.2	166.4	142.6	112.9	89.1	83.2	77.3	65.4
40°	683.4	320.9	249.6	178.3	160.5	136.7	118.9	95.1	89.1	77.3	71.3
42.5°	921.1	368.5	267.4	166.4	148.6	136.7	118.9	101.0	89.1	83.2	71.3
45°	1533.2	546.7	362.5	172.3	154.5	136.7	118.9	101.0	95.1	83.2	77.3
47.5°	2608.9	950.8	564.6	178.3	160.5	136.7	118.9	95.1	89.1	83.2	71.3
50°	3339.8	1218.3	713.1	208.0	178.3	154.5	124.8	95.1	89.1	83.2	77.3
52.5°	3547.8	1295.5	772.6	243.7	208.0	172.3	130.7	95.1	89.1	89.1	83.2
55°	3250.7	1259.9	772.6	285.3	237.7	196.1	148.6	101.0	95.1	95.1	89.1
57.5°	2763.4	1164.8	736.9	309.0	261.5	208.0	160.5	107.0	101.0	101.0	95.1
60°	2276.1	980.6	665.6	344.7	291.2	237.7	184.2	130.7	124.8	118.9	107.0
62.5°	1806.6	790.4	582.4	368.5	315.0	255.5	202.1	142.6	136.7	130.7	124.8
65°	1360.9	689.4	540.8	386.3	326.9	267.4	208.0	148.6	142.6	142.6	136.7
67.5°	1045.9	629.9	517.0	398.2	338.7	279.3	219.9	160.5	154.5	148.6	142.6
70°	826.0	582.4	487.3	392.2	338.7	285.3	225.8	172.3	160.5	154.5	142.6
72.5°	689.4	528.9	451.6	374.4	332.8	291.2	249.6	208.0	184.2	166.4	142.6
75°	576.4	475.4	410.0	338.7	309.0	285.3	255.5	225.8	196.1	166.4	136.7
77.5°	380.3	344.7	315.0	285.3	267.4	249.6	225.8	208.0	178.3	154.5	124.8
80°	160.5	148.6	154.5	154.5	154.5	154.5	148.6	148.6	130.7	112.9	89.1
82.5°	35.7	29.7	35.7	35.7	35.7	35.7	29.7	29.7	29.7	23.8	23.8
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
5°	47.5	47.5	47.5	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
7.5°	47.5	47.5	47.5	41.6	41.6	41.6	41.6	35.7	35.7	35.7	35.7
10°	47.5	47.5	47.5	41.6	41.6	41.6	41.6	35.7	35.7	35.7	35.7
12.5°	53.5	53.5	47.5	47.5	41.6	41.6	41.6	35.7	35.7	35.7	35.7
15°	53.5	53.5	47.5	47.5	41.6	41.6	41.6	35.7	35.7	35.7	35.7
17.5°	59.4	53.5	53.5	47.5	41.6	41.6	41.6	35.7	35.7	35.7	35.7
20°	59.4	53.5	53.5	47.5	41.6	41.6	41.6	35.7	35.7	35.7	35.7
22.5°	59.4	53.5	53.5	47.5	41.6	41.6	35.7	35.7	29.7	29.7	23.8
25°	59.4	53.5	53.5	47.5	41.6	41.6	35.7	35.7	29.7	23.8	23.8
27.5°	59.4	53.5	53.5	47.5	41.6	35.7	35.7	29.7	23.8	17.8	17.8
30°	59.4	53.5	53.5	47.5	41.6	35.7	29.7	23.8	17.8	17.8	11.9
32.5°	59.4	53.5	47.5	41.6	35.7	29.7	29.7	23.8	17.8	11.9	11.9
35°	59.4	53.5	47.5	41.6	35.7	29.7	29.7	23.8	17.8	11.9	11.9
37.5°	59.4	53.5	47.5	41.6	35.7	29.7	23.8	17.8	11.9	11.9	5.9
40°	59.4	53.5	47.5	41.6	35.7	29.7	23.8	17.8	11.9	11.9	5.9
42.5°	59.4	53.5	47.5	41.6	35.7	29.7	23.8	17.8	11.9	11.9	5.9
45°	65.4	59.4	53.5	41.6	35.7	29.7	29.7	23.8	17.8	11.9	11.9
47.5°	65.4	59.4	53.5	41.6	35.7	29.7	29.7	23.8	17.8	11.9	11.9
50°	71.3	65.4	59.4	47.5	41.6	35.7	29.7	17.8	11.9	11.9	5.9
52.5°	77.3	71.3	65.4	59.4	53.5	41.6	29.7	17.8	5.9	5.9	5.9
55°	83.2	77.3	77.3	71.3	65.4	47.5	35.7	17.8	0.0	0.0	0.0
57.5°	89.1	83.2	83.2	77.3	71.3	53.5	35.7	17.8	0.0	0.0	0.0
60°	101.0	95.1	89.1	77.3	71.3	53.5	35.7	17.8	0.0	0.0	0.0
62.5°	118.9	107.0	89.1	77.3	59.4	47.5	29.7	17.8	0.0	0.0	0.0
65°	130.7	112.9	95.1	71.3	53.5	41.6	29.7	11.9	0.0	0.0	0.0
67.5°	136.7	112.9	95.1	71.3	47.5	35.7	23.8	11.9	0.0	0.0	0.0
70°	130.7	107.0	89.1	65.4	41.6	29.7	23.8	11.9	0.0	0.0	0.0
72.5°	118.9	101.0	77.3	59.4	35.7	29.7	17.8	11.9	0.0	0.0	0.0
75°	107.0	89.1	65.4	47.5	23.8	17.8	11.9	5.9	0.0	0.0	0.0
77.5°	95.1	77.3	53.5	35.7	11.9	11.9	5.9	5.9	0.0	0.0	0.0
80°	71.3	53.5	35.7	17.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	17.8	11.9	11.9	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	35.7	35.7	35.7	35.7	35.7	35.7	35.7	35.7	35.7	35.7	35.7
5°	35.7	35.7	35.7	35.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7
7.5°	35.7	35.7	35.7	35.7	29.7	29.7	29.7	29.7	23.8	23.8	23.8
10°	29.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7	23.8	23.8	23.8
12.5°	29.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7	23.8	23.8	23.8
15°	29.7	29.7	29.7	29.7	29.7	29.7	29.7	23.8	23.8	17.8	17.8
17.5°	29.7	29.7	29.7	29.7	23.8	23.8	23.8	17.8	17.8	11.9	11.9
20°	29.7	29.7	29.7	23.8	23.8	17.8	17.8	11.9	11.9	5.9	5.9
22.5°	23.8	17.8	17.8	11.9	11.9	5.9	5.9	5.9	0.0	0.0	0.0
25°	17.8	11.9	11.9	5.9	5.9	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	11.9	5.9	5.9	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	11.9	5.9	5.9	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	35.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7
5°	29.7	29.7	29.7	29.7	23.8	23.8	23.8	23.8	23.8	23.8	23.8
7.5°	23.8	23.8	23.8	23.8	23.8	23.8	17.8	17.8	17.8	17.8	17.8
10°	23.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	11.9	11.9
12.5°	23.8	17.8	17.8	17.8	11.9	11.9	11.9	11.9	11.9	5.9	5.9
15°	17.8	11.9	11.9	11.9	5.9	5.9	5.9	5.9	5.9	0.0	0.0
17.5°	11.9	5.9	5.9	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	29.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7	29.7	35.7	35.7
5°	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8	23.8
7.5°	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8	17.8
10°	11.9	11.9	11.9	11.9	11.9	11.9	5.9	5.9	5.9	5.9	5.9
12.5°	5.9	5.9	5.9	5.9	5.9	5.9	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	35.7	35.7	35.7	35.7	35.7	41.6	41.6	47.5	47.5	53.5	53.5
5°	23.8	23.8	29.7	29.7	29.7	29.7	35.7	35.7	35.7	41.6	41.6
7.5°	17.8	17.8	17.8	17.8	17.8	23.8	23.8	29.7	29.7	35.7	35.7
10°	5.9	5.9	11.9	11.9	11.9	11.9	17.8	17.8	17.8	23.8	29.7
12.5°	0.0	0.0	5.9	5.9	5.9	5.9	11.9	11.9	11.9	17.8	23.8
15°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9	11.9	17.8
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	11.9
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	59.4	59.4	65.4	65.4	71.3	71.3	77.3	77.3	77.3	77.3	77.3
5°	47.5	47.5	53.5	59.4	59.4	65.4	71.3	71.3	71.3	71.3	71.3
7.5°	41.6	41.6	47.5	53.5	53.5	59.4	65.4	65.4	71.3	71.3	71.3
10°	29.7	35.7	41.6	47.5	47.5	53.5	59.4	59.4	65.4	65.4	65.4
12.5°	23.8	29.7	35.7	41.6	41.6	47.5	53.5	53.5	59.4	59.4	65.4
15°	17.8	23.8	29.7	35.7	35.7	41.6	47.5	47.5	53.5	59.4	65.4
17.5°	11.9	17.8	23.8	29.7	29.7	35.7	41.6	47.5	53.5	53.5	59.4
20°	11.9	11.9	17.8	23.8	23.8	29.7	35.7	41.6	47.5	47.5	53.5
22.5°	5.9	5.9	11.9	17.8	17.8	23.8	29.7	35.7	41.6	41.6	47.5
25°	0.0	0.0	5.9	11.9	11.9	17.8	23.8	23.8	29.7	29.7	35.7
27.5°	0.0	0.0	5.9	5.9	11.9	11.9	17.8	17.8	23.8	23.8	29.7
30°	0.0	0.0	5.9	5.9	11.9	11.9	17.8	17.8	23.8	23.8	23.8
32.5°	0.0	0.0	0.0	5.9	5.9	5.9	11.9	11.9	17.8	17.8	23.8
35°	0.0	0.0	0.0	5.9	5.9	5.9	11.9	11.9	17.8	17.8	17.8
37.5°	0.0	0.0	0.0	5.9	5.9	5.9	11.9	11.9	11.9	11.9	17.8
40°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	11.9	11.9	11.9
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	11.9	11.9	11.9
45°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	11.9	11.9	11.9
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	11.9	11.9	11.9
50°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	11.9	11.9	11.9
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9	5.9	5.9
55°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9	5.9	5.9
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9
75°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9	5.9	5.9
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	11.9	11.9	11.9
80°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	11.9	11.9	11.9
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9	5.9	11.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9	5.9	5.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.9	5.9	5.9	5.9	5.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	77.3	77.3
5°	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	71.3	71.3
7.5°	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	71.3	71.3
10°	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3
12.5°	65.4	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3
15°	65.4	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3
17.5°	59.4	65.4	65.4	65.4	71.3	71.3	71.3	71.3	71.3	71.3	71.3
20°	53.5	59.4	59.4	59.4	65.4	65.4	65.4	65.4	71.3	71.3	71.3
22.5°	47.5	53.5	53.5	53.5	59.4	59.4	59.4	59.4	65.4	65.4	65.4
25°	41.6	41.6	47.5	47.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
27.5°	29.7	35.7	35.7	35.7	41.6	41.6	41.6	41.6	47.5	47.5	47.5
30°	29.7	29.7	29.7	29.7	35.7	35.7	35.7	35.7	41.6	41.6	41.6
32.5°	23.8	29.7	29.7	29.7	35.7	35.7	35.7	35.7	41.6	41.6	41.6
35°	23.8	23.8	23.8	23.8	29.7	29.7	29.7	29.7	35.7	35.7	35.7
37.5°	17.8	23.8	23.8	23.8	29.7	29.7	29.7	29.7	35.7	35.7	35.7
40°	17.8	17.8	17.8	17.8	23.8	23.8	23.8	23.8	29.7	29.7	29.7
42.5°	17.8	17.8	17.8	17.8	23.8	23.8	23.8	23.8	29.7	29.7	29.7
45°	17.8	17.8	17.8	17.8	23.8	23.8	23.8	23.8	29.7	29.7	29.7
47.5°	17.8	17.8	17.8	17.8	23.8	23.8	23.8	23.8	29.7	29.7	29.7
50°	17.8	17.8	17.8	17.8	23.8	23.8	23.8	23.8	29.7	29.7	29.7
52.5°	11.9	11.9	11.9	11.9	17.8	17.8	17.8	17.8	23.8	23.8	23.8
55°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	17.8	17.8	17.8
57.5°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	17.8	17.8	17.8
60°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9
62.5°	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9
65°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	5.9	5.9
67.5°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9
70°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9
72.5°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9
75°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9
77.5°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9
80°	17.8	17.8	17.8	17.8	17.8	11.9	11.9	11.9	11.9	11.9	11.9
82.5°	11.9	17.8	17.8	17.8	17.8	11.9	11.9	11.9	11.9	11.9	11.9
85°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9
87.5°	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9	11.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	77.3	77.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	77.3	77.3
5°	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	77.3	77.3
7.5°	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	77.3	77.3
10°	71.3	71.3	71.3	71.3	65.4	65.4	71.3	71.3	71.3	77.3	77.3
12.5°	71.3	71.3	71.3	71.3	65.4	65.4	71.3	71.3	77.3	77.3	83.2
15°	71.3	71.3	65.4	65.4	65.4	65.4	71.3	71.3	77.3	77.3	83.2
17.5°	71.3	71.3	65.4	65.4	65.4	65.4	71.3	71.3	77.3	77.3	83.2
20°	71.3	71.3	65.4	65.4	65.4	65.4	65.4	65.4	71.3	77.3	77.3
22.5°	65.4	65.4	65.4	65.4	59.4	59.4	65.4	65.4	71.3	77.3	77.3
25°	53.5	59.4	59.4	59.4	59.4	59.4	65.4	65.4	71.3	77.3	77.3
27.5°	47.5	53.5	53.5	53.5	53.5	59.4	59.4	65.4	71.3	77.3	77.3
30°	41.6	47.5	47.5	47.5	53.5	59.4	59.4	65.4	71.3	77.3	77.3
32.5°	41.6	47.5	47.5	47.5	53.5	53.5	59.4	59.4	65.4	71.3	77.3
35°	41.6	41.6	47.5	47.5	47.5	53.5	53.5	59.4	65.4	71.3	77.3
37.5°	41.6	41.6	47.5	47.5	47.5	53.5	53.5	59.4	65.4	71.3	77.3
40°	35.7	41.6	41.6	47.5	47.5	53.5	53.5	59.4	65.4	77.3	83.2
42.5°	35.7	35.7	41.6	41.6	47.5	53.5	53.5	59.4	65.4	77.3	83.2
45°	35.7	41.6	41.6	47.5	53.5	59.4	59.4	65.4	71.3	77.3	83.2
47.5°	35.7	41.6	41.6	47.5	59.4	59.4	65.4	65.4	71.3	77.3	83.2
50°	35.7	41.6	41.6	47.5	65.4	65.4	65.4	65.4	71.3	77.3	83.2
52.5°	29.7	35.7	35.7	41.6	53.5	59.4	65.4	71.3	77.3	83.2	89.1
55°	23.8	29.7	29.7	35.7	47.5	53.5	65.4	77.3	83.2	89.1	95.1
57.5°	23.8	23.8	29.7	29.7	41.6	53.5	71.3	83.2	89.1	95.1	101.0
60°	17.8	17.8	23.8	23.8	35.7	47.5	65.4	83.2	89.1	101.0	107.0
62.5°	11.9	17.8	17.8	23.8	29.7	47.5	65.4	83.2	95.1	107.0	112.9
65°	11.9	11.9	17.8	17.8	29.7	41.6	59.4	71.3	89.1	107.0	124.8
67.5°	17.8	17.8	23.8	23.8	29.7	41.6	59.4	71.3	89.1	112.9	130.7
70°	17.8	17.8	23.8	23.8	35.7	47.5	59.4	71.3	89.1	112.9	130.7
72.5°	17.8	17.8	23.8	23.8	35.7	41.6	53.5	65.4	83.2	101.0	118.9
75°	11.9	17.8	17.8	17.8	29.7	35.7	47.5	59.4	77.3	95.1	112.9
77.5°	11.9	11.9	11.9	11.9	23.8	29.7	41.6	47.5	65.4	83.2	101.0
80°	11.9	11.9	11.9	11.9	17.8	23.8	35.7	41.6	59.4	77.3	95.1
82.5°	11.9	11.9	5.9	5.9	11.9	17.8	23.8	29.7	47.5	59.4	77.3
85°	11.9	11.9	5.9	5.9	5.9	11.9	11.9	17.8	23.8	29.7	35.7
87.5°	11.9	11.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	77.3	77.3	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2
5°	77.3	83.2	83.2	89.1	89.1	89.1	95.1	95.1	95.1	95.1	95.1
7.5°	77.3	83.2	83.2	89.1	89.1	89.1	95.1	95.1	95.1	101.0	101.0
10°	77.3	83.2	83.2	89.1	89.1	95.1	101.0	101.0	107.0	107.0	107.0
12.5°	83.2	89.1	89.1	95.1	95.1	101.0	107.0	107.0	112.9	118.9	118.9
15°	83.2	89.1	95.1	95.1	101.0	107.0	112.9	112.9	118.9	124.8	130.7
17.5°	83.2	89.1	95.1	95.1	101.0	107.0	118.9	124.8	130.7	142.6	148.6
20°	83.2	89.1	95.1	95.1	101.0	112.9	118.9	130.7	136.7	148.6	160.5
22.5°	83.2	89.1	95.1	101.0	107.0	118.9	130.7	136.7	148.6	166.4	178.3
25°	83.2	89.1	95.1	101.0	107.0	118.9	130.7	142.6	154.5	178.3	202.1
27.5°	83.2	89.1	101.0	107.0	112.9	124.8	142.6	154.5	166.4	208.0	249.6
30°	83.2	89.1	101.0	107.0	112.9	130.7	148.6	160.5	178.3	249.6	315.0
32.5°	83.2	95.1	101.0	112.9	118.9	136.7	160.5	178.3	196.1	297.1	392.2
35°	83.2	95.1	101.0	112.9	118.9	142.6	166.4	190.2	213.9	362.5	511.1
37.5°	83.2	95.1	101.0	112.9	118.9	154.5	190.2	225.8	261.5	416.0	570.5
40°	89.1	101.0	107.0	118.9	124.8	160.5	196.1	231.8	267.4	421.9	576.4
42.5°	89.1	101.0	107.0	118.9	124.8	154.5	190.2	219.9	249.6	421.9	594.3
45°	89.1	101.0	112.9	118.9	130.7	160.5	190.2	213.9	243.7	463.5	677.5
47.5°	89.1	101.0	112.9	118.9	130.7	160.5	190.2	219.9	249.6	612.1	968.7
50°	89.1	101.0	112.9	118.9	130.7	166.4	202.1	237.7	273.4	915.2	1557.0
52.5°	95.1	101.0	112.9	118.9	124.8	166.4	208.0	249.6	291.2	1188.5	2080.0
55°	101.0	107.0	112.9	118.9	124.8	178.3	231.8	285.3	338.7	1277.7	2210.7
57.5°	107.0	112.9	118.9	118.9	124.8	190.2	261.5	326.9	392.2	1271.7	2145.3
60°	112.9	118.9	124.8	130.7	136.7	202.1	273.4	338.7	404.1	1152.9	1901.7
62.5°	124.8	136.7	148.6	154.5	166.4	231.8	291.2	356.6	416.0	944.9	1467.9
65°	142.6	154.5	160.5	172.3	178.3	237.7	303.1	362.5	421.9	784.4	1141.0
67.5°	148.6	160.5	166.4	178.3	184.2	243.7	303.1	362.5	421.9	665.6	903.3
70°	148.6	160.5	172.3	178.3	190.2	249.6	303.1	362.5	416.0	576.4	736.9
72.5°	136.7	154.5	166.4	184.2	196.1	249.6	297.1	350.6	398.2	511.1	624.0
75°	130.7	154.5	172.3	196.1	213.9	249.6	291.2	326.9	362.5	445.7	528.9
77.5°	118.9	148.6	178.3	208.0	237.7	261.5	279.3	303.1	320.9	374.4	427.9
80°	112.9	142.6	172.3	202.1	231.8	243.7	249.6	261.5	267.4	273.4	279.3
82.5°	89.1	112.9	136.7	154.5	178.3	166.4	160.5	148.6	136.7	130.7	124.8
85°	41.6	47.5	47.5	53.5	53.5	53.5	47.5	47.5	41.6	35.7	29.7
87.5°	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9	5.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	83.2	83.2	83.2	83.2	77.3	77.3	77.3	77.3	71.3	71.3	71.3
5°	95.1	95.1	95.1	95.1	89.1	89.1	89.1	89.1	83.2	83.2	83.2
7.5°	101.0	101.0	101.0	101.0	101.0	101.0	101.0	101.0	101.0	101.0	101.0
10°	112.9	112.9	112.9	118.9	118.9	118.9	118.9	118.9	118.9	118.9	118.9
12.5°	124.8	124.8	130.7	130.7	136.7	136.7	142.6	142.6	148.6	148.6	148.6
15°	136.7	142.6	148.6	154.5	154.5	160.5	166.4	172.3	178.3	184.2	190.2
17.5°	160.5	166.4	178.3	190.2	202.1	213.9	231.8	255.5	273.4	291.2	315.0
20°	178.3	196.1	231.8	273.4	309.0	344.7	433.8	523.0	612.1	701.2	790.4
22.5°	213.9	249.6	368.5	493.2	612.1	731.0	1010.3	1289.6	1562.9	1842.3	2091.8
25°	285.3	362.5	635.9	909.2	1176.7	1450.0	1949.2	2454.4	2953.5	3452.7	3916.3
27.5°	392.2	534.8	980.6	1432.2	1877.9	2323.6	3048.6	3779.6	4504.6	5235.6	5883.3
30°	546.7	778.5	1444.1	2115.6	2781.2	3446.8	4362.0	5283.1	6198.3	7113.5	7707.7
32.5°	742.8	1087.5	1931.4	2775.3	3619.1	4463.0	5473.3	6483.5	7487.9	8498.1	9128.1
35°	950.8	1390.6	2406.8	3429.0	4445.2	5467.3	6531.1	7594.8	8658.6	9722.3	10494.9
37.5°	1069.7	1568.9	2775.3	3981.6	5182.1	6388.5	7553.2	8724.0	9888.7	11053.5	11992.5
40°	1182.6	1782.8	3173.4	4564.0	5954.6	7345.2	8706.1	10067.0	11427.9	12788.8	13995.2
42.5°	1349.0	2103.7	3726.1	5348.5	6964.9	8587.3	10376.0	12170.8	13959.5	15748.3	17602.4
45°	1693.7	2709.9	4813.6	6917.4	9015.2	11118.9	13656.4	16199.9	18737.5	21281.0	23658.1
47.5°	2525.7	4076.7	6947.1	9817.4	12687.8	15558.1	18482.0	21405.8	24329.6	27253.4	30082.2
50°	3910.3	6257.7	9847.1	13436.6	17020.0	20609.5	23527.3	26445.2	29357.2	32275.1	35086.0
52.5°	5211.8	8343.6	12200.5	16063.3	19920.1	23782.9	26368.0	28953.1	31538.2	34123.3	36845.0
55°	5657.5	9098.3	13002.7	16913.1	20817.5	24727.8	27217.8	29713.7	32203.8	34693.8	37516.6
57.5°	5265.3	8385.2	12319.3	16253.4	20181.6	24115.7	26896.9	29684.0	32465.2	35252.4	38277.3
60°	4409.5	6911.4	11041.6	15177.8	19308.0	23438.2	26576.0	29713.7	32851.5	35989.3	39008.2
62.5°	3494.3	5514.9	9888.7	14262.6	18636.5	23010.3	26201.6	29398.8	32590.0	35781.3	38099.0
65°	2680.2	4219.4	8521.9	12830.4	17132.9	21441.4	24056.3	26677.0	29291.8	31912.6	33517.1
67.5°	1990.8	3078.3	6840.1	10607.8	14369.6	18131.3	20056.8	21988.2	23913.6	25845.0	27093.0
70°	1467.9	2192.9	4754.2	7315.5	9870.9	12432.2	14197.2	15962.2	17721.3	19486.3	20781.8
72.5°	1016.2	1402.5	2935.7	4474.9	6008.1	7541.3	9330.1	11118.9	12901.7	14690.5	16164.3
75°	695.3	861.7	1580.8	2299.8	3018.9	3738.0	5092.9	6447.9	7802.8	9157.8	9936.3
77.5°	517.0	606.2	820.1	1040.0	1253.9	1467.9	1729.3	1990.8	2252.3	2513.8	2852.5
80°	285.3	285.3	315.0	338.7	368.5	392.2	463.5	540.8	612.1	689.4	784.4
82.5°	130.7	136.7	148.6	160.5	166.4	178.3	190.2	202.1	213.9	225.8	225.8
85°	35.7	41.6	41.6	35.7	35.7	29.7	29.7	35.7	35.7	35.7	35.7
87.5°	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	71.3	65.4	65.4	65.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
5°	83.2	83.2	83.2	83.2	77.3	77.3	77.3	77.3	77.3	71.3	71.3
7.5°	101.0	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	89.1	89.1
10°	118.9	118.9	118.9	118.9	118.9	118.9	118.9	118.9	118.9	112.9	112.9
12.5°	148.6	148.6	148.6	148.6	154.5	154.5	148.6	148.6	148.6	142.6	142.6
15°	196.1	202.1	208.0	208.0	213.9	213.9	213.9	208.0	208.0	202.1	196.1
17.5°	332.8	350.6	374.4	398.2	421.9	439.8	439.8	427.9	416.0	404.1	392.2
20°	885.5	974.6	1069.7	1164.8	1265.8	1337.1	1289.6	1253.9	1218.3	1176.7	1141.0
22.5°	2347.4	2597.0	2852.5	3030.8	3209.1	3333.9	3232.9	3036.7	2840.6	2650.5	2454.4
25°	4379.8	4837.4	5300.9	5491.1	5687.2	5829.8	5764.5	5467.3	5170.2	4879.0	4581.9
27.5°	6531.1	7172.9	7820.7	7987.1	8153.5	8278.3	8254.5	7868.2	7481.9	7095.6	6709.4
30°	8302.0	8896.3	9490.6	9657.0	9823.4	9936.3	9811.5	9425.2	9038.9	8652.6	8266.4
32.5°	9763.9	10393.9	11029.7	11249.6	11469.5	11618.1	11469.5	11006.0	10542.4	10084.8	9621.3
35°	11267.5	12034.1	12806.6	13085.9	13365.2	13543.5	13293.9	12723.4	12152.9	11588.4	11017.9
37.5°	12931.4	13864.4	14803.4	15183.7	15570.0	15837.4	15647.3	14934.1	14215.1	13501.9	12782.9
40°	15207.5	16413.9	17626.2	18309.6	18987.1	19468.4	19129.7	18303.7	17471.7	16645.6	15813.7
42.5°	19462.5	21316.6	23170.8	24151.3	25125.9	25833.1	25452.8	24436.6	23420.4	22404.2	21388.0
45°	26035.2	28406.3	30783.4	32215.6	33653.8	34711.6	34271.8	32994.1	31710.5	30432.8	29155.1
47.5°	32910.9	35739.7	38568.4	39709.5	40856.4	41747.8	41640.8	40048.2	38455.5	36868.8	35276.2
50°	37902.9	40713.8	43524.7	44505.3	45491.7	46222.7	45949.3	43922.9	41890.4	39864.0	37831.5
52.5°	39566.8	42282.7	45004.4	46175.2	47345.9	48219.5	47886.7	45604.7	43322.6	41046.6	38764.6
55°	40339.4	43162.2	45985.0	47411.3	48843.5	49889.4	49408.0	46906.1	44398.3	41896.4	39388.5
57.5°	41302.1	44327.0	47351.8	48914.8	50477.7	51606.8	50965.0	48374.0	45782.9	43197.8	40606.8
60°	42027.1	45040.1	48059.0	49312.9	50572.8	51452.3	50834.3	48314.6	45788.9	43269.2	40749.4
62.5°	40422.6	42740.3	45057.9	45990.9	46924.0	47601.4	47250.8	44861.8	42472.8	40083.8	37694.9
65°	35127.6	36732.1	38342.6	38972.6	39596.5	40077.9	39970.9	37956.3	35941.7	33933.1	31918.5
67.5°	28346.9	29594.9	30848.8	31740.2	32637.6	33332.9	33255.6	31419.3	29583.0	27746.7	25910.4
70°	22083.3	23378.8	24674.3	25797.5	26926.6	27800.2	27687.3	25981.7	24270.2	22564.6	20853.1
72.5°	17644.0	19117.8	20591.6	21233.4	21875.3	22326.9	21994.1	20704.5	19409.0	18119.4	16823.9
75°	10714.8	11487.3	12265.8	12259.9	12259.9	12188.6	11855.8	11118.9	10382.0	9645.1	8908.2
77.5°	3191.3	3530.0	3868.7	4195.6	4528.4	4778.0	4712.6	4326.3	3934.1	3547.8	3155.6
80°	879.5	968.7	1063.8	1105.4	1147.0	1200.4	1337.1	1242.0	1147.0	1057.8	962.7
82.5°	225.8	225.8	225.8	219.9	213.9	202.1	184.2	172.3	160.5	148.6	136.7
85°	35.7	29.7	29.7	29.7	23.8	23.8	23.8	23.8	17.8	17.8	11.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5
2.5°	59.4	59.4	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	47.5
5°	71.3	71.3	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	59.4
7.5°	89.1	89.1	83.2	83.2	83.2	83.2	77.3	77.3	77.3	77.3	71.3
10°	112.9	107.0	107.0	101.0	101.0	101.0	95.1	95.1	95.1	89.1	89.1
12.5°	142.6	136.7	136.7	130.7	124.8	124.8	118.9	112.9	107.0	107.0	101.0
15°	190.2	184.2	178.3	172.3	166.4	154.5	148.6	136.7	130.7	124.8	118.9
17.5°	362.5	332.8	303.1	273.4	249.6	225.8	202.1	178.3	166.4	154.5	142.6
20°	1010.3	873.6	742.8	612.1	528.9	445.7	362.5	279.3	243.7	213.9	178.3
22.5°	2186.9	1913.6	1646.1	1372.8	1152.9	939.0	719.1	499.2	416.0	338.7	255.5
25°	4064.8	3541.9	3024.9	2501.9	2085.9	1669.9	1253.9	837.9	683.4	528.9	374.4
27.5°	6031.9	5354.4	4676.9	3999.5	3339.8	2674.2	2008.6	1349.0	1081.6	820.1	552.7
30°	7547.3	6828.2	6115.1	5396.0	4564.0	3732.0	2894.1	2062.1	1640.2	1218.3	790.4
32.5°	8848.8	8070.3	7297.7	6519.2	5556.5	4593.7	3631.0	2668.3	2139.4	1610.5	1075.6
35°	10138.3	9252.9	8373.3	7487.9	6453.8	5419.8	4385.7	3351.7	2680.2	2008.6	1331.2
37.5°	11707.2	10625.6	9550.0	8474.4	7410.6	6352.8	5289.0	4225.3	3369.5	2519.7	1664.0
40°	14440.9	13062.2	11689.4	10310.7	9068.6	7832.5	6590.5	5348.5	4272.8	3197.2	2115.6
42.5°	19658.6	17929.3	16205.9	14476.5	12759.1	11041.6	9318.2	7600.8	6067.5	4540.3	3007.0
45°	26938.5	24721.8	22511.1	20294.5	18178.9	16069.2	13953.6	11838.0	9508.4	7178.8	4843.3
47.5°	32851.5	30420.9	27996.3	25565.7	23218.3	20876.9	18529.5	16182.1	13198.8	10221.5	7238.3
50°	35519.8	33202.1	30890.4	28572.7	26219.4	23860.1	21500.9	19147.5	15724.5	12307.4	8884.4
52.5°	36417.2	34063.8	31716.5	29363.1	27027.6	24692.1	22356.6	20021.1	16461.4	12907.7	9347.9
55°	36910.4	34426.3	31948.2	29464.2	26950.4	24430.6	21910.9	19397.1	15855.3	12319.3	8777.4
57.5°	37908.8	35204.8	32506.8	29802.9	26938.5	24074.1	21203.7	18339.3	14845.0	11350.7	7856.3
60°	38093.0	35430.7	32774.3	30117.9	26950.4	23782.9	20609.5	17442.0	13971.4	10506.8	7036.2
62.5°	35472.3	33249.7	31033.0	28810.5	25637.0	22463.6	19284.2	16110.8	12788.8	9466.8	6138.9
65°	29999.0	28079.5	26165.9	24246.4	21655.4	19070.3	16479.2	13888.2	10922.8	7963.3	4997.9
67.5°	24032.5	22154.6	20282.6	18404.7	16455.5	14512.2	12563.0	10613.8	8325.8	6037.8	3749.9
70°	19052.5	17245.9	15445.2	13638.6	11915.2	10185.9	8456.5	6733.1	5312.8	3898.4	2478.1
72.5°	15100.5	13371.2	11647.8	9918.4	8355.5	6792.6	5229.6	3666.7	2959.5	2258.2	1551.1
75°	8010.8	7113.5	6222.1	5324.7	4445.2	3559.7	2674.2	1794.7	1515.4	1236.1	950.8
77.5°	2763.4	2371.2	1984.9	1592.7	1325.2	1057.8	790.4	523.0	493.2	469.5	439.8
80°	837.9	713.1	588.3	463.5	410.0	356.6	303.1	249.6	231.8	213.9	190.2
82.5°	130.7	118.9	112.9	101.0	95.1	95.1	89.1	83.2	71.3	65.4	53.5
85°	11.9	5.9	5.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	53.5	53.5
2.5°	47.5	47.5
5°	59.4	59.4
7.5°	71.3	71.3
10°	83.2	83.2
12.5°	95.1	95.1
15°	112.9	107.0
17.5°	130.7	124.8
20°	142.6	130.7
22.5°	172.3	148.6
25°	219.9	184.2
27.5°	285.3	225.8
30°	368.5	285.3
32.5°	546.7	398.2
35°	659.6	481.4
37.5°	808.2	558.6
40°	1040.0	677.5
42.5°	1473.8	921.1
45°	2513.8	1527.3
47.5°	4261.0	2602.9
50°	5461.4	3339.8
52.5°	5794.2	3541.9
55°	5241.5	3250.7
57.5°	4362.0	2763.4
60°	3571.6	2276.1
62.5°	2816.9	1800.7
65°	2032.4	1360.9
67.5°	1461.9	1045.9
70°	1063.8	820.1
72.5°	843.9	683.4
75°	671.5	570.5
77.5°	416.0	380.3
80°	172.3	160.5
82.5°	41.6	35.7
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066639

CATALOG NUMBER: NVN-SA5C-830-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-9

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-830-U-5WQ

Data in this report applies to families of products including GSS-SB1A-830-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-9
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-830-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI
 3000K CCT 26 LEDS

Spectral Parameters

CCT (K): 3055
 CIE u' : 0.2475
 CIE v' : 0.5247
 Duv: 0.0032
 CIE x: 0.4377
 CIE y: 0.4124
 CIE z: 0.1499
 Peak Wavelength (nm): 604
 Dominant Wavelength (nm): 581
 Purity: 55.16339
 R_f: 81.5
 R_g: 99.2

CRI (Ra): 80.9
 R1: 79.5
 R2: 85.6
 R3: 92.1
 R4: 82.4
 R5: 78.9
 R6: 81.7
 R7: 85.1
 R8: 61.9
 R9: 6.8
 R10: 67.1
 R11: 82.5
 R12: 63.4
 R13: 80.2
 R14: 95.1
 R15: 71.7



Test Conditions

Stabilization Time: 20M
 Operation Time: 1H 20M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-9

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-9

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-9

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)
360	0	NR	490	170	NR	620	938	NR	750	35	NR	880	1	NR
365	0	NR	495	234	NR	625	894	NR	755	30	NR	885	1	NR
370	0	NR	500	302	NR	630	847	NR	760	26	NR	890	1	NR
375	0	NR	505	371	NR	635	788	NR	765	22	NR	895	1	NR
380	0	NR	510	431	NR	640	728	NR	770	19	NR	900	1	NR
385	0	NR	515	482	NR	645	665	NR	775	16	NR	905	1	NR
390	0	NR	520	523	NR	650	603	NR	780	14	NR	910	0	NR
395	2	NR	525	553	NR	655	542	NR	785	12	NR	915	0	NR
400	4	NR	530	580	NR	660	484	NR	790	11	NR	920	0	NR
405	8	NR	535	603	NR	665	430	NR	795	9	NR	925	0	NR
410	18	NR	540	622	NR	670	377	NR	800	8	NR	930	0	NR
415	36	NR	545	644	NR	675	330	NR	805	7	NR	935	0	NR
420	71	NR	550	668	NR	680	289	NR	810	6	NR	940	0	NR
425	131	NR	555	693	NR	685	250	NR	815	5	NR	945	0	NR
430	215	NR	560	720	NR	690	218	NR	820	4	NR	950	0	NR
435	341	NR	565	754	NR	695	188	NR	825	4	NR	955	0	NR
440	514	NR	570	792	NR	700	161	NR	830	3	NR	960	0	NR
445	576	NR	575	832	NR	705	139	NR	835	3	NR	965	0	NR
450	358	NR	580	875	NR	710	119	NR	840	3	NR	970	0	NR
455	222	NR	585	913	NR	715	102	NR	845	2	NR	975	0	NR
460	170	NR	590	950	NR	720	88	NR	850	2	NR	980	0	NR
465	115	NR	595	977	NR	725	76	NR	855	2	NR	985	0	NR
470	88	NR	600	994	NR	730	65	NR	860	1	NR	990	0	NR
475	87	NR	605	997	NR	735	56	NR	865	1	NR	995	0	NR
480	96	NR	610	990	NR	740	47	NR	870	1	NR	1000	0	NR
485	122	NR	615	971	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-9

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.28

λ (nm)	Power W ^Λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^Λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^Λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^Λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^Λ /nm	Lumens (Φ/nm)
360	0	NR	490	170	NR	620	938	NR	750	35	NR	880	1	NR
365	0	NR	495	234	NR	625	894	NR	755	30	NR	885	1	NR
370	0	NR	500	302	NR	630	847	NR	760	26	NR	890	1	NR
375	0	NR	505	371	NR	635	788	NR	765	22	NR	895	1	NR
380	0	NR	510	431	NR	640	728	NR	770	19	NR	900	1	NR
385	0	NR	515	482	NR	645	665	NR	775	16	NR	905	1	NR
390	0	NR	520	523	NR	650	603	NR	780	14	NR	910	0	NR
395	2	NR	525	553	NR	655	542	NR	785	12	NR	915	0	NR
400	4	NR	530	580	NR	660	484	NR	790	11	NR	920	0	NR
405	8	NR	535	603	NR	665	430	NR	795	9	NR	925	0	NR
410	18	NR	540	622	NR	670	377	NR	800	8	NR	930	0	NR
415	36	NR	545	644	NR	675	330	NR	805	7	NR	935	0	NR
420	71	NR	550	668	NR	680	289	NR	810	6	NR	940	0	NR
425	131	NR	555	693	NR	685	250	NR	815	5	NR	945	0	NR
430	215	NR	560	720	NR	690	218	NR	820	4	NR	950	0	NR
435	341	NR	565	754	NR	695	188	NR	825	4	NR	955	0	NR
440	514	NR	570	792	NR	700	161	NR	830	3	NR	960	0	NR
445	576	NR	575	832	NR	705	139	NR	835	3	NR	965	0	NR
450	358	NR	580	875	NR	710	119	NR	840	3	NR	970	0	NR
455	222	NR	585	913	NR	715	102	NR	845	2	NR	975	0	NR
460	170	NR	590	950	NR	720	88	NR	850	2	NR	980	0	NR
465	115	NR	595	977	NR	725	76	NR	855	2	NR	985	0	NR
470	88	NR	600	994	NR	730	65	NR	860	1	NR	990	0	NR
475	87	NR	605	997	NR	735	56	NR	865	1	NR	995	0	NR
480	96	NR	610	990	NR	740	47	NR	870	1	NR	1000	0	NR
485	122	NR	615	971	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-9

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.33


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	170	NR	620	938	NR	750	35	NR	880	1	NR
365	0	NR	495	234	NR	625	894	NR	755	30	NR	885	1	NR
370	0	NR	500	302	NR	630	847	NR	760	26	NR	890	1	NR
375	0	NR	505	371	NR	635	788	NR	765	22	NR	895	1	NR
380	0	NR	510	431	NR	640	728	NR	770	19	NR	900	1	NR
385	0	NR	515	482	NR	645	665	NR	775	16	NR	905	1	NR
390	0	NR	520	523	NR	650	603	NR	780	14	NR	910	0	NR
395	2	NR	525	553	NR	655	542	NR	785	12	NR	915	0	NR
400	4	NR	530	580	NR	660	484	NR	790	11	NR	920	0	NR
405	8	NR	535	603	NR	665	430	NR	795	9	NR	925	0	NR
410	18	NR	540	622	NR	670	377	NR	800	8	NR	930	0	NR
415	36	NR	545	644	NR	675	330	NR	805	7	NR	935	0	NR
420	71	NR	550	668	NR	680	289	NR	810	6	NR	940	0	NR
425	131	NR	555	693	NR	685	250	NR	815	5	NR	945	0	NR
430	215	NR	560	720	NR	690	218	NR	820	4	NR	950	0	NR
435	341	NR	565	754	NR	695	188	NR	825	4	NR	955	0	NR
440	514	NR	570	792	NR	700	161	NR	830	3	NR	960	0	NR
445	576	NR	575	832	NR	705	139	NR	835	3	NR	965	0	NR
450	358	NR	580	875	NR	710	119	NR	840	3	NR	970	0	NR
455	222	NR	585	913	NR	715	102	NR	845	2	NR	975	0	NR
460	170	NR	590	950	NR	720	88	NR	850	2	NR	980	0	NR
465	115	NR	595	977	NR	725	76	NR	855	2	NR	985	0	NR
470	88	NR	600	994	NR	730	65	NR	860	1	NR	990	0	NR
475	87	NR	605	997	NR	735	56	NR	865	1	NR	995	0	NR
480	96	NR	610	990	NR	740	47	NR	870	1	NR	1000	0	NR
485	122	NR	615	971	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-9



TM-30-18

Summary

$R_f = 81.5$
 $R_g = 99.2$
 $CIE R_a = 80.9$
 $R_9 = 6.8$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 74	CES51 = 89	CES76 = 70
CES02 = 63	CES27 = 88	CES52 = 91	CES77 = 86
CES03 = 31	CES28 = 89	CES53 = 81	CES78 = 72
CES04 = 70	CES29 = 67	CES54 = 87	CES79 = 90
CES05 = 50	CES30 = 68	CES55 = 85	CES80 = 88
CES06 = 51	CES31 = 71	CES56 = 78	CES81 = 78
CES07 = 42	CES32 = 70	CES57 = 76	CES82 = 95
CES08 = 41	CES33 = 71	CES58 = 78	CES83 = 90
CES09 = 29	CES34 = 82	CES59 = 92	CES84 = 93
CES10 = 76	CES35 = 90	CES60 = 95	CES85 = 86
CES11 = 59	CES36 = 93	CES61 = 93	CES86 = 72
CES12 = 65	CES37 = 87	CES62 = 83	CES87 = 85
CES13 = 43	CES38 = 75	CES63 = 77	CES88 = 83
CES14 = 74	CES39 = 94	CES64 = 83	CES89 = 75
CES15 = 71	CES40 = 89	CES65 = 77	CES90 = 81
CES16 = 47	CES41 = 85	CES66 = 80	CES91 = 96
CES17 = 50	CES42 = 86	CES67 = 79	CES92 = 73
CES18 = 56	CES43 = 81	CES68 = 84	CES93 = 84
CES19 = 72	CES44 = 99	CES69 = 90	CES94 = 64
CES20 = 66	CES45 = 87	CES70 = 77	CES95 = 80
CES21 = 87	CES46 = 82	CES71 = 76	CES96 = 84
CES22 = 79	CES47 = 77	CES72 = 92	CES97 = 87
CES23 = 92	CES48 = 71	CES73 = 71	CES98 = 81
CES24 = 91	CES49 = 81	CES74 = 93	CES99 = 74
CES25 = 72	CES50 = 89	CES75 = 74	



Color Rendition by Hue-Angle Bin



Measure Comparisons


(END OF REPORT)