

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066641

Luminaire Tested: **NVN-SA6A-830-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066641
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA6A-830-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 615mA 6xLight Square PACKAGE
80CRI 3000K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (84) 3000K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 14671 lumens
Efficiency: N/A
Efficacy: 90.8 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 161.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

Iso-Footcandle Lines of Horizontal Illumination


× Max cd
 - - - 1/2 Max cd



Based on 15 foot mounting height. Maximum calculated value = 2.9 fc
 Type III - Short - N/A

REPORT NUMBER: P1066641
CATALOG NUMBER: NVN-SA6A-830-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	87.3	0.0	87.3
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	14583.7	0.0	14583.7
	% Fixture	99.4	0.0	99.4
Total	Lumens	14670.9	0.0	14670.9
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.3	0.0
10°-20°	21.5	0.1
20°-30°	273.8	1.9
30°-40°	922.9	6.3
40°-50°	2787.0	19.0
50°-60°	4917.2	33.5
60°-70°	4332.1	29.5
70°-80°	1379.0	9.4
80°-90°	33.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	14670.9	100.0
0°-180°	14671.0	100.0



REPORT NUMBER: P1066641


CATALOG NUMBER: NVN-SA6A-830-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	286.6	2.0			
FM	(30°-60°)	8593.3	58.6			
FH	(60°-80°)	5676.9	38.7			G3/7500
FVH	(80°-90°)	27.0	0.2			G1/100
BL	(0°-30°)	13.1	0.1	B0/110		
BM	(30°-60°)	33.8	0.2	B0/220		
BH	(60°-80°)	34.2	0.2	B0/110		G0/110
BVH	(80°-90°)	6.2	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	32.2
5°	46.0	46.0	46.0	41.4	41.4	41.4	36.8	36.8	36.8	36.8	36.8
7.5°	55.2	50.6	50.6	46.0	46.0	46.0	41.4	41.4	41.4	41.4	36.8
10°	64.4	59.8	59.8	55.2	55.2	50.6	50.6	46.0	46.0	41.4	41.4
12.5°	73.6	69.0	64.4	59.8	59.8	55.2	55.2	50.6	50.6	46.0	46.0
15°	82.8	78.2	73.6	69.0	64.4	64.4	59.8	55.2	50.6	50.6	46.0
17.5°	96.6	87.4	82.8	73.6	69.0	64.4	59.8	55.2	55.2	50.6	50.6
20°	101.2	92.0	87.4	78.2	73.6	69.0	64.4	59.8	55.2	55.2	50.6
22.5°	119.6	101.2	96.6	87.4	82.8	78.2	69.0	64.4	59.8	55.2	50.6
25°	147.2	119.6	105.8	92.0	87.4	78.2	73.6	64.4	59.8	55.2	50.6
27.5°	179.4	133.4	119.6	101.2	92.0	82.8	73.6	64.4	59.8	55.2	50.6
30°	220.8	156.4	133.4	110.4	101.2	92.0	78.2	69.0	64.4	59.8	50.6
32.5°	308.3	193.2	156.4	119.6	105.8	96.6	82.8	69.0	64.4	59.8	50.6
35°	372.7	234.6	188.6	138.0	119.6	105.8	87.4	69.0	64.4	59.8	50.6
37.5°	432.5	239.2	193.2	147.2	128.8	110.4	87.4	69.0	64.4	59.8	50.6
40°	529.1	248.4	193.2	138.0	124.2	105.8	92.0	73.6	69.0	59.8	55.2
42.5°	713.1	285.3	207.0	128.8	115.0	105.8	92.0	78.2	69.0	64.4	55.2
45°	1187.0	423.3	280.6	133.4	119.6	105.8	92.0	78.2	73.6	64.4	59.8
47.5°	2019.8	736.1	437.1	138.0	124.2	105.8	92.0	73.6	69.0	64.4	55.2
50°	2585.7	943.2	552.1	161.0	138.0	119.6	96.6	73.6	69.0	64.4	59.8
52.5°	2746.7	1003.0	598.1	188.6	161.0	133.4	101.2	73.6	69.0	69.0	64.4
55°	2516.6	975.4	598.1	220.8	184.0	151.8	115.0	78.2	73.6	73.6	69.0
57.5°	2139.4	901.8	570.5	239.2	202.4	161.0	124.2	82.8	78.2	78.2	73.6
60°	1762.1	759.1	515.3	266.8	225.4	184.0	142.6	101.2	96.6	92.0	82.8
62.5°	1398.6	611.9	450.9	285.3	243.8	197.8	156.4	110.4	105.8	101.2	96.6
65°	1053.6	533.7	418.7	299.1	253.0	207.0	161.0	115.0	110.4	110.4	105.8
67.5°	809.7	487.7	400.3	308.3	262.2	216.2	170.2	124.2	119.6	115.0	110.4
70°	639.5	450.9	377.3	303.7	262.2	220.8	174.8	133.4	124.2	119.6	110.4
72.5°	533.7	409.5	349.7	289.9	257.6	225.4	193.2	161.0	142.6	128.8	110.4
75°	446.3	368.1	317.5	262.2	239.2	220.8	197.8	174.8	151.8	128.8	105.8
77.5°	294.5	266.8	243.8	220.8	207.0	193.2	174.8	161.0	138.0	119.6	96.6
80°	124.2	115.0	119.6	119.6	119.6	119.6	115.0	115.0	101.2	87.4	69.0
82.5°	27.6	23.0	27.6	27.6	27.6	27.6	23.0	23.0	23.0	18.4	18.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2
5°	36.8	36.8	36.8	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2
7.5°	36.8	36.8	36.8	32.2	32.2	32.2	32.2	27.6	27.6	27.6	27.6
10°	36.8	36.8	36.8	32.2	32.2	32.2	32.2	27.6	27.6	27.6	27.6
12.5°	41.4	41.4	36.8	36.8	32.2	32.2	32.2	27.6	27.6	27.6	27.6
15°	41.4	41.4	36.8	36.8	32.2	32.2	32.2	27.6	27.6	27.6	27.6
17.5°	46.0	41.4	41.4	36.8	32.2	32.2	32.2	27.6	27.6	27.6	27.6
20°	46.0	41.4	41.4	36.8	32.2	32.2	32.2	27.6	27.6	27.6	27.6
22.5°	46.0	41.4	41.4	36.8	32.2	32.2	27.6	27.6	23.0	23.0	18.4
25°	46.0	41.4	41.4	36.8	32.2	32.2	27.6	27.6	23.0	18.4	18.4
27.5°	46.0	41.4	41.4	36.8	32.2	27.6	27.6	23.0	18.4	13.8	13.8
30°	46.0	41.4	41.4	36.8	32.2	27.6	23.0	18.4	13.8	13.8	9.2
32.5°	46.0	41.4	36.8	32.2	27.6	23.0	23.0	18.4	13.8	9.2	9.2
35°	46.0	41.4	36.8	32.2	27.6	23.0	23.0	18.4	13.8	9.2	9.2
37.5°	46.0	41.4	36.8	32.2	27.6	23.0	18.4	13.8	9.2	9.2	4.6
40°	46.0	41.4	36.8	32.2	27.6	23.0	18.4	13.8	9.2	9.2	4.6
42.5°	46.0	41.4	36.8	32.2	27.6	23.0	18.4	13.8	9.2	9.2	4.6
45°	50.6	46.0	41.4	32.2	27.6	23.0	23.0	18.4	13.8	9.2	9.2
47.5°	50.6	46.0	41.4	32.2	27.6	23.0	23.0	18.4	13.8	9.2	9.2
50°	55.2	50.6	46.0	36.8	32.2	27.6	23.0	13.8	9.2	9.2	4.6
52.5°	59.8	55.2	50.6	46.0	41.4	32.2	23.0	13.8	4.6	4.6	4.6
55°	64.4	59.8	59.8	55.2	50.6	36.8	27.6	13.8	0.0	0.0	0.0
57.5°	69.0	64.4	64.4	59.8	55.2	41.4	27.6	13.8	0.0	0.0	0.0
60°	78.2	73.6	69.0	59.8	55.2	41.4	27.6	13.8	0.0	0.0	0.0
62.5°	92.0	82.8	69.0	59.8	46.0	36.8	23.0	13.8	0.0	0.0	0.0
65°	101.2	87.4	73.6	55.2	41.4	32.2	23.0	9.2	0.0	0.0	0.0
67.5°	105.8	87.4	73.6	55.2	36.8	27.6	18.4	9.2	0.0	0.0	0.0
70°	101.2	82.8	69.0	50.6	32.2	23.0	18.4	9.2	0.0	0.0	0.0
72.5°	92.0	78.2	59.8	46.0	27.6	23.0	13.8	9.2	0.0	0.0	0.0
75°	82.8	69.0	50.6	36.8	18.4	13.8	9.2	4.6	0.0	0.0	0.0
77.5°	73.6	59.8	41.4	27.6	9.2	9.2	4.6	4.6	0.0	0.0	0.0
80°	55.2	41.4	27.6	13.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	13.8	9.2	9.2	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6
5°	27.6	27.6	27.6	27.6	23.0	23.0	23.0	23.0	23.0	23.0	23.0
7.5°	27.6	27.6	27.6	27.6	23.0	23.0	23.0	23.0	18.4	18.4	18.4
10°	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	18.4	18.4	18.4
12.5°	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	18.4	18.4	18.4
15°	23.0	23.0	23.0	23.0	23.0	23.0	23.0	18.4	18.4	13.8	13.8
17.5°	23.0	23.0	23.0	23.0	18.4	18.4	18.4	13.8	13.8	9.2	9.2
20°	23.0	23.0	23.0	18.4	18.4	13.8	13.8	9.2	9.2	4.6	4.6
22.5°	18.4	13.8	13.8	9.2	9.2	4.6	4.6	4.6	0.0	0.0	0.0
25°	13.8	9.2	9.2	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	9.2	4.6	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	9.2	4.6	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	27.6	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0
5°	23.0	23.0	23.0	23.0	18.4	18.4	18.4	18.4	18.4	18.4	18.4
7.5°	18.4	18.4	18.4	18.4	18.4	18.4	13.8	13.8	13.8	13.8	13.8
10°	18.4	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8	9.2	9.2
12.5°	18.4	13.8	13.8	13.8	9.2	9.2	9.2	9.2	9.2	4.6	4.6
15°	13.8	9.2	9.2	9.2	4.6	4.6	4.6	4.6	4.6	0.0	0.0
17.5°	9.2	4.6	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	23.0	27.6	27.6
5°	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4
7.5°	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8	13.8
10°	9.2	9.2	9.2	9.2	9.2	9.2	4.6	4.6	4.6	4.6	4.6
12.5°	4.6	4.6	4.6	4.6	4.6	4.6	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	27.6	27.6	27.6	27.6	27.6	32.2	32.2	36.8	36.8	41.4	41.4
5°	18.4	18.4	23.0	23.0	23.0	23.0	27.6	27.6	27.6	32.2	32.2
7.5°	13.8	13.8	13.8	13.8	13.8	18.4	18.4	23.0	23.0	27.6	27.6
10°	4.6	4.6	9.2	9.2	9.2	9.2	13.8	13.8	13.8	18.4	23.0
12.5°	0.0	0.0	4.6	4.6	4.6	4.6	9.2	9.2	9.2	13.8	18.4
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	9.2	13.8
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	9.2
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	46.0	46.0	50.6	50.6	55.2	55.2	59.8	59.8	59.8	59.8	59.8
5°	36.8	36.8	41.4	46.0	46.0	50.6	55.2	55.2	55.2	55.2	55.2
7.5°	32.2	32.2	36.8	41.4	41.4	46.0	50.6	50.6	55.2	55.2	55.2
10°	23.0	27.6	32.2	36.8	36.8	41.4	46.0	46.0	50.6	50.6	50.6
12.5°	18.4	23.0	27.6	32.2	32.2	36.8	41.4	41.4	46.0	46.0	50.6
15°	13.8	18.4	23.0	27.6	27.6	32.2	36.8	36.8	41.4	46.0	50.6
17.5°	9.2	13.8	18.4	23.0	23.0	27.6	32.2	36.8	41.4	41.4	46.0
20°	9.2	9.2	13.8	18.4	18.4	23.0	27.6	32.2	36.8	36.8	41.4
22.5°	4.6	4.6	9.2	13.8	13.8	18.4	23.0	27.6	32.2	32.2	36.8
25°	0.0	0.0	4.6	9.2	9.2	13.8	18.4	18.4	23.0	23.0	27.6
27.5°	0.0	0.0	4.6	4.6	9.2	9.2	13.8	13.8	18.4	18.4	23.0
30°	0.0	0.0	4.6	4.6	9.2	9.2	13.8	13.8	18.4	18.4	18.4
32.5°	0.0	0.0	0.0	4.6	4.6	4.6	9.2	9.2	13.8	13.8	18.4
35°	0.0	0.0	0.0	4.6	4.6	4.6	9.2	9.2	13.8	13.8	13.8
37.5°	0.0	0.0	0.0	4.6	4.6	4.6	9.2	9.2	9.2	9.2	13.8
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	9.2	9.2	9.2
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	9.2
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.6	4.6	4.6	4.6	4.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	59.8	59.8
5°	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	55.2	55.2
7.5°	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	55.2	55.2
10°	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
12.5°	50.6	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
15°	50.6	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
17.5°	46.0	50.6	50.6	50.6	55.2	55.2	55.2	55.2	55.2	55.2	55.2
20°	41.4	46.0	46.0	46.0	50.6	50.6	50.6	50.6	55.2	55.2	55.2
22.5°	36.8	41.4	41.4	41.4	46.0	46.0	46.0	46.0	50.6	50.6	50.6
25°	32.2	32.2	36.8	36.8	41.4	41.4	41.4	41.4	41.4	41.4	41.4
27.5°	23.0	27.6	27.6	27.6	32.2	32.2	32.2	32.2	36.8	36.8	36.8
30°	23.0	23.0	23.0	23.0	27.6	27.6	27.6	27.6	32.2	32.2	32.2
32.5°	18.4	23.0	23.0	23.0	27.6	27.6	27.6	27.6	32.2	32.2	32.2
35°	18.4	18.4	18.4	18.4	23.0	23.0	23.0	23.0	27.6	27.6	27.6
37.5°	13.8	18.4	18.4	18.4	23.0	23.0	23.0	23.0	27.6	27.6	27.6
40°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
42.5°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
45°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
47.5°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
50°	13.8	13.8	13.8	13.8	18.4	18.4	18.4	18.4	23.0	23.0	23.0
52.5°	9.2	9.2	9.2	9.2	13.8	13.8	13.8	13.8	18.4	18.4	18.4
55°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	13.8	13.8	13.8
57.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	13.8	13.8	13.8
60°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
62.5°	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
65°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	4.6	4.6
67.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
70°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
72.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
75°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
77.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
80°	13.8	13.8	13.8	13.8	13.8	9.2	9.2	9.2	9.2	9.2	9.2
82.5°	9.2	13.8	13.8	13.8	13.8	9.2	9.2	9.2	9.2	9.2	9.2
85°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
87.5°	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	59.8	59.8	55.2	55.2	55.2	55.2	55.2	55.2	55.2	59.8	59.8
5°	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	59.8	59.8
7.5°	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	59.8	59.8
10°	55.2	55.2	55.2	55.2	50.6	50.6	55.2	55.2	55.2	59.8	59.8
12.5°	55.2	55.2	55.2	55.2	50.6	50.6	55.2	55.2	59.8	59.8	64.4
15°	55.2	55.2	50.6	50.6	50.6	50.6	55.2	55.2	59.8	59.8	64.4
17.5°	55.2	55.2	50.6	50.6	50.6	50.6	55.2	55.2	59.8	59.8	64.4
20°	55.2	55.2	50.6	50.6	50.6	50.6	50.6	50.6	55.2	59.8	59.8
22.5°	50.6	50.6	50.6	50.6	46.0	46.0	50.6	50.6	55.2	59.8	59.8
25°	41.4	46.0	46.0	46.0	46.0	46.0	50.6	50.6	55.2	59.8	59.8
27.5°	36.8	41.4	41.4	41.4	41.4	46.0	46.0	50.6	55.2	59.8	59.8
30°	32.2	36.8	36.8	36.8	41.4	46.0	46.0	50.6	55.2	59.8	59.8
32.5°	32.2	36.8	36.8	36.8	41.4	41.4	46.0	46.0	50.6	55.2	59.8
35°	32.2	32.2	36.8	36.8	36.8	41.4	41.4	46.0	50.6	55.2	59.8
37.5°	32.2	32.2	36.8	36.8	36.8	41.4	41.4	46.0	50.6	55.2	59.8
40°	27.6	32.2	32.2	36.8	36.8	41.4	41.4	46.0	50.6	59.8	64.4
42.5°	27.6	27.6	32.2	32.2	36.8	41.4	41.4	46.0	50.6	59.8	64.4
45°	27.6	32.2	32.2	36.8	41.4	46.0	46.0	50.6	55.2	59.8	64.4
47.5°	27.6	32.2	32.2	36.8	46.0	46.0	50.6	50.6	55.2	59.8	64.4
50°	27.6	32.2	32.2	36.8	50.6	50.6	50.6	50.6	55.2	59.8	64.4
52.5°	23.0	27.6	27.6	32.2	41.4	46.0	50.6	55.2	59.8	64.4	69.0
55°	18.4	23.0	23.0	27.6	36.8	41.4	50.6	59.8	64.4	69.0	73.6
57.5°	18.4	18.4	23.0	23.0	32.2	41.4	55.2	64.4	69.0	73.6	78.2
60°	13.8	13.8	18.4	18.4	27.6	36.8	50.6	64.4	69.0	78.2	82.8
62.5°	9.2	13.8	13.8	18.4	23.0	36.8	50.6	64.4	73.6	82.8	87.4
65°	9.2	9.2	13.8	13.8	23.0	32.2	46.0	55.2	69.0	82.8	96.6
67.5°	13.8	13.8	18.4	18.4	23.0	32.2	46.0	55.2	69.0	87.4	101.2
70°	13.8	13.8	18.4	18.4	27.6	36.8	46.0	55.2	69.0	87.4	101.2
72.5°	13.8	13.8	18.4	18.4	27.6	32.2	41.4	50.6	64.4	78.2	92.0
75°	9.2	13.8	13.8	13.8	23.0	27.6	36.8	46.0	59.8	73.6	87.4
77.5°	9.2	9.2	9.2	9.2	18.4	23.0	32.2	36.8	50.6	64.4	78.2
80°	9.2	9.2	9.2	9.2	13.8	18.4	27.6	32.2	46.0	59.8	73.6
82.5°	9.2	9.2	4.6	4.6	9.2	13.8	18.4	23.0	36.8	46.0	59.8
85°	9.2	9.2	4.6	4.6	4.6	9.2	9.2	13.8	18.4	23.0	27.6
87.5°	9.2	9.2	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	59.8	59.8	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
5°	59.8	64.4	64.4	69.0	69.0	69.0	73.6	73.6	73.6	73.6	73.6
7.5°	59.8	64.4	64.4	69.0	69.0	69.0	73.6	73.6	73.6	78.2	78.2
10°	59.8	64.4	64.4	69.0	69.0	73.6	78.2	78.2	82.8	82.8	82.8
12.5°	64.4	69.0	69.0	73.6	73.6	78.2	82.8	82.8	87.4	92.0	92.0
15°	64.4	69.0	73.6	73.6	78.2	82.8	87.4	87.4	92.0	96.6	101.2
17.5°	64.4	69.0	73.6	73.6	78.2	82.8	92.0	96.6	101.2	110.4	115.0
20°	64.4	69.0	73.6	73.6	78.2	87.4	92.0	101.2	105.8	115.0	124.2
22.5°	64.4	69.0	73.6	78.2	82.8	92.0	101.2	105.8	115.0	128.8	138.0
25°	64.4	69.0	73.6	78.2	82.8	92.0	101.2	110.4	119.6	138.0	156.4
27.5°	64.4	69.0	78.2	82.8	87.4	96.6	110.4	119.6	128.8	161.0	193.2
30°	64.4	69.0	78.2	82.8	87.4	101.2	115.0	124.2	138.0	193.2	243.8
32.5°	64.4	73.6	78.2	87.4	92.0	105.8	124.2	138.0	151.8	230.0	303.7
35°	64.4	73.6	78.2	87.4	92.0	110.4	128.8	147.2	165.6	280.6	395.7
37.5°	64.4	73.6	78.2	87.4	92.0	119.6	147.2	174.8	202.4	322.1	441.7
40°	69.0	78.2	82.8	92.0	96.6	124.2	151.8	179.4	207.0	326.7	446.3
42.5°	69.0	78.2	82.8	92.0	96.6	119.6	147.2	170.2	193.2	326.7	460.1
45°	69.0	78.2	87.4	92.0	101.2	124.2	147.2	165.6	188.6	358.9	524.5
47.5°	69.0	78.2	87.4	92.0	101.2	124.2	147.2	170.2	193.2	473.9	749.9
50°	69.0	78.2	87.4	92.0	101.2	128.8	156.4	184.0	211.6	708.5	1205.4
52.5°	73.6	78.2	87.4	92.0	96.6	128.8	161.0	193.2	225.4	920.2	1610.3
55°	78.2	82.8	87.4	92.0	96.6	138.0	179.4	220.8	262.2	989.2	1711.5
57.5°	82.8	87.4	92.0	92.0	96.6	147.2	202.4	253.0	303.7	984.6	1660.9
60°	87.4	92.0	96.6	101.2	105.8	156.4	211.6	262.2	312.9	892.6	1472.3
62.5°	96.6	105.8	115.0	119.6	128.8	179.4	225.4	276.0	322.1	731.5	1136.4
65°	110.4	119.6	124.2	133.4	138.0	184.0	234.6	280.6	326.7	607.3	883.4
67.5°	115.0	124.2	128.8	138.0	142.6	188.6	234.6	280.6	326.7	515.3	699.3
70°	115.0	124.2	133.4	138.0	147.2	193.2	234.6	280.6	322.1	446.3	570.5
72.5°	105.8	119.6	128.8	142.6	151.8	193.2	230.0	271.4	308.3	395.7	483.1
75°	101.2	119.6	133.4	151.8	165.6	193.2	225.4	253.0	280.6	345.1	409.5
77.5°	92.0	115.0	138.0	161.0	184.0	202.4	216.2	234.6	248.4	289.9	331.3
80°	87.4	110.4	133.4	156.4	179.4	188.6	193.2	202.4	207.0	211.6	216.2
82.5°	69.0	87.4	105.8	119.6	138.0	128.8	124.2	115.0	105.8	101.2	96.6
85°	32.2	36.8	36.8	41.4	41.4	41.4	36.8	36.8	32.2	27.6	23.0
87.5°	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	64.4	64.4	64.4	64.4	59.8	59.8	59.8	59.8	55.2	55.2	55.2
5°	73.6	73.6	73.6	73.6	69.0	69.0	69.0	69.0	64.4	64.4	64.4
7.5°	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2
10°	87.4	87.4	87.4	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0
12.5°	96.6	96.6	101.2	101.2	105.8	105.8	110.4	110.4	115.0	115.0	115.0
15°	105.8	110.4	115.0	119.6	119.6	124.2	128.8	133.4	138.0	142.6	147.2
17.5°	124.2	128.8	138.0	147.2	156.4	165.6	179.4	197.8	211.6	225.4	243.8
20°	138.0	151.8	179.4	211.6	239.2	266.8	335.9	404.9	473.9	542.9	611.9
22.5°	165.6	193.2	285.3	381.9	473.9	565.9	782.1	998.4	1210.0	1426.3	1619.5
25°	220.8	280.6	492.3	703.9	911.0	1122.6	1509.1	1900.1	2286.6	2673.1	3031.9
27.5°	303.7	414.1	759.1	1108.8	1453.9	1798.9	2360.2	2926.1	3487.4	4053.3	4554.8
30°	423.3	602.7	1118.0	1637.9	2153.2	2668.5	3377.0	4090.1	4798.6	5507.2	5967.3
32.5°	575.1	841.9	1495.3	2148.6	2801.9	3455.2	4237.3	5019.5	5797.0	6579.2	7066.8
35°	736.1	1076.6	1863.3	2654.7	3441.4	4232.7	5056.3	5879.8	6703.4	7526.9	8125.0
37.5°	828.1	1214.6	2148.6	3082.5	4011.9	4945.9	5847.6	6754.0	7655.8	8557.5	9284.4
40°	915.6	1380.2	2456.8	3533.4	4610.0	5686.6	6740.2	7793.8	8847.4	9900.9	10834.9
42.5°	1044.4	1628.7	2884.7	4140.7	5392.2	6648.2	8033.0	9422.5	10807.3	12192.2	13627.6
45°	1311.2	2098.0	3726.7	5355.3	6979.4	8608.1	10572.7	12541.8	14506.4	16475.5	18315.8
47.5°	1955.3	3156.2	5378.3	7600.5	9822.7	12044.9	14308.5	16572.1	18835.7	21099.3	23289.3
50°	3027.3	4844.7	7623.5	10402.4	13176.7	15955.6	18214.6	20473.6	22728.0	24987.0	27163.2
52.5°	4034.9	6459.5	9445.5	12436.0	15421.9	18412.4	20413.8	22415.2	24416.5	26417.9	28525.0
55°	4380.0	7043.8	10066.6	13093.9	16116.6	19144.0	21071.7	23004.1	24931.8	26859.5	29044.9
57.5°	4076.3	6491.7	9537.5	12583.2	15624.4	18670.1	20823.3	22981.1	25134.2	27292.0	29633.8
60°	3413.8	5350.7	8548.3	11750.5	14948.0	18145.6	20574.8	23004.1	25433.3	27862.5	30199.7
62.5°	2705.3	4269.6	7655.8	11041.9	14428.1	17814.3	20285.0	22760.2	25230.9	27701.5	29495.8
65°	2075.0	3266.6	6597.6	9933.2	13264.1	16599.7	18624.1	20653.0	22677.4	24706.4	25948.6
67.5°	1541.3	2383.2	5295.5	8212.4	11124.8	14037.1	15527.7	17023.0	18513.7	20008.9	20975.1
70°	1136.4	1697.7	3680.6	5663.6	7641.9	9624.9	10991.3	12357.8	13719.6	15086.1	16089.0
72.5°	786.7	1085.8	2272.8	3464.4	4651.4	5838.4	7223.3	8608.1	9988.4	11373.2	12514.2
75°	538.3	667.1	1223.8	1780.5	2337.2	2893.9	3942.9	4991.9	6040.9	7089.9	7692.6
77.5°	400.3	469.3	634.9	805.1	970.8	1136.4	1338.8	1541.3	1743.7	1946.1	2208.4
80°	220.8	220.8	243.8	262.2	285.3	303.7	358.9	418.7	473.9	533.7	607.3
82.5°	101.2	105.8	115.0	124.2	128.8	138.0	147.2	156.4	165.6	174.8	174.8
85°	27.6	32.2	32.2	27.6	27.6	23.0	23.0	27.6	27.6	27.6	27.6
87.5°	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	55.2	50.6	50.6	50.6	46.0	46.0	46.0	46.0	46.0	46.0	46.0
5°	64.4	64.4	64.4	64.4	59.8	59.8	59.8	59.8	59.8	55.2	55.2
7.5°	78.2	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	69.0	69.0
10°	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	87.4	87.4
12.5°	115.0	115.0	115.0	115.0	119.6	119.6	115.0	115.0	115.0	110.4	110.4
15°	151.8	156.4	161.0	161.0	165.6	165.6	165.6	161.0	161.0	156.4	151.8
17.5°	257.6	271.4	289.9	308.3	326.7	340.5	340.5	331.3	322.1	312.9	303.7
20°	685.5	754.5	828.1	901.8	980.0	1035.2	998.4	970.8	943.2	911.0	883.4
22.5°	1817.3	2010.6	2208.4	2346.4	2484.4	2581.1	2502.8	2351.0	2199.2	2052.0	1900.1
25°	3390.8	3745.1	4103.9	4251.2	4403.0	4513.4	4462.8	4232.7	4002.7	3777.3	3547.2
27.5°	5056.3	5553.2	6054.7	6183.5	6312.3	6408.9	6390.5	6091.5	5792.4	5493.4	5194.3
30°	6427.3	6887.4	7347.5	7476.3	7605.1	7692.6	7595.9	7296.9	6997.8	6698.8	6399.7
32.5°	7559.1	8046.8	8539.1	8709.3	8879.6	8994.6	8879.6	8520.7	8161.8	7807.6	7448.7
35°	8723.1	9316.6	9914.7	10131.0	10347.2	10485.3	10292.0	9850.3	9408.7	8971.6	8529.9
37.5°	10011.4	10733.7	11460.6	11755.1	12054.1	12261.2	12113.9	11561.8	11005.1	10453.0	9896.3
40°	11773.5	12707.4	13646.0	14175.1	14699.6	15072.3	14810.0	14170.5	13526.4	12886.9	12242.8
42.5°	15067.7	16503.1	17938.6	18697.7	19452.2	19999.7	19705.3	18918.5	18131.8	17345.1	16558.3
45°	20156.2	21991.9	23832.2	24941.0	26054.4	26873.3	26532.9	25543.7	24549.9	23560.8	22571.6
47.5°	25479.3	27669.3	29859.3	30742.6	31630.6	32320.7	32237.9	31004.9	29771.9	28543.4	27310.4
50°	29344.0	31520.2	33696.3	34455.5	35219.2	35785.1	35573.5	34004.6	32431.1	30862.2	29288.8
52.5°	30632.2	32734.8	34841.9	35748.3	36654.7	37331.0	37073.3	35306.6	33539.9	31777.8	30011.1
55°	31230.3	33415.7	35601.1	36705.3	37814.1	38623.8	38251.1	36314.2	34372.7	32435.7	30494.2
57.5°	31975.6	34317.5	36659.3	37869.3	39079.3	39953.4	39456.6	37450.6	35444.7	33443.3	31437.3
60°	32536.9	34869.6	37206.8	38177.5	39152.9	39833.8	39355.3	37404.6	35449.3	33498.5	31547.8
62.5°	31294.7	33089.0	34883.4	35605.7	36328.0	36852.5	36581.1	34731.5	32882.0	31032.5	29182.9
65°	27195.4	28437.6	29684.4	30172.1	30655.2	31027.9	30945.1	29385.4	27825.7	26270.6	24711.0
67.5°	21945.9	22912.0	23882.8	24572.9	25267.7	25806.0	25746.1	24324.5	22902.8	21481.2	20059.5
70°	17096.6	18099.6	19102.6	19972.1	20846.3	21522.6	21435.2	20114.7	18789.7	17469.3	16144.2
72.5°	13659.8	14800.8	15941.8	16438.7	16935.6	17285.3	17027.6	16029.2	15026.3	14027.9	13024.9
75°	8295.3	8893.4	9496.1	9491.5	9491.5	9436.3	9178.6	8608.1	8037.6	7467.1	6896.6
77.5°	2470.6	2732.9	2995.1	3248.2	3505.8	3699.1	3648.4	3349.4	3045.7	2746.7	2443.0
80°	680.9	749.9	823.5	855.8	888.0	929.4	1035.2	961.6	888.0	818.9	745.3
82.5°	174.8	174.8	174.8	170.2	165.6	156.4	142.6	133.4	124.2	115.0	105.8
85°	27.6	23.0	23.0	23.0	18.4	18.4	18.4	18.4	13.8	13.8	9.2
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4
2.5°	46.0	46.0	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	36.8
5°	55.2	55.2	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6	46.0
7.5°	69.0	69.0	64.4	64.4	64.4	64.4	59.8	59.8	59.8	59.8	55.2
10°	87.4	82.8	82.8	78.2	78.2	78.2	73.6	73.6	73.6	69.0	69.0
12.5°	110.4	105.8	105.8	101.2	96.6	96.6	92.0	87.4	82.8	82.8	78.2
15°	147.2	142.6	138.0	133.4	128.8	119.6	115.0	105.8	101.2	96.6	92.0
17.5°	280.6	257.6	234.6	211.6	193.2	174.8	156.4	138.0	128.8	119.6	110.4
20°	782.1	676.3	575.1	473.9	409.5	345.1	280.6	216.2	188.6	165.6	138.0
22.5°	1693.1	1481.5	1274.4	1062.8	892.6	726.9	556.7	386.5	322.1	262.2	197.8
25°	3147.0	2742.1	2341.8	1936.9	1614.9	1292.8	970.8	648.7	529.1	409.5	289.9
27.5°	4669.8	4145.3	3620.8	3096.3	2585.7	2070.4	1555.1	1044.4	837.3	634.9	427.9
30°	5843.0	5286.3	4734.2	4177.5	3533.4	2889.3	2240.6	1596.5	1269.8	943.2	611.9
32.5°	6850.6	6247.9	5649.8	5047.1	4301.8	3556.4	2811.1	2065.8	1656.3	1246.8	832.7
35°	7849.0	7163.5	6482.5	5797.0	4996.5	4195.9	3395.4	2594.9	2075.0	1555.1	1030.6
37.5°	9063.6	8226.3	7393.5	6560.8	5737.2	4918.3	4094.7	3271.2	2608.7	1950.7	1288.2
40°	11180.0	10112.6	9049.8	7982.4	7020.8	6063.9	5102.3	4140.7	3308.0	2475.2	1637.9
42.5°	15219.5	13880.6	12546.4	11207.6	9877.9	8548.3	7214.1	5884.4	4697.4	3515.0	2328.0
45°	20855.5	19139.4	17427.9	15711.8	14073.9	12440.6	10802.7	9164.8	7361.3	5557.8	3749.7
47.5°	25433.3	23551.6	21674.4	19792.7	17975.4	16162.7	14345.3	12528.0	10218.4	7913.4	5603.8
50°	27499.1	25704.7	23915.0	22120.7	20298.8	18472.3	16645.7	14823.8	12173.7	9528.3	6878.2
52.5°	28193.8	26371.9	24554.5	22732.6	20924.5	19116.4	17308.3	15500.1	12744.2	9993.0	7237.1
55°	28575.6	26652.5	24734.0	22810.8	20864.7	18913.9	16963.2	15017.0	12275.0	9537.5	6795.4
57.5°	29348.6	27255.2	25166.4	23073.1	20855.5	18637.9	16415.7	14198.1	11492.8	8787.6	6082.3
60°	29491.2	27430.0	25373.5	23316.9	20864.7	18412.4	15955.6	13503.4	10816.5	8134.2	5447.4
62.5°	27462.2	25741.5	24025.4	22304.7	19847.9	17391.1	14929.6	12472.8	9900.9	7329.1	4752.6
65°	23224.9	21738.8	20257.4	18771.3	16765.4	14764.0	12758.1	10752.1	8456.3	6165.1	3869.3
67.5°	18605.7	17151.8	15702.6	14248.7	12739.6	11235.2	9726.1	8217.0	6445.7	4674.4	2903.1
70°	14750.2	13351.6	11957.5	10558.9	9224.6	7885.8	6547.0	5212.7	4113.1	3018.1	1918.5
72.5°	11690.7	10351.8	9017.6	7678.8	6468.7	5258.7	4048.7	2838.7	2291.2	1748.3	1200.8
75°	6201.9	5507.2	4817.0	4122.3	3441.4	2755.9	2070.4	1389.4	1173.2	957.0	736.1
77.5°	2139.4	1835.7	1536.7	1233.0	1026.0	818.9	611.9	404.9	381.9	363.5	340.5
80°	648.7	552.1	455.5	358.9	317.5	276.0	234.6	193.2	179.4	165.6	147.2
82.5°	101.2	92.0	87.4	78.2	73.6	73.6	69.0	64.4	55.2	50.6	41.4
85°	9.2	4.6	4.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066641
 CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	41.4	41.4
2.5°	36.8	36.8
5°	46.0	46.0
7.5°	55.2	55.2
10°	64.4	64.4
12.5°	73.6	73.6
15°	87.4	82.8
17.5°	101.2	96.6
20°	110.4	101.2
22.5°	133.4	115.0
25°	170.2	142.6
27.5°	220.8	174.8
30°	285.3	220.8
32.5°	423.3	308.3
35°	510.7	372.7
37.5°	625.7	432.5
40°	805.1	524.5
42.5°	1141.0	713.1
45°	1946.1	1182.4
47.5°	3298.8	2015.2
50°	4228.1	2585.7
52.5°	4485.8	2742.1
55°	4057.9	2516.6
57.5°	3377.0	2139.4
60°	2765.1	1762.1
62.5°	2180.8	1394.0
65°	1573.5	1053.6
67.5°	1131.8	809.7
70°	823.5	634.9
72.5°	653.3	529.1
75°	519.9	441.7
77.5°	322.1	294.5
80°	133.4	124.2
82.5°	32.2	27.6
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066641

CATALOG NUMBER: NVN-SA6A-830-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-9

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-830-U-5WQ

Data in this report applies to families of products including GSS-SB1A-830-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-9
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-830-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI
 3000K CCT 26 LEDS

Spectral Parameters

CCT (K): 3055
 CIE u' : 0.2475
 CIE v' : 0.5247
 Duv: 0.0032
 CIE x: 0.4377
 CIE y: 0.4124
 CIE z: 0.1499
 Peak Wavelength (nm): 604
 Dominant Wavelength (nm): 581
 Purity: 55.16339
 R_f: 81.5
 R_g: 99.2

CRI (Ra): 80.9
 R1: 79.5
 R2: 85.6
 R3: 92.1
 R4: 82.4
 R5: 78.9
 R6: 81.7
 R7: 85.1
 R8: 61.9
 R9: 6.8
 R10: 67.1
 R11: 82.5
 R12: 63.4
 R13: 80.2
 R14: 95.1
 R15: 71.7



Test Conditions


Stabilization Time: 20M
 Operation Time: 1H 20M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-9


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-9

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-9

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (φ/nm)
360	0	NR	490	170	NR	620	938	NR	750	35	NR	880	1	NR
365	0	NR	495	234	NR	625	894	NR	755	30	NR	885	1	NR
370	0	NR	500	302	NR	630	847	NR	760	26	NR	890	1	NR
375	0	NR	505	371	NR	635	788	NR	765	22	NR	895	1	NR
380	0	NR	510	431	NR	640	728	NR	770	19	NR	900	1	NR
385	0	NR	515	482	NR	645	665	NR	775	16	NR	905	1	NR
390	0	NR	520	523	NR	650	603	NR	780	14	NR	910	0	NR
395	2	NR	525	553	NR	655	542	NR	785	12	NR	915	0	NR
400	4	NR	530	580	NR	660	484	NR	790	11	NR	920	0	NR
405	8	NR	535	603	NR	665	430	NR	795	9	NR	925	0	NR
410	18	NR	540	622	NR	670	377	NR	800	8	NR	930	0	NR
415	36	NR	545	644	NR	675	330	NR	805	7	NR	935	0	NR
420	71	NR	550	668	NR	680	289	NR	810	6	NR	940	0	NR
425	131	NR	555	693	NR	685	250	NR	815	5	NR	945	0	NR
430	215	NR	560	720	NR	690	218	NR	820	4	NR	950	0	NR
435	341	NR	565	754	NR	695	188	NR	825	4	NR	955	0	NR
440	514	NR	570	792	NR	700	161	NR	830	3	NR	960	0	NR
445	576	NR	575	832	NR	705	139	NR	835	3	NR	965	0	NR
450	358	NR	580	875	NR	710	119	NR	840	3	NR	970	0	NR
455	222	NR	585	913	NR	715	102	NR	845	2	NR	975	0	NR
460	170	NR	590	950	NR	720	88	NR	850	2	NR	980	0	NR
465	115	NR	595	977	NR	725	76	NR	855	2	NR	985	0	NR
470	88	NR	600	994	NR	730	65	NR	860	1	NR	990	0	NR
475	87	NR	605	997	NR	735	56	NR	865	1	NR	995	0	NR
480	96	NR	610	990	NR	740	47	NR	870	1	NR	1000	0	NR
485	122	NR	615	971	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-9

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.28

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	170	NR	620	938	NR	750	35	NR	880	1	NR
365	0	NR	495	234	NR	625	894	NR	755	30	NR	885	1	NR
370	0	NR	500	302	NR	630	847	NR	760	26	NR	890	1	NR
375	0	NR	505	371	NR	635	788	NR	765	22	NR	895	1	NR
380	0	NR	510	431	NR	640	728	NR	770	19	NR	900	1	NR
385	0	NR	515	482	NR	645	665	NR	775	16	NR	905	1	NR
390	0	NR	520	523	NR	650	603	NR	780	14	NR	910	0	NR
395	2	NR	525	553	NR	655	542	NR	785	12	NR	915	0	NR
400	4	NR	530	580	NR	660	484	NR	790	11	NR	920	0	NR
405	8	NR	535	603	NR	665	430	NR	795	9	NR	925	0	NR
410	18	NR	540	622	NR	670	377	NR	800	8	NR	930	0	NR
415	36	NR	545	644	NR	675	330	NR	805	7	NR	935	0	NR
420	71	NR	550	668	NR	680	289	NR	810	6	NR	940	0	NR
425	131	NR	555	693	NR	685	250	NR	815	5	NR	945	0	NR
430	215	NR	560	720	NR	690	218	NR	820	4	NR	950	0	NR
435	341	NR	565	754	NR	695	188	NR	825	4	NR	955	0	NR
440	514	NR	570	792	NR	700	161	NR	830	3	NR	960	0	NR
445	576	NR	575	832	NR	705	139	NR	835	3	NR	965	0	NR
450	358	NR	580	875	NR	710	119	NR	840	3	NR	970	0	NR
455	222	NR	585	913	NR	715	102	NR	845	2	NR	975	0	NR
460	170	NR	590	950	NR	720	88	NR	850	2	NR	980	0	NR
465	115	NR	595	977	NR	725	76	NR	855	2	NR	985	0	NR
470	88	NR	600	994	NR	730	65	NR	860	1	NR	990	0	NR
475	87	NR	605	997	NR	735	56	NR	865	1	NR	995	0	NR
480	96	NR	610	990	NR	740	47	NR	870	1	NR	1000	0	NR
485	122	NR	615	971	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-9

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.33


λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	170	NR	620	938	NR	750	35	NR	880	1	NR
365	0	NR	495	234	NR	625	894	NR	755	30	NR	885	1	NR
370	0	NR	500	302	NR	630	847	NR	760	26	NR	890	1	NR
375	0	NR	505	371	NR	635	788	NR	765	22	NR	895	1	NR
380	0	NR	510	431	NR	640	728	NR	770	19	NR	900	1	NR
385	0	NR	515	482	NR	645	665	NR	775	16	NR	905	1	NR
390	0	NR	520	523	NR	650	603	NR	780	14	NR	910	0	NR
395	2	NR	525	553	NR	655	542	NR	785	12	NR	915	0	NR
400	4	NR	530	580	NR	660	484	NR	790	11	NR	920	0	NR
405	8	NR	535	603	NR	665	430	NR	795	9	NR	925	0	NR
410	18	NR	540	622	NR	670	377	NR	800	8	NR	930	0	NR
415	36	NR	545	644	NR	675	330	NR	805	7	NR	935	0	NR
420	71	NR	550	668	NR	680	289	NR	810	6	NR	940	0	NR
425	131	NR	555	693	NR	685	250	NR	815	5	NR	945	0	NR
430	215	NR	560	720	NR	690	218	NR	820	4	NR	950	0	NR
435	341	NR	565	754	NR	695	188	NR	825	4	NR	955	0	NR
440	514	NR	570	792	NR	700	161	NR	830	3	NR	960	0	NR
445	576	NR	575	832	NR	705	139	NR	835	3	NR	965	0	NR
450	358	NR	580	875	NR	710	119	NR	840	3	NR	970	0	NR
455	222	NR	585	913	NR	715	102	NR	845	2	NR	975	0	NR
460	170	NR	590	950	NR	720	88	NR	850	2	NR	980	0	NR
465	115	NR	595	977	NR	725	76	NR	855	2	NR	985	0	NR
470	88	NR	600	994	NR	730	65	NR	860	1	NR	990	0	NR
475	87	NR	605	997	NR	735	56	NR	865	1	NR	995	0	NR
480	96	NR	610	990	NR	740	47	NR	870	1	NR	1000	0	NR
485	122	NR	615	971	NR	745	41	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-9





TM-30-18

Summary

$R_f = 81.5$
 $R_g = 99.2$
 $CIE R_a = 80.9$
 $R_9 = 6.8$




Color Vector Graphics







Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 74	CES51 = 89	CES76 = 70
CES02 = 63	CES27 = 88	CES52 = 91	CES77 = 86
CES03 = 31	CES28 = 89	CES53 = 81	CES78 = 72
CES04 = 70	CES29 = 67	CES54 = 87	CES79 = 90
CES05 = 50	CES30 = 68	CES55 = 85	CES80 = 88
CES06 = 51	CES31 = 71	CES56 = 78	CES81 = 78
CES07 = 42	CES32 = 70	CES57 = 76	CES82 = 95
CES08 = 41	CES33 = 71	CES58 = 78	CES83 = 90
CES09 = 29	CES34 = 82	CES59 = 92	CES84 = 93
CES10 = 76	CES35 = 90	CES60 = 95	CES85 = 86
CES11 = 59	CES36 = 93	CES61 = 93	CES86 = 72
CES12 = 65	CES37 = 87	CES62 = 83	CES87 = 85
CES13 = 43	CES38 = 75	CES63 = 77	CES88 = 83
CES14 = 74	CES39 = 94	CES64 = 83	CES89 = 75
CES15 = 71	CES40 = 89	CES65 = 77	CES90 = 81
CES16 = 47	CES41 = 85	CES66 = 80	CES91 = 96
CES17 = 50	CES42 = 86	CES67 = 79	CES92 = 73
CES18 = 56	CES43 = 81	CES68 = 84	CES93 = 84
CES19 = 72	CES44 = 99	CES69 = 90	CES94 = 64
CES20 = 66	CES45 = 87	CES70 = 77	CES95 = 80
CES21 = 87	CES46 = 82	CES71 = 76	CES96 = 84
CES22 = 79	CES47 = 77	CES72 = 92	CES97 = 87
CES23 = 92	CES48 = 71	CES73 = 71	CES98 = 81
CES24 = 91	CES49 = 81	CES74 = 93	CES99 = 74
CES25 = 72	CES50 = 89	CES75 = 74	



Color Rendition by Hue-Angle Bin



Measure Comparisons


(END OF REPORT)