

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066652

Luminaire Tested: **NVN-SA2D-835-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066652
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA2D-835-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1200mA 2xLight Square PACKAGE
80CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (28) 3500K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 9294.5 lumens
Efficiency: N/A
Efficacy: 86.9 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 107
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 1.8 fc
 Type III - Short - N/A

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	55.3	0.0	55.3
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	9239.2	0.0	9239.2
	% Fixture	99.4	0.0	99.4
Total	Lumens	9294.5	0.0	9294.5
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2.7	0.0
10°-20°	13.6	0.1
20°-30°	173.5	1.9
30°-40°	584.7	6.3
40°-50°	1765.7	19.0
50°-60°	3115.2	33.5
60°-70°	2744.5	29.5
70°-80°	873.6	9.4
80°-90°	21.0	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	9294.5	100.0
0°-180°	9294.5	100.0



REPORT NUMBER: P1066652


CATALOG NUMBER: NVN-SA2D-835-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	181.6	2.0			
FM	(30°-60°)	5444.1	58.6			
FH	(60°-80°)	3596.5	38.7			G2/5000
FVH	(80°-90°)	17.1	0.2			G1/100
BL	(0°-30°)	8.3	0.1	B0/110		
BM	(30°-60°)	21.4	0.2	B0/220		
BH	(60°-80°)	21.6	0.2	B0/110		G0/110
BVH	(80°-90°)	3.9	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	23.3	23.3	23.3	23.3	23.3	23.3	23.3	23.3	23.3	23.3	20.4
5°	29.1	29.1	29.1	26.2	26.2	26.2	23.3	23.3	23.3	23.3	23.3
7.5°	35.0	32.1	32.1	29.1	29.1	29.1	26.2	26.2	26.2	26.2	23.3
10°	40.8	37.9	37.9	35.0	35.0	32.1	32.1	29.1	29.1	26.2	26.2
12.5°	46.6	43.7	40.8	37.9	37.9	35.0	35.0	32.1	32.1	29.1	29.1
15°	52.5	49.6	46.6	43.7	40.8	40.8	37.9	35.0	32.1	32.1	29.1
17.5°	61.2	55.4	52.5	46.6	43.7	40.8	37.9	35.0	35.0	32.1	32.1
20°	64.1	58.3	55.4	49.6	46.6	43.7	40.8	37.9	35.0	35.0	32.1
22.5°	75.8	64.1	61.2	55.4	52.5	49.6	43.7	40.8	37.9	35.0	32.1
25°	93.3	75.8	67.0	58.3	55.4	49.6	46.6	40.8	37.9	35.0	32.1
27.5°	113.7	84.5	75.8	64.1	58.3	52.5	46.6	40.8	37.9	35.0	32.1
30°	139.9	99.1	84.5	70.0	64.1	58.3	49.6	43.7	40.8	37.9	32.1
32.5°	195.3	122.4	99.1	75.8	67.0	61.2	52.5	43.7	40.8	37.9	32.1
35°	236.1	148.7	119.5	87.4	75.8	67.0	55.4	43.7	40.8	37.9	32.1
37.5°	274.0	151.6	122.4	93.3	81.6	70.0	55.4	43.7	40.8	37.9	32.1
40°	335.2	157.4	122.4	87.4	78.7	67.0	58.3	46.6	43.7	37.9	35.0
42.5°	451.8	180.7	131.2	81.6	72.9	67.0	58.3	49.6	43.7	40.8	35.0
45°	752.0	268.2	177.8	84.5	75.8	67.0	58.3	49.6	46.6	40.8	37.9
47.5°	1279.6	466.4	276.9	87.4	78.7	67.0	58.3	46.6	43.7	40.8	35.0
50°	1638.1	597.5	349.8	102.0	87.4	75.8	61.2	46.6	43.7	40.8	37.9
52.5°	1740.1	635.4	378.9	119.5	102.0	84.5	64.1	46.6	43.7	43.7	40.8
55°	1594.4	617.9	378.9	139.9	116.6	96.2	72.9	49.6	46.6	46.6	43.7
57.5°	1355.4	571.3	361.4	151.6	128.2	102.0	78.7	52.5	49.6	49.6	46.6
60°	1116.4	480.9	326.5	169.1	142.8	116.6	90.4	64.1	61.2	58.3	52.5
62.5°	886.1	387.7	285.6	180.7	154.5	125.3	99.1	70.0	67.0	64.1	61.2
65°	667.5	338.1	265.2	189.5	160.3	131.2	102.0	72.9	70.0	70.0	67.0
67.5°	513.0	309.0	253.6	195.3	166.1	137.0	107.8	78.7	75.8	72.9	70.0
70°	405.2	285.6	239.0	192.4	166.1	139.9	110.8	84.5	78.7	75.8	70.0
72.5°	338.1	259.4	221.5	183.6	163.2	142.8	122.4	102.0	90.4	81.6	70.0
75°	282.7	233.2	201.1	166.1	151.6	139.9	125.3	110.8	96.2	81.6	67.0
77.5°	186.5	169.1	154.5	139.9	131.2	122.4	110.8	102.0	87.4	75.8	61.2
80°	78.7	72.9	75.8	75.8	75.8	75.8	72.9	72.9	64.1	55.4	43.7
82.5°	17.5	14.6	17.5	17.5	17.5	17.5	14.6	14.6	14.6	11.7	11.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4
5°	23.3	23.3	23.3	20.4	20.4	20.4	20.4	20.4	20.4	20.4	20.4
7.5°	23.3	23.3	23.3	20.4	20.4	20.4	20.4	17.5	17.5	17.5	17.5
10°	23.3	23.3	23.3	20.4	20.4	20.4	20.4	17.5	17.5	17.5	17.5
12.5°	26.2	26.2	23.3	23.3	20.4	20.4	20.4	17.5	17.5	17.5	17.5
15°	26.2	26.2	23.3	23.3	20.4	20.4	20.4	17.5	17.5	17.5	17.5
17.5°	29.1	26.2	26.2	23.3	20.4	20.4	20.4	17.5	17.5	17.5	17.5
20°	29.1	26.2	26.2	23.3	20.4	20.4	20.4	17.5	17.5	17.5	17.5
22.5°	29.1	26.2	26.2	23.3	20.4	20.4	17.5	17.5	14.6	14.6	11.7
25°	29.1	26.2	26.2	23.3	20.4	20.4	17.5	17.5	14.6	11.7	11.7
27.5°	29.1	26.2	26.2	23.3	20.4	17.5	17.5	14.6	11.7	8.7	8.7
30°	29.1	26.2	26.2	23.3	20.4	17.5	14.6	11.7	8.7	8.7	5.8
32.5°	29.1	26.2	23.3	20.4	17.5	14.6	14.6	11.7	8.7	5.8	5.8
35°	29.1	26.2	23.3	20.4	17.5	14.6	14.6	11.7	8.7	5.8	5.8
37.5°	29.1	26.2	23.3	20.4	17.5	14.6	11.7	8.7	5.8	5.8	2.9
40°	29.1	26.2	23.3	20.4	17.5	14.6	11.7	8.7	5.8	5.8	2.9
42.5°	29.1	26.2	23.3	20.4	17.5	14.6	11.7	8.7	5.8	5.8	2.9
45°	32.1	29.1	26.2	20.4	17.5	14.6	14.6	11.7	8.7	5.8	5.8
47.5°	32.1	29.1	26.2	20.4	17.5	14.6	14.6	11.7	8.7	5.8	5.8
50°	35.0	32.1	29.1	23.3	20.4	17.5	14.6	8.7	5.8	5.8	2.9
52.5°	37.9	35.0	32.1	29.1	26.2	20.4	14.6	8.7	2.9	2.9	2.9
55°	40.8	37.9	37.9	35.0	32.1	23.3	17.5	8.7	0.0	0.0	0.0
57.5°	43.7	40.8	40.8	37.9	35.0	26.2	17.5	8.7	0.0	0.0	0.0
60°	49.6	46.6	43.7	37.9	35.0	26.2	17.5	8.7	0.0	0.0	0.0
62.5°	58.3	52.5	43.7	37.9	29.1	23.3	14.6	8.7	0.0	0.0	0.0
65°	64.1	55.4	46.6	35.0	26.2	20.4	14.6	5.8	0.0	0.0	0.0
67.5°	67.0	55.4	46.6	35.0	23.3	17.5	11.7	5.8	0.0	0.0	0.0
70°	64.1	52.5	43.7	32.1	20.4	14.6	11.7	5.8	0.0	0.0	0.0
72.5°	58.3	49.6	37.9	29.1	17.5	14.6	8.7	5.8	0.0	0.0	0.0
75°	52.5	43.7	32.1	23.3	11.7	8.7	5.8	2.9	0.0	0.0	0.0
77.5°	46.6	37.9	26.2	17.5	5.8	5.8	2.9	2.9	0.0	0.0	0.0
80°	35.0	26.2	17.5	8.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	8.7	5.8	5.8	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
5°	17.5	17.5	17.5	17.5	14.6	14.6	14.6	14.6	14.6	14.6	14.6
7.5°	17.5	17.5	17.5	17.5	14.6	14.6	14.6	14.6	11.7	11.7	11.7
10°	14.6	14.6	14.6	14.6	14.6	14.6	14.6	14.6	11.7	11.7	11.7
12.5°	14.6	14.6	14.6	14.6	14.6	14.6	14.6	14.6	11.7	11.7	11.7
15°	14.6	14.6	14.6	14.6	14.6	14.6	14.6	11.7	11.7	8.7	8.7
17.5°	14.6	14.6	14.6	14.6	11.7	11.7	11.7	8.7	8.7	5.8	5.8
20°	14.6	14.6	14.6	11.7	11.7	8.7	8.7	5.8	5.8	2.9	2.9
22.5°	11.7	8.7	8.7	5.8	5.8	2.9	2.9	2.9	0.0	0.0	0.0
25°	8.7	5.8	5.8	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	5.8	2.9	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	5.8	2.9	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	17.5	14.6	14.6	14.6	14.6	14.6	14.6	14.6	14.6	14.6	14.6
5°	14.6	14.6	14.6	14.6	11.7	11.7	11.7	11.7	11.7	11.7	11.7
7.5°	11.7	11.7	11.7	11.7	11.7	11.7	8.7	8.7	8.7	8.7	8.7
10°	11.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	5.8	5.8
12.5°	11.7	8.7	8.7	8.7	5.8	5.8	5.8	5.8	5.8	2.9	2.9
15°	8.7	5.8	5.8	5.8	2.9	2.9	2.9	2.9	2.9	0.0	0.0
17.5°	5.8	2.9	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	14.6	14.6	14.6	14.6	14.6	14.6	14.6	14.6	14.6	17.5	17.5
5°	11.7	11.7	11.7	11.7	11.7	11.7	11.7	11.7	11.7	11.7	11.7
7.5°	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7
10°	5.8	5.8	5.8	5.8	5.8	5.8	2.9	2.9	2.9	2.9	2.9
12.5°	2.9	2.9	2.9	2.9	2.9	2.9	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	17.5	17.5	17.5	17.5	17.5	20.4	20.4	23.3	23.3	26.2	26.2
5°	11.7	11.7	14.6	14.6	14.6	14.6	17.5	17.5	17.5	20.4	20.4
7.5°	8.7	8.7	8.7	8.7	8.7	11.7	11.7	14.6	14.6	17.5	17.5
10°	2.9	2.9	5.8	5.8	5.8	5.8	8.7	8.7	8.7	11.7	14.6
12.5°	0.0	0.0	2.9	2.9	2.9	2.9	5.8	5.8	5.8	8.7	11.7
15°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	5.8	8.7
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	5.8
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	29.1	29.1	32.1	32.1	35.0	35.0	37.9	37.9	37.9	37.9	37.9
5°	23.3	23.3	26.2	29.1	29.1	32.1	35.0	35.0	35.0	35.0	35.0
7.5°	20.4	20.4	23.3	26.2	26.2	29.1	32.1	32.1	35.0	35.0	35.0
10°	14.6	17.5	20.4	23.3	23.3	26.2	29.1	29.1	32.1	32.1	32.1
12.5°	11.7	14.6	17.5	20.4	20.4	23.3	26.2	26.2	29.1	29.1	32.1
15°	8.7	11.7	14.6	17.5	17.5	20.4	23.3	23.3	26.2	29.1	32.1
17.5°	5.8	8.7	11.7	14.6	14.6	17.5	20.4	23.3	26.2	26.2	29.1
20°	5.8	5.8	8.7	11.7	11.7	14.6	17.5	20.4	23.3	23.3	26.2
22.5°	2.9	2.9	5.8	8.7	8.7	11.7	14.6	17.5	20.4	20.4	23.3
25°	0.0	0.0	2.9	5.8	5.8	8.7	11.7	11.7	14.6	14.6	17.5
27.5°	0.0	0.0	2.9	2.9	5.8	5.8	8.7	8.7	11.7	11.7	14.6
30°	0.0	0.0	2.9	2.9	5.8	5.8	8.7	8.7	11.7	11.7	11.7
32.5°	0.0	0.0	0.0	2.9	2.9	2.9	5.8	5.8	8.7	8.7	11.7
35°	0.0	0.0	0.0	2.9	2.9	2.9	5.8	5.8	8.7	8.7	8.7
37.5°	0.0	0.0	0.0	2.9	2.9	2.9	5.8	5.8	5.8	5.8	8.7
40°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
45°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
50°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
55°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9
75°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
80°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	5.8	5.8	5.8
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	5.8
85°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	2.9	2.9	2.9	2.9	2.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8	37.9	37.9
5°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	35.0	35.0
7.5°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	35.0	35.0
10°	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0
12.5°	32.1	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0
15°	32.1	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0
17.5°	29.1	32.1	32.1	32.1	35.0	35.0	35.0	35.0	35.0	35.0	35.0
20°	26.2	29.1	29.1	29.1	32.1	32.1	32.1	32.1	35.0	35.0	35.0
22.5°	23.3	26.2	26.2	26.2	29.1	29.1	29.1	29.1	32.1	32.1	32.1
25°	20.4	20.4	23.3	23.3	26.2	26.2	26.2	26.2	26.2	26.2	26.2
27.5°	14.6	17.5	17.5	17.5	20.4	20.4	20.4	20.4	23.3	23.3	23.3
30°	14.6	14.6	14.6	14.6	17.5	17.5	17.5	17.5	20.4	20.4	20.4
32.5°	11.7	14.6	14.6	14.6	17.5	17.5	17.5	17.5	20.4	20.4	20.4
35°	11.7	11.7	11.7	11.7	14.6	14.6	14.6	14.6	17.5	17.5	17.5
37.5°	8.7	11.7	11.7	11.7	14.6	14.6	14.6	14.6	17.5	17.5	17.5
40°	8.7	8.7	8.7	8.7	11.7	11.7	11.7	11.7	14.6	14.6	14.6
42.5°	8.7	8.7	8.7	8.7	11.7	11.7	11.7	11.7	14.6	14.6	14.6
45°	8.7	8.7	8.7	8.7	11.7	11.7	11.7	11.7	14.6	14.6	14.6
47.5°	8.7	8.7	8.7	8.7	11.7	11.7	11.7	11.7	14.6	14.6	14.6
50°	8.7	8.7	8.7	8.7	11.7	11.7	11.7	11.7	14.6	14.6	14.6
52.5°	5.8	5.8	5.8	5.8	8.7	8.7	8.7	8.7	11.7	11.7	11.7
55°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	8.7	8.7	8.7
57.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	8.7	8.7	8.7
60°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
62.5°	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9
65°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	2.9	2.9
67.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
70°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
72.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
75°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
77.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
80°	8.7	8.7	8.7	8.7	8.7	5.8	5.8	5.8	5.8	5.8	5.8
82.5°	5.8	8.7	8.7	8.7	8.7	5.8	5.8	5.8	5.8	5.8	5.8
85°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
87.5°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	37.9	37.9	35.0	35.0	35.0	35.0	35.0	35.0	35.0	37.9	37.9
5°	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	37.9	37.9
7.5°	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	37.9	37.9
10°	35.0	35.0	35.0	35.0	32.1	32.1	35.0	35.0	35.0	37.9	37.9
12.5°	35.0	35.0	35.0	35.0	32.1	32.1	35.0	35.0	37.9	37.9	40.8
15°	35.0	35.0	32.1	32.1	32.1	32.1	35.0	35.0	37.9	37.9	40.8
17.5°	35.0	35.0	32.1	32.1	32.1	32.1	35.0	35.0	37.9	37.9	40.8
20°	35.0	35.0	32.1	32.1	32.1	32.1	32.1	32.1	35.0	37.9	37.9
22.5°	32.1	32.1	32.1	32.1	29.1	29.1	32.1	32.1	35.0	37.9	37.9
25°	26.2	29.1	29.1	29.1	29.1	29.1	32.1	32.1	35.0	37.9	37.9
27.5°	23.3	26.2	26.2	26.2	26.2	29.1	29.1	32.1	35.0	37.9	37.9
30°	20.4	23.3	23.3	23.3	26.2	29.1	29.1	32.1	35.0	37.9	37.9
32.5°	20.4	23.3	23.3	23.3	26.2	26.2	29.1	29.1	32.1	35.0	37.9
35°	20.4	20.4	23.3	23.3	23.3	26.2	26.2	29.1	32.1	35.0	37.9
37.5°	20.4	20.4	23.3	23.3	23.3	26.2	26.2	29.1	32.1	35.0	37.9
40°	17.5	20.4	20.4	23.3	23.3	26.2	26.2	29.1	32.1	37.9	40.8
42.5°	17.5	17.5	20.4	20.4	23.3	26.2	26.2	29.1	32.1	37.9	40.8
45°	17.5	20.4	20.4	23.3	26.2	29.1	29.1	32.1	35.0	37.9	40.8
47.5°	17.5	20.4	20.4	23.3	29.1	29.1	32.1	32.1	35.0	37.9	40.8
50°	17.5	20.4	20.4	23.3	32.1	32.1	32.1	32.1	35.0	37.9	40.8
52.5°	14.6	17.5	17.5	20.4	26.2	29.1	32.1	35.0	37.9	40.8	43.7
55°	11.7	14.6	14.6	17.5	23.3	26.2	32.1	37.9	40.8	43.7	46.6
57.5°	11.7	11.7	14.6	14.6	20.4	26.2	35.0	40.8	43.7	46.6	49.6
60°	8.7	8.7	11.7	11.7	17.5	23.3	32.1	40.8	43.7	49.6	52.5
62.5°	5.8	8.7	8.7	11.7	14.6	23.3	32.1	40.8	46.6	52.5	55.4
65°	5.8	5.8	8.7	8.7	14.6	20.4	29.1	35.0	43.7	52.5	61.2
67.5°	8.7	8.7	11.7	11.7	14.6	20.4	29.1	35.0	43.7	55.4	64.1
70°	8.7	8.7	11.7	11.7	17.5	23.3	29.1	35.0	43.7	55.4	64.1
72.5°	8.7	8.7	11.7	11.7	17.5	20.4	26.2	32.1	40.8	49.6	58.3
75°	5.8	8.7	8.7	8.7	14.6	17.5	23.3	29.1	37.9	46.6	55.4
77.5°	5.8	5.8	5.8	5.8	11.7	14.6	20.4	23.3	32.1	40.8	49.6
80°	5.8	5.8	5.8	5.8	8.7	11.7	17.5	20.4	29.1	37.9	46.6
82.5°	5.8	5.8	2.9	2.9	5.8	8.7	11.7	14.6	23.3	29.1	37.9
85°	5.8	5.8	2.9	2.9	2.9	5.8	5.8	8.7	11.7	14.6	17.5
87.5°	5.8	5.8	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	37.9	37.9	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8
5°	37.9	40.8	40.8	43.7	43.7	43.7	46.6	46.6	46.6	46.6	46.6
7.5°	37.9	40.8	40.8	43.7	43.7	43.7	46.6	46.6	46.6	49.6	49.6
10°	37.9	40.8	40.8	43.7	43.7	46.6	49.6	49.6	52.5	52.5	52.5
12.5°	40.8	43.7	43.7	46.6	46.6	49.6	52.5	52.5	55.4	58.3	58.3
15°	40.8	43.7	46.6	46.6	49.6	52.5	55.4	55.4	58.3	61.2	64.1
17.5°	40.8	43.7	46.6	46.6	49.6	52.5	58.3	61.2	64.1	70.0	72.9
20°	40.8	43.7	46.6	46.6	49.6	55.4	58.3	64.1	67.0	72.9	78.7
22.5°	40.8	43.7	46.6	49.6	52.5	58.3	64.1	67.0	72.9	81.6	87.4
25°	40.8	43.7	46.6	49.6	52.5	58.3	64.1	70.0	75.8	87.4	99.1
27.5°	40.8	43.7	49.6	52.5	55.4	61.2	70.0	75.8	81.6	102.0	122.4
30°	40.8	43.7	49.6	52.5	55.4	64.1	72.9	78.7	87.4	122.4	154.5
32.5°	40.8	46.6	49.6	55.4	58.3	67.0	78.7	87.4	96.2	145.7	192.4
35°	40.8	46.6	49.6	55.4	58.3	70.0	81.6	93.3	104.9	177.8	250.7
37.5°	40.8	46.6	49.6	55.4	58.3	75.8	93.3	110.8	128.2	204.0	279.8
40°	43.7	49.6	52.5	58.3	61.2	78.7	96.2	113.7	131.2	206.9	282.7
42.5°	43.7	49.6	52.5	58.3	61.2	75.8	93.3	107.8	122.4	206.9	291.5
45°	43.7	49.6	55.4	58.3	64.1	78.7	93.3	104.9	119.5	227.4	332.3
47.5°	43.7	49.6	55.4	58.3	64.1	78.7	93.3	107.8	122.4	300.2	475.1
50°	43.7	49.6	55.4	58.3	64.1	81.6	99.1	116.6	134.1	448.9	763.7
52.5°	46.6	49.6	55.4	58.3	61.2	81.6	102.0	122.4	142.8	583.0	1020.2
55°	49.6	52.5	55.4	58.3	61.2	87.4	113.7	139.9	166.1	626.7	1084.3
57.5°	52.5	55.4	58.3	58.3	61.2	93.3	128.2	160.3	192.4	623.8	1052.2
60°	55.4	58.3	61.2	64.1	67.0	99.1	134.1	166.1	198.2	565.5	932.7
62.5°	61.2	67.0	72.9	75.8	81.6	113.7	142.8	174.9	204.0	463.4	719.9
65°	70.0	75.8	78.7	84.5	87.4	116.6	148.7	177.8	206.9	384.7	559.6
67.5°	72.9	78.7	81.6	87.4	90.4	119.5	148.7	177.8	206.9	326.5	443.0
70°	72.9	78.7	84.5	87.4	93.3	122.4	148.7	177.8	204.0	282.7	361.4
72.5°	67.0	75.8	81.6	90.4	96.2	122.4	145.7	172.0	195.3	250.7	306.0
75°	64.1	75.8	84.5	96.2	104.9	122.4	142.8	160.3	177.8	218.6	259.4
77.5°	58.3	72.9	87.4	102.0	116.6	128.2	137.0	148.7	157.4	183.6	209.9
80°	55.4	70.0	84.5	99.1	113.7	119.5	122.4	128.2	131.2	134.1	137.0
82.5°	43.7	55.4	67.0	75.8	87.4	81.6	78.7	72.9	67.0	64.1	61.2
85°	20.4	23.3	23.3	26.2	26.2	26.2	23.3	23.3	20.4	17.5	14.6
87.5°	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	40.8	40.8	40.8	40.8	37.9	37.9	37.9	37.9	35.0	35.0	35.0
5°	46.6	46.6	46.6	46.6	43.7	43.7	43.7	43.7	40.8	40.8	40.8
7.5°	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
10°	55.4	55.4	55.4	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3
12.5°	61.2	61.2	64.1	64.1	67.0	67.0	70.0	70.0	72.9	72.9	72.9
15°	67.0	70.0	72.9	75.8	75.8	78.7	81.6	84.5	87.4	90.4	93.3
17.5°	78.7	81.6	87.4	93.3	99.1	104.9	113.7	125.3	134.1	142.8	154.5
20°	87.4	96.2	113.7	134.1	151.6	169.1	212.8	256.5	300.2	343.9	387.7
22.5°	104.9	122.4	180.7	241.9	300.2	358.5	495.5	632.5	766.6	903.6	1026.0
25°	139.9	177.8	311.9	446.0	577.1	711.2	956.0	1203.8	1448.6	1693.5	1920.8
27.5°	192.4	262.3	480.9	702.5	921.1	1139.7	1495.3	1853.8	2209.4	2567.9	2885.6
30°	268.2	381.8	708.3	1037.7	1364.1	1690.6	2139.4	2591.2	3040.1	3489.0	3780.4
32.5°	364.3	533.4	947.3	1361.2	1775.1	2189.0	2684.5	3180.0	3672.6	4168.1	4477.1
35°	466.4	682.1	1180.5	1681.8	2180.2	2681.6	3203.3	3725.1	4246.8	4768.6	5147.5
37.5°	524.7	769.5	1361.2	1952.9	2541.7	3133.4	3704.7	4278.9	4850.2	5421.5	5882.0
40°	580.0	874.4	1556.5	2238.5	2920.6	3602.6	4270.1	4937.6	5605.1	6272.6	6864.3
42.5°	661.7	1031.8	1827.6	2623.3	3416.1	4211.8	5089.2	5969.4	6846.8	7724.1	8633.5
45°	830.7	1329.1	2361.0	3392.8	4421.7	5453.5	6698.1	7945.6	9190.2	10437.8	11603.7
47.5°	1238.8	1999.5	3407.4	4815.2	6223.0	7630.8	9064.9	10499.0	11933.0	13367.1	14754.5
50°	1917.9	3069.2	4829.8	6590.3	8347.9	10108.4	11539.5	12970.7	14398.9	15830.1	17208.8
52.5°	2556.2	4092.3	5984.0	7878.6	9770.3	11664.9	12932.8	14200.7	15468.6	16736.6	18071.5
55°	2774.9	4462.5	6377.5	8295.4	10210.4	12128.3	13349.6	14573.8	15795.1	17016.4	18400.9
57.5°	2582.5	4112.7	6042.3	7971.9	9898.5	11828.1	13192.2	14559.2	15923.3	17290.4	18774.0
60°	2162.8	3389.9	5415.6	7444.3	9470.1	11495.8	13034.8	14573.8	16112.8	17651.8	19132.5
62.5°	1713.9	2704.9	4850.2	6995.4	9140.7	11286.0	12851.2	14419.3	15984.6	17549.8	18686.5
65°	1314.6	2069.5	4179.8	6293.0	8403.3	10516.5	11799.0	13084.4	14366.9	15652.3	16439.3
67.5°	976.4	1509.8	3354.9	5202.8	7047.9	8892.9	9837.3	10784.6	11729.0	12676.3	13288.4
70°	719.9	1075.5	2331.8	3588.1	4841.4	6097.7	6963.4	7829.1	8691.8	9557.5	10192.9
72.5°	498.4	687.9	1439.9	2194.8	2946.8	3698.8	4576.2	5453.5	6327.9	7205.3	7928.2
75°	341.0	422.6	775.3	1128.0	1480.7	1833.4	2498.0	3162.5	3827.1	4491.6	4873.5
77.5°	253.6	297.3	402.2	510.1	615.0	719.9	848.2	976.4	1104.7	1232.9	1399.1
80°	139.9	139.9	154.5	166.1	180.7	192.4	227.4	265.2	300.2	338.1	384.7
82.5°	64.1	67.0	72.9	78.7	81.6	87.4	93.3	99.1	104.9	110.8	110.8
85°	17.5	20.4	20.4	17.5	17.5	14.6	14.6	17.5	17.5	17.5	17.5
87.5°	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	35.0	32.1	32.1	32.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1
5°	40.8	40.8	40.8	40.8	37.9	37.9	37.9	37.9	37.9	35.0	35.0
7.5°	49.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	43.7	43.7
10°	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	55.4	55.4
12.5°	72.9	72.9	72.9	72.9	75.8	75.8	72.9	72.9	72.9	70.0	70.0
15°	96.2	99.1	102.0	102.0	104.9	104.9	104.9	102.0	102.0	99.1	96.2
17.5°	163.2	172.0	183.6	195.3	206.9	215.7	215.7	209.9	204.0	198.2	192.4
20°	434.3	478.0	524.7	571.3	620.8	655.8	632.5	615.0	597.5	577.1	559.6
22.5°	1151.3	1273.8	1399.1	1486.5	1574.0	1635.2	1585.6	1489.4	1393.3	1300.0	1203.8
25°	2148.2	2372.6	2600.0	2693.2	2789.4	2859.4	2827.3	2681.6	2535.8	2393.0	2247.3
27.5°	3203.3	3518.1	3835.8	3917.4	3999.1	4060.3	4048.6	3859.1	3669.7	3480.2	3290.8
30°	4071.9	4363.4	4654.9	4736.5	4818.1	4873.5	4812.3	4622.8	4433.4	4243.9	4054.4
32.5°	4789.0	5097.9	5409.8	5517.6	5625.5	5698.4	5625.5	5398.1	5170.8	4946.4	4719.0
35°	5526.4	5902.4	6281.3	6418.3	6555.3	6642.7	6520.3	6240.5	5960.7	5683.8	5404.0
37.5°	6342.5	6800.1	7260.7	7447.2	7636.7	7767.8	7674.6	7324.8	6972.1	6622.3	6269.7
40°	7458.9	8050.6	8645.2	8980.4	9312.7	9548.8	9382.6	8977.5	8569.4	8164.2	7756.2
42.5°	9545.8	10455.3	11364.7	11845.6	12323.6	12670.5	12483.9	11985.5	11487.1	10988.7	10490.2
45°	12769.6	13932.6	15098.5	15800.9	16506.3	17025.1	16809.4	16182.8	15553.2	14926.5	14299.8
47.5°	16142.0	17529.4	18916.8	19476.4	20039.0	20476.2	20423.7	19642.6	18861.4	18083.2	17302.0
50°	18590.4	19969.0	21347.7	21828.7	22312.5	22671.0	22536.9	21543.0	20546.2	19552.2	18555.4
52.5°	19406.5	20738.5	22073.5	22647.7	23221.9	23650.4	23487.2	22367.9	21248.6	20132.3	19013.0
55°	19785.4	21169.9	22554.4	23254.0	23956.4	24469.4	24233.3	23006.2	21776.2	20549.1	19319.0
57.5°	20257.6	21741.2	23224.8	23991.4	24758.0	25311.8	24997.0	23726.2	22455.3	21187.4	19916.6
60°	20613.2	22091.0	23571.7	24186.7	24804.6	25236.0	24932.9	23697.0	22458.2	21222.4	19986.5
62.5°	19826.2	20963.0	22099.7	22557.3	23015.0	23347.2	23175.3	22003.5	20831.8	19660.1	18488.3
65°	17229.2	18016.1	18806.0	19115.0	19421.1	19657.2	19604.7	18616.6	17628.5	16643.3	15655.2
67.5°	13903.4	14515.5	15130.5	15567.7	16007.9	16348.9	16311.0	15410.3	14509.7	13609.0	12708.4
70°	10831.3	11466.7	12102.1	12653.0	13206.8	13635.3	13579.9	12743.3	11903.9	11067.4	10227.9
72.5°	8653.9	9376.8	10099.6	10414.4	10729.2	10950.8	10787.5	10155.0	9519.6	8887.1	8251.7
75°	5255.3	5634.2	6016.1	6013.2	6013.2	5978.2	5814.9	5453.5	5092.1	4730.7	4369.2
77.5°	1565.2	1731.4	1897.5	2057.8	2221.0	2343.5	2311.4	2121.9	1929.6	1740.1	1547.7
80°	431.4	475.1	521.7	542.1	562.5	588.8	655.8	609.2	562.5	518.8	472.2
82.5°	110.8	110.8	110.8	107.8	104.9	99.1	90.4	84.5	78.7	72.9	67.0
85°	17.5	14.6	14.6	14.6	11.7	11.7	11.7	11.7	8.7	8.7	5.8
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2
2.5°	29.1	29.1	26.2	26.2	26.2	26.2	26.2	26.2	26.2	26.2	23.3
5°	35.0	35.0	32.1	32.1	32.1	32.1	32.1	32.1	32.1	32.1	29.1
7.5°	43.7	43.7	40.8	40.8	40.8	40.8	37.9	37.9	37.9	37.9	35.0
10°	55.4	52.5	52.5	49.6	49.6	49.6	46.6	46.6	46.6	43.7	43.7
12.5°	70.0	67.0	67.0	64.1	61.2	61.2	58.3	55.4	52.5	52.5	49.6
15°	93.3	90.4	87.4	84.5	81.6	75.8	72.9	67.0	64.1	61.2	58.3
17.5°	177.8	163.2	148.7	134.1	122.4	110.8	99.1	87.4	81.6	75.8	70.0
20°	495.5	428.5	364.3	300.2	259.4	218.6	177.8	137.0	119.5	104.9	87.4
22.5°	1072.6	938.6	807.4	673.3	565.5	460.5	352.7	244.8	204.0	166.1	125.3
25°	1993.7	1737.2	1483.6	1227.1	1023.1	819.0	615.0	411.0	335.2	259.4	183.6
27.5°	2958.5	2626.2	2293.9	1961.6	1638.1	1311.6	985.2	661.7	530.5	402.2	271.1
30°	3701.7	3349.1	2999.3	2646.6	2238.5	1830.5	1419.5	1011.4	804.5	597.5	387.7
32.5°	4340.1	3958.2	3579.3	3197.5	2725.3	2253.1	1780.9	1308.7	1049.3	789.9	527.6
35°	4972.6	4538.3	4106.9	3672.6	3165.4	2658.3	2151.1	1643.9	1314.6	985.2	652.9
37.5°	5742.1	5211.6	4684.0	4156.5	3634.7	3115.9	2594.1	2072.4	1652.7	1235.9	816.1
40°	7082.9	6406.6	5733.3	5057.1	4447.9	3841.7	3232.5	2623.3	2095.7	1568.1	1037.7
42.5°	9642.0	8793.8	7948.6	7100.4	6258.0	5415.6	4570.3	3728.0	2976.0	2226.9	1474.9
45°	13212.6	12125.4	11041.1	9953.9	8916.3	7881.5	6843.9	5806.2	4663.6	3521.0	2375.5
47.5°	16112.8	14920.7	13731.4	12539.3	11388.0	10239.6	9088.2	7936.9	6473.7	5013.4	3550.2
50°	17421.5	16284.8	15150.9	14014.2	12859.9	11702.8	10545.6	9391.4	7712.5	6036.5	4357.6
52.5°	17861.7	16707.4	15556.1	14401.8	13256.3	12110.8	10965.3	9819.8	8073.9	6330.9	4584.9
55°	18103.6	16885.2	15669.8	14451.4	13218.4	11982.6	10746.7	9513.8	7776.6	6042.3	4305.1
57.5°	18593.3	17267.0	15943.7	14617.5	13212.6	11807.7	10399.9	8995.0	7281.1	5567.2	3853.3
60°	18683.6	17377.8	16074.9	14772.0	13218.4	11664.9	10108.4	8554.8	6852.6	5153.3	3451.1
62.5°	17398.2	16308.1	15220.9	14130.8	12574.3	11017.8	9458.4	7901.9	6272.6	4643.2	3010.9
65°	14713.7	13772.2	12833.7	11892.2	10621.4	9353.5	8082.6	6811.8	5357.3	3905.8	2451.3
67.5°	11787.3	10866.2	9948.1	9027.0	8071.0	7117.8	6161.8	5205.8	4083.6	2961.4	1839.2
70°	9344.7	8458.6	7575.5	6689.4	5844.1	4995.9	4147.7	3302.4	2605.8	1912.1	1215.5
72.5°	7406.4	6558.2	5712.9	4864.7	4098.2	3331.6	2565.0	1798.4	1451.6	1107.6	760.8
75°	3929.1	3489.0	3051.8	2611.6	2180.2	1745.9	1311.6	880.3	743.3	606.3	466.4
77.5°	1355.4	1163.0	973.5	781.2	650.0	518.8	387.7	256.5	241.9	230.3	215.7
80°	411.0	349.8	288.6	227.4	201.1	174.9	148.7	122.4	113.7	104.9	93.3
82.5°	64.1	58.3	55.4	49.6	46.6	46.6	43.7	40.8	35.0	32.1	26.2
85°	5.8	2.9	2.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066652
 CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	26.2	26.2
2.5°	23.3	23.3
5°	29.1	29.1
7.5°	35.0	35.0
10°	40.8	40.8
12.5°	46.6	46.6
15°	55.4	52.5
17.5°	64.1	61.2
20°	70.0	64.1
22.5°	84.5	72.9
25°	107.8	90.4
27.5°	139.9	110.8
30°	180.7	139.9
32.5°	268.2	195.3
35°	323.5	236.1
37.5°	396.4	274.0
40°	510.1	332.3
42.5°	722.9	451.8
45°	1232.9	749.1
47.5°	2089.9	1276.7
50°	2678.7	1638.1
52.5°	2841.9	1737.2
55°	2570.8	1594.4
57.5°	2139.4	1355.4
60°	1751.8	1116.4
62.5°	1381.6	883.2
65°	996.8	667.5
67.5°	717.0	513.0
70°	521.7	402.2
72.5°	413.9	335.2
75°	329.4	279.8
77.5°	204.0	186.5
80°	84.5	78.7
82.5°	20.4	17.5
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066652

CATALOG NUMBER: NVN-SA2D-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-10

Test Date: 10/11/2024

Luminaire Tested: GSS-SB1A-835-U-5WQ

Data in this report applies to families of products including GSS-SB1A-835-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-10
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-835-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI
 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3411
 CIE u' : 0.2360
 CIE v' : 0.5189
 Duv: 0.0044
 CIE x: 0.4154
 CIE y: 0.4059
 CIE z: 0.1787
 Peak Wavelength (nm): 601
 Dominant Wavelength (nm): 579
 Purity: 46.51914
 Rf: 86.6
 Rg: 95.9

CRI (Ra): 83.5
 R1: 81.1
 R2: 88.9
 R3: 97.2
 R4: 83.8
 R5: 81.7
 R6: 86.9
 R7: 86.1
 R8: 62.2
 R9: 6.3
 R10: 75.4
 R11: 84.1
 R12: 69.7
 R13: 82.8
 R14: 98.5
 R15: 72.6



Test Conditions


Stabilization Time: 35M
 Operation Time: 1H 35M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-10


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-10

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-10

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.48

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.88


λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10





TM-30-18

Summary

$R_f = 86.6$
 $R_g = 95.9$
 $CIE R_a = 83.5$
 $R_9 = 6.3$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 86	CES26 = 85	CES51 = 97	CES76 = 81
CES02 = 62	CES27 = 95	CES52 = 96	CES77 = 87
CES03 = 31	CES28 = 94	CES53 = 91	CES78 = 80
CES04 = 70	CES29 = 87	CES54 = 92	CES79 = 93
CES05 = 49	CES30 = 93	CES55 = 92	CES80 = 91
CES06 = 51	CES31 = 89	CES56 = 88	CES81 = 77
CES07 = 41	CES32 = 84	CES57 = 87	CES82 = 96
CES08 = 40	CES33 = 91	CES58 = 88	CES83 = 95
CES09 = 29	CES34 = 91	CES59 = 93	CES84 = 92
CES10 = 75	CES35 = 95	CES60 = 94	CES85 = 80
CES11 = 58	CES36 = 90	CES61 = 91	CES86 = 72
CES12 = 64	CES37 = 95	CES62 = 95	CES87 = 86
CES13 = 43	CES38 = 100	CES63 = 88	CES88 = 88
CES14 = 74	CES39 = 97	CES64 = 85	CES89 = 77
CES15 = 71	CES40 = 94	CES65 = 80	CES90 = 88
CES16 = 47	CES41 = 97	CES66 = 84	CES91 = 81
CES17 = 49	CES42 = 96	CES67 = 82	CES92 = 67
CES18 = 56	CES43 = 93	CES68 = 85	CES93 = 81
CES19 = 72	CES44 = 99	CES69 = 89	CES94 = 63
CES20 = 66	CES45 = 95	CES70 = 81	CES95 = 76
CES21 = 86	CES46 = 91	CES71 = 79	CES96 = 84
CES22 = 78	CES47 = 93	CES72 = 93	CES97 = 92
CES23 = 91	CES48 = 85	CES73 = 76	CES98 = 86
CES24 = 90	CES49 = 92	CES74 = 95	CES99 = 77
CES25 = 72	CES50 = 96	CES75 = 80	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)