

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066654

Luminaire Tested: **NVN-SA3B-835-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066654
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA3B-835-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 3xLight Square PACKAGE
80CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 3500K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 10153.2 lumens
Efficiency: N/A
Efficacy: 95.6 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2

Input Watts (W): 106.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2 fc
 Type III - Short - N/A

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	60.4	0.0	60.4
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	10092.8	0.0	10092.8
	% Fixture	99.4	0.0	99.4
Total	Lumens	10153.2	0.0	10153.2
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.0	0.0
10°-20°	14.9	0.1
20°-30°	189.5	1.9
30°-40°	638.7	6.3
40°-50°	1928.8	19.0
50°-60°	3403.0	33.5
60°-70°	2998.0	29.5
70°-80°	954.3	9.4
80°-90°	23.0	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	10153.2	100.0
0°-180°	10153.2	100.0



REPORT NUMBER: P1066654


CATALOG NUMBER: NVN-SA3B-835-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	198.3	2.0			
FM	(30°-60°)	5947.1	58.6			
FH	(60°-80°)	3928.7	38.7			G2/5000
FVH	(80°-90°)	18.7	0.2			G1/100
BL	(0°-30°)	9.1	0.1	B0/110		
BM	(30°-60°)	23.4	0.2	B0/220		
BH	(60°-80°)	23.7	0.2	B0/110		G0/110
BVH	(80°-90°)	4.3	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	25.5	25.5	25.5	25.5	25.5	25.5	25.5	25.5	25.5	25.5	22.3
5°	31.8	31.8	31.8	28.7	28.7	28.7	25.5	25.5	25.5	25.5	25.5
7.5°	38.2	35.0	35.0	31.8	31.8	31.8	28.7	28.7	28.7	28.7	25.5
10°	44.6	41.4	41.4	38.2	38.2	35.0	35.0	31.8	31.8	28.7	28.7
12.5°	50.9	47.8	44.6	41.4	41.4	38.2	38.2	35.0	35.0	31.8	31.8
15°	57.3	54.1	50.9	47.8	44.6	44.6	41.4	38.2	35.0	35.0	31.8
17.5°	66.9	60.5	57.3	50.9	47.8	44.6	41.4	38.2	38.2	35.0	35.0
20°	70.0	63.7	60.5	54.1	50.9	47.8	44.6	41.4	38.2	38.2	35.0
22.5°	82.8	70.0	66.9	60.5	57.3	54.1	47.8	44.6	41.4	38.2	35.0
25°	101.9	82.8	73.2	63.7	60.5	54.1	50.9	44.6	41.4	38.2	35.0
27.5°	124.2	92.3	82.8	70.0	63.7	57.3	50.9	44.6	41.4	38.2	35.0
30°	152.8	108.3	92.3	76.4	70.0	63.7	54.1	47.8	44.6	41.4	35.0
32.5°	213.3	133.7	108.3	82.8	73.2	66.9	57.3	47.8	44.6	41.4	35.0
35°	257.9	162.4	130.5	95.5	82.8	73.2	60.5	47.8	44.6	41.4	35.0
37.5°	299.3	165.6	133.7	101.9	89.2	76.4	60.5	47.8	44.6	41.4	35.0
40°	366.2	171.9	133.7	95.5	86.0	73.2	63.7	50.9	47.8	41.4	38.2
42.5°	493.5	197.4	143.3	89.2	79.6	73.2	63.7	54.1	47.8	44.6	38.2
45°	821.5	292.9	194.2	92.3	82.8	73.2	63.7	54.1	50.9	44.6	41.4
47.5°	1397.8	509.4	302.5	95.5	86.0	73.2	63.7	50.9	47.8	44.6	38.2
50°	1789.4	652.7	382.1	111.4	95.5	82.8	66.9	50.9	47.8	44.6	41.4
52.5°	1900.9	694.1	413.9	130.5	111.4	92.3	70.0	50.9	47.8	47.8	44.6
55°	1741.7	675.0	413.9	152.8	127.4	105.1	79.6	54.1	50.9	50.9	47.8
57.5°	1480.6	624.1	394.8	165.6	140.1	111.4	86.0	57.3	54.1	54.1	50.9
60°	1219.5	525.4	356.6	184.7	156.0	127.4	98.7	70.0	66.9	63.7	57.3
62.5°	967.9	423.5	312.0	197.4	168.8	136.9	108.3	76.4	73.2	70.0	66.9
65°	729.1	369.3	289.7	207.0	175.1	143.3	111.4	79.6	76.4	76.4	73.2
67.5°	560.4	337.5	277.0	213.3	181.5	149.6	117.8	86.0	82.8	79.6	76.4
70°	442.6	312.0	261.1	210.1	181.5	152.8	121.0	92.3	86.0	82.8	76.4
72.5°	369.3	283.4	242.0	200.6	178.3	156.0	133.7	111.4	98.7	89.2	76.4
75°	308.9	254.7	219.7	181.5	165.6	152.8	136.9	121.0	105.1	89.2	73.2
77.5°	203.8	184.7	168.8	152.8	143.3	133.7	121.0	111.4	95.5	82.8	66.9
80°	86.0	79.6	82.8	82.8	82.8	82.8	79.6	79.6	70.0	60.5	47.8
82.5°	19.1	15.9	19.1	19.1	19.1	19.1	15.9	15.9	15.9	12.7	12.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3
5°	25.5	25.5	25.5	22.3	22.3	22.3	22.3	22.3	22.3	22.3	22.3
7.5°	25.5	25.5	25.5	22.3	22.3	22.3	22.3	19.1	19.1	19.1	19.1
10°	25.5	25.5	25.5	22.3	22.3	22.3	22.3	19.1	19.1	19.1	19.1
12.5°	28.7	28.7	25.5	25.5	22.3	22.3	22.3	19.1	19.1	19.1	19.1
15°	28.7	28.7	25.5	25.5	22.3	22.3	22.3	19.1	19.1	19.1	19.1
17.5°	31.8	28.7	28.7	25.5	22.3	22.3	22.3	19.1	19.1	19.1	19.1
20°	31.8	28.7	28.7	25.5	22.3	22.3	22.3	19.1	19.1	19.1	19.1
22.5°	31.8	28.7	28.7	25.5	22.3	22.3	19.1	19.1	15.9	15.9	12.7
25°	31.8	28.7	28.7	25.5	22.3	22.3	19.1	19.1	15.9	12.7	12.7
27.5°	31.8	28.7	28.7	25.5	22.3	19.1	19.1	15.9	12.7	9.6	9.6
30°	31.8	28.7	28.7	25.5	22.3	19.1	15.9	12.7	9.6	9.6	6.4
32.5°	31.8	28.7	25.5	22.3	19.1	15.9	15.9	12.7	9.6	6.4	6.4
35°	31.8	28.7	25.5	22.3	19.1	15.9	15.9	12.7	9.6	6.4	6.4
37.5°	31.8	28.7	25.5	22.3	19.1	15.9	12.7	9.6	6.4	6.4	3.2
40°	31.8	28.7	25.5	22.3	19.1	15.9	12.7	9.6	6.4	6.4	3.2
42.5°	31.8	28.7	25.5	22.3	19.1	15.9	12.7	9.6	6.4	6.4	3.2
45°	35.0	31.8	28.7	22.3	19.1	15.9	15.9	12.7	9.6	6.4	6.4
47.5°	35.0	31.8	28.7	22.3	19.1	15.9	15.9	12.7	9.6	6.4	6.4
50°	38.2	35.0	31.8	25.5	22.3	19.1	15.9	9.6	6.4	6.4	3.2
52.5°	41.4	38.2	35.0	31.8	28.7	22.3	15.9	9.6	3.2	3.2	3.2
55°	44.6	41.4	41.4	38.2	35.0	25.5	19.1	9.6	0.0	0.0	0.0
57.5°	47.8	44.6	44.6	41.4	38.2	28.7	19.1	9.6	0.0	0.0	0.0
60°	54.1	50.9	47.8	41.4	38.2	28.7	19.1	9.6	0.0	0.0	0.0
62.5°	63.7	57.3	47.8	41.4	31.8	25.5	15.9	9.6	0.0	0.0	0.0
65°	70.0	60.5	50.9	38.2	28.7	22.3	15.9	6.4	0.0	0.0	0.0
67.5°	73.2	60.5	50.9	38.2	25.5	19.1	12.7	6.4	0.0	0.0	0.0
70°	70.0	57.3	47.8	35.0	22.3	15.9	12.7	6.4	0.0	0.0	0.0
72.5°	63.7	54.1	41.4	31.8	19.1	15.9	9.6	6.4	0.0	0.0	0.0
75°	57.3	47.8	35.0	25.5	12.7	9.6	6.4	3.2	0.0	0.0	0.0
77.5°	50.9	41.4	28.7	19.1	6.4	6.4	3.2	3.2	0.0	0.0	0.0
80°	38.2	28.7	19.1	9.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	9.6	6.4	6.4	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1
5°	19.1	19.1	19.1	19.1	15.9	15.9	15.9	15.9	15.9	15.9	15.9
7.5°	19.1	19.1	19.1	19.1	15.9	15.9	15.9	15.9	12.7	12.7	12.7
10°	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	12.7	12.7	12.7
12.5°	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	12.7	12.7	12.7
15°	15.9	15.9	15.9	15.9	15.9	15.9	15.9	12.7	12.7	9.6	9.6
17.5°	15.9	15.9	15.9	15.9	12.7	12.7	12.7	9.6	9.6	6.4	6.4
20°	15.9	15.9	15.9	12.7	12.7	9.6	9.6	6.4	6.4	3.2	3.2
22.5°	12.7	9.6	9.6	6.4	6.4	3.2	3.2	3.2	0.0	0.0	0.0
25°	9.6	6.4	6.4	3.2	3.2	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	6.4	3.2	3.2	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	6.4	3.2	3.2	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	19.1	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9
5°	15.9	15.9	15.9	15.9	12.7	12.7	12.7	12.7	12.7	12.7	12.7
7.5°	12.7	12.7	12.7	12.7	12.7	12.7	9.6	9.6	9.6	9.6	9.6
10°	12.7	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	6.4	6.4
12.5°	12.7	9.6	9.6	9.6	6.4	6.4	6.4	6.4	6.4	3.2	3.2
15°	9.6	6.4	6.4	6.4	3.2	3.2	3.2	3.2	3.2	0.0	0.0
17.5°	6.4	3.2	3.2	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.9	19.1	19.1
5°	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7
7.5°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
10°	6.4	6.4	6.4	6.4	6.4	6.4	3.2	3.2	3.2	3.2	3.2
12.5°	3.2	3.2	3.2	3.2	3.2	3.2	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	19.1	19.1	19.1	19.1	19.1	22.3	22.3	25.5	25.5	28.7	28.7
5°	12.7	12.7	15.9	15.9	15.9	15.9	19.1	19.1	19.1	22.3	22.3
7.5°	9.6	9.6	9.6	9.6	9.6	12.7	12.7	15.9	15.9	19.1	19.1
10°	3.2	3.2	6.4	6.4	6.4	6.4	9.6	9.6	9.6	12.7	15.9
12.5°	0.0	0.0	3.2	3.2	3.2	3.2	6.4	6.4	6.4	9.6	12.7
15°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2	6.4	9.6
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	6.4
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	31.8	31.8	35.0	35.0	38.2	38.2	41.4	41.4	41.4	41.4	41.4
5°	25.5	25.5	28.7	31.8	31.8	35.0	38.2	38.2	38.2	38.2	38.2
7.5°	22.3	22.3	25.5	28.7	28.7	31.8	35.0	35.0	38.2	38.2	38.2
10°	15.9	19.1	22.3	25.5	25.5	28.7	31.8	31.8	35.0	35.0	35.0
12.5°	12.7	15.9	19.1	22.3	22.3	25.5	28.7	28.7	31.8	31.8	35.0
15°	9.6	12.7	15.9	19.1	19.1	22.3	25.5	25.5	28.7	31.8	35.0
17.5°	6.4	9.6	12.7	15.9	15.9	19.1	22.3	25.5	28.7	28.7	31.8
20°	6.4	6.4	9.6	12.7	12.7	15.9	19.1	22.3	25.5	25.5	28.7
22.5°	3.2	3.2	6.4	9.6	9.6	12.7	15.9	19.1	22.3	22.3	25.5
25°	0.0	0.0	3.2	6.4	6.4	9.6	12.7	12.7	15.9	15.9	19.1
27.5°	0.0	0.0	3.2	3.2	6.4	6.4	9.6	9.6	12.7	12.7	15.9
30°	0.0	0.0	3.2	3.2	6.4	6.4	9.6	9.6	12.7	12.7	12.7
32.5°	0.0	0.0	0.0	3.2	3.2	3.2	6.4	6.4	9.6	9.6	12.7
35°	0.0	0.0	0.0	3.2	3.2	3.2	6.4	6.4	9.6	9.6	9.6
37.5°	0.0	0.0	0.0	3.2	3.2	3.2	6.4	6.4	6.4	6.4	9.6
40°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	6.4	6.4	6.4
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	6.4	6.4	6.4
45°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	6.4	6.4	6.4
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	6.4	6.4	6.4
50°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	6.4	6.4	6.4
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2	3.2	3.2
55°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2	3.2	3.2
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2
75°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2	3.2	3.2
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	6.4	6.4	6.4
80°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	6.4	6.4	6.4
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2	3.2	6.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2	3.2	3.2
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.2	3.2	3.2	3.2	3.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	41.4	41.4
5°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	38.2	38.2
7.5°	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	41.4	38.2	38.2
10°	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2
12.5°	35.0	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2
15°	35.0	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2
17.5°	31.8	35.0	35.0	35.0	38.2	38.2	38.2	38.2	38.2	38.2	38.2
20°	28.7	31.8	31.8	31.8	35.0	35.0	35.0	35.0	38.2	38.2	38.2
22.5°	25.5	28.7	28.7	28.7	31.8	31.8	31.8	31.8	35.0	35.0	35.0
25°	22.3	22.3	25.5	25.5	28.7	28.7	28.7	28.7	28.7	28.7	28.7
27.5°	15.9	19.1	19.1	19.1	22.3	22.3	22.3	22.3	25.5	25.5	25.5
30°	15.9	15.9	15.9	15.9	19.1	19.1	19.1	19.1	22.3	22.3	22.3
32.5°	12.7	15.9	15.9	15.9	19.1	19.1	19.1	19.1	22.3	22.3	22.3
35°	12.7	12.7	12.7	12.7	15.9	15.9	15.9	15.9	19.1	19.1	19.1
37.5°	9.6	12.7	12.7	12.7	15.9	15.9	15.9	15.9	19.1	19.1	19.1
40°	9.6	9.6	9.6	9.6	12.7	12.7	12.7	12.7	15.9	15.9	15.9
42.5°	9.6	9.6	9.6	9.6	12.7	12.7	12.7	12.7	15.9	15.9	15.9
45°	9.6	9.6	9.6	9.6	12.7	12.7	12.7	12.7	15.9	15.9	15.9
47.5°	9.6	9.6	9.6	9.6	12.7	12.7	12.7	12.7	15.9	15.9	15.9
50°	9.6	9.6	9.6	9.6	12.7	12.7	12.7	12.7	15.9	15.9	15.9
52.5°	6.4	6.4	6.4	6.4	9.6	9.6	9.6	9.6	12.7	12.7	12.7
55°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	9.6	9.6	9.6
57.5°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	9.6	9.6	9.6
60°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
62.5°	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
65°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	3.2	3.2
67.5°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
70°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
72.5°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
75°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
77.5°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
80°	9.6	9.6	9.6	9.6	9.6	6.4	6.4	6.4	6.4	6.4	6.4
82.5°	6.4	9.6	9.6	9.6	9.6	6.4	6.4	6.4	6.4	6.4	6.4
85°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
87.5°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	41.4	41.4	38.2	38.2	38.2	38.2	38.2	38.2	38.2	41.4	41.4
5°	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	41.4	41.4
7.5°	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	41.4	41.4
10°	38.2	38.2	38.2	38.2	35.0	35.0	38.2	38.2	38.2	41.4	41.4
12.5°	38.2	38.2	38.2	38.2	35.0	35.0	38.2	38.2	41.4	41.4	44.6
15°	38.2	38.2	35.0	35.0	35.0	35.0	38.2	38.2	41.4	41.4	44.6
17.5°	38.2	38.2	35.0	35.0	35.0	35.0	38.2	38.2	41.4	41.4	44.6
20°	38.2	38.2	35.0	35.0	35.0	35.0	35.0	35.0	38.2	41.4	41.4
22.5°	35.0	35.0	35.0	35.0	31.8	31.8	35.0	35.0	38.2	41.4	41.4
25°	28.7	31.8	31.8	31.8	31.8	31.8	35.0	35.0	38.2	41.4	41.4
27.5°	25.5	28.7	28.7	28.7	28.7	31.8	31.8	35.0	38.2	41.4	41.4
30°	22.3	25.5	25.5	25.5	28.7	31.8	31.8	35.0	38.2	41.4	41.4
32.5°	22.3	25.5	25.5	25.5	28.7	28.7	31.8	31.8	35.0	38.2	41.4
35°	22.3	22.3	25.5	25.5	25.5	28.7	28.7	31.8	35.0	38.2	41.4
37.5°	22.3	22.3	25.5	25.5	25.5	28.7	28.7	31.8	35.0	38.2	41.4
40°	19.1	22.3	22.3	25.5	25.5	28.7	28.7	31.8	35.0	41.4	44.6
42.5°	19.1	19.1	22.3	22.3	25.5	28.7	28.7	31.8	35.0	41.4	44.6
45°	19.1	22.3	22.3	25.5	28.7	31.8	31.8	35.0	38.2	41.4	44.6
47.5°	19.1	22.3	22.3	25.5	31.8	31.8	35.0	35.0	38.2	41.4	44.6
50°	19.1	22.3	22.3	25.5	35.0	35.0	35.0	35.0	38.2	41.4	44.6
52.5°	15.9	19.1	19.1	22.3	28.7	31.8	35.0	38.2	41.4	44.6	47.8
55°	12.7	15.9	15.9	19.1	25.5	28.7	35.0	41.4	44.6	47.8	50.9
57.5°	12.7	12.7	15.9	15.9	22.3	28.7	38.2	44.6	47.8	50.9	54.1
60°	9.6	9.6	12.7	12.7	19.1	25.5	35.0	44.6	47.8	54.1	57.3
62.5°	6.4	9.6	9.6	12.7	15.9	25.5	35.0	44.6	50.9	57.3	60.5
65°	6.4	6.4	9.6	9.6	15.9	22.3	31.8	38.2	47.8	57.3	66.9
67.5°	9.6	9.6	12.7	12.7	15.9	22.3	31.8	38.2	47.8	60.5	70.0
70°	9.6	9.6	12.7	12.7	19.1	25.5	31.8	38.2	47.8	60.5	70.0
72.5°	9.6	9.6	12.7	12.7	19.1	22.3	28.7	35.0	44.6	54.1	63.7
75°	6.4	9.6	9.6	9.6	15.9	19.1	25.5	31.8	41.4	50.9	60.5
77.5°	6.4	6.4	6.4	6.4	12.7	15.9	22.3	25.5	35.0	44.6	54.1
80°	6.4	6.4	6.4	6.4	9.6	12.7	19.1	22.3	31.8	41.4	50.9
82.5°	6.4	6.4	3.2	3.2	6.4	9.6	12.7	15.9	25.5	31.8	41.4
85°	6.4	6.4	3.2	3.2	3.2	6.4	6.4	9.6	12.7	15.9	19.1
87.5°	6.4	6.4	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	41.4	41.4	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6
5°	41.4	44.6	44.6	47.8	47.8	47.8	50.9	50.9	50.9	50.9	50.9
7.5°	41.4	44.6	44.6	47.8	47.8	47.8	50.9	50.9	50.9	54.1	54.1
10°	41.4	44.6	44.6	47.8	47.8	50.9	54.1	54.1	57.3	57.3	57.3
12.5°	44.6	47.8	47.8	50.9	50.9	54.1	57.3	57.3	60.5	63.7	63.7
15°	44.6	47.8	50.9	50.9	54.1	57.3	60.5	60.5	63.7	66.9	70.0
17.5°	44.6	47.8	50.9	50.9	54.1	57.3	63.7	66.9	70.0	76.4	79.6
20°	44.6	47.8	50.9	50.9	54.1	60.5	63.7	70.0	73.2	79.6	86.0
22.5°	44.6	47.8	50.9	54.1	57.3	63.7	70.0	73.2	79.6	89.2	95.5
25°	44.6	47.8	50.9	54.1	57.3	63.7	70.0	76.4	82.8	95.5	108.3
27.5°	44.6	47.8	54.1	57.3	60.5	66.9	76.4	82.8	89.2	111.4	133.7
30°	44.6	47.8	54.1	57.3	60.5	70.0	79.6	86.0	95.5	133.7	168.8
32.5°	44.6	50.9	54.1	60.5	63.7	73.2	86.0	95.5	105.1	159.2	210.1
35°	44.6	50.9	54.1	60.5	63.7	76.4	89.2	101.9	114.6	194.2	273.8
37.5°	44.6	50.9	54.1	60.5	63.7	82.8	101.9	121.0	140.1	222.9	305.7
40°	47.8	54.1	57.3	63.7	66.9	86.0	105.1	124.2	143.3	226.1	308.9
42.5°	47.8	54.1	57.3	63.7	66.9	82.8	101.9	117.8	133.7	226.1	318.4
45°	47.8	54.1	60.5	63.7	70.0	86.0	101.9	114.6	130.5	248.4	363.0
47.5°	47.8	54.1	60.5	63.7	70.0	86.0	101.9	117.8	133.7	328.0	519.0
50°	47.8	54.1	60.5	63.7	70.0	89.2	108.3	127.4	146.5	490.3	834.2
52.5°	50.9	54.1	60.5	63.7	66.9	89.2	111.4	133.7	156.0	636.8	1114.4
55°	54.1	57.3	60.5	63.7	66.9	95.5	124.2	152.8	181.5	684.6	1184.5
57.5°	57.3	60.5	63.7	63.7	66.9	101.9	140.1	175.1	210.1	681.4	1149.4
60°	60.5	63.7	66.9	70.0	73.2	108.3	146.5	181.5	216.5	617.7	1018.9
62.5°	66.9	73.2	79.6	82.8	89.2	124.2	156.0	191.0	222.9	506.3	786.5
65°	76.4	82.8	86.0	92.3	95.5	127.4	162.4	194.2	226.1	420.3	611.3
67.5°	79.6	86.0	89.2	95.5	98.7	130.5	162.4	194.2	226.1	356.6	484.0
70°	79.6	86.0	92.3	95.5	101.9	133.7	162.4	194.2	222.9	308.9	394.8
72.5°	73.2	82.8	89.2	98.7	105.1	133.7	159.2	187.9	213.3	273.8	334.3
75°	70.0	82.8	92.3	105.1	114.6	133.7	156.0	175.1	194.2	238.8	283.4
77.5°	63.7	79.6	95.5	111.4	127.4	140.1	149.6	162.4	171.9	200.6	229.3
80°	60.5	76.4	92.3	108.3	124.2	130.5	133.7	140.1	143.3	146.5	149.6
82.5°	47.8	60.5	73.2	82.8	95.5	89.2	86.0	79.6	73.2	70.0	66.9
85°	22.3	25.5	25.5	28.7	28.7	28.7	25.5	25.5	22.3	19.1	15.9
87.5°	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	44.6	44.6	44.6	44.6	41.4	41.4	41.4	41.4	38.2	38.2	38.2
5°	50.9	50.9	50.9	50.9	47.8	47.8	47.8	47.8	44.6	44.6	44.6
7.5°	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
10°	60.5	60.5	60.5	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
12.5°	66.9	66.9	70.0	70.0	73.2	73.2	76.4	76.4	79.6	79.6	79.6
15°	73.2	76.4	79.6	82.8	82.8	86.0	89.2	92.3	95.5	98.7	101.9
17.5°	86.0	89.2	95.5	101.9	108.3	114.6	124.2	136.9	146.5	156.0	168.8
20°	95.5	105.1	124.2	146.5	165.6	184.7	232.4	280.2	328.0	375.7	423.5
22.5°	114.6	133.7	197.4	264.3	328.0	391.6	541.3	690.9	837.4	987.1	1120.8
25°	152.8	194.2	340.7	487.2	630.4	776.9	1044.4	1315.0	1582.5	1849.9	2098.3
27.5°	210.1	286.6	525.4	767.4	1006.2	1245.0	1633.4	2025.0	2413.5	2805.1	3152.2
30°	292.9	417.1	773.7	1133.5	1490.1	1846.7	2337.1	2830.6	3321.0	3811.3	4129.7
32.5°	398.0	582.7	1034.8	1486.9	1939.1	2391.2	2932.5	3473.8	4011.9	4553.2	4890.7
35°	509.4	745.1	1289.5	1837.2	2381.7	2929.3	3499.3	4069.2	4639.1	5209.1	5623.0
37.5°	573.1	840.6	1486.9	2133.3	2776.5	3422.8	4046.9	4674.2	5298.2	5922.3	6425.4
40°	633.6	955.2	1700.3	2445.3	3190.4	3935.5	4664.6	5393.8	6122.9	6852.1	7498.4
42.5°	722.8	1127.2	1996.4	2865.6	3731.7	4600.9	5559.3	6520.9	7479.3	8437.7	9431.1
45°	907.5	1451.9	2579.1	3706.2	4830.2	5957.3	7316.9	8679.7	10039.3	11402.0	12675.7
47.5°	1353.2	2184.3	3722.1	5260.0	6797.9	8335.8	9902.4	11468.9	13035.5	14602.0	16117.6
50°	2095.1	3352.8	5276.0	7199.1	9119.1	11042.3	12605.6	14169.0	15729.2	17292.5	18798.6
52.5°	2792.4	4470.4	6536.8	8606.5	10672.9	12742.5	14127.6	15512.6	16897.7	18282.8	19741.1
55°	3031.2	4874.8	6966.7	9061.8	11153.7	13248.8	14582.9	15920.2	17254.3	18588.4	20100.8
57.5°	2821.1	4492.7	6600.5	8708.4	10813.0	12920.8	14411.0	15904.3	17394.4	18887.7	20508.4
60°	2362.6	3703.0	5915.9	8132.0	10344.9	12557.9	14239.0	15920.2	17601.4	19282.6	20900.0
62.5°	1872.2	2954.8	5298.2	7641.7	9985.2	12328.6	14038.4	15751.4	17461.3	19171.1	20412.9
65°	1436.0	2260.7	4565.9	6874.3	9179.6	11488.0	12889.0	14293.2	15694.1	17098.3	17958.0
67.5°	1066.7	1649.3	3664.8	5683.5	7699.0	9714.5	10746.1	11781.0	12812.6	13847.4	14516.0
70°	786.5	1174.9	2547.2	3919.6	5288.7	6661.0	7606.7	8552.3	9494.8	10440.5	11134.6
72.5°	544.5	751.4	1572.9	2397.6	3219.1	4040.5	4998.9	5957.3	6912.6	7870.9	8660.6
75°	372.5	461.7	847.0	1232.2	1617.5	2002.8	2728.7	3454.7	4180.6	4906.6	5323.7
77.5°	277.0	324.8	439.4	557.2	671.8	786.5	926.6	1066.7	1206.8	1346.8	1528.3
80°	152.8	152.8	168.8	181.5	197.4	210.1	248.4	289.7	328.0	369.3	420.3
82.5°	70.0	73.2	79.6	86.0	89.2	95.5	101.9	108.3	114.6	121.0	121.0
85°	19.1	22.3	22.3	19.1	19.1	15.9	15.9	19.1	19.1	19.1	19.1
87.5°	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	38.2	35.0	35.0	35.0	31.8	31.8	31.8	31.8	31.8	31.8	31.8
5°	44.6	44.6	44.6	44.6	41.4	41.4	41.4	41.4	41.4	38.2	38.2
7.5°	54.1	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	47.8	47.8
10°	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	60.5	60.5
12.5°	79.6	79.6	79.6	79.6	82.8	82.8	79.6	79.6	79.6	76.4	76.4
15°	105.1	108.3	111.4	111.4	114.6	114.6	114.6	111.4	111.4	108.3	105.1
17.5°	178.3	187.9	200.6	213.3	226.1	235.6	235.6	229.3	222.9	216.5	210.1
20°	474.4	522.2	573.1	624.1	678.2	716.4	690.9	671.8	652.7	630.4	611.3
22.5°	1257.7	1391.4	1528.3	1623.9	1719.4	1786.2	1732.1	1627.0	1522.0	1420.1	1315.0
25°	2346.6	2591.8	2840.2	2942.1	3047.1	3123.5	3088.5	2929.3	2770.1	2614.1	2454.9
27.5°	3499.3	3843.1	4190.2	4279.4	4368.5	4435.4	4422.6	4215.7	4008.7	3801.7	3594.8
30°	4448.1	4766.5	5084.9	5174.1	5263.2	5323.7	5256.9	5049.9	4842.9	4636.0	4429.0
32.5°	5231.4	5568.9	5909.6	6027.4	6145.2	6224.8	6145.2	5896.8	5648.5	5403.3	5155.0
35°	6036.9	6447.7	6861.6	7011.3	7160.9	7256.4	7122.7	6817.0	6511.4	6208.9	5903.2
37.5°	6928.5	7428.4	7931.4	8135.2	8342.2	8485.5	8383.6	8001.5	7616.2	7234.1	6848.9
40°	8148.0	8794.3	9443.9	9810.0	10173.0	10430.9	10249.4	9806.8	9361.1	8918.5	8472.7
42.5°	10427.7	11421.2	12414.6	12939.9	13462.1	13841.0	13637.2	13092.8	12548.3	12003.8	11459.4
45°	13949.3	15219.7	16493.3	17260.7	18031.2	18598.0	18362.4	17677.8	16990.0	16305.5	15620.9
47.5°	17633.2	19148.8	20664.4	21275.8	21890.3	22367.9	22310.6	21457.3	20603.9	19753.8	18900.5
50°	20307.8	21813.9	23319.9	23845.3	24373.8	24765.5	24619.0	23533.2	22444.3	21358.5	20269.6
52.5°	21199.3	22654.5	24112.7	24740.0	25367.3	25835.3	25657.0	24434.3	23211.7	21992.2	20769.5
55°	21613.3	23125.7	24638.1	25402.3	26169.6	26730.0	26472.1	25131.6	23788.0	22447.5	21103.8
57.5°	22129.1	23749.8	25370.4	26207.8	27045.2	27650.2	27306.3	25918.1	24529.9	23144.8	21756.6
60°	22517.5	24131.8	25749.3	26421.2	27096.2	27567.4	27236.3	25886.3	24533.0	23183.0	21833.0
62.5°	21657.8	22899.6	24141.4	24641.3	25141.2	25504.2	25316.3	24036.3	22756.3	21476.4	20196.4
65°	18820.9	19680.6	20543.4	20880.9	21215.3	21473.2	21415.9	20336.5	19257.1	18180.9	17101.5
67.5°	15187.9	15856.5	16528.4	17006.0	17486.8	17859.3	17817.9	16834.0	15850.2	14866.3	13882.4
70°	11831.9	12526.0	13220.1	13821.9	14426.9	14894.9	14834.4	13920.6	13003.6	12089.8	11172.8
72.5°	9453.4	10243.1	11032.7	11376.6	11720.5	11962.4	11784.1	11093.2	10399.1	9708.1	9014.0
75°	5740.8	6154.8	6571.9	6568.7	6568.7	6530.5	6352.2	5957.3	5562.5	5167.7	4772.9
77.5°	1709.8	1891.3	2072.8	2247.9	2426.2	2560.0	2524.9	2318.0	2107.8	1900.9	1690.7
80°	471.2	519.0	569.9	592.2	614.5	643.2	716.4	665.5	614.5	566.8	515.8
82.5°	121.0	121.0	121.0	117.8	114.6	108.3	98.7	92.3	86.0	79.6	73.2
85°	19.1	15.9	15.9	15.9	12.7	12.7	12.7	12.7	9.6	9.6	6.4
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7
2.5°	31.8	31.8	28.7	28.7	28.7	28.7	28.7	28.7	28.7	28.7	25.5
5°	38.2	38.2	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	31.8
7.5°	47.8	47.8	44.6	44.6	44.6	44.6	41.4	41.4	41.4	41.4	38.2
10°	60.5	57.3	57.3	54.1	54.1	54.1	50.9	50.9	50.9	47.8	47.8
12.5°	76.4	73.2	73.2	70.0	66.9	66.9	63.7	60.5	57.3	57.3	54.1
15°	101.9	98.7	95.5	92.3	89.2	82.8	79.6	73.2	70.0	66.9	63.7
17.5°	194.2	178.3	162.4	146.5	133.7	121.0	108.3	95.5	89.2	82.8	76.4
20°	541.3	468.1	398.0	328.0	283.4	238.8	194.2	149.6	130.5	114.6	95.5
22.5°	1171.7	1025.3	882.0	735.5	617.7	503.1	385.3	267.5	222.9	181.5	136.9
25°	2177.9	1897.7	1620.7	1340.5	1117.6	894.7	671.8	448.9	366.2	283.4	200.6
27.5°	3231.8	2868.8	2505.8	2142.9	1789.4	1432.8	1076.2	722.8	579.5	439.4	296.1
30°	4043.7	3658.5	3276.4	2891.1	2445.3	1999.6	1550.6	1104.9	878.8	652.7	423.5
32.5°	4741.0	4323.9	3910.0	3492.9	2977.1	2461.3	1945.4	1429.6	1146.3	862.9	576.3
35°	5432.0	4957.6	4486.3	4011.9	3457.9	2903.8	2349.8	1795.8	1436.0	1076.2	713.2
37.5°	6272.6	5693.1	5116.8	4540.4	3970.5	3403.7	2833.8	2263.9	1805.4	1350.0	891.5
40°	7737.2	6998.5	6263.0	5524.3	4858.8	4196.6	3531.1	2865.6	2289.3	1713.0	1133.5
42.5°	10532.8	9606.3	8682.9	7756.3	6836.1	5915.9	4992.6	4072.4	3250.9	2432.6	1611.1
45°	14433.3	13245.6	12061.1	10873.5	9740.0	8609.6	7476.1	6342.6	5094.5	3846.3	2595.0
47.5°	17601.4	16299.1	15000.0	13697.7	12440.0	11185.5	9927.8	8670.1	7071.8	5476.6	3878.2
50°	19031.0	17789.2	16550.6	15308.9	14048.0	12783.9	11519.9	10259.0	8425.0	6594.1	4760.1
52.5°	19511.8	18250.9	16993.2	15732.3	14481.0	13229.7	11978.4	10727.0	8819.8	6915.7	5008.5
55°	19776.1	18445.1	17117.4	15786.5	14439.6	13089.6	11739.6	10392.7	8495.0	6600.5	4702.8
57.5°	20311.0	18862.3	17416.7	15968.0	14433.3	12898.5	11360.7	9825.9	7953.7	6081.5	4209.3
60°	20409.7	18983.3	17560.0	16136.7	14439.6	12742.5	11042.3	9345.2	7485.7	5629.4	3769.9
62.5°	19005.5	17814.7	16627.1	15436.2	13736.0	12035.7	10332.2	8631.9	6852.1	5072.2	3289.1
65°	16073.0	15044.6	14019.3	12990.9	11602.6	10217.6	8829.3	7441.1	5852.3	4266.6	2677.8
67.5°	12876.3	11870.1	10867.1	9861.0	8816.6	7775.4	6731.1	5686.7	4460.8	3235.0	2009.1
70°	10208.0	9240.1	8275.3	7307.4	6384.0	5457.4	4530.9	3607.5	2846.5	2088.7	1327.7
72.5°	8090.6	7164.1	6240.7	5314.2	4476.8	3639.4	2802.0	1964.6	1585.7	1209.9	831.0
75°	4292.1	3811.3	3333.7	2852.9	2381.7	1907.2	1432.8	961.6	811.9	662.3	509.4
77.5°	1480.6	1270.4	1063.5	853.3	710.0	566.8	423.5	280.2	264.3	251.5	235.6
80°	448.9	382.1	315.2	248.4	219.7	191.0	162.4	133.7	124.2	114.6	101.9
82.5°	70.0	63.7	60.5	54.1	50.9	50.9	47.8	44.6	38.2	35.0	28.7
85°	6.4	3.2	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	28.7	28.7
2.5°	25.5	25.5
5°	31.8	31.8
7.5°	38.2	38.2
10°	44.6	44.6
12.5°	50.9	50.9
15°	60.5	57.3
17.5°	70.0	66.9
20°	76.4	70.0
22.5°	92.3	79.6
25°	117.8	98.7
27.5°	152.8	121.0
30°	197.4	152.8
32.5°	292.9	213.3
35°	353.4	257.9
37.5°	433.0	299.3
40°	557.2	363.0
42.5°	789.6	493.5
45°	1346.8	818.3
47.5°	2283.0	1394.6
50°	2926.1	1789.4
52.5°	3104.4	1897.7
55°	2808.3	1741.7
57.5°	2337.1	1480.6
60°	1913.6	1219.5
62.5°	1509.2	964.8
65°	1088.9	729.1
67.5°	783.3	560.4
70°	569.9	439.4
72.5°	452.1	366.2
75°	359.8	305.7
77.5°	222.9	203.8
80°	92.3	86.0
82.5°	22.3	19.1
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066654

CATALOG NUMBER: NVN-SA3B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-10

Test Date: 10/11/2024

Luminaire Tested: GSS-SB1A-835-U-5WQ

Data in this report applies to families of products including GSS-SB1A-835-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-10
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-835-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3411
 CIE u' : 0.2360
 CIE v' : 0.5189
 Duv: 0.0044
 CIE x: 0.4154
 CIE y: 0.4059
 CIE z: 0.1787
 Peak Wavelength (nm): 601
 Dominant Wavelength (nm): 579
 Purity: 46.51914
 R_f: 86.6
 R_g: 95.9

CRI (Ra): 83.5
 R1: 81.1
 R2: 88.9
 R3: 97.2
 R4: 83.8
 R5: 81.7
 R6: 86.9
 R7: 86.1
 R8: 62.2
 R9: 6.3
 R10: 75.4
 R11: 84.1
 R12: 69.7
 R13: 82.8
 R14: 98.5
 R15: 72.6



Test Conditions


Stabilization Time: 35M
 Operation Time: 1H 35M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-10

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-10

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.48

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.88


λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10





TM-30-18

Summary

$R_f = 86.6$
 $R_g = 95.9$
 $CIE R_a = 83.5$
 $R_9 = 6.3$







Color Vector Graphics





Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 85	CES51 = 97	CES76 = 81
CES02 = 62	CES27 = 95	CES52 = 96	CES77 = 87
CES03 = 31	CES28 = 94	CES53 = 91	CES78 = 80
CES04 = 70	CES29 = 87	CES54 = 92	CES79 = 93
CES05 = 49	CES30 = 93	CES55 = 92	CES80 = 91
CES06 = 51	CES31 = 89	CES56 = 88	CES81 = 77
CES07 = 41	CES32 = 84	CES57 = 87	CES82 = 96
CES08 = 40	CES33 = 91	CES58 = 88	CES83 = 95
CES09 = 29	CES34 = 91	CES59 = 93	CES84 = 92
CES10 = 75	CES35 = 95	CES60 = 94	CES85 = 80
CES11 = 58	CES36 = 90	CES61 = 91	CES86 = 72
CES12 = 64	CES37 = 95	CES62 = 95	CES87 = 86
CES13 = 43	CES38 = 100	CES63 = 88	CES88 = 88
CES14 = 74	CES39 = 97	CES64 = 85	CES89 = 77
CES15 = 71	CES40 = 94	CES65 = 80	CES90 = 88
CES16 = 47	CES41 = 97	CES66 = 84	CES91 = 81
CES17 = 49	CES42 = 96	CES67 = 82	CES92 = 67
CES18 = 56	CES43 = 93	CES68 = 85	CES93 = 81
CES19 = 72	CES44 = 99	CES69 = 89	CES94 = 63
CES20 = 66	CES45 = 95	CES70 = 81	CES95 = 76
CES21 = 86	CES46 = 91	CES71 = 79	CES96 = 84
CES22 = 78	CES47 = 93	CES72 = 93	CES97 = 92
CES23 = 91	CES48 = 85	CES73 = 76	CES98 = 86
CES24 = 90	CES49 = 92	CES74 = 95	CES99 = 77
CES25 = 72	CES50 = 96	CES75 = 80	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)