

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066655

Luminaire Tested: **NVN-SA3C-835-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066655
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA3C-835-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 1050mA 3xLight Square PACKAGE
80CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (42) 3500K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 12555.2 lumens
Efficiency: N/A
Efficacy: 89.4 lumens/watt
Luminous Opening: Rectangular (W 0.5' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G2


Input Watts (W): 140.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	74.7	0.0	74.7
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	12480.5	0.0	12480.5
	% Fixture	99.4	0.0	99.4
Total	Lumens	12555.1	0.0	12555.1
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.7	0.0
10°-20°	18.4	0.1
20°-30°	234.3	1.9
30°-40°	789.8	6.3
40°-50°	2385.1	19.0
50°-60°	4208.1	33.5
60°-70°	3707.3	29.5
70°-80°	1180.1	9.4
80°-90°	28.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	12555.1	100.0
0°-180°	12555.2	100.0



REPORT NUMBER: P1066655


CATALOG NUMBER: NVN-SA3C-835-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	245.3	2.0			
FM	(30°-60°)	7354.0	58.6			
FH	(60°-80°)	4858.2	38.7			G2/5000
FVH	(80°-90°)	23.1	0.2			G1/100
BL	(0°-30°)	11.2	0.1	B0/110		
BM	(30°-60°)	28.9	0.2	B0/220		
BH	(60°-80°)	29.3	0.2	B0/110		G0/110
BVH	(80°-90°)	5.3	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G2

Type III Short



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	27.6
5°	39.4	39.4	39.4	35.4	35.4	35.4	31.5	31.5	31.5	31.5	31.5
7.5°	47.2	43.3	43.3	39.4	39.4	39.4	35.4	35.4	35.4	35.4	31.5
10°	55.1	51.2	51.2	47.2	47.2	43.3	43.3	39.4	39.4	35.4	35.4
12.5°	63.0	59.1	55.1	51.2	51.2	47.2	47.2	43.3	43.3	39.4	39.4
15°	70.9	66.9	63.0	59.1	55.1	55.1	51.2	47.2	43.3	43.3	39.4
17.5°	82.7	74.8	70.9	63.0	59.1	55.1	51.2	47.2	47.2	43.3	43.3
20°	86.6	78.7	74.8	66.9	63.0	59.1	55.1	51.2	47.2	47.2	43.3
22.5°	102.4	86.6	82.7	74.8	70.9	66.9	59.1	55.1	51.2	47.2	43.3
25°	126.0	102.4	90.6	78.7	74.8	66.9	63.0	55.1	51.2	47.2	43.3
27.5°	153.6	114.2	102.4	86.6	78.7	70.9	63.0	55.1	51.2	47.2	43.3
30°	189.0	133.9	114.2	94.5	86.6	78.7	66.9	59.1	55.1	51.2	43.3
32.5°	263.8	165.4	133.9	102.4	90.6	82.7	70.9	59.1	55.1	51.2	43.3
35°	318.9	200.8	161.4	118.1	102.4	90.6	74.8	59.1	55.1	51.2	43.3
37.5°	370.1	204.7	165.4	126.0	110.2	94.5	74.8	59.1	55.1	51.2	43.3
40°	452.8	212.6	165.4	118.1	106.3	90.6	78.7	63.0	59.1	51.2	47.2
42.5°	610.3	244.1	177.2	110.2	98.4	90.6	78.7	66.9	59.1	55.1	47.2
45°	1015.8	362.2	240.2	114.2	102.4	90.6	78.7	66.9	63.0	55.1	51.2
47.5°	1728.5	630.0	374.0	118.1	106.3	90.6	78.7	63.0	59.1	55.1	47.2
50°	2212.8	807.1	472.5	137.8	118.1	102.4	82.7	63.0	59.1	55.1	51.2
52.5°	2350.6	858.3	511.8	161.4	137.8	114.2	86.6	63.0	59.1	59.1	55.1
55°	2153.7	834.7	511.8	189.0	157.5	129.9	98.4	66.9	63.0	63.0	59.1
57.5°	1830.8	771.7	488.2	204.7	173.2	137.8	106.3	70.9	66.9	66.9	63.0
60°	1508.0	649.7	441.0	228.4	192.9	157.5	122.1	86.6	82.7	78.7	70.9
62.5°	1196.9	523.7	385.9	244.1	208.7	169.3	133.9	94.5	90.6	86.6	82.7
65°	901.6	456.7	358.3	255.9	216.6	177.2	137.8	98.4	94.5	94.5	90.6
67.5°	693.0	417.4	342.5	263.8	224.4	185.1	145.7	106.3	102.4	98.4	94.5
70°	547.3	385.9	322.9	259.9	224.4	189.0	149.6	114.2	106.3	102.4	94.5
72.5°	456.7	350.4	299.2	248.0	220.5	192.9	165.4	137.8	122.1	110.2	94.5
75°	381.9	315.0	271.7	224.4	204.7	189.0	169.3	149.6	129.9	110.2	90.6
77.5°	252.0	228.4	208.7	189.0	177.2	165.4	149.6	137.8	118.1	102.4	82.7
80°	106.3	98.4	102.4	102.4	102.4	102.4	98.4	98.4	86.6	74.8	59.1
82.5°	23.6	19.7	23.6	23.6	23.6	23.6	19.7	19.7	19.7	15.7	15.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6
5°	31.5	31.5	31.5	27.6	27.6	27.6	27.6	27.6	27.6	27.6	27.6
7.5°	31.5	31.5	31.5	27.6	27.6	27.6	27.6	23.6	23.6	23.6	23.6
10°	31.5	31.5	31.5	27.6	27.6	27.6	27.6	23.6	23.6	23.6	23.6
12.5°	35.4	35.4	31.5	31.5	27.6	27.6	27.6	23.6	23.6	23.6	23.6
15°	35.4	35.4	31.5	31.5	27.6	27.6	27.6	23.6	23.6	23.6	23.6
17.5°	39.4	35.4	35.4	31.5	27.6	27.6	27.6	23.6	23.6	23.6	23.6
20°	39.4	35.4	35.4	31.5	27.6	27.6	27.6	23.6	23.6	23.6	23.6
22.5°	39.4	35.4	35.4	31.5	27.6	27.6	23.6	23.6	19.7	19.7	15.7
25°	39.4	35.4	35.4	31.5	27.6	27.6	23.6	23.6	19.7	15.7	15.7
27.5°	39.4	35.4	35.4	31.5	27.6	23.6	23.6	19.7	15.7	11.8	11.8
30°	39.4	35.4	35.4	31.5	27.6	23.6	19.7	15.7	11.8	11.8	7.9
32.5°	39.4	35.4	31.5	27.6	23.6	19.7	19.7	15.7	11.8	7.9	7.9
35°	39.4	35.4	31.5	27.6	23.6	19.7	19.7	15.7	11.8	7.9	7.9
37.5°	39.4	35.4	31.5	27.6	23.6	19.7	15.7	11.8	7.9	7.9	3.9
40°	39.4	35.4	31.5	27.6	23.6	19.7	15.7	11.8	7.9	7.9	3.9
42.5°	39.4	35.4	31.5	27.6	23.6	19.7	15.7	11.8	7.9	7.9	3.9
45°	43.3	39.4	35.4	27.6	23.6	19.7	19.7	15.7	11.8	7.9	7.9
47.5°	43.3	39.4	35.4	27.6	23.6	19.7	19.7	15.7	11.8	7.9	7.9
50°	47.2	43.3	39.4	31.5	27.6	23.6	19.7	11.8	7.9	7.9	3.9
52.5°	51.2	47.2	43.3	39.4	35.4	27.6	19.7	11.8	3.9	3.9	3.9
55°	55.1	51.2	51.2	47.2	43.3	31.5	23.6	11.8	0.0	0.0	0.0
57.5°	59.1	55.1	55.1	51.2	47.2	35.4	23.6	11.8	0.0	0.0	0.0
60°	66.9	63.0	59.1	51.2	47.2	35.4	23.6	11.8	0.0	0.0	0.0
62.5°	78.7	70.9	59.1	51.2	39.4	31.5	19.7	11.8	0.0	0.0	0.0
65°	86.6	74.8	63.0	47.2	35.4	27.6	19.7	7.9	0.0	0.0	0.0
67.5°	90.6	74.8	63.0	47.2	31.5	23.6	15.7	7.9	0.0	0.0	0.0
70°	86.6	70.9	59.1	43.3	27.6	19.7	15.7	7.9	0.0	0.0	0.0
72.5°	78.7	66.9	51.2	39.4	23.6	19.7	11.8	7.9	0.0	0.0	0.0
75°	70.9	59.1	43.3	31.5	15.7	11.8	7.9	3.9	0.0	0.0	0.0
77.5°	63.0	51.2	35.4	23.6	7.9	7.9	3.9	3.9	0.0	0.0	0.0
80°	47.2	35.4	23.6	11.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	11.8	7.9	7.9	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6
5°	23.6	23.6	23.6	23.6	19.7	19.7	19.7	19.7	19.7	19.7	19.7
7.5°	23.6	23.6	23.6	23.6	19.7	19.7	19.7	19.7	15.7	15.7	15.7
10°	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	15.7	15.7	15.7
12.5°	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	15.7	15.7	15.7
15°	19.7	19.7	19.7	19.7	19.7	19.7	19.7	15.7	15.7	11.8	11.8
17.5°	19.7	19.7	19.7	19.7	15.7	15.7	15.7	11.8	11.8	7.9	7.9
20°	19.7	19.7	19.7	15.7	15.7	11.8	11.8	7.9	7.9	3.9	3.9
22.5°	15.7	11.8	11.8	7.9	7.9	3.9	3.9	3.9	0.0	0.0	0.0
25°	11.8	7.9	7.9	3.9	3.9	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	7.9	3.9	3.9	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	7.9	3.9	3.9	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	23.6	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7
5°	19.7	19.7	19.7	19.7	15.7	15.7	15.7	15.7	15.7	15.7	15.7
7.5°	15.7	15.7	15.7	15.7	15.7	15.7	11.8	11.8	11.8	11.8	11.8
10°	15.7	11.8	11.8	11.8	11.8	11.8	11.8	11.8	11.8	7.9	7.9
12.5°	15.7	11.8	11.8	11.8	7.9	7.9	7.9	7.9	7.9	3.9	3.9
15°	11.8	7.9	7.9	7.9	3.9	3.9	3.9	3.9	3.9	0.0	0.0
17.5°	7.9	3.9	3.9	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	19.7	23.6	23.6
5°	15.7	15.7	15.7	15.7	15.7	15.7	15.7	15.7	15.7	15.7	15.7
7.5°	11.8	11.8	11.8	11.8	11.8	11.8	11.8	11.8	11.8	11.8	11.8
10°	7.9	7.9	7.9	7.9	7.9	7.9	3.9	3.9	3.9	3.9	3.9
12.5°	3.9	3.9	3.9	3.9	3.9	3.9	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	23.6	23.6	23.6	23.6	23.6	27.6	27.6	31.5	31.5	35.4	35.4
5°	15.7	15.7	19.7	19.7	19.7	19.7	23.6	23.6	23.6	27.6	27.6
7.5°	11.8	11.8	11.8	11.8	11.8	15.7	15.7	19.7	19.7	23.6	23.6
10°	3.9	3.9	7.9	7.9	7.9	7.9	11.8	11.8	11.8	15.7	19.7
12.5°	0.0	0.0	3.9	3.9	3.9	3.9	7.9	7.9	7.9	11.8	15.7
15°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9	7.9	11.8
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	7.9
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	39.4	39.4	43.3	43.3	47.2	47.2	51.2	51.2	51.2	51.2	51.2
5°	31.5	31.5	35.4	39.4	39.4	43.3	47.2	47.2	47.2	47.2	47.2
7.5°	27.6	27.6	31.5	35.4	35.4	39.4	43.3	43.3	47.2	47.2	47.2
10°	19.7	23.6	27.6	31.5	31.5	35.4	39.4	39.4	43.3	43.3	43.3
12.5°	15.7	19.7	23.6	27.6	27.6	31.5	35.4	35.4	39.4	39.4	43.3
15°	11.8	15.7	19.7	23.6	23.6	27.6	31.5	31.5	35.4	39.4	43.3
17.5°	7.9	11.8	15.7	19.7	19.7	23.6	27.6	31.5	35.4	35.4	39.4
20°	7.9	7.9	11.8	15.7	15.7	19.7	23.6	27.6	31.5	31.5	35.4
22.5°	3.9	3.9	7.9	11.8	11.8	15.7	19.7	23.6	27.6	27.6	31.5
25°	0.0	0.0	3.9	7.9	7.9	11.8	15.7	15.7	19.7	19.7	23.6
27.5°	0.0	0.0	3.9	3.9	7.9	7.9	11.8	11.8	15.7	15.7	19.7
30°	0.0	0.0	3.9	3.9	7.9	7.9	11.8	11.8	15.7	15.7	15.7
32.5°	0.0	0.0	0.0	3.9	3.9	3.9	7.9	7.9	11.8	11.8	15.7
35°	0.0	0.0	0.0	3.9	3.9	3.9	7.9	7.9	11.8	11.8	11.8
37.5°	0.0	0.0	0.0	3.9	3.9	3.9	7.9	7.9	7.9	7.9	11.8
40°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	7.9	7.9	7.9
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	7.9	7.9	7.9
45°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	7.9	7.9	7.9
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	7.9	7.9	7.9
50°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	7.9	7.9	7.9
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9	3.9	3.9
55°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9	3.9	3.9
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9
75°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9	3.9	3.9
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	7.9	7.9	7.9
80°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	7.9	7.9	7.9
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9	3.9	7.9
85°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9	3.9	3.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	3.9	3.9	3.9	3.9	3.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	51.2	51.2
5°	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	47.2	47.2
7.5°	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	47.2	47.2
10°	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2
12.5°	43.3	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2
15°	43.3	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2
17.5°	39.4	43.3	43.3	43.3	47.2	47.2	47.2	47.2	47.2	47.2	47.2
20°	35.4	39.4	39.4	39.4	43.3	43.3	43.3	43.3	47.2	47.2	47.2
22.5°	31.5	35.4	35.4	35.4	39.4	39.4	39.4	39.4	43.3	43.3	43.3
25°	27.6	27.6	31.5	31.5	35.4	35.4	35.4	35.4	35.4	35.4	35.4
27.5°	19.7	23.6	23.6	23.6	27.6	27.6	27.6	27.6	31.5	31.5	31.5
30°	19.7	19.7	19.7	19.7	23.6	23.6	23.6	23.6	27.6	27.6	27.6
32.5°	15.7	19.7	19.7	19.7	23.6	23.6	23.6	23.6	27.6	27.6	27.6
35°	15.7	15.7	15.7	15.7	19.7	19.7	19.7	19.7	23.6	23.6	23.6
37.5°	11.8	15.7	15.7	15.7	19.7	19.7	19.7	19.7	23.6	23.6	23.6
40°	11.8	11.8	11.8	11.8	15.7	15.7	15.7	15.7	19.7	19.7	19.7
42.5°	11.8	11.8	11.8	11.8	15.7	15.7	15.7	15.7	19.7	19.7	19.7
45°	11.8	11.8	11.8	11.8	15.7	15.7	15.7	15.7	19.7	19.7	19.7
47.5°	11.8	11.8	11.8	11.8	15.7	15.7	15.7	15.7	19.7	19.7	19.7
50°	11.8	11.8	11.8	11.8	15.7	15.7	15.7	15.7	19.7	19.7	19.7
52.5°	7.9	7.9	7.9	7.9	11.8	11.8	11.8	11.8	15.7	15.7	15.7
55°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	11.8	11.8	11.8
57.5°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	11.8	11.8	11.8
60°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9
62.5°	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9
65°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	3.9	3.9
67.5°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9
70°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9
72.5°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9
75°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9
77.5°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9
80°	11.8	11.8	11.8	11.8	11.8	7.9	7.9	7.9	7.9	7.9	7.9
82.5°	7.9	11.8	11.8	11.8	11.8	7.9	7.9	7.9	7.9	7.9	7.9
85°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9
87.5°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	51.2	51.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	51.2	51.2
5°	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	51.2	51.2
7.5°	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2	51.2	51.2
10°	47.2	47.2	47.2	47.2	43.3	43.3	47.2	47.2	47.2	51.2	51.2
12.5°	47.2	47.2	47.2	47.2	43.3	43.3	47.2	47.2	51.2	51.2	55.1
15°	47.2	47.2	43.3	43.3	43.3	43.3	47.2	47.2	51.2	51.2	55.1
17.5°	47.2	47.2	43.3	43.3	43.3	43.3	47.2	47.2	51.2	51.2	55.1
20°	47.2	47.2	43.3	43.3	43.3	43.3	43.3	43.3	47.2	51.2	51.2
22.5°	43.3	43.3	43.3	43.3	39.4	39.4	43.3	43.3	47.2	51.2	51.2
25°	35.4	39.4	39.4	39.4	39.4	39.4	43.3	43.3	47.2	51.2	51.2
27.5°	31.5	35.4	35.4	35.4	35.4	39.4	39.4	43.3	47.2	51.2	51.2
30°	27.6	31.5	31.5	31.5	35.4	39.4	39.4	43.3	47.2	51.2	51.2
32.5°	27.6	31.5	31.5	31.5	35.4	35.4	39.4	39.4	43.3	47.2	51.2
35°	27.6	27.6	31.5	31.5	31.5	35.4	35.4	39.4	43.3	47.2	51.2
37.5°	27.6	27.6	31.5	31.5	31.5	35.4	35.4	39.4	43.3	47.2	51.2
40°	23.6	27.6	27.6	31.5	31.5	35.4	35.4	39.4	43.3	51.2	55.1
42.5°	23.6	23.6	27.6	27.6	31.5	35.4	35.4	39.4	43.3	51.2	55.1
45°	23.6	27.6	27.6	31.5	35.4	39.4	39.4	43.3	47.2	51.2	55.1
47.5°	23.6	27.6	27.6	31.5	39.4	39.4	43.3	43.3	47.2	51.2	55.1
50°	23.6	27.6	27.6	31.5	43.3	43.3	43.3	43.3	47.2	51.2	55.1
52.5°	19.7	23.6	23.6	27.6	35.4	39.4	43.3	47.2	51.2	55.1	59.1
55°	15.7	19.7	19.7	23.6	31.5	35.4	43.3	51.2	55.1	59.1	63.0
57.5°	15.7	15.7	19.7	19.7	27.6	35.4	47.2	55.1	59.1	63.0	66.9
60°	11.8	11.8	15.7	15.7	23.6	31.5	43.3	55.1	59.1	66.9	70.9
62.5°	7.9	11.8	11.8	15.7	19.7	31.5	43.3	55.1	63.0	70.9	74.8
65°	7.9	7.9	11.8	11.8	19.7	27.6	39.4	47.2	59.1	70.9	82.7
67.5°	11.8	11.8	15.7	15.7	19.7	27.6	39.4	47.2	59.1	74.8	86.6
70°	11.8	11.8	15.7	15.7	23.6	31.5	39.4	47.2	59.1	74.8	86.6
72.5°	11.8	11.8	15.7	15.7	23.6	27.6	35.4	43.3	55.1	66.9	78.7
75°	7.9	11.8	11.8	11.8	19.7	23.6	31.5	39.4	51.2	63.0	74.8
77.5°	7.9	7.9	7.9	7.9	15.7	19.7	27.6	31.5	43.3	55.1	66.9
80°	7.9	7.9	7.9	7.9	11.8	15.7	23.6	27.6	39.4	51.2	63.0
82.5°	7.9	7.9	3.9	3.9	7.9	11.8	15.7	19.7	31.5	39.4	51.2
85°	7.9	7.9	3.9	3.9	3.9	7.9	7.9	11.8	15.7	19.7	23.6
87.5°	7.9	7.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	51.2	51.2	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1
5°	51.2	55.1	55.1	59.1	59.1	59.1	63.0	63.0	63.0	63.0	63.0
7.5°	51.2	55.1	55.1	59.1	59.1	59.1	63.0	63.0	63.0	66.9	66.9
10°	51.2	55.1	55.1	59.1	59.1	63.0	66.9	66.9	70.9	70.9	70.9
12.5°	55.1	59.1	59.1	63.0	63.0	66.9	70.9	70.9	74.8	78.7	78.7
15°	55.1	59.1	63.0	63.0	66.9	70.9	74.8	74.8	78.7	82.7	86.6
17.5°	55.1	59.1	63.0	63.0	66.9	70.9	78.7	82.7	86.6	94.5	98.4
20°	55.1	59.1	63.0	63.0	66.9	74.8	78.7	86.6	90.6	98.4	106.3
22.5°	55.1	59.1	63.0	66.9	70.9	78.7	86.6	90.6	98.4	110.2	118.1
25°	55.1	59.1	63.0	66.9	70.9	78.7	86.6	94.5	102.4	118.1	133.9
27.5°	55.1	59.1	66.9	70.9	74.8	82.7	94.5	102.4	110.2	137.8	165.4
30°	55.1	59.1	66.9	70.9	74.8	86.6	98.4	106.3	118.1	165.4	208.7
32.5°	55.1	63.0	66.9	74.8	78.7	90.6	106.3	118.1	129.9	196.9	259.9
35°	55.1	63.0	66.9	74.8	78.7	94.5	110.2	126.0	141.7	240.2	338.6
37.5°	55.1	63.0	66.9	74.8	78.7	102.4	126.0	149.6	173.2	275.6	378.0
40°	59.1	66.9	70.9	78.7	82.7	106.3	129.9	153.6	177.2	279.5	381.9
42.5°	59.1	66.9	70.9	78.7	82.7	102.4	126.0	145.7	165.4	279.5	393.7
45°	59.1	66.9	74.8	78.7	86.6	106.3	126.0	141.7	161.4	307.1	448.9
47.5°	59.1	66.9	74.8	78.7	86.6	106.3	126.0	145.7	165.4	405.5	641.8
50°	59.1	66.9	74.8	78.7	86.6	110.2	133.9	157.5	181.1	606.3	1031.6
52.5°	63.0	66.9	74.8	78.7	82.7	110.2	137.8	165.4	192.9	787.5	1378.1
55°	66.9	70.9	74.8	78.7	82.7	118.1	153.6	189.0	224.4	846.5	1464.7
57.5°	70.9	74.8	78.7	78.7	82.7	126.0	173.2	216.6	259.9	842.6	1421.4
60°	74.8	78.7	82.7	86.6	90.6	133.9	181.1	224.4	267.7	763.8	1259.9
62.5°	82.7	90.6	98.4	102.4	110.2	153.6	192.9	236.2	275.6	626.0	972.5
65°	94.5	102.4	106.3	114.2	118.1	157.5	200.8	240.2	279.5	519.7	756.0
67.5°	98.4	106.3	110.2	118.1	122.1	161.4	200.8	240.2	279.5	441.0	598.5
70°	98.4	106.3	114.2	118.1	126.0	165.4	200.8	240.2	275.6	381.9	488.2
72.5°	90.6	102.4	110.2	122.1	129.9	165.4	196.9	232.3	263.8	338.6	413.4
75°	86.6	102.4	114.2	129.9	141.7	165.4	192.9	216.6	240.2	295.3	350.4
77.5°	78.7	98.4	118.1	137.8	157.5	173.2	185.1	200.8	212.6	248.0	283.5
80°	74.8	94.5	114.2	133.9	153.6	161.4	165.4	173.2	177.2	181.1	185.1
82.5°	59.1	74.8	90.6	102.4	118.1	110.2	106.3	98.4	90.6	86.6	82.7
85°	27.6	31.5	31.5	35.4	35.4	35.4	31.5	31.5	27.6	23.6	19.7
87.5°	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	55.1	55.1	55.1	55.1	51.2	51.2	51.2	51.2	47.2	47.2	47.2
5°	63.0	63.0	63.0	63.0	59.1	59.1	59.1	59.1	55.1	55.1	55.1
7.5°	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9
10°	74.8	74.8	74.8	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7
12.5°	82.7	82.7	86.6	86.6	90.6	90.6	94.5	94.5	98.4	98.4	98.4
15°	90.6	94.5	98.4	102.4	102.4	106.3	110.2	114.2	118.1	122.1	126.0
17.5°	106.3	110.2	118.1	126.0	133.9	141.7	153.6	169.3	181.1	192.9	208.7
20°	118.1	129.9	153.6	181.1	204.7	228.4	287.4	346.5	405.5	464.6	523.7
22.5°	141.7	165.4	244.1	326.8	405.5	484.3	669.3	854.4	1035.5	1220.6	1385.9
25°	189.0	240.2	421.3	602.4	779.6	960.7	1291.4	1626.1	1956.8	2287.6	2594.7
27.5°	259.9	354.4	649.7	948.9	1244.2	1539.5	2019.8	2504.1	2984.5	3468.8	3897.9
30°	362.2	515.8	956.8	1401.7	1842.7	2283.6	2890.0	3500.3	4106.6	4712.9	5106.7
32.5°	492.2	720.5	1279.6	1838.7	2397.8	2956.9	3626.2	4295.6	4961.0	5630.3	6047.7
35°	630.0	921.3	1594.6	2271.8	2945.1	3622.3	4327.1	5031.9	5736.6	6441.4	6953.3
37.5°	708.7	1039.4	1838.7	2638.0	3433.3	4232.6	5004.3	5779.9	6551.7	7323.4	7945.5
40°	783.5	1181.2	2102.5	3023.8	3945.2	4866.5	5768.1	6669.8	7571.4	8473.1	9272.3
42.5°	893.8	1393.8	2468.7	3543.6	4614.5	5689.4	6874.5	8063.6	9248.7	10433.8	11662.3
45°	1122.1	1795.4	3189.2	4583.0	5972.9	7366.7	9047.9	10733.1	12414.3	14099.4	15674.4
47.5°	1673.3	2701.0	4602.7	6504.4	8406.1	10307.8	12245.0	14182.1	16119.3	18056.4	19930.6
50°	2590.7	4146.0	6524.1	8902.2	11276.4	13654.5	15587.7	17521.0	19450.2	21383.4	23245.8
52.5°	3453.0	5528.0	8083.3	10642.5	13197.8	15757.0	17469.8	19182.5	20895.2	22607.9	24411.2
55°	3748.3	6028.0	8614.8	11205.5	13792.3	16383.1	18032.8	19686.5	21336.2	22985.9	24856.1
57.5°	3488.4	5555.5	8162.0	10768.5	13371.0	15977.5	17820.2	19666.8	21509.4	23356.0	25360.1
60°	2921.5	4579.1	7315.5	10055.8	12792.3	15528.7	17607.6	19686.5	21765.4	23844.3	25844.4
62.5°	2315.1	3653.8	6551.7	9449.5	12347.4	15245.2	17359.5	19477.8	21592.1	23706.4	25242.0
65°	1775.7	2795.5	5646.1	8500.6	11351.2	14205.8	15938.2	17674.5	19406.9	21143.3	22206.3
67.5°	1319.0	2039.5	4531.8	7028.1	9520.4	12012.7	13288.4	14568.0	15843.7	17123.3	17950.1
70°	972.5	1452.9	3149.8	4846.8	6539.8	8236.8	9406.2	10575.6	11741.0	12910.4	13768.7
72.5°	673.3	929.2	1945.0	2964.8	3980.6	4996.4	6181.6	7366.7	8547.9	9733.0	10709.4
75°	460.7	570.9	1047.3	1523.7	2000.1	2476.6	3374.3	4272.0	5169.7	6067.4	6583.2
77.5°	342.5	401.6	543.3	689.0	830.8	972.5	1145.8	1319.0	1492.2	1665.5	1889.9
80°	189.0	189.0	208.7	224.4	244.1	259.9	307.1	358.3	405.5	456.7	519.7
82.5°	86.6	90.6	98.4	106.3	110.2	118.1	126.0	133.9	141.7	149.6	149.6
85°	23.6	27.6	27.6	23.6	23.6	19.7	19.7	23.6	23.6	23.6	23.6
87.5°	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	47.2	43.3	43.3	43.3	39.4	39.4	39.4	39.4	39.4	39.4	39.4
5°	55.1	55.1	55.1	55.1	51.2	51.2	51.2	51.2	51.2	47.2	47.2
7.5°	66.9	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	59.1	59.1
10°	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	74.8	74.8
12.5°	98.4	98.4	98.4	98.4	102.4	102.4	98.4	98.4	98.4	94.5	94.5
15°	129.9	133.9	137.8	137.8	141.7	141.7	141.7	137.8	137.8	133.9	129.9
17.5°	220.5	232.3	248.0	263.8	279.5	291.4	291.4	283.5	275.6	267.7	259.9
20°	586.7	645.7	708.7	771.7	838.6	885.9	854.4	830.8	807.1	779.6	756.0
22.5°	1555.2	1720.6	1889.9	2008.0	2126.1	2208.8	2141.9	2012.0	1882.0	1756.0	1626.1
25°	2901.8	3205.0	3512.1	3638.1	3768.0	3862.5	3819.2	3622.3	3425.4	3232.5	3035.7
27.5°	4327.1	4752.3	5181.5	5291.7	5402.0	5484.7	5468.9	5213.0	4957.1	4701.1	4445.2
30°	5500.4	5894.1	6287.9	6398.1	6508.3	6583.2	6500.5	6244.5	5988.6	5732.7	5476.8
32.5°	6469.0	6886.3	7307.6	7453.3	7599.0	7697.4	7599.0	7291.9	6984.8	6681.6	6374.5
35°	7465.1	7973.0	8484.9	8669.9	8855.0	8973.1	8807.7	8429.7	8051.8	7677.7	7299.7
37.5°	8567.6	9185.7	9807.8	10059.8	10315.7	10492.9	10366.9	9894.4	9418.0	8945.5	8469.1
40°	10075.5	10874.8	11678.0	12130.8	12579.7	12898.6	12674.1	12126.9	11575.6	11028.4	10477.1
42.5°	12894.6	14123.1	15351.5	16001.2	16646.9	17115.4	16863.4	16190.2	15516.9	14843.6	14170.3
45°	17249.3	18820.3	20395.2	21344.1	22296.9	22997.7	22706.4	21859.9	21009.4	20162.9	19316.4
47.5°	21804.7	23678.9	25553.0	26309.0	27068.9	27659.5	27588.6	26533.4	25478.2	24427.0	23371.8
50°	25112.1	26974.4	28836.7	29486.4	30140.0	30624.3	30443.2	29100.5	27754.0	26411.4	25064.8
52.5°	26214.5	28013.8	29817.1	30592.8	31368.4	31947.2	31726.7	30214.8	28702.9	27194.9	25683.0
55°	26726.4	28596.6	30466.8	31411.7	32360.6	33053.6	32734.7	31077.1	29415.5	27757.9	26096.4
57.5°	27364.2	29368.3	31372.4	32407.9	33443.4	34191.5	33766.2	32049.6	30332.9	28620.2	26903.5
60°	27844.5	29840.7	31840.9	32671.7	33506.4	34089.1	33679.6	32010.2	30336.8	28667.4	26998.0
62.5°	26781.5	28317.0	29852.6	30470.7	31088.9	31537.7	31305.4	29722.6	28139.8	26557.0	24974.3
65°	23273.3	24336.4	25403.4	25820.8	26234.2	26553.1	26482.2	25147.5	23812.8	22481.9	21147.2
67.5°	18780.9	19607.7	20438.5	21029.1	21623.6	22084.3	22033.1	20816.5	19599.8	18383.2	17166.6
70°	14631.0	15489.3	16347.6	17091.8	17839.9	18418.7	18343.9	17213.8	16079.9	14949.9	13816.0
72.5°	11689.8	12666.3	13642.7	14068.0	14493.2	14792.4	14571.9	13717.5	12859.2	12004.8	11146.5
75°	7098.9	7610.8	8126.6	8122.6	8122.6	8075.4	7854.9	7366.7	6878.5	6390.2	5902.0
77.5°	2114.3	2338.8	2563.2	2779.7	3000.2	3165.6	3122.3	2866.3	2606.5	2350.6	2090.7
80°	582.7	641.8	704.8	732.3	759.9	795.3	885.9	822.9	759.9	700.8	637.8
82.5°	149.6	149.6	149.6	145.7	141.7	133.9	122.1	114.2	106.3	98.4	90.6
85°	23.6	19.7	19.7	19.7	15.7	15.7	15.7	15.7	11.8	11.8	7.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4
2.5°	39.4	39.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	35.4	31.5
5°	47.2	47.2	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	39.4
7.5°	59.1	59.1	55.1	55.1	55.1	55.1	51.2	51.2	51.2	51.2	47.2
10°	74.8	70.9	70.9	66.9	66.9	66.9	63.0	63.0	63.0	59.1	59.1
12.5°	94.5	90.6	90.6	86.6	82.7	82.7	78.7	74.8	70.9	70.9	66.9
15°	126.0	122.1	118.1	114.2	110.2	102.4	98.4	90.6	86.6	82.7	78.7
17.5°	240.2	220.5	200.8	181.1	165.4	149.6	133.9	118.1	110.2	102.4	94.5
20°	669.3	578.8	492.2	405.5	350.4	295.3	240.2	185.1	161.4	141.7	118.1
22.5°	1448.9	1267.8	1090.6	909.5	763.8	622.1	476.4	330.7	275.6	224.4	169.3
25°	2693.1	2346.6	2004.1	1657.6	1382.0	1106.4	830.8	555.2	452.8	350.4	248.0
27.5°	3996.4	3547.5	3098.7	2649.8	2212.8	1771.8	1330.8	893.8	716.6	543.3	366.2
30°	5000.4	4524.0	4051.5	3575.1	3023.8	2472.6	1917.5	1366.2	1086.7	807.1	523.7
32.5°	5862.6	5346.8	4835.0	4319.2	3681.4	3043.5	2405.7	1767.8	1417.4	1067.0	712.7
35°	6717.0	6130.4	5547.6	4961.0	4275.9	3590.8	2905.7	2220.6	1775.7	1330.8	882.0
37.5°	7756.5	7039.9	6327.2	5614.6	4909.8	4209.0	3504.2	2799.4	2232.4	1669.4	1102.4
40°	9567.6	8654.2	7744.7	6831.2	6008.3	5189.4	4366.5	3543.6	2830.9	2118.3	1401.7
42.5°	13024.6	11878.8	10737.0	9591.2	8453.4	7315.5	6173.7	5035.8	4020.0	3008.1	1992.3
45°	17847.8	16379.1	14914.5	13445.9	12044.2	10646.4	9244.8	7843.1	6299.7	4756.3	3208.9
47.5°	21765.4	20155.0	18548.6	16938.2	15383.0	13831.7	12276.5	10721.3	8744.7	6772.1	4795.6
50°	23533.2	21997.7	20466.1	18930.5	17371.3	15808.2	14245.1	12686.0	10418.1	8154.1	5886.3
52.5°	24127.7	22568.6	21013.3	19454.2	17906.8	16359.5	14812.1	13264.7	10906.3	8551.8	6193.4
55°	24454.5	22808.7	21166.9	19521.1	17855.6	16186.2	14516.8	12851.3	10504.7	8162.0	5815.4
57.5°	25116.0	23324.5	21537.0	19745.5	17847.8	15950.0	14048.3	12150.5	9835.4	7520.2	5205.1
60°	25238.1	23474.1	21714.2	19954.2	17855.6	15757.0	13654.5	11556.0	9256.6	6961.1	4661.8
62.5°	23501.7	22029.2	20560.5	19088.0	16985.5	14883.0	12776.5	10674.0	8473.1	6272.1	4067.2
65°	19875.5	18603.7	17335.9	16064.2	14347.5	12634.8	10918.1	9201.5	7236.7	5276.0	3311.3
67.5°	15922.4	14678.2	13438.0	12193.8	10902.4	9614.9	8323.4	7032.0	5516.1	4000.3	2484.4
70°	12623.0	11426.0	10233.0	9036.1	7894.3	6748.5	5602.8	4461.0	3519.9	2582.9	1641.9
72.5°	10004.7	8858.9	7717.1	6571.3	5535.8	4500.3	3464.8	2429.3	1960.8	1496.2	1027.6
75°	5307.5	4712.9	4122.3	3527.8	2945.1	2358.4	1771.8	1189.1	1004.0	819.0	630.0
77.5°	1830.8	1571.0	1315.1	1055.2	878.0	700.8	523.7	346.5	326.8	311.0	291.4
80°	555.2	472.5	389.8	307.1	271.7	236.2	200.8	165.4	153.6	141.7	126.0
82.5°	86.6	78.7	74.8	66.9	63.0	63.0	59.1	55.1	47.2	43.3	35.4
85°	7.9	3.9	3.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	35.4	35.4
2.5°	31.5	31.5
5°	39.4	39.4
7.5°	47.2	47.2
10°	55.1	55.1
12.5°	63.0	63.0
15°	74.8	70.9
17.5°	86.6	82.7
20°	94.5	86.6
22.5°	114.2	98.4
25°	145.7	122.1
27.5°	189.0	149.6
30°	244.1	189.0
32.5°	362.2	263.8
35°	437.0	318.9
37.5°	535.5	370.1
40°	689.0	448.9
42.5°	976.4	610.3
45°	1665.5	1011.9
47.5°	2823.0	1724.5
50°	3618.4	2212.8
52.5°	3838.9	2346.6
55°	3472.7	2153.7
57.5°	2890.0	1830.8
60°	2366.3	1508.0
62.5°	1866.3	1193.0
65°	1346.6	901.6
67.5°	968.6	693.0
70°	704.8	543.3
72.5°	559.1	452.8
75°	444.9	378.0
77.5°	275.6	252.0
80°	114.2	106.3
82.5°	27.6	23.6
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066655

CATALOG NUMBER: NVN-SA3C-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-10

Test Date: 10/11/2024

Luminaire Tested: GSS-SB1A-835-U-5WQ

Data in this report applies to families of products including GSS-SB1A-835-U-5WQ

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-10
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-835-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI
 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3411
 CIE u' : 0.2360
 CIE v' : 0.5189
 Duv: 0.0044
 CIE x: 0.4154
 CIE y: 0.4059
 CIE z: 0.1787
 Peak Wavelength (nm): 601
 Dominant Wavelength (nm): 579
 Purity: 46.51914
 Rf: 86.6
 Rg: 95.9

CRI (Ra): 83.5
 R1: 81.1
 R2: 88.9
 R3: 97.2
 R4: 83.8
 R5: 81.7
 R6: 86.9
 R7: 86.1
 R8: 62.2
 R9: 6.3
 R10: 75.4
 R11: 84.1
 R12: 69.7
 R13: 82.8
 R14: 98.5
 R15: 72.6



Test Conditions


Stabilization Time: 35M
 Operation Time: 1H 35M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-10

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-10

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-10

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.48

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.88

λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10


TM-30-18

Summary

$R_f = 86.6$
 $R_g = 95.9$
 $\text{CIE } R_a = 83.5$
 $R_9 = 6.3$




Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 85	CES51 = 97	CES76 = 81
CES02 = 62	CES27 = 95	CES52 = 96	CES77 = 87
CES03 = 31	CES28 = 94	CES53 = 91	CES78 = 80
CES04 = 70	CES29 = 87	CES54 = 92	CES79 = 93
CES05 = 49	CES30 = 93	CES55 = 92	CES80 = 91
CES06 = 51	CES31 = 89	CES56 = 88	CES81 = 77
CES07 = 41	CES32 = 84	CES57 = 87	CES82 = 96
CES08 = 40	CES33 = 91	CES58 = 88	CES83 = 95
CES09 = 29	CES34 = 91	CES59 = 93	CES84 = 92
CES10 = 75	CES35 = 95	CES60 = 94	CES85 = 80
CES11 = 58	CES36 = 90	CES61 = 91	CES86 = 72
CES12 = 64	CES37 = 95	CES62 = 95	CES87 = 86
CES13 = 43	CES38 = 100	CES63 = 88	CES88 = 88
CES14 = 74	CES39 = 97	CES64 = 85	CES89 = 77
CES15 = 71	CES40 = 94	CES65 = 80	CES90 = 88
CES16 = 47	CES41 = 97	CES66 = 84	CES91 = 81
CES17 = 49	CES42 = 96	CES67 = 82	CES92 = 67
CES18 = 56	CES43 = 93	CES68 = 85	CES93 = 81
CES19 = 72	CES44 = 99	CES69 = 89	CES94 = 63
CES20 = 66	CES45 = 95	CES70 = 81	CES95 = 76
CES21 = 86	CES46 = 91	CES71 = 79	CES96 = 84
CES22 = 78	CES47 = 93	CES72 = 93	CES97 = 92
CES23 = 91	CES48 = 85	CES73 = 76	CES98 = 86
CES24 = 90	CES49 = 92	CES74 = 95	CES99 = 77
CES25 = 72	CES50 = 96	CES75 = 80	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)