

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066658

Luminaire Tested: **NVN-SA4B-835-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066658
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA4B-835-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 4xLight Square PACKAGE
80CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (56) 3500K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 13337 lumens
Efficiency: N/A
Efficacy: 92.6 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 144.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.6 fc
 Type III - Short - N/A

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	79.3	0.0	79.3
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	13257.6	0.0	13257.6
	% Fixture	99.4	0.0	99.4
Total	Lumens	13337.0	0.0	13337.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.9	0.0
10°-20°	19.6	0.1
20°-30°	248.9	1.9
30°-40°	838.9	6.3
40°-50°	2533.6	19.0
50°-60°	4470.1	33.5
60°-70°	3938.1	29.5
70°-80°	1253.6	9.4
80°-90°	30.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	13337.0	100.0
0°-180°	13337.0	100.0



REPORT NUMBER: P1066658


CATALOG NUMBER: NVN-SA4B-835-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	260.5	2.0			
FM	(30°-60°)	7811.9	58.6			
FH	(60°-80°)	5160.7	38.7			G3/7500
FVH	(80°-90°)	24.5	0.2			G1/100
BL	(0°-30°)	11.9	0.1	B0/110		
BM	(30°-60°)	30.7	0.2	B0/220		
BH	(60°-80°)	31.1	0.2	B0/110		G0/110
BVH	(80°-90°)	5.6	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5	29.3
5°	41.8	41.8	41.8	37.6	37.6	37.6	33.5	33.5	33.5	33.5	33.5
7.5°	50.2	46.0	46.0	41.8	41.8	41.8	37.6	37.6	37.6	37.6	33.5
10°	58.6	54.4	54.4	50.2	50.2	46.0	46.0	41.8	41.8	37.6	37.6
12.5°	66.9	62.7	58.6	54.4	54.4	50.2	50.2	46.0	46.0	41.8	41.8
15°	75.3	71.1	66.9	62.7	58.6	58.6	54.4	50.2	46.0	46.0	41.8
17.5°	87.8	79.5	75.3	66.9	62.7	58.6	54.4	50.2	50.2	46.0	46.0
20°	92.0	83.6	79.5	71.1	66.9	62.7	58.6	54.4	50.2	50.2	46.0
22.5°	108.7	92.0	87.8	79.5	75.3	71.1	62.7	58.6	54.4	50.2	46.0
25°	133.8	108.7	96.2	83.6	79.5	71.1	66.9	58.6	54.4	50.2	46.0
27.5°	163.1	121.3	108.7	92.0	83.6	75.3	66.9	58.6	54.4	50.2	46.0
30°	200.8	142.2	121.3	100.4	92.0	83.6	71.1	62.7	58.6	54.4	46.0
32.5°	280.2	175.7	142.2	108.7	96.2	87.8	75.3	62.7	58.6	54.4	46.0
35°	338.8	213.3	171.5	125.5	108.7	96.2	79.5	62.7	58.6	54.4	46.0
37.5°	393.2	217.5	175.7	133.8	117.1	100.4	79.5	62.7	58.6	54.4	46.0
40°	481.0	225.9	175.7	125.5	112.9	96.2	83.6	66.9	62.7	54.4	50.2
42.5°	648.3	259.3	188.2	117.1	104.6	96.2	83.6	71.1	62.7	58.6	50.2
45°	1079.1	384.8	255.1	121.3	108.7	96.2	83.6	71.1	66.9	58.6	54.4
47.5°	1836.1	669.2	397.3	125.5	112.9	96.2	83.6	66.9	62.7	58.6	50.2
50°	2350.5	857.4	501.9	146.4	125.5	108.7	87.8	66.9	62.7	58.6	54.4
52.5°	2496.9	911.8	543.7	171.5	146.4	121.3	92.0	66.9	62.7	62.7	58.6
55°	2287.8	886.7	543.7	200.8	167.3	138.0	104.6	71.1	66.9	66.9	62.7
57.5°	1944.8	819.8	518.6	217.5	184.0	146.4	112.9	75.3	71.1	71.1	66.9
60°	1601.9	690.1	468.4	242.6	204.9	167.3	129.7	92.0	87.8	83.6	75.3
62.5°	1271.5	556.3	409.9	259.3	221.7	179.8	142.2	100.4	96.2	92.0	87.8
65°	957.8	485.2	380.6	271.9	230.0	188.2	146.4	104.6	100.4	100.4	96.2
67.5°	736.1	443.3	363.9	280.2	238.4	196.6	154.8	112.9	108.7	104.6	100.4
70°	581.4	409.9	343.0	276.0	238.4	200.8	158.9	121.3	112.9	108.7	100.4
72.5°	485.2	372.2	317.9	263.5	234.2	204.9	175.7	146.4	129.7	117.1	100.4
75°	405.7	334.6	288.6	238.4	217.5	200.8	179.8	158.9	138.0	117.1	96.2
77.5°	267.7	242.6	221.7	200.8	188.2	175.7	158.9	146.4	125.5	108.7	87.8
80°	112.9	104.6	108.7	108.7	108.7	108.7	104.6	104.6	92.0	79.5	62.7
82.5°	25.1	20.9	25.1	25.1	25.1	25.1	20.9	20.9	20.9	16.7	16.7
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
5°	33.5	33.5	33.5	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
7.5°	33.5	33.5	33.5	29.3	29.3	29.3	29.3	25.1	25.1	25.1	25.1
10°	33.5	33.5	33.5	29.3	29.3	29.3	29.3	25.1	25.1	25.1	25.1
12.5°	37.6	37.6	33.5	33.5	29.3	29.3	29.3	25.1	25.1	25.1	25.1
15°	37.6	37.6	33.5	33.5	29.3	29.3	29.3	25.1	25.1	25.1	25.1
17.5°	41.8	37.6	37.6	33.5	29.3	29.3	29.3	25.1	25.1	25.1	25.1
20°	41.8	37.6	37.6	33.5	29.3	29.3	29.3	25.1	25.1	25.1	25.1
22.5°	41.8	37.6	37.6	33.5	29.3	29.3	25.1	25.1	20.9	20.9	16.7
25°	41.8	37.6	37.6	33.5	29.3	29.3	25.1	25.1	20.9	16.7	16.7
27.5°	41.8	37.6	37.6	33.5	29.3	25.1	25.1	20.9	16.7	12.5	12.5
30°	41.8	37.6	37.6	33.5	29.3	25.1	20.9	16.7	12.5	12.5	8.4
32.5°	41.8	37.6	33.5	29.3	25.1	20.9	20.9	16.7	12.5	8.4	8.4
35°	41.8	37.6	33.5	29.3	25.1	20.9	20.9	16.7	12.5	8.4	8.4
37.5°	41.8	37.6	33.5	29.3	25.1	20.9	16.7	12.5	8.4	8.4	4.2
40°	41.8	37.6	33.5	29.3	25.1	20.9	16.7	12.5	8.4	8.4	4.2
42.5°	41.8	37.6	33.5	29.3	25.1	20.9	16.7	12.5	8.4	8.4	4.2
45°	46.0	41.8	37.6	29.3	25.1	20.9	20.9	16.7	12.5	8.4	8.4
47.5°	46.0	41.8	37.6	29.3	25.1	20.9	20.9	16.7	12.5	8.4	8.4
50°	50.2	46.0	41.8	33.5	29.3	25.1	20.9	12.5	8.4	8.4	4.2
52.5°	54.4	50.2	46.0	41.8	37.6	29.3	20.9	12.5	4.2	4.2	4.2
55°	58.6	54.4	54.4	50.2	46.0	33.5	25.1	12.5	0.0	0.0	0.0
57.5°	62.7	58.6	58.6	54.4	50.2	37.6	25.1	12.5	0.0	0.0	0.0
60°	71.1	66.9	62.7	54.4	50.2	37.6	25.1	12.5	0.0	0.0	0.0
62.5°	83.6	75.3	62.7	54.4	41.8	33.5	20.9	12.5	0.0	0.0	0.0
65°	92.0	79.5	66.9	50.2	37.6	29.3	20.9	8.4	0.0	0.0	0.0
67.5°	96.2	79.5	66.9	50.2	33.5	25.1	16.7	8.4	0.0	0.0	0.0
70°	92.0	75.3	62.7	46.0	29.3	20.9	16.7	8.4	0.0	0.0	0.0
72.5°	83.6	71.1	54.4	41.8	25.1	20.9	12.5	8.4	0.0	0.0	0.0
75°	75.3	62.7	46.0	33.5	16.7	12.5	8.4	4.2	0.0	0.0	0.0
77.5°	66.9	54.4	37.6	25.1	8.4	8.4	4.2	4.2	0.0	0.0	0.0
80°	50.2	37.6	25.1	12.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	12.5	8.4	8.4	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	25.1	25.1	25.1	25.1	25.1	25.1	25.1	25.1	25.1	25.1	25.1
5°	25.1	25.1	25.1	25.1	20.9	20.9	20.9	20.9	20.9	20.9	20.9
7.5°	25.1	25.1	25.1	25.1	20.9	20.9	20.9	20.9	16.7	16.7	16.7
10°	20.9	20.9	20.9	20.9	20.9	20.9	20.9	20.9	16.7	16.7	16.7
12.5°	20.9	20.9	20.9	20.9	20.9	20.9	20.9	20.9	16.7	16.7	16.7
15°	20.9	20.9	20.9	20.9	20.9	20.9	20.9	16.7	16.7	12.5	12.5
17.5°	20.9	20.9	20.9	20.9	16.7	16.7	16.7	12.5	12.5	8.4	8.4
20°	20.9	20.9	20.9	16.7	16.7	12.5	12.5	8.4	8.4	4.2	4.2
22.5°	16.7	12.5	12.5	8.4	8.4	4.2	4.2	4.2	0.0	0.0	0.0
25°	12.5	8.4	8.4	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.4	4.2	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.4	4.2	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	25.1	20.9	20.9	20.9	20.9	20.9	20.9	20.9	20.9	20.9	20.9
5°	20.9	20.9	20.9	20.9	16.7	16.7	16.7	16.7	16.7	16.7	16.7
7.5°	16.7	16.7	16.7	16.7	16.7	16.7	12.5	12.5	12.5	12.5	12.5
10°	16.7	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	8.4	8.4
12.5°	16.7	12.5	12.5	12.5	8.4	8.4	8.4	8.4	8.4	4.2	4.2
15°	12.5	8.4	8.4	8.4	4.2	4.2	4.2	4.2	4.2	0.0	0.0
17.5°	8.4	4.2	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	20.9	20.9	20.9	20.9	20.9	20.9	20.9	20.9	20.9	25.1	25.1
5°	16.7	16.7	16.7	16.7	16.7	16.7	16.7	16.7	16.7	16.7	16.7
7.5°	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5
10°	8.4	8.4	8.4	8.4	8.4	8.4	4.2	4.2	4.2	4.2	4.2
12.5°	4.2	4.2	4.2	4.2	4.2	4.2	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	25.1	25.1	25.1	25.1	25.1	29.3	29.3	33.5	33.5	37.6	37.6
5°	16.7	16.7	20.9	20.9	20.9	20.9	25.1	25.1	25.1	29.3	29.3
7.5°	12.5	12.5	12.5	12.5	12.5	16.7	16.7	20.9	20.9	25.1	25.1
10°	4.2	4.2	8.4	8.4	8.4	8.4	12.5	12.5	12.5	16.7	20.9
12.5°	0.0	0.0	4.2	4.2	4.2	4.2	8.4	8.4	8.4	12.5	16.7
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	8.4	12.5
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	8.4
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	41.8	41.8	46.0	46.0	50.2	50.2	54.4	54.4	54.4	54.4	54.4
5°	33.5	33.5	37.6	41.8	41.8	46.0	50.2	50.2	50.2	50.2	50.2
7.5°	29.3	29.3	33.5	37.6	37.6	41.8	46.0	46.0	50.2	50.2	50.2
10°	20.9	25.1	29.3	33.5	33.5	37.6	41.8	41.8	46.0	46.0	46.0
12.5°	16.7	20.9	25.1	29.3	29.3	33.5	37.6	37.6	41.8	41.8	46.0
15°	12.5	16.7	20.9	25.1	25.1	29.3	33.5	33.5	37.6	41.8	46.0
17.5°	8.4	12.5	16.7	20.9	20.9	25.1	29.3	33.5	37.6	37.6	41.8
20°	8.4	8.4	12.5	16.7	16.7	20.9	25.1	29.3	33.5	33.5	37.6
22.5°	4.2	4.2	8.4	12.5	12.5	16.7	20.9	25.1	29.3	29.3	33.5
25°	0.0	0.0	4.2	8.4	8.4	12.5	16.7	16.7	20.9	20.9	25.1
27.5°	0.0	0.0	4.2	4.2	8.4	8.4	12.5	12.5	16.7	16.7	20.9
30°	0.0	0.0	4.2	4.2	8.4	8.4	12.5	12.5	16.7	16.7	16.7
32.5°	0.0	0.0	0.0	4.2	4.2	4.2	8.4	8.4	12.5	12.5	16.7
35°	0.0	0.0	0.0	4.2	4.2	4.2	8.4	8.4	12.5	12.5	12.5
37.5°	0.0	0.0	0.0	4.2	4.2	4.2	8.4	8.4	8.4	8.4	12.5
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	8.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	54.4	54.4
5°	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	50.2	50.2
7.5°	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	50.2	50.2
10°	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2
12.5°	46.0	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2
15°	46.0	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2
17.5°	41.8	46.0	46.0	46.0	50.2	50.2	50.2	50.2	50.2	50.2	50.2
20°	37.6	41.8	41.8	41.8	46.0	46.0	46.0	46.0	50.2	50.2	50.2
22.5°	33.5	37.6	37.6	37.6	41.8	41.8	41.8	41.8	46.0	46.0	46.0
25°	29.3	29.3	33.5	33.5	37.6	37.6	37.6	37.6	37.6	37.6	37.6
27.5°	20.9	25.1	25.1	25.1	29.3	29.3	29.3	29.3	33.5	33.5	33.5
30°	20.9	20.9	20.9	20.9	25.1	25.1	25.1	25.1	29.3	29.3	29.3
32.5°	16.7	20.9	20.9	20.9	25.1	25.1	25.1	25.1	29.3	29.3	29.3
35°	16.7	16.7	16.7	16.7	20.9	20.9	20.9	20.9	25.1	25.1	25.1
37.5°	12.5	16.7	16.7	16.7	20.9	20.9	20.9	20.9	25.1	25.1	25.1
40°	12.5	12.5	12.5	12.5	16.7	16.7	16.7	16.7	20.9	20.9	20.9
42.5°	12.5	12.5	12.5	12.5	16.7	16.7	16.7	16.7	20.9	20.9	20.9
45°	12.5	12.5	12.5	12.5	16.7	16.7	16.7	16.7	20.9	20.9	20.9
47.5°	12.5	12.5	12.5	12.5	16.7	16.7	16.7	16.7	20.9	20.9	20.9
50°	12.5	12.5	12.5	12.5	16.7	16.7	16.7	16.7	20.9	20.9	20.9
52.5°	8.4	8.4	8.4	8.4	12.5	12.5	12.5	12.5	16.7	16.7	16.7
55°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	12.5	12.5	12.5
57.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	12.5	12.5	12.5
60°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
62.5°	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
65°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	4.2	4.2
67.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
70°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
72.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
75°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
77.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
80°	12.5	12.5	12.5	12.5	12.5	8.4	8.4	8.4	8.4	8.4	8.4
82.5°	8.4	12.5	12.5	12.5	12.5	8.4	8.4	8.4	8.4	8.4	8.4
85°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
87.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	54.4	54.4	50.2	50.2	50.2	50.2	50.2	50.2	50.2	54.4	54.4
5°	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	54.4	54.4
7.5°	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	54.4	54.4
10°	50.2	50.2	50.2	50.2	46.0	46.0	50.2	50.2	50.2	54.4	54.4
12.5°	50.2	50.2	50.2	50.2	46.0	46.0	50.2	50.2	54.4	54.4	58.6
15°	50.2	50.2	46.0	46.0	46.0	46.0	50.2	50.2	54.4	54.4	58.6
17.5°	50.2	50.2	46.0	46.0	46.0	46.0	50.2	50.2	54.4	54.4	58.6
20°	50.2	50.2	46.0	46.0	46.0	46.0	46.0	46.0	50.2	54.4	54.4
22.5°	46.0	46.0	46.0	46.0	41.8	41.8	46.0	46.0	50.2	54.4	54.4
25°	37.6	41.8	41.8	41.8	41.8	41.8	46.0	46.0	50.2	54.4	54.4
27.5°	33.5	37.6	37.6	37.6	37.6	41.8	41.8	46.0	50.2	54.4	54.4
30°	29.3	33.5	33.5	33.5	37.6	41.8	41.8	46.0	50.2	54.4	54.4
32.5°	29.3	33.5	33.5	33.5	37.6	37.6	41.8	41.8	46.0	50.2	54.4
35°	29.3	29.3	33.5	33.5	33.5	37.6	37.6	41.8	46.0	50.2	54.4
37.5°	29.3	29.3	33.5	33.5	33.5	37.6	37.6	41.8	46.0	50.2	54.4
40°	25.1	29.3	29.3	33.5	33.5	37.6	37.6	41.8	46.0	54.4	58.6
42.5°	25.1	25.1	29.3	29.3	33.5	37.6	37.6	41.8	46.0	54.4	58.6
45°	25.1	29.3	29.3	33.5	37.6	41.8	41.8	46.0	50.2	54.4	58.6
47.5°	25.1	29.3	29.3	33.5	41.8	41.8	46.0	46.0	50.2	54.4	58.6
50°	25.1	29.3	29.3	33.5	46.0	46.0	46.0	46.0	50.2	54.4	58.6
52.5°	20.9	25.1	25.1	29.3	37.6	41.8	46.0	50.2	54.4	58.6	62.7
55°	16.7	20.9	20.9	25.1	33.5	37.6	46.0	54.4	58.6	62.7	66.9
57.5°	16.7	16.7	20.9	20.9	29.3	37.6	50.2	58.6	62.7	66.9	71.1
60°	12.5	12.5	16.7	16.7	25.1	33.5	46.0	58.6	62.7	71.1	75.3
62.5°	8.4	12.5	12.5	16.7	20.9	33.5	46.0	58.6	66.9	75.3	79.5
65°	8.4	8.4	12.5	12.5	20.9	29.3	41.8	50.2	62.7	75.3	87.8
67.5°	12.5	12.5	16.7	16.7	20.9	29.3	41.8	50.2	62.7	79.5	92.0
70°	12.5	12.5	16.7	16.7	25.1	33.5	41.8	50.2	62.7	79.5	92.0
72.5°	12.5	12.5	16.7	16.7	25.1	29.3	37.6	46.0	58.6	71.1	83.6
75°	8.4	12.5	12.5	12.5	20.9	25.1	33.5	41.8	54.4	66.9	79.5
77.5°	8.4	8.4	8.4	8.4	16.7	20.9	29.3	33.5	46.0	58.6	71.1
80°	8.4	8.4	8.4	8.4	12.5	16.7	25.1	29.3	41.8	54.4	66.9
82.5°	8.4	8.4	4.2	4.2	8.4	12.5	16.7	20.9	33.5	41.8	54.4
85°	8.4	8.4	4.2	4.2	4.2	8.4	8.4	12.5	16.7	20.9	25.1
87.5°	8.4	8.4	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	54.4	54.4	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6
5°	54.4	58.6	58.6	62.7	62.7	62.7	66.9	66.9	66.9	66.9	66.9
7.5°	54.4	58.6	58.6	62.7	62.7	62.7	66.9	66.9	66.9	71.1	71.1
10°	54.4	58.6	58.6	62.7	62.7	66.9	71.1	71.1	75.3	75.3	75.3
12.5°	58.6	62.7	62.7	66.9	66.9	71.1	75.3	75.3	79.5	83.6	83.6
15°	58.6	62.7	66.9	66.9	71.1	75.3	79.5	79.5	83.6	87.8	92.0
17.5°	58.6	62.7	66.9	66.9	71.1	75.3	83.6	87.8	92.0	100.4	104.6
20°	58.6	62.7	66.9	66.9	71.1	79.5	83.6	92.0	96.2	104.6	112.9
22.5°	58.6	62.7	66.9	71.1	75.3	83.6	92.0	96.2	104.6	117.1	125.5
25°	58.6	62.7	66.9	71.1	75.3	83.6	92.0	100.4	108.7	125.5	142.2
27.5°	58.6	62.7	71.1	75.3	79.5	87.8	100.4	108.7	117.1	146.4	175.7
30°	58.6	62.7	71.1	75.3	79.5	92.0	104.6	112.9	125.5	175.7	221.7
32.5°	58.6	66.9	71.1	79.5	83.6	96.2	112.9	125.5	138.0	209.1	276.0
35°	58.6	66.9	71.1	79.5	83.6	100.4	117.1	133.8	150.6	255.1	359.7
37.5°	58.6	66.9	71.1	79.5	83.6	108.7	133.8	158.9	184.0	292.8	401.5
40°	62.7	71.1	75.3	83.6	87.8	112.9	138.0	163.1	188.2	297.0	405.7
42.5°	62.7	71.1	75.3	83.6	87.8	108.7	133.8	154.8	175.7	297.0	418.2
45°	62.7	71.1	79.5	83.6	92.0	112.9	133.8	150.6	171.5	326.2	476.8
47.5°	62.7	71.1	79.5	83.6	92.0	112.9	133.8	154.8	175.7	430.8	681.7
50°	62.7	71.1	79.5	83.6	92.0	117.1	142.2	167.3	192.4	644.1	1095.8
52.5°	66.9	71.1	79.5	83.6	87.8	117.1	146.4	175.7	204.9	836.5	1463.9
55°	71.1	75.3	79.5	83.6	87.8	125.5	163.1	200.8	238.4	899.2	1555.9
57.5°	75.3	79.5	83.6	83.6	87.8	133.8	184.0	230.0	276.0	895.0	1509.9
60°	79.5	83.6	87.8	92.0	96.2	142.2	192.4	238.4	284.4	811.4	1338.4
62.5°	87.8	96.2	104.6	108.7	117.1	163.1	204.9	250.9	292.8	665.0	1033.1
65°	100.4	108.7	112.9	121.3	125.5	167.3	213.3	255.1	297.0	552.1	803.0
67.5°	104.6	112.9	117.1	125.5	129.7	171.5	213.3	255.1	297.0	468.4	635.7
70°	104.6	112.9	121.3	125.5	133.8	175.7	213.3	255.1	292.8	405.7	518.6
72.5°	96.2	108.7	117.1	129.7	138.0	175.7	209.1	246.8	280.2	359.7	439.2
75°	92.0	108.7	121.3	138.0	150.6	175.7	204.9	230.0	255.1	313.7	372.2
77.5°	83.6	104.6	125.5	146.4	167.3	184.0	196.6	213.3	225.9	263.5	301.1
80°	79.5	100.4	121.3	142.2	163.1	171.5	175.7	184.0	188.2	192.4	196.6
82.5°	62.7	79.5	96.2	108.7	125.5	117.1	112.9	104.6	96.2	92.0	87.8
85°	29.3	33.5	33.5	37.6	37.6	37.6	33.5	33.5	29.3	25.1	20.9
87.5°	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	58.6	58.6	58.6	58.6	54.4	54.4	54.4	54.4	50.2	50.2	50.2
5°	66.9	66.9	66.9	66.9	62.7	62.7	62.7	62.7	58.6	58.6	58.6
7.5°	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1
10°	79.5	79.5	79.5	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6
12.5°	87.8	87.8	92.0	92.0	96.2	96.2	100.4	100.4	104.6	104.6	104.6
15°	96.2	100.4	104.6	108.7	108.7	112.9	117.1	121.3	125.5	129.7	133.8
17.5°	112.9	117.1	125.5	133.8	142.2	150.6	163.1	179.8	192.4	204.9	221.7
20°	125.5	138.0	163.1	192.4	217.5	242.6	305.3	368.1	430.8	493.5	556.3
22.5°	150.6	175.7	259.3	347.1	430.8	514.4	711.0	907.6	1100.0	1296.6	1472.2
25°	200.8	255.1	447.5	639.9	828.1	1020.5	1371.8	1727.4	2078.7	2430.0	2756.2
27.5°	276.0	376.4	690.1	1008.0	1321.7	1635.3	2145.6	2660.0	3170.3	3684.8	4140.6
30°	384.8	547.9	1016.3	1489.0	1957.4	2425.8	3069.9	3718.2	4362.3	5006.4	5424.7
32.5°	522.8	765.4	1359.3	1953.2	2547.1	3141.0	3852.1	4563.1	5269.9	5980.9	6424.3
35°	669.2	978.7	1693.9	2413.3	3128.5	3847.9	4596.5	5345.2	6093.9	6842.5	7386.2
37.5°	752.8	1104.2	1953.2	2802.3	3647.1	4496.1	5315.9	6139.9	6959.6	7779.4	8440.2
40°	832.3	1254.7	2233.4	3212.1	4190.8	5169.5	6127.3	7085.1	8042.9	9000.7	9849.7
42.5°	949.4	1480.6	2622.4	3764.2	4901.8	6043.7	7302.6	8565.7	9824.6	11083.5	12388.5
45°	1192.0	1907.2	3387.8	4868.4	6344.8	7825.4	9611.3	11401.4	13187.3	14977.4	16650.4
47.5°	1777.5	2869.2	4889.3	6909.4	8929.6	10949.7	13007.5	15065.2	17123.0	19180.8	21171.6
50°	2752.1	4404.1	6930.3	9456.6	11978.6	14504.8	16558.4	18612.0	20661.4	22715.0	24693.3
52.5°	3668.0	5872.2	8586.6	11305.2	14019.6	16738.2	18557.6	20377.0	22196.3	24015.7	25931.3
55°	3981.7	6403.4	9151.2	11903.3	14651.2	17403.2	19155.7	20912.3	22664.8	24417.2	26403.9
57.5°	3705.7	5901.5	8670.2	11439.0	14203.7	16972.4	18929.8	20891.4	22848.8	24810.4	26939.3
60°	3103.4	4864.2	7771.0	10682.0	13588.8	16495.6	18704.0	20912.3	23120.7	25329.0	27453.7
62.5°	2459.3	3881.3	6959.6	10037.9	13116.2	16194.5	18440.5	20690.7	22936.6	25182.6	26813.8
65°	1886.3	2969.6	5997.7	9029.9	12058.0	15090.3	16930.6	18775.1	20615.4	22459.8	23589.1
67.5°	1401.1	2166.5	4814.0	7465.7	10113.2	12760.7	14115.8	15475.1	16830.2	18189.5	19067.9
70°	1033.1	1543.3	3346.0	5148.6	6947.1	8749.7	9991.9	11234.1	12472.1	13714.3	14626.1
72.5°	715.2	987.1	2066.1	3149.4	4228.5	5307.5	6566.5	7825.4	9080.1	10339.1	11376.3
75°	489.3	606.5	1112.5	1618.6	2124.7	2630.8	3584.4	4538.0	5491.6	6445.2	6993.1
77.5°	363.9	426.6	577.2	731.9	882.5	1033.1	1217.1	1401.1	1585.2	1769.2	2007.6
80°	200.8	200.8	221.7	238.4	259.3	276.0	326.2	380.6	430.8	485.2	552.1
82.5°	92.0	96.2	104.6	112.9	117.1	125.5	133.8	142.2	150.6	158.9	158.9
85°	25.1	29.3	29.3	25.1	25.1	20.9	20.9	25.1	25.1	25.1	25.1
87.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	50.2	46.0	46.0	46.0	41.8	41.8	41.8	41.8	41.8	41.8	41.8
5°	58.6	58.6	58.6	58.6	54.4	54.4	54.4	54.4	54.4	50.2	50.2
7.5°	71.1	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	62.7	62.7
10°	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	79.5	79.5
12.5°	104.6	104.6	104.6	104.6	108.7	108.7	104.6	104.6	104.6	100.4	100.4
15°	138.0	142.2	146.4	146.4	150.6	150.6	150.6	146.4	146.4	142.2	138.0
17.5°	234.2	246.8	263.5	280.2	297.0	309.5	309.5	301.1	292.8	284.4	276.0
20°	623.2	685.9	752.8	819.8	890.9	941.1	907.6	882.5	857.4	828.1	803.0
22.5°	1652.1	1827.7	2007.6	2133.1	2258.5	2346.4	2275.3	2137.2	1999.2	1865.4	1727.4
25°	3082.5	3404.5	3730.8	3864.6	4002.6	4103.0	4057.0	3847.9	3638.7	3433.8	3224.7
27.5°	4596.5	5048.2	5504.1	5621.2	5738.3	5826.2	5809.4	5537.6	5265.7	4993.9	4722.0
30°	5842.9	6261.2	6679.4	6796.5	6913.6	6993.1	6905.2	6633.4	6361.5	6089.7	5817.8
32.5°	6871.8	7315.1	7762.7	7917.4	8072.2	8176.7	8072.2	7745.9	7419.7	7097.6	6771.4
35°	7930.0	8469.5	9013.2	9209.8	9406.4	9531.8	9356.2	8954.7	8553.1	8155.8	7754.3
37.5°	9101.0	9757.7	10418.5	10686.2	10958.1	11146.3	11012.4	10510.5	10004.5	9502.6	8996.5
40°	10702.9	11552.0	12405.2	12886.2	13363.0	13701.8	13463.4	12882.0	12296.4	11715.1	11129.5
42.5°	13697.6	15002.5	16307.4	16997.5	17683.5	18181.2	17913.5	17198.3	16483.1	15767.9	15052.7
45°	18323.4	19992.2	21665.2	22673.1	23685.3	24429.8	24120.3	23221.0	22317.6	21418.4	20519.2
47.5°	23162.5	25153.3	27144.2	27947.2	28754.4	29381.8	29306.5	28185.6	27064.7	25948.0	24827.1
50°	26675.8	28654.1	30632.4	31322.5	32016.8	32531.2	32338.8	30912.6	29482.2	28056.0	26625.6
52.5°	27846.9	29758.2	31673.8	32497.8	33321.7	33936.5	33702.3	32096.2	30490.2	28888.3	27282.2
55°	28390.6	30377.2	32363.9	33367.7	34375.7	35111.8	34773.0	33012.2	31247.2	29486.4	27721.4
57.5°	29068.1	31197.0	33325.9	34425.9	35525.9	36320.5	35868.8	34045.3	32221.7	30402.3	28578.8
60°	29578.4	31698.9	33823.6	34706.1	35592.8	36211.8	35776.8	34003.4	32225.9	30452.5	28679.2
62.5°	28449.1	30080.3	31711.4	32368.1	33024.7	33501.5	33254.8	31573.4	29892.1	28210.7	26529.4
65°	24722.6	25851.8	26985.3	27428.6	27867.8	28206.5	28131.3	26713.4	25295.5	23881.9	22464.0
67.5°	19950.4	20828.7	21711.2	22338.5	22970.1	23459.4	23405.1	22112.7	20820.3	19527.9	18235.5
70°	15542.0	16453.8	17365.6	18156.1	18950.7	19565.6	19486.1	18285.7	17081.2	15880.8	14676.3
72.5°	12417.7	13455.0	14492.2	14943.9	15395.7	15713.5	15479.3	14571.7	13659.9	12752.3	11840.6
75°	7541.0	8084.7	8632.6	8628.4	8628.4	8578.2	8344.0	7825.4	7306.8	6788.1	6269.5
77.5°	2246.0	2484.4	2722.8	2952.8	3187.0	3362.7	3316.7	3044.8	2768.8	2496.9	2220.9
80°	619.0	681.7	748.7	777.9	807.2	844.9	941.1	874.1	807.2	744.5	677.6
82.5°	158.9	158.9	158.9	154.8	150.6	142.2	129.7	121.3	112.9	104.6	96.2
85°	25.1	20.9	20.9	20.9	16.7	16.7	16.7	16.7	12.5	12.5	8.4
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
2.5°	41.8	41.8	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6	33.5
5°	50.2	50.2	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	41.8
7.5°	62.7	62.7	58.6	58.6	58.6	58.6	54.4	54.4	54.4	54.4	50.2
10°	79.5	75.3	75.3	71.1	71.1	71.1	66.9	66.9	66.9	62.7	62.7
12.5°	100.4	96.2	96.2	92.0	87.8	87.8	83.6	79.5	75.3	75.3	71.1
15°	133.8	129.7	125.5	121.3	117.1	108.7	104.6	96.2	92.0	87.8	83.6
17.5°	255.1	234.2	213.3	192.4	175.7	158.9	142.2	125.5	117.1	108.7	100.4
20°	711.0	614.8	522.8	430.8	372.2	313.7	255.1	196.6	171.5	150.6	125.5
22.5°	1539.1	1346.8	1158.5	966.1	811.4	660.8	506.1	351.3	292.8	238.4	179.8
25°	2860.8	2492.7	2128.9	1760.8	1468.0	1175.3	882.5	589.7	481.0	372.2	263.5
27.5°	4245.2	3768.4	3291.6	2814.8	2350.5	1882.1	1413.7	949.4	761.2	577.2	389.0
30°	5311.7	4805.7	4303.8	3797.7	3212.1	2626.6	2036.9	1451.3	1154.4	857.4	556.3
32.5°	6227.7	5679.8	5136.1	4588.2	3910.6	3233.0	2555.5	1877.9	1505.7	1133.4	757.0
35°	7135.3	6512.1	5893.1	5269.9	4542.2	3814.4	3086.7	2358.9	1886.3	1413.7	936.9
37.5°	8239.5	7478.2	6721.2	5964.2	5215.5	4471.1	3722.4	2973.7	2371.5	1773.4	1171.1
40°	10163.4	9193.1	8226.9	7256.6	6382.4	5512.5	4638.4	3764.2	3007.2	2250.2	1489.0
42.5°	13835.6	12618.5	11405.6	10188.5	8979.8	7771.0	6558.1	5349.4	4270.3	3195.4	2116.3
45°	18959.1	17399.1	15843.2	14283.1	12794.2	11309.4	9820.4	8331.5	6691.9	5052.4	3408.7
47.5°	23120.7	21410.0	19703.6	17993.0	16340.9	14693.0	13040.9	11388.9	9289.3	7193.8	5094.2
50°	24998.6	23367.4	21740.5	20109.3	18453.0	16792.6	15132.2	13475.9	11066.8	8661.9	6252.8
52.5°	25630.1	23973.9	22321.8	20665.6	19021.9	17378.1	15734.4	14090.7	11585.4	9084.3	6579.0
55°	25977.3	24229.0	22484.9	20736.7	18967.5	17194.1	15420.7	13651.6	11158.8	8670.2	6177.5
57.5°	26679.9	24776.9	22878.1	20975.1	18959.1	16943.2	14923.0	12907.1	10447.8	7988.5	5529.2
60°	26809.6	24935.9	23066.3	21196.7	18967.5	16738.2	14504.8	12275.5	9833.0	7394.6	4952.0
62.5°	24965.1	23400.9	21840.8	20276.6	18043.2	15809.7	13572.1	11338.7	9000.7	6662.7	4320.5
65°	21113.1	19762.1	18415.4	17064.5	15240.9	13421.5	11598.0	9774.4	7687.4	5604.5	3517.5
67.5°	16913.9	15592.2	14274.8	12953.1	11581.2	10213.6	8841.7	7469.9	5859.6	4249.4	2639.1
70°	13409.0	12137.5	10870.2	9598.8	8385.8	7168.7	5951.6	4738.7	3739.1	2743.7	1744.1
72.5°	10627.6	9410.5	8197.6	6980.5	5880.5	4780.6	3680.6	2580.6	2082.9	1589.3	1091.6
75°	5638.0	5006.4	4379.0	3747.5	3128.5	2505.3	1882.1	1263.1	1066.5	870.0	669.2
77.5°	1944.8	1668.8	1396.9	1120.9	932.7	744.5	556.3	368.1	347.1	330.4	309.5
80°	589.7	501.9	414.1	326.2	288.6	250.9	213.3	175.7	163.1	150.6	133.8
82.5°	92.0	83.6	79.5	71.1	66.9	66.9	62.7	58.6	50.2	46.0	37.6
85°	8.4	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066658
 CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	37.6	37.6
2.5°	33.5	33.5
5°	41.8	41.8
7.5°	50.2	50.2
10°	58.6	58.6
12.5°	66.9	66.9
15°	79.5	75.3
17.5°	92.0	87.8
20°	100.4	92.0
22.5°	121.3	104.6
25°	154.8	129.7
27.5°	200.8	158.9
30°	259.3	200.8
32.5°	384.8	280.2
35°	464.3	338.8
37.5°	568.8	393.2
40°	731.9	476.8
42.5°	1037.3	648.3
45°	1769.2	1074.9
47.5°	2998.8	1831.9
50°	3843.7	2350.5
52.5°	4077.9	2492.7
55°	3688.9	2287.8
57.5°	3069.9	1944.8
60°	2513.7	1601.9
62.5°	1982.5	1267.3
65°	1430.4	957.8
67.5°	1028.9	736.1
70°	748.7	577.2
72.5°	593.9	481.0
75°	472.6	401.5
77.5°	292.8	267.7
80°	121.3	112.9
82.5°	29.3	25.1
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066658

CATALOG NUMBER: NVN-SA4B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-10

Test Date: 10/11/2024

Luminaire Tested: GSS-SB1A-835-U-5WQ

Data in this report applies to families of products including GSS-SB1A-835-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-10
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-835-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3411
 CIE u' : 0.2360
 CIE v' : 0.5189
 Duv: 0.0044
 CIE x: 0.4154
 CIE y: 0.4059
 CIE z: 0.1787
 Peak Wavelength (nm): 601
 Dominant Wavelength (nm): 579
 Purity: 46.51914
 R_f: 86.6
 R_g: 95.9

CRI (Ra): 83.5
 R1: 81.1
 R2: 88.9
 R3: 97.2
 R4: 83.8
 R5: 81.7
 R6: 86.9
 R7: 86.1
 R8: 62.2
 R9: 6.3
 R10: 75.4
 R11: 84.1
 R12: 69.7
 R13: 82.8
 R14: 98.5
 R15: 72.6



Test Conditions


Stabilization Time: 35M
 Operation Time: 1H 35M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-10

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-10

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)	λ (nm)	Power W/nm	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.48

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Melanopic Flux vs. Wavelength

Melanopic Lumens: NR
M/P: 2.88


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10





TM-30-18

Summary

$R_f = 86.6$
 $R_g = 95.9$
 $CIE R_a = 83.5$
 $R_9 = 6.3$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 85	CES51 = 97	CES76 = 81
CES02 = 62	CES27 = 95	CES52 = 96	CES77 = 87
CES03 = 31	CES28 = 94	CES53 = 91	CES78 = 80
CES04 = 70	CES29 = 87	CES54 = 92	CES79 = 93
CES05 = 49	CES30 = 93	CES55 = 92	CES80 = 91
CES06 = 51	CES31 = 89	CES56 = 88	CES81 = 77
CES07 = 41	CES32 = 84	CES57 = 87	CES82 = 96
CES08 = 40	CES33 = 91	CES58 = 88	CES83 = 95
CES09 = 29	CES34 = 91	CES59 = 93	CES84 = 92
CES10 = 75	CES35 = 95	CES60 = 94	CES85 = 80
CES11 = 58	CES36 = 90	CES61 = 91	CES86 = 72
CES12 = 64	CES37 = 95	CES62 = 95	CES87 = 86
CES13 = 43	CES38 = 100	CES63 = 88	CES88 = 88
CES14 = 74	CES39 = 97	CES64 = 85	CES89 = 77
CES15 = 71	CES40 = 94	CES65 = 80	CES90 = 88
CES16 = 47	CES41 = 97	CES66 = 84	CES91 = 81
CES17 = 49	CES42 = 96	CES67 = 82	CES92 = 67
CES18 = 56	CES43 = 93	CES68 = 85	CES93 = 81
CES19 = 72	CES44 = 99	CES69 = 89	CES94 = 63
CES20 = 66	CES45 = 95	CES70 = 81	CES95 = 76
CES21 = 86	CES46 = 91	CES71 = 79	CES96 = 84
CES22 = 78	CES47 = 93	CES72 = 93	CES97 = 92
CES23 = 91	CES48 = 85	CES73 = 76	CES98 = 86
CES24 = 90	CES49 = 92	CES74 = 95	CES99 = 77
CES25 = 72	CES50 = 96	CES75 = 80	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)