

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066661

Luminaire Tested: **NVN-SA5A-835-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066661
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5A-835-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 615mA 5xLight Square PACKAGE
80CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 3500K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 13431.2 lumens
Efficiency: N/A
Efficacy: 97.8 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 137.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 2.7 fc
 Type III - Short - N/A

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	79.9	0.0	79.9
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	13351.3	0.0	13351.3
	% Fixture	99.4	0.0	99.4
Total	Lumens	13431.2	0.0	13431.2
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	4.0	0.0
10°-20°	19.7	0.1
20°-30°	250.7	1.9
30°-40°	844.9	6.3
40°-50°	2551.5	19.0
50°-60°	4501.7	33.5
60°-70°	3966.0	29.5
70°-80°	1262.5	9.4
80°-90°	30.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	13431.2	100.0
0°-180°	13431.2	100.0



REPORT NUMBER: P1066661


CATALOG NUMBER: NVN-SA5A-835-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	262.4	2.0			
FM	(30°-60°)	7867.1	58.6			
FH	(60°-80°)	5197.2	38.7			G3/7500
FVH	(80°-90°)	24.7	0.2			G1/100
BL	(0°-30°)	12.0	0.1	B0/110		
BM	(30°-60°)	31.0	0.2	B0/220		
BH	(60°-80°)	31.3	0.2	B0/110		G0/110
BVH	(80°-90°)	5.7	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	29.5
5°	42.1	42.1	42.1	37.9	37.9	37.9	33.7	33.7	33.7	33.7	33.7
7.5°	50.5	46.3	46.3	42.1	42.1	42.1	37.9	37.9	37.9	37.9	33.7
10°	59.0	54.8	54.8	50.5	50.5	46.3	46.3	42.1	42.1	37.9	37.9
12.5°	67.4	63.2	59.0	54.8	54.8	50.5	50.5	46.3	46.3	42.1	42.1
15°	75.8	71.6	67.4	63.2	59.0	59.0	54.8	50.5	46.3	46.3	42.1
17.5°	88.5	80.0	75.8	67.4	63.2	59.0	54.8	50.5	50.5	46.3	46.3
20°	92.7	84.2	80.0	71.6	67.4	63.2	59.0	54.8	50.5	50.5	46.3
22.5°	109.5	92.7	88.5	80.0	75.8	71.6	63.2	59.0	54.8	50.5	46.3
25°	134.8	109.5	96.9	84.2	80.0	71.6	67.4	59.0	54.8	50.5	46.3
27.5°	164.3	122.1	109.5	92.7	84.2	75.8	67.4	59.0	54.8	50.5	46.3
30°	202.2	143.2	122.1	101.1	92.7	84.2	71.6	63.2	59.0	54.8	46.3
32.5°	282.2	176.9	143.2	109.5	96.9	88.5	75.8	63.2	59.0	54.8	46.3
35°	341.2	214.8	172.7	126.4	109.5	96.9	80.0	63.2	59.0	54.8	46.3
37.5°	395.9	219.0	176.9	134.8	117.9	101.1	80.0	63.2	59.0	54.8	46.3
40°	484.4	227.4	176.9	126.4	113.7	96.9	84.2	67.4	63.2	54.8	50.5
42.5°	652.9	261.1	189.5	117.9	105.3	96.9	84.2	71.6	63.2	59.0	50.5
45°	1086.7	387.5	256.9	122.1	109.5	96.9	84.2	71.6	67.4	59.0	54.8
47.5°	1849.1	673.9	400.1	126.4	113.7	96.9	84.2	67.4	63.2	59.0	50.5
50°	2367.2	863.5	505.4	147.4	126.4	109.5	88.5	67.4	63.2	59.0	54.8
52.5°	2514.6	918.2	547.6	172.7	147.4	122.1	92.7	67.4	63.2	63.2	59.0
55°	2304.0	893.0	547.6	202.2	168.5	139.0	105.3	71.6	67.4	67.4	63.2
57.5°	1958.6	825.6	522.3	219.0	185.3	147.4	113.7	75.8	71.6	71.6	67.4
60°	1613.2	695.0	471.7	244.3	206.4	168.5	130.6	92.7	88.5	84.2	75.8
62.5°	1280.5	560.2	412.8	261.1	223.2	181.1	143.2	101.1	96.9	92.7	88.5
65°	964.6	488.6	383.3	273.8	231.7	189.5	147.4	105.3	101.1	101.1	96.9
67.5°	741.3	446.5	366.4	282.2	240.1	198.0	155.8	113.7	109.5	105.3	101.1
70°	585.5	412.8	345.4	278.0	240.1	202.2	160.1	122.1	113.7	109.5	101.1
72.5°	488.6	374.9	320.1	265.4	235.9	206.4	176.9	147.4	130.6	117.9	101.1
75°	408.6	337.0	290.6	240.1	219.0	202.2	181.1	160.1	139.0	117.9	96.9
77.5°	269.6	244.3	223.2	202.2	189.5	176.9	160.1	147.4	126.4	109.5	88.5
80°	113.7	105.3	109.5	109.5	109.5	109.5	105.3	105.3	92.7	80.0	63.2
82.5°	25.3	21.1	25.3	25.3	25.3	25.3	21.1	21.1	21.1	16.8	16.8
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	29.5	29.5	29.5	29.5	29.5	29.5	29.5	29.5	29.5	29.5	29.5
5°	33.7	33.7	33.7	29.5	29.5	29.5	29.5	29.5	29.5	29.5	29.5
7.5°	33.7	33.7	33.7	29.5	29.5	29.5	29.5	25.3	25.3	25.3	25.3
10°	33.7	33.7	33.7	29.5	29.5	29.5	29.5	25.3	25.3	25.3	25.3
12.5°	37.9	37.9	33.7	33.7	29.5	29.5	29.5	25.3	25.3	25.3	25.3
15°	37.9	37.9	33.7	33.7	29.5	29.5	29.5	25.3	25.3	25.3	25.3
17.5°	42.1	37.9	37.9	33.7	29.5	29.5	29.5	25.3	25.3	25.3	25.3
20°	42.1	37.9	37.9	33.7	29.5	29.5	29.5	25.3	25.3	25.3	25.3
22.5°	42.1	37.9	37.9	33.7	29.5	29.5	25.3	25.3	21.1	21.1	16.8
25°	42.1	37.9	37.9	33.7	29.5	29.5	25.3	25.3	21.1	16.8	16.8
27.5°	42.1	37.9	37.9	33.7	29.5	25.3	25.3	21.1	16.8	12.6	12.6
30°	42.1	37.9	37.9	33.7	29.5	25.3	21.1	16.8	12.6	12.6	8.4
32.5°	42.1	37.9	33.7	29.5	25.3	21.1	21.1	16.8	12.6	8.4	8.4
35°	42.1	37.9	33.7	29.5	25.3	21.1	21.1	16.8	12.6	8.4	8.4
37.5°	42.1	37.9	33.7	29.5	25.3	21.1	16.8	12.6	8.4	8.4	4.2
40°	42.1	37.9	33.7	29.5	25.3	21.1	16.8	12.6	8.4	8.4	4.2
42.5°	42.1	37.9	33.7	29.5	25.3	21.1	16.8	12.6	8.4	8.4	4.2
45°	46.3	42.1	37.9	29.5	25.3	21.1	21.1	16.8	12.6	8.4	8.4
47.5°	46.3	42.1	37.9	29.5	25.3	21.1	21.1	16.8	12.6	8.4	8.4
50°	50.5	46.3	42.1	33.7	29.5	25.3	21.1	12.6	8.4	8.4	4.2
52.5°	54.8	50.5	46.3	42.1	37.9	29.5	21.1	12.6	4.2	4.2	4.2
55°	59.0	54.8	54.8	50.5	46.3	33.7	25.3	12.6	0.0	0.0	0.0
57.5°	63.2	59.0	59.0	54.8	50.5	37.9	25.3	12.6	0.0	0.0	0.0
60°	71.6	67.4	63.2	54.8	50.5	37.9	25.3	12.6	0.0	0.0	0.0
62.5°	84.2	75.8	63.2	54.8	42.1	33.7	21.1	12.6	0.0	0.0	0.0
65°	92.7	80.0	67.4	50.5	37.9	29.5	21.1	8.4	0.0	0.0	0.0
67.5°	96.9	80.0	67.4	50.5	33.7	25.3	16.8	8.4	0.0	0.0	0.0
70°	92.7	75.8	63.2	46.3	29.5	21.1	16.8	8.4	0.0	0.0	0.0
72.5°	84.2	71.6	54.8	42.1	25.3	21.1	12.6	8.4	0.0	0.0	0.0
75°	75.8	63.2	46.3	33.7	16.8	12.6	8.4	4.2	0.0	0.0	0.0
77.5°	67.4	54.8	37.9	25.3	8.4	8.4	4.2	4.2	0.0	0.0	0.0
80°	50.5	37.9	25.3	12.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	12.6	8.4	8.4	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3	25.3
5°	25.3	25.3	25.3	25.3	21.1	21.1	21.1	21.1	21.1	21.1	21.1
7.5°	25.3	25.3	25.3	25.3	21.1	21.1	21.1	21.1	16.8	16.8	16.8
10°	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	16.8	16.8	16.8
12.5°	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	16.8	16.8	16.8
15°	21.1	21.1	21.1	21.1	21.1	21.1	21.1	16.8	16.8	12.6	12.6
17.5°	21.1	21.1	21.1	21.1	16.8	16.8	16.8	12.6	12.6	8.4	8.4
20°	21.1	21.1	21.1	16.8	16.8	12.6	12.6	8.4	8.4	4.2	4.2
22.5°	16.8	12.6	12.6	8.4	8.4	4.2	4.2	4.2	0.0	0.0	0.0
25°	12.6	8.4	8.4	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	8.4	4.2	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	8.4	4.2	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	25.3	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1
5°	21.1	21.1	21.1	21.1	16.8	16.8	16.8	16.8	16.8	16.8	16.8
7.5°	16.8	16.8	16.8	16.8	16.8	16.8	12.6	12.6	12.6	12.6	12.6
10°	16.8	12.6	12.6	12.6	12.6	12.6	12.6	12.6	12.6	8.4	8.4
12.5°	16.8	12.6	12.6	12.6	8.4	8.4	8.4	8.4	8.4	4.2	4.2
15°	12.6	8.4	8.4	8.4	4.2	4.2	4.2	4.2	4.2	0.0	0.0
17.5°	8.4	4.2	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	25.3	25.3
5°	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8
7.5°	12.6	12.6	12.6	12.6	12.6	12.6	12.6	12.6	12.6	12.6	12.6
10°	8.4	8.4	8.4	8.4	8.4	8.4	4.2	4.2	4.2	4.2	4.2
12.5°	4.2	4.2	4.2	4.2	4.2	4.2	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	25.3	25.3	25.3	25.3	25.3	29.5	29.5	33.7	33.7	37.9	37.9
5°	16.8	16.8	21.1	21.1	21.1	21.1	25.3	25.3	25.3	29.5	29.5
7.5°	12.6	12.6	12.6	12.6	12.6	16.8	16.8	21.1	21.1	25.3	25.3
10°	4.2	4.2	8.4	8.4	8.4	8.4	12.6	12.6	12.6	16.8	21.1
12.5°	0.0	0.0	4.2	4.2	4.2	4.2	8.4	8.4	8.4	12.6	16.8
15°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	8.4	12.6
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	8.4
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	42.1	42.1	46.3	46.3	50.5	50.5	54.8	54.8	54.8	54.8	54.8
5°	33.7	33.7	37.9	42.1	42.1	46.3	50.5	50.5	50.5	50.5	50.5
7.5°	29.5	29.5	33.7	37.9	37.9	42.1	46.3	46.3	50.5	50.5	50.5
10°	21.1	25.3	29.5	33.7	33.7	37.9	42.1	42.1	46.3	46.3	46.3
12.5°	16.8	21.1	25.3	29.5	29.5	33.7	37.9	37.9	42.1	42.1	46.3
15°	12.6	16.8	21.1	25.3	25.3	29.5	33.7	33.7	37.9	42.1	46.3
17.5°	8.4	12.6	16.8	21.1	21.1	25.3	29.5	33.7	37.9	37.9	42.1
20°	8.4	8.4	12.6	16.8	16.8	21.1	25.3	29.5	33.7	33.7	37.9
22.5°	4.2	4.2	8.4	12.6	12.6	16.8	21.1	25.3	29.5	29.5	33.7
25°	0.0	0.0	4.2	8.4	8.4	12.6	16.8	16.8	21.1	21.1	25.3
27.5°	0.0	0.0	4.2	4.2	8.4	8.4	12.6	12.6	16.8	16.8	21.1
30°	0.0	0.0	4.2	4.2	8.4	8.4	12.6	12.6	16.8	16.8	16.8
32.5°	0.0	0.0	0.0	4.2	4.2	4.2	8.4	8.4	12.6	12.6	16.8
35°	0.0	0.0	0.0	4.2	4.2	4.2	8.4	8.4	12.6	12.6	12.6
37.5°	0.0	0.0	0.0	4.2	4.2	4.2	8.4	8.4	8.4	8.4	12.6
40°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
45°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
50°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
55°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2
75°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
80°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	8.4	8.4	8.4
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	8.4
85°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	4.2	4.2	4.2	4.2	4.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0	54.8	54.8
5°	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	50.5	50.5
7.5°	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	50.5	50.5
10°	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5
12.5°	46.3	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5
15°	46.3	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5
17.5°	42.1	46.3	46.3	46.3	50.5	50.5	50.5	50.5	50.5	50.5	50.5
20°	37.9	42.1	42.1	42.1	46.3	46.3	46.3	46.3	50.5	50.5	50.5
22.5°	33.7	37.9	37.9	37.9	42.1	42.1	42.1	42.1	46.3	46.3	46.3
25°	29.5	29.5	33.7	33.7	37.9	37.9	37.9	37.9	37.9	37.9	37.9
27.5°	21.1	25.3	25.3	25.3	29.5	29.5	29.5	29.5	33.7	33.7	33.7
30°	21.1	21.1	21.1	21.1	25.3	25.3	25.3	25.3	29.5	29.5	29.5
32.5°	16.8	21.1	21.1	21.1	25.3	25.3	25.3	25.3	29.5	29.5	29.5
35°	16.8	16.8	16.8	16.8	21.1	21.1	21.1	21.1	25.3	25.3	25.3
37.5°	12.6	16.8	16.8	16.8	21.1	21.1	21.1	21.1	25.3	25.3	25.3
40°	12.6	12.6	12.6	12.6	16.8	16.8	16.8	16.8	21.1	21.1	21.1
42.5°	12.6	12.6	12.6	12.6	16.8	16.8	16.8	16.8	21.1	21.1	21.1
45°	12.6	12.6	12.6	12.6	16.8	16.8	16.8	16.8	21.1	21.1	21.1
47.5°	12.6	12.6	12.6	12.6	16.8	16.8	16.8	16.8	21.1	21.1	21.1
50°	12.6	12.6	12.6	12.6	16.8	16.8	16.8	16.8	21.1	21.1	21.1
52.5°	8.4	8.4	8.4	8.4	12.6	12.6	12.6	12.6	16.8	16.8	16.8
55°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	12.6	12.6	12.6
57.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	12.6	12.6	12.6
60°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
62.5°	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
65°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	4.2	4.2
67.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
70°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
72.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
75°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
77.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
80°	12.6	12.6	12.6	12.6	12.6	8.4	8.4	8.4	8.4	8.4	8.4
82.5°	8.4	12.6	12.6	12.6	12.6	8.4	8.4	8.4	8.4	8.4	8.4
85°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
87.5°	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	54.8	54.8	50.5	50.5	50.5	50.5	50.5	50.5	50.5	54.8	54.8
5°	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	54.8	54.8
7.5°	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	54.8	54.8
10°	50.5	50.5	50.5	50.5	46.3	46.3	50.5	50.5	50.5	54.8	54.8
12.5°	50.5	50.5	50.5	50.5	46.3	46.3	50.5	50.5	54.8	54.8	59.0
15°	50.5	50.5	46.3	46.3	46.3	46.3	50.5	50.5	54.8	54.8	59.0
17.5°	50.5	50.5	46.3	46.3	46.3	46.3	50.5	50.5	54.8	54.8	59.0
20°	50.5	50.5	46.3	46.3	46.3	46.3	46.3	46.3	50.5	54.8	54.8
22.5°	46.3	46.3	46.3	46.3	42.1	42.1	46.3	46.3	50.5	54.8	54.8
25°	37.9	42.1	42.1	42.1	42.1	42.1	46.3	46.3	50.5	54.8	54.8
27.5°	33.7	37.9	37.9	37.9	37.9	42.1	42.1	46.3	50.5	54.8	54.8
30°	29.5	33.7	33.7	33.7	37.9	42.1	42.1	46.3	50.5	54.8	54.8
32.5°	29.5	33.7	33.7	33.7	37.9	37.9	42.1	42.1	46.3	50.5	54.8
35°	29.5	29.5	33.7	33.7	33.7	37.9	37.9	42.1	46.3	50.5	54.8
37.5°	29.5	29.5	33.7	33.7	33.7	37.9	37.9	42.1	46.3	50.5	54.8
40°	25.3	29.5	29.5	33.7	33.7	37.9	37.9	42.1	46.3	54.8	59.0
42.5°	25.3	25.3	29.5	29.5	33.7	37.9	37.9	42.1	46.3	54.8	59.0
45°	25.3	29.5	29.5	33.7	37.9	42.1	42.1	46.3	50.5	54.8	59.0
47.5°	25.3	29.5	29.5	33.7	42.1	42.1	46.3	46.3	50.5	54.8	59.0
50°	25.3	29.5	29.5	33.7	46.3	46.3	46.3	46.3	50.5	54.8	59.0
52.5°	21.1	25.3	25.3	29.5	37.9	42.1	46.3	50.5	54.8	59.0	63.2
55°	16.8	21.1	21.1	25.3	33.7	37.9	46.3	54.8	59.0	63.2	67.4
57.5°	16.8	16.8	21.1	21.1	29.5	37.9	50.5	59.0	63.2	67.4	71.6
60°	12.6	12.6	16.8	16.8	25.3	33.7	46.3	59.0	63.2	71.6	75.8
62.5°	8.4	12.6	12.6	16.8	21.1	33.7	46.3	59.0	67.4	75.8	80.0
65°	8.4	8.4	12.6	12.6	21.1	29.5	42.1	50.5	63.2	75.8	88.5
67.5°	12.6	12.6	16.8	16.8	21.1	29.5	42.1	50.5	63.2	80.0	92.7
70°	12.6	12.6	16.8	16.8	25.3	33.7	42.1	50.5	63.2	80.0	92.7
72.5°	12.6	12.6	16.8	16.8	25.3	29.5	37.9	46.3	59.0	71.6	84.2
75°	8.4	12.6	12.6	12.6	21.1	25.3	33.7	42.1	54.8	67.4	80.0
77.5°	8.4	8.4	8.4	8.4	16.8	21.1	29.5	33.7	46.3	59.0	71.6
80°	8.4	8.4	8.4	8.4	12.6	16.8	25.3	29.5	42.1	54.8	67.4
82.5°	8.4	8.4	4.2	4.2	8.4	12.6	16.8	21.1	33.7	42.1	54.8
85°	8.4	8.4	4.2	4.2	4.2	8.4	8.4	12.6	16.8	21.1	25.3
87.5°	8.4	8.4	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	54.8	54.8	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0	59.0
5°	54.8	59.0	59.0	63.2	63.2	63.2	67.4	67.4	67.4	67.4	67.4
7.5°	54.8	59.0	59.0	63.2	63.2	63.2	67.4	67.4	67.4	71.6	71.6
10°	54.8	59.0	59.0	63.2	63.2	67.4	71.6	71.6	75.8	75.8	75.8
12.5°	59.0	63.2	63.2	67.4	67.4	71.6	75.8	75.8	80.0	84.2	84.2
15°	59.0	63.2	67.4	67.4	71.6	75.8	80.0	80.0	84.2	88.5	92.7
17.5°	59.0	63.2	67.4	67.4	71.6	75.8	84.2	88.5	92.7	101.1	105.3
20°	59.0	63.2	67.4	67.4	71.6	80.0	84.2	92.7	96.9	105.3	113.7
22.5°	59.0	63.2	67.4	71.6	75.8	84.2	92.7	96.9	105.3	117.9	126.4
25°	59.0	63.2	67.4	71.6	75.8	84.2	92.7	101.1	109.5	126.4	143.2
27.5°	59.0	63.2	71.6	75.8	80.0	88.5	101.1	109.5	117.9	147.4	176.9
30°	59.0	63.2	71.6	75.8	80.0	92.7	105.3	113.7	126.4	176.9	223.2
32.5°	59.0	67.4	71.6	80.0	84.2	96.9	113.7	126.4	139.0	210.6	278.0
35°	59.0	67.4	71.6	80.0	84.2	101.1	117.9	134.8	151.6	256.9	362.2
37.5°	59.0	67.4	71.6	80.0	84.2	109.5	134.8	160.1	185.3	294.8	404.4
40°	63.2	71.6	75.8	84.2	88.5	113.7	139.0	164.3	189.5	299.1	408.6
42.5°	63.2	71.6	75.8	84.2	88.5	109.5	134.8	155.8	176.9	299.1	421.2
45°	63.2	71.6	80.0	84.2	92.7	113.7	134.8	151.6	172.7	328.5	480.2
47.5°	63.2	71.6	80.0	84.2	92.7	113.7	134.8	155.8	176.9	433.8	686.6
50°	63.2	71.6	80.0	84.2	92.7	117.9	143.2	168.5	193.8	648.7	1103.6
52.5°	67.4	71.6	80.0	84.2	88.5	117.9	147.4	176.9	206.4	842.4	1474.2
55°	71.6	75.8	80.0	84.2	88.5	126.4	164.3	202.2	240.1	905.6	1566.9
57.5°	75.8	80.0	84.2	84.2	88.5	134.8	185.3	231.7	278.0	901.4	1520.5
60°	80.0	84.2	88.5	92.7	96.9	143.2	193.8	240.1	286.4	817.1	1347.8
62.5°	88.5	96.9	105.3	109.5	117.9	164.3	206.4	252.7	294.8	669.7	1040.4
65°	101.1	109.5	113.7	122.1	126.4	168.5	214.8	256.9	299.1	556.0	808.7
67.5°	105.3	113.7	117.9	126.4	130.6	172.7	214.8	256.9	299.1	471.7	640.2
70°	105.3	113.7	122.1	126.4	134.8	176.9	214.8	256.9	294.8	408.6	522.3
72.5°	96.9	109.5	117.9	130.6	139.0	176.9	210.6	248.5	282.2	362.2	442.3
75°	92.7	109.5	122.1	139.0	151.6	176.9	206.4	231.7	256.9	315.9	374.9
77.5°	84.2	105.3	126.4	147.4	168.5	185.3	198.0	214.8	227.4	265.4	303.3
80°	80.0	101.1	122.1	143.2	164.3	172.7	176.9	185.3	189.5	193.8	198.0
82.5°	63.2	80.0	96.9	109.5	126.4	117.9	113.7	105.3	96.9	92.7	88.5
85°	29.5	33.7	33.7	37.9	37.9	37.9	33.7	33.7	29.5	25.3	21.1
87.5°	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	59.0	59.0	59.0	59.0	54.8	54.8	54.8	54.8	50.5	50.5	50.5
5°	67.4	67.4	67.4	67.4	63.2	63.2	63.2	63.2	59.0	59.0	59.0
7.5°	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6
10°	80.0	80.0	80.0	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2
12.5°	88.5	88.5	92.7	92.7	96.9	96.9	101.1	101.1	105.3	105.3	105.3
15°	96.9	101.1	105.3	109.5	109.5	113.7	117.9	122.1	126.4	130.6	134.8
17.5°	113.7	117.9	126.4	134.8	143.2	151.6	164.3	181.1	193.8	206.4	223.2
20°	126.4	139.0	164.3	193.8	219.0	244.3	307.5	370.7	433.8	497.0	560.2
22.5°	151.6	176.9	261.1	349.6	433.8	518.1	716.0	914.0	1107.8	1305.7	1482.6
25°	202.2	256.9	450.7	644.4	834.0	1027.7	1381.5	1739.6	2093.4	2447.2	2775.7
27.5°	278.0	379.1	695.0	1015.1	1331.0	1646.9	2160.8	2678.9	3192.7	3710.8	4169.9
30°	387.5	551.8	1023.5	1499.5	1971.2	2443.0	3091.6	3744.5	4393.1	5041.8	5463.0
32.5°	526.5	770.8	1368.9	1967.0	2565.1	3163.2	3879.3	4595.3	5307.2	6023.2	6469.7
35°	673.9	985.6	1705.9	2430.3	3150.6	3875.1	4629.0	5383.0	6136.9	6890.9	7438.4
37.5°	758.2	1112.0	1967.0	2822.1	3672.9	4527.9	5353.5	6183.3	7008.8	7834.4	8499.9
40°	838.2	1263.6	2249.2	3234.8	4220.5	5206.1	6170.6	7135.2	8099.7	9064.3	9919.3
42.5°	956.1	1491.1	2640.9	3790.8	4936.5	6086.4	7354.2	8626.2	9894.1	11161.9	12476.0
45°	1200.4	1920.7	3411.7	4902.8	6389.7	7880.7	9679.2	11482.0	13280.5	15083.3	16768.1
47.5°	1790.1	2889.5	4923.9	6958.3	8992.7	11027.1	13099.4	15171.7	17244.1	19316.4	21321.3
50°	2771.5	4435.3	6979.3	9523.4	12063.3	14607.3	16675.4	18743.5	20807.4	22875.5	24867.8
52.5°	3694.0	5913.7	8647.3	11385.1	14118.7	16856.5	18688.8	20521.0	22353.2	24185.5	26114.6
55°	4009.9	6448.6	9215.9	11987.4	14754.7	17526.3	19291.1	21060.2	22825.0	24589.8	26590.6
57.5°	3731.9	5943.2	8731.5	11519.9	14304.1	17092.4	19063.7	21039.1	23010.3	24985.8	27129.7
60°	3125.3	4898.6	7826.0	10757.5	13684.9	16612.3	18836.2	21060.2	23284.1	25508.1	27647.8
62.5°	2476.7	3908.8	7008.8	10108.9	13208.9	16309.0	18570.8	20836.9	23098.8	25360.6	27003.3
65°	1899.6	2990.5	6040.1	9093.8	12143.3	15197.0	17050.3	18907.8	20761.1	22618.6	23755.9
67.5°	1411.0	2181.8	4848.0	7518.5	10184.7	12850.9	14215.6	15584.5	16949.2	18318.1	19202.6
70°	1040.4	1554.2	3369.6	5185.0	6996.2	8811.6	10062.5	11313.5	12560.3	13811.2	14729.5
72.5°	720.3	994.0	2080.7	3171.7	4258.4	5345.1	6612.9	7880.7	9144.3	10412.1	11456.7
75°	492.8	610.7	1120.4	1630.1	2139.7	2649.4	3609.7	4570.1	5530.4	6490.7	7042.5
77.5°	366.4	429.6	581.3	737.1	888.7	1040.4	1225.7	1411.0	1596.4	1781.7	2021.8
80°	202.2	202.2	223.2	240.1	261.1	278.0	328.5	383.3	433.8	488.6	556.0
82.5°	92.7	96.9	105.3	113.7	117.9	126.4	134.8	143.2	151.6	160.1	160.1
85°	25.3	29.5	29.5	25.3	25.3	21.1	21.1	25.3	25.3	25.3	25.3
87.5°	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	50.5	46.3	46.3	46.3	42.1	42.1	42.1	42.1	42.1	42.1	42.1
5°	59.0	59.0	59.0	59.0	54.8	54.8	54.8	54.8	54.8	50.5	50.5
7.5°	71.6	67.4	67.4	67.4	67.4	67.4	67.4	67.4	67.4	63.2	63.2
10°	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	80.0	80.0
12.5°	105.3	105.3	105.3	105.3	109.5	109.5	105.3	105.3	105.3	101.1	101.1
15°	139.0	143.2	147.4	147.4	151.6	151.6	151.6	147.4	147.4	143.2	139.0
17.5°	235.9	248.5	265.4	282.2	299.1	311.7	311.7	303.3	294.8	286.4	278.0
20°	627.6	690.8	758.2	825.6	897.2	947.7	914.0	888.7	863.5	834.0	808.7
22.5°	1663.8	1840.7	2021.8	2148.1	2274.5	2362.9	2291.3	2152.3	2013.4	1878.6	1739.6
25°	3104.3	3428.6	3757.1	3891.9	4030.9	4132.0	4085.7	3875.1	3664.5	3458.1	3247.5
27.5°	4629.0	5083.9	5543.0	5661.0	5778.9	5867.4	5850.5	5576.7	5302.9	5029.2	4755.4
30°	5884.2	6305.4	6726.6	6844.6	6962.5	7042.5	6954.1	6680.3	6406.5	6132.7	5858.9
32.5°	6920.4	7366.8	7817.5	7973.4	8129.2	8234.5	8129.2	7800.7	7472.1	7147.8	6819.3
35°	7986.0	8529.4	9076.9	9274.9	9472.9	9599.2	9422.3	9018.0	8613.6	8213.5	7809.1
37.5°	9165.4	9826.7	10492.2	10761.7	11035.5	11225.1	11090.3	10584.8	10075.2	9569.7	9060.1
40°	10778.6	11633.6	12492.9	12977.3	13457.4	13798.6	13558.5	12973.1	12383.4	11797.9	11208.2
42.5°	13794.4	15108.6	16422.7	17117.7	17808.5	18309.7	18040.1	17319.9	16599.6	15879.4	15159.1
45°	18452.9	20133.5	21818.3	22833.4	23852.7	24602.5	24290.8	23385.2	22475.4	21569.8	20664.2
47.5°	23326.2	25331.2	27336.1	28144.8	28957.7	29589.5	29513.7	28384.9	27256.1	26131.4	25002.6
50°	26864.3	28856.6	30848.9	31543.9	32243.1	32761.2	32567.4	31131.1	29690.6	28254.3	26813.8
52.5°	28043.7	29968.6	31897.7	32727.5	33557.3	34176.4	33940.5	32323.1	30705.7	29092.5	27475.1
55°	28591.3	30592.0	32592.7	33603.6	34618.7	35360.0	35018.8	33245.6	31468.1	29694.8	27917.3
57.5°	29273.6	31417.5	33561.5	34669.2	35777.0	36577.3	36122.4	34285.9	32449.5	30617.3	28780.8
60°	29787.5	31923.0	34062.7	34951.4	35844.4	36467.8	36029.7	34243.8	32453.7	30667.8	28881.9
62.5°	28650.2	30292.9	31935.6	32596.9	33258.2	33738.4	33489.9	31796.6	30103.4	28410.1	26716.9
65°	24897.3	26034.6	27176.0	27622.5	28064.8	28405.9	28330.1	26902.2	25474.4	24050.7	22622.8
67.5°	20091.4	20975.9	21864.7	22496.5	23132.5	23625.3	23570.5	22269.0	20967.5	19666.0	18364.5
70°	15651.9	16570.1	17488.4	18284.4	19084.7	19703.9	19623.9	18415.0	17201.9	15993.1	14780.0
72.5°	12505.5	13550.1	14594.7	15049.6	15504.5	15824.6	15588.7	14674.7	13756.5	12842.5	11924.3
75°	7594.3	8141.9	8693.6	8689.4	8689.4	8638.9	8403.0	7880.7	7358.4	6836.1	6313.8
77.5°	2261.9	2501.9	2742.0	2973.7	3209.6	3386.5	3340.1	3066.4	2788.4	2514.6	2236.6
80°	623.4	686.6	754.0	783.4	812.9	850.8	947.7	880.3	812.9	749.7	682.3
82.5°	160.1	160.1	160.1	155.8	151.6	143.2	130.6	122.1	113.7	105.3	96.9
85°	25.3	21.1	21.1	21.1	16.8	16.8	16.8	16.8	12.6	12.6	8.4
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
2.5°	42.1	42.1	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	33.7
5°	50.5	50.5	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3	42.1
7.5°	63.2	63.2	59.0	59.0	59.0	59.0	54.8	54.8	54.8	54.8	50.5
10°	80.0	75.8	75.8	71.6	71.6	71.6	67.4	67.4	67.4	63.2	63.2
12.5°	101.1	96.9	96.9	92.7	88.5	88.5	84.2	80.0	75.8	75.8	71.6
15°	134.8	130.6	126.4	122.1	117.9	109.5	105.3	96.9	92.7	88.5	84.2
17.5°	256.9	235.9	214.8	193.8	176.9	160.1	143.2	126.4	117.9	109.5	101.1
20°	716.0	619.2	526.5	433.8	374.9	315.9	256.9	198.0	172.7	151.6	126.4
22.5°	1550.0	1356.3	1166.7	973.0	817.1	665.5	509.7	353.8	294.8	240.1	181.1
25°	2881.0	2510.4	2143.9	1773.3	1478.4	1183.6	888.7	593.9	484.4	374.9	265.4
27.5°	4275.2	3795.0	3314.9	2834.7	2367.2	1895.4	1423.7	956.1	766.6	581.3	391.7
30°	5349.3	4839.6	4334.2	3824.5	3234.8	2645.2	2051.3	1461.6	1162.5	863.5	560.2
32.5°	6271.7	5719.9	5172.4	4620.6	3938.2	3255.9	2573.6	1891.2	1516.3	1141.5	762.4
35°	7185.7	6558.1	5934.8	5307.2	4574.3	3841.4	3108.5	2375.6	1899.6	1423.7	943.5
37.5°	8297.7	7531.1	6768.7	6006.4	5252.4	4502.7	3748.7	2994.8	2388.2	1785.9	1179.4
40°	10235.2	9258.0	8285.1	7307.9	6427.6	5551.5	4671.1	3790.8	3028.5	2266.1	1499.5
42.5°	13933.4	12707.7	11486.2	10260.5	9043.2	7826.0	6604.5	5387.2	4300.5	3218.0	2131.3
45°	19093.1	17522.0	15955.2	14384.1	12884.6	11389.3	9889.8	8390.4	6739.2	5088.1	3432.8
47.5°	23284.1	21561.4	19842.9	18120.2	16456.4	14796.9	13133.1	11469.4	9354.9	7244.7	5130.3
50°	25175.3	23532.6	21894.1	20251.4	18583.5	16911.3	15239.1	13571.2	11145.0	8723.1	6297.0
52.5°	25811.3	24143.4	22479.6	20811.6	19156.3	17501.0	15845.7	14190.3	11667.3	9148.5	6625.5
55°	26160.9	24400.3	22643.9	20883.3	19101.6	17315.7	15529.8	13748.1	11237.7	8731.5	6221.2
57.5°	26868.5	24952.1	23039.8	21123.3	19093.1	17062.9	15028.5	12998.3	10521.7	8045.0	5568.3
60°	26999.1	25112.1	23229.4	21346.6	19101.6	16856.5	14607.3	12362.3	9902.5	7446.9	4987.0
62.5°	25141.6	23566.3	21995.2	20419.9	18170.7	15921.5	13668.0	11418.8	9064.3	6709.8	4351.0
65°	21262.3	19901.8	18545.6	17185.1	15348.6	13516.4	11680.0	9843.5	7741.7	5644.1	3542.3
67.5°	17033.5	15702.5	14375.7	13044.7	11663.1	10285.8	8904.2	7522.7	5901.1	4279.4	2657.8
70°	13503.8	12223.3	10947.1	9666.6	8445.1	7219.4	5993.7	4772.2	3765.6	2763.1	1756.4
72.5°	10702.8	9477.1	8255.6	7029.9	5922.1	4814.4	3706.6	2598.8	2097.6	1600.6	1099.3
75°	5677.8	5041.8	4410.0	3774.0	3150.6	2523.0	1895.4	1272.0	1074.1	876.1	673.9
77.5°	1958.6	1680.6	1406.8	1128.8	939.3	749.7	560.2	370.7	349.6	332.8	311.7
80°	593.9	505.4	417.0	328.5	290.6	252.7	214.8	176.9	164.3	151.6	134.8
82.5°	92.7	84.2	80.0	71.6	67.4	67.4	63.2	59.0	50.5	46.3	37.9
85°	8.4	4.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661

CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066661
 CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	37.9	37.9
2.5°	33.7	33.7
5°	42.1	42.1
7.5°	50.5	50.5
10°	59.0	59.0
12.5°	67.4	67.4
15°	80.0	75.8
17.5°	92.7	88.5
20°	101.1	92.7
22.5°	122.1	105.3
25°	155.8	130.6
27.5°	202.2	160.1
30°	261.1	202.2
32.5°	387.5	282.2
35°	467.5	341.2
37.5°	572.8	395.9
40°	737.1	480.2
42.5°	1044.6	652.9
45°	1781.7	1082.5
47.5°	3020.0	1844.9
50°	3870.9	2367.2
52.5°	4106.7	2510.4
55°	3715.0	2304.0
57.5°	3091.6	1958.6
60°	2531.4	1613.2
62.5°	1996.5	1276.2
65°	1440.5	964.6
67.5°	1036.2	741.3
70°	754.0	581.3
72.5°	598.1	484.4
75°	476.0	404.4
77.5°	294.8	269.6
80°	122.1	113.7
82.5°	29.5	25.3
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0



REPORT NUMBER: P1066661
 CATALOG NUMBER: NVN-SA5A-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-10

Test Date: 10/11/2024

Luminaire Tested: GSS-SB1A-835-U-5WQ

Data in this report applies to families of products including GSS-SB1A-835-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-10
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-835-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI
 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3411
 CIE u' : 0.2360
 CIE v' : 0.5189
 Duv: 0.0044
 CIE x: 0.4154
 CIE y: 0.4059
 CIE z: 0.1787
 Peak Wavelength (nm): 601
 Dominant Wavelength (nm): 579
 Purity: 46.51914
 R_f: 86.6
 R_g: 95.9

CRI (Ra): 83.5
 R1: 81.1
 R2: 88.9
 R3: 97.2
 R4: 83.8
 R5: 81.7
 R6: 86.9
 R7: 86.1
 R8: 62.2
 R9: 6.3
 R10: 75.4
 R11: 84.1
 R12: 69.7
 R13: 82.8
 R14: 98.5
 R15: 72.6



Test Conditions


Stabilization Time: 35M
 Operation Time: 1H 35M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-10

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-10

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.48

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Melanopic Flux vs. Wavelength

Melanopic Lumens: NR
M/P: 2.88


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10





TM-30-18

Summary

$R_f = 86.6$
 $R_g = 95.9$
 $CIE R_a = 83.5$
 $R_9 = 6.3$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 86	CES26 = 85	CES51 = 97	CES76 = 81
CES02 = 62	CES27 = 95	CES52 = 96	CES77 = 87
CES03 = 31	CES28 = 94	CES53 = 91	CES78 = 80
CES04 = 70	CES29 = 87	CES54 = 92	CES79 = 93
CES05 = 49	CES30 = 93	CES55 = 92	CES80 = 91
CES06 = 51	CES31 = 89	CES56 = 88	CES81 = 77
CES07 = 41	CES32 = 84	CES57 = 87	CES82 = 96
CES08 = 40	CES33 = 91	CES58 = 88	CES83 = 95
CES09 = 29	CES34 = 91	CES59 = 93	CES84 = 92
CES10 = 75	CES35 = 95	CES60 = 94	CES85 = 80
CES11 = 58	CES36 = 90	CES61 = 91	CES86 = 72
CES12 = 64	CES37 = 95	CES62 = 95	CES87 = 86
CES13 = 43	CES38 = 100	CES63 = 88	CES88 = 88
CES14 = 74	CES39 = 97	CES64 = 85	CES89 = 77
CES15 = 71	CES40 = 94	CES65 = 80	CES90 = 88
CES16 = 47	CES41 = 97	CES66 = 84	CES91 = 81
CES17 = 49	CES42 = 96	CES67 = 82	CES92 = 67
CES18 = 56	CES43 = 93	CES68 = 85	CES93 = 81
CES19 = 72	CES44 = 99	CES69 = 89	CES94 = 63
CES20 = 66	CES45 = 95	CES70 = 81	CES95 = 76
CES21 = 86	CES46 = 91	CES71 = 79	CES96 = 84
CES22 = 78	CES47 = 93	CES72 = 93	CES97 = 92
CES23 = 91	CES48 = 85	CES73 = 76	CES98 = 86
CES24 = 90	CES49 = 92	CES74 = 95	CES99 = 77
CES25 = 72	CES50 = 96	CES75 = 80	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)