

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P1066662

Luminaire Tested: **NVN-SA5B-835-U-RBC**

Issue Date: 08/07/2025

Test Information

Test Method: LM-79-08
Report Number: P1066662
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/07/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SA5B-835-U-RBC
Description: Navion AREA AND ROADWAY LUMINAIRE 800mA 5xLight Square PACKAGE
80CRI 3500K FIXTURE w/ RIGHT CORNER BACKLIGHT CONTROL
Light Source: (70) 3500K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 16815.9 lumens
Efficiency: N/A
Efficacy: 94.0 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1.5' x H: 0')
IES Classification: Type III - Short
BUG Rating: B0 - U0 - G3

Input Watts (W): 178.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

Iso-Footcandle Lines of Horizontal Illumination

× Max cd
 - - - 1/2 Max cd




Based on 15 foot mounting height. Maximum calculated value = 3.3 fc
 Type III - Short - N/A

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

Luminous Intensity Polar Plot



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	100.0	0.0	100.0
	% Fixture	0.6	0.0	0.6
Street Side	Lumens	16715.8	0.0	16715.8
	% Fixture	99.4	0.0	99.4
Total	Lumens	16815.9	0.0	16815.9
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	5.0	0.0
10°-20°	24.7	0.1
20°-30°	313.9	1.9
30°-40°	1057.8	6.3
40°-50°	3194.5	19.0
50°-60°	5636.1	33.5
60°-70°	4965.4	29.5
70°-80°	1580.6	9.4
80°-90°	38.0	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	16815.9	100.0
0°-180°	16815.9	100.0



REPORT NUMBER: P1066662


CATALOG NUMBER: NVN-SA5B-835-U-RBC

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	328.5	2.0			
FM	(30°-60°)	9849.6	58.6			
FH	(60°-80°)	6506.8	38.7			G3/7500
FVH	(80°-90°)	30.9	0.2			G1/100
BL	(0°-30°)	15.0	0.1	B0/110		
BM	(30°-60°)	38.8	0.2	B0/220		
BH	(60°-80°)	39.2	0.2	B0/110		G0/110
BVH	(80°-90°)	7.1	0.0			G0/10
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B0-U0-G3

Type III Short



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	36.9
5°	52.7	52.7	52.7	47.5	47.5	47.5	42.2	42.2	42.2	42.2	42.2
7.5°	63.3	58.0	58.0	52.7	52.7	52.7	47.5	47.5	47.5	47.5	42.2
10°	73.8	68.6	68.6	63.3	63.3	58.0	58.0	52.7	52.7	47.5	47.5
12.5°	84.4	79.1	73.8	68.6	68.6	63.3	63.3	58.0	58.0	52.7	52.7
15°	94.9	89.6	84.4	79.1	73.8	73.8	68.6	63.3	58.0	58.0	52.7
17.5°	110.7	100.2	94.9	84.4	79.1	73.8	68.6	63.3	63.3	58.0	58.0
20°	116.0	105.5	100.2	89.6	84.4	79.1	73.8	68.6	63.3	63.3	58.0
22.5°	137.1	116.0	110.7	100.2	94.9	89.6	79.1	73.8	68.6	63.3	58.0
25°	168.8	137.1	121.3	105.5	100.2	89.6	84.4	73.8	68.6	63.3	58.0
27.5°	205.7	152.9	137.1	116.0	105.5	94.9	84.4	73.8	68.6	63.3	58.0
30°	253.1	179.3	152.9	126.6	116.0	105.5	89.6	79.1	73.8	68.6	58.0
32.5°	353.3	221.5	179.3	137.1	121.3	110.7	94.9	79.1	73.8	68.6	58.0
35°	427.1	268.9	216.2	158.2	137.1	121.3	100.2	79.1	73.8	68.6	58.0
37.5°	495.7	274.2	221.5	168.8	147.7	126.6	100.2	79.1	73.8	68.6	58.0
40°	606.4	284.8	221.5	158.2	142.4	121.3	105.5	84.4	79.1	68.6	63.3
42.5°	817.4	327.0	237.3	147.7	131.8	121.3	105.5	89.6	79.1	73.8	63.3
45°	1360.6	485.2	321.7	152.9	137.1	121.3	105.5	89.6	84.4	73.8	68.6
47.5°	2315.0	843.8	501.0	158.2	142.4	121.3	105.5	84.4	79.1	73.8	63.3
50°	2963.7	1081.1	632.8	184.6	158.2	137.1	110.7	84.4	79.1	73.8	68.6
52.5°	3148.3	1149.6	685.5	216.2	184.6	152.9	116.0	84.4	79.1	79.1	73.8
55°	2884.6	1118.0	685.5	253.1	210.9	174.0	131.8	89.6	84.4	84.4	79.1
57.5°	2452.2	1033.6	653.9	274.2	232.0	184.6	142.4	94.9	89.6	89.6	84.4
60°	2019.7	870.1	590.6	305.9	258.4	210.9	163.5	116.0	110.7	105.5	94.9
62.5°	1603.1	701.4	516.8	327.0	279.5	226.8	179.3	126.6	121.3	116.0	110.7
65°	1207.6	611.7	479.9	342.8	290.0	237.3	184.6	131.8	126.6	126.6	121.3
67.5°	928.1	559.0	458.8	353.3	300.6	247.9	195.1	142.4	137.1	131.8	126.6
70°	733.0	516.8	432.4	348.0	300.6	253.1	200.4	152.9	142.4	137.1	126.6
72.5°	611.7	469.3	400.8	332.2	295.3	258.4	221.5	184.6	163.5	147.7	126.6
75°	511.5	421.9	363.9	300.6	274.2	253.1	226.8	200.4	174.0	147.7	121.3
77.5°	337.5	305.9	279.5	253.1	237.3	221.5	200.4	184.6	158.2	137.1	110.7
80°	142.4	131.8	137.1	137.1	137.1	137.1	131.8	131.8	116.0	100.2	79.1
82.5°	31.6	26.4	31.6	31.6	31.6	31.6	26.4	26.4	26.4	21.1	21.1
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	36.9	36.9	36.9	36.9	36.9	36.9	36.9	36.9	36.9	36.9	36.9
5°	42.2	42.2	42.2	36.9	36.9	36.9	36.9	36.9	36.9	36.9	36.9
7.5°	42.2	42.2	42.2	36.9	36.9	36.9	36.9	31.6	31.6	31.6	31.6
10°	42.2	42.2	42.2	36.9	36.9	36.9	36.9	31.6	31.6	31.6	31.6
12.5°	47.5	47.5	42.2	42.2	36.9	36.9	36.9	31.6	31.6	31.6	31.6
15°	47.5	47.5	42.2	42.2	36.9	36.9	36.9	31.6	31.6	31.6	31.6
17.5°	52.7	47.5	47.5	42.2	36.9	36.9	36.9	31.6	31.6	31.6	31.6
20°	52.7	47.5	47.5	42.2	36.9	36.9	36.9	31.6	31.6	31.6	31.6
22.5°	52.7	47.5	47.5	42.2	36.9	36.9	31.6	31.6	26.4	26.4	21.1
25°	52.7	47.5	47.5	42.2	36.9	36.9	31.6	31.6	26.4	21.1	21.1
27.5°	52.7	47.5	47.5	42.2	36.9	31.6	31.6	26.4	21.1	15.8	15.8
30°	52.7	47.5	47.5	42.2	36.9	31.6	26.4	21.1	15.8	15.8	10.5
32.5°	52.7	47.5	42.2	36.9	31.6	26.4	26.4	21.1	15.8	10.5	10.5
35°	52.7	47.5	42.2	36.9	31.6	26.4	26.4	21.1	15.8	10.5	10.5
37.5°	52.7	47.5	42.2	36.9	31.6	26.4	21.1	15.8	10.5	10.5	5.3
40°	52.7	47.5	42.2	36.9	31.6	26.4	21.1	15.8	10.5	10.5	5.3
42.5°	52.7	47.5	42.2	36.9	31.6	26.4	21.1	15.8	10.5	10.5	5.3
45°	58.0	52.7	47.5	36.9	31.6	26.4	26.4	21.1	15.8	10.5	10.5
47.5°	58.0	52.7	47.5	36.9	31.6	26.4	26.4	21.1	15.8	10.5	10.5
50°	63.3	58.0	52.7	42.2	36.9	31.6	26.4	15.8	10.5	10.5	5.3
52.5°	68.6	63.3	58.0	52.7	47.5	36.9	26.4	15.8	5.3	5.3	5.3
55°	73.8	68.6	68.6	63.3	58.0	42.2	31.6	15.8	0.0	0.0	0.0
57.5°	79.1	73.8	73.8	68.6	63.3	47.5	31.6	15.8	0.0	0.0	0.0
60°	89.6	84.4	79.1	68.6	63.3	47.5	31.6	15.8	0.0	0.0	0.0
62.5°	105.5	94.9	79.1	68.6	52.7	42.2	26.4	15.8	0.0	0.0	0.0
65°	116.0	100.2	84.4	63.3	47.5	36.9	26.4	10.5	0.0	0.0	0.0
67.5°	121.3	100.2	84.4	63.3	42.2	31.6	21.1	10.5	0.0	0.0	0.0
70°	116.0	94.9	79.1	58.0	36.9	26.4	21.1	10.5	0.0	0.0	0.0
72.5°	105.5	89.6	68.6	52.7	31.6	26.4	15.8	10.5	0.0	0.0	0.0
75°	94.9	79.1	58.0	42.2	21.1	15.8	10.5	5.3	0.0	0.0	0.0
77.5°	84.4	68.6	47.5	31.6	10.5	10.5	5.3	5.3	0.0	0.0	0.0
80°	63.3	47.5	31.6	15.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	15.8	10.5	10.5	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	31.6	31.6	31.6	31.6	31.6	31.6	31.6	31.6	31.6	31.6	31.6
5°	31.6	31.6	31.6	31.6	26.4	26.4	26.4	26.4	26.4	26.4	26.4
7.5°	31.6	31.6	31.6	31.6	26.4	26.4	26.4	26.4	21.1	21.1	21.1
10°	26.4	26.4	26.4	26.4	26.4	26.4	26.4	26.4	21.1	21.1	21.1
12.5°	26.4	26.4	26.4	26.4	26.4	26.4	26.4	26.4	21.1	21.1	21.1
15°	26.4	26.4	26.4	26.4	26.4	26.4	26.4	21.1	21.1	15.8	15.8
17.5°	26.4	26.4	26.4	26.4	21.1	21.1	21.1	15.8	15.8	10.5	10.5
20°	26.4	26.4	26.4	21.1	21.1	15.8	15.8	10.5	10.5	5.3	5.3
22.5°	21.1	15.8	15.8	10.5	10.5	5.3	5.3	5.3	0.0	0.0	0.0
25°	15.8	10.5	10.5	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	10.5	5.3	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	10.5	5.3	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	31.6	26.4	26.4	26.4	26.4	26.4	26.4	26.4	26.4	26.4	26.4
5°	26.4	26.4	26.4	26.4	21.1	21.1	21.1	21.1	21.1	21.1	21.1
7.5°	21.1	21.1	21.1	21.1	21.1	21.1	15.8	15.8	15.8	15.8	15.8
10°	21.1	15.8	15.8	15.8	15.8	15.8	15.8	15.8	15.8	10.5	10.5
12.5°	21.1	15.8	15.8	15.8	10.5	10.5	10.5	10.5	10.5	5.3	5.3
15°	15.8	10.5	10.5	10.5	5.3	5.3	5.3	5.3	5.3	0.0	0.0
17.5°	10.5	5.3	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	26.4	26.4	26.4	26.4	26.4	26.4	26.4	26.4	26.4	31.6	31.6
5°	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1	21.1
7.5°	15.8	15.8	15.8	15.8	15.8	15.8	15.8	15.8	15.8	15.8	15.8
10°	10.5	10.5	10.5	10.5	10.5	10.5	5.3	5.3	5.3	5.3	5.3
12.5°	5.3	5.3	5.3	5.3	5.3	5.3	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	31.6	31.6	31.6	31.6	31.6	36.9	36.9	42.2	42.2	47.5	47.5
5°	21.1	21.1	26.4	26.4	26.4	26.4	31.6	31.6	31.6	36.9	36.9
7.5°	15.8	15.8	15.8	15.8	15.8	21.1	21.1	26.4	26.4	31.6	31.6
10°	5.3	5.3	10.5	10.5	10.5	10.5	15.8	15.8	15.8	21.1	26.4
12.5°	0.0	0.0	5.3	5.3	5.3	5.3	10.5	10.5	10.5	15.8	21.1
15°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	10.5	15.8
17.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	10.5
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3
22.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	52.7	52.7	58.0	58.0	63.3	63.3	68.6	68.6	68.6	68.6	68.6
5°	42.2	42.2	47.5	52.7	52.7	58.0	63.3	63.3	63.3	63.3	63.3
7.5°	36.9	36.9	42.2	47.5	47.5	52.7	58.0	58.0	63.3	63.3	63.3
10°	26.4	31.6	36.9	42.2	42.2	47.5	52.7	52.7	58.0	58.0	58.0
12.5°	21.1	26.4	31.6	36.9	36.9	42.2	47.5	47.5	52.7	52.7	58.0
15°	15.8	21.1	26.4	31.6	31.6	36.9	42.2	42.2	47.5	52.7	58.0
17.5°	10.5	15.8	21.1	26.4	26.4	31.6	36.9	42.2	47.5	47.5	52.7
20°	10.5	10.5	15.8	21.1	21.1	26.4	31.6	36.9	42.2	42.2	47.5
22.5°	5.3	5.3	10.5	15.8	15.8	21.1	26.4	31.6	36.9	36.9	42.2
25°	0.0	0.0	5.3	10.5	10.5	15.8	21.1	21.1	26.4	26.4	31.6
27.5°	0.0	0.0	5.3	5.3	10.5	10.5	15.8	15.8	21.1	21.1	26.4
30°	0.0	0.0	5.3	5.3	10.5	10.5	15.8	15.8	21.1	21.1	21.1
32.5°	0.0	0.0	0.0	5.3	5.3	5.3	10.5	10.5	15.8	15.8	21.1
35°	0.0	0.0	0.0	5.3	5.3	5.3	10.5	10.5	15.8	15.8	15.8
37.5°	0.0	0.0	0.0	5.3	5.3	5.3	10.5	10.5	10.5	10.5	15.8
40°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.5	10.5	10.5
42.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.5	10.5	10.5
45°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.5	10.5	10.5
47.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.5	10.5	10.5
50°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.5	10.5	10.5
52.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
55°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
57.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
62.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
67.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
72.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3
75°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
77.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.5	10.5	10.5
80°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	10.5	10.5	10.5
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	10.5
85°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	5.3	5.3	5.3	5.3	5.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	68.6	68.6
5°	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	63.3	63.3
7.5°	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	63.3	63.3
10°	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
12.5°	58.0	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
15°	58.0	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
17.5°	52.7	58.0	58.0	58.0	63.3	63.3	63.3	63.3	63.3	63.3	63.3
20°	47.5	52.7	52.7	52.7	58.0	58.0	58.0	58.0	63.3	63.3	63.3
22.5°	42.2	47.5	47.5	47.5	52.7	52.7	52.7	52.7	58.0	58.0	58.0
25°	36.9	36.9	42.2	42.2	47.5	47.5	47.5	47.5	47.5	47.5	47.5
27.5°	26.4	31.6	31.6	31.6	36.9	36.9	36.9	36.9	42.2	42.2	42.2
30°	26.4	26.4	26.4	26.4	31.6	31.6	31.6	31.6	36.9	36.9	36.9
32.5°	21.1	26.4	26.4	26.4	31.6	31.6	31.6	31.6	36.9	36.9	36.9
35°	21.1	21.1	21.1	21.1	26.4	26.4	26.4	26.4	31.6	31.6	31.6
37.5°	15.8	21.1	21.1	21.1	26.4	26.4	26.4	26.4	31.6	31.6	31.6
40°	15.8	15.8	15.8	15.8	21.1	21.1	21.1	21.1	26.4	26.4	26.4
42.5°	15.8	15.8	15.8	15.8	21.1	21.1	21.1	21.1	26.4	26.4	26.4
45°	15.8	15.8	15.8	15.8	21.1	21.1	21.1	21.1	26.4	26.4	26.4
47.5°	15.8	15.8	15.8	15.8	21.1	21.1	21.1	21.1	26.4	26.4	26.4
50°	15.8	15.8	15.8	15.8	21.1	21.1	21.1	21.1	26.4	26.4	26.4
52.5°	10.5	10.5	10.5	10.5	15.8	15.8	15.8	15.8	21.1	21.1	21.1
55°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	15.8	15.8	15.8
57.5°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	15.8	15.8	15.8
60°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
62.5°	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
65°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	5.3	5.3
67.5°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
70°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
72.5°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
75°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
77.5°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
80°	15.8	15.8	15.8	15.8	15.8	10.5	10.5	10.5	10.5	10.5	10.5
82.5°	10.5	15.8	15.8	15.8	15.8	10.5	10.5	10.5	10.5	10.5	10.5
85°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
87.5°	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	68.6	68.6	63.3	63.3	63.3	63.3	63.3	63.3	63.3	68.6	68.6
5°	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	68.6	68.6
7.5°	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	68.6	68.6
10°	63.3	63.3	63.3	63.3	58.0	58.0	63.3	63.3	63.3	68.6	68.6
12.5°	63.3	63.3	63.3	63.3	58.0	58.0	63.3	63.3	68.6	68.6	73.8
15°	63.3	63.3	58.0	58.0	58.0	58.0	63.3	63.3	68.6	68.6	73.8
17.5°	63.3	63.3	58.0	58.0	58.0	58.0	63.3	63.3	68.6	68.6	73.8
20°	63.3	63.3	58.0	58.0	58.0	58.0	58.0	58.0	63.3	68.6	68.6
22.5°	58.0	58.0	58.0	58.0	52.7	52.7	58.0	58.0	63.3	68.6	68.6
25°	47.5	52.7	52.7	52.7	52.7	52.7	58.0	58.0	63.3	68.6	68.6
27.5°	42.2	47.5	47.5	47.5	47.5	52.7	52.7	58.0	63.3	68.6	68.6
30°	36.9	42.2	42.2	42.2	47.5	52.7	52.7	58.0	63.3	68.6	68.6
32.5°	36.9	42.2	42.2	42.2	47.5	47.5	52.7	52.7	58.0	63.3	68.6
35°	36.9	36.9	42.2	42.2	42.2	47.5	47.5	52.7	58.0	63.3	68.6
37.5°	36.9	36.9	42.2	42.2	42.2	47.5	47.5	52.7	58.0	63.3	68.6
40°	31.6	36.9	36.9	42.2	42.2	47.5	47.5	52.7	58.0	68.6	73.8
42.5°	31.6	31.6	36.9	36.9	42.2	47.5	47.5	52.7	58.0	68.6	73.8
45°	31.6	36.9	36.9	42.2	47.5	52.7	52.7	58.0	63.3	68.6	73.8
47.5°	31.6	36.9	36.9	42.2	52.7	52.7	58.0	58.0	63.3	68.6	73.8
50°	31.6	36.9	36.9	42.2	58.0	58.0	58.0	58.0	63.3	68.6	73.8
52.5°	26.4	31.6	31.6	36.9	47.5	52.7	58.0	63.3	68.6	73.8	79.1
55°	21.1	26.4	26.4	31.6	42.2	47.5	58.0	68.6	73.8	79.1	84.4
57.5°	21.1	21.1	26.4	26.4	36.9	47.5	63.3	73.8	79.1	84.4	89.6
60°	15.8	15.8	21.1	21.1	31.6	42.2	58.0	73.8	79.1	89.6	94.9
62.5°	10.5	15.8	15.8	21.1	26.4	42.2	58.0	73.8	84.4	94.9	100.2
65°	10.5	10.5	15.8	15.8	26.4	36.9	52.7	63.3	79.1	94.9	110.7
67.5°	15.8	15.8	21.1	21.1	26.4	36.9	52.7	63.3	79.1	100.2	116.0
70°	15.8	15.8	21.1	21.1	31.6	42.2	52.7	63.3	79.1	100.2	116.0
72.5°	15.8	15.8	21.1	21.1	31.6	36.9	47.5	58.0	73.8	89.6	105.5
75°	10.5	15.8	15.8	15.8	26.4	31.6	42.2	52.7	68.6	84.4	100.2
77.5°	10.5	10.5	10.5	10.5	21.1	26.4	36.9	42.2	58.0	73.8	89.6
80°	10.5	10.5	10.5	10.5	15.8	21.1	31.6	36.9	52.7	68.6	84.4
82.5°	10.5	10.5	5.3	5.3	10.5	15.8	21.1	26.4	42.2	52.7	68.6
85°	10.5	10.5	5.3	5.3	5.3	10.5	10.5	15.8	21.1	26.4	31.6
87.5°	10.5	10.5	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	68.6	68.6	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8
5°	68.6	73.8	73.8	79.1	79.1	79.1	84.4	84.4	84.4	84.4	84.4
7.5°	68.6	73.8	73.8	79.1	79.1	79.1	84.4	84.4	84.4	89.6	89.6
10°	68.6	73.8	73.8	79.1	79.1	84.4	89.6	89.6	94.9	94.9	94.9
12.5°	73.8	79.1	79.1	84.4	84.4	89.6	94.9	94.9	100.2	105.5	105.5
15°	73.8	79.1	84.4	84.4	89.6	94.9	100.2	100.2	105.5	110.7	116.0
17.5°	73.8	79.1	84.4	84.4	89.6	94.9	105.5	110.7	116.0	126.6	131.8
20°	73.8	79.1	84.4	84.4	89.6	100.2	105.5	116.0	121.3	131.8	142.4
22.5°	73.8	79.1	84.4	89.6	94.9	105.5	116.0	121.3	131.8	147.7	158.2
25°	73.8	79.1	84.4	89.6	94.9	105.5	116.0	126.6	137.1	158.2	179.3
27.5°	73.8	79.1	89.6	94.9	100.2	110.7	126.6	137.1	147.7	184.6	221.5
30°	73.8	79.1	89.6	94.9	100.2	116.0	131.8	142.4	158.2	221.5	279.5
32.5°	73.8	84.4	89.6	100.2	105.5	121.3	142.4	158.2	174.0	263.7	348.0
35°	73.8	84.4	89.6	100.2	105.5	126.6	147.7	168.8	189.8	321.7	453.5
37.5°	73.8	84.4	89.6	100.2	105.5	137.1	168.8	200.4	232.0	369.1	506.3
40°	79.1	89.6	94.9	105.5	110.7	142.4	174.0	205.7	237.3	374.4	511.5
42.5°	79.1	89.6	94.9	105.5	110.7	137.1	168.8	195.1	221.5	374.4	527.3
45°	79.1	89.6	100.2	105.5	116.0	142.4	168.8	189.8	216.2	411.3	601.2
47.5°	79.1	89.6	100.2	105.5	116.0	142.4	168.8	195.1	221.5	543.2	859.6
50°	79.1	89.6	100.2	105.5	116.0	147.7	179.3	210.9	242.6	812.1	1381.6
52.5°	84.4	89.6	100.2	105.5	110.7	147.7	184.6	221.5	258.4	1054.7	1845.7
55°	89.6	94.9	100.2	105.5	110.7	158.2	205.7	253.1	300.6	1133.8	1961.7
57.5°	94.9	100.2	105.5	105.5	110.7	168.8	232.0	290.0	348.0	1128.5	1903.7
60°	100.2	105.5	110.7	116.0	121.3	179.3	242.6	300.6	358.6	1023.1	1687.5
62.5°	110.7	121.3	131.8	137.1	147.7	205.7	258.4	316.4	369.1	838.5	1302.5
65°	126.6	137.1	142.4	152.9	158.2	210.9	268.9	321.7	374.4	696.1	1012.5
67.5°	131.8	142.4	147.7	158.2	163.5	216.2	268.9	321.7	374.4	590.6	801.6
70°	131.8	142.4	152.9	158.2	168.8	221.5	268.9	321.7	369.1	511.5	653.9
72.5°	121.3	137.1	147.7	163.5	174.0	221.5	263.7	311.1	353.3	453.5	553.7
75°	116.0	137.1	152.9	174.0	189.8	221.5	258.4	290.0	321.7	395.5	469.3
77.5°	105.5	131.8	158.2	184.6	210.9	232.0	247.9	268.9	284.8	332.2	379.7
80°	100.2	126.6	152.9	179.3	205.7	216.2	221.5	232.0	237.3	242.6	247.9
82.5°	79.1	100.2	121.3	137.1	158.2	147.7	142.4	131.8	121.3	116.0	110.7
85°	36.9	42.2	42.2	47.5	47.5	47.5	42.2	42.2	36.9	31.6	26.4
87.5°	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	73.8	73.8	73.8	73.8	68.6	68.6	68.6	68.6	63.3	63.3	63.3
5°	84.4	84.4	84.4	84.4	79.1	79.1	79.1	79.1	73.8	73.8	73.8
7.5°	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6
10°	100.2	100.2	100.2	105.5	105.5	105.5	105.5	105.5	105.5	105.5	105.5
12.5°	110.7	110.7	116.0	116.0	121.3	121.3	126.6	126.6	131.8	131.8	131.8
15°	121.3	126.6	131.8	137.1	137.1	142.4	147.7	152.9	158.2	163.5	168.8
17.5°	142.4	147.7	158.2	168.8	179.3	189.8	205.7	226.8	242.6	258.4	279.5
20°	158.2	174.0	205.7	242.6	274.2	305.9	385.0	464.1	543.2	622.3	701.4
22.5°	189.8	221.5	327.0	437.7	543.2	648.6	896.5	1144.3	1386.9	1634.8	1856.3
25°	253.1	321.7	564.3	806.8	1044.1	1286.7	1729.7	2177.9	2620.9	3063.9	3475.2
27.5°	348.0	474.6	870.1	1270.9	1666.4	2061.9	2705.3	3353.9	3997.3	4645.9	5220.7
30°	485.2	690.8	1281.4	1877.3	2468.0	3058.6	3870.7	4688.1	5500.2	6312.3	6839.7
32.5°	659.2	965.0	1713.9	2462.7	3211.5	3960.4	4856.9	5753.3	6644.6	7541.0	8100.0
35°	843.8	1234.0	2135.7	3042.8	3944.5	4851.6	5795.5	6739.5	7683.4	8627.4	9312.9
37.5°	949.2	1392.2	2462.7	3533.2	4598.5	5669.0	6702.6	7741.4	8775.0	9808.6	10641.8
40°	1049.4	1582.0	2816.0	4050.0	5284.0	6518.0	7725.6	8933.2	10140.9	11348.5	12419.0
42.5°	1197.1	1866.8	3306.5	4746.1	6180.5	7620.1	9207.5	10800.0	12387.3	13974.7	15620.0
45°	1502.9	2404.7	4271.5	6138.3	7999.8	9866.6	12118.4	14375.4	16627.2	18884.2	20993.6
47.5°	2241.2	3617.6	6164.7	8711.7	11258.8	13805.9	16400.4	18995.0	21589.5	24184.1	26694.2
50°	3469.9	5552.9	8738.1	11923.3	15103.2	18288.3	20877.6	23466.9	26050.9	28640.1	31134.5
52.5°	4624.8	7403.9	10826.4	14254.1	17676.6	21104.4	23398.3	25692.3	27986.2	30280.2	32695.4
55°	5020.3	8073.7	11538.3	15008.2	18472.9	21942.8	24152.4	26367.3	28576.8	30786.4	33291.3
57.5°	4672.3	7440.8	10931.9	14422.9	17908.6	21399.7	23867.7	26340.9	28808.9	31282.1	33966.3
60°	3912.9	6133.0	9798.1	13468.4	17133.5	20798.5	23582.9	26367.3	29151.7	31936.0	34615.0
62.5°	3100.8	4893.8	8775.0	12656.3	16537.6	20418.8	23250.7	26087.8	28919.6	31751.5	33808.1
65°	2378.3	3744.2	7562.1	11385.4	15203.4	19026.6	21346.9	23672.5	25992.9	28318.4	29742.3
67.5°	1766.6	2731.6	6069.7	9413.1	12751.2	16089.3	17797.9	19511.8	21220.4	22934.3	24041.7
70°	1302.5	1945.9	4218.8	6491.6	8759.2	11032.1	12598.3	14164.5	15725.4	17291.7	18441.3
72.5°	901.8	1244.5	2605.1	3970.9	5331.5	6692.0	8279.3	9866.6	11448.7	13036.0	14343.8
75°	617.0	764.7	1402.7	2040.8	2678.9	3317.0	4519.3	5721.7	6924.0	8126.4	8817.2
77.5°	458.8	537.9	727.7	922.9	1112.7	1302.5	1534.6	1766.6	1998.6	2230.7	2531.3
80°	253.1	253.1	279.5	300.6	327.0	348.0	411.3	479.9	543.2	611.7	696.1
82.5°	116.0	121.3	131.8	142.4	147.7	158.2	168.8	179.3	189.8	200.4	200.4
85°	31.6	36.9	36.9	31.6	31.6	26.4	26.4	31.6	31.6	31.6	31.6
87.5°	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	63.3	58.0	58.0	58.0	52.7	52.7	52.7	52.7	52.7	52.7	52.7
5°	73.8	73.8	73.8	73.8	68.6	68.6	68.6	68.6	68.6	63.3	63.3
7.5°	89.6	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	79.1	79.1
10°	105.5	105.5	105.5	105.5	105.5	105.5	105.5	105.5	105.5	100.2	100.2
12.5°	131.8	131.8	131.8	131.8	137.1	137.1	131.8	131.8	131.8	126.6	126.6
15°	174.0	179.3	184.6	184.6	189.8	189.8	189.8	184.6	184.6	179.3	174.0
17.5°	295.3	311.1	332.2	353.3	374.4	390.2	390.2	379.7	369.1	358.6	348.0
20°	785.7	864.8	949.2	1033.6	1123.2	1186.5	1144.3	1112.7	1081.1	1044.1	1012.5
22.5°	2083.0	2304.5	2531.3	2689.5	2847.7	2958.4	2868.8	2694.7	2520.7	2352.0	2177.9
25°	3886.5	4292.6	4703.9	4872.7	5046.7	5173.3	5115.3	4851.6	4587.9	4329.5	4065.8
27.5°	5795.5	6365.1	6939.9	7087.5	7235.2	7345.9	7324.8	6982.1	6639.3	6296.5	5953.7
30°	7367.0	7894.4	8421.7	8569.4	8717.0	8817.2	8706.5	8363.7	8020.9	7678.1	7335.4
32.5°	8664.3	9223.3	9787.5	9982.6	10177.8	10309.6	10177.8	9766.4	9355.1	8949.1	8537.7
35°	9998.5	10678.7	11364.3	11612.1	11860.0	12018.2	11796.7	11290.5	10784.2	10283.2	9777.0
37.5°	11475.0	12303.0	13136.2	13473.7	13816.4	14053.8	13885.0	13252.2	12614.1	11981.3	11343.2
40°	13494.8	14565.3	15641.1	16247.5	16848.7	17275.8	16975.2	16242.2	15504.0	14770.9	14032.7
42.5°	17270.6	18915.9	20561.2	21431.3	22296.2	22923.7	22586.2	21684.4	20782.7	19880.9	18979.2
45°	23103.0	25207.1	27316.5	28587.4	29863.6	30802.2	30412.0	29278.2	28139.1	27005.4	25871.6
47.5°	29204.4	31714.6	34224.7	35237.2	36255.0	37046.0	36951.1	35537.8	34124.5	32716.5	31303.2
50°	33634.1	36128.4	38622.8	39492.9	40368.3	41016.9	40774.3	38976.1	37172.6	35374.3	33570.8
52.5°	35110.7	37520.6	39935.9	40974.7	42013.6	42788.8	42493.5	40468.5	38443.5	36423.7	34398.7
55°	35796.2	38301.1	40806.0	42071.6	43342.5	44270.6	43843.5	41623.4	39398.0	37177.8	34952.5
57.5°	36650.5	39334.7	42018.9	43405.8	44792.7	45794.7	45225.1	42925.9	40626.7	38332.7	36033.5
60°	37293.9	39967.5	42646.4	43759.1	44877.1	45657.6	45109.1	42873.2	40632.0	38396.0	36160.1
62.5°	35870.0	37926.7	39983.3	40811.3	41639.2	42240.4	41929.2	39809.3	37689.4	35569.4	33449.5
65°	31171.4	32595.2	34024.3	34583.3	35137.0	35564.2	35469.3	33681.5	31893.8	30111.4	28323.7
67.5°	25154.4	26261.8	27374.5	28165.5	28961.8	29578.8	29510.2	27880.8	26251.3	24621.8	22992.3
70°	19596.2	20745.8	21895.4	22892.1	23894.0	24669.2	24569.0	23055.5	21536.8	20023.3	18504.5
72.5°	15656.9	16964.7	18272.5	18842.1	19411.6	19812.4	19517.1	18372.7	17223.1	16078.8	14929.1
75°	9508.0	10193.6	10884.4	10879.1	10879.1	10815.9	10520.5	9866.6	9212.7	8558.8	7904.9
77.5°	2831.8	3132.4	3433.0	3723.1	4018.4	4239.9	4181.8	3839.1	3491.0	3148.3	2800.2
80°	780.5	859.6	943.9	980.9	1017.8	1065.2	1186.5	1102.2	1017.8	938.7	854.3
82.5°	200.4	200.4	200.4	195.1	189.8	179.3	163.5	152.9	142.4	131.8	121.3
85°	31.6	26.4	26.4	26.4	21.1	21.1	21.1	21.1	15.8	15.8	10.5
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5
2.5°	52.7	52.7	47.5	47.5	47.5	47.5	47.5	47.5	47.5	47.5	42.2
5°	63.3	63.3	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	52.7
7.5°	79.1	79.1	73.8	73.8	73.8	73.8	68.6	68.6	68.6	68.6	63.3
10°	100.2	94.9	94.9	89.6	89.6	89.6	84.4	84.4	84.4	79.1	79.1
12.5°	126.6	121.3	121.3	116.0	110.7	110.7	105.5	100.2	94.9	94.9	89.6
15°	168.8	163.5	158.2	152.9	147.7	137.1	131.8	121.3	116.0	110.7	105.5
17.5°	321.7	295.3	268.9	242.6	221.5	200.4	179.3	158.2	147.7	137.1	126.6
20°	896.5	775.2	659.2	543.2	469.3	395.5	321.7	247.9	216.2	189.8	158.2
22.5°	1940.6	1698.1	1460.7	1218.2	1023.1	833.2	638.1	443.0	369.1	300.6	226.8
25°	3607.0	3143.0	2684.2	2220.1	1851.0	1481.8	1112.7	743.6	606.4	469.3	332.2
27.5°	5352.6	4751.4	4150.2	3549.0	2963.7	2373.1	1782.4	1197.1	959.8	727.7	490.4
30°	6697.3	6059.2	5426.4	4788.3	4050.0	3311.7	2568.2	1829.9	1455.5	1081.1	701.4
32.5°	7852.2	7161.4	6475.8	5785.0	4930.7	4076.4	3222.1	2367.8	1898.4	1429.1	954.5
35°	8996.5	8210.8	7430.3	6644.6	5727.0	4809.4	3891.8	2974.2	2378.3	1782.4	1181.3
37.5°	10388.7	9428.9	8474.4	7519.9	6576.0	5637.3	4693.4	3749.4	2990.0	2235.9	1476.6
40°	12814.5	11591.1	10372.9	9149.4	8047.3	6950.4	5848.3	4746.1	3791.6	2837.1	1877.3
42.5°	17444.6	15910.0	14380.7	12846.1	11322.1	9798.1	8268.8	6744.7	5384.2	4028.9	2668.4
45°	23904.6	21937.6	19975.8	18008.8	16131.5	14259.4	12382.1	10504.7	8437.5	6370.3	4297.9
47.5°	29151.7	26994.8	24843.2	22686.4	20603.4	18525.6	16442.6	14359.6	11712.3	9070.3	6423.1
50°	31519.4	29462.8	27411.4	25354.8	23266.5	21172.9	19079.4	16991.1	13953.6	10921.3	7883.8
52.5°	32315.7	30227.4	28144.4	26056.1	23983.7	21911.2	19838.7	17766.3	14607.5	11453.9	8295.1
55°	32753.4	30549.1	28350.1	26145.8	23915.1	21679.2	19443.2	17212.6	14069.6	10931.9	7788.9
57.5°	33639.4	31239.9	28845.8	26446.4	23904.6	21362.8	18815.7	16273.9	13173.1	10072.3	6971.5
60°	33802.8	31440.3	29083.1	26725.9	23915.1	21104.4	18288.3	15477.6	12397.9	9323.5	6243.8
62.5°	31477.2	29505.0	27538.0	25565.7	22749.7	19933.7	17112.4	14296.3	11348.5	8400.6	5447.5
65°	26620.4	24917.1	23219.0	21515.7	19216.5	16922.5	14623.3	12324.1	9692.6	7066.4	4435.0
67.5°	21325.8	19659.4	17998.3	16331.9	14602.2	12877.8	11148.1	9418.4	7388.1	5357.8	3327.5
70°	16906.7	15303.6	13705.7	12102.6	10573.3	9038.7	7504.1	5974.8	4714.5	3459.4	2199.0
72.5°	13399.8	11865.3	10336.0	8801.4	7414.5	6027.6	4640.6	3253.7	2626.2	2003.9	1376.4
75°	7108.6	6312.3	5521.3	4725.0	3944.5	3158.8	2373.1	1592.6	1344.7	1096.9	843.8
77.5°	2452.2	2104.1	1761.3	1413.3	1176.0	938.7	701.4	464.1	437.7	416.6	390.2
80°	743.6	632.8	522.1	411.3	363.9	316.4	268.9	221.5	205.7	189.8	168.8
82.5°	116.0	105.5	100.2	89.6	84.4	84.4	79.1	73.8	63.3	58.0	47.5
85°	10.5	5.3	5.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	47.5	47.5
2.5°	42.2	42.2
5°	52.7	52.7
7.5°	63.3	63.3
10°	73.8	73.8
12.5°	84.4	84.4
15°	100.2	94.9
17.5°	116.0	110.7
20°	126.6	116.0
22.5°	152.9	131.8
25°	195.1	163.5
27.5°	253.1	200.4
30°	327.0	253.1
32.5°	485.2	353.3
35°	585.4	427.1
37.5°	717.2	495.7
40°	922.9	601.2
42.5°	1307.8	817.4
45°	2230.7	1355.3
47.5°	3781.1	2309.8
50°	4846.3	2963.7
52.5°	5141.6	3143.0
55°	4651.2	2884.6
57.5°	3870.7	2452.2
60°	3169.3	2019.7
62.5°	2499.6	1597.9
65°	1803.5	1207.6
67.5°	1297.3	928.1
70°	943.9	727.7
72.5°	748.8	606.4
75°	595.9	506.3
77.5°	369.1	337.5
80°	152.9	142.4
82.5°	36.9	31.6
85°	0.0	0.0
87.5°	0.0	0.0
90°	0.0	0.0
92.5°	0.0	0.0
95°	0.0	0.0
97.5°	0.0	0.0
100°	0.0	0.0
102.5°	0.0	0.0
105°	0.0	0.0
107.5°	0.0	0.0
110°	0.0	0.0

REPORT NUMBER: P1066662

CATALOG NUMBER: NVN-SA5B-835-U-RBC

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	0.0	0.0
115°	0.0	0.0
117.5°	0.0	0.0
120°	0.0	0.0
122.5°	0.0	0.0
125°	0.0	0.0
127.5°	0.0	0.0
130°	0.0	0.0
132.5°	0.0	0.0
135°	0.0	0.0
137.5°	0.0	0.0
140°	0.0	0.0
142.5°	0.0	0.0
145°	0.0	0.0
147.5°	0.0	0.0
150°	0.0	0.0
152.5°	0.0	0.0
155°	0.0	0.0
157.5°	0.0	0.0
160°	0.0	0.0
162.5°	0.0	0.0
165°	0.0	0.0
167.5°	0.0	0.0
170°	0.0	0.0
172.5°	0.0	0.0
175°	0.0	0.0
177.5°	0.0	0.0
180°	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-10

Test Date: 10/11/2024

Luminaire Tested: GSS-SB1A-835-U-5WQ

Data in this report applies to families of products including GSS-SB1A-835-U-5WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-184-10
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 10/15/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: McGraw-Edison
 Catalog Number: **GSS-SB1A-835-U-5WQ**
 Description: GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 80 CRI 3500K CCT 26 LEDS

Spectral Parameters

CCT (K): 3411
 CIE u' : 0.2360
 CIE v' : 0.5189
 Duv: 0.0044
 CIE x: 0.4154
 CIE y: 0.4059
 CIE z: 0.1787
 Peak Wavelength (nm): 601
 Dominant Wavelength (nm): 579
 Purity: 46.51914
 R_f: 86.6
 R_g: 95.9

CRI (Ra): 83.5
 R1: 81.1
 R2: 88.9
 R3: 97.2
 R4: 83.8
 R5: 81.7
 R6: 86.9
 R7: 86.1
 R8: 62.2
 R9: 6.3
 R10: 75.4
 R11: 84.1
 R12: 69.7
 R13: 82.8
 R14: 98.5
 R15: 72.6



Test Conditions


Stabilization Time: 35M
 Operation Time: 1H 35M
 Sphere Temperature (°C): 25.2

REPORT NUMBER: SP1-2407-184-10


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-10

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3500K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-10

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.48

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.88


λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	311	NR	620	903	NR	750	26	NR	880	1	NR
365	0	NR	495	376	NR	625	851	NR	755	22	NR	885	1	NR
370	0	NR	500	438	NR	630	797	NR	760	19	NR	890	0	NR
375	0	NR	505	491	NR	635	735	NR	765	16	NR	895	0	NR
380	0	NR	510	533	NR	640	672	NR	770	14	NR	900	0	NR
385	0	NR	515	566	NR	645	607	NR	775	12	NR	905	0	NR
390	0	NR	520	592	NR	650	546	NR	780	10	NR	910	0	NR
395	1	NR	525	608	NR	655	487	NR	785	9	NR	915	0	NR
400	3	NR	530	625	NR	660	429	NR	790	7	NR	920	0	NR
405	6	NR	535	642	NR	665	378	NR	795	6	NR	925	0	NR
410	12	NR	540	657	NR	670	329	NR	800	5	NR	930	0	NR
415	22	NR	545	677	NR	675	286	NR	805	5	NR	935	0	NR
420	43	NR	550	701	NR	680	248	NR	810	4	NR	940	0	NR
425	80	NR	555	728	NR	685	213	NR	815	3	NR	945	0	NR
430	140	NR	560	757	NR	690	184	NR	820	3	NR	950	0	NR
435	243	NR	565	793	NR	695	156	NR	825	3	NR	955	0	NR
440	412	NR	570	831	NR	700	134	NR	830	2	NR	960	0	NR
445	610	NR	575	872	NR	705	114	NR	835	2	NR	965	0	NR
450	597	NR	580	911	NR	710	97	NR	840	2	NR	970	0	NR
455	412	NR	585	944	NR	715	83	NR	845	1	NR	975	0	NR
460	330	NR	590	974	NR	720	70	NR	850	1	NR	980	0	NR
465	274	NR	595	992	NR	725	60	NR	855	1	NR	985	0	NR
470	211	NR	600	999	NR	730	51	NR	860	1	NR	990	0	NR
475	200	NR	605	992	NR	735	43	NR	865	1	NR	995	0	NR
480	220	NR	610	975	NR	740	36	NR	870	1	NR	1000	0	NR
485	255	NR	615	944	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-184-10





TM-30-18

Summary

$R_f = 86.6$
 $R_g = 95.9$
 $CIE R_a = 83.5$
 $R_9 = 6.3$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 85	CES51 = 97	CES76 = 81
CES02 = 62	CES27 = 95	CES52 = 96	CES77 = 87
CES03 = 31	CES28 = 94	CES53 = 91	CES78 = 80
CES04 = 70	CES29 = 87	CES54 = 92	CES79 = 93
CES05 = 49	CES30 = 93	CES55 = 92	CES80 = 91
CES06 = 51	CES31 = 89	CES56 = 88	CES81 = 77
CES07 = 41	CES32 = 84	CES57 = 87	CES82 = 96
CES08 = 40	CES33 = 91	CES58 = 88	CES83 = 95
CES09 = 29	CES34 = 91	CES59 = 93	CES84 = 92
CES10 = 75	CES35 = 95	CES60 = 94	CES85 = 80
CES11 = 58	CES36 = 90	CES61 = 91	CES86 = 72
CES12 = 64	CES37 = 95	CES62 = 95	CES87 = 86
CES13 = 43	CES38 = 100	CES63 = 88	CES88 = 88
CES14 = 74	CES39 = 97	CES64 = 85	CES89 = 77
CES15 = 71	CES40 = 94	CES65 = 80	CES90 = 88
CES16 = 47	CES41 = 97	CES66 = 84	CES91 = 81
CES17 = 49	CES42 = 96	CES67 = 82	CES92 = 67
CES18 = 56	CES43 = 93	CES68 = 85	CES93 = 81
CES19 = 72	CES44 = 99	CES69 = 89	CES94 = 63
CES20 = 66	CES45 = 95	CES70 = 81	CES95 = 76
CES21 = 86	CES46 = 91	CES71 = 79	CES96 = 84
CES22 = 78	CES47 = 93	CES72 = 93	CES97 = 92
CES23 = 91	CES48 = 85	CES73 = 76	CES98 = 86
CES24 = 90	CES49 = 92	CES74 = 95	CES99 = 77
CES25 = 72	CES50 = 96	CES75 = 80	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)